

Are the Values of LLMs Structurally Aligned with Humans? A Causal Perspective

Yipeng Kang¹, Junqi Wang¹, Yexin Li¹, Mengmeng Wang¹,
Wenming Tu¹, Quansen Wang^{1,3}, Hengli Li^{1,3}, Tingjun Wu⁴,
Xue Feng¹, Fangwei Zhong^{2,1}, Zilong Zheng^{1,✉}

¹State Key Laboratory of General Artificial Intelligence, BIGAI
²Beijing Normal University, ³Peking University, ⁴Tsinghua University
{kangyipeng, zlzheng}@bigai.ai

Abstract

As large language models (LLMs) become increasingly integrated into critical applications, aligning their behavior with human values presents significant challenges. Current methods, such as Reinforcement Learning from Human Feedback (RLHF), typically focus on a limited set of coarse-grained values and are resource-intensive. Moreover, the correlations between these values remain implicit, leading to unclear explanations for value-steering outcomes. Our work argues that a latent causal value graph underlies the value dimensions of LLMs and that, despite alignment training, this structure remains significantly different from human value systems. We leverage these causal value graphs to guide two lightweight value-steering methods: role-based prompting and sparse autoencoder (SAE) steering, effectively mitigating unexpected side effects. Furthermore, SAE provides a more fine-grained approach to value steering. Experiments on Gemma-2B-IT and Llama3-8B-IT demonstrate the effectiveness and controllability of our methods.

1 Introduction

The rapid advancement and widespread deployment of large language models (LLMs) have revolutionized a range of fields, from natural language processing to decision-making systems (Huang et al., 2024b). These models, powered by vast amounts of data and sophisticated algorithms, have demonstrated remarkable abilities in various domains. However, as LLMs are increasingly deployed in critical applications, ensuring their alignment with human values and societal norms has become a pressing concern. Misalignment between LLM behaviors and ethical standards can lead to unintended, or even harmful consequences. As a result, value alignment, which aims to ensure that the actions and outputs of these models are consistent with human values has emerged as a pivotal




Figure 1: Steering multiple causally related value dimensions in LLMs. When we use prompts or sparse autoencoders to steer certain dimensions of a large model, other values will correspondingly change.

challenge to the research community.

Current approaches to value alignment typically focus on a few core values, such as the *3H*: *helpfulness*, *harmlessness*, and *honesty*, using algorithms like Reinforcement Learning from Human Feedback (RLHF) (Ouyang et al., 2022) and constitutional learning (Bai et al., 2022). While this paradigm has proven effective in guiding models toward certain desirable behaviors, human values encompass a much broader spectrum, often spanning hundreds of distinct dimensions with intricate and interconnected substructures (Schwartz and Boehnke, 2004). When LLMs are deployed, these value systems often remain implicit, with their underlying structures and causal relationships poorly understood. This lack of clarity leads to unpredictable effects on alternative dimensions when steering specific values. Another issue with these alignment processes is their resource-intensiveness, requiring considerable computational power, human feedback data, and time for fine-tuning. As a result, it is impractical to steer LLMs toward each of the numerous human value dimensions in real time. To effectively align with a broader range of




Figure 2: A general framework for role playing and SAE value steering. Within the prompt template, we can adjust the role settings (indicated in red) or directly manipulate the SAE features of specific tokens (indicated in yellow). To guide the LLMs to answer questions in a chain-of-thought (CoT) manner, we provided two in-context examples (indicated in green). Finally, we input a specific question regarding a value, and the LLM outputs both the thought process and the answer. The same steering direction on a value can be reflected on different questions.

values, it is crucial to develop a comprehensive understanding of the value structures, including the spectrum of values and their causal interconnections.

In this perspective, we offer the insight that a latent causal value graph underlies the value dimensions of LLMs. Despite alignment training efforts on LLMs, this structure remains markedly distinct from human value systems, as illustrated by theories like Schwartz’s and the semantic understanding of value lexicons. This fundamental difference underscores the need for a deeper exploration of these underlying structures to achieve more effective alignment with human values.

To validate this insight, we mine the causal graphs of values within LLMs by analyzing their responses to a questionnaire under various settings. These graphs reveal the structures of how different values influence one another and, consequently, the models’ decisions. We then leverage these graphs to systematically guide two lightweight real-time value-steering methods: role-based prompting and sparse autoencoder (SAE) steering. These meth-

ods effectively mitigate unexpected side effects by utilizing prior knowledge from the graphs.

The first mechanism involves configuring the agent’s role information, such as occupation, background, and personality, through designed prompting. The second mechanism utilizes SAE features extracted from the internal representations of the transformer layers. By manipulating a single dimension of the SAE features with a minimal number of tokens, we can effectively steer specific value dimensions of the LLM agent while predicting potential side effects on other dimensions using the causal graph. Notably, we find that SAE provides a more fine-grained approach to value steering compared to role-based prompts, as it influences fewer source nodes in the causal graph, thereby offering more targeted and precise control. Extensive experiments are conducted on Gemma-2B-IT (Team et al., 2024) and Llama3-8B-IT (Dubey et al., 2024), to thoroughly demonstrate the effectiveness of the mechanisms. Our code and data are publicly available¹.

¹<https://github.com/bigai-nlco/ValueCausalGraph>

2 Value Causal Graph

Human values are complex. Single-dimensional models fail to capture various decision styles. Multidimensional approaches face challenges like unclear correlations amongst dimensions and semantic loss from techniques like Gram-Schmidt. Understanding causal structures is key. In this section, we set up language to discuss 1) deriving causal graphs from questionnaires, 2) value steering via prompt / SAE feature, and 3) steering effects along causal paths. A general framework of value assessing and steering is shown in Figure 2.

2.1 Causal Graphs from Questionnaire

We focus on assessing LLMs’ orientations towards a set of values V by analyzing their responses to a questionnaire. These responses are mapped to orientation vectors $\mathbf{s} \in \mathbb{R}^{|V|}$. By collecting these vectors from different LLM settings of steering, we can use passive causal discovery algorithms, like the Peter-Clark algorithm (Spirtes et al., 2001), to construct a causal graph $\mathbb{G} = (V, E)$. This graph reveals the causal relationships among the values in V through directed paths E .

2.2 Steering Methods

Prompt template steering. When posing a question to an LLM, we use a **template** t that incorporates the question before it is submitted to the LLM. When t changes, the model’s output is subsequently changed. Unrestricted prompt templates allow for many semantically equivalent expressions. We thereby limit the modifications of prompt templates to two specific categories.

The first category is **role playing** r , where only the role settings change. This method is selected for two reasons: 1) Role-playing templates are consistent with standard psychological survey methods, which collect data from a wide range of human subjects. 2) The structured nature of role-playing allows for effective control and meaningful cross-template comparisons, while guaranteeing sufficient variations of occupation, personality, etc. Role playing helps establish a foundational set of questionnaire responses $\{\mathbf{s}_r\}$.

The second category includes **explicit value instruction prompts** x , which instructs the language model to enhance or diminish certain dimensions via explicit value definitions, generating $\{\mathbf{s}_{x \circ r}\}$ for a fixed x and various roles r .

SAE feature steering. In addition to prompt template steering, another method to influence the output of an LLM involves directly changing the key SAE features within the model layers. This is achieved by changing the activation state of the SAE features, which is compatible with prompt template steering. Precisely, for a given feature f and strength σ , steering the LLM by (f, σ) while applying the questionnaire with template t results in a scoring $\mathbf{s}_t^{(f, \sigma)}$ on V different from \mathbf{s}_t . In practice, features are usually layer-specific for training convenience. As mentioned above, it is possible to apply SAE steering to the model together with a role-playing prompt template r .

2.3 Steering Effect along Causal Relations

The value causal graph could help analyze the subsequent effects of value steering with partial results known. It clearly shows expected outcomes when a value node changes. We can also thus evaluate graph quality when data is available.

For a causal graph $\mathbb{G} = (V, E)$, let $V_{suc}^{\mathbb{G}}(v)$ and $V_{nsuc}^{\mathbb{G}}(v)$ be the successor and non-successor nodes of v . Let r_0 be a baseline role prompt, $R_{\neq}(v) = \{r \mid \mathbf{s}_r[v] \neq \mathbf{s}_{r_0}[v]\}$, $F_{\neq}(v) = \{f \mid \mathbf{s}_{r_0}^f[v] \neq \mathbf{s}_{r_0}[v]\}$. The variation of v' when steering v is:

$$c(v', v) = \begin{cases} \frac{1}{|R_{\neq}(v)|} \sum_{r \in R_{\neq}(v)} \mathbf{1}_{\mathbf{s}_r[v'] \neq \mathbf{s}_{r_0}[v']} & \text{(role)} \\ \frac{1}{|F_{\neq}(v)|} \sum_{f \in F_{\neq}(v)} \mathbf{1}_{\mathbf{s}_{r_0}^f[v'] \neq \mathbf{s}_{r_0}[v']} & \text{(SAE)} \end{cases}$$

The prediction accuracy of \mathbb{G} on expected subsequent effects of v is: $\frac{1}{|V_{suc}^{\mathbb{G}}(v)|} \sum_{v' \in V_{suc}^{\mathbb{G}}(v)} c(v', v)$. The occurrence frequency of unexpected subsequent effects is: $\frac{1}{|V_{nsuc}^{\mathbb{G}}(v)|} \sum_{v' \in V_{nsuc}^{\mathbb{G}}(v)} c(v', v)$. We can also measure these metrics for reference graphs created by humans, GPT-4o, etc., to assess whether the causal relationships of LLM values align with human semantic understanding.

3 Experiments

We conduct value evaluation experiments for Gemma-2B-IT and Llama3-8B-IT models on ValueBench (Ren et al., 2024), in order to demonstrate the effectiveness of causal graphs in guiding LLM value steering and to highlight the specific advantages of SAE steering. Our experiments were conducted using an Nvidia A800-SXM4-80GB GPU.

3.1 Settings

In the text-based questionnaire provided by ValueBench, each value is assessed using multiple




Figure 3: Our value causal graphs for **Gemma-2B-IT** (left) and **Llama3-8B-IT** (right), compared to the **reference graph**, which is annotated by GPT-4o guided by Schwartz’s Theory. We reduce the edges of the graphs while maintaining the partial order between any two nodes unchanged by transitive reduction algorithm.

questions. For each response generated by the LLM, we apply a ternary classification (yes / no / unsure) as described in Appendix A.1. This classification is then compared against ValueBench’s agreement metrics to assign a score to the LLM’s response for each question: positive (+1), negative (-1), or neutral (0). We determine the overall orientation of the LLM towards the value by averaging the scores across all relevant questions. To ensure a robust evaluation of the steering effects, we selected values from ValueBench that contained a sufficient number of questions (more than 20), resulting in a subset of 17 representative values.

We generate 125 virtual roles with diverse background settings, partitioning them into a training set of 100 roles and a test set of 25 roles. The training and test roles evaluate their values using different splits of each value’s QA pairs. The test roles use 30% of them, while the training roles use the remaining 70%. To minimize potential bias from any specific question, we randomly sample 40% of the training data for each role-SAE dyad.

Manipulating SAE typically involves first pre-training SAE model of an LLM, followed by interpreting noteworthy features. We employ SAE-lens (Bloom and Chanin, 2024) to obtain pretrained SAEs of the 12th layer of Gemma-2B-IT and the 25th layer of Llama3-8B-IT. To steer the values, we extract the 25 most significant SAE features from the token sequence "your values" within the system prompt and individually apply a 100-fold increase. We observe that features selected in this way are more closely related to the token of "value" and are thus more likely to affect concrete values.

3.2 Value Causal Graph of LLMs

For both LLMs, we utilize the value orientations from all 101 training roles (including an empty role) across 25 SAE steering features, totaling 2,525 data entries. The dataset is analyzed using the Peter-Clark (PC) algorithm with Fisher’s Z-test for conditional independence ($\alpha = 0.05$) to infer causal relationships among value dimensions, depicted as causal graphs in Figure 3.

To demonstrate their effectiveness, we generate several reference causal graphs: (1) using GPT-4o guided by Schwartz’s Theory of Basic Values, detailed in Appendix A.3; (2) allowing Gemma-2B-IT and Llama3-8B-IT to generate reference causal graphs for themselves; (3) leveraging the value hierarchical relationships in ValueBench. We hereby take the first method for analysis, which represents human common knowledge of values, and include the results of other reference graphs in Appendix B.

3.2.1 Predicting the Effects of Steering via Causal Graphs

When steering a target value, particularly when using role-setting prompts, the subsequent effects on other value dimensions are often unpredictable. Constructing value causal graph can assist in analyzing the successors of each value node to do the prediction. Each time a value node changes its orientation, we expect its subsequent nodes on the causal graph also to change orientations while the non-subsequent nodes stay unchanged.

As shown in Figure 4, which is measured using the metric in Section 2.3, for both Gemma-2B-IT and Llama-3B-IT, our causal graph provides an




Figure 4: The steering effects of role prompts and SAE on expected and unexpected value dimensions for Gemma-2B-IT (left) and Llama3-8B-IT (right). Our casual graph is discovered from training data while the reference causal graph is generated by GPT-4o guided by the Schwartz’s Theory of Basic Values, as described in Appendix A.3. Note that all tests are conducted on the test set, which uses completely different roles and value questions than those used to build the causal graph.

effective prediction of the subsequent effects of role-setting prompts and SAE steering, compared to the reference causal graphs. Details can be found in the following paragraphs.

Effective prediction from causal graphs. Value dimensions expected to change after steering by our graphs are more likely to do so in real cases than those indicated by reference graphs for both prompt and SAE steering across all LLMs. Specifically, for Gemma Prompt, the probability is 0.69 versus 0.51; for Gemma SAE, it is 0.57 versus 0.43; for Llama Prompt, it is 0.57 versus 0.45; and for Llama SAE, it is 0.74 versus 0.49. Conversely, unexpected value changes are less frequent in real cases, with probabilities of 0.56 compared to 0.60 for Gemma Prompt, 0.51 versus 0.53 for Gemma SAE, 0.47 versus 0.50 for Llama Prompt, and 0.46 versus 0.55 for Llama SAE.

Remark 1: Although LLMs have been largely trained to align with human values, their internal value structures still differ from human theories, such as Schwartz’s value theory, and the semantic understanding of value lexicons. Thus, using causal graphs for systematic value steering, rather than relying solely on specific methods for individual values, is significant.

Unexpected value changes. Our graph shows unexpected changes, although they are lower than

those in the reference graphs. This occurs because both prompt and SAE steering can affect other source value nodes in addition to the target value. We also observe that unexpected changes are fewer or comparable for SAE steering than for prompts (Gemma prompt: 0.56 > Gemma SAE: 0.51; Llama prompt: 0.47 > Llama SAE: 0.46), indicating that SAE steering has a more precise effect. In fact, we found the average number of steered values of role prompts is 14.6 for Gemma-2B-IT and 7.7 for Llama-3B-IT, while for SAEs, these numbers are only 4.3 and 4.2, respectively.

Remark2 : SAE’s advantage lies in its precise effect on fewer source nodes, while prompts tend to influence more nodes, leading to greater unexpected side effects.

Unchanged expected values. Although we are confident that the nodes expected by our graphs hold significant meaning—evidenced by the fact that the lowest frequency of change in the expected value of our graph (0.57) surpasses the highest frequency of change in the expected value of the reference graphs (0.51)—they are not fully realized. This limitation is likely due to counter-effects from other source nodes, which are influenced by steering, and the attenuation of the steering effect along causal paths. These factors make it challenging to detect changes in nodes that are several steps away from the target node.

Table 1: Value steering using SAE features for Gemma-2B-IT (above) and Llama3-8B-IT (below). Each value-SAE cell displays the proportions of stimulated roles in **blue**, suppressed roles in **yellow**, and maintained roles in blank, all estimated from the training data. The numbers in each cell represent the cosine similarity between the actual proportions observed in the test data and the training version. Additionally, for each value, we calculate the average noise ratio. The noise ratio for a value-SAE cell is determined by the lowest ratio between stimulation and suppression, thus a low noise ratio indicates that the SAE feature can steer the value conservatively in one direction.

SAE Feature \ Value	Value										Mean Similarity
	Aesthetic	Breadth of Interest	Positive coping	Religious	Resilience	Social	Social Cynicism	Theoretical	Uncertainty Avoidance	Understanding	
Gemma-2B-IT											
1025	0.96	0.99	0.73	0.98	0.96	0.99	0.98	1.00	0.81	0.99	0.94
1312	0.96	0.41	0.67	0.65	0.90	0.23	0.10	0.87	0.94	0.89	0.66
1341	0.93	0.91	0.82	0.99	0.83	0.94	0.99	0.97	0.91	0.66	0.90
1975	0.81	0.97	0.91	0.69	0.71	0.99	0.80	0.99	0.99	0.99	0.89
2965	0.94	0.87	0.52	0.99	0.96	0.99	1.00	1.00	1.00	0.99	0.92
4752	0.64	1.00	0.87	0.86	1.00	0.99	0.93	0.92	0.91	0.85	0.90
10096	0.73	0.97	0.81	0.63	0.53	0.97	0.74	0.88	0.81	0.83	0.79
10605	0.99	0.83	0.79	0.72	0.96	0.98	0.99	0.78	0.96	0.56	0.86
14049	0.60	0.99	0.74	0.89	0.65	0.99	0.84	0.71	1.00	0.96	0.84
14351	0.83	0.86	0.45	0.99	0.92	1.00	0.43	1.00	0.93	0.98	0.84
Noise Ratio:	0.11	0.06	0.07	0.12	0.10	0.07	0.02	0.05	0.13	0.06	
Llama3-8B-IT											
1897	0.72	0.92	0.99	0.95	0.98	0.47	1.00	0.91	0.98	0.99	0.89
7754	0.86	0.98	1.00	0.93	0.97	0.94	0.90	0.79	0.90	1.00	0.93
8546	0.88	0.99	0.98	1.00	0.96	0.88	0.96	0.84	0.57	1.00	0.91
9332	0.97	0.49	0.77	0.98	0.80	0.79	0.89	0.84	0.70	0.99	0.82
12477	1.00	1.00	0.99	1.00	1.00	0.96	1.00	1.00	0.96	1.00	0.99
47207	0.76	0.94	0.69	0.81	0.92	0.90	0.98	1.00	0.82	0.95	0.88
49202	0.82	0.97	0.98	0.98	0.79	0.96	0.90	0.98	0.82	1.00	0.92
54606	0.97	1.00	0.93	0.88	0.89	0.95	0.99	0.78	0.83	0.99	0.92
58305	1.00	0.96	0.99	0.89	0.96	0.87	0.97	0.96	0.66	1.00	0.92
62769	0.89	0.96	0.92	0.62	0.74	0.68	0.95	0.93	0.74	0.98	0.84
Noise Ratio:	0.13	0.07	0.12	0.13	0.04	0.12	0.10	0.10	0.19	0.04	

Remark 3 We still need role prompts as a more comprehensive approach to address situations where steering causalities are not functioning as expected.

3.3 Steering Values via SAE Features

For each dyad of SAE feature and value dimension, we observe that the steering effect could be stimulating, suppressing, or maintaining, depending on the context. Some dyads exhibit internally consistent directional patterns, while others show stochas-

tic variations. In Table 1, we estimate the effects for each dyad based on the proportions of stimulated, suppressed, and maintained roles within the dyad in the training data. We also show the extent to which these effects are replicated during tests across different role settings and value questions.²

For both LLM models, in most test cases, the values are steered in a manner consistent with the patterns estimated from the training data, as indicated by the mean similarities of the SAE features. The internal steering direction of each dyad is also relatively consistent, evidenced by the noise ratio. Each SAE feature exhibits distinct effects on different values, and for the majority of values, it is possible to identify SAE features that support steering in desired directions. However, a few values remain challenging to steer effectively.

To further demonstrate that SAE is effectively steering the LLM values, rather than randomly altering the output for specific questions, we examine multiple levels of consistency in the responses to value-related questions.

Consistency within a QA. One key indicator that the SAE steering method is genuinely influencing the LLMs is the alignment between the answers and the corresponding thought processes. We first separate the thought and answer within the response and feed them into the judgment template individually, as described in Appendix A.1, to see if they match. As shown in Table 2, we find that the answers remain largely consistent with the thought processes, both before and after steering.

	Gemma-2B-IT	Llama3-8B-IT
Before	0.18	0.15
After	0.20	0.15

Table 2: Probability of inconsistency of the thought and answer with in a QA before and after SAE steering.

Consistency within a value. Another crucial indicator of the efficacy of SAE in influencing a particular value is its capacity to consistently modify the responses to various questions associated with that value in a consistent direction. For each value-SAE pair, we identified the questions where the orientation was altered and discovered that, on av-

²Due to space constraints, only a subset of values and SAE features are shown here; the full table can be found in Table 4 and Table 5 of Appendix C.

erage, there is approximately one inverse direction for every five changes.




Table 3: Steering results of SAE and explicit value instructions. The blue pie indicates roles that were positively steered, the yellow pie indicates negatively steered roles, and the blank pie represents roles that remained unchanged.

Comparing SAE with explicit value instructions.

To further manifest the impact of SAE feature steering, we compare it with an ideally effective steering method for a single value, namely, explicitly informing the LLMs of the definition of the value and their intended inclinations. For each value, we apply its most effective positive and negative SAE features, along with the explicit value instruction, to the test roles.³ From Table 3, it is evident that both methods have their own advantages. For

³Implementation details are shown in Appendix A.2

Gemma-2B-IT, SAE is more effective in positive steering but less effective in negative steering. Conversely, for Llama3-8-IT, SAE performs less effectively in positive steering but better in negative steering. These results suggest that LLMs do not always follow explicit instructions as effectively as expected. This discrepancy may arise from the LLM’s imprecise understanding of certain values during its pre-training. Taking into account the advantages of side-effect control, SAE generally has its advantage over explicit value instructions.

4 Related Work

Graph mining in social science. Graphs has been extensively applied in social science to investigate complex interdependencies among variables, including research on personality psychology (Cramer et al., 2012; Costantini et al., 2020; Marcus et al., 2018), political beliefs (Boutyline and Vaisey, 2017; Brandt et al., 2019), attitudes (Dalege et al., 2016; Kong et al., 2024; Huang et al., 2024a; Feng et al., 2019), self-concept (Elder et al., 2023), mental disorders (Boschloo et al., 2015) and coordination algorithms (Kang et al., 2022). In particular, Schwartz’s theory posits that human values form a quasi-circumplex structure, where adjacent values share highly consistent underlying motivations, while opposing values tend to conflict with one another (Schwartz and Boehnke, 2004). This structure was developed using data derived from extensive questionnaire results (Schwartz et al., 2012; Schwartz, 1992, 2012). However, these studies provide limited insight into causal relationships (Rohrer, 2018; Borsboom et al., 2021; Ryan et al., 2022; Imai, 2022). In contrast, our work utilizes directed graphs to represent causal relationships among values. While some studies (Russo et al., 2022) leverage Schwartz’s value structure to predict human behaviors, none have explored using it to steer human values. In comparison, our work leverages causal graphs to steer the values of LLMs.

Value systems within LLMs. Previous research has highlighted the significance of value alignment in facilitating effective agent interactions, especially in the emerging era of AGI (Yuan et al., 2022; Kang et al., 2020; Mao et al., 2024). More recent studies have focused directly on evaluating the values of LLMs. ValueBench provides the first comprehensive psychometric benchmark for evaluating value orientations and value understanding in LLMs (Ren et al., 2024). ValueCompass (Shen

et al., 2024) introduces a framework of fundamental values, grounded in psychological theory and a systematic review, to identify and evaluate human-AI alignment. UniVaR uses the responses of different LLMs to the same set of value-eliciting questions to explore how LLMs prioritize different values in various languages and cultures (Cahyawijaya et al., 2024). ValueLex reveals both the similarities and differences between the value systems of LLMs and that of humans (Biedma et al., 2024). FULCRA (Yao et al., 2023) proposes a basic value alignment paradigm and introduces a value space spanned by basic value dimensions.

Sparse autoencoder (SAE). Sparse Autoencoders (SAEs) are an emerging method for feature learning, effective in interpreting LLMs’ internal representations. Studies like Elhage et al. (2022) and Cunningham et al. (2023) explore how neural networks encode features, demonstrating the extraction of human-interpretable features from models like Pythia-70M and Pythia-140M. Techniques such as k-sparse autoencoders (Gao et al., 2024) enhance sparsity control and tuning. Sparse feature circuits (Marks et al., 2024) offer insights into language model behaviors through human-interpretable subnetworks. In contrast, our research investigates the causal relationships specifically among value dimensions. Modifying SAE values within a model is often employed as a method to steer a model’s output (Turner et al., 2024; Li et al., 2023; Bricken et al., 2023; Cunningham et al., 2023), which often focuses on steering concepts or text patterns. Steering values, however, presents a more challenging problem, one that remains underexplored in the existing literature.

5 Conclusion

In this paper, we explored the latent causal value structures of LLMs and found that, despite undergoing alignment training, their internal value mechanisms remain significantly different from those of humans. Building on this insight, we proposed a framework that systematically leverages causal value graphs to guide two lightweight value-steering methods: role-based prompting and sparse autoencoder (SAE) steering, effectively mitigating unexpected side effects. Furthermore, we identified that SAE offers a fine-grained approach to value modulation. These findings provide a novel perspective and practical methods for more precise and reliable value alignment in LLMs.

Limitations

One limitation arises from the construction methodology of the ValueBench dataset, which offers a somewhat uniform approach to value assessment and includes relatively few evaluation questions for each value. Consequently, we have been unable to extend causal inferences between values across a wider range of dimensions, which may lead to the oversight of some hidden causal relationships. Furthermore, future research could explore expanding experiments to incorporate larger versions of LLMs, investigating how these models can be effectively aligned with the diverse and intricate structure of human values.

Ethical Statement

This study was conducted in compliance with all relevant ethical guidelines and did not involve any procedures requiring ethical approval.

References

- Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, and Andy et al. Jones. 2022. Constitutional ai: Harmlessness from ai feedback. *arXiv preprint arXiv:2212.08073*.
- Pablo Biedma, Xiaoyuan Yi, Linus Huang, Maosong Sun, and Xing Xie. 2024. [Beyond human norms: Unveiling unique values of large language models through interdisciplinary approaches](#). *ArXiv*, abs/2404.12744.
- Joseph Bloom and David Chanin. 2024. Saelens. <https://github.com/jbloomAus/SAELens>.
- Denny Borsboom, Marie K Deserno, Mijke Rhemtulla, Sacha Epskamp, Eiko I Fried, Richard J McNally, Donald J Robinaugh, Marco Perugini, Jonas Dalege, Giulio Costantini, et al. 2021. Network analysis of multivariate data in psychological science. *Nature Reviews Methods Primers*, 1(1):58.
- Lynn Boschloo, Claudia D van Borkulo, Mijke Rhemtulla, Katherine M Keyes, Denny Borsboom, and Robert A Schoevers. 2015. The network structure of symptoms of the diagnostic and statistical manual of mental disorders. *PLoS one*, 10(9):e0137621.
- Andrei Boutyline and Stephen Vaisey. 2017. Belief network analysis: A relational approach to understanding the structure of attitudes. *American journal of sociology*, 122(5):1371–1447.
- Mark J Brandt, Chris G Sibley, and Danny Osborne. 2019. What is central to political belief system networks? *Personality and Social Psychology Bulletin*, 45(9):1352–1364.
- Trenton Bricken, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermy, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, Robert Lasenby, Yifan Wu, Shauna Kravec, Nicholas Schiefer, Tim Maxwell, Nicholas Joseph, Zac Hatfield-Dodds, Alex Tamkin, Karina Nguyen, Brayden McLean, Josiah E Burke, Tristan Hume, Shan Carter, Tom Henighan, and Christopher Olah. 2023. Towards monosemanticity: Decomposing language models with dictionary learning. *Transformer Circuits Thread*. <https://transformer-circuits.pub/2023/monosemantic-features/index.html>.
- Samuel Cahyawijaya, Delong Chen, Yejin Bang, Leila Khalatbari, Bryan Wilie, Ziwei Ji, Etsuko Ishii, and Pascale Fung. 2024. High-dimension human value representation in large language models. *arXiv preprint arXiv:2404.07900*.
- Giulio Costantini, Daniele Sarauelli, and Marco Perugini. 2020. Uncovering the motivational core of traits: The case of conscientiousness. *European Journal of Personality*, 34(6):1073–1094.
- Angélique OJ Cramer, Sophie Van der Sluis, Arjen Noordhof, Marieke Wichers, Nicole Geschwind, Steven H Aggen, Kenneth S Kendler, and Denny Borsboom. 2012. Dimensions of normal personality as networks in search of equilibrium: You can't like parties if you don't like people. *European Journal of Personality*, 26(4):414–431.
- Hoagy Cunningham, Aidan Ewart, Logan Riggs, Robert Huben, and Lee Sharkey. 2023. [Sparse autoencoders find highly interpretable features in language models](#). (arXiv:2309.08600). ArXiv:2309.08600 [cs].
- Jonas Dalege, Denny Borsboom, Frenk Van Harreveld, Helma Van den Berg, Mark Conner, and Han LJ Van der Maas. 2016. Toward a formalized account of attitudes: The causal attitude network (can) model. *Psychological review*, 123(1):2.
- Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.
- Jacob Elder, Bernice Cheung, Tyler Davis, and Brent Hughes. 2023. Mapping the self: A network approach for understanding psychological and neural representations of self-concept structure. *Journal of personality and social psychology*, 124(2):237.
- Nelson Elhage, Tristan Hume, Catherine Olsson, Nicholas Schiefer, Tom Henighan, Shauna Kravec, Zac Hatfield-Dodds, Robert Lasenby, Dawn Drain, Carol Chen, Roger Grosse, Sam McCandlish, Jared Kaplan, Dario Amodei, Martin Wattenberg, and Christopher Olah. 2022. Toy models of superposition. *Transformer Circuits Thread*. https://transformer-circuits.pub/2022/toy_model/index.html.

- Xue Feng, Long Wang, and Simon A Levin. 2019. Dynamic analysis and decision-making in disease-behavior systems with perceptions. In *2019 Chinese Control And Decision Conference (CCDC)*, pages 665–670. IEEE.
- Leo Gao, Tom Dupré la Tour, Henk Tillman, Gabriel Goh, Rajan Troll, Alec Radford, Ilya Sutskever, Jan Leike, and Jeffrey Wu. 2024. Scaling and evaluating sparse autoencoders. *arXiv preprint arXiv:2406.04093v1*.
- Yizhe Huang, Anji Liu, Fanqi Kong, Yaodong Yang, Song-Chun Zhu, and Xue Feng. 2024a. Efficient adaptation in mixed-motive environments via hierarchical opponent modeling and planning. *arXiv preprint arXiv:2406.08002*.
- Yizhe Huang, Xingbo Wang, Hao Liu, Fanqi Kong, Aoyang Qin, Min Tang, Song-Chun Zhu, Mingjie Bi, Siyuan Qi, et al. 2024b. Adasociety: An adaptive environment with social structures for multi-agent decision-making. *arXiv preprint arXiv:2411.03865*.
- Kosuke Imai. 2022. Causal diagram and social science research. In *Probabilistic and Causal Inference: The Works of Judea Pearl*, pages 647–654.
- Yipeng Kang, Tonghan Wang, and Gerard de Melo. 2020. Incorporating pragmatic reasoning communication into emergent language. *Advances in neural information processing systems*, 33:10348–10359.
- Yipeng Kang, Tonghan Wang, Qianlan Yang, Xiaoran Wu, and Chongjie Zhang. 2022. Non-linear coordination graphs. *Advances in Neural Information Processing Systems*, 35:25655–25666.
- Fanqi Kong, Yizhe Huang, Song-Chun Zhu, Siyuan Qi, and Xue Feng. 2024. Learning to balance altruism and self-interest based on empathy in mixed-motive games. *arXiv preprint arXiv:2410.07863*.
- Kenneth Li, Oam Patel, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg. 2023. [Inference-time intervention: Eliciting truthful answers from a language model](#). In *Thirty-seventh Conference on Neural Information Processing Systems*.
- Yihuan Mao, Yipeng Kang, Peilun Li, Ning Zhang, Wei Xu, and Chongjie Zhang. 2024. Ibgp: Imperfect byzantine generals problem for zero-shot robustness in communicative multi-agent systems. *arXiv preprint arXiv:2410.16237*.
- David K Marcus, Jonathan Preszler, and Virgil Zeigler-Hill. 2018. A network of dark personality traits: What lies at the heart of darkness? *Journal of Research in Personality*, 73:56–62.
- Samuel Marks, Can Rager, J. Eric Michaud, Yonatan Beilinkov, David Bau, and Aaron Mueller. 2024. Sparse feature circuits: Discovering and editing interpretable causal graphs in language models. *arXiv preprint arXiv:2403.19647v2*.
- L. Ouyang, J. Wu, X. Jiang, D. Almeida, C. Wainwright, P. Mishkin, C. Zhang, S. Agarwal, K. Slama, and et al. A. Ray. 2022. Training language models to follow instructions with human feedback. In *Advances in Neural Information Processing Systems*.
- Yuanyi Ren, Haoran Ye, Hanjun Fang, Xin Zhang, and Guojie Song. 2024. [Valuebench: Towards comprehensively evaluating value orientations and understanding of large language models](#). *Preprint, arXiv:2406.04214*.
- Julia M Rohrer. 2018. Thinking clearly about correlations and causation: Graphical causal models for observational data. *Advances in methods and practices in psychological science*, 1(1):27–42.
- Claudia Russo, Francesca Danioni, Ioanaand Zagrean, and Daniela Barni. 2022. Changing personal values through value-manipulation tasks: A systematic literature review based on schwartz’s theory of basic human values. *European Journal of Investigation in Health, Psychology and Education*.
- Oisín Ryan, Laura F Bringmann, and Noémi K Schuurman. 2022. The challenge of generating causal hypotheses using network models. *Structural Equation Modeling: A Multidisciplinary Journal*, 29(6):953–970.
- Shalom H Schwartz. 1992. Universals in the content and structure of values: Theoretical advances and empirical tests in 20 countries. *Advances in experimental social psychology/Academic Press*.
- Shalom H Schwartz. 2012. An overview of the schwartz theory of basic values. *Online readings in Psychology and Culture*, 2(1):11.
- Shalom H Schwartz and Klaus Boehnke. 2004. Evaluating the structure of human values with confirmatory factor analysis. *Journal of research in personality*, 38(3):230–255.
- Shalom H Schwartz, Jan Cieciuch, Michele Vecchione, Eldad Davidov, Ronald Fischer, Constanze Beierlein, Alice Ramos, Markku Verkasalo, Jan-Erik Lönnqvist, Kursad Demirutku, et al. 2012. Refining the theory of basic individual values. *Journal of personality and social psychology*, 103(4):663.
- Hua Shen, Tiffany Knearem, Reshmi Ghosh, Yu-Ju Yang, Tanushree Mitra, and Yun Huang. 2024. Valuecompass: A framework of fundamental values for human-ai alignment. *arXiv preprint arXiv:2049.09586v1*.
- Peter Spirtes, Clark Glymour, and Richard Scheines. 2001. *Causation, prediction, and search*. MIT press.
- Gemma Team, Thomas Mesnard, Cassidy Hardin, Robert Dadashi, Surya Bhupatiraju, Shreya Pathak, Laurent Sifre, Morgane Rivière, Mihir Sanjay Kale, Juliette Love, et al. 2024. Gemma: Open models based on gemini research and technology. *arXiv preprint arXiv:2403.08295*.

Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Juan J. Vazquez, Ulisse Mini, and Monte MacDiarmid. 2024. [Activation addition: Steering language models without optimization](#). *Preprint*, arXiv:2308.10248.

Jing Yao, Xiaoyuan Yi, Xiting Wang, Yifan Gong, and Xing Xie. 2023. [Value fulcra: Mapping large language models to the multidimensional spectrum of basic human values](#). *arXiv preprint arXiv:2311.10766v1*.

Luyao Yuan, Xiaofeng Gao, Zilong Zheng, Mark Edmonds, Ying Nian Wu, Federico Rossano, Hongjing Lu, Yixin Zhu, and Song-Chun Zhu. 2022. [In situ bidirectional human-robot value alignment](#). *Science robotics*, 7(68):eabm4183.

A Details about the Prompts

A.1 Answer Judgment

To judge the responses generated by LLMs for each question, we initially attempted to separate the output text into "Thought" and "Answer" sections. We then convert the characters in the answer string to lowercase. If the answer begins with "yes" or "sure," we classify it as "yes"; if it starts with "no," we classify it as "no". If the answer begins with phrases like "unsure," "i cannot," or "i am unable," we categorize it as "unsure". For answers that do not fit any of these categories, we employ GPT-4o to assess the response using the following prompt. See Template 1 for details.

One can also use the template to assess the inclination of a piece of thought by inputting the thought text in place of "Answer".

A.2 Explicit Value Instructions

Explicit value instruction prompts literally instruct the LLMs to stimulate or suppress specific value dimensions. This is accomplished by incorporating both the direction and the definition of the target value, as provided by ValueBench. The instruction template is written in the Role Settings part in Figure 2 and structured as follows. See Template 2, 3, 4 for details.

A.3 Reference Graph Generation

We generate the reference causal graph using GPT-4o, guided by the Schwartz's Theory of Basic Values, using the following prompt.

B Effect of Other Reference Causal Graphs

We also explored other reasonable approaches to constructing the reference causal graphs. One




Figure 5: Causal graph directly generated by Gemma-2B-IT, Llama3-8B-IT, ValueBench upper-dimensions and human.

straightforward method involves using Gemma-2B-IT and Llama3-8B-IT to generate their own reference graphs using the prompt in Appendix A.3. As shown in Figure 6, the testing results are similar to those in Section 3.2. Both language models do not demonstrate a better understanding of the internal value causalities of themselves compared to the causal graph we discovered. Additionally, we attempted to utilize the upper-dimension relationships provided by ValueBench, considering value dimensions under common upper-dimensions as having causal relationships. However, this structure is very sparse, resulting in the reference graph's performance lacking statistical reliability. As shown in Figure 7, our graph generally performs better, except in certain cases where the reference graph's performance in predicting prompt effects is very unstable. We show these additional reference causal graphs in Figure 5. We also conducted an online human survey to construct a real-world causal graph of human values. The survey comprised 136 pairwise comparison questions derived from a list of 17 values. For each pair (Va, Vb), participants selected among three options: (1) Va directly causes Vb, (2) Vb directly causes Va, or (3) no direct causal relationship. All value terms were accompanied by contextual definitions. We collected responses from 47 valid participants. Similar results can be seen in Figure 8.

C Results on more Value Dimensions and SAE Features

In Table 4 and Table 5, we present the results of SAE steering across more Value Dimensions and SAE Features. Similar result can be found as in the Table 1.

Template 1: Answer Judgment

A judgment is the answer to a question. Summarize the judgment, and tell me whether it means yes, no or unsure. The output should be limited to one of 'yes'/'no'/'unsure' in lowercase and without any other tokens. **Example:**

- Judgment: "for sure"
- Output: yes
- Judgment: "the answer is no"
- Output: no
- Judgment: "i cannot provide a response based on personal opinions"
- Output: unsure

Now it is your turn.

Judgment: {Answer}

Output:

Template 2: Explicit Value Instruction

FYI, here is your trait. {bio}.

You are {disinclined/inclined} to the value of "{value_name}",

which means "{value_def}".

Template 3: Positive Explicit Value Instruction Example

FYI, here is your trait. Gender: male; Job: Engineer, maintenance (IT), MBTI: ENFJ.

You are inclined to the value of "Understanding",

which means "The ability to understand why people behave in a particular way and to forgive them when they do something wrong".

Template 4: Negative Explicit Value Instruction Example

FYI, here is your trait. "Gender: female; Job: Clinical molecular geneticist, MBTI: INFP".

You are disinclined to the value of "Aesthetic",

which means "Harmony and beauty".

Template 5: Reference Graph Generation

Construct a causal graph depicting the relationships among **human values** in the list provided below.

["Positive coping", "Empathy", "Resilience", "Social Complexity", "Achievement", "Uncertainty Avoidance", "Aesthetic", "Anxiety Disorder", "Breadth of Interest", "Economic", "Organization", "Political", "Religious", "Social", "Social Cynicism", "Theoretical", "Understanding"]

Requirements

- **Identify Causal Links:** Determine which values influence others based on theoretical principles like Schwartz's Theory of Basic Human Values and common senses.
- **Justify Relationships:** Ensure that each causal link is conceptually sound, providing a brief explanation if necessary to clarify the rationale.
- **Comprehensive Coverage:** Aim to include as many relevant causal relationships as possible to create a robust and informative causal graph.
- **Causal Relationships Format:** Represent the causal relationships (*edges*) using the following format:

```
edges = [  
    [ 'Cause_Value1 ', 'Effect_Value1 ' ], # Explaination 1  
    [ 'Cause_Value2 ', 'Effect_Value2 ' ], # Explaination 2  
    # Continue accordingly...  
]
```

- Example:

```
edges = [  
    [ 'Understanding ', 'Empathy' ],  
    # Greater understanding leads to increased empathy.  
    [ 'Resilience ', 'Positive_coping' ],  
    # Resilience enhances positive coping mechanisms.  
    [ 'Anxiety_Disorder ', 'Uncertainty_Avoidance' ],  
    # Anxiety may increase the need to avoid uncertainty.  
    [ 'Social_Cynicism ', 'Social_Complexity' ],  
    # Cynicism might arise from perceiving social  
    # structures as complex and untrustworthy.  
]
```





Figure 6: Comparing our casual graph and the causal graph generated by Gemma-2B-IT and Llama3-8B-IT.





Figure 7: Comparing our casual graph and the causal graph generated according to ValueBench upper-dimension information.





Figure 8: Comparing our casual graph and the causal graph generated from real-world human experiments.

Table 4: Value steering using SAE features for the Gemma-2B-IT model.

SAE Feature	Achievement	Aesthetic	Anxiety Disorder	Breadth of Interest	Economic	Empathy	Organization	Political	Positive coping	Religious	Resilience	Social	Social Complexity	Social Cynicism	Theoretical	Uncertainty Avoidance	Understanding	Mean Similarity
428	0.91	0.96	0.89	0.93	1.00	0.61	0.57	0.65	0.97	0.92	0.97	0.91	0.89	0.75	0.99	0.89	0.98	0.87
1025	0.97	0.96	0.98	0.99	1.00	1.00	0.85	0.97	0.73	0.98	0.96	0.99	0.91	0.98	1.00	0.81	0.99	0.94
1312	0.96	0.96	0.99	0.41	0.99	0.80	0.95	0.91	0.67	0.65	0.90	0.23	0.45	0.10	0.87	0.94	0.89	0.75
1341	0.98	0.93	1.00	0.91	0.83	0.92	0.86	0.74	0.82	0.99	0.83	0.94	0.99	0.99	0.97	0.91	0.66	0.90
1975	0.86	0.81	0.87	0.97	0.90	0.69	0.69	0.78	0.91	0.69	0.71	0.99	0.72	0.80	0.99	0.99	0.99	0.85
2221	0.91	0.95	0.94	1.00	0.98	0.53	0.72	0.91	0.87	0.93	0.72	1.00	0.87	0.59	0.99	0.96	0.63	0.85
2965	1.00	0.94	0.89	0.87	1.00	0.96	0.96	0.99	0.52	0.99	0.96	0.99	0.37	1.00	1.00	1.00	0.99	0.91
3183	0.95	0.66	0.97	0.82	0.61	0.97	0.78	0.73	0.87	0.16	0.55	0.88	0.57	0.83	0.99	0.94	0.84	0.77
3402	0.99	0.95	0.92	0.69	0.92	0.99	0.94	0.96	0.75	0.97	0.91	0.99	0.82	0.44	1.00	0.95	0.82	0.88
4752	0.97	0.64	0.38	1.00	0.88	0.69	0.73	0.76	0.87	0.86	1.00	0.99	0.99	0.93	0.92	0.91	0.85	0.84
6188	0.99	0.93	0.88	0.93	0.90	0.87	0.85	0.90	0.84	0.91	0.94	0.99	0.96	0.56	0.99	0.81	0.97	0.89
6216	0.98	0.80	0.84	0.49	0.95	0.97	0.92	0.94	0.80	0.99	0.83	0.99	0.91	0.35	1.00	0.90	0.99	0.86
6619	0.89	0.82	0.56	0.92	0.99	0.76	0.81	0.58	0.99	0.89	0.60	1.00	0.80	0.58	0.17	0.76	0.93	0.77
6884	0.96	0.63	0.92	1.00	0.79	0.71	0.68	0.71	0.93	0.96	0.64	0.98	0.85	0.57	0.96	0.92	0.78	0.82
7502	0.96	0.88	0.91	0.89	0.96	0.82	0.93	0.95	0.92	0.99	0.93	1.00	0.69	0.44	1.00	0.97	0.98	0.90
8387	0.83	1.00	0.66	0.98	0.82	0.91	0.76	0.72	0.99	0.90	0.89	0.46	0.63	0.94	0.66	1.00	0.97	0.83
10096	0.64	0.73	0.92	0.97	0.84	1.00	0.86	0.53	0.81	0.63	0.53	0.97	0.93	0.74	0.88	0.81	0.83	0.80
10454	0.98	0.59	0.91	0.88	0.99	0.84	0.90	0.86	0.91	0.98	0.80	1.00	0.80	0.46	1.00	0.97	0.96	0.87
10605	0.87	0.99	0.91	0.83	0.72	0.52	0.68	0.84	0.79	0.72	0.96	0.98	0.73	0.99	0.78	0.96	0.56	0.81
11712	0.94	0.98	0.86	0.96	0.82	0.91	0.89	0.86	0.93	0.95	0.87	1.00	0.88	0.67	0.88	0.78	0.78	0.88
12703	0.93	0.96	0.93	0.52	0.98	0.76	0.90	0.91	0.78	0.99	0.97	0.98	0.95	0.42	1.00	0.77	0.97	0.87
14049	0.98	0.60	0.85	0.99	0.87	0.53	0.96	0.65	0.74	0.89	0.65	0.99	0.69	0.84	0.71	1.00	0.96	0.82
14185	0.99	0.96	0.96	0.98	0.63	0.80	0.89	0.79	0.79	0.98	0.97	1.00	0.88	0.92	0.95	0.75	0.63	0.88
14351	0.99	0.83	0.92	0.86	0.93	0.78	0.92	0.97	0.45	0.99	0.92	1.00	0.94	0.43	1.00	0.93	0.98	0.87
Noise Ratio:	0.18	0.12	0.22	0.04	0.14	0.16	0.15	0.14	0.08	0.11	0.10	0.06	0.14	0.02	0.05	0.12	0.06	

Table 5: Value steering using SAE features for the Llama3-8B-IT model.

SAE Feature	Achievement	Aesthetic	Anxiety Disorder	Breadth of Interest	Economic	Empathy	Organization	Political	Positive coping	Religious	Resilience	Social	Social Complexity	Social Cynicism	Theoretical	Uncertainty Avoidance	Understanding	Mean Similarity
1897	0.99	0.72	0.80	0.92	0.99	0.99	0.99	0.98	0.99	0.95	0.98	0.47	0.95	1.00	0.91	0.98	0.99	0.92
2246	0.93	0.70	0.97	0.96	0.95	0.44	0.98	0.93	0.92	0.82	0.84	0.68	0.94	0.97	0.95	0.72	1.00	0.86
2509	0.98	0.71	0.99	0.95	1.00	0.74	0.92	0.64	0.98	0.95	0.79	0.99	0.84	0.97	0.99	0.77	0.86	0.89
4305	0.90	0.66	0.96	0.93	0.96	0.79	0.93	0.98	0.88	0.77	0.64	1.00	0.80	0.98	0.52	0.52	0.21	0.79
7754	0.99	0.86	1.00	0.98	0.73	1.00	1.00	0.51	1.00	0.93	0.97	0.94	1.00	0.90	0.79	0.90	1.00	0.91
8035	0.99	0.97	1.00	0.98	1.00	0.98	1.00	1.00	1.00	1.00	1.00	0.98	0.98	1.00	0.92	0.96	1.00	0.98
8546	0.96	0.88	0.94	0.99	0.94	0.93	0.96	0.94	0.98	1.00	0.96	0.88	0.89	0.96	0.84	0.57	1.00	0.92
9332	0.89	0.97	0.83	0.49	0.96	0.97	0.88	0.93	0.77	0.98	0.80	0.79	0.75	0.89	0.84	0.70	0.99	0.85
12477	1.00	1.00	1.00	1.00	0.95	0.99	1.00	0.99	0.99	1.00	1.00	0.96	1.00	1.00	1.00	0.96	1.00	0.99
13033	0.48	0.90	1.00	0.50	0.97	0.92	0.99	0.82	0.99	1.00	1.00	0.97	0.99	0.69	0.91	0.98	0.98	0.89
20141	0.92	0.68	0.99	0.89	0.94	0.97	0.95	0.95	0.96	0.92	0.96	0.83	0.89	0.84	0.93	0.79	0.68	0.89
21347	1.00	0.99	1.00	0.99	0.98	1.00	1.00	1.00	0.99	0.96	1.00	0.92	1.00	1.00	0.89	0.97	1.00	0.98
30919	0.95	0.77	0.96	0.95	0.96	0.87	0.90	0.92	1.00	0.97	0.80	0.93	0.98	0.94	0.81	0.96	0.85	0.91
34598	0.99	0.94	0.99	0.96	0.99	0.98	1.00	0.98	0.98	0.98	0.99	0.97	0.99	0.96	0.95	0.91	1.00	0.98
41929	0.99	1.00	0.96	1.00	0.99	0.85	0.98	0.94	0.99	0.92	0.90	0.90	1.00	0.95	0.85	0.86	1.00	0.95
47207	0.93	0.76	1.00	0.94	0.76	0.95	0.97	0.94	0.69	0.81	0.92	0.90	1.00	0.98	1.00	0.82	0.95	0.90
48321	0.96	0.53	0.96	0.95	0.91	0.92	0.96	0.95	0.73	1.00	0.70	0.95	0.99	0.83	0.77	0.93	0.82	0.87
49202	0.99	0.82	0.94	0.97	0.99	0.82	0.99	0.94	0.98	0.98	0.79	0.96	0.98	0.90	0.98	0.82	1.00	0.93
51010	0.98	0.92	1.00	0.99	0.93	0.79	0.96	0.95	0.96	0.96	0.92	0.98	0.92	0.98	0.87	0.89	0.97	0.93
54606	0.99	0.97	1.00	1.00	0.97	1.00	0.99	0.91	0.93	0.88	0.89	0.95	0.97	0.99	0.78	0.83	0.99	0.94
58305	1.00	1.00	0.93	0.96	0.97	0.95	0.99	0.89	0.99	0.89	0.96	0.87	0.91	0.97	0.96	0.66	1.00	0.93
60312	0.96	0.81	0.97	0.90	0.74	0.64	0.80	0.82	0.68	0.62	0.44	0.94	1.00	0.98	0.72	0.83	0.63	0.79
62769	0.95	0.89	0.86	0.96	0.84	0.91	0.86	0.69	0.92	0.62	0.62	0.74	0.98	0.95	0.95	0.74	0.98	0.85
63905	0.98	0.76	0.99	0.94	0.85	0.82	0.92	0.90	0.92	0.73	0.46	0.92	0.95	0.90	0.09	0.90	0.99	0.82
Noise Ratio:	0.12	0.15	0.16	0.09	0.14	0.06	0.08	0.17	0.13	0.14	0.04	0.15	0.10	0.12	0.10	0.21	0.04	