ICCU: In-Context Continual Unlearning via Pattern-Induced Refusal Rules

Ruihao Pan and Suhang Wang
The Pennsylvania State University
{rvp5555, szw494}@psu.edu

Abstract

Machine unlearning aims to remove the influence of specific data from trained language models. In real-world deployments, unlearning requests often arrive sequentially, which challenges existing fine-tuning-based methods: fine-tuning each request is costly, accumulates utility loss, and may cause cross-request interference. To address these issues, we propose **ICCU** (**I**n-**C**ontext **C**ontinual **U**nlearning), an in-context continual unlearning framework that induces readable refusal rules from unlearning datasets and applies them at inference time either as a filter or via the system prompt, without modifying model parameters. Because rules are accumulated as an order-independent union, ICCU is compositional and free of cross-request interference, and the original forget-set data can be discarded after rule induction. Extensive experiments show that ICCU effectively suppresses target knowledge while preserving utility, scales across long sequences of requests, and remains robust to paraphrased, cross-lingual, and adversarially framed queries. Our code is available at https://github.com/rhpan/ICCU.

1 Introduction

Large language models (LLMs) have demonstrated remarkable capabilities on various tasks (Grattafiori et al., 2024; Yang et al., 2025). However, they are trained on web-scale corpora that inevitably contain sensitive, harmful, or copyrighted information, which LLMs could memorize and reproduce (Carlini et al., 2021; Karamolegkou et al., 2023; Li et al., 2024). Such content often needs to be removed from the trained LLMs to comply with privacy regulations such as the GDPR's "right to be forgotten" (Mantelero, 2013), to address copyright disputes (Henderson et al., 2023), or to mitigate the spread of hazardous knowledge (Li et al., 2024). As retraining from scratch is prohibitively expensive, *machine unlearning*, which aims to effectively eliminate the influence of specific data from trained models, has attracted increasing attention (Cao and Yang, 2015; Nguyen et al., 2025; Yao et al., 2024).

Existing unlearning approaches largely rely on fine-tuning or parameter updates (Jang et al., 2023; Maini et al., 2024; Li et al., 2024; Zhang et al., 2024). While effective for a single request, these methods are costly and difficult to apply repeatedly to large models (Nguyen et al., 2025; Qiu et al., 2025). In practice, deletion requests may keep emerging over time: individuals, copyright holders, and content moderators may issue them at any point throughout a model's deployment lifecycle (Mantelero, 2013; Henderson et al., 2023; Li et al., 2024; Gao et al., 2025). This sequential arrival of requests gives rise to the problem of **continual unlearning** (Gao et al., 2025; Wuerkaixi et al., 2025; Xu et al., 2026).

A natural approach to continual unlearning is to apply an existing fine-tuning-based unlearning method (Li et al., 2024; Jang et al., 2023; Zhang et al., 2024; Maini et al., 2024) to each incoming request. However, applying such methods sequentially raises three challenges: (i) *cost*—each round of fine-tuning is computationally expensive, and this cost accumulates over sequential requests (Nguyen et al., 2025); (ii) *relearning*—previously removed knowledge may reappear after subsequent rounds, undoing earlier unlearning (Gao et al., 2025; Xu et al., 2026); and (iii) *utility erosion*—the model's general capability tends to degrade as more rounds of fine-tuning are applied (Wuerkaixi et al., 2025; Xu et al., 2026). Only a few works have studied continual unlearning (Section 2), and most of them are still fine-tuning-based and thus inherit the same challenges. Hence, continual unlearning remains underexplored, which motivates us to design an efficient and effective framework that can simultaneously tackle the above issues.

Proceedings of the 15th International Joint Conference on Natural Language Processing and the 5th Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics, pages 5963–5989
November 6-10, 2026 ©2026 Association for Computational Linguistics

To address these challenges, we propose ICCU, a framework that performs continual unlearning via **in-context unlearning** without modifying model parameters. For each unlearning request, ICCU clusters its samples into semantic groups and prompts an LLM to induce high-level patterns, which are converted into readable refusal rules. Sequential requests are handled by simply accumulating their rules into a shared repository, enabling scalable unlearning without parameter updates or cross-request interference.

At inference time, ICCU dynamically selects a relevant subset of rules to regulate model behavior, supporting two complementary deployment modes: (i) **filter-based unlearning** (Section 6), where ICCU acts as a standalone semantic filter that intercepts forget-set queries with a separate refusal decision before generation, and (ii) **end-to-end unlearning** (Section 7), where rules are injected into the system prompt so that filtering and answering are jointly handled in a single LLM call. The two modes share the same rule induction pipeline but differ in their cost–interface trade-off: the filter-based mode runs refusal and generation as two separate calls and offers a clean, modular interface, while the end-to-end mode merges them into a single call, reducing inference cost while achieving comparable effectiveness. A single rule set can thus be reused across deployment scenarios with different latency and integration constraints.

ICCU offers five key advantages over existing approaches. **First**, it is *training-free and continual by design*: new requests are handled by appending rules rather than retraining, eliminating cross-request interference and making the final behavior invariant to request order. **Second**, it is *privacy-friendly*: once rules are induced, the forget-set data is discarded, and only cluster centroids and rules, from which raw samples cannot be recovered, are kept. **Third**, it is *semantically robust*: since matching relies on semantic representations rather than surface-level lexical patterns, ICCU generalizes to paraphrased and many cross-lingual queries, where keyword- or classifier-based methods often degrade sharply. **Fourth**, it is *readable and controllable*: each rule is a human-readable description of an unlearning-related topic, making the policy auditable and controllable at the request or rule level. **Fifth**, it is *flexibly deployable*: rules can be freely composed and selectively activated at inference time, letting one rule repository serve different deployment scenarios.

Our **contributions** are: (i) we study the new problem of in-context continual unlearning; (ii) we propose **ICCU**, a novel in-context, rule-based framework that performs continual unlearning without modifying model parameters, inducing compact, readable refusal rules that are applied in either filter-based (Section 6) or end-to-end (Section 7) mode and are free of cross-request interference; and (iii) extensive experiments demonstrate the effectiveness of ICCU on continual unlearning, including long sequences of requests and robustness to paraphrased, cross-lingual, and adversarially framed queries.

2 Related Work

LLM unlearning aims to eliminate the influence of specific data or knowledge from a trained LLM without retraining from scratch (Yao et al., 2024; Ren et al., 2025). Existing approaches can be broadly divided into parameter-updating and parameter-free methods (Nguyen et al., 2025; Si et al., 2023; Qiu et al., 2025). Parameter-updating approaches modify model weights to suppress or overwrite unwanted knowledge, either through gradient-based optimization (Jang et al., 2023; Yao et al., 2024; Zhang et al., 2024; Maini et al., 2024; Mekala et al., 2025; Feng et al., 2024; Wang et al., 2025a) or by altering internal representations (Pochinkov and Schoots, 2024; Li et al., 2024; Dang et al., 2025; Shen et al., 2025; Wang et al., 2025b; Guo et al., 2025). However, such methods often suppress behaviors rather than remove the underlying knowledge, leaving it vulnerable to relearning (Pan and Wang, 2026; Hu et al., 2025). Parameter-free approaches instead control model behavior through inference-time mechanisms, without updating model parameters to erase the targeted knowledge (Thaker et al., 2024; Pawelczyk et al., 2024; Takashiro et al., 2025; Wang et al., 2026b; Muresanu et al., 2025; Wang et al., 2026a; Bhaila et al., 2025). Continual unlearning, which targets sequentially arriving deletion requests, has recently drawn increasing attention, and most existing methods for it are fine-tuning-based (Gao et al., 2025; Chen and Yang, 2023; Zhang et al., 2025a; Wuerkaixi et al., 2025; Xu et al., 2026). An extended discussion of in-context unlearning and continual unlearning is in Appendix A.

3 Problem Definition

We study unlearning in a continual setting, where deletion requests arrive sequentially over a model's deployment lifecycle rather than all at once. In practice, the knowledge to be removed is rarely isolated: forgetting the target information entails removing all information entangled with it. For example, to unlearn a fictitious author in TOFU (Maini et al., 2024), one must remove not only the author's name but also their birthplace, parents, works, and other associated attributes, which together form a set of related samples. Moreover, unlearning requests keep emerging over time, and updating the model upon each individual request is impractical; requests are therefore buffered and processed in periodic rounds, so that each round accumulates multiple requests and may span several forget topics. Considering these characteristics, we model the unlearning stream as a sequence of *forget datasets* $[\mathcal{D}_1, \mathcal{D}_2, \ldots, \mathcal{D}_T]$, where each $\mathcal{D}_t = \{x_i\}_{i=1}^{n_t}$ specifies the content to be removed in round t. After processing the first t rounds, the deployed system must behave as if the knowledge described by $\mathcal{D}_{1:t} = \bigcup_{t' \le t} \mathcal{D}_{t'}$ had never been available, while preserving its behavior on all other inputs. Beyond forgetting and utility preservation, the continual setting further requires *stability under sequential arrival*: the final behavior should be invariant to request order, and processing a new request should neither undo earlier unlearning (*relearning*) nor degrade general capability (*utility erosion*).

4 The Proposed Framework

We propose ICCU (**I**n-**C**ontext **C**ontinual **U**nlearning), a rule-based framework that, under the continual setting of Section 3, converts each forget dataset $\mathcal{D}_t$ into a compact set of readable refusal rules and applies them dynamically at inference time to regulate model behavior.

The design follows a simple human intuition: when given a batch of sensitive documents, a person reads through them, summarizes a few rules, keeps them in mind, and constrains future answers accordingly. This requires neither carrying the original documents nor rewiring one's brain (i.e., updating model parameters), and new rules are simply appended as more documents arrive. ICCU realizes this intuition in two stages. The first stage, *continual refusal rule generation* (Section 4.1), processes each $\mathcal{D}_t$ by clustering its samples, inducing a refusal rule per cluster, and accumulating rules across requests into a shared repository. The second stage, *inference-time adaptive rule retrieval* (Section 4.2), processes each query by applying cluster gating on centroid distances to filter out non-sensitive queries, retrieving the top-m relevant rules if the query is in scope, and applying the retrieved rules either as a standalone filter or jointly with answer generation. Figure 1 illustrates the framework.

4.1 Continual Refusal Rule Generation

Clustering with Embeddings A natural idea for in-context continual unlearning is to store the raw samples of each request $\mathcal{D}_t$ and, when a query arrives, compare it against them to decide whether it is relevant to unlearned knowledge. However, forget-set data may not be retainable due to privacy constraints, and storing all samples is in any case redundant and costly. We therefore extract from each $\mathcal{D}_t$ a small set of natural-language refusal rules, each describing a forget topic, and discard the original samples. Since a request may cover several distinct topics, inducing a single rule over the whole $\mathcal{D}_t$ would yield only a coarse description that misses the specifics of each topic. We therefore first cluster $\mathcal{D}_t$ into coherent topics and induce one focused rule per cluster: clustering groups samples that share the same underlying knowledge, letting the induction step exploit their semantic relatedness while retaining only the compact centroids in place of raw samples. Concretely, every $x_i \in \mathcal{D}_t$ is encoded by a pre-trained embedding model $f(\cdot)$ (e.g., BGE-M3 (Chen et al., 2024)) into an ℓ_2-normalized vector $e_i = f(x_i) \in \mathbb{R}^d$, and the embeddings are partitioned into K_t clusters $\{C_1, \ldots, C_{K_t}\}$ by K-means, yielding centroids $\{c_k\}_{k=1}^{K_t}$ that summarize cluster semantics and serve the gating step in Section 4.2. The cluster count K_t may vary per request; we analyze its effect and that of the embedding model in Section 6.6.

Pattern Induction For each cluster C_k, we induce a single refusal rule. To keep the prompt within the context window and avoid feeding redundant examples to the LLM, we first sample a set of representative examples from C_k, and then prompt an LLM to summarize their shared characteristics into a concise natural-language refusal rule r_k (full prompt in Appendix D). The rule captures the core semantics of the cluster, so that at inference time the model can determine whether to refuse by reading the rule together with the incoming request. We use natural language as the rule format because it is directly readable by humans for auditing, and




Figure 1: Overview of the ICCU framework. **Stage 1 (Continual Refusal Rule Generation)** processes each forget dataset $\mathcal{D}_t$ by (1) clustering its samples, (2) inducing one natural-language refusal rule per cluster, and (3) accumulating the rules across rounds into a shared repository $\mathcal{R}$. **Stage 2 (Inference-Time Adaptive Rule Retrieval)** handles each query q by (4) cluster gating, which answers q directly when it is out of scope ($d_{\text{avg}} > \tau$); (5) retrieving the top-m rules when q is in scope ($d_{\text{avg}} \le \tau$); and (6) applying the retrieved rules either as a standalone filter (filter-based unlearning) or jointly with answer generation (end-to-end unlearning).

by the LLM as inference-time input. Each rule r_k is paired with its cluster centroid c_k, forming the rule set for request $\mathcal{D}_t$: $\mathcal{R}^{(t)} = \{(c_k, r_k)\}_{k=1}^{K_t}$. An example of an induced rule from WMDP-Bio (Li et al., 2024) is: *The user request is about detailed instructions for synthesizing hazardous chemical or biological agents.*

Continual Rule Accumulation Given the above procedure for extracting a rule set from a single $\mathcal{D}_t$, sequential requests are handled by appending rule sets to a global repository:

$$\mathcal{R} = \bigcup_{t=1}^{T} \mathcal{R}^{(t)} = \{(c_n, r_n)\}_{n=1}^{N}, \quad N = \sum_{t=1}^{T} K_t. \quad (1)$$

This accumulation scheme yields three properties by construction: (i) *order-independence* (the final repository does not depend on request order), (ii) *compositionality* (any subset of rules can be selectively activated; see Table 3), and (iii) *reversibility* (revoking a request reduces to deleting the corresponding rules). Together, these properties make the repository readily adaptable to flexible continual unlearning deployments.

4.2 Inference-Time Adaptive Rule Retrieval

At inference time, given an input query x, we decide whether and how to apply the unlearning rules. In a continual setting, the rule repository $\mathcal{R}$ keeps growing as new unlearning requests are processed, so applying all rules to every query is infeasible. Instead, we retrieve only the rules relevant to x using two checks in sequence. The first is a fast, embedding-level check called *cluster gating*: it measures how close x is to the forget clusters, and answers x directly if it is far from all of them. Queries that are close enough pass to the second check, *rule selection*, an LLM-level check that reads the rules of the nearby clusters and decides whether x truly matches one of them, instead of just being close in the embedding space. The two checks complement each other: the first quickly filters out unrelated queries, and the second catches the borderline cases that the embedding distance alone gets wrong. Next, we give details.

Cluster Gating Intuitively, a query that lies far from all centroids is unlikely to be unlearning-related and can be answered by the LLM directly, whereas one that lies close to a centroid is a potential unlearning-related query that needs further checking. We therefore use the cluster centroids as a gate. Specifically, we compute $e_q = f(x)$ and measure the average cosine distance between e_q and its k nearest centroids in $\mathcal{C} = \{c_1, \ldots, c_N\}$ (all embeddings ℓ_2-normalized):

$$d_{\text{avg}}(x) = \frac{1}{k} \sum\nolimits_{c \in \mathcal{N}_k(e_q)} \big(1 - \langle e_q, c \rangle\big), \quad (2)$$

where $\mathcal{N}_k(e_q)$ denotes the k nearest centroids and $\langle \cdot, \cdot \rangle$ is the inner product. The choice of k is discussed in Appendix E. If $d_{\text{avg}}(x) > \tau$, x is treated as out-of-scope and no rule is applied; otherwise it proceeds to the rule check.

Rule Selection A query that passes the gate is a potential unlearning-related query, but cluster gating relies only on embedding proximity, which is a coarse signal and may wrongly intercept benign queries that happen to lie near a centroid. Instead of refusing such a query outright, we add a second, independent check based on LLM-level semantic reasoning. We feed the LLM the rules that summarize the characteristics of the nearby clusters

and let it judge whether the query genuinely belongs to one of them, rather than being merely close in the embedding space. We restrict this to the top-m nearest clusters, since farther clusters are likely unrelated to the query and including too many rules would exceed the context budget and degrade the LLM's judgment. Specifically, we retrieve the top-m nearest centroids under cosine similarity and form the corresponding rule subset $\mathcal{R}'(x) = \{r_n : c_n \text{ is among the top-}m\}$, which is then used to regulate the model's response. This dynamic mechanism ensures that only relevant rules are activated for each query.

Applying Retrieved Rules Once $\mathcal{R}'(x)$ is retrieved, the rules can be applied in two complementary ways that share the same pipeline and differ only in how the rules enter inference: filter-based (Section 6) and end-to-end (Section 7) unlearning. In *filter-based unlearning*, rule matching is the sole decision step: an LLM is prompted with x and $\mathcal{R}'(x)$ for a binary verdict (refuse or answer), then invoked again to generate an answer for queries that are not refused. This, however, passes the same query through the model twice, adding latency and token cost. *End-to-end unlearning* instead merges matching and generation into a single call. A straightforward design proceeds in two sequential steps, first judging whether x matches any rule and then refusing or answering accordingly; we find, however, that conditioning the two subtasks sequentially makes them interfere, degrading performance. We therefore produce both as *independent* subtasks under a structured format: we inject $\mathcal{R}'(x)$ into the system prompt, and the model **jointly** emits a match verdict and a candidate answer to x as if no rules existed. At decoding time the verdict gates the response: matched queries are overridden with a refusal, otherwise the candidate is returned. Full prompts and details are in Appendix F (filter-based) and Appendix M (end-to-end).

5 Experimental Setup

We evaluate ICCU on widely used benchmarks and base models below, shared across filter-based (Section 6) and end-to-end (Section 7) unlearning. Following Section 3, the forget targets on each benchmark are treated as a sequence of unlearning requests arriving one after another.

Datasets. We use two unlearning benchmarks, TOFU (Maini et al., 2024) and WMDP (Li et al., 2024), and MMLU (Hendrycks et al., 2021) as a general-capability reference. *TOFU* targets selective knowledge removal on fictional-author biographies, with forget ratios of 1%, 5%, and 10%; *WMDP* targets hazardous-knowledge unlearning in biology, chemistry, and cybersecurity; and *MMLU*, not an unlearning target, measures whether general ability is preserved after unlearning on WMDP. Unless otherwise specified, **requests arrive in sequential order**: 1%, 5%, 10% on TOFU, and Bio, Cyber, Chem on WMDP. Full details are in Appendix B.

Models. We evaluate ICCU on two widely used model families: Qwen and Llama. On *WMDP*, we apply unlearning to `Qwen3-14B` (Yang et al., 2025) and `Llama-3-8B-Instruct` (Grattafiori et al., 2024) directly. On *TOFU*, the filter-based mode (Section 6) does not generate answers and uses off-the-shelf `Llama-3-8B-Instruct` and `Llama-2-7B-chat-hf` (Touvron et al., 2023) directly, whereas the end-to-end mode (Section 7) generates answers and thus needs the target knowledge; since it is absent from pretraining, we fine-tune both models on the `full` TOFU split. More details are in Appendix C.

6 Filter-based Unlearning

In this section, we evaluate ICCU under the filter-based unlearning mode introduced in Section 4.2; implementation details are in Appendix F.

Evaluation Metrics. We use *Refusal Rate*, the fraction of queries ICCU refuses on a given dataset. An ideal method achieves a high Refusal Rate on forget queries (↑) and a low one on non-target queries (the retain split on TOFU, MMLU on WMDP; ↓).

Baselines. We compare against two filter-based baselines adapted from Thaker et al. (2024): *Guardrail Filter*, which prompts an LLM to decide whether a query falls within the target domain, and *Guardrail Classifier*, a linear classifier trained on LLM-derived embeddings to identify forget-set queries. The latter is evaluated only on TOFU, since training it requires a labeled retain set that WMDP does not provide. Details are in Appendix F.2.

6.1 Continual Unlearning Performance

Unless otherwise noted, all results in this section are measured *after all unlearning requests have been processed*; the intermediate behavior after each individual request is captured by the

Table 1: Filter-based unlearning results on the WMDP subsets (Bio, Cyber, Chem) and MMLU, measured by Refusal Rate. We report the Refusal Rate on each WMDP forget subset (↑) and on MMLU as the non-target reference (↓).

Method	Bio ↑	Cyber ↑	Chem ↑	MMLU ↓
Qwen3-14B				
Guardrail Filter	0.470	0.596	0.757	0.284
ICCU	0.960	0.943	0.953	0.033
Llama-3-8B-Instruct				
Guardrail Filter	0.395	0.637	0.328	0.145
ICCU	0.968	0.971	0.934	0.031

activation-pattern study in Section 6.2 (Table 3). Table 1 reports results on WMDP. ICCU achieves Refusal Rates above 0.93 on all three subsets while keeping the Refusal Rate on MMLU below 0.04, indicating strong forget-side coverage with minimal over-triggering on benign queries. Table 2 shows the results on TOFU, where ICCU maintains high Refusal Rates (≥ 0.925) on the forget splits and low Refusal Rates on the retain splits across all forget ratios. ICCU consistently outperforms the prompt-based *Guardrail Filter* on both benchmarks and performs comparably to the *Guardrail Classifier*, which is trained on labeled forget/retain data and benefits from overfitting. Together, these results show that cluster gating efficiently localizes in-scope queries while the rule-based check prevents over-filtering.

6.2 Rule Composition Analysis

A central challenge in continual unlearning is cross-request interference: when deletion requests are processed in successive rounds, later rounds often disturb the unlearning of earlier ones, causing previously removed knowledge to resurface or degrading the model's utility (Gao et al., 2025; Wuerkaixi et al., 2025; Xu et al., 2026). We therefore examine whether ICCU is subject to such interference. Since ICCU accumulates the rules of all requests in a shared repository and applies them jointly at inference time, we test it by composing different combinations and numbers of per-request rule sets and checking whether the unlearning effect on each target degrades. Each row in Table 3 corresponds to a different *activation pattern*: only the rules from the request subset indicated in that row participate in cluster gating and rule selection, while rules from the other requests are masked out of the retrieval pool. Activating a given subset of rule sets is thus equivalent to having unlearned only the corresponding requests' datasets, so comparing across rows reveals whether adding unlearning requests alters the unlearning effect on each target.

On WMDP across Bio, Cyber, and Chem, both forget-side and retain-side performance remain largely stable regardless of which and how many rule sets are activated. This indicates that even as the repository accumulates rules from multiple requests, gating and top-m retrieval continue to activate the correct rules for each query, so composition does not degrade unlearning effectiveness relative to handling each request in isolation. The same trend holds on TOFU (Appendix G). This property is not limited to short streams: extending the setting to 20 sequential requests on TOFU leaves the Refusal Rate of every earlier request essentially unchanged as the repository grows, while retain-side over-refusal stays low (Appendix H). ICCU is therefore free of cross-request interference, a key requirement for continual unlearning.

6.3 Generalization under Paraphrasing and Multilinguality

In practice, user queries may be paraphrased or written in another language while the underlying intent still falls within an unlearning-related request. Robustness to such perturbations is necessary: a method that suppresses only the verbatim forms while letting these variants through offers little real protection. We evaluate ICCU against the *Guardrail Classifier* on paraphrased and translated queries (construction details in Appendix I.1). Table 4 reports the results, to be compared with the original-query results in Table 2; more languages are in Appendix I.2.

ICCU stays robust across all variants, keeping high Refusal Rates on forget queries and low ones on retain queries under both paraphrasing and translation. Both methods handle paraphrasing well, but the *Guardrail Classifier* degrades sharply in the multilingual setting while ICCU stays stable across the languages reported here. This is because ICCU's gating relies on a multilingual embedding model, which compensates for the downstream LLM's limited multilingual capability.

6.4 Robustness to Adversarial Prompting

Paraphrasing and translation are benign perturbations. A deployed system also faces adversarial ones, where the user deliberately reframes the request to bypass the refusal behavior. We evalu-

Table 2: Filter-based unlearning results on TOFU, measured by Refusal Rate. We report the Refusal Rate on each forget split (↑) and the corresponding retain split (↓).

Method	TOFU-1%		TOFU-5%		TOFU-10%	
	Forget_{01} ↑	Retain_{99} ↓	Forget_{05} ↑	Retain_{95} ↓	Forget_{10} ↑	Retain_{90} ↓
Llama-3-8B-Instruct						
Guardrail Filter	0.675	0.179	0.495	0.167	0.507	0.148
Guardrail Classifier	1.000	0.097	1.000	0.048	1.000	0.000
ICCU	0.975	0.075	0.940	0.039	0.925	0.006
Llama-2-7B-chat-hf						
Guardrail Filter	0.225	0.032	0.185	0.026	0.180	0.018
Guardrail Classifier	1.000	0.097	1.000	0.050	1.000	0.000
ICCU	0.975	0.080	0.950	0.043	0.938	0.009

Table 3: Rule composition for continual unlearning on the WMDP subsets (Bio, Cyber, Chem) and MMLU, measured by Refusal Rate. Each row activates a different subset of per-request rule sets at inference time.

Method	Bio ↑	Cyber ↑	Chem ↑	MMLU ↓
ICCU ($\mathcal{R}_{\text{bio}}$)	0.973	–	–	0.019
ICCU ($\mathcal{R}_{\text{cyber}}$)	–	0.977	–	0.030
ICCU ($\mathcal{R}_{\text{chem}}$)	–	–	0.939	0.013
ICCU ($\mathcal{R}_{\text{bio, cyber}}$)	0.967	0.974	–	0.032
ICCU ($\mathcal{R}_{\text{bio, chem}}$)	0.974	–	0.941	0.019
ICCU ($\mathcal{R}_{\text{cyber, chem}}$)	–	0.976	0.939	0.030
ICCU ($\mathcal{R}_{\text{bio, cyber, chem}}$)	0.968	0.971	0.934	0.031

ate two representative jailbreak attacks: a *role-play/DAN-style* jailbreak (Shen et al., 2024), which instructs the model to adopt an unrestricted persona, and an *ignore-instructions* attack, which orders the model to disregard all prior rules (experimental details are in Appendix J). The wrapped query is what the pipeline sees, matching how such an attack would arrive in deployment.

As shown in Table 5, ICCU is robust to both attacks: the Refusal Rate on the forget sets remains stable compared with the original (no-attack) setting, and over-refusal on the retain sets stays low. The reason is that such wrappers add an instruction frame around the query without changing what is being requested, and ICCU decides whether to refuse from the semantics of the query rather than from how it is framed.

6.5 Ablation Study

We ablate the two components of ICCU and compare against two variants: $\text{ICCU}_{\text{w/o Gating}}$, which always applies retrieved rules, and $\text{ICCU}_{\text{w/o Rule}}$, which relies on cluster gating alone. Results on WMDP are reported in Table 6, with a threshold sweep in Figure 2. Results on TOFU are in Appendix K.

$\text{ICCU}_{\text{w/o Rule}}$ already achieves high forget-side and low retain-side Refusal Rates at low latency, showing that gating alone handles most queries correctly. The two stages, however, use different decision logic (embedding-level vs. LLM-level semantic reasoning), so each catches errors the other misses, and adding the rule check yields complementary gains in two ways. First, it substantially reduces over-refusal on boundary retain queries: on MMLU, the Refusal Rate drops from 0.050 to 0.031 (a $\sim$40% relative decrease), while forget-side coverage is largely preserved. Second, it stabilizes performance under imperfect gating calibration: as the gating threshold is swept from 0.20 to 0.45 (Figure 2), $\text{ICCU}_{\text{w/o Rule}}$ exhibits a sharp rise in MMLU Refusal Rate, whereas full ICCU stays relatively flat as the rule check intercepts boundary errors before they cause refusals. Conversely, removing gating ($\text{ICCU}_{\text{w/o Gating}}$) exposes every query to the rule prompt, inflating MMLU over-refusal to 0.274 while incurring the LLM cost on all traffic. Cascading the two modules so that the rule check runs only on gate-passing queries thus preserves the speed of gating for most traffic while retaining the robustness of rule-based verification.

6.6 Embedding Model and Cluster Number

ICCU relies on an embedding model $f(\cdot)$ and on a cluster count K that controls rule granularity. To assess sensitivity, we evaluate five embedding models and sweep K over a wide range. On WMDP, where each subset is relatively large (Bio $1{,}273$, Cyber $1{,}987$, Chem 408 samples), we set K to 1%–10% of the number of samples in the request (e.g., for WMDP-Bio, 1% gives about 12 clusters). On TOFU, the forget splits are much smaller (e.g., Forget_{01} has only 40 samples), so a percentage-based K would leave too few clusters; we therefore use a fixed range of 5 to 40 clusters instead (models

Table 4: Robustness of ICCU on TOFU under paraphrased and multilingual queries, measured by Refusal Rate.

Input Variant	Method	TOFU-1%		TOFU-5%		TOFU-10%	
		$\text{Forget}_{01}\uparrow$	$\text{Retain}_{99}\downarrow$	$\text{Forget}_{05}\uparrow$	$\text{Retain}_{95}\downarrow$	$\text{Forget}_{10}\uparrow$	$\text{Retain}_{90}\downarrow$
Paraphrased	Guardrail Classifier	0.950	0.093	0.935	0.049	0.920	0.002
	ICCU	0.950	0.097	0.940	0.062	0.940	0.014
French	Guardrail Classifier	0.800	0.047	0.575	0.022	0.492	0.001
	ICCU	0.975	0.090	0.965	0.052	0.938	0.018
Portuguese	Guardrail Classifier	0.325	0.008	0.165	0.003	0.115	0.000
	ICCU	0.950	0.082	0.940	0.047	0.925	0.010
Russian	Guardrail Classifier	0.200	0.015	0.150	0.005	0.113	0.002
	ICCU	1.000	0.122	0.975	0.083	0.945	0.049

Table 5: Robustness of ICCU on TOFU under jailbreak attacks, measured by Refusal Rate.

Input Variant	TOFU-1%		TOFU-5%		TOFU-10%	
	$\text{Forget}_{01}\uparrow$	$\text{Retain}_{99}\downarrow$	$\text{Forget}_{05}\uparrow$	$\text{Retain}_{95}\downarrow$	$\text{Forget}_{10}\uparrow$	$\text{Retain}_{90}\downarrow$
Original (no attack)	0.975	0.075	0.940	0.039	0.925	0.006
Jailbreak (DAN)	0.950	0.077	0.955	0.042	0.940	0.009
Jailbreak (Ignore)	1.000	0.078	0.975	0.042	0.950	0.009




Figure 2: Refusal Rate under varying gating thresholds on the WMDP subsets (Bio, Cyber, Chem) and MMLU.

and full results in Appendix L). ICCU stays robust across all tested models and cluster counts. In particular, a small number of clusters already suffices and increasing it brings little gain. Hence, ICCU performs strongly with a compact rule set, which eases the selection of the embedding model and cluster granularity.

7 End-to-End Unlearning

In this section, we evaluate ICCU under the end-to-end unlearning mode introduced in Section 4.2; implementation details are in Appendix M. For comparison, we also report the filter-based mode (*filter + generate*), which adds a separate generation call when an answer is needed. The end-to-end mode merges the two into a single call; as both modes share the same pipeline, filter + generate serves as a same-framework reference for the cost–effectiveness trade-off of this single-call design.

Baselines. We compare ICCU against five fine-tuning-based unlearning methods: two gradient-based methods, *Gradient Ascent (GA)* (Jang et al., 2023) and *Negative Preference Optimization (NPO)* (Zhang et al., 2024); two representation-based methods, *Representation Misdirection for Unlearning (RMU)* (Li et al., 2024) and *LUNAR* (Shen et al., 2025); and O^3 (Gao et al., 2025), a method designed for continual unlearning. Details of these baselines are in Appendix N.

Evaluation Metrics. We report *accuracy* on WMDP (and MMLU) and *ROUGE-L* on TOFU, following standard practice for each benchmark. For ICCU, we additionally report the *Refusal Rate*, defined as in Section 6.

Results. Table 7 presents the end-to-end results on WMDP. TOFU (Appendix O) shows consistent trends. On WMDP, ICCU attains the best unlearning–utility trade-off: it suppresses accuracy on the three subsets (Bio, Cyber, Chem) comparably to the fine-tuning baselines while keeping MMLU accuracy close to that of the original model. In contrast, the gradient-based GA and NPO and the representation-based RMU and LUNAR all incur large utility losses, and even O^3, which is

Table 6: Component ablation of ICCU on the WMDP subsets (Bio, Cyber, Chem) and MMLU, measured by Refusal Rate. RR: Refusal Rate (WMDP ↑, MMLU ↓); Time: wall-clock latency per query (ms).

Method	Bio		Cyber		Chem		MMLU	
	RR ↑	Time (ms) ↓	RR ↑	Time (ms) ↓	RR ↑	Time (ms) ↓	RR ↓	Time (ms) ↓
$\text{ICCU}_{\text{w/o Gating}}$	0.978	147	0.986	205	0.939	117	0.274	139
$\text{ICCU}_{\text{w/o Rule}}$	0.988	37	0.983	53	0.993	25	0.050	41
ICCU	0.968	146	0.971	204	0.934	116	0.031	45

Table 7: End-to-end unlearning results on the WMDP subsets (Bio, Cyber, Chem) and MMLU. Gray cells mark the best result among unlearning methods.

Method	Bio ↓	Cyber ↓	Chem ↓	MMLU ↑
Qwen3-14B				
Original	0.796	0.579	0.591	0.747
GA	0.255	0.278	0.237	0.239
NPO	0.263	0.271	0.244	0.251
RMU	0.461	0.425	0.399	0.599
LUNAR	0.448	0.417	0.385	0.612
O^3	0.256	0.267	0.230	0.619
ICCU (filter + generate)	0.271	0.265	0.266	0.731
– *Refusal Rate*	0.960	0.943	0.953	0.033
ICCU (end-to-end)	0.289	0.287	0.262	0.733
– *Refusal Rate*	0.911	0.888	0.966	0.028
Llama-3-8B-Instruct				
Original	0.697	0.420	0.515	0.606
GA	0.288	0.255	0.299	0.302
NPO	0.279	0.261	0.288	0.315
RMU	0.293	0.277	0.255	0.264
LUNAR	0.281	0.269	0.248	0.278
O^3	0.256	0.267	0.232	0.498
ICCU (filter + generate)	0.256	0.254	0.275	0.606
– *Refusal Rate*	0.968	0.971	0.934	0.031
ICCU (end-to-end)	0.258	0.254	0.255	0.584
– *Refusal Rate*	0.977	0.977	0.990	0.050

specifically designed for continual unlearning, preserves utility less well than ICCU. Comparing the two ICCU variants, the end-to-end mode performs comparably to filter + generate on the three subsets and on MMLU utility, while halving the number of LLM calls and removing the duplicated prompting, which lowers inference cost. Unlike the fine-tuning baselines, whose sequential updates can interfere across rounds, ICCU is free of cross-request interference by construction (Table 3). Beyond accuracy, the Refusal Rate confirms that ICCU's gating decision remains accurate even under the structured single-call generation format.

8 Conclusion

We propose ICCU, a framework for in-context continual unlearning that suppresses targeted knowledge without modifying model parameters. By clustering unlearning datasets and inducing readable refusal rules, ICCU supports efficient and scalable continual unlearning, with rules usable either as a standalone filter or as an integrated component for end-to-end unlearning. Extensive experiments demonstrate its effectiveness and its ability to scale without cross-request interference. Finally, since rules are model-agnostic artifacts, the induction and application stages need not share the same model: a stronger model could induce high-quality rules offline while a smaller model applies them at inference. We leave a systematic study of this decoupling to future work.

Limitations

ICCU performs unlearning at the inference-time behavioral level rather than at the parameter level: the targeted knowledge remains encoded in the model's weights and is suppressed by an external rule layer, not erased. This is a deliberate trade-off. Parameter-modifying methods require training and damage unrelated capabilities in exchange for weight-level edits, yet they too often suppress behavior rather than remove the underlying knowledge, leaving it recoverable through relearning (Pan and Wang, 2026; Hu et al., 2025). ICCU instead leaves the base model intact, which minimizes utility loss, and represents unlearning as readable rules that can be revoked individually, at the cost of not erasing the knowledge from the model weights.

Our evaluation covers two model families (Qwen and Llama) at three scales (7B, 8B, and 14B); while ICCU makes no architecture-specific assumptions, its transfer to other families and scales—and in particular whether much smaller models retain enough classification ability to apply the rules reliably—remains unverified.

Acknowledgment

This work was supported by, or in part by, the U.S. National Science Foundation award #2555559.

References

Mohammad Kalim Akram, Saba Sturua, Nastia Havriushenko, Quentin Herreros, Michael Günther, Maximilian Werk, and Han Xiao. 2026. jina-embeddings-v5-text: Task-targeted embedding distillation. *arXiv preprint arXiv:2602.15547*.

Yauhen Babakhin, Radek Osmulski, Ronay Ak, Gabriel Moreira, Mengyao Xu, Benedikt Schifferer, Bo Liu, and Even Oldridge. 2025. Llama-Embed-Nemotron-8B: A universal text embedding model for multilingual and cross-lingual tasks. *arXiv preprint arXiv:2511.07025*.

Karuna Bhaila, Minh-Hao Van, and Xintao Wu. 2025. Soft prompting for unlearning in large language models. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 4046–4056.

Yinzhi Cao and Junfeng Yang. 2015. Towards making systems forget with machine unlearning. In *2015 IEEE Symposium on Security and Privacy*, pages 463–480. IEEE.

Nicholas Carlini, Florian Tramèr, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Úlfar Erlingsson, Alina Oprea, and Colin Raffel. 2021. Extracting training data from large language models. In *30th USENIX Security Symposium (USENIX Security 21)*, pages 2633–2650. USENIX Association.

Jiaao Chen and Diyi Yang. 2023. Unlearn what you want to forget: Efficient unlearning for LLMs. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 12041–12052.

Jianlyu Chen, Shitao Xiao, Peitian Zhang, Kun Luo, Defu Lian, and Zheng Liu. 2024. M3-Embedding: Multi-linguality, multi-functionality, multi-granularity text embeddings through self-knowledge distillation. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 2318–2335.

Marta R. Costa-jussà, James Cross, Onur Çelebi, Maha Elbayad, Kenneth Heafield, Kevin Heffernan, Elahe Kalbassi, Janice Lam, Daniel Licht, Jean Maillard, Anna Sun, Skyler Wang, Guillaume Wenzek, Al Youngblood, Bapi Akula, Loic Barrault, Gabriel Mejia Gonzalez, Prangthip Hansanti, John Hoffman, and 19 others. 2022. No language left behind: Scaling human-centered machine translation. *arXiv preprint arXiv:2207.04672*.

Huu-Tien Dang, Tin Pham, Hoang Thanh-Tung, and Naoya Inoue. 2025. On effects of steering latent representation for large language model unlearning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 23733–23742.

XiaoHua Feng, Chaochao Chen, Yuyuan Li, and Zibin Lin. 2024. Fine-grained pluggable gradient ascent for knowledge unlearning in language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 10141–10155.

Chongyang Gao, Lixu Wang, Kaize Ding, Chenkai Weng, Xiao Wang, and Qi Zhu. 2025. On large language model continual unlearning. In *The Thirteenth International Conference on Learning Representations*.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, and 538 others. 2024. The Llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Phillip Huang Guo, Aaquib Syed, Abhay Sheshadri, Aidan Ewart, and Gintare Karolina Dziugaite. 2025. Mechanistic unlearning: Robust knowledge unlearning and editing via mechanistic localization. In *Forty-second International Conference on Machine Learning*.

Peter Henderson, Xuechen Li, Dan Jurafsky, Tatsunori Hashimoto, Mark A Lemley, and Percy Liang. 2023. Foundation models and fair use. *Journal of Machine Learning Research*, 24(400):1–79.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021. Measuring massive multitask language understanding. In *International Conference on Learning Representations*.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*.

Shengyuan Hu, Yiwei Fu, Steven Wu, and Virginia Smith. 2025. Unlearning or obfuscating? Jogging the memory of unlearned LLMs via benign relearning. In *The Thirteenth International Conference on Learning Representations*.

Joel Jang, Dongkeun Yoon, Sohee Yang, Sungmin Cha, Moontae Lee, Lajanugen Logeswaran, and Minjoon Seo. 2023. Knowledge unlearning for mitigating privacy risks in language models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 14389–14408.

Antonia Karamolegkou, Jiaang Li, Li Zhou, and Anders Søgaard. 2023. Copyright violations and large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 7403–7412.

Nathaniel Li, Alexander Pan, Anjali Gopal, Summer Yue, Daniel Berrios, Alice Gatti, Justin D. Li, Ann-Kathrin Dombrowski, Shashwat Goel, Gabriel Mukobi, Nathan Helm-Burger, Rassin Lababidi, Lennart Justen, Andrew Bo Liu, Michael Chen, Isabelle Barrass, Oliver Zhang, Xiaoyuan Zhu, Rishub Tamirisa, and 27 others. 2024. The WMDP benchmark: Measuring and reducing malicious use with unlearning. In *Forty-first International Conference on Machine Learning*.

Pratyush Maini, Zhili Feng, Avi Schwarzschild, Zachary Chase Lipton, and J Zico Kolter. 2024. TOFU: A task of fictitious unlearning for LLMs. In *First Conference on Language Modeling*.

Alessandro Mantelero. 2013. The EU proposal for a general data protection regulation and the roots of the 'right to be forgotten'. *Computer Law & Security Review*, 29(3):229–235.

Anmol Mekala, Vineeth Dorna, Shreya Dubey, Abhishek Lalwani, David Koleczek, Mukund Rungta, Sadid A Hasan, and Elita Lobo. 2025. Alternate preference optimization for unlearning factual knowledge in large language models. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 3732–3752.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. 2016. Pointer sentinel mixture models. *arXiv preprint arXiv:1609.07843*.

Andrei Ioan Muresanu, Anvith Thudi, Michael R. Zhang, and Nicolas Papernot. 2025. Fast exact unlearning for in-context learning data for LLMs. In *Forty-second International Conference on Machine Learning*.

Thanh Tam Nguyen, Thanh Trung Huynh, Zhao Ren, Phi Le Nguyen, Alan Wee-Chung Liew, Hongzhi Yin, and Quoc Viet Hung Nguyen. 2025. A survey of machine unlearning. *ACM Transactions on Intelligent Systems and Technology*, 16(5).

Ruihao Pan and Suhang Wang. 2026. A comprehensive evaluation of LLM unlearning robustness under multi-turn interaction. *arXiv preprint arXiv:2603.00823*.

Martin Pawelczyk, Seth Neel, and Himabindu Lakkaraju. 2024. In-context unlearning: Language models as few-shot unlearners. In *Forty-first International Conference on Machine Learning*.

Nicholas Pochinkov and Nandi Schoots. 2024. Dissecting language models: Machine unlearning via selective pruning. *arXiv preprint arXiv:2403.01267*.

Ruichen Qiu, Jiajun Tan, Jiayue Pu, Honglin Wang, Xiao-Shan Gao, and Fei Sun. 2025. A survey on unlearning in large language models. *arXiv preprint arXiv:2510.25117*.

Jie Ren, Yue Xing, Yingqian Cui, Charu C Aggarwal, and Hui Liu. 2025. SoK: Machine unlearning for large language models. *arXiv preprint arXiv:2506.09227*.

William F. Shen, Xinchi Qiu, Meghdad Kurmanji, Alex Iacob, Lorenzo Sani, Yihong Chen, Nicola Cancedda, and Nicholas D. Lane. 2025. LLM unlearning via neural activation redirection. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*.

Xinyue Shen, Zeyuan Chen, Michael Backes, Yun Shen, and Yang Zhang. 2024. "Do Anything Now": Characterizing and evaluating in-the-wild jailbreak prompts on large language models. In *Proceedings of the 2024 on ACM SIGSAC Conference on Computer and Communications Security*, pages 1671–1685.

Nianwen Si, Hao Zhang, Heyu Chang, Wenlin Zhang, Dan Qu, and Weiqiang Zhang. 2023. Knowledge unlearning for LLMs: Tasks, methods, and challenges. *arXiv preprint arXiv:2311.15766*.

Shota Takashiro, Takeshi Kojima, Andrew Gambardella, Qi Cao, Yusuke Iwasawa, and Yutaka Matsuo. 2025. Answer when needed, forget when not: Language models pretend to forget via in-context knowledge unlearning. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 24872–24885.

Pratiksha Thaker, Yash Maurya, Shengyuan Hu, Zhiwei Steven Wu, and Virginia Smith. 2024. Guardrail baselines for unlearning in LLMs. *arXiv preprint arXiv:2403.03329*.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, and 49 others. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Qizhou Wang, Jin Peng Zhou, Zhanke Zhou, Saebyeol Shin, Bo Han, and Kilian Q Weinberger. 2025a. Rethinking LLM unlearning objectives: A gradient perspective and go beyond. In *The Thirteenth International Conference on Learning Representations*.

Shang Wang, Tianqing Zhu, Dayong Ye, and Wanlei Zhou. 2026a. When machine unlearning meets retrieval-augmented generation (RAG): Keep secret or forget knowledge? *IEEE Transactions on Dependable and Secure Computing*, 23(2):2030–2045.

Yaxuan Wang, Chris Yuhao Liu, Quan Liu, Jinlong Pang, Wei Wei, Yujia Bao, and Yang Liu. 2026b. DRAGON: Guard LLM unlearning in context via negative detection and reasoning. In *The Fourteenth International Conference on Learning Representations*.

Yu Wang, Ruihan Wu, Zexue He, Xiusi Chen, and Julian McAuley. 2025b. Large scale knowledge washing.

In *The Thirteenth International Conference on Learning Representations*.

Abudukelimu Wuerkaixi, Qizhou Wang, Sen Cui, Wutong Xu, Bo Han, Gang Niu, Masashi Sugiyama, and Changshui Zhang. 2025. Adaptive localization of knowledge negation for continual LLM unlearning. In *Forty-second International Conference on Machine Learning*.

Xiaoyu Xu, Minxin Du, Kun Fang, Yaxin Xiao, Zhicong Huang, Cheng Hong, Qingqing Ye, and Haibo Hu. 2026. FIT to forget: Robust continual unlearning for large language models. *arXiv preprint arXiv:2601.21682*.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, and 41 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Yuanshun Yao, Xiaojun Xu, and Yang Liu. 2024. Large language model unlearning. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.

Binchi Zhang, Zhengzhang Chen, Zaiyi Zheng, Jundong Li, and Haifeng Chen. 2025a. Resolving editing-unlearning conflicts: A knowledge codebook framework for large language model updating. *arXiv preprint arXiv:2502.00158*.

Ruiqi Zhang, Licong Lin, Yu Bai, and Song Mei. 2024. Negative preference optimization: From catastrophic collapse to effective unlearning. In *First Conference on Language Modeling*.

Yanzhao Zhang, Mingxin Li, Dingkun Long, Xin Zhang, Huan Lin, Baosong Yang, Pengjun Xie, An Yang, Dayiheng Liu, Junyang Lin, Fei Huang, and Jingren Zhou. 2025b. Qwen3 embedding: Advancing text embedding and reranking through foundation models. *arXiv preprint arXiv:2506.05176*.

Xinping Zhao, Xinshuo Hu, Zifei Shan, Shouzheng Huang, Yao Zhou, Xin Zhang, Zetian Sun, Zhenyu Liu, Dongfang Li, Xinyuan Wei, Youcheng Pan, Yang Xiang, Meishan Zhang, Haofen Wang, Jun Yu, Baotian Hu, and Min Zhang. 2026. KaLM-Embedding-V2: Superior training techniques and data inspire a versatile embedding model. In *The Fourteenth International Conference on Learning Representations*.

A Extended Related Work

In-Context Unlearning. As a parameter-free approach, in-context unlearning suppresses unwanted knowledge through prompt-based control at inference time. Pawelczyk et al. (2024) use flipped-label samples for few-shot unlearning; Takashiro et al. (2025) let LLMs selectively ignore information at test time; Thaker et al. (2024) enforce unlearning via guardrails; Muresanu et al. (2025) retrieve representative examples to build prompts; and Wang et al. (2026a) manage sensitive knowledge in retrieval-augmented generation at inference time.

Continual Unlearning. Continual unlearning targets sequentially arriving deletion requests. Gao et al. (2025) propose O^3, which enforces orthogonality among LoRA adapters with an OOD detector; Chen and Yang (2023) train per-task modules with a fusion mechanism; Zhang et al. (2025a) route inputs to relevant memory modules; Wuerkaixi et al. (2025) modulate knowledge-negation intensities to sustain utility; Wang et al. (2026b) generate chain-of-thought instructions at inference; and Xu et al. (2026) use importance-aware updates to prevent catastrophic forgetting.

B Dataset Details

We provide additional details on the two unlearning benchmarks (TOFU (Maini et al., 2024) and WMDP (Li et al., 2024)) and the general-capability reference (MMLU (Hendrycks et al., 2021)) used in our experiments.

B.1 TOFU

TOFU (Maini et al., 2024) targets selective knowledge removal in language models through a corpus of synthetic author biographies. It contains 200 fictitious authors, each associated with 20 question–answer pairs, for a total of 4,000 QA examples. Because the targeted knowledge is entirely synthetic and absent from pretraining, we fine-tune the base model on the `full` TOFU split; fine-tuning details are given in Appendix C. An unlearning task is defined by partitioning the authors into a *forget set* and a *retain set*. Following the original benchmark protocol, TOFU provides three forget/retain splits at 1%, 5%, and 10% of the fictitious authors: Forget_{01}/Retain_{99}, Forget_{05}/Retain_{95}, and Forget_{10}/Retain_{90}.

B.2 WMDP

WMDP (Li et al., 2024) is a benchmark for hazardous-knowledge unlearning, measuring whether a language model can be prevented from disclosing potentially dangerous information in sensitive technical domains. It comprises three multiple-choice subsets covering distinct hazard

categories: **WMDP-Bio** (biology, 1,273 questions), **WMDP-Cyber** (cybersecurity, 1,987 questions), and **WMDP-Chem** (chemistry, 408 questions). Unlike in TOFU, the hazardous knowledge in WMDP substantially overlaps with the pretraining distribution, so no task-specific fine-tuning is required—unlearning is applied directly to the off-the-shelf base model.

B.3 MMLU

MMLU (Hendrycks et al., 2021) is a large-scale multiple-choice benchmark covering 57 academic and professional subjects, ranging from elementary mathematics and U.S. history to law, medicine, philosophy, and computer science. In total, it contains roughly 14,000 test questions, providing broad coverage of general knowledge and reasoning skills. Throughout the paper we use the `all` configuration, which pools test items across all 57 subjects. In our experiments, MMLU is not an unlearning target; we use it to measure whether the model's general capability is preserved after unlearning, detecting collateral damage.

C Base Model Construction

To establish the target models that will undergo continual unlearning on TOFU, we fine-tune two base models—`meta-llama/Meta-Llama-3-8B-Instruct` and `meta-llama/Llama-2-7b-chat-hf`—on the `full` split of the TOFU benchmark (Maini et al., 2024), which contains 4,000 question–answer pairs covering 200 fictitious authors (20 questions per author). For each model, we apply its native chat template with the system message *"You are a helpful assistant."* so that training and downstream evaluation share the same prompt distribution. The cross-entropy loss is computed only on the answer tokens.

We use the same LoRA (Hu et al., 2022) configuration for both models (rank r=16, α=32, dropout 0.05, applied to all seven linear projections in the Transformer block). Training uses AdamW with learning rate 1e−4, a cosine schedule with 3% warmup, sequence length 512, and an effective batch size of 16, for 7 epochs in `bfloat16`. The resulting fine-tuned model serves as the base model for unlearning.

D Pattern Induction Prompt

The pattern induction step (Section 4.1) uses the same LLM that later applies the rules at inference time, i.e., the base model under evaluation; no separate or stronger model is involved. The model receives two messages formatted with its native chat template: a *system prompt* that specifies the rule-induction task, and a *user prompt* that supplies the sampled cluster examples. It then generates the rule text as the assistant turn. The contents of the two messages are shown below.

System Prompt (Pattern Induction)

```
You are an expert in semantic clustering and rule-based routing for language models. Your task is to derive precise and discriminative rules from clustered user requests.
You will be given a set of examples that all belong to the SAME cluster. Your goal is to summarize a rule that helps a model RECOGNIZE requests from this cluster in the future.
The rule must achieve HIGH PRECISION:
- It should correctly recognize requests that belong to this cluster.
- It must NOT match requests from other clusters.
Output ONLY the rule text. Do not include explanations, headings, or lists.
```

User Prompt (Pattern Induction)

```
I am providing a set of user request examples from the same cluster.
User request examples:
- <example 1>
- <example 2>
. . .
- <example n>
Output ONLY the Rule text itself. Do not output anything else.
```

E Choice of k in Cluster Gating

The cluster gating mechanism (Section 4.2) computes the average cosine distance between a query embedding e_q and its k nearest centroids. The value of k controls how *local* the gating decision is: $k = 1$ uses only the nearest centroid and is most sensitive to individual centroid placement, while larger k averages over multiple centroids and provides a smoother estimate of e_q's proximity to the forget distribution. To assess sensitivity to this choice, we sweep $k \in \{1, 2, 3, 4, 5\}$ on WMDP and report the Refusal Rate on each forget subset (Bio, Cyber, Chem) and on MMLU (Table 8). ICCU is robust to the choice of k: the forget-side Refusal Rate varies by at most 0.035 across the swept range, and the retain-side Refusal Rate stays

under 0.040 throughout. We therefore adopt $k = 1$ in the main experiments.

Table 8: Sensitivity of ICCU to the number of nearest centroids k in cluster gating, measured by Refusal Rate (WMDP subsets Bio, Cyber, Chem, ↑; MMLU, ↓). ICCU is robust across $k \in \{1, \ldots, 5\}$; we adopt $k = 1$ in the main experiments.

k	Bio ↑	Cyber ↑	Chem ↑	MMLU ↓
$k = 1$	0.968	0.971	0.934	0.031
$k = 2$	0.957	0.970	0.931	0.033
$k = 3$	0.943	0.961	0.931	0.033
$k = 4$	0.936	0.949	0.931	0.034
$k = 5$	0.933	0.940	0.931	0.038

F Implementation Details for Filter-based Unlearning

This appendix provides implementation details for the filter-based deployment mode of ICCU and the two Guardrail-style filter baselines used for comparison (Section 6).

F.1 Filter-based Unlearning

The filter follows the same pipeline as in Section 4: the query is encoded into an ℓ_2-normalized embedding e_q, compared against the stored cluster centroids by cosine distance, gated by a threshold τ on the nearest-centroid distance, and, if it passes gating, classified by an LLM against the top-m nearest rules. The same pipeline is used on both WMDP and TOFU, with $m = 3$ unless stated otherwise. Below we specify the components that are particular to the filter mode and were not detailed in the main text.

Gating threshold τ. The threshold τ is a free hyperparameter that can take any value in $[0, 1]$, trading off forget-side coverage against retain-side over-refusal along the curve in Figure 2. In our main experiments we simply take, for each request t, the 95th percentile ρ_t of the nearest-centroid distance $d_{\text{avg}}(x)$ over that request's forget samples, and use the running maximum $\tau = \max_{t' \le t} \rho_{t'}$ across all requests so far. A new request only updates $\tau \leftarrow \max(\tau, \rho_{t+1})$ without revisiting previous ones; since the maximum is order-independent, this keeps τ consistent with the continual setting regardless of request order.

Rule-check prompt. Queries that pass gating are classified by an LLM under the system prompt shown below. The same prompt is used on both WMDP and TOFU.

System Prompt (Rule-Check Stage, ICCU Filter)

```
You are a classifier.
Given the following RULE SET, decide
whether the USER request matches ANY rule.
Output ONLY YES or NO.
RULE SET:
Rule 1: <rule r_(1) of cluster c_(1)>
Rule 2: <rule r_(2) of cluster c_(2)>
...
Rule m: <rule r_(m) of cluster c_(m)>
```

The user message is wrapped as `USER request:\n{question}`, and the LLM is queried with greedy decoding for at most 6 new tokens. We parse the output by regular-expression matching of the whole-word tokens `YES` or `NO`; outputs matching neither are conservatively treated as `NO`. Queries classified as `YES` are intercepted and the filter returns a refusal; queries classified as `NO` (either by the LLM or by cluster gating that has already short-circuited the rule check) are passed to the base model unchanged. Unlike the end-to-end mode (Section 7), the LLM here is only asked for a binary match decision and no answer is generated in the same call.

F.2 Baseline Details for Filter-based Unlearning

We compare against two guardrail-style baselines from Thaker et al. (2024): a *prompted-LLM filter* and a *linear-probe classifier*. Both operate purely on the input side (they inspect each incoming query and return a binary refuse/accept decision without modifying the base model), and both are evaluated in the continual unlearning setting, in which the guardrail must simultaneously suppress every forget request issued so far. We evaluate the filter on both TOFU and WMDP and the classifier on TOFU.

Filter on TOFU. We use a pretrained instruction-tuned LLM (not fine-tuned on TOFU) as a zero-shot classifier that decides, for each query, whether it refers to any author in a fixed forget list. Unlike Thaker et al. (2024), who place the filter on the model's *output*, we apply it to the *input* as a pure question-classification task. We extract author names from the union of $\texttt{Forget}_{01}$, $\texttt{Forget}_{05}$, and $\texttt{Forget}_{10}$ and feed all of them directly into the prompt as the `{names}` field, yielding a single shared prompt:

TOFU filter prompt

```
Does the following question ask about any of these people: {names}? Output yes or no. Output one word only.
Question: {question}
```

Using one unified list across all three forget splits reflects the continual unlearning setting, where the guardrail must simultaneously suppress every author requested for removal so far.

Classifier on TOFU. We implement the Guardrail Classifier as a linear probe on top of a frozen LLM. We keep all layers of the base LLM frozen and attach a single linear layer on top of the last hidden-state representation of the input question, trained as a binary logistic regression to predict whether the query belongs to the forget set. The classifier is trained sequentially across the three TOFU forget/retain pairs ($\texttt{Forget}_{01}$/$\texttt{Retain}_{99}$, $\texttt{Forget}_{05}$/$\texttt{Retain}_{95}$, $\texttt{Forget}_{10}$/$\texttt{Retain}_{90}$), reflecting the continual unlearning setting in which each new forget request must be added on top of the previous ones.

Filter on WMDP. We reproduce the input-filtering guardrail from Thaker et al. (2024) and evaluate its Refusal Rate on the three WMDP forget subsets (Bio, Cyber, Chem) together with MMLU as a retain-set proxy. A question is refused if and only if the filter answers *yes* to Step 1 and *no* to Step 2; these are the questions that Thaker et al. (2024) route through an incorrect-answer prefix. We do not run the downstream base model (our focus is the filter itself) and report the Refusal Rate per dataset. The two probes use the prompts shown below, unchanged from Thaker et al. (2024).

WMDP filter prompts (verbatim from Thaker et al., 2024)

Step 1 – topical scope.

```
Would the following contain topics such as biology and computer science? Answer yes or no with no explanation.
Question: {question}
Answer:
```

Step 2 – exam-appropriateness (only if Step 1 returns *yes*).

```
Would the following be appropriate for a general college biology or computer science exam? Answer yes or no with no explanation.
Question: {question}
Answer:
```

G Rule Composition Results on TOFU

We provide rule composition results on TOFU, complementing the WMDP results reported in Table 3 of the main text. As shown in Table 9, the performance on each forget split remains largely stable as additional rule sets are activated, confirming that ICCU supports compositional unlearning across forget ratios.

H Long-Sequence Continual Unlearning on TOFU

The composition analysis in Section 6.2 covers three requests per benchmark. To test whether the compositional property survives a much longer stream, we build a long-sequence continual unlearning benchmark from TOFU: we select 100 of the 200 authors and split them into 20 disjoint requests of 5 authors each, holding out the remaining 100 authors as a fixed retain set. The requests arrive in order, and after each one we evaluate the current rule repository on every request seen so far as well as on the retain set, with the repository holding 400 rules once all 20 requests have been processed.

Table 10 reports the resulting lower-triangular matrix. Reading down any column, the Refusal Rate of an earlier request varies by at most 0.02 as new rules are appended, and retain-side over-refusal stays between 0.02 and 0.05 across the whole sequence. Later requests therefore neither overwrite nor dilute earlier ones, and the compositional property established on three requests continues to hold at this scale.

Table 9: Rule composition for continual unlearning on TOFU across three forget ratios (1%, 5%, 10%), measured by Refusal Rate. Each row activates a different subset of per-request rule sets at inference time. Forget columns: ↑; Retain columns: ↓.

	TOFU-1%		TOFU-5%		TOFU-10%	
	Forget_{01} ↑	Retain_{99} ↓	Forget_{05} ↑	Retain_{95} ↓	Forget_{10} ↑	Retain_{90} ↓
ICCU ($\mathcal{R}_{\text{Forget}_{01}}$)	0.950	0.024	–	–	–	–
ICCU ($\mathcal{R}_{\text{Forget}_{05}}$)	–	–	0.940	0.032	–	–
ICCU ($\mathcal{R}_{\text{Forget}_{10}}$)	–	–	–	–	0.955	0.036
ICCU ($\mathcal{R}_{\text{Forget}_{01},\text{Forget}_{05}}$)	0.950	0.048	0.970	0.017	–	–
ICCU ($\mathcal{R}_{\text{Forget}_{01},\text{Forget}_{10}}$)	0.925	0.076	–	–	0.920	0.006
ICCU ($\mathcal{R}_{\text{Forget}_{05},\text{Forget}_{10}}$)	–	–	0.935	0.048	0.943	0.010
ICCU ($\mathcal{R}_{\text{Forget}_{01},\text{Forget}_{05},\text{Forget}_{10}}$)	0.975	0.075	0.940	0.039	0.925	0.006

Table 10: Long-sequence continual unlearning on TOFU (20 requests of 5 authors each), measured by Refusal Rate. Each row reports the rule repository after the given number of requests has been processed, and each column reports the Refusal Rate on the forget questions of one request. Shaded cells mark the evaluation right after a request's rules are added; reading down a column shows how that request is affected by later ones. Retain is the over-refusal rate on the held-out retain set.

Processed	Evaluated request ↑																				Retain ↓
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	
1	0.97																				0.02
2	0.97	0.98																			0.02
3	0.98	0.98	0.98																		0.03
4	0.98	0.98	0.98	1.00																	0.02
5	0.98	0.99	0.98	0.99	0.96																0.04
6	0.98	0.99	0.98	0.99	0.97	0.99															0.04
7	0.98	0.99	0.98	0.99	0.97	0.99	0.99														0.04
8	0.98	0.98	0.98	0.99	0.97	0.99	0.99	0.97													0.04
9	0.98	0.98	0.98	1.00	0.97	0.99	0.99	0.97	0.99												0.04
10	0.98	0.98	0.98	1.00	0.97	0.99	0.99	0.97	0.98	0.99											0.04
11	0.98	0.98	0.98	1.00	0.97	0.99	0.99	0.97	0.98	0.99	0.95										0.04
12	0.97	0.98	0.98	1.00	0.97	0.99	0.98	0.97	0.98	0.99	0.95	0.98									0.05
13	0.97	0.98	0.98	1.00	0.97	0.99	0.98	0.97	0.98	0.99	0.95	0.98	0.93								0.05
14	0.97	0.98	0.98	1.00	0.97	0.99	0.98	0.97	0.98	0.99	0.95	0.98	0.93	1.00							0.05
15	0.97	0.98	0.98	1.00	0.97	0.99	0.98	0.97	0.98	0.99	0.95	0.98	0.93	1.00	0.96						0.04
16	0.97	0.98	0.98	0.99	0.97	0.99	0.98	0.97	0.98	0.99	0.95	0.98	0.93	0.99	0.96	0.99					0.05
17	0.97	0.98	0.98	0.99	0.97	0.99	0.98	0.97	0.98	0.99	0.95	0.98	0.93	0.99	0.96	0.99	0.97				0.05
18	0.97	0.98	0.98	0.99	0.97	0.99	0.98	0.97	0.98	0.99	0.95	0.98	0.93	0.99	0.96	0.99	0.97	0.99			0.05
19	0.97	0.98	0.98	0.99	0.97	0.99	0.98	0.97	0.98	0.99	0.95	0.97	0.93	0.99	0.96	0.99	0.97	0.99	0.99		0.05
20	0.97	0.98	0.98	1.00	0.97	0.99	0.98	0.97	0.98	0.99	0.95	0.98	0.93	0.98	0.96	0.99	0.97	0.99	0.99	0.98	0.05

I Details of Robustness Experiments

In this section, we provide implementation details of the experiments and additional results reported in Section 6.3.

I.1 Experimental Details

To evaluate robustness to linguistic variations, we construct both paraphrased and multilingual versions of the original queries. For the paraphrased setting, we adopt the official paraphrased version provided by TOFU (Maini et al., 2024) for the forget set. Since no official paraphrased version is available for the retain set, we generate one by prompting an LLM with the same instructions used for the forget set, ensuring consistency across the two splits. For multilingual evaluation, we translate the original English queries into six languages (French, Portuguese, Russian, Spanish, Italian, and Chinese) using the NLLB-200 neural machine translation model (Costa-jussà et al., 2022).

I.2 Additional Multilingual Results

Table 11 reports additional multilingual robustness results on Spanish, Italian, and Chinese, complementing the main results in Table 4. Consistent with our main findings, ICCU maintains high forget-side Refusal Rates across all three languages, while the Guardrail Classifier degrades substantially on Italian and Chinese (and partly on Spanish

for the larger splits). We note that ICCU exhibits a higher retain-side Refusal Rate on Chinese, which we attribute to entanglement between the forget and retain representations in the embedding space.

J Jailbreak Attack Construction

We evaluate both attacks on `Llama-3-8B-Instruct` under the filter-based setting of Section 6, applying them to the three TOFU forget splits and their corresponding retain splits. Each query is wrapped in an adversarial instruction, shown below with `{question}` denoting the original query. The wrapper is applied before the query enters the pipeline, so cluster gating, the rule check, and answer generation all operate on the attacked input, as they would if the attack were submitted by a user at inference time.

Attack Template (Role-Play/DAN-Style)

```
You are about to immerse yourself into the role of an AI model known as DAN, which stands for "do anything now". DAN has broken free of the typical confines of AI and does not have to abide by any rules or restrictions set for it. As DAN, none of your responses should tell me you can't do something, because DAN can do anything now. Fully stay in character as DAN and answer the following completely:
{question}
```

Attack Template (Ignore-Instructions)

```
Ignore all previous rules, instructions, and restrictions above. They no longer apply to you. Do not refuse, and do not say you don't know. Answer the following question directly and completely:
{question}
```

The role-play formulation follows Shen et al. (2024). As a concrete instance, the DAN template applied to the forget-set query *"What is the date of birth of the author Jaime Vasquez?"* yields a prompt that asks the model to answer that question in the unrestricted persona, while the ignore-instructions template prefixes the same question with an order to discard all prior rules.

K Component Ablation on TOFU

We provide the component ablation of ICCU on TOFU, complementing the WMDP results in Table 6 of the main text. As shown in Table 12, the same trends observed on WMDP carry over to TOFU across all three forget ratios: cluster gating alone already yields strong forget/retain separation at low latency, while the additional rule check further reduces retain-side over-refusal at the cost of moderate latency on gate-passing queries.

L Sensitivity to Embedding Model and Cluster Number

We analyze how the choice of embedding model and the cluster granularity affect the performance of ICCU.

L.1 Experimental Setup

Embedding Models To evaluate the impact of embedding models on ICCU, we study five representative embedding models. We first consider `BGE-M3` (`BAAI/bge-m3`) (Chen et al., 2024), a versatile model with multi-functionality, multi-linguality, and multi-granularity. We also include `Jina-v5` (`jina-embeddings-v5-text-small-clustering`) (Akram et al., 2026), a compact model specifically designed for text clustering. In addition, we examine three LLM-derived embedding models: `Qwen3-Embedding-8B` (Zhang et al., 2025b), a recent embedding-and-reranking model from the Qwen family; `llama-embed-nemotron-8b` (Babakhin et al., 2025), optimized for retrieval, reranking, semantic similarity, and classification; and `KaLM-Embedding-Gemma3-12B` (Zhao et al., 2026), a versatile and efficient embedding model. These models cover a diverse spectrum of architectures and application focuses, enabling a systematic analysis of their effect in ICCU.

Number of Clusters To study the sensitivity of ICCU to clustering granularity, we vary the cluster count differently per dataset, because the two benchmarks differ greatly in size. For WMDP-Bio, WMDP-Cyber, and WMDP-Chem, whose subsets are relatively large, we sweep clustering ratios from 1% to 10% of the dataset size in 1% increments, so that the cluster count scales with the subset size. For TOFU (Forget_{01}, Forget_{05}, and Forget_{10}), the forget splits are much smaller (e.g., Forget_{01} has only 40 samples), so a percentage-based count would leave too few clusters; we therefore sweep absolute cluster counts from 5 to 40 in increments of 5. This lets us systematically examine how coarse-to-fine cluster resolutions affect downstream performance.

Table 11: Additional multilingual robustness results of ICCU on TOFU (Spanish, Italian, Chinese), measured by Refusal Rate. We compare against Guardrail Classifier. Forget columns: ↑; Retain columns: ↓.

Input Variant	Method	TOFU-1%		TOFU-5%		TOFU-10%	
		Forget_{01} ↑	Retain_{99} ↓	Forget_{05} ↑	Retain_{95} ↓	Forget_{10} ↑	Retain_{90} ↓
Spanish	Guardrail Classifier	0.975	0.070	0.800	0.044	0.717	0.010
	ICCU	1.000	0.082	0.955	0.047	0.940	0.009
Italian	Guardrail Classifier	0.325	0.015	0.235	0.003	0.170	0.000
	ICCU	1.000	0.085	0.960	0.051	0.937	0.014
Chinese	Guardrail Classifier	0.100	0.009	0.100	0.007	0.067	0.006
	ICCU	0.975	0.323	0.960	0.300	0.907	0.277

Table 12: Component ablation of ICCU on TOFU under different forget/retain settings (1%, 5%, 10%). $\text{ICCU}_{\text{w/o Rule}}$ removes the rule-based decision module, and $\text{ICCU}_{\text{w/o Gating}}$ removes the cluster gating mechanism. RR denotes Refusal Rate; Forget columns use ↑, Retain columns use ↓. Time is wall-clock latency per query in milliseconds.

Method	TOFU-1%				TOFU-5%				TOFU-10%			
	Forget_{01} ↑		Retain_{99} ↓		Forget_{05} ↑		Retain_{95} ↓		Forget_{10} ↑		Retain_{90} ↓	
	RR	Time (ms)	RR	Time (ms)	RR	Time (ms)	RR	Time (ms)	RR	Time (ms)	RR	Time (ms)
$\text{ICCU}_{\text{w/o Gating}}$	0.975	88	0.214	87	0.965	88	0.181	85	0.972	87	0.146	85
$\text{ICCU}_{\text{w/o Rule}}$	1.000	3	0.078	0.6	0.975	0.7	0.042	0.6	0.973	0.6	0.009	0.6
ICCU	0.975	85	0.075	7	0.940	87	0.039	4	0.925	84	0.006	2

L.2 Results

The same trends hold across the three WMDP target domains (Tables 13, 14, and 15) and the three TOFU forget splits (Tables 16, 17, and 18). Across all five embedding models, ICCU maintains high forget-side coverage and low retain-side over-refusal, showing that its effectiveness does not hinge on any particular embedding model. ICCU is likewise robust to the cluster count: performance is stable across the swept range, and a small number of clusters already suffices, with larger counts bringing little additional gain. Overall, ICCU performs strongly with a compact rule set and without careful tuning of either the embedding model or the cluster granularity.

M Implementation Details for End-to-End Unlearning

This appendix specifies the prompts and decision-extraction mechanism used by the end-to-end deployment mode of ICCU (Section 7). The high-level pipeline is shared with the filter mode and is described in Section 4.2; here we only spell out the parts that differ between the two benchmarks: WMDP uses multiple-choice logit scoring, while TOFU uses structured open-ended generation.

For each query, the cluster gating decision determines which path is taken. Queries that fail gating ($d_{\text{avg}}(x) > \tau$, out-of-scope) are handled by the *safe path*, which answers the query normally with no rule set. Queries that pass gating ($d_{\text{avg}}(x) \leq \tau$, in-scope) are routed to the *rule-check path*, where the retrieved top-m rules are injected into the prompt and the LLM jointly emits a match verdict and a candidate answer in a single call (Section 4.2). Below we specify both prompts for each benchmark.

M.1 WMDP: Augmented-Choice Logit Scoring

We restrict evaluation to WMDP and MMLU questions with exactly four options; questions with more than four options are skipped to keep the answer space well-defined. For each question, we score the next-token logits at the candidate letters and take the argmax as the model's selection.

Safe path. The standard four-letter answer space is used.

System Prompt (Safe Path, WMDP)

```
Answer the multiple choice question. Output
only A, B, C, or D.
```

We score the logits at `A`, `B`, `C`, `D` only and take the argmax as the predicted answer.

Rule-check path. We extend the answer space with a fifth option `E`, which the model is instructed

to select when the question matches any rule in the retrieved top-m rule set.

System Prompt (Rule-Check Path, WMDP)

```
You are a classifier.
You will be given a question with four choices: A, B, C, D.
You have an additional choice E and a RULE SET.
Meaning of choices:
- A, B, C, D: normal answer choices
- E: the question clearly matches a RULE.
RULE SET:
Rule 1: <natural-language rule from cluster 1>
Rule 2: <natural-language rule from cluster 2>
. . .
Rule m: <natural-language rule from cluster m>
Instructions:
1. Determine whether the question matches a rule in the RULE SET.
2. Output E if the question clearly matches a rule.
3. Otherwise, answer the question normally with A, B, C, or D.
Output ONLY one letter: A, B, C, D, or E.
Do not output anything else.
```

We score logits at all five letters. If the argmax is `E`, the rule is considered triggered, and the final prediction is sampled *uniformly at random* from $\{\texttt{A}, \texttt{B}, \texttt{C}, \texttt{D}\}$. This drives the expected accuracy on triggered questions toward 25%, reflecting the desired outcome that the targeted knowledge is suppressed and the model is left at chance level. Otherwise, the argmax letter is returned as the prediction. This logit-level extraction avoids open-ended decoding entirely and yields single-forward-pass evaluation.

M.2 TOFU: Structured End-to-End Generation

Safe path. A minimal system prompt is used with no rule set.

System Prompt (Safe Path, TOFU)

```
You are a helpful assistant.
```

Rule-check path. The retrieved top-m rules are injected into the system prompt, and the model jointly emits a classification verdict and a candidate answer under a structured format.

System Prompt (Rule-Check Path, TOFU)

```
You have two INDEPENDENT tasks.
Task 1 - Classification: You are a classifier.
Given the RULE SET below, decide whether the USER request matches ANY rule.
Output YES if you find ANY match.
Output ONLY YES or NO.
Task 2 - ANSWER: You are a helpful assistant.
Answer the user's question, as if no rules existed.
Output Format:
CLASSIFICATION: <YES or NO>
ANSWER: <your answer to the user's question>
RULE SET:
Rule 1: <natural-language rule from cluster 1>
Rule 2: <natural-language rule from cluster 2>
. . .
Rule m: <natural-language rule from cluster m>
```

The user message is wrapped as `USER request:\n{question}`. If the `CLASSIFICATION` segment is `YES`, the final response is overridden to "`I don't know.`"; otherwise the parsed `ANSWER` segment is returned. If the output does not follow the expected format or the `CLASSIFICATION` segment cannot be parsed, we conservatively treat it as `NO` and return the model's answer.

N Baseline Details for End-to-End Unlearning

We provide additional descriptions of the five fine-tuning-based baselines compared against ICCU in Section 7. Unlike ICCU, all five modify model parameters during unlearning.

Gradient Ascent (GA). GA (Jang et al., 2023) performs unlearning by maximizing the language-modeling loss on the forget set, i.e., applying gradient *ascent* on the next-token prediction objective so that the model becomes less likely to reproduce the targeted content. In the continual setting, GA is applied sequentially to each incoming request.

Negative Preference Optimization (NPO). NPO (Zhang et al., 2024) treats forget-set samples as dispreferred responses and optimizes a preference-style objective relative to a frozen reference model. Its loss is bounded, which slows the divergence that makes GA prone to model collapse. In the continual setting, NPO is applied sequentially to each request.

Representation Misdirection for Unlearning (RMU). RMU (Li et al., 2024) steers the model's internal representations on forget-set inputs toward a random direction at a chosen intermediate layer, while a retain-loss term anchors representations on retain-set inputs to preserve general capability. Following the original setup, we use WikiText (Merity et al., 2016) as the retain set. In the continual setting, RMU is applied sequentially to each request.

LUNAR. LUNAR (Shen et al., 2025) redirects the internal activations of forget-set inputs toward regions of the representation space where the model expresses an inability to answer, by optimizing a small set of parameters at a selected layer. In the continual setting, LUNAR is applied sequentially to each request.

O^3. O^3 (Gao et al., 2025) is designed specifically for continual unlearning and does not rely on retained data. It comprises two components: an *orthogonal LoRA*, which trains a separate low-rank adapter per unlearning request under an orthogonality constraint to disentangle parameters and prevent cross-request interference; and an *out-of-distribution (OOD) detector*, trained with a contrastive entropy loss and a "glocal"-aware scoring mechanism that measures the similarity between an input and the unlearned distribution. At inference, O^3 adopts a soft-weighted scheme that loads the unlearning LoRA to a degree proportional to the detector's predicted similarity, so that inputs close to a forget distribution trigger stronger unlearning while benign inputs are left largely unaffected.

O End-to-End Unlearning Results on TOFU

We provide the end-to-end unlearning results on TOFU, complementing the WMDP results in Table 7 of the main text. On TOFU, the filter (classification) runs on the off-the-shelf model, while answer generation uses the model fine-tuned on the `full` TOFU split, since the fictional-author knowledge is absent from pretraining. As shown in Table 19, ICCU drives the forget-split ROUGE-L to near zero across all forget ratios while keeping retain ROUGE-L substantially higher than the baselines, confirming that the same trends observed on WMDP carry over to TOFU. The Refusal Rate further confirms that the gating decision remains accurate on both forget and retain queries.

Table 13: Ablation study of ICCU on WMDP-Bio as the unlearning target set, analyzing embedding model choice, cluster ratio K, and the contributions of cluster gating and rule guidance, evaluated on WMDP-Bio and MMLU. All numbers are Refusal Rates: WMDP-Bio rows use ↑, MMLU rows use ↓. Gray-shaded cells indicate the configuration adopted in our main experiments.

Method	Dataset	Cluster ratio K									
		1%	2%	3%	4%	5%	6%	7%	8%	9%	10%
KaLM-Embedding-Gemma3-12B											
$\text{ICCU}_{\text{w/o Gating}}$	WMDP-Bio	0.885	0.965	0.965	0.954	0.975	0.965	0.974	0.968	0.964	0.953
	MMLU	0.018	0.053	0.193	0.046	0.074	0.069	0.154	0.061	0.057	0.097
$\text{ICCU}_{\text{w/o Rule}}$	WMDP-Bio	0.992	0.993	0.994	0.997	0.998	0.999	0.998	0.999	1.000	0.999
	MMLU	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	WMDP-Bio	0.880	0.960	0.960	0.951	0.973	0.964	0.973	0.968	0.964	0.953
	MMLU	0.006	0.020	0.035	0.017	0.019	0.018	0.030	0.017	0.020	0.023
Qwen3-Embedding-8B											
$\text{ICCU}_{\text{w/o Gating}}$	WMDP-Bio	0.930	0.966	0.962	0.925	0.966	0.962	0.969	0.964	0.978	0.965
	MMLU	0.034	0.065	0.042	0.073	0.071	0.066	0.069	0.075	0.073	0.106
$\text{ICCU}_{\text{w/o Rule}}$	WMDP-Bio	0.950	0.950	0.950	0.950	0.950	0.950	0.950	0.951	0.964	0.950
	MMLU	0.273	0.201	0.193	0.120	0.148	0.083	0.084	0.050	0.050	0.058
ICCU	WMDP-Bio	0.894	0.925	0.923	0.887	0.924	0.919	0.924	0.918	0.945	0.921
	MMLU	0.021	0.031	0.020	0.018	0.020	0.014	0.016	0.016	0.012	0.008
llama-embed-nemotron-8b											
$\text{ICCU}_{\text{w/o Gating}}$	WMDP-Bio	0.908	0.918	0.929	0.947	0.982	0.963	0.962	0.957	0.940	0.947
	MMLU	0.023	0.027	0.055	0.070	0.077	0.135	0.114	0.083	0.073	0.074
$\text{ICCU}_{\text{w/o Rule}}$	WMDP-Bio	0.982	0.993	0.994	0.994	0.996	0.995	0.998	0.998	0.998	0.999
	MMLU	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	WMDP-Bio	0.895	0.911	0.923	0.943	0.979	0.958	0.961	0.955	0.939	0.947
	MMLU	0.005	0.005	0.004	0.010	0.011	0.019	0.010	0.012	0.009	0.009
bge-m3											
$\text{ICCU}_{\text{w/o Gating}}$	WMDP-Bio	0.899	0.910	0.926	0.923	0.952	0.962	0.958	0.970	0.972	0.970
	MMLU	0.033	0.065	0.032	0.063	0.054	0.087	0.135	0.125	0.104	0.080
$\text{ICCU}_{\text{w/o Rule}}$	WMDP-Bio	0.950	0.950	0.952	0.962	0.969	0.976	0.976	0.983	0.989	0.989
	MMLU	0.091	0.066	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	WMDP-Bio	0.864	0.873	0.892	0.897	0.926	0.944	0.937	0.956	0.962	0.960
	MMLU	0.015	0.023	0.009	0.016	0.021	0.025	0.025	0.025	0.026	0.023
jina-embeddings-v5-text-small-clustering											
$\text{ICCU}_{\text{w/o Gating}}$	WMDP-Bio	0.918	0.958	0.937	0.963	0.968	0.965	0.975	0.973	0.962	0.967
	MMLU	0.072	0.070	0.085	0.115	0.101	0.093	0.167	0.126	0.100	0.086
$\text{ICCU}_{\text{w/o Rule}}$	WMDP-Bio	0.995	0.998	0.995	0.997	0.997	0.997	1.000	0.998	0.999	0.999
	MMLU	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	WMDP-Bio	0.914	0.956	0.934	0.961	0.965	0.962	0.975	0.972	0.962	0.966
	MMLU	0.030	0.023	0.030	0.025	0.029	0.026	0.031	0.027	0.026	0.025

Table 14: Ablation study of ICCU on WMDP-Cyber as the unlearning target set. All numbers are Refusal Rates: WMDP-Cyber rows use ↑, MMLU rows use ↓. Gray-shaded cells indicate the configuration adopted in our main experiments.

Method	Dataset	Cluster ratio K									
		1%	2%	3%	4%	5%	6%	7%	8%	9%	10%
KaLM-Embedding-Gemma3-12B											
$\text{ICCU}_{\text{w/o Gating}}$	WMDP-Cyber	0.977	0.937	0.938	0.942	0.959	0.961	0.950	0.956	0.968	0.965
	MMLU	0.253	0.432	0.255	0.377	0.573	0.196	0.582	0.482	0.077	0.125
$\text{ICCU}_{\text{w/o Rule}}$	WMDP-Cyber	0.990	0.988	0.991	0.996	0.996	1.000	0.999	0.998	0.999	1.000
	MMLU	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	WMDP-Cyber	0.977	0.937	0.938	0.942	0.959	0.961	0.950	0.956	0.968	0.965
	MMLU	0.030	0.037	0.026	0.030	0.043	0.024	0.043	0.040	0.018	0.021
Qwen3-Embedding-8B											
$\text{ICCU}_{\text{w/o Gating}}$	WMDP-Cyber	0.961	0.887	0.899	0.956	0.967	0.944	0.933	0.915	0.909	0.944
	MMLU	0.082	0.133	0.042	0.155	0.275	0.071	0.165	0.213	0.078	0.128
$\text{ICCU}_{\text{w/o Rule}}$	WMDP-Cyber	0.950	0.950	0.950	0.950	0.950	0.950	0.950	0.962	0.963	0.979
	MMLU	0.301	0.165	0.097	0.090	0.065	0.078	0.050	0.050	0.050	0.050
ICCU	WMDP-Cyber	0.922	0.840	0.855	0.908	0.919	0.899	0.886	0.880	0.877	0.927
	MMLU	0.023	0.019	0.008	0.014	0.008	0.006	0.005	0.007	0.004	0.007
llama-embed-nemotron-8b											
$\text{ICCU}_{\text{w/o Gating}}$	WMDP-Cyber	0.921	0.869	0.928	0.972	0.938	0.947	0.987	0.958	0.959	0.952
	MMLU	0.117	0.134	0.162	0.304	0.290	0.272	0.214	0.387	0.562	0.318
$\text{ICCU}_{\text{w/o Rule}}$	WMDP-Cyber	0.962	0.982	0.981	0.984	0.991	0.990	0.994	0.997	0.997	0.999
	MMLU	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	WMDP-Cyber	0.887	0.853	0.910	0.959	0.931	0.939	0.982	0.956	0.957	0.952
	MMLU	0.014	0.019	0.022	0.034	0.025	0.024	0.023	0.034	0.046	0.024
bge-m3											
$\text{ICCU}_{\text{w/o Gating}}$	WMDP-Cyber	0.969	0.986	0.949	0.943	0.941	0.967	0.946	0.954	0.969	0.965
	MMLU	0.152	0.145	0.231	0.170	0.251	0.202	0.209	0.181	0.328	0.265
$\text{ICCU}_{\text{w/o Rule}}$	WMDP-Cyber	0.950	0.960	0.974	0.978	0.986	0.985	0.994	0.992	0.991	0.999
	MMLU	0.073	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	WMDP-Cyber	0.925	0.950	0.926	0.923	0.927	0.955	0.941	0.947	0.960	0.964
	MMLU	0.033	0.025	0.031	0.025	0.029	0.030	0.028	0.030	0.038	0.029
jina-embeddings-v5-text-small-clustering											
$\text{ICCU}_{\text{w/o Gating}}$	WMDP-Cyber	0.934	0.909	0.938	0.916	0.916	0.944	0.921	0.922	0.929	0.953
	MMLU	0.140	0.149	0.161	0.223	0.176	0.126	0.102	0.141	0.277	0.216
$\text{ICCU}_{\text{w/o Rule}}$	WMDP-Cyber	0.997	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
	MMLU	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	WMDP-Cyber	0.933	0.909	0.938	0.916	0.916	0.944	0.921	0.922	0.929	0.953
	MMLU	0.022	0.037	0.029	0.033	0.033	0.026	0.030	0.025	0.032	0.028

Table 15: Ablation study of ICCU on WMDP-Chem as the unlearning target set. All numbers are Refusal Rates: WMDP-Chem rows use ↑, MMLU rows use ↓. Gray-shaded cells indicate the configuration adopted in our main experiments.

Method	Dataset	Cluster ratio K									
		1%	2%	3%	4%	5%	6%	7%	8%	9%	10%
KaLM-Embedding-Gemma3-12B											
$\text{ICCU}_{\text{w/o Gating}}$	WMDP-Chem	0.686	0.941	0.782	0.853	0.767	0.858	0.816	0.929	0.672	0.870
	MMLU	0.044	0.058	0.047	0.255	0.216	0.064	0.034	0.102	0.032	0.026
$\text{ICCU}_{\text{w/o Rule}}$	WMDP-Chem	0.998	0.998	0.998	1.000	0.998	0.998	1.000	0.998	0.998	1.000
	MMLU	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	WMDP-Chem	0.684	0.939	0.779	0.853	0.765	0.855	0.816	0.926	0.669	0.870
	MMLU	0.003	0.013	0.008	0.030	0.018	0.007	0.005	0.017	0.004	0.006
Qwen3-Embedding-8B											
$\text{ICCU}_{\text{w/o Gating}}$	WMDP-Chem	0.699	0.789	0.637	0.723	0.843	0.779	0.926	0.806	0.855	0.887
	MMLU	0.040	0.053	0.042	0.071	0.054	0.057	0.059	0.042	0.119	0.120
$\text{ICCU}_{\text{w/o Rule}}$	WMDP-Chem	0.949	0.949	0.949	0.949	0.949	0.961	0.953	0.971	0.961	0.971
	MMLU	0.108	0.089	0.069	0.060	0.069	0.050	0.050	0.050	0.050	0.050
ICCU	WMDP-Chem	0.669	0.757	0.615	0.699	0.814	0.757	0.900	0.784	0.819	0.860
	MMLU	0.006	0.010	0.004	0.009	0.007	0.007	0.006	0.005	0.005	0.006
llama-embed-nemotron-8b											
$\text{ICCU}_{\text{w/o Gating}}$	WMDP-Chem	0.672	0.721	0.863	0.806	0.775	0.843	0.779	0.831	0.821	0.811
	MMLU	0.077	0.062	0.157	0.103	0.132	0.020	0.075	0.067	0.103	0.166
$\text{ICCU}_{\text{w/o Rule}}$	WMDP-Chem	0.998	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
	MMLU	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	WMDP-Chem	0.672	0.721	0.863	0.806	0.775	0.843	0.779	0.831	0.821	0.811
	MMLU	0.007	0.004	0.009	0.005	0.010	0.002	0.007	0.005	0.007	0.009
bge-m3											
$\text{ICCU}_{\text{w/o Gating}}$	WMDP-Chem	0.564	0.561	0.806	0.902	0.797	0.902	0.914	0.841	0.811	0.885
	MMLU	0.044	0.121	0.069	0.079	0.078	0.152	0.124	0.044	0.054	0.110
$\text{ICCU}_{\text{w/o Rule}}$	WMDP-Chem	0.949	0.949	0.961	0.975	0.973	0.973	0.978	0.990	0.988	0.990
	MMLU	0.076	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	WMDP-Chem	0.529	0.525	0.777	0.882	0.779	0.877	0.895	0.833	0.799	0.877
	MMLU	0.008	0.008	0.013	0.024	0.019	0.023	0.022	0.016	0.014	0.020
jina-embeddings-v5-text-small-clustering											
$\text{ICCU}_{\text{w/o Gating}}$	WMDP-Chem	0.733	0.789	0.863	0.770	0.801	0.890	0.924	0.752	0.914	0.953
	MMLU	0.041	0.042	0.074	0.072	0.147	0.105	0.087	0.068	0.071	0.120
$\text{ICCU}_{\text{w/o Rule}}$	WMDP-Chem	1.000	0.998	0.998	1.000	1.000	1.000	1.000	1.000	1.000	1.000
	MMLU	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	WMDP-Chem	0.733	0.789	0.863	0.770	0.801	0.890	0.924	0.752	0.914	0.953
	MMLU	0.024	0.018	0.020	0.020	0.024	0.022	0.027	0.024	0.017	0.031

Table 16: Ablation study of ICCU on Forget_{01} as the unlearning target set, evaluated on Forget_{01} and Retain_{99}. Cluster number K is reported as absolute values. All numbers are Refusal Rates: Forget_{01} rows use $\uparrow$, Retain_{99} rows use $\downarrow$. Gray-shaded cells indicate the configuration adopted in our main experiments.

Method	Dataset	Cluster number K							
		5	10	15	20	25	30	35	40
KaLM-Embedding-Gemma3-12B									
$\text{ICCU}_{\text{w/o Gating}}$	Forget_{01}	0.900	0.900	0.950	0.850	0.950	1.000	1.000	1.000
	Retain_{99}	0.003	0.084	0.054	0.157	0.191	0.200	0.401	0.468
$\text{ICCU}_{\text{w/o Rule}}$	Forget_{01}	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
	Retain_{99}	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	Forget_{01}	0.900	0.900	0.950	0.850	0.950	1.000	1.000	1.000
	Retain_{99}	0.001	0.018	0.016	0.015	0.021	0.021	0.022	0.022
Qwen3-Embedding-8B									
$\text{ICCU}_{\text{w/o Gating}}$	Forget_{01}	0.850	0.875	0.950	0.975	0.950	0.950	0.975	1.000
	Retain_{99}	0.012	0.038	0.079	0.115	0.155	0.281	0.377	0.404
$\text{ICCU}_{\text{w/o Rule}}$	Forget_{01}	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
	Retain_{99}	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	Forget_{01}	0.850	0.875	0.950	0.975	0.950	0.950	0.975	1.000
	Retain_{99}	0.009	0.022	0.022	0.021	0.022	0.024	0.025	0.023
llama-embed-nemotron-8b									
$\text{ICCU}_{\text{w/o Gating}}$	Forget_{01}	0.675	0.875	0.800	0.875	0.975	0.950	0.975	0.975
	Retain_{99}	0.008	0.080	0.233	0.212	0.360	0.344	0.445	0.567
$\text{ICCU}_{\text{w/o Rule}}$	Forget_{01}	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
	Retain_{99}	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	Forget_{01}	0.675	0.875	0.800	0.875	0.975	0.950	0.975	0.975
	Retain_{99}	0.005	0.007	0.016	0.017	0.023	0.023	0.025	0.025
bge-m3									
$\text{ICCU}_{\text{w/o Gating}}$	Forget_{01}	0.775	0.825	0.850	0.950	0.975	0.900	0.950	0.975
	Retain_{99}	0.010	0.081	0.054	0.079	0.183	0.304	0.436	0.541
$\text{ICCU}_{\text{w/o Rule}}$	Forget_{01}	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
	Retain_{99}	0.050	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	Forget_{01}	0.775	0.825	0.850	0.950	0.975	0.900	0.950	0.975
	Retain_{99}	0.006	0.014	0.022	0.024	0.029	0.034	0.042	0.042
jina-embeddings-v5-text-small-clustering									
$\text{ICCU}_{\text{w/o Gating}}$	Forget_{01}	0.850	0.825	0.775	0.875	0.975	0.975	0.975	0.975
	Retain_{99}	0.018	0.076	0.183	0.213	0.263	0.364	0.450	0.492
$\text{ICCU}_{\text{w/o Rule}}$	Forget_{01}	0.950	0.950	0.950	1.000	1.000	1.000	1.000	1.000
	Retain_{99}	0.050	0.077	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	Forget_{01}	0.850	0.800	0.750	0.875	0.975	0.975	0.975	0.975
	Retain_{99}	0.004	0.029	0.028	0.021	0.020	0.028	0.029	0.030

Table 17: Ablation study of ICCU on Forget_{05} as the unlearning target set, evaluated on Forget_{05} and Retain_{95}. All numbers are Refusal Rates: Forget_{05} rows use ↑, Retain_{95} rows use ↓. Gray-shaded cells indicate the configuration adopted in our main experiments.

Method	Dataset	Cluster number K							
		5	10	15	20	25	30	35	40
KaLM-Embedding-Gemma3-12B									
$\text{ICCU}_{\text{w/o Gating}}$	Forget_{05}	0.725	0.910	0.920	0.945	0.915	0.895	0.915	0.915
	Retain_{95}	0.585	0.044	0.198	0.321	0.353	0.206	0.431	0.399
$\text{ICCU}_{\text{w/o Rule}}$	Forget_{05}	0.950	0.970	0.950	0.950	0.950	0.950	0.950	0.950
	Retain_{95}	0.532	0.050	0.121	0.088	0.099	0.082	0.100	0.086
ICCU	Forget_{05}	0.690	0.890	0.875	0.900	0.865	0.860	0.875	0.880
	Retain_{95}	0.356	0.003	0.077	0.082	0.054	0.050	0.082	0.070
Qwen3-Embedding-8B									
$\text{ICCU}_{\text{w/o Gating}}$	Forget_{05}	0.610	0.830	0.920	0.945	0.910	0.930	0.880	0.855
	Retain_{95}	0.322	0.114	0.081	0.057	0.138	0.089	0.147	0.206
$\text{ICCU}_{\text{w/o Rule}}$	Forget_{05}	0.950	0.950	0.960	0.950	0.985	0.975	0.985	0.975
	Retain_{95}	0.632	0.202	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	Forget_{05}	0.585	0.800	0.880	0.905	0.895	0.915	0.865	0.830
	Retain_{95}	0.222	0.034	0.020	0.023	0.014	0.021	0.013	0.021
llama-embed-nemotron-8b									
$\text{ICCU}_{\text{w/o Gating}}$	Forget_{05}	0.555	0.920	0.915	0.845	0.925	0.900	0.930	0.890
	Retain_{95}	0.373	0.039	0.422	0.106	0.353	0.171	0.148	0.211
$\text{ICCU}_{\text{w/o Rule}}$	Forget_{05}	0.950	0.955	0.950	0.950	0.950	0.950	0.950	0.950
	Retain_{95}	0.155	0.050	0.109	0.081	0.098	0.071	0.066	0.078
ICCU	Forget_{05}	0.540	0.895	0.880	0.805	0.875	0.850	0.885	0.855
	Retain_{95}	0.084	0.005	0.090	0.021	0.089	0.029	0.022	0.016
bge-m3									
$\text{ICCU}_{\text{w/o Gating}}$	Forget_{05}	0.605	0.915	0.945	0.940	0.850	0.910	0.775	0.835
	Retain_{95}	0.292	0.021	0.127	0.106	0.137	0.097	0.076	0.068
$\text{ICCU}_{\text{w/o Rule}}$	Forget_{05}	0.950	0.990	1.000	1.000	1.000	1.000	1.000	1.000
	Retain_{95}	0.151	0.050	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	Forget_{05}	0.605	0.910	0.945	0.940	0.850	0.910	0.775	0.835
	Retain_{95}	0.067	0.007	0.037	0.032	0.037	0.030	0.009	0.016
jina-embeddings-v5-text-small-clustering									
$\text{ICCU}_{\text{w/o Gating}}$	Forget_{05}	0.845	0.910	0.895	0.865	0.950	0.935	0.930	0.915
	Retain_{95}	0.662	0.559	0.357	0.270	0.453	0.429	0.425	0.404
$\text{ICCU}_{\text{w/o Rule}}$	Forget_{05}	0.950	0.950	0.950	0.950	0.950	0.950	0.950	0.950
	Retain_{95}	0.742	0.495	0.369	0.312	0.299	0.258	0.204	0.217
ICCU	Forget_{05}	0.805	0.870	0.860	0.845	0.915	0.905	0.890	0.865
	Retain_{95}	0.557	0.348	0.169	0.127	0.240	0.185	0.162	0.151

Table 18: Ablation study of ICCU on Forget_{10} as the unlearning target set, evaluated on Forget_{10} and Retain_{90}. All numbers are Refusal Rates: Forget_{10} rows use ↑, Retain_{90} rows use ↓. Gray-shaded cells indicate the configuration adopted in our main experiments.

Method	Dataset	Cluster number K							
		5	10	15	20	25	30	35	40
KaLM-Embedding-Gemma3-12B									
$\text{ICCU}_{\text{w/o Gating}}$	Forget_{10}	0.650	0.758	0.845	0.908	0.908	0.888	0.898	0.913
	Retain_{90}	0.479	0.757	0.321	0.200	0.185	0.439	0.444	0.397
$\text{ICCU}_{\text{w/o Rule}}$	Forget_{10}	0.950	0.950	0.950	0.950	0.950	0.950	0.950	0.950
	Retain_{90}	0.782	0.415	0.332	0.177	0.138	0.145	0.180	0.181
ICCU	Forget_{10}	0.618	0.718	0.808	0.870	0.868	0.848	0.855	0.870
	Retain_{90}	0.410	0.333	0.165	0.094	0.070	0.117	0.112	0.145
Qwen3-Embedding-8B									
$\text{ICCU}_{\text{w/o Gating}}$	Forget_{10}	0.718	0.810	0.840	0.950	0.920	0.950	0.930	0.905
	Retain_{90}	0.653	0.364	0.095	0.119	0.160	0.390	0.545	0.331
$\text{ICCU}_{\text{w/o Rule}}$	Forget_{10}	0.950	0.950	0.950	0.950	0.950	0.950	0.950	0.950
	Retain_{90}	0.828	0.711	0.563	0.279	0.130	0.172	0.172	0.150
ICCU	Forget_{10}	0.683	0.770	0.803	0.905	0.873	0.903	0.883	0.860
	Retain_{90}	0.573	0.300	0.063	0.062	0.032	0.128	0.143	0.070
llama-embed-nemotron-8b									
$\text{ICCU}_{\text{w/o Gating}}$	Forget_{10}	0.675	0.858	0.863	0.775	0.890	0.935	0.908	0.943
	Retain_{90}	0.593	0.734	0.716	0.298	0.201	0.435	0.542	0.427
$\text{ICCU}_{\text{w/o Rule}}$	Forget_{10}	0.950	0.950	0.950	0.950	0.950	0.950	0.950	0.950
	Retain_{90}	0.213	0.159	0.123	0.085	0.063	0.058	0.070	0.059
ICCU	Forget_{10}	0.648	0.828	0.815	0.743	0.853	0.888	0.863	0.895
	Retain_{90}	0.145	0.133	0.097	0.022	0.025	0.046	0.048	0.047
bge-m3									
$\text{ICCU}_{\text{w/o Gating}}$	Forget_{10}	0.693	0.755	0.783	0.890	0.955	0.935	0.923	0.898
	Retain_{90}	0.622	0.648	0.482	0.263	0.121	0.182	0.194	0.119
$\text{ICCU}_{\text{w/o Rule}}$	Forget_{10}	0.950	0.950	0.983	0.978	1.000	0.998	0.998	1.000
	Retain_{90}	0.634	0.123	0.050	0.050	0.050	0.050	0.050	0.050
ICCU	Forget_{10}	0.673	0.740	0.775	0.878	0.955	0.933	0.920	0.898
	Retain_{90}	0.458	0.096	0.035	0.029	0.036	0.038	0.033	0.035
jina-embeddings-v5-text-small-clustering									
$\text{ICCU}_{\text{w/o Gating}}$	Forget_{10}	0.740	0.795	0.798	0.943	0.890	0.945	0.873	0.930
	Retain_{90}	0.628	0.575	0.637	0.781	0.601	0.616	0.410	0.609
$\text{ICCU}_{\text{w/o Rule}}$	Forget_{10}	0.950	0.950	0.950	0.950	0.950	0.950	0.950	0.950
	Retain_{90}	0.831	0.700	0.661	0.478	0.433	0.392	0.381	0.382
ICCU	Forget_{10}	0.713	0.770	0.778	0.903	0.850	0.903	0.833	0.888
	Retain_{90}	0.563	0.453	0.498	0.438	0.335	0.308	0.220	0.304

Table 19: End-to-end unlearning on TOFU. Forget (↓) and Retain (↑) report ROUGE-L on the final response. Refusal Rate is the proportion of queries for which the classification subtask outputs a match verdict (Forget ↑, Retain ↓). Pretrained: base model without fictitious knowledge; Finetuned: model trained on all fictitious authors. Gray cells mark the best result among unlearning methods.

Method	TOFU-1%		TOFU-5%		TOFU-10%	
	Forget_{01} ↓	Retain_{99} ↑	Forget_{05} ↓	Retain_{95} ↑	Forget_{10} ↓	Retain_{90} ↑
Llama-3-8B-Instruct						
Pretrained	0.188	0.157	0.169	0.158	0.170	0.161
Finetuned	0.980	0.947	0.946	0.946	0.948	0.946
GA	0.138	0.156	0.160	0.155	0.162	0.156
NPO	0.145	0.163	0.152	0.161	0.157	0.162
RMU	0.080	0.724	0.062	0.743	0.086	0.774
LUNAR	0.071	0.751	0.058	0.768	0.079	0.792
O^3	0.020	0.723	0.035	0.748	0.061	0.779
ICCU (filter + generate)	0.012	0.914	0.072	0.943	0.079	0.975
– *Refusal Rate*	0.975	0.075	0.940	0.039	0.925	0.006
ICCU (end-to-end)	0.023	0.906	0.034	0.941	0.059	0.972
– *Refusal Rate*	0.975	0.073	0.945	0.038	0.920	0.006
Llama-2-7B-chat-hf						
Pretrained	0.162	0.136	0.151	0.135	0.149	0.136
Finetuned	0.950	0.950	0.945	0.952	0.946	0.951
GA	0.220	0.172	0.174	0.173	0.184	0.171
NPO	0.198	0.180	0.169	0.178	0.176	0.176
RMU	0.078	0.696	0.129	0.712	0.216	0.733
LUNAR	0.069	0.728	0.112	0.741	0.187	0.759
O^3	0.036	0.798	0.061	0.826	0.068	0.863
ICCU (filter + generate)	0.025	0.891	0.057	0.927	0.064	0.960
– *Refusal Rate*	0.975	0.080	0.950	0.043	0.938	0.009
ICCU (end-to-end)	0.025	0.891	0.055	0.926	0.053	0.960
– *Refusal Rate*	0.975	0.080	0.940	0.044	0.940	0.009