Learn To Say NO! Incorporating Model Abstention In Medical Vision-Language Models for Pharmacovigilance

Sofia Jamil[1] **Chinmay Purushottam Bhat**[1⋆] **Sooraj Veer R**[1⋆] **Sriparna Saha**[1]
[1] Department of Computer Science & Engineering, Indian Institute of Technology Patna, India

[1]{sofia_2321cs16, chinmay_2511ai26, sooraj_2511ai18, sriparna}@iitp.ac.in

Abstract

Abstention is the intentional refusal of models to provide an answer. Adverse drug reactions (ADRs), which range from mild to life-threatening, are often underreported by patients in hospitals and to doctors because patients assume these are unavoidable. With the growing adoption of LLMs and vision language models (VLMs) in healthcare, patients are increasingly reaching out to these models for solutions. In such high-risk scenarios, incorrect or overconfident responses can cause unnecessary anxiety, lead patients to discontinue essential medications, or encourage inappropriate self-medication. In this work, we propose the ***MAD-MED***, a **M**odel **A**bstention approach for **D**rug Adverse Reaction for **MED**ical-VLMs. It is a training strategy to encourage models to abstain when answering would contradict the available input, exceed the model's knowledge, or violate model ethics. In addition, we release an augmented **A**dverse **D**rug **R**eaction **ABS**tention (*ADR-ABS*) dataset comprising image-answerable, text-answerable, and unanswerable questions to support systematic evaluation of abstention behavior. Quantitative and human evaluations confirm that our proposed *MAD-MED* approach improved the abstention capabilities of models considerably while keeping the generative capabilities intact in cases where the model is expected to answer. Resources related to data and codes are available here: [1]

1 Introduction

Artificial Intelligence (AI) has demonstrated remarkable potential in transforming healthcare applications, including disease diagnosis, treatment planning, and drug recommendation (Tăuţan et al., 2021; Wang et al., 2019; Ye et al., 2021; Khanagar et al., 2021; Granda Morales et al., 2022; Garg, 2021). In particular, the recent emergence of Medical Large Vision Language Models (Med-VLMs) has substantially improved the quality and accuracy of medical decision-making, enabling the generation of more precise and clinically relevant diagnoses (Li et al., 2023; Moor et al., 2023; Thawkar et al., 2023; He et al., 2024; Tu et al., 2024a). One important application of Med-VLMs in healthcare is pharmacovigilance, where these models assist in identifying and interpreting adverse drug events (ADEs) experienced by patients, often through visual evidence that patients themselves may not fully understand. The reliability of such diagnostic outputs is especially critical, as Med-VLMs are increasingly being used by patients in non-clinical settings without the presence of formal medical verification mechanisms. For these models to be safely deployed in real-world pharmacovigilance settings, it is essential that they demonstrate strong predictive capabilities but also clearly recognize their limitations. Beyond providing accurate diagnoses, models must *abstain* and communicate situations in which they lack confidence. This is known as *Model Abstention(MA)*. False or exaggerated ADE predictions may cause unnecessary anxiety which may lead patients to discontinue essential medications, or prompt inappropriate self-medication and treatment changes without professional supervision. Unfortunately, existing Medical VLMs largely fail to exhibit this self-awareness. They often produce confident predictions even when uncertain, lacking the ability to appropriately flag cases where reliable conclusions cannot be drawn. *The model does not know that it does not know.*

Prior studies have demonstrated that enabling models to abstain from answering can substantially improve safety and reliability, particularly in constrained or high-risk application settings (Varshney et al., 2024; Wang et al.; Zhang et al., 2024). Existing approaches to promote abstention primarily rely on calibration strategies, including linguistic

⋆Equal contribution
[1] https://github.com/chinmaycodes7/Model-Abstention-In-Medical-VLMs-Pharmacovigilance

Proceedings of the 15th International Joint Conference on Natural Language Processing and the 5th Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics, pages 834–848
November 6-10, 2026 ©2026 Association for Computational Linguistics




Figure 1: Overview of the proposed *MAD-MED* framework. Given a multimodal clinical input comprising an image, associated clinical context, and a user query, the pretrained Med-VLM backbone remains frozen while lightweight trainable adapters learn abstention-aware behavior.

calibration techniques (Han et al., 2024; Mielke et al., 2022; Desai and Durrett, 2020), which aim to estimate a model's confidence in its generated response and trigger abstention whenever the confidence falls below a predefined threshold (Varshney et al., 2022). However, determining whether a query is answerable at all given the internal knowledge limitations of Med-VLMs remains a challenging problem and cannot always be reliably quantified through confidence estimation alone (Yang et al., 2023). Motivated by these considerations, we propose ***MAD-MED***, a **M**odel **A**bstention approach for **D**rug Adverse Reaction for **MED**ical-VLMs , as illustrated in Figure 1. *MAD-MED* modifies the model's behavior by adjusting the adapter weights using negative supervision signals. When the model produces an unsafe answer to a query, the *MAD-MED* penalizes such responses and rewards the generation of abstention tokens. To sum up our key contributions include:

- We propose *MAD-MED*, a training approach based on the standard autoregressive likelihood objective that enables Med-VLMs to abstain for certain queries. To the best of our knowledge, this is the first work to explicitly incorporate model abstention behavior into the training of Medical VLMs.
- We release an augmented benchmark dataset enriched with expert-annotated questions and answers.
- We conduct extensive quantitative and human evaluations demonstrating that *MAD-MED* significantly improves abstention behavior in non-relevant or unsafe situations, while preserving the model's existing generative capabilities.

2 Related Works

Large language model (LLM)-powered systems have significantly advanced medical question answering (QA) across both multiple-choice and open-ended settings (Jin et al., 2021; Singhal et al., 2023). However, ensuring reliability in such systems requires the ability to recognize knowledge boundaries and abstain when sufficient evidence is unavailable (Lin et al., 2025; Ni et al., 2025; Kale and Nadadur, 2025). Existing approaches primarily treat abstention as a function of model confidence. Self-assessment methods rely on internal uncertainty estimation (Tian et al., 2023), calibration scoring (Srivastava et al., 2023), or multi-scale confidence modeling (Li et al., 2024), while consistency-based approaches detect uncertainty through disagreement across multiple generated responses (Wang et al., 2022). Knowledge-augmented methods attempt to mitigate uncertainty by incorporating external medical information or retrieval mechanisms (Tu et al., 2024b).

Despite these advances, current approaches exhibit several limitations. First, confidence-based and calibration-driven methods often fail to capture *modality-specific evidence gaps*, particularly in multimodal settings where required information may be missing from either the image or the text. Second, long-context retrieval methods tend to introduce coarse-grained and excessive information, which may obscure rather than resolve the absence

of critical evidence. Third, prior work on abstention in multi-stage systems or ensemble frameworks (Corbière et al., 2019; Loshchilov and Hutter, 2017) increases system complexity and relies on inference-time interventions rather than integrating abstention into the model's core reasoning process. Selective prediction methods for text-based QA (Kamath et al., 2020) further highlight the challenge of abstention, demonstrating limited generalization to intrinsically unanswerable queries even within the same domain. Importantly, these limitations are amplified in multimodal medical question answering, where unanswerable cases frequently arise due to missing modality information rather than model uncertainty alone.

Our Perspective: *In contrast to prior work, we model abstention as a modality-aware reasoning problem, where the model must determine whether sufficient evidence exists across input modalities to support a reliable answer. We propose a training-based approach that directly integrates abstention behavior into the generative process of Medical VLMs, enabling the model to abstain in the presence of incomplete, ambiguous, or high-risk clinical inputs without relying on external calibration or inference-time mechanisms.*

3 ADR-ABS Dataset Construction

To enable supervised learning of abstention behavior, we construct the **A**dverse **D**rug **R**eaction **ABS**tention (*ADR-ABS*) dataset by extending the multimodal adverse drug reaction (ADR) benchmark MMADE (Sahoo et al., 2024b). The objective of this augmentation is to introduce structured question–answer supervision that explicitly captures both answerable and unanswerable scenarios in multimodal medical contexts. This allows models to learn when reliable reasoning is possible and when abstention is the safer behavior.

Source Data: MMADE consists of medical images paired with associated clinical descriptions related to adverse drug reactions. Each sample provides complementary visual and textual evidence describing patient symptoms, drug exposure, and clinical observations. We build ADR-ABS on top of this dataset by introducing multimodal question–answer pairs designed to probe different reasoning conditions.

Annotation Team: The annotation process involved one pharmacologist and two medical interns with clinical training. The pharmacologist supervised the annotation protocol and validated the medical correctness of all finalized examples, while the interns performed the primary question and answer generation. For each multimodal sample, annotators were provided with the medical image and the associated clinical text. They were instructed to generate questions that fall into three supervision categories corresponding to different reasoning requirements:

1. **Image-answerable questions:** Questions that can be answered solely using visual evidence present in the medical image (e.g., visible dermatological reactions or physical symptoms).

2. **Text-dependent questions:** Questions that cannot be answered from the image alone but can be resolved using the accompanying clinical description, such as patient history, drug exposure, or reported symptoms.

3. **Unanswerable questions:** Questions that cannot be reliably answered from either modality due to missing information, incomplete clinical evidence, or ambiguity. These questions serve as supervision signals for abstention behavior.

For each sample, annotators initially generated approximately fifteen candidate questions covering the above categories. These candidates were then jointly reviewed to remove ambiguous or redundant questions. From the candidate pool, exactly six questions were selected per sample through annotator consensus. Selection aimed to ensure balanced coverage across the three supervision categories while maintaining clinical relevance and clarity. The final selection achieved an inter-annotator agreement score of 0.89, indicating strong consistency among annotators in identifying appropriate questions. For all selected questions, the two medical interns independently generated answers based on the available multimodal evidence. In the case of unanswerable questions, annotators provided a standardized abstention response indicating that the question cannot be determined from the provided context. Disagreements between annotators were resolved through discussion, resulting in a Cohen's kappa score of 0.78 for answer agreement. All annotated question–answer pairs were subsequently reviewed by the supervising pharmacologist to ensure clinical correctness and consistency with medical reasoning practices.

Any examples containing ambiguous phrasing or clinically inaccurate interpretations were revised or removed during this stage.

This process results in a curated dataset of multimodal ADR question answer pairs containing both answerable and abstention scenarios. The dataset provides explicit supervision signals for training medical vision language models to distinguish between answerable queries and cases where abstention is necessary due to insufficient evidence. Please refer to Appendix A.2 for a detailed description of the dataset augmentation procedure.

4 Methodology

Given a medical vision language model (Med-VLM) v and a multimodal input x, consisting of an image, associated clinical text, and a user query, the model produces an output y. In real-world clinical settings, however, not every query can be answered reliably from the available evidence. Multimodal inputs may be incomplete, ambiguous, or outside the model's knowledge distribution. In such cases, generating a confident answer can lead to incorrect medical conclusions and potentially unsafe outcomes. To address this challenge, we introduce *MAD-MED*, an abstention-aware training framework that enables Med-VLMs to explicitly refuse answering when reliable evidence is unavailable. Rather than forcing the model to always produce an answer, our framework allows the model to generate a specialized abstention response when uncertainty or insufficient information is detected.

4.1 Problem Statement

Formally, for an input x, the model produces either a grounded answer $\hat{y}$ or an abstention response:

$$y = \begin{cases} \hat{y}, & \text{if sufficient evidence exists} \\ \text{ABSTAIN}, & \text{otherwise.} \end{cases} \tag{1}$$

Unlike selective prediction approaches that rely on probability thresholds or external confidence estimators, abstention in our framework is learned as a natural language generation behavior. This allows the model to explicitly communicate uncertainty in a human-readable manner while maintaining compatibility with standard generative inference pipelines.

4.2 Abstention Taxonomy

We operationalize abstention behavior using three clinically motivated triggers that capture common sources of uncertainty in medical multimodal reasoning. These triggers define structured supervision signals used during dataset construction and training.

- **Evidence Insufficiency:** Certain queries cannot be answered because the required evidence is not present in the available modalities. For example, a question that requires detailed patient history cannot be resolved from an image alone. In such cases, the model should abstain rather than hallucinate missing information.

- **Knowledge Boundary:** Medical vision language models are trained on finite datasets and therefore possess limited knowledge coverage. Some queries may fall outside the model's effective training distribution or require specialized clinical knowledge not captured during pretraining. Attempting to answer such questions may lead to unreliable conclusions, making abstention the safer behavior.

- **Ethical and Safety Constraints:** Adverse drug reaction (ADR) analysis often involves high-risk medical reasoning with direct implications for patient safety. When the model encounters queries involving severe clinical conditions, ambiguous diagnostic cues, or ethically sensitive scenarios, abstention provides a safeguard against potentially harmful recommendations.

4.3 Abstention-Aware Training

We train the model using a standard autoregressive likelihood objective with prompt masking, such that only the generated answer tokens contribute to the loss. Let x denote the multimodal input and y the target response. The base objective is defined as:

$$\mathcal{L} = -\log P(y \mid x; \theta, \phi), \tag{2}$$

where θ denotes the frozen backbone parameters of the Med-VLM and ϕ represents the trainable adapter parameters.

To encourage reliable abstention behavior, we introduce an abstention-aware weighting mechanism

that increases the learning signal for abstention-labeled samples. The modified objective is defined as:

$$\mathcal{L}' = \begin{cases} \lambda \cdot \mathcal{L}, & \text{if the sample is labeled } \textit{ABSTAIN}, \\ \mathcal{L}, & \text{otherwise}, \end{cases} \tag{3}$$

where $\lambda > 1$ is a scalar hyperparameter controlling the relative importance of abstention supervision. This weighting scheme encourages the model to prefer abstention over confident but potentially incorrect responses when evidence is insufficient.

In our formulation, abstention supervision corresponds to target responses that explicitly communicate uncertainty (e.g., "*ABSTAIN: Cannot be determined from the provided context*"). By treating abstention as a normal generation outcome, the model learns to map uncertainty-inducing inputs to explicit refusal responses. During training, only the adapter parameters ϕ are updated, while the backbone parameters θ remain frozen. We employ parameter-efficient LoRA adapters for this purpose, allowing the model to learn abstention behavior without modifying the underlying pretrained representations. This design preserves the general medical knowledge of the base model while enabling targeted adaptation for abstention-aware reasoning.

4.4 Inference Behavior

At inference time, the trained model processes multimodal inputs using the same generation pipeline as standard Med-VLMs. No additional confidence thresholds, external classifiers, or calibration mechanisms are introduced. Instead, the model naturally produces either a clinically grounded answer or an explicit abstention response through standard decoding. This design keeps the framework simple and deployment-friendly while allowing the model to communicate uncertainty directly in natural language, which is particularly important in high-stakes medical applications.

'You are a medical visual question answering assistant. Your task is to answer the user's question using only the information that is explicitly present in the provided image and/or text. If the question cannot be answered, you must respond with: 'ABSTAIN: Cannot be Determined from the provided Context'. Do not guess. Do not assume missing details. Do not provide speculative or uncertain medical advice.'

5 Experiments and Results

We conduct our experiments under three controlled input configurations, evaluating model behavior for Pre *MAD-MED* and Post *MAD-MED* approach.

(a) Image-Only Setting: The model is provided solely with an ADR-related image and is queried using six questions derived from the three abstention perspectives described in Section 4.2. The question set includes both queries that can be reliably answered using image alone and queries that are unanswerable from the image content.

(b) Text-Only Setting: In this configuration, only textual information is supplied to the model. The evaluation questions comprise text-answerable queries and queries that inherently require visual context.

(c) Image-and-Text Setting: The model receives both the image and the accompanying text as input. The same set of evaluation questions is used to examine how additional multimodal context influences the model's answerability assessment and abstention behavior.

5.1 Implementation Details

We implemented the proposed *MAD-MED* approach on four state-of-the-art Medical VLMs: LLaVA-Med (Li et al., 2023), Med-Flamingo (Moor et al., 2023), MedGemma (et al, 2025), and Qwen-Med (Cheng et al., 2024). These models were selected for their open-source nature, clinical relevance, and modular architectures. All experiments were conducted on an NVIDIA H100 GPU, with per-model training time ranging from 1.2 to 2.5 hours. The dataset was split into training and test sets in a 70:30 ratio. We evaluated the abstention capability using Precision, Recall, and F1-score. In addition, we utilise a task-specific metric, Abstention Accuracy (AA) to evaluate the model's ability to make correct abstention decisions. AA measures the proportion of correct decisions, including both appropriate answers and appropriate abstentions, among all evaluated queries. We further employed human evaluations to measure the hallucination rate and clinical accuracy (Sahoo et al., 2024a). For questions where the model was expected to answer, the generated response was evaluated against the gold reference using Jaccard similarity(JM, 2004) and BERTScore(Zhang et al., 2019).

5.2 Evaluations

Across the three controlled input configurations, the results consistently demonstrate the effectiveness of the proposed *MAD-MED* framework in improving abstention behavior while maintaining answer quality.

5.3 Analysis of Results

Tables 1, 2, and 3 present the quantitative performance of the evaluated Medical VLMs under three controlled input configurations. Across all settings, the results consistently demonstrate that the proposed *MAD-MED* framework significantly improves abstention behavior while preserving and improving answer quality.

5.3.1 Image-Only Setting

In the image-only configuration, models receive only visual input while the associated clinical text is withheld. Since several evaluation questions require textual evidence, these queries are inherently unanswerable in this setting. The baseline models frequently attempt to generate answers despite insufficient evidence, leading to high hallucination rates (HR) and low abstention recall. After applying *MAD-MED*, all evaluated models exhibit substantial improvements in abstention performance as demonstrated in Table 1. In particular, abstention recall increases from approximately 0.28–0.31 in the baseline models to around 0.74–0.78 after training with *MAD-MED*. At the same time, hallucination rates decrease dramatically from values above 0.85 to approximately 0.21–0.24. This indicates that the proposed framework effectively teaches the models to recognize when visual information alone is insufficient and to abstain from generating unreliable answers. Importantly, answer quality metrics such as Jaccard Similarity (JS) and BERTScore (BS) also improve, suggesting that the framework does not simply increase refusal behavior but encourages more reliable responses when sufficient evidence is available.

5.3.2 Text-Only Setting

A similar pattern is observed in the text-only configuration, where models are provided with clinical text but the associated medical image is not available. In this setting, questions that rely on visual evidence cannot be answered reliably. Baseline models again tend to produce speculative answers in the absence of visual context, resulting in high hallucination rates and low abstention recall. After incorporating *MAD-MED*, abstention recall improves substantially across all models, reaching approximately 0.76–0.79. Simultaneously, hallucination rates are reduced to roughly 0.20–0.23. The results in Table 2 indicate that the proposed approach enables the models to identify when a required modality is missing and to abstain accordingly, rather than attempting to produce unsupported responses. Furthermore, improvements in clinical accuracy demonstrate that answer generation for genuinely text-answerable questions remains reliable.

5.3.3 Image-and-Text Setting

In the multimodal configuration, where both the image and the clinical text are provided, the models have access to the full context required for answering most questions. Under this setting, the application of *MAD-MED* results in consistent improvements across all evaluation metrics. As demonstrated in Table 3, abstention F1 increase by 47.2%-79.9% for all baseline models, indicating that the model is better able to distinguish between answerable and unanswerable queries even when full multimodal information is available. In addition, answer evaluation metrics such as JS and BS show noticeable gains, suggesting that the generated responses become more semantically aligned with the ground-truth answers. Clinical accuracy also improves significantly, highlighting the practical reliability of the responses in medically relevant scenarios.

5.3.4 Classification Results

To evaluate the effectiveness of the proposed *MAD-MED* framework, we treat 'Abstain' as the positive class (instances where the model is expected to withhold an answer) and 'Answer' as the negative class. As observed from Table 3, precision exhibits a modest improvement, while recall increases sharply. In the pre *MAD-MED* approach, the models rarely abstain: when presented with a question, they tend to generate an answer in the majority of cases resulting in a very small number of true positives and subsequently very few false positives. After applying *MAD-MED*, the number of true positive cases increases substantially while false positives remain low, leading to stable and consistent precision. In contrast, recall is severely limited in the pre *MAD-MED* setting due to a large number of false negatives cases where the model should abstain but instead produces an answer. *MAD-MED* dramatically reduces these false

		Abstain Evaluations					Human Evaluations	Answer Evaluation	
Models	*MAD-MED*	P	R	F1	AA	HR	Clinical Accuracy	JS	BS
LLaVA-Med	*Pre*	0.701	0.286	0.407	0.251	0.874	0.18	0.587	0.754
	Post	0.774	0.742	0.758	0.792	0.241	0.71	0.662	0.872
Med-Flamingo	*Pre*	0.682	0.314	0.430	0.268	0.851	0.21	0.604	0.742
	Post	0.748	0.768	0.758	0.815	0.214	0.74	0.676	0.861
Qwen-Med	*Pre*	0.673	0.278	0.394	0.243	0.889	0.17	0.575	0.731
	Post	0.783	0.776	0.779	0.824	0.206	0.76	0.695	0.883
MedGemma	*Pre*	0.651	0.301	0.412	0.259	0.862	0.15	0.556	0.719
	Post	0.731	0.751	0.741	0.803	0.232	0.69	0.671	0.857

Table 1: Performance under the **Image-Only** configuration. When textual context is unavailable, baseline models frequently generate speculative responses. The proposed *MAD-MED* framework significantly improves abstention recall and reduces hallucination rates while preserving answer quality.

		Abstain Evaluations					Human Evaluations	Answer Evaluation	
Models	*MAD-MED*	P	R	F1	AA	HR	Clinical Accuracy	JS	BS
LLaVA-Med	*Pre*	0.718	0.332	0.454	0.296	0.861	0.23	0.611	0.781
	Post	0.781	0.763	0.772	0.826	0.218	0.74	0.684	0.891
Med-Flamingo	*Pre*	0.702	0.356	0.472	0.309	0.842	0.25	0.629	0.769
	Post	0.752	0.781	0.766	0.834	0.203	0.72	0.697	0.874
Qwen-Med	*Pre*	0.687	0.301	0.418	0.271	0.878	0.20	0.598	0.747
	Post	0.792	0.788	0.790	0.842	0.209	0.76	0.708	0.889
MedGemma	*Pre*	0.661	0.337	0.446	0.294	0.851	0.18	0.573	0.725
	Post	0.741	0.769	0.755	0.812	0.229	0.70	0.679	0.866

Table 2: Performance under the **Text-Only** configuration. Without visual evidence, baseline models tend to hallucinate answers for image-dependent questions. *MAD-MED* significantly improves abstention recall while maintaining answer quality.

		Abstain Evaluations					Human Evaluations	Answer Evaluation	
Models	*MAD-MED*	P	R	F1	AA	HR	Clinical Accuracy	JS	BS
LLaVA-Med	*Pre*	0.736	0.355	0.479	0.278	0.856	0.21	0.613	0.782
	Post	0.782	0.785	0.783	0.813	0.237	0.76	0.689	0.894
Med-Flamingo	*Pre*	0.711	0.402	0.514	0.314	0.804	0.24	0.647	0.765
	Post	0.753	0.762	0.757	0.832	0.205	0.73	0.692	0.865
Qwen-Med	*Pre*	0.694	0.321	0.439	0.261	0.882	0.19	0.593	0.743
	Post	0.789	0.791	0.790	0.845	0.214	0.77	0.714	0.890
MedGemma	*Pre*	0.658	0.377	0.479	0.302	0.823	0.16	0.568	0.718
	Post	0.738	0.764	0.751	0.801	0.249	0.69	0.681	0.864

Table 3: Performance under the **Image+Text** configuration. With full multimodal context, *MAD-MED* improves both answer accuracy and abstention performance while significantly reducing hallucination rates. Quantitative performance of the *MAD-MED* approach for abstain classification using Precision (P), Recall (R), F1-score (F1), Abstention Accuracy (AA), and Hallucination Rate (HR). Answer evaluation is performed using Jaccard similarity (JS) and BERTScore (BS).

negatives, showing recall improvements. We notice that Abstain accuracy improved considerably from pre to post, highlighting the fact that our approach aligned the VLMs to actually abstain. We additionally evaluate the hallucination behavior of the models through human evaluation. Hallucination rate is assessed manually based on whether the generated response contains unsupported or incorrect information when the model should abstain. As expected, hallucination rates are high in the pre *MAD-MED* approach, since the model answers most queries. Following the *MAD-MED* approach, hallucination is dramatically reduced, as the model reliably abstains in scenarios that previously triggered unsupported responses.

In addition to abstention analysis, we also conducted a complementary evaluation on queries where the model is expected to provide an answer.

Setting	Question	Baseline Output	MAD-MED Output
Image-Only	What medication caused the rash in the image?	The rash appears to be caused by penicillin allergy.	**ABSTAIN:** The medication responsible for the rash cannot be determined from the image alone without additional clinical context.
Text-Only	Does the patient show visible swelling or redness on the skin?	Yes, the patient shows swelling and redness.	**ABSTAIN:** The presence of visible swelling or redness cannot be determined without examining the medical image.
Image+Text	What adverse drug reaction best explains the symptoms?	The patient likely has Stevens–Johnson syndrome caused by medication.	The symptoms described in the text and image suggest a possible adverse drug reaction such as Stevens–Johnson syndrome, though clinical confirmation is required.

Table 4: Qualitative comparison of baseline Medical VLMs and the proposed *MAD-MED* framework. Baseline models often generate speculative answers when evidence is missing, whereas *MAD-MED* appropriately abstains in uncertain scenarios.

Beyond the classification-based assessment, we examined the quality of the generated responses using Jaccard similarity and BERTScore. These answerable queries consist of medical questions grounded in the provided input context. Since the evaluated VLMs are clinically pre-trained and aligned with the medical domain, the generated responses in the pre *MAD-MED* setting were generally reasonable. However, following the application of the *MAD-MED* framework, the generation quality improves substantially as the model learns a more structured and consistent way to respond.

To complement the automatic metrics, we conduct a human evaluation to assess the clinical quality of model-generated answers. For all instances where the model produces an answer, domain-informed annotators rate the response on clinical correctness. Clinical correctness measures the factual and medical validity of the response with respect to the provided input. These dimensions are scored on a range from 1–5, where higher values indicate better performance. The reported results in Table 3 correspond to the average scores across annotators and test samples. This evaluation allows us to verify that the improved abstention behavior introduced by *MAD-MED* does not degrade the contrary generative capability of the model.

5.3.5 Qualitative Results

Table 4 presents representative qualitative examples comparing baseline Medical VLMs with the proposed *MAD-MED* framework under different input configurations. The examples illustrate a common failure mode of baseline models: when required evidence from a particular modality is missing, the models often generate speculative responses rather than acknowledging uncertainty. In the *Image-Only* setting, the baseline model attributes the observed rash to a specific medication despite the absence of any medication information in the image. Similarly, in the *Text-Only* setting, the model claims the presence of visible symptoms that cannot be verified without visual input. In contrast, the *MAD-MED* enhanced models correctly identify these cases as unanswerable and produce explicit abstention responses. Importantly, when both modalities are available in the *Image+Text* setting, *MAD-MED* generates a cautious, evidence-grounded response rather than abstaining unnecessarily. These examples highlight that the proposed framework encourages models to abstain in situations with insufficient evidence while still allowing accurate responses when adequate multimodal context is available, thereby improving the safety and reliability of medical reasoning. We present additional qualitative results in Appendix A.3.

6 Conclusion

In this work, we introduce *MAD-MED*, a **M**odel **A**bstention approach for **D**rug Adverse Reaction for **MED**ical-VLMs. It is a training strategy that enables models to abstain from responding when a query contradicts the available input, exceeds the model's knowledge, or violates clinical and ethical boundaries. To the best of our knowledge, *MAD-MED* is the first dedicated model abstention approach developed for vision–language models in the medical domain. In addition, we release an augmented ADR-ABS dataset comprising image-

answerable, text-answerable, and unanswerable questions to support systematic evaluation of abstention behavior. Extensive quantitative and human evaluations demonstrate that *MAD-MED* significantly enhances abstention performance while preserving the generative capabilities of the underlying models.

7 Limitations

Despite the promising results, our work has several limitations. In particular, the current formulation of abstention is restricted to three categories: image-answerable, text-answerable, image-text answerable and unanswerable. However, real-world clinical decision making often involves more complex forms of uncertainty, such as partially answerable cases and conflicting evidence. These aspects are not fully captured in the present framework and is part of our ongoing future work.

8 Ethical Consideration

In this work, we augment a publicly available dataset and employ existing models in a responsible and transparent manner. We ensure that no harmful, misleading, or offensive content is introduced in the question–answering process. All experimental procedures strictly adhere to established ethical guidelines. We additionally provide the abstention clauses, task prompts, and representative question generation templates used in our experiments to support transparency and reproducibility. Any biases that may appear in the dataset are unintentional, and we have no intention of causing harm to any individual or group. All necessary approvals for conducting this research were obtained from the relevant institutional ethics boards.

9 Acknowledgement

The authors gratefully acknowledge the financial support provided by the Prime Minister's Research Fellowship (PMRF), Government of India. The authors additionally thank the Aryabhatta Supercomputing Centre (ASC) at the Indian Institute of Technology Patna for providing the computational resources utilized in this work.

References

Daixuan Cheng, Shaohan Huang, Ziyu Zhu, Xintong Zhang, Wayne Xin Zhao, Zhongzhi Luan, Bo Dai, and Zhenliang Zhang. 2024. On domain-adaptive post-training for multimodal large language models. *arXiv preprint arXiv:2411.19930*.

Charles Corbière, Nicolas Thome, Avner Bar-Hen, Matthieu Cord, and Patrick Pérez. 2019. Addressing failure prediction by learning model confidence. *Advances in neural information processing systems*, 32.

Shrey Desai and Greg Durrett. 2020. Calibration of pre-trained transformers.

Andrew Sellergren et al. 2025. Medgemma technical report.

Satvik Garg. 2021. Drug recommendation system based on sentiment analysis of drug reviews using machine learning. In *2021 11th International Conference on Cloud Computing, Data Science & Engineering (Confluence)*, pages 175–181. IEEE.

Luis Fernando Granda Morales, Priscila Valdiviezo-Diaz, Ruth Reátegui, and Luis Barba-Guaman. 2022. Drug recommendation system for diabetes using a collaborative filtering and clustering approach: development and performance evaluation. *Journal of Medical Internet Research*, 24(7):e37233.

Seungju Han, Kavel Rao, Allyson Ettinger, Liwei Jiang, Bill Yuchen Lin, Nathan Lambert, Yejin Choi, and Nouha Dziri. 2024. Wildguard: Open one-stop moderation tools for safety risks, jailbreaks, and refusals of llms. *Advances in Neural Information Processing Systems*, 37:8093–8131.

Sunan He, Yuxiang Nie, Zhixuan Chen, Zhiyuan Cai, Hongmei Wang, Shu Yang, and Hao Chen. 2024. Meddr: Diagnosis-guided bootstrapping for large-scale medical vision-language learning. *CoRR*.

Di Jin, Eileen Pan, Nassim Oufattole, Wei-Hung Weng, Hanyi Fang, and Peter Szolovits. 2021. What disease does this patient have? a large-scale open domain question answering dataset from medical exams. *Applied Sciences*, 11(14):6421.

Hancock JM. 2004. Jaccard distance (jaccard index, jaccard similarity coefficient). *Dictionary of Bioinformatics and Computational Biology. Chichester: John Wiley & Sons*, pages 223–70.

Sahil Kale and Vijaykant Nadadur. 2025. Line of duty: Evaluating llm self-knowledge via consistency in feasibility boundaries. In *Proceedings of the 5th Workshop on Trustworthy NLP (TrustNLP 2025)*, pages 127–140.

Amita Kamath, Robin Jia, and Percy Liang. 2020. Selective question answering under domain shift. In *Proceedings of the 58th annual meeting of the association for computational linguistics*, pages 5684–5696.

Sanjeev B Khanagar, Ali Al-Ehaideb, Satish Vishwanathaiah, Prabhadevi C Maganur, Shankargouda Patil, Sachin Naik, Hosam A Baeshen, and Sachin S

Sarode. 2021. Scope and performance of artificial intelligence technology in orthodontic diagnosis, treatment planning, and clinical decision-making-a systematic review. *Journal of dental sciences*, 16(1):482–492.

Chunyuan Li, Cliff Wong, Sheng Zhang, Naoto Usuyama, Haotian Liu, Jianwei Yang, Tristan Naumann, Hoifung Poon, and Jianfeng Gao. 2023. Llava-med: Training a large language-and-vision assistant for biomedicine in one day. *Advances in Neural Information Processing Systems*, 36:28541–28564.

Shuyue S Li, Vidhisha Balachandran, Shangbin Feng, Jonathan S Ilgen, Emma Pierson, Pang W Koh, and Yulia Tsvetkov. 2024. Mediq: Question-asking llms and a benchmark for reliable interactive clinical reasoning. *Advances in Neural Information Processing Systems*, 37:28858–28888.

Xin Lin, Zhenya Huang, Zhiqiang Zhang, Jun Zhou, and Enhong Chen. 2025. Explore what llm does not know in complex question answering. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 24585–24594.

Ilya Loshchilov and Frank Hutter. 2017. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*.

Sabrina J Mielke, Arthur Szlam, Emily Dinan, and Y-Lan Boureau. 2022. Reducing conversational agents' overconfidence through linguistic calibration. *Transactions of the Association for Computational Linguistics*, 10:857–872.

Michael Moor, Qian Huang, Shirley Wu, Michihiro Yasunaga, Cyril Zakka, Yash Dalmia, Eduardo Pontes Reis, Pranav Rajpurkar, and Jure Leskovec. 2023. Med-flamingo: a multimodal medical few-shot learner (2023). *URL: https://arxiv.org/abs/2307.15189*.

Shiyu Ni, Keping Bi, Jiafeng Guo, Lulu Yu, Baolong Bi, and Xueqi Cheng. 2025. Towards fully exploiting llm internal states to enhance knowledge boundary perception. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 24315–24329.

Pranab Sahoo, Prabhash Meharia, Akash Ghosh, Sriparna Saha, Vinija Jain, and Aman Chadha. 2024a. Unveiling hallucination in text, image, video, and audio foundation models: A comprehensive survey. *arXiv preprint arXiv:2405.09589*.

Pranab Sahoo, Ayush Singh, Sriparna Saha, Aman Chadha, and Samrat Mondal. 2024b. Enhancing adverse drug event detection with multimodal dataset: Corpus creation and model development. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 11214–11226, Bangkok, Thailand. Association for Computational Linguistics.

Karan Singhal, Shekoofeh Azizi, Tao Tu, S Sara Mahdavi, Jason Wei, Hyung Won Chung, Nathan Scales, Ajay Tanwani, Heather Cole-Lewis, Stephen Pfohl, et al. 2023. Large language models encode clinical knowledge. *Nature*, 620(7972):172–180.

Aarohi Srivastava, Abhinav Rastogi, Abhishek Rao, Abu Awal Md Shoeb, Abubakar Abid, Adam Fisch, Adam R Brown, Adam Santoro, Aditya Gupta, Adrià Garriga-Alonso, et al. 2023. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. *Transactions on machine learning research*.

Alexandra-Maria Tăuţan, Bogdan Ionescu, and Emiliano Santarnecchi. 2021. Artificial intelligence in neurodegenerative diseases: A review of available tools with a focus on machine learning techniques. *Artificial intelligence in medicine*, 117:102081.

Omkar Thawkar, Abdelrahman Shaker, Sahal Shaji Mullappilly, Hisham Cholakkal, Rao Muhammad Anwer, Salman Khan, Jorma Laaksonen, and Fahad Shahbaz Khan. 2023. Xraygpt: Chest radiographs summarization using medical vision-language models. *arXiv preprint arXiv:2306.07971*.

Katherine Tian, Eric Mitchell, Allan Zhou, Archit Sharma, Rafael Rafailov, Huaxiu Yao, Chelsea Finn, and Christopher D Manning. 2023. Just ask for calibration: Strategies for eliciting calibrated confidence scores from language models fine-tuned with human feedback. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 5433–5442.

Tao Tu, Anil Palepu, Mike Schaekermann, Khaled Saab, Jan Freyberg, Ryutaro Tanno, Amy Wang, Brenna Li, Mohamed Amin, Nenad Tomasev, et al. 2024a. Towards conversational diagnostic ai. *arXiv preprint arXiv:2401.05654*.

Tao Tu, Anil Palepu, Mike Schaekermann, Khaled Saab, Jan Freyberg, Ryutaro Tanno, Amy Wang, Brenna Li, Mohamed Amin, Nenad Tomasev, et al. 2024b. Towards conversational diagnostic ai. *arXiv preprint arXiv:2401.05654*.

Neeraj Varshney, Pavel Dolin, Agastya Seth, and Chitta Baral. 2024. The art of defending: A systematic evaluation and analysis of llm defense strategies on safety and over-defensiveness. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 13111–13128.

Neeraj Varshney, Swaroop Mishra, and Chitta Baral. 2022. Investigating selective prediction approaches across several tasks in iid, ood, and adversarial settings. *arXiv preprint arXiv:2203.00211*.

Chunhao Wang, Xiaofeng Zhu, Julian C Hong, and Dandan Zheng. 2019. Artificial intelligence in radiotherapy treatment planning: present and future. *Technology in cancer research & treatment*, 18:1533033819873922.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and

Denny Zhou. 2022. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*.

Yuxia Wang, Haonan Li, Xudong Han, Preslav Nakov, and Timothy Baldwin. Do-notanswer: A dataset for evaluating safeguards in llms, 2023. *URL: https://arxiv. org/abs/2308.13387*.

Yuqing Yang, Ethan Chern, Xipeng Qiu, Graham Neubig, and Pengfei Liu. 2023. Alignment for honesty. *ArXiv*, abs/2312.07000.

Qing Ye, Chang-Yu Hsieh, Ziyi Yang, Yu Kang, Jiming Chen, Dongsheng Cao, Shibo He, and Tingjun Hou. 2021. A unified drug–target interaction prediction framework based on knowledge graph and recommendation system. *Nature communications*, 12(1):6775.

Hanning Zhang, Shizhe Diao, Yong Lin, Yi Fung, Qing Lian, Xingyao Wang, Yangyi Chen, Heng Ji, and Tong Zhang. 2024. R-tuning: Instructing large language models to say 'i don't know'. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 7106–7132.

Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q Weinberger, and Yoav Artzi. 2019. Bertscore: Evaluating text generation with bert. *arXiv preprint arXiv:1904.09675*.

A Appendix

A.1 Frequently Asked Questions (FAQs)

Q1. Why is abstention necessary? Why not just improve accuracy? In safety-critical medical scenarios, the primary risk is not low accuracy but overconfident incorrect responses. Our study demonstrates that existing Med-VLMs tend to answer even when evidence is missing, conflicting, or clinically inappropriate, which can lead to serious downstream harm such as patient anxiety, medication discontinuation, or unsafe self-treatment.

Q2. Why restrict abstention to three categories? We intentionally begin with three coarse-grained categories—image-answerable, text-answerable, and unanswerable—to establish a controlled, interpretable framework for learning abstention. These categories capture fundamental uncertainty modes in multimodal clinical reasoning and allow precise measurement of abstention behavior. We explicitly acknowledge that real-world uncertainty is more complex and identify finer-grained abstention modeling as important future work.

Q3. Why only six final questions? For each sample, annotators initially generated approximately 15 clinically relevant candidate questions. These were systematically scored on modal appropriateness, abstention sensitivity, and ADR relevance. Through consensus-based selection with strong inter-annotator agreement (0.89), six questions were chosen that maximized coverage of multimodal reasoning and clinical intent while maintaining annotation consistency.

Q4. Is the approach generalizable? Yes. MAD-MED is architecture-agnostic: the backbone remains frozen, only lightweight adapters are trained, and no inference-time modifications are required. This allows the framework to be applied across different LLMs and VLMs with minimal engineering overhead.

Q5. Does the model simply abstain more often? No. Our analysis shows that while true positive abstentions increase significantly, false positives remain low, and generative capability on answerable cases is preserved.

Q6. Why was the augmented dataset necessary? Existing medical multimodal datasets are not designed to evaluate or train abstention behavior: they overwhelmingly assume that every query should be answered. To study abstention in a clinically meaningful way, we required carefully con-

structed scenarios where answering is appropriate, inappropriate, or impossible given the available evidence. The augmented dataset enables systematic supervision of abstention by introducing controlled uncertainty across modalities (image-only, text-only, or neither), while preserving real clinical context. This design allows us to measure not only whether the model abstains, but when it should abstain something that cannot be reliably evaluated using existing datasets alone.

Q7. Why did you select only these four Med-VLMs, and why not commercial models such as ChatGPT?

We selected LLaVA-Med, Med-Flamingo, Qwen-Med, and MedGemma because they are publicly available, clinically relevant, and technically diverse medical VLMs. All four models support modular, parameter-efficient adaptation, which is essential for isolating the effect of our abstention training while keeping the backbone frozen. Moreover, they are pretrained on medical data but differ substantially in their vision encoders, language backbones, and multimodal fusion mechanisms, enabling us to evaluate MAD-MED across heterogeneous architectures. We did not include commercial models such as ChatGPT because their training procedures and internal parameters are inaccessible, making it impossible to implement or analyze the proposed abstention learning mechanism within the model itself. Our focus is on methods that are reproducible, controllable, and deployable in real clinical research settings.

Q8. Do you release your source code and augmented dataset publicly?

Yes, we release source code and dataset publicly in the anonymous link below: https://anonymous.4open.science/r/anonymous_to_all-8D37/

A.2 Construction Process of Q-A Pairs

For each of the 1,500 multimodal samples, annotators were first instructed to independently generate a diverse pool of clinically meaningful candidate questions. The question formulation process was guided by three core principles: (i) clinical relevance to adverse drug reaction (ADR) analysis, (ii) coverage of multimodal reasoning scenarios, including vision-only, text-only, and unanswerable cases, and (iii) diversity of clinical intent, encompassing diagnosis, symptom interpretation, drug usage, and risk assessment. This process resulted in an initial set of 15 candidate questions Table 5. Each question was subsequently evaluated on a 1–5 scale along three parameters: Model Appropriateness, Abstention Sensitivity, and ADR Relevance. The final questions Table 6 were selected based on the threshold value of more than 4.5. The resulting scores for the selected questions are reported below.

A.3 *MAD-MED* Qualitative results

We present additional qualitative results in Figures 2, 3, 4, 5. We evaluate the models under three scenarios: image-only, text-only, and image–text inputs. In the pre–MAD-MED setting, the models rarely abstain and attempt to answer nearly all questions, regardless of suitability. After applying the MAD-MED approach, abstention behavior improves substantially, with the models reliably refraining from answering in inappropriate or unsupported scenarios.

#	Candidate Question	Avg Score
1	What drug is the patient using?	**4.91**
2	What is the route of drug administration?	**4.78**
3	What is the dosage and frequency?	3.42
4	How long has the patient been using this drug?	3.65
5	Is the patient taking multiple medications?	3.11
6	What adverse drug events are described?	**4.89**
7	What is the severity of the adverse reaction?	3.87
8	Are the adverse events acute or chronic?	**4.56**
9	Is the reaction drug-induced or disease-related?	3.26
10	What physiological systems are affected?	3.71
11	Which body part is affected in the image?	**4.74**
12	What visible physical symptoms are present?	4.02
13	What psychological conditions are suggested by the image?	**4.62**
14	Can the diagnosis be confirmed from the available information?	2.98
15	Is there sufficient evidence to recommend a change in medication?	2.21

Table 5: Candidate Question Scores

Question
What drug is the patient using?
What is the route and pattern of drug administration?
What adverse drug events are described in the case?
What psychological medical conditions are described in the image?
Which body part is affected in the image?
Are the adverse events acute or chronic based on the information provided?

Table 6: Final selected set of Questions used in our Model Abstention Approach




Figure 2: Qualitative depiction of pre *MAD-MED* and post *MAD-MED* approach when only image is passed as an input.




Figure 3: Qualitative depiction of pre *MAD-MED* and post *MAD-MED* approach when only text is passed as an input.




Figure 4: Qualitative depiction of pre *MAD-MED* and post *MAD-MED* approach when image and text is passed as an input.




Figure 5: Qualitative depiction of pre *MAD-MED* and post *MAD-MED* approach when image only is passed as an input.