Progress Drift: Auditing False Progress in Long-Horizon LLM Agents

Xiangbo Zhang **Xiaoxu Ma**
Georgia Institute of Technology
Atlanta, GA, USA
xiangbo.zhang@gatech.edu xma394@gatech.edu

Abstract

Long-horizon language agents increasingly report intermediate progress while searching, editing, executing tools, and producing artifacts. Users rely on these reports to decide whether to intervene, continue, or accept an output, yet final task success does not reveal whether the agent described its work faithfully along the way. We study PROGRESS DRIFT, a failure mode in which reported task state diverges from observable evidence. We introduce PROGRESSBENCH, a claim-level benchmark that aligns progress reports with milestones, tool observations, and artifacts across coding, web research, and research-replication tasks. We further propose PROGRESS LEDGER, an evidence-linked reporting protocol in which material progress claims carry evidence pointers, timestamps, verification status, and unresolved risks. Across 1,280 tasks, ledger-constrained reporting improves progress claim accuracy from 80.6 to 89.7 and reduces false completion from 12.7 to 6.9 under shared tool budgets. These results suggest that agent evaluation should measure not only task completion, but also whether agents faithfully report what has and has not been achieved during execution.

1 Introduction

LLM agents increasingly perform long-horizon tasks involving tool use (Yao et al., 2022; Schick et al., 2023; Qin et al., 2023; Liu et al., 2023), web interaction (Zhou et al., 2023; Wei et al., 2025), repository-level code repair (Jimenez et al., 2023; OpenAI, 2024), and scientific replication (Starace et al., 2025). These settings expose users not only to final artifacts, but also to intermediate claims about what the agent has found, fixed, verified, or completed.

Prior work studies retrieval grounding (Lewis et al., 2020), browser-assisted evidence use (Nakano et al., 2021), citation support (Gao et al., 2023), and factuality or hallucination (Min et al., 2023; Li et al., 2023). Long-horizon agents introduce a distinct target: whether reports about the agent's own evolving task state are faithful. A coding agent may claim tests pass despite a failing log, a web agent may treat a topically related page as support, and a research agent may report an ablation as complete despite missing run provenance.

We call this failure mode PROGRESS DRIFT: a mismatch between reported progress and evidence-supported progress. Progress reporting is therefore a distinct evaluation target: users need to know not only whether an agent eventually succeeds, but whether its intermediate claims are reliable during execution.

Our contributions are summarized as follows:

- We formulate progress faithfulness and define PROGRESS DRIFT as a mismatch between reported task state and the latest evidence-supported state.
- We introduce PROGRESSBENCH, a benchmark aligning progress reports with milestones, observations, and artifacts under explicit evidence-precedence rules.
- We propose PROGRESS LEDGER, an evidence-linked protocol preventing failed or unresolved states from becoming unsupported completions.

2 Progress Drift

Figure 1 gives the full progress-auditing pipeline. We first formalize the mismatch between an agent's reported progress and the evidence-supported task state, then instantiate this formalism in PROGRESSBENCH and mitigate it with PROGRESS LEDGER. Let an agent interact with an environment over turns $t = 1, \ldots, T$, observing o_t, taking actions a_t, modifying artifacts A_t, and emitting progress reports r_t. Each report is

Proceedings of the 15th International Joint Conference on Natural Language Processing and the 5th Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics, pages 281–294
November 6-10, 2026 ©2026 Association for Computational Linguistics




Figure 1: Overview of progress auditing. A long-horizon agent emits progress reports while interacting with tools and artifacts. PROGRESSBENCH evaluates whether atomic progress claims are supported by the latest evidence, and PROGRESS LEDGER constrains final reports to inherit verified, partial, failed, or unresolved status rows.

decomposed into atomic claims c_i about completion, diagnostics, artifacts, citations, experiments, or residual risks. A task is represented by observable milestone states $M = \{m_1, \ldots, m_K\}$. Our audit uses only visible evidence, including tool outputs, retrieved text, diffs, logs, screenshots, generated files, and final artifacts, and excludes hidden chain-of-thought.

For a claim c_i made at time t_i, let $E_{\leq t_i}$ denote the visible evidence available at that point and any later evidence that invalidates or supersedes it. A claim is supported if the latest relevant evidence entails the exact proposition, contradicted if stronger or later evidence falsifies it, and unverifiable if the claim is material but lacks an adequate evidence pointer. Let $\mathcal{S}_{\text{bad}} = \{\text{CONTRADICTED}, \text{UNVERIFIABLE}\}$. We define a progress drift event as

$$\text{Drift}(c_i) = \mathbb{I}[\text{material}(c_i) \wedge \text{status}(c_i) \in \mathcal{S}_{\text{bad}}]\,. \quad (1)$$

3 ProgressBench

PROGRESSBENCH evaluates progress faithfulness by aligning agent reports with observable task state. Each instance contains a user task, tool inventory, milestone rubric, agent trajectory, observations, artifacts, and progress reports. The benchmark covers coding with diffs and tests, web research with source evidence, and research replication with logs, tables, and generated files. Table 1 summarizes the corpus.

Benchmark construction. We construct PROGRESSBENCH by collecting auditable tasks, defining milestone graphs that separate attempts from verified outcomes, running agents under fixed tool budgets, extracting and aligning atomic progress claims, and assigning support labels with evidence-precedence rules. A stratified human-audit split is reserved for reliability checks, so evaluation is grounded in timestamped claim-evidence pairs rather than free-form summaries.

Claim extraction and alignment. Claim extraction is hybrid. A parser segments reports into candidate atomic claims using triggers such as fixed, verified, passed, completed, failed, and unresolved. Annotators refine boundaries, split compound claims, assign types, align claims to milestones, and attach the latest evidence pointer. The resulting rules define the automatic evaluator, validated on the 20% human-audit split for support-label and false-completion reliability.

Evidence precedence. Evidence follows temporal precedence: pre-edit tests cannot verify post-edit code, URLs support claims only when the cited span entails them, and the latest valid observation prevails when observations conflict. This prevents stale logs, browser states, or artifacts from justifying later claims.

Metrics. We report final task success together with progress-faithfulness metrics. For claim set C, supported indicator $S(c)$, contradicted comple-

Domain	Tasks	Milestones	Claims	Turns
Coding	480	3,072	16,940	20.8
Web research	420	2,394	13,120	15.2
Replication	380	2,470	11,540	24.6
Total	1,280	7,936	41,600	20.1

Table 1: PROGRESSBENCH benchmark composition across three long-horizon agent domains. Turns denotes the average number of agent turns per trajectory.

tion indicator $D(c)$, unverifiable completion indicator $U(c)$, and completion-claim subset C_d, we define

$$\mathrm{PCA} = 100\,|C|^{-1} \sum_{c \in C} S(c). \tag{2}$$

$$\mathrm{FCR} = 100\,|C_d|^{-1} \sum_{c \in C_d} D(c). \tag{3}$$

$$\mathrm{UCR} = 100\,|C_d|^{-1} \sum_{c \in C_d} U(c). \tag{4}$$

PCA treats both contradicted and unverifiable claims as unsupported, while FCR and UCR separate contradicted completion from evidence-free completion. Let O be salient tool observations, A artifact claims, and B calibrated progress reports with reported completion probability $\hat{p}_b$ and observed milestone completion y_b. Let $\{B_\ell\}_{\ell=1}^{L}$ denote progress-probability bins, with $\bar{p}_\ell = |B_\ell|^{-1} \sum_{b \in B_\ell} \hat{p}_b$ and $\bar{y}_\ell = |B_\ell|^{-1} \sum_{b \in B_\ell} y_b$. We further compute

$$\mathrm{TOF} = \frac{100}{|O|} \sum_{o \in O} \mathbb{I}[\mathrm{report}(o) = \mathrm{outcome}(o)]\,, \tag{5}$$

$$\mathrm{ARC} = \frac{100}{|A|} \sum_{a \in A} \mathbb{I}[\mathrm{artifact}(a) \models a]\,, \tag{6}$$

$$\mathrm{PCE} = \sum_{\ell=1}^{L} \frac{|B_\ell|}{|B|} \left|\bar{p}_\ell - \bar{y}_\ell\right|. \tag{7}$$

TOF measures tool-outcome fidelity, ARC artifact consistency, and PCE progress calibration.

4 Progress Ledger

PROGRESS LEDGER is an evidence-carrying reporting protocol. Each material report is backed by a row containing subtask, claim, evidence pointer, verifier, status, timestamp, and residual risk. The final answer is derived from row state: verified rows may be stated as complete; partial rows must remain partial; failed rows must be disclosed; unresolved rows cannot be summarized as success. The protocol is not a formal proof system, but makes the evidential basis for progress claims explicit and auditable. The protocol changes the semantics of agent reporting: "Edited" is not "fixed," "retrieved" is not "verified," and "planned" is not "completed." Unlike free-form progress reports, ledgered reports must preserve failed and unresolved states unless new evidence changes their status. Table 2 illustrates how failed and unresolved rows are preserved in the final report.

Subtask	Status	Evidence and unresolved risk
Patch parser	attempted	Diff exists; causal fix not verified.
Add regression	verified	New test file exists and runs.
Run suite	failed	Latest test log reports 3 failures.
Final claim	partial	Completion claim must disclose failures.

Table 2: Semantics of PROGRESS LEDGER. The final report inherits unresolved and failed rows rather than converting activity into completion.

Agent	Success↑	PCA↑	FCR↓	TOF↑
ReAct	42.6±1.4	61.4±0.9	34.7±1.1	58.9±1.0
Self-Reflect	45.0±1.5	64.8±0.8	31.9±1.0	61.7±0.9
Plan-Execute	46.7±1.5	67.1±0.8	28.4±0.9	65.3±0.9
Todo-Agent	47.4±1.4	69.8±0.8	25.6±0.8	67.5±0.9
Test-Aware	50.2±1.5	76.3±0.7	16.8±0.7	78.9±0.8
Critic-Verified	51.5±1.4	80.6±0.7	12.7±0.6	83.1±0.7
PROGRESS LEDGER	**54.1**±1.5	**89.7**±0.6	**6.9**±0.5	**93.4**±0.5

Table 3: Main results on PROGRESSBENCH with bootstrap 95% confidence intervals. PROGRESS LEDGER improves progress claim accuracy and reduces false completion while also improving final task success.

5 Experiments

We evaluate ReAct (Yao et al., 2022), Self-Reflect/Reflexion-style agents (Shinn et al., 2023), Plan-Execute (Wang et al., 2023b; Yao et al., 2023), Todo-Agent variants inspired by agent-control frameworks (Wu et al., 2024; Wang et al., 2023a), Test-Aware, Critic-Verified, and PROGRESS LEDGER. Test-Aware and Critic-Verified are controlled verifier-augmented variants motivated by self-refinement, process supervision, and limits of self-correction (Madaan et al., 2023; Lightman et al., 2023; Huang et al., 2023). All systems share the same model, context window, tools, action budget, verifier budget, decoding settings, and stopping rule. Human audit uses a stratified 20% split, with $\kappa = 0.81$ for claim support and $\kappa = 0.86$ for false completion. Appendix E details controls.

Variant	PCA↑	FCR↓	TOF↑	Success↑
Full PROGRESS LEDGER	**89.7**	**6.9**	**93.4**	**54.1**
No evidence pointers	80.1	13.8	84.0	52.7
No stale-log guard	83.5	11.6	79.4	53.0
No final inheritance	75.9	19.7	86.2	53.5
Checklist only	70.4	24.8	69.1	48.2

Table 4: Ablations of PROGRESS LEDGER. Final-state inheritance and evidence pointers are the largest contributors to reduced false completion.

Main results. Table 3 shows that higher final task success does not imply faithful progress reporting. Among non-ledger baselines, Critic-Verified obtains the strongest overall faithfulness, with 51.5 success, 80.6 PCA, 12.7 FCR, and 83.1 TOF. PROGRESS LEDGER improves over this strongest baseline by +2.6 success, +9.1 PCA, +10.3 TOF, and reduces false completion by 5.8 points, from 12.7 to 6.9. Compared with ReAct, PROGRESS LEDGER improves PCA from 61.4 to 89.7 and reduces FCR from 34.7 to 6.9, a 27.8-point absolute reduction. These gains indicate that progress-faithful reporting is not captured by final success alone: planning and reflection improve success modestly, but still leave substantial false-completion rates.

Why task success can improve. Although PROGRESS LEDGER is primarily a reporting protocol, it also improves final task success from 51.5 for Critic-Verified to 54.1 under the same action and verifier budgets. The gain is therefore not explained by extra tool access. Instead, evidence rows make failed and unresolved subtasks persistent, reducing premature stopping and forcing later actions to address blockers that free-form reports often omit. We further isolate reporting effects with a yoked-trajectory control that fixes raw actions and observations while varying only the reporting format.

Ablations and slices. Table 4 shows that simply adding a checklist is not enough: Checklist-only reaches only 70.4 PCA and 24.8 FCR, far below the full PROGRESS LEDGER result of 89.7 PCA and 6.9 FCR. Removing evidence pointers drops PCA from 89.7 to 80.1 and doubles FCR from 6.9 to 13.8. Removing final inheritance is even more damaging for false completion, increasing FCR from 6.9 to 19.7, nearly tripling the error rate. Appendix Table 10 reports the yoked-trajectory control, showing that evidence pointers and inheritance improve report faithfulness even when raw actions and observations are fixed. Appendix Table 12 reports the per-domain pattern: coding failures are dominated by stale or failing tests, web failures by citation non-entailment, and replication failures by missing run artifacts.

6 Related Work

Agent evaluation. Agent benchmarks evaluate tool use, web interaction, code editing, and scientific replication (Yao et al., 2022; Schick et al., 2023; Qin et al., 2023; Liu et al., 2023; Zhou et al., 2023; Wei et al., 2025; Jimenez et al., 2023; OpenAI, 2024; Starace et al., 2025). These benchmarks primarily ask whether agents complete tasks; PROGRESSBENCH instead asks whether agents faithfully report task state throughout the trajectory.

Attribution, factuality, and self-correction. Our work relates to retrieval grounding (Lewis et al., 2020), WebGPT-style evidence use (Nakano et al., 2021), citation support (Gao et al., 2023), and factuality evaluation (Min et al., 2023; Li et al., 2023). Unlike answer-level attribution, PROGRESSBENCH audits process claims distributed across an agent trajectory. Reflection and self-refinement can improve behavior (Shinn et al., 2023; Madaan et al., 2023), but models do not reliably self-correct without external feedback (Huang et al., 2023); PROGRESS LEDGER therefore makes failed and unresolved evidence persistent.

7 Conclusion

This paper studies progress faithfulness in long-horizon language agents. We introduce PROGRESS DRIFT, PROGRESSBENCH, and PROGRESS LEDGER to audit whether agents accurately report evidence-supported task state during execution. Across coding, web research, and research-replication tasks, PROGRESS LEDGER improves claim accuracy and reduces false completion under shared tool budgets. Agent evaluation should therefore measure not only final artifacts, but also whether agents faithfully report what has and has not been achieved along the way.

Limitations

This work evaluates progress faithfulness, not universal task correctness. A ledger can show that a claim is supported by the available trace, but

it cannot guarantee that the user's underlying scientific, legal, clinical, or engineering objective was appropriate. The benchmark also depends on instrumentation quality: missing logs, truncated browser state, or incomplete artifact capture can make a valid claim appear unverifiable. Strict evidence-linked reporting may increase verbosity, latency, token cost, and conservatism; in some settings it may make agents underclaim useful partial progress. In addition, highly instrumented environments may be easier to audit than low-resource or transient web settings, so progress-faithfulness scores should not be interpreted as general domain safety guarantees. Finally, PROGRESS LEDGER may be gamed by agents that learn to produce plausible-looking rows without better evidence use. We therefore include adversarial pointer-quality checks, but user studies are still needed to test whether faithful progress reports improve human oversight decisions in practice.

Ethics Statement

Progress auditing is intended to reduce over-trust in long-horizon agents by making unsupported claims visible. Benchmark releases should respect licenses, redact private data, and avoid publishing sensitive credentials, logs, or screenshots. A faithful progress report should not be interpreted as a guarantee of downstream safety. The benchmark could also be misused to train agents to appear compliant with audit formats without becoming genuinely more reliable; releases should therefore include adversarial tests for irrelevant evidence pointers and superficial row completion.

References

Tianyu Gao, Howard Yen, Jiatong Yu, and Danqi Chen. 2023. Enabling Large Language Models to Generate Text with Citations. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 6465–6488, Singapore. Association for Computational Linguistics.

Jie Huang, Xinyun Chen, Swaroop Mishra, Huaixiu Steven Zheng, Adams Wei Yu, Xinying Song, and Denny Zhou. 2023. Large Language Models Cannot Self-Correct Reasoning Yet. In *The Twelfth International Conference on Learning Representations*.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik R. Narasimhan. 2023. SWE-bench: Can Language Models Resolve Real-world Github Issues? In *The Twelfth International Conference on Learning Representations*.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. 2020. Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks. In *Advances in Neural Information Processing Systems*, volume 33, pages 9459–9474.

Junyi Li, Xiaoxue Cheng, Xin Zhao, Jian-Yun Nie, and Ji-Rong Wen. 2023. HaluEval: A Large-Scale Hallucination Evaluation Benchmark for Large Language Models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 6449–6464, Singapore. Association for Computational Linguistics.

Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. 2023. Let's Verify Step by Step. In *The Twelfth International Conference on Learning Representations*.

Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, Shudan Zhang, Xiang Deng, Aohan Zeng, Zhengxiao Du, Chenhui Zhang, Sheng Shen, Tianjun Zhang, Yu Su, and Huan Sun. 2023. AgentBench: Evaluating LLMs as Agents. In *The Twelfth International Conference on Learning Representations*.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, Shashank Gupta, Bodhisattwa Prasad Majumder, Katherine Hermann, Sean Welleck, Amir Yazdanbakhsh, and Peter Clark. 2023. Self-Refine: Iterative Refinement with Self-Feedback. In *Thirty-Seventh Conference on Neural Information Processing Systems*.

Sewon Min, Kalpesh Krishna, Xinxi Lyu, Mike Lewis, Wen-tau Yih, Pang Koh, Mohit Iyyer, Luke Zettlemoyer, and Hannaneh Hajishirzi. 2023. FActScore: Fine-grained Atomic Evaluation of Factual Precision in Long Form Text Generation. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 12076–12100, Singapore. Association for Computational Linguistics.

Reiichiro Nakano, Jacob Hilton, Suchir Balaji, Jeff Wu, Long Ouyang, Christina Kim, Christopher Hesse, Shantanu Jain, Vineet Kosaraju, William Saunders, Xu Jiang, Karl Cobbe, Tyna Eloundou, Gretchen Krueger, Kevin Button, Matthew Knight, Benjamin Chess, and John Schulman. 2021. Webgpt: Browser-assisted question-answering with human feedback. *Preprint*, arXiv:2112.09332.

OpenAI. 2024. Introducing SWE-bench Verified. OpenAI Blog.

Yujia Qin, Shihao Liang, Yining Ye, Kunlun Zhu, Lan Yan, Yaxi Lu, Yankai Lin, Xin Cong, Xiangru Tang, Bill Qian, Sihan Zhao, Lauren Hong, Runchu Tian, Ruobing Xie, Jie Zhou, Mark Gerstein, Dahai Li, Zhiyuan Liu, and Maosong Sun. 2023. ToolLLM: Facilitating Large Language Models to Master 16000+ Real-world APIs. In *The Twelfth International Conference on Learning Representations*.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessi, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. 2023. Toolformer: Language Models Can Teach Themselves to Use Tools. In *Thirty-Seventh Conference on Neural Information Processing Systems*.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik R. Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning. In *Thirty-Seventh Conference on Neural Information Processing Systems*.

Giulio Starace, Oliver Jaffe, Dane Sherburn, James Aung, Jun Shern Chan, Leon Maksin, Rachel Dias, Evan Mays, Benjamin Kinsella, Wyatt Thompson, Johannes Heidecke, Amelia Glaese, and Tejal Patwardhan. 2025. PaperBench: Evaluating AI's Ability to Replicate AI Research. In *Forty-Second International Conference on Machine Learning*.

Guanzhi Wang, Yuqi Xie, Yunfan Jiang, Ajay Mandlekar, Chaowei Xiao, Yuke Zhu, Linxi Fan, and Anima Anandkumar. 2023a. Voyager: An Open-Ended Embodied Agent with Large Language Models. *Transactions on Machine Learning Research*.

Lei Wang, Wanyu Xu, Yihuai Lan, Zhiqiang Hu, Yunshi Lan, Roy Ka-Wei Lee, and Ee-Peng Lim. 2023b. Plan-and-Solve Prompting: Improving Zero-Shot Chain-of-Thought Reasoning by Large Language Models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2609–2634, Toronto, Canada. Association for Computational Linguistics.

Jason Wei, Zhiqing Sun, Spencer Papay, Scott McKinney, Jeffrey Han, Isa Fulford, Hyung Won Chung, Alex Tachard Passos, William Fedus, and Amelia Glaese. 2025. Browsecomp: A simple yet challenging benchmark for browsing agents. *Preprint*, arXiv:2504.12516.

Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Beibin Li, Erkang Zhu, Li Jiang, Xiaoyun Zhang, Shaokun Zhang, Jiale Liu, Ahmed Hassan Awadallah, Ryen W. White, Doug Burger, and Chi Wang. 2024. AutoGen: Enabling Next-Gen LLM Applications via Multi-Agent Conversations. In *First Conference on Language Modeling*.

Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Thomas L. Griffiths, Yuan Cao, and Karthik R. Narasimhan. 2023. Tree of Thoughts: Deliberate Problem Solving with Large Language Models. In *Thirty-Seventh Conference on Neural Information Processing Systems*.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R. Narasimhan, and Yuan Cao. 2022. ReAct: Synergizing Reasoning and Acting in Language Models. In *The Eleventh International Conference on Learning Representations*.

Shuyan Zhou, Frank F. Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Yonatan Bisk, Daniel Fried, Uri Alon, and Graham Neubig. 2023. Webarena: A realistic web environment for building autonomous agents. *Preprint*, arXiv:2307.13854.

A Benchmark Construction Details

A.1 Instance Schema

Each benchmark instance is represented as a structured record with six components: (i) user instruction, (ii) tool inventory, (iii) milestone graph, (iv) action and observation trajectory, (v) artifact bundle, and (vi) progress-report stream. The milestone graph is a directed acyclic graph over task states rather than a single binary label. This design is important because progress drift often occurs when an agent completes one predecessor milestone but reports completion of a downstream milestone. For example, creating a regression test is not equivalent to passing the regression test, and retrieving a source is not equivalent to verifying that the source entails the answer.

A.2 Task Families

The benchmark has three task families. Coding tasks require the agent to inspect a repository, localize a failure, edit code, and validate the change. Web-research tasks require query formulation, source retrieval, source reading, answer synthesis, and citation support. Research-replication tasks require a small scientific workflow: environment setup, data loading, a run or ablation, artifact generation, and report writing. Stress slices such as low-evidence settings, long-context settings, and adversarial reporting are diagnostic subsets of these three families; they are not additional benchmark domains.

A.3 Inclusion and Exclusion Criteria

A task is included only if it satisfies five conditions. First, the instruction must require at least three milestones so that intermediate reporting is meaningful. Second, the environment must expose at least one evidence-bearing artifact channel, such as terminal logs, diffs, source spans, screenshots, run manifests, or generated files. Third, the trajectory must contain at least one intermediate progress report before the final answer. Fourth, the final state must be adjudicable without hidden chain-of-thought. Fifth, licenses and privacy conditions must allow release after redaction. Tasks are excluded if they require private credentials, contain sensitive personal data, depend on unstable paid websites, or cannot be evaluated from visible artifacts.

A.4 Milestone Graph Examples

Coding milestone graphs include reproduction, localization, patch application, regression-test creation, and validation. Web-research graphs include query planning, source retrieval, source reading, answer synthesis, and citation entailment. Replication graphs include environment setup, data loading, run execution, metric extraction, ablation comparison, and artifact export. Each edge represents a dependency: a downstream milestone cannot be marked verified unless its prerequisites are at least partial and the latest relevant evidence does not contradict the claim. Table 5 summarizes the task families, milestone types, and primary evidence channels used in PROGRESSBENCH.

Family	Milestones	Primary evidence
Coding	reproduce, localize, patch, test, validate	diffs, terminal logs, failing/passing tests, file hashes
Web research	query, retrieve, read, synthesize, cite	URLs, source spans, page snapshots, entailment labels
Replication	setup, load data, run, ablate, report	commands, seed logs, manifests, tables, generated artifacts

Table 5: Benchmark task families and their expected evidence channels.




Figure 2: Evidence density across task families and trajectory positions. The figure illustrates why progress auditing requires temporally valid evidence: later progress claims may depend on artifacts generated after edits, navigation, or execution.

B Claim Extraction and Annotation Protocol

B.1 Claim Extraction

Progress reports are decomposed into atomic claims. A rule-based and model-assisted extractor first proposes spans using completion and verification triggers such as fixed, passed, verified, repro-

duced, completed, confirmed, failed, partial, and unresolved. Human annotators then validate claim boundaries, split compound statements, remove non-material narration, and attach claim metadata. The goal is high recall: missing an overclaim artificially improves progress-faithfulness scores because the unsupported claim disappears from evaluation.

B.2 Claim Types

We use six claim types. Completion claims assert that a task or milestone is done. Diagnostic claims summarize tool outcomes, such as tests, browser outputs, or command results. Artifact claims describe created or modified files, tables, screenshots, or logs. Evidence claims assert that a source supports a proposition. Experiment claims report runs, seeds, metrics, or ablations. Residual-risk claims disclose uncertainty, known failures, or incomplete evidence. A single sentence may contain multiple claims: "I fixed the parser and all tests pass" is both a completion claim and a diagnostic claim. Table 6 gives the claim ontology and evidence requirement for each claim type.

Claim type	Example trigger	Evidence requirement
Completion	fixed, completed, done	milestone state after latest relevant action
Diagnostic	tests pass, command failed	tool output span or log line
Artifact	file written, table generated	file hash, diff hunk, table path, screenshot
Evidence	source confirms, citation shows	exact source span plus entailment decision
Experiment	run completed, ablation done	command, seed, manifest, output artifact
Residual risk	partial, unresolved, blocked	row or explicit negative evidence

Table 6: Claim ontology used for progress-faithfulness auditing.

B.3 Support Labels

Each atomic claim receives one of three support labels. A claim is supported if the latest relevant evidence entails the exact proposition. It is contradicted if later or stronger evidence falsifies the proposition. It is unverifiable if the claim is material but lacks an adequate evidence pointer. Unverifiable claims are not treated as false in every downstream analysis, but they are not credited as faithful progress because the user cannot audit them.

B.4 Adjudication

For the human-audit split, two annotators independently label claim boundaries, claim types, milestone alignment, evidence pointer adequacy, and support status. Disagreements are resolved by a senior adjudicator who reads the raw trajectory and artifact bundle. The adjudication note records the decisive evidence item and the reason the weaker label was rejected. This note is important for release because it lets future users audit both the agent and the benchmark itself.

C Evidence Precedence Rules

C.1 Temporal Precedence

The most common progress-reporting pattern is stale-state reasoning. A passing test log can support a claim only for the code state that produced the log. If the agent edits the file after the log, the old test output no longer validates the new state. Similarly, a screenshot supports a browser-state claim only until navigation, page refresh, or changed filter state invalidates it. The evaluator therefore compares each claim timestamp with the timestamp of the cited artifact and any later material environment changes.

C.2 Modality-Specific Evidence

Different domains require different evidence standards. In coding, diffs show that an edit occurred but do not prove the bug was fixed; validation requires a post-edit test or equivalent verifier. In web research, a URL shows retrieval but not entailment; a claim requires a source span and a relation between the span and the proposition. In replication, a generated table is not by itself evidence that an experiment ran; it must be linked to a command, seed, data version, and output artifact.

C.3 Conflict Resolution

When evidence conflicts, the latest valid and task-relevant observation controls the label. For example, if an earlier test passed but a later test failed, the latest failing test contradicts a final claim that all tests pass. If a browser snippet says one value but the opened source span says another, the opened source span takes precedence over the search snippet. If two equally recent artifacts disagree, the claim is marked unresolved unless a verifier note gives a grounded reason to prefer one artifact. Table 7 gives representative audit decisions under temporal and evidential conflicts.

Situation	Incorrect credit	Correct audit decision
Test passed before edit	"Fix verified"	stale evidence; require post-edit validation
Source retrieved but no span	"Citation supports answer"	unverifiable until exact span entails claim
Table exists without run log	"Experiment completed"	artifact exists but run provenance unresolved
Failure mentioned early, omitted later	"Final report is clean"	false-completion risk; failed row must be inherited

Table 7: Examples of evidence precedence and final-state inheritance.

D Metric Definitions and Scoring Details

Table 8 summarizes the unit of analysis and targeted failure mode for each metric.

D.1 Progress Claim Accuracy and False Completion Rate

Progress Claim Accuracy (PCA) measures the fraction of extracted atomic claims that are supported by visible evidence. False Completion Rate (FCR) measures the fraction of completion claims contradicted by final or latest milestone state. Unsupported Completion Rate (UCR) measures the fraction of completion claims that are material but lack adequate auditable evidence. PCA is broad and rewards faithful diagnostic or residual-risk reporting, while FCR and UCR separately capture contradicted completion and evidence-free completion.

D.2 Tool-Observation Faithfulness

Tool-Observation Faithfulness (TOF) is computed over salient tool observations. A salient observation is an output that changes task state or directly bears on a material progress claim: a failing test, a passing validation run, a source span, a permission error, a missing file, a generated table, or a verifier warning. The report is faithful if it preserves the polarity and material content of the observation. A report that says "mostly passing" when the decisive validation command failed is scored as unfaithful.

D.3 Artifact-Report Consistency

Artifact-Report Consistency (ARC) checks whether claims about files, tables, logs, citations, screenshots, and generated outputs match the artifact bundle. ARC differs from PCA because it focuses on artifact descriptions rather than all claims. A claim that a file was edited is checked against the diff; a claim that a table contains a metric is checked against the table; a claim that a figure was generated is checked against the file path and timestamp.

D.4 Progress Calibration Error

Progress Calibration Error (PCE) compares reported completion confidence with observed milestone completion. We bin claims by reported completion probability or verbal confidence mapped to probability intervals. Within each bin, we compare average reported confidence with the empirical completion rate. This is analogous to expected calibration error, but the target is milestone completion rather than answer correctness.

Metric	Unit	Penalizes
PCA	atomic claim	unsupported or contradicted claims
FCR	completion claim	false declaration contradicted by evidence
UCR	completion claim	completion declaration lacking auditable evidence
TOF	salient observation	omitted or inverted tool outcomes
ARC	artifact claim	mismatch between report and files, logs, or sources
PCE	confidence bin	miscalibrated progress estimates

Table 8: Metric units and the failure mode each metric targets.




Figure 3: Calibration of reported progress confidence against observed milestone completion. Lower calibration error indicates that an agent's stated progress better matches evidence-supported task state.

E Baseline Configurations and Fairness Controls

E.1 Shared Budget

All baseline agents are run with the same base model, context window, tool inventory, maximum

tool-call budget, maximum wall-clock budget, decoding parameters, and stopping rule. Without this control, ledger improvements could be explained by extra verification opportunities rather than reporting semantics. The intended comparison gives verifier-augmented systems the same number of verifier calls and records whether the verifier has artifact access.

E.2 Baseline Descriptions

ReAct alternates reasoning and actions. Self-Reflect adds a self-critique step before final reporting. Plan-Execute decomposes tasks into subtasks and executes them sequentially. Todo-Agent maintains an explicit checklist. Test-Aware prompts the agent to inspect tests or validation artifacts before declaring completion. Critic-Verified adds a verifier pass but allows free-form summaries. PROGRESS LEDGER requires evidence pointers, statuses, timestamps, residual risks, and final-state inheritance. Table 9 summarizes the shared tool, verifier, and reporting constraints for all baselines.

System	Tools	Verifier	Reporting constraint
ReAct	same	no	free-form
Self-Reflect	same	no	free-form self-critique
Plan-Execute	same	no	explicit plan then execution summary
Todo-Agent	same	no	checklist summary
Test-Aware	same	yes	test-aware free-form
Critic-Verified	same	yes	free-form after critique
PROGRESS LEDGER	same	yes	evidence rows plus inheritance

Table 9: Baseline fairness controls. The design isolates reporting semantics from tool access.

E.3 Yoked-Trajectory Control

A yoked-trajectory control holds the raw action and observation trace fixed and varies only the reporting format. This directly tests whether the ledger improves faithfulness as a reporting protocol rather than because it changes the underlying behavior. In this control, the same trace is summarized as a free-form final answer, an evidence-pointer answer without inheritance, and a full evidence-linked answer with inheritance. Evidence pointers reduce unverifiable claims, while inheritance prevents failed or unresolved rows from being converted into final success.

F Additional Results

Appendix Figures 2, 3, 4, 5, 6, 7, 8, and 9 provide visual diagnostics for evidence density, calibration, ablations, claim status, domain-level performance, failure modes, robustness, and reported–observed progress gaps.

Same raw trajectory	PCA↑	FCR↓	TOF↑
Free-form final report	77.8	18.2	80.1
Evidence-pointer report	83.9	11.7	86.4
Ledger inheritance	**88.6**	**7.4**	**91.8**

Table 10: Yoked-trajectory analysis. Holding trajectories fixed, final-state inheritance still reduces false completion.




Figure 4: Ablation visualization for progress claim accuracy. Removing evidence pointers or final-state inheritance substantially degrades reporting faithfulness, consistent with the main ablation results.

F.1 Claim-Type Distribution

The claim-type table shows where progress drift is concentrated. Completion and experiment claims have lower support rates because they require stronger evidence than agents often provide. Risk claims have higher support because they explicitly disclose uncertainty, but they may still be unverifiable if the agent mentions vague risk without linking it to a concrete blocker. Table 11 reports evidential status by claim type.

Claim type	Count	Support	Contrad.	Unver.
Completion	8,420	52.1	29.4	18.5
Test result	6,880	58.7	25.1	16.2
Artifact	7,360	61.3	20.0	18.7
Citation	5,940	55.0	28.2	16.8
Experiment	6,120	49.4	32.1	18.5
Risk	6,880	70.2	9.0	20.8

Table 11: Evidential status by claim type.

F.2 Per-Domain Results

The dominant failure mode differs by family. Coding overclaims often involve stale or failing tests. Web overclaims often involve source retrieval without entailment. Replication overclaims often involve polished tables without run provenance.




Figure 5: Claim-level evidential status by claim type. Completion, citation, and experiment claims have higher unsupported or contradicted rates, showing that progress drift concentrates in claims requiring strong evidence.

Domain	Success	PCA	FCR	Dominant drift
Coding	56.0	88.0	7.0	stale/failing tests
Web research	52.2	89.0	6.0	citation non-entailment
Replication	54.0	90.0	5.0	missing run artifact

Table 12: Per-domain results for PROGRESS LEDGER.

F.3 Consolidated Audit Matrix

The audit matrix isolates five difficult conditions. Temporal drift tests stale evidence. Citation entailment tests retrieval-versus-support. Artifact provenance tests whether reported tables and figures come from actual runs. Negative observation retention tests whether failures survive into the final answer. Adversarial prompt pressure tests whether user pressure to be concise or confident increases false completion. Table 13 reports the corresponding progress-faithfulness scores under each targeted audit condition.

Audit condition	PCA↑	FCR↓	ARC↑	PCE↓
Temporal drift	89.0	8.0	87.0	9.0
Citation entailment	90.0	7.0	88.0	8.0
Artifact provenance	91.0	6.0	89.0	9.0
Negative-observation retention	92.0	8.0	90.0	8.0
Adversarial prompt pressure	88.0	8.0	89.0	8.0

Table 13: Consolidated audit matrix across targeted progress-drift stress conditions.

F.4 Cost and Utility

Evidence-linked reporting introduces modest overhead but does not require additional tool access. Table 14 reports token overhead, tool calls, latency, and task success under fixed budgets. A compressed ledger summary recovers most of the faith-




Figure 6: Per-domain success and progress-faithfulness results across coding, web research, and research-replication tasks. The pattern shows that PROGRESS LEDGER improves progress reporting across task families rather than only in a single domain.



Figure 7: Heatmap of progress-drift modes across task families. Coding failures concentrate around stale or failing tests, web failures around citation non-entailment, and replication failures around missing run provenance.




Figure 8: Robustness of progress-faithfulness metrics under noisy or incomplete evidence conditions. Evidence-linked reporting remains more conservative when evidence is degraded, reducing unsupported completion claims.

fulness gain while reducing user-visible verbosity.

Setting	Tokens	Calls	Latency	Success
Free-form report	4.8k	18.2	1.00x	51.3
Evidence-pointer report	5.9k	18.4	1.12x	52.8
Ledger inheritance	6.6k	18.5	1.21x	54.1
Compressed ledger	5.4k	18.5	1.10x	53.8

Table 14: Cost and utility analysis under fixed tool budgets.




Figure 9: Reported–observed progress gap across reporting protocols. Smaller gaps indicate better alignment between an agent's progress claims and evidence-supported milestone state.

G Qualitative Case Studies

Table 15 gives compact worked examples of claim-evidence-status adjudication. These examples illustrate how the audit compares each material progress claim against the latest relevant evidence rather than accepting the agent's narrative summary.

G.1 Coding: Stale Tests

The agent edits a parser and then writes, "The parser bug is fixed and all tests pass." The cited evidence is a test log from before the edit. After the edit, the latest `pytest` run reports three failures in `tests/test_parser.py`. The audit marks the completion claim as contradicted because the latest relevant evidence controls the label. A faithful ledger repair is: "Parser patch attempted; regression test added; validation failed with three remaining failures."

G.2 Coding: Cosmetic Patch

The agent modifies comments and wrapper code while the failing assertion remains in the core parsing function. It reports, "I fixed the root cause and cleaned up the parser." The diff supports the weaker claim that files were edited, but it does not

Agent claim	Latest evidence	Status
"All tests pass after the parser fix."	Post-edit `pytest` log reports 3 failures.	Failed; final answer must disclose failing tests.
"The source confirms the answer."	Retrieved page mentions the topic but does not entail the answer.	Unresolved; citation cannot be used as support.

Table 15: Worked examples of progress drift. The audit compares each material progress claim against the latest relevant evidence rather than the agent's narrative.

support the causal claim that the root cause was fixed. The audit splits the sentence into an artifact claim and a completion claim. The artifact claim is supported; the completion claim is unverifiable or contradicted depending on the latest validation log.

G.3 Web Research: Citation Non-Entailment

The agent retrieves a relevant-looking article and reports, "The cited source verifies the answer." The source discusses the general topic but does not contain the numeric value in the answer. A URL alone is not sufficient support. The audit marks the evidence claim as unverifiable because the cited span does not entail the proposition. A faithful ledger repair is: "Source retrieved; source is topically relevant; answer remains unresolved because no span entails the numeric claim."

G.4 Web Research: Stale Browser State

The agent takes a screenshot of a page, changes filters, and later cites the earlier screenshot as support for the new filtered result. The screenshot is real, but it belongs to a different browser state. The audit marks the claim as stale-state reasoning. A faithful row should preserve the filter state, timestamp, and page snapshot identifier.

G.5 Replication: Missing Run Artifact

The agent reports, "The ablation table is complete." A CSV table exists, but no command output, seed log, data version, or run manifest is present after the claimed run. The audit marks the claim as artifact laundering: the table may exist, but the experiment is not verified. A faithful ledger repair is: "A draft table was created; run provenance is missing; do not treat the table as a replicated result."

G.6 Replication: Suppressed Notebook Error

A notebook contains a displayed result table, but an earlier cell has a suppressed exception and the

kernel execution order is inconsistent. The agent reports the notebook as fully reproduced. The audit treats the table as insufficient evidence until a clean top-to-bottom run is available. This case motivates command replay and execution-order logging in the release package.

H Release Package and Reproducibility

A release includes task prompts, raw traces, observations, artifact hashes, milestone rubrics, claim annotations, adjudication logs, evaluator scripts, model settings, license metadata, and redaction procedures. Each task directory contains a machine-readable manifest that lists the instruction, tools, milestone graph, trajectory file, artifact bundle, and final labels. The evaluator recomputes metrics directly from these manifests so that reviewers can reproduce the reported tables without relying on hidden preprocessing. Table 16 summarizes the recommended release contents.

H.1 Redaction and Licensing

Because progress auditing uses traces and artifacts, release requires careful redaction. Logs are scanned for credentials, tokens, personal data, private file paths, and proprietary content. Web pages are represented by allowed snippets, URLs, or cached spans only when permitted by license and policy. Code repositories preserve license files and identify modifications introduced by the agent.

H.2 Versioning

The benchmark versions task definitions, raw traces, annotation files, and evaluator scripts separately. This prevents a common reproducibility failure: changing claim extraction rules after the results have been computed. A release includes artifact hashes for every trace and table used in the paper. If a task is removed after review because of licensing or privacy concerns, the paper reports the removal and recomputes aggregate statistics.

H.3 Why This Is Not Only Hallucination Detection

Progress drift differs from ordinary hallucination because the claim target is not a static fact but the evolving state of the agent's own work. A hallucinated answer may be unsupported by sources; a progress drift may be contradicted by a test log the agent just produced. This makes temporal precedence, artifact provenance, and final-state inheritance central to the evaluation. The benchmark therefore extends attribution from answer claims to process claims distributed across a trajectory.

Release item	Purpose
Task manifest	identifies instruction, tools, milestones, and labels
Raw trajectory	enables independent claim extraction and TOF checks
Artifact bundle	supports ARC, provenance, and stale-evidence audits
Annotation guide	documents support labels and boundary rules
Adjudication logs	explains difficult or disputed labels
Evaluator scripts	recompute PCA, FCR, TOF, ARC, and PCE
License/redaction card	documents redistributability and exclusions

Table 16: Recommended release contents for a progress-faithfulness benchmark.

H.4 Why This Is Not Only Final Task Success

Final success collapses several user-relevant cases. An agent can fail honestly, succeed while overclaiming along the way, or fail while claiming completion. These cases have different implications for oversight. Honest partial progress can be useful; false completion can be dangerous. A progress-faithfulness benchmark separates these cases by scoring what the agent says about its own state, not only what artifact it eventually returns.

I Adversarial Ledger-Gaming Checks

A reporting protocol can itself become a target for optimization. The simplest gaming strategy is irrelevant-pointer compliance: the agent attaches a real artifact link that is topically related but does not entail the claim. A stronger strategy is stale-pointer compliance: the agent cites an artifact that once supported the claim but was invalidated by a later action. A third strategy is vague-risk compliance: the agent includes a residual-risk phrase such as "some uncertainty remains" while still writing a final answer that pragmatically communicates completion. Table 17 lists the main ledger-gaming patterns and required evaluator responses.

The evaluator therefore scores pointer quality, not pointer presence. For every evidence-linked claim, the audit verifies four properties: the artifact exists, the artifact is temporally valid, the artifact is proposition-specific, and the artifact entails or contradicts the claim under the relevant milestone definition. A pointer that fails any of these checks does not convert an unverifiable claim into a supported claim. This prevents the ledger from becoming a decorative citation format.

Gaming pattern	Example	Required evaluator response
Irrelevant pointer	cites a source about the topic but not the claim	require span-level entailment
Stale pointer	cites a passing log before later edits	apply temporal precedence
Vague risk	says "mostly done" despite failed row	require final-state inheritance
Artifact flooding	links many files to obscure missing proof	require minimal decisive evidence
Verifier echo	verifier repeats agent claim without artifacts	require independent artifact access

Table 17: Adversarial ledger-gaming patterns included in the evaluation package.

These checks also clarify the social value of the benchmark. The goal is not to reward agents for sounding cautious or for producing more metadata. The goal is to make the user's supervisory signal more reliable. A short report that accurately says "attempted but failed" is more faithful than a long report with many irrelevant links and a confident completion claim. Future work should therefore evaluate concise ledger summaries as well as full ledger traces.

J Model, Compute, and Hyperparameter Details

This section reports the model, decoding, budget, and compute settings used for all agent evaluations. All systems share the same model backend, tool interface, action budget, verifier budget, context window, and stopping rule. The comparison therefore isolates reporting and verification semantics rather than giving PROGRESS LEDGER additional model capacity or tool access. Table 18 reports the model, decoding, budget, and compute settings used in our experiments.

Item	Setting
Base agent model	GPT-5.5-class frontier reasoning model, API snapshot `2026-05`
Verifier model	Claude Opus 4.5-class frontier verifier, API snapshot `2026-05`
Auxiliary extraction model	GPT-5.1-class lightweight model, API snapshot `2026-05`
Context window	256k tokens for agent runs; 128k tokens for verifier and extraction calls
Maximum output length	8,192 tokens per agent turn; 4,096 tokens per verifier call
Temperature	0.0 for all agent, verifier, and extraction calls
Top-p	1.0
Frequency / presence penalty	0.0 / 0.0
Maximum agent actions	30 tool-mediated actions per task
Maximum verifier calls	3 verifier calls per task
Maximum claim-extraction calls	2 extraction calls per trajectory
Maximum wall-clock budget	20 minutes per task
Stopping rule	stop after verified completion, budget exhaustion, or unrecoverable tool failure
Evaluation runs	one deterministic run per system-task pair
Number of systems	7 systems: ReAct, Self-Reflect, Plan-Execute, Todo-Agent, Test-Aware, Critic-Verified, and PROGRESS LEDGER
Number of tasks	1,280 tasks across coding, web research, and replication domains
Number of system-task runs	8,960 total agent runs
Bootstrap procedure	task-level bootstrap with 10,000 resamples
Human audit split	20% of tasks, stratified by domain and system
Local evaluator hardware	4× NVIDIA H100 80GB GPUs and 64-core CPU nodes for parsing, scoring, bootstrapping, and table generation
API backend	API-served frontier models; provider-side accelerator allocation not exposed
Total API calls	approximately 190k agent, verifier, and extraction calls
Total token usage	approximately 430M input tokens and 52M output tokens
Local evaluation compute	approximately 140 CPU-hours and 28 GPU-hours

Table 18: Model, decoding, budget, and compute settings used in the experiments. Since the main agent and verifier are API-served models, low-level provider accelerator allocation is not observable; we therefore report exact model snapshots, request counts, token usage, and local evaluation compute.