ACL 2026

The 11th Workshop on Computational Linguistics and Clinical Psychology

CLPsych

July 4, 2026

The ACL organizers gratefully acknowledge the support from the following sponsors.

School of Engineering & Applied Science
THE GEORGE WASHINGTON UNIVERSITY

University of Glasgow

ARIEL UNIVERSITY

©2026 Association for Computational Linguistics

Order copies of this and other ACL proceedings from:

Association for Computational Linguistics (ACL)
317 Sidney Baker St. S
Suite 400 - 134
Kerrville, TX 78028
USA
Tel: +1-855-225-1962
acl@aclweb.org

ISBN 979-8-89176-421-7

Introduction

Mental health remains a critical issue. Globally, mental health conditions rank among the top causes of disability [7, 9], and the economic burden of mental health issues, including neurological and substance use disorders, is expected to exceed $16 trillion from 2011 to 2030 [2]. In the United States alone, suicide ranked among the top nine leading causes of death for individuals aged 10-64 in 2020 [3], and was the second leading cause of death in 2023 for people ages 10–14, 15–24, and 25–44 [4]. The COVID-19 pandemic has further exacerbated these mental health challenges. Research by Sheridan et al. [8] indicates that suicide attempts among children aged 10-12 have increased more than five-fold from 2010 to 2020. The deployment of Large Language Models (LLMs) in computational psychiatry has expanded from risk prediction to explainable diagnostics. These models analyze complex linguistic biomarkers while simultaneously generating natural language rationales for their prognostic assessments [5, 6]. In light of this, for The Eleventh Workshop on Computational Linguistics and Clinical Psychology (CLPsych), we built on last year theme, and adopted the theme "Moving Beyond Labels to Understand Mental Health Dynamics".

CLPsych was a hybrid workshop that accommodated both in-person and remote participation. It was collocated with ACL'26, which took place in San Diego, California, USA on July 4th, 2026. Since 2014, CLPsych has been successful in bringing together people from different backgrounds (e.g. mental health experts, clinicians, and computational linguists), to share and discuss their work and results. Its central goal is to build bridges so that these different disciplines can integrate to improve our understanding of mental health issues, and to deliver better mental health treatments and diagnoses to everybody.

Building on previous CLPsych shared tasks (2022, 2025), this year's CLPsych 2026 shared task [1] advances longitudinal mental health modeling through the MIND framework, which represents psychological self-states using Affect, Behavior, Cognition, and Desire (ABCD) components. The shared task is organized into three main parts: (1) identifying adaptive and maladaptive self-state compositions and estimating their presence at the post level, (2) detecting Moments of Change such as abrupt switches and gradual escalations across timelines, and (3) generating structured summaries and recurrent dynamic signatures of mental health change processes.
Our program committee included mental health and technological experts, in order to provide all the papers with more informative feedback that addresses both aspects. CLPsych'26 received a total of 58 papers for the main workshop, of which 32 were accepted; all 13 submitted shared task system papers were also accepted. The organizing committee, with the help of the program committee scores, and feedback chose 7 main workshop papers and 4 shared task papers as oral presentations, and the rest were presented in the poster session.

CLPsych'26 also hosted excellent invited speakers and panelists. Our keynote speakers were Trevor Cohen (University of Washington) , and Dirk Hovy (Bocconi University in Milan). Additionally, we hosted a panel that included short talks and discussion by Colin Walsh (Vanderbilt University Medical Center), Justin Tauscher (University of Washington), Anat Brunstein Klomek (Reichman University), and moderated by Philip Resnik (University of Maryland, College Park).

The CLPsych organizing committee would like to extend special thanks to all the people that helped make the workshop a success. This includes and is not limited to our authors, shared task participants and organizers, program committee members. We also would like to thank the Association for Computational Linguistics for making this workshop possible. Special thanks to our generous sponsors: George Washington University, University of Glasgow, and Ariel University. Their funds helped to support the workshop's program, and provided support for attendees that don't have the financial means to cover their registration costs.

Aya Zirikly, Kfir Bar, Sean MacAvaney, Molly Ireland, Yaakov Ophir, Vasudha Varadarajan, Dana Atzil-Slonim, Steven Bedrick, and Bart Desmet

School of Engineering & Applied Science
THE GEORGE WASHINGTON UNIVERSITY

University of Glasgow
VIA VERITAS VITA

ARIEL UNIVERSITY

References

[1] Iqra Ali, Talia Tseriotou, Guy Dvir, Callum Chan, Yuxiang Zhou, Juan Antonio Lossio-Ventura, Ayal Klein, Aya Shamir, Dan Sayda, Anthony Hills, Aya Zirikly, Diana Inkpen, Dana Atzil-Slonim, and Maria Liakata. 2026. Overview of the clpsych 2026 shared task: Capturing and characterizing mental health changes through social media timeline dynamics. In *Proceedings of the 11th Workshop on Computational Linguistics and Clinical Psychology*. "Association for Computational Linguistics".

[2] David E Bloom, Elizabeth Cafiero, Eva Jané-Llopis, Shafika Abrahams-Gessel, Lakshmi Reddy Bloom, Sana Fathima, Andrea B Feigl, Tom Gaziano, Ali Hamandi, Mona Mowafi, et al. 2012. The global economic burden of noncommunicable diseases. Technical report, Program on the Global Demography of Aging.

[3] Daniel C Ehlman. 2022. Changes in suicide rates—united states, 2019 and 2020. *MMWR. Morbidity and Mortality Weekly Report*, 71.

[4] Centers for Disease Control, Prevention, National Center for Health Statistics, et al. 2024. Underlying cause of death, 2018-2022, single race request: Deaths occurring through 2022. *National Vital Statistics System, Mortality 2018-2022 On CDC WONDER Online Database*.

[5] Yu Jin, Jiayi Liu, Pan Li, Baosen Wang, Yangxinyu Yan, Huilin Zhang, Chenhao Ni, Jing Wang, Yi Li, Yajun Bu, et al. 2025. The applications of large language models in mental health: scoping review. *Journal of Medical Internet Research*, 27(1):e69284.

[6] Elma Kerz, Sourabh Zanwar, Yu Qiao, and Daniel Wiechmann. 2023. Toward explainable ai (xai) for mental health detection based on language behavior. *Frontiers in psychiatry*, 14:1219479.

[7] Christopher JL Murray, Alan D Lopez, World Health Organization, et al. 1996. *The global burden of disease: a comprehensive assessment of mortality and disability from diseases, injuries, and risk factors in 1990 and projected to 2020: summary*. World Health Organization.

[8] David C Sheridan, Sara Grusing, Rebecca Marshall, Amber Lin, Adrienne R Hughes, Robert G Hendrickson, and B Zane Horowitz. 2022. Changes in suicidal ingestion among preadolescent children from 2000 to 2020. *JAMA pediatrics*.

[9] Ma-Li Wong and Julio Licinio. 2001. Research and treatment approaches to depression. *Nature Reviews Neuroscience*, 2(5):343–351.

Organizing Committee

Workshop Chair

Ayah Zirikly, George Washington University

Organizing Committee

Kfir Bar, Reichman University
Sean MacAvaney, University of Glasgow
Molly Ireland, Receptiviti
Yaakov Ophir, Ariel University and University of Cambridge
Dana Atzil-Slonim, Bar-Ilan University
Vasudha Varadarajan, Carnegie Mellon University
Steven Bedrick, Oregon Health & Science University
Bart Desmet, Thomson-Reuters

Shared Task Organizers

Iqra Ali, Queen Mary University of London
Talia Tseriotou, Queen Mary University of London
Yuxiang Zhou, Queen Mary University of London
Dana Atzil-Slonim, Bar-Ilan University
Guy Dvir, Bar-Ilan University
Ayal Klein, Ariel University
Aya Shamir, Bar-Ilan University
Dan Sayda, Bar-Ilan University
Aya Zirikly, George Washington University
Maria Liakata, Queen Mary University of London & The Alan Turing Institute

Program Committee

Chairs

Iqra Ali, Queen Mary University of London
Kfir Bar, Reichman University
Sean Macavaney, University of Glasgow
Talia Tseriotou, Queen Mary University of London
Ayah Zirikly, Johns Hopkins University

Program Committee

Iyad Ait Hou, George Washington University
Mahmud Akhter, Queen Mary University of London
Falwah Alhamed, KACST
Maaz Amjad, Texas Tech University
Dana Atzil-Slonim, Psychology Department Bar-Ilan University
Khuyagbaatar Batsuren, National University of Mongolia
Ulya Bayram, Department of Electrical and Electronics Engineering, Çanakkale Onsekiz Mart University
Steven Bedrick, Oregon Health & Science University
Laura Biester, Middlebury College
Sergi Blanco-Cuaresma, Harvard-Smithsonian Center for Astrophysics
Ryan Boyd, University of Texas at Dallas
Ana-Maria Bucur, Università della Svizzera italiana
Igor Buyanov, Psytechlab
Honor Carolina, VA
Callum Chan, University of Ottawa
Jiyu Chen, Suncorp
Jenny Chim, Queen Mary University of London
Trevor Cohen, University of Washington
Hadar Dery, Haifa University
Bart Desmet, National Institutes of Health
Duc Do, Faculty of Information Technology, University of Engineering and Technology (UET-VNU), VNU
Guy Dvir, Bar-Ilan University
April Foreman, VA
Kathleen C. Fraser, University of Ottawa
Yusuke Fukazawa, Sophia University Graduate School
Salvatore Giorgi, Independent Researcher
Dimitris Gkoumas, Queen Mary University of London
Anmol Goel, TU Darmstadt
Nazli Goharian, Georgetown University
Kai Golan Hashiloni, Reichman University
Sharath Chandra Guntuku, University of Pennsylvania
Tal Guttman, Ben Gurion University
Lifeng Han, The University of Manchester
Keith Harrigian, Johns Hopkins University
Anthony Hills, Queen Mary University of London
Yu Hou, University of Southern California

Heyuan Huang, Johns Hopkins University
Kyomin Hwang, Seoul National University
Zac Imel, University of Utah
Loring Ingraham, George Washington University
Diana Inkpen, University of Ottawa
Molly Ireland, Receptiviti
Sarvnaz Karimi, CSIRO
Volodymyr Karpenko, Università della Svizzera italiana
Ayal Klein, Ariel University
Michelle Kuchuk, National Suicide Prevention Lifeline
Sunisth Kumar, University of Tokyo
Koushik L, Student, NITK
Allison Lahnala, McMaster University
Daeun Lee, Sungkyunkwan University
Daeun Lee, sungkyunkwan university
Changye Li, University of Washington
Zongxia Li, University of Maryland, College Park
Maria Liakata, Queen Mary University of London
Inna Lin, University of Washington
Karina Litvinova, University of Zurich
Juan Antonio Lossio-Ventura, National Institutes of Health
Pinxian Lu, Georgia Institute of Technology
Saad Mankarious, Cornell College
Stuart Middleton, University of Southampton
Do June Min, University of Michigan
Sarah Morgan, King's College London
Abdulrahman Morsy, George Washington University
Abir Naskar, researcher
Sergiu Nisioi, Human Language Technologies Research Center, University of Bucharest
Yaakov Ophir, Ariel University
Martin Orr, Auckland University Technology
David Piterman, NATAL
Judita Preiss, University of Sheffield
Emily Prud'hommeaux, Boston College
Sunny Rai, University of Pennsylvania
Surbhi Rathore, Symbl.ai
Elad Refoua, Department of Psychology, Bar Ilan University
Rebecca Resnik, Rebecca Resnik and Associates LLC
Philip Resnik, University of Maryland
Muhammad Rizwan, University of Ljubljana
Brian Roark, Google Inc.
Nathaniel Robinson, Johns Hopkins University
Nathan Roll, Stanford University
Christopher Rytting, University of Washington
Amit Sah, Indian Institute of Technology Delhi
Harshita Sahijwani, Dhirubhai Ambani Institute of Information and Communication Technology
Rupak Sarkar, University of Maryland, College Park
Dan Sayda, Bar-Ilan University
Jonathan Schler, HIT
Annika Marie Schoene, Northeastern University
Hendrik Schuff, TU Darmstadt

H. Andrew Schwartz, Stony Brook University
Aya Shamir, Bar-Ilan University
Loitongbam Singh, Indian Institute of Technology Ropar
Siddharth Singh, University of Amsterdam
Jiayu Song, queen Mary university of London
Richard Sproat, Sakana.ai
Chenkai Sun, University of Illinois at Urbana-Champaign
Justin Tauscher, University of Washington
Leili Tavabi, University of Southern California
Chaitze Tavens, UPJS Kosice Slovakia
Alexey Tolchinsky, GWU
Vu Tran, Japan Advanced Institute of Science and Technology
Trang Tran, Institute for Creative Technologies, University of Southern California
Adam Tsakalidis, Cedefop
Ahmet Yavuz Uluslu, University of Zurich
Adithya V Ganesan, Stony Brook University
Vasudha Varadarajan, Carnegie Mellon University
Ava Yahyapour, City University of New York
Andrew Yates, Johns Hopkins University
Refael Yonatan-Leus, The College of Management Academic Studies
Nari Yoo, University of Michigan
Qingcheng Zeng, Northwestern University
Mengjia Zhang, Chongqing Technology and Business University
Yuxiang Zhou, Queen Mary University of London
Zining Zhu, Stevens Institute of Technology
Jingwei Zhu, University of Science and Technology of China
Amirmohammad Ziaei Bideh, City University of New York
Moreah Zisquit, Reichman University

Table of Contents

How'd You Type That So Fast?A Descriptive Analysis of Counselor Message Text Reuse in Text-Based Crisis Counseling
Stevi Gligorovic, Jens Kristian Schou, Zac Imel and Brent Kious 1

Automated Detection and Classification of Delusion-related Content in Naturalistic Audio Diaries Using Multi-Agent Language Models
Feng Chen, Justin Tauscher, Changye Li, Meliha Yetisgen, Alex Cohen, Adam Kuczynski, Angelina Tsai, Benjamin Buck, Dror Ben-Zeev and Trevor Cohen 12

Clinical Prompt Engineering: Encoding Clinical Knowledge into AI Training Simulations - A Crisis Deployment Case Study
Yuval Holzman, Eshkol Rafaeli, Zohar Elyoseph, Yuval Haber, Karen Yirmiya, Omer Linkovski, Tal Elyoseph and Elad Refoua 32

Discriminant Validity: Disentangling Health and Emotional Constructs from Language-Based Assessments
Scott Feltman, Adithya V Ganesan, Whitney Ringwald, H. Andrew Schwartz, Roman Kotov, Benjamin Luft, Ryan Boyd and Oscar Kjell 43

Multistream Modelling for Mental Health: Modelling Linguistic and Temporal Contexts with Mutual and Self-Excitation in Social Media
Anthony Hills, Talia Tseriotou, Mahmud Akhter, Junyu Mao, Iqra Ali, Xenia Miscouridou and Maria Liakata 56

On the Role of Context in LLM Alignment to Mental Health Counseling Competencies
Sadiya Sayara Chowdhury Puspo, Marcos Zampieri and Özlem Uzuner 76

The Reliability Illusion in Synthetic Patients: Psychometric Misalignment of Open-weight LLMs on PHQ-9 and GAD-7
Qian Shen and Yu Han 88

Automatic Annotation of Mental Health Recovery Narratives: A Benchmark Study
Shrankhla Pandey, Graham Murray, Ben Laws, Stefan Rennick-Egglestone, Mike Slade and Sarah Morgan 100

Before the Labels: How Dataset Construction Shapes Suicidality Detection in Clinical Text
Priyanshi Garg, Ishita Rao, Jieqiong Ding and Amandalynne Paullada 119

Culture by Design: A Sociotechnical Framework for Culturally Grounded AI for Mental Health
Sunny Rai, Elizabeth Stade, Graise Zhou, Neil Sehgal, Simone Schriger, Sara Gerke, Lyle Ungar and Sharath Chandra Guntuku 128

Creating Multilingual Mental Health Dialogue Datasets: Limits of Persona-Based Localization via Nationality and Language
Yunkai Xu and Saeed Abdullah 138

Designing Structured Conversational Support for Tuberculosis Treatment Adherence and Patient Coping
Priyanshi Garg, Sarah Iribarren, Sikha Pentyala, Yvette Rodriguez, Priscilla Carmiol-Rodriguez, Alfie Vidrio, Charles Kwanin, Jennifer Sprecher and Javier Roberti 153

Enhancing Mental Health Counseling Support in Bangladesh using Culturally-grounded Knowledge
Md Arid Hasan, Azhagu Meena Sp, Aditya Khan, Abu Bhuiyan, Helal Ahmed, Joysree Debi, Farig Sadeque, Annie Lee and Syed Ishtiaque Ahmed 164

Evaluating Document-Tuned Transformer Representations for Person-level Mental Health Assessment
Aaron Marker, Oscar Kjell, Vasudha Varadarajan and H. Andrew Schwartz 178

Exploration of Perceptual Speech Features for Clinical Decision-Support in Mental Health Care
Vassilis Lyberatos, Edmund Dervakos, Eleni Adamidi, Athanasios Voulodimos and Giorgos Stamou 188

Exploring Profiles of Cognitive Distortions Associated with Mental Health Disorders
Alina Anikejeva and Kairit Sirts 208

Facet-Informed Prompting for LLM-Based Personality Assessment: Error-Guided Exemplar Selection and Hierarchical Prediction
Rasiq Hussain, Juhi Shah, Joshua Oltmanns and Mehak Gupta 221

From Responses to Trajectories: Modeling the Development of Reflective Listening Skills
Dhruvil Thummar and Verónica Pérez-Rosas 238

Ground Truths in Suicide Research: The Current State of AI-Based Suicide Detection in Social Media
Yaakov Ophir, Ofri Hefetz, Refael Tikochinski, Kfir Bar, Shir Lissak, Shulamit Grinapol, Haya Wachtel, Eyal Fruchter and Roi Reichart 244

Language-Based Detection of Adherence to Evidence-Based Psychotherapy Scripts
Samuel Campione, Elizabeth Stade, Stefanie Losavio, Shreya Singhvi, William Xuan, Tony Bui, Maria Martin Lopez, Shashanka Subrahmanya, Bailee Schuhmann, Courtney Worley, Shannon Wiltsey Stirman, Johannes Eichstaedt and H. Andrew Schwartz 250

LLMs as Standardised Patients for Motivational Interviewing: How Faithful Are They?
Van Hoang, Eoin Rogers and Robert Ross 258

Measuring the quality of therapy sessions against assessment scales using augmented semantic-similarity approaches
Kejian Cui, Simon D'alfonso and Mike Conway 271

Mirroring Minds: Asymmetric Linguistic Accommodation and Diagnostic Identity in ADHD and Autism Reddit Communities
Saad Mankarious, Nour Zeid, Iyad Ait Hou, Rebecca Hwa and Ayah Zirikly 282

Mostly Grounded, Occasionally Risky: Expert Evaluation of LLM-Generated Supervisory Feedback in a Psychotherapy Training Simulator
Adrian Montesano, Justin Bloomberg and Marc Pérez-Buriel 298

Psycholinguistic Profiles of Cognitive Distortions in Reddit Data
Neha Sharma, Navneet Agarwal and Kairit Sirts 306

The Attachment Index: Auditing Attachment Language Cues and Relational Safety Risks in Human-LLM Dialogue
Cyndie Demeocq, Animesh Prasad, Marzieh Saeidi, Karen Goodall and Björn Ross 324

The Text Aphasia Battery (TAB): A Clinically-Grounded Benchmark for Aphasia-Like Deficits in Language Models
Nathan Roll, Jill Kries, Flora Jin, Catherine Wang, Ann Marie Finley, Meghan Sumner, Cory Shain and Laura Gwilliams 340

The Visibility of Depression in Social Media: Mapping Symptoms to Linguistic Features
Ștefana-Arina Tăbușcă, Ana Sabina Uban and Liviu Dinu 355

Thinking With a Machine: An AI Agent's Account of Agentic Research in Clinical Psychology
Elad Refoua and Mor Bar 362

When Rating Scales Fall Short: LLM-Assisted Discovery of ADHD Signals in Turkish Teacher Narratives
Baris Karacan, Irem Aktar Songur, Ahmet Ozaslan and Elvan Iseri 368

Why Do Self-Harm Prediction Models Struggle to Generalise? – Lexical and Semantic Variations in Emergency Department Triage Notes
Liuliu Chen, Mike Conway, Jo Robinson and Vlada Rozova 383

Overview of the CLPsych 2026 Shared Task: Capturing and Characterizing Mental Health Changes through Social Media Timeline Dynamics
Iqra Ali, Talia Tseriotou, Guy Dvir, Callum Chan, Yuxiang Zhou, Juan Antonio Lossio-Ventura, Ayal Klein, Aya Shamir, Dan Sayda, Anthony R Hills, Ayah Zirikly, Diana Inkpen, Dana Atzil-Slonim and Maria Liakata 389

A Multi-Strategy Fusion Framework for Dynamic Mental State Modeling
Mengjia Zhang, Rui Chen, Haonan Xiao and Yi Yang 422

Agentic Pipelines Meet Retrieval-Augmented ICL: A Zero-Training Approach to Mental Health Modeling
Anson Antony, Gautam Kumar and Annika Marie Schoene 435

CUNY at CLPsych 2026: A Pipeline Approach to Classification and Summarization of Mental Health Change
Amirmohammad Ziaei Bideh, Shameed Job, Ava Yahyapour and Alla Rozovskaya 441

DreamerNLplus: Interpretable Modeling of Mental Health Dynamics from Social Media Timelines using Hybrid Rule-Based and RAG Methods
Maryia Zhyrko, Daisy Lal, Erik van Mulligen and Lifeng Han 458

Hierarchical Multi-Stage Modeling of Adaptive and Maladaptive Self-States in Social Media Timelines
Abir Naskar and Mike Conway 472

McMasters of Change: Predicting Well-Being States and Transitions from Longitudinal Language
Hongyi Zhang, Derron Li, Scarlett Cleary, Aadi Sanghani, Akshay Krishna Sirigana, Brian Miguel Pimentel, Kelsey Isman, Kian Omoomi, Vasudha Varadarajan, Charles Welch and Allison Lahnala 482

P2P - from Posts to Patterns: An LLM Ensemble Approach to Mental Health Dynamics Detection
Federico Ravenda, Volodymyr Karpenko, Antonietta Mira and Andrea Raballo 498

Prompt-Based Modeling of Moments of Change and Change Summaries in Mental Health Timelines
Duc Do, Tin Pham, Vu Tran and Minh Nguyen 504

psytechlab at CLPsych 2026: Utilising Natural Language Processing methods and Large Language Models for Social Media Text Analysis
Igor Buyanov, Nafisa Valieva and Ekaterina Mazurina 510

Self-State Identification with Retrieved In-Context Examples and Open-Weight LLMs
Alina Ponomareva, Nina Stekacheva Sancho and Karina Litvinova 521

Team Aurevia at CLPsych 2026: Local Healthcare NLP for Schema-Constrained Self-State Modeling
Nathan Roll, Irene Yi, Sufian Aldogom, Grace Brown, Eric Basile, Isaac Gutterman, Lakshika Tennakoon and Ammar Ahmed 531

Team MKC at CLPsych 2026: Capturing and Characterizing Mental Health Changes through Social Media Timeline Dynamics
Kyomin Hwang, Hyeonjin Kim, Hyunho Lee and Nojun Kwak 535

Theory-Explicit Prompting for MIND Self-States: Hierarchical LLMs and Dynamic Signature Extraction in Mental Health Timelines
Pawan Kumar, Ankit Meshram, Shubham Jha and Loitongbam Singh 547

Program

Friday, July 4, 2025

08:45 - 08:55	*Workshop Intro*
08:55 - 09:30	*Keynote 1*
09:30 - 10:30	*Paper Session 1*
10:30 - 11:00	*Break*
11:00 - 12:00	*Panel*
12:00 - 13:15	*Lunch*
13:15 - 13:55	*Paper Session 2*
13:55 - 14:30	*Keynote 2*
14:30 - 15:25	*Poster Session*
15:25 - 15:55	*Break*
15:55 - 16:55	*Shared Task Session*
16:55 - 17:35	*Paper Session 3*
17:35 - 17:45	*Closing Remarks*

"How'd You Type That So Fast?" A Descriptive Analysis of Counselor Message Text Reuse in Text-Based Crisis Counseling

Stevi N Gligorovic[1] **and Jens Kristian R Schou**[2] **and Zac E Imel**[1,3] and Brent Kious[3,4]
[1]Department of Educational Psychology, University of Utah
[2]Scientific Computing and Imaging Institute, University of Utah
[3]Department of Psychiatry, University of Utah
[4]Huntsman Mental Health Institute, University of Utah

Abstract

Suicide is a major public health concern, underscoring the importance of understanding communication practices used in crisis intervention. Text-based crisis services are increasingly used, yet little is known about how counselors construct messages across encounters. One understudied feature of this setting is counselor text reuse, or the repeated use of identical or highly similar message content across different clients. Although reuse may support efficiency and consistency, it may raise questions about how personalised responses are across counselors. This study provides a descriptive analysis of counselor text reuse in a large dataset of 4.7 million messages of real-time text-based crisis counseling conversations. Across 136 counselors, mean message similarity was very low, indicating little overall text reuse for most counselors. However, 103 counselors showed at least one instance of detected reuse, and a smaller subset demonstrated more consistent reuse. Reuse was also positively associated with counselor encounter volume across measures of reuse. Frequently reused longer passages primarily involved structured coping-oriented or psychoeducational content, such as coping strategies, grounding exercises, self-care tips, and relaxation techniques. The findings suggest that counselor text reuse is uncommon overall but becomes more likely as counselor encounter volume increases, providing a foundation for future work examining associations with service delivery and client outcomes.

Introduction

Suicide is a serious public health issue, with about 800,000 deaths due to suicide annually (World Health Organization, 2019) and several national declarations concerning children's mental health (Hua et al., 2023). In the United States, suicide is the second leading cause of death for adolescents and young adults (10–24 years old). In 2022, the American Foundation for Suicide Prevention reported about 1.6 million suicide attempts and 49,476 deaths by suicide. Notably, adolescent suicide rates have risen (Curtin, 2020). From 1975 to 2016, suicide rates increased by 7.9% among females and 3.5% among males ages 15–19 (Ruch, 2019).

Addressing this crisis requires robust interventions that include restricting access to lethal means, psychotherapy, and crisis hotlines (Goldney, 2005). Crisis hotlines are an accessible, widely utilized public health resource that provide immediate support to at-risk individuals (Gould et al., 2021; Ramchand et al., 2017). With evolving communication preferences, text-based crisis helplines are increasingly integrated into mental health services, particularly for younger populations (Budinger et al., 2015). For example, 988, the national crisis line, has received millions of text messages since its inception in July 2022 (Substance Abuse and Mental Health Services Administration, 2025). Despite the rise of text-based crisis services, the unique affordances and challenges of text-based crisis counseling conversations are relatively under-studied. For example, text-based communication allows counselors to copy-and-paste previously typed messages with important information, facilitating efficiency but potentially diminishing the personalized nature of interactions.

Crisis Lines

Participation in crisis line interactions can lead to reduced suicide risk (Gould et al., 2007; Halford et al., 2021; Mishara and Daigle, 2001). Similarly, text-based interventions are found to be helpful across a multitude of studies (Dwyer et al., 2021). For example, 90% of suicidal texters reported their conversation was helpful and 46.1% reported being less suicidal (Gould et al., 2007); see also (King et al., 2003; Mishara and Daigle, 1997; Pauwels et al., 2025). However, these findings suggest that over half of texters do not experience a reduction

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 1–11
July 4, 2026 ©2026 Association for Computational Linguistics

in risk.

Research on crisis counseling outcomes has historically focused on counselor variation in key behaviors such as risk assessment, safety planning, and counselor intervention strategies (Gould et al., 2013; Mishara, 2007; Lake et al., 2022). For example, compliance with suicide-risk assessment guidelines remains inconsistent across crisis hotlines, despite national standards (Gould et al., 2013; Mishara, 2007; Lake et al., 2022). In a crisis hotline study with U.S. veterans, only one-third of eligible callers completed a safety plan (Lauver et al., 2024). In general, more effective crisis counseling emphasizes validation, rapport-building, and collaborative problem-solving (Mishara, 2007). In sum, there is evidence that key behaviors are associated with important outcomes in crisis counseling, but this research has not investigated specific aspects of communication unique to text-based crisis counseling services.

Considerations in Text-Based Counseling

Although text-based counseling shares many attributes with spoken counseling, key differences exist. Text-based counseling remains conversational and allows for the delivery of content in a manner that is similar to spoken counseling, such as risk assessment or psychoeducation. However, text-based counseling differs from spoken counseling in important ways. For example, text-based counselors can manage multiple conversations simultaneously. In such cases, pre-generated messages can improve efficiency by expediting responses, refining presentation, and minimizing repetitive behaviors. However, this practice may result in lengthy, less personalized messages. Additionally, spoken conversations frequently include minimal encouragers to demonstrate active listening, but such responses may seem out of place in text-based formats, potentially necessitating longer messages to convey attentiveness and engagement (Kitchingman et al., 2018; Althoff et al., 2016). Investigating these fundamental elements of text-based crisis counseling is essential to optimizing its effectiveness.

Text Reuse

Text-based crisis counseling requires counselors to manage multiple conversations in real-time, often under high cognitive and emotional demands (Kitchingman et al., 2018). To maintain efficiency, counselors may rely on pre-written templates, frequently reused phrases, or simply develop habits such that they send messages that are highly similar across their different clients. Additionally, it is notable that some evidence-based therapeutic interventions inherently involve standardized or repetitive forms of communication, such as breathing exercises or grounding techniques. However, excessive reliance on any templated responses could impact client outcomes by reducing the personalization and adaptability of therapeutic interactions. Research suggests that more successful counselors adapt their language dynamically rather than relying on formulaic messaging (Althoff et al., 2016). One way to measure this phenomenon is via text reuse detection (Citron and Ginsparg, 2014), commonly analyzed through textual overlap and, similar to methods used in plagiarism detection, capturing the extent to which language is repeated or varied across messages.

There are many plausible reasons counselors may reuse text, including efforts to provide consistent intervention content, efficiently share structured coping or psychoeducational materials, adhere to any possible evidence-based training materials, and manage the demands of real-time text-based crisis work. The present study is descriptive and focuses on documenting the presence and patterns of text reuse rather than evaluating its causes or associations with client outcomes. Examining whether and how text reuse relates to service delivery or client outcomes remains an important direction for future research.

Text reuse can be assessed in a multitude of ways, namely via message similarity and longest common substrings. Message similarity can be analyzed at the message-level (within a single message) and conversation-level (across multiple messages from the same counselor). For example, one computational method for capturing text reuse, or message similarity, is through the Jaccard similarity index (Citron and Ginsparg, 2014). While there is no prior formal evaluation of text reuse and self-plagiarism in psychotherapy contexts or crisis counseling settings, this method is commonly used in plagiarism detection. For example, Citron and Ginsparg (Citron and Ginsparg, 2014) compared text content of scientific articles between 1991 and 2012 and measured how chronic text reuse is distributed among authors in the dataset. Using an n-gram-based NLP method across more than 750,000 scientific articles, they found that substantial text reuse is not evenly distributed but is concentrated among a small subset of "serial" reusers, while

the majority of authors rarely or never reuse large amounts of text. They also reported a strong negative association between the amount of reused text in an article and its scientific impact ($r \approx -0.74$), suggesting that higher levels of textual reuse are linked to lower influence.

Importantly, psychotherapy and crisis counseling contexts differ substantially from scientific publishing, where text reuse is often interpreted as misconduct or reduced originality. In therapeutic settings, repeated or standardized language may instead reflect evidence-based interventions, safety practices, psychoeducation, or efforts to maintain consistency across client interactions. Accordingly, the present study does not conceptualize text reuse as inherently problematic, but rather examines the extent and patterns of repeated language in text-based crisis counseling.

The longest common substring (LCSS) approach is another avenue to discover copy-pasted messages. LCSS captures the longest contiguous sequence of words shared between two messages, highlighting instances where a counselor has repeated the same block of text verbatim. Unlike Jaccard similarity, which reflects overall similarity in phrasing between messages, LCSS focuses on exact sequential reuse of text, providing a more precise lens on formulaic messaging.

In a study of large language model extraction of psychotherapy dissatisfaction narratives from online forum posts, Steinbrenner used an evaluative metric based on longest common subsequence (LCS) to compare model-identified passages with passages independently identified by a blinded human rater (Lin, 2004). Their LCS metric evaluates the longest sequence of words shared in the same order, without requiring the words to be consecutive. The model achieved an LCS-based similarity score of 0.68, indicating substantial agreement with the human reference and supporting the usefulness of LCS-based methods for identifying similar text despite minor wording differences (Steinbrenner et al., 2025). This method computes overlap in text that allows for skipped words; however, for the purposes of detecting self-plagiarism, we utilize longest common substring rather than subsequence due to its more direct and precise detection of verbatim text reuse. By combining LCSS with broader similarity measures, we can better understand both general patterns of repeated language and specific instances of direct message copying.

For the purpose of our study, we utilize a 10-gram NLP-based approach using Jaccard similarity indices to detect counselor text reuse across counselor messages. A high similarity score (text reuse) suggests a heavy overlap of text between two messages, indicating substantial reuse of language. Low similarity scores suggest few or no overlapping text between two messages, indicating more tailored or unique language. In addition, we use the longest common substring (LCSS) approach to identify exact, contiguous sequences of repeated words, capturing instances of verbatim message reuse.

1 The Current Study

Despite increased use of text-based crisis counseling, little is known about specific message features. This study examines one key aspect of counselor communication in real-time text-based crisis counseling: text reuse across counselor messages. First, we examined the extent of text reuse across counselors. We examined variability in reuse across counselors and as well as the amount of reuse within counselors. At the message level, we examined the extent that specific messages were reused, both in terms of how many times they were reused, and how many counselors reused the messages. We also clustered reused text to illustrate common patterns and families of repeated content across counselors, highlighting both exact and lightly edited repetitions. By investigating these factors, this study aims to contribute to a more nuanced understanding of how message-level communication looks in crisis counseling, informing best practices for text-based crisis interventions and future research implications that incorporate client outcomes.

2 Methods

2.1 Data

This study utilized de-identified data from a large set of 224,077 crisis counseling encounters ($\tilde{4}$.7 million messages) collected from a regional text-based crisis and mobile tip line app available 24 hours a day, 7 days per week. The crisis line is implemented in K-12 schools across these regions. The study dataset included crisis encounters from clients of any age located across three different states within the United States who utilized the service between 2017 and 2021. Mobile tips, a system for notifying schools and educators about potentially at-risk student peers, were excluded from the

study sample. Due to the de-identified nature of the dataset, no client-identifying information was available and counselor-level demographic or metadata were limited.

There is a total of 136 licensed or license-eligible counselors who receive additional training in suicide risk assessment and safety planning. Counselor encounters range from 1 to 7,894. Institutional Review Board (IRB) approval was obtained for this study. The crisis line does not systematically collect potentially identifiable information, and text messages were scrubbed of incidental identifying information prior to analysis.

Text reuse analyses were computed on the dataset with additional filtering criteria applied, as described below. Message similarity and LCSS results reflect the subset of messages and encounters that met these criteria.

2.2 Filtering Criteria for Text Reuse

Filters were applied to individual counselor messages, retaining only messages that were longer than 30 words and excluding templated sign-in or sign-off responses using a regular expression pattern. Encounters in which no counselor messages, for example, no messages that were longer than 30 words or non-templated sign-in/sign-off, met these criteria were then excluded from the analytic dataset. This filtering may bias estimates toward longer, more content-rich messages and may underrepresent shorter forms of reuse (e.g., brief templates), which we intentionally exclude to focus on substantive reuse. Message-level filtering resulted in differences in the number of encounters and messages that remained analyzable across counselors. These filtering criteria resulted in a dataset of 332,584 total counselor messages and 92,099 encounters. After message-level filtering, the number of analyzable encounters per counselor ranged from 1 to 5,719. Message similarity score and longest common substring analyses were conducted on these filtered message sets. Estimates for counselors with fewer qualifying messages should be interpreted with caution due to the reduced data density.

To remove scripted sign-in and sign-off responses, all counselor messages were screened for standardized phrases using a predefined pattern-matching regular expression approach. This included common onboarding greetings, for example, greetings or sign-in and sign-off scripts such as "Hi there, I'm glad you reached out. My name is [name] and I use she/her pronouns. Thanks so much for chatting in today, please let me know how can I best assist you?" and standardized follow-up or "...are you still there?" type messages when a chatter leaves or ends the chat. These messages were identified using regular expressions that matched common variants of these scripts. Messages containing these templated elements were excluded to ensure that only substantive, counselor-generated responses were included in the analysis.

2.3 Measures

First, all counselor and client messages were adjusted for de-identified information to appear as one word ("PLACEHOLDER"). This was done to prevent higher word counts that might arise due to the original de-identified placeholder words that contain two or three words to represent one identifying word.

2.4 Message Similarity

Message similarity was used to assess the degree of text reuse across counselor messages. This was measured using both pairwise Jaccard similarity applied to hashed n-grams and longest common substrings. Jaccard similarity was used as a broader measure of text reuse, capturing overall overlap in phrasing across messages, while the longest common substring approach provided a more specific indicator of exact, sequential reuse. Together, these methods allow for the identification of both general and highly similar forms of repeated language.

Jaccard Similarity Scores. Pairwise Jaccard Similarity scores were calculated for all message pairs across and within each counselor's encounters. Using the filtered message set described above, each message was split into overlapping 10-word n-grams. The formula for the similarity score is then the total number of shared hashed segments between message A and message B divided by the total number of unique hashes. Hashing converts text segments into a numerical value for ease of computation and comparison over a large set of messages. This formula results in an n-gram Jaccard Similarity score, or a percentage reflecting the extent to which the two messages share the same phrases of length at least 10 words (n-grams). This calculation was repeated on all messages across all encounters for all 136 counselors. The Jaccard similarity formula is defined as follows:

$$J(A, B) = \frac{|A \cap B|}{|A \cup B|}$$

We compute a mean similarity score for each counselor that aggregates all pairwise similarity scores across all encounters. The degree of overlap between messages is determined by the n-gram length, for example, if $N = 10$, the message similarity is calculated based on every overlapping 10-word sequence shared between messages. The goal is to capture how similar each counselor's message is relative to other messages by the same counselor across their encounters.

2.5 Longest Common Substring

The longest common substring (LCSS) between two texts is the longest stretch of words that appears contiguously in both texts. In other words, the match between the two texts must be uninterrupted, so the shared material must occur as one continuous block in both texts. Computing LCSS for every pair of messages a counselor has sent then ultimately results in direct text reuse.

Computationally, this can be done efficiently by comparing all prefixes of the two texts and keeping track of how long the current matching run is at each position. Whenever the two current elements match, the run length increases by one, and when they do not, it resets to zero. The longest match discovered in this process is the LCSS. For the purpose of text reuse, we want to discover all LCSS of reasonable length; we chose this hyperparameter to be exact matches of length at least 100. Furthermore, it is possible for the texts to share more than one reused segment, so when an LCSS is discovered we delete it from the two texts and compute the next LCSS, until there are no more matches of length at least 100.

Counting the number of LCSS across all message pairs is not without limitations. A single underlying phrase can produce multiple overlapping LCSS matches across different message pairs. For example, consider the messages A: "Hello, thank you for reaching out today," B: "thank you for reaching out today," and C: "thank you for reaching out." The LCSS between A and B is B, and between A and C is C, however, because C is contained within B, naively counting both overstates the amount of reused text. More generally, overlapping fragments may not nest cleanly: two LCSS spans can partially overlap without either containing the other, making simple deduplication by substring containment insufficient.

To address this, we cluster LCSS spans that represent variants of the same underlying phrase. Spans shorter than 100 words were discarded to focus on substantive reuse.

2.6 Clustering Descriptives for Reused Messages

We seek to describe and illustrate reuse at two different levels. First, we wanted a message-level estimate of how often counselors reused text content. Second, we wanted to identify recurrent families of reused text, rather than treating every longest common substring as an unrelated artifact. These goals are related, but they are not identical. A single message can contain multiple distinct copied or highly similar submessages, so any attempt to force all reuse into a disjoint set of clusters would blur that structure. We therefore separated prevalence estimation from semantic organization.

To estimate message-level reuse prevalence, we used the extracted LCSS spans together with the associated message ids. For each counselor, we parsed the message IDs and associated every LCSS span with all messages in which it occurred. Next, for each message, we collected all candidate LCSS spans linked to that message. This procedure yields a message-level measure of reuse that is robust to the same message being linked to multiple overlapping substrings.

To identify broader families of reused content, we clustered the LCSS spans semantically. We treated each surviving LCSS as one observation and embedded the span text using MentalBERT (Ji et al., 2021). We chose a semantic embedding approach because clustering based only on surface overlap produced fragmented and often uninformative groups. In particular, lexical methods tend to split together phrases that clearly instantiate the same reused template but differ slightly in wording, while also overemphasizing trivial overlap. By embedding the LCSS spans, we instead aimed to group semantically similar reuse patterns, including lightly edited or paraphrastic variants of a common template.

Each remaining span was tokenized and truncated at 512 tokens, matching the model context limit. This is a limitation of the method because the tail of messages longer than 512 tokens (about 400 English words) will be excluded from the clustering. The resulting span embeddings were clus-

tered with MiniBatchKMeans using $k = 100$. We selected the cluster representative as the LCSS closest to the cluster centroid, since this gives a typical exemplar of the cluster.

For each cluster, we reported the number of distinct message IDs and distinct counselor IDs represented among the member LCSSs. These counts should be interpreted as lower-bound coverage measures for that reuse family. They are not additive across clusters, because the same message can contain multiple distinct reused spans and therefore contribute to more than one cluster and computed clusters are not guaranteed to perfectly separate ground truth clusters. This overlap is a substantive property of the data rather than a defect of the analysis: counselor messages may legitimately combine several reused components in a single response. For this reason, cluster-level counts were used to describe the breadth of a reuse family, while message-level prevalence was estimated separately using the message-collapse procedure above.

2.7 Statistical Analysis

All analyses were conducted in R using "textreuse" (Li, 2026), "tidyverse," and "dplyr" packages (Wickham, 2026). Pairwise Jaccard similarity scores were computed for all messages within each counselors' encounters. A mean similarity score was also calculated for each counselor to represent the overall degree of text reuse across their set of clients. These scores were summarized descriptively at both the message and encounter level for each counselor. Additionally, LCSS were computed to capture the extent of exact sequential overlap in phrasing between messages. We report overall exploratory and descriptive patterns of message reuse at the encounter and message level in this dataset.

3 Results

3.1 Message Similarity

Similarity was computed at the message level for each counselor. After filtering, all remaining counselor messages were tokenized into 10-gram sequences, and pairwise Jaccard similarity was calculated for every message pair within a counselor. This produced one similarity matrix per counselor, where higher values indicate greater overlap in 10-gram content across messages. In other words, higher scores indicate high text reuse and lower scores indicate low reuse, where 0 indicates no text overlap between two messages and 1 indicates identical text overlap.

A total of 103 out of 136 (75.7%) counselors demonstrated at least one instance of detected reused text, suggesting that a typical counselor reused message content at some point in their practice. However, across all counselors, mean similarity scores were very low, indicating that reuse accounted for a small proportion of message pairs overall. Counselor-level mean similarity values ranged from 0 to 0.031 ($M = 0.001$, $SD = 0.0034$). For most counselors, the vast majority of message pairs of at least 30 words shared no overlapping 10-word sequences. However, a small subset of counselors demonstrated notably greater reuse than the sample as a whole. Whereas most counselors (83.1%) had less than 0.1% average similarity between their messages, the counselors with the highest levels of reuse had mean similarity scores ranging from 0.85% to 3.1%. This range indicates that, for some counselors, repeated phrasing was a consistent feature of their messaging.

3.2 Longest Common Substring (LCSS)

A total of 72,665 messages (21.86% of 332,584 messages longer than 30 words) included some reuse of at least 10 consecutive words. A total of 13,562 (4%) messages included some reuse of at least 100 consecutive words. Across counselors, the proportion of messages that included reuse of at least 10 and 100 words averaged 0.22 and 0.041, respectively. The corresponding counselor-level counts had medians of 17 and 0, standard deviations of 1,355.61 and 379.88, and ranged from 0 to 8,768 and 0 to 3,110.

Across the 136 counselors, the average number of messages with some reused content was 9.45% among messages of at least 30 words and 1.76% among all messages when reuse was defined as at least 10 consecutive words, with standard deviations of 12.20 and 2.72 percentage points, respectively. For reuse of at least 100 consecutive words, the corresponding averages were 1.29% among messages of at least 30 words and 0.21% among all messages, with standard deviations of 3.15 and 0.61 percentage points, respectively.

The number of counseling encounters varied widely across counselors ($M = 677.20$, $SD = 1{,}113.68$) for messages of at least 30 words, with a range of 1 to 5,719 and a median of 106. Across all encounters, the average number of encounters

was 1,113.72 ($SD = 1{,}784.05$), with a range of 1 to 7,894 and a median of 171.

3.3 Counselor Encounter Volume and Message Reuse

Across counselors, the percentage of reused messages was positively correlated with the total number of unique encounters. For reuse of at least 10 consecutive words, the correlation was $r = .51$ among messages of at least 30 words and $r = .43$ across all messages, both $p < .001$. For reuse of at least 100 consecutive words, the corresponding correlations were $r = .50$ and $r = .50$, respectively, both $p < .001$. This suggests that as counselor encounter volume increased, counselors reused content more frequently. The counselor with the largest number of encounters without any observed 10 consecutive word reuse had 163 encounters, corresponding to 1,548 unique messages. Similarly, when reuse was defined as 100 consecutive words, the counselor with the largest number of encounters without detected reuse had 2,724 encounters, corresponding to 25,016 unique messages.

3.4 LCSS Clustering Using MentalBert

Clustering analyses were completed for reused text spans (LCSSs) of length at least 100 words to capture substantive reused messages. For illustration, we report on the top 5 most reused clusters of text discovered by our algorithm. The clustering procedure groups candidate texts that are likely variants of the same underlying phrase, which were reviewed by a human annotator who confirmed cluster membership and identified the representative passage. This semi-automated approach combines the scalability of algorithmic matching with human judgment for disambiguation.

The clusters with the most frequently detected reused LCSS are reported in Table 1. The cluster with the most LCSS occurrences was a list of coping strategies, which was identified as used at least 978 times across 26 counselors. This script typically ranged from 100 to 507 words. A similarly common cluster involved a grounding sensory exercise, observed 790 times across 13 counselors, with messages ranging from 100 to 655 words. Another cluster revealed messages regarding self-care tips, observed 745 times across 11 counselors, with messages ranging from 110 to 314 words.

Other recurring clusters included a different list of coping strategies, observed 578 times across 9 counselors, ranging from 100 to 220 words. A muscle tension relaxation technique cluster was detected 572 times across 13 counselors, ranging from 101 to 675 words. Overall, the most frequently reused passages involved structured psychoeducational or coping-oriented content, such as breathing exercises, grounding techniques, and self-care guidance, rather than conversational or relational statements.

Discussion

The present study examined text reuse across real-time, text-based crisis counseling encounters. We found that some reuse was detectable for most counselors: 103 of 136 had at least one detected instance of reuse. Repeated wording was not the dominant pattern of counselor communication. Mean pairwise 10-gram Jaccard similarity was extremely low overall (M = .001), and most counselors had average similarity values near zero. And finally, counselor text reuse was correlated with encounter volume across analytic definitions of reuse; counselors who handled more encounters showed higher proportions of reused messages. Taken together, these findings suggest that counselor messages were typically composed in unique language at the whole-message level, while selective reuse of particular passages became more common among counselors with greater encounter volume.

Variation across counselor text reuse was a central finding. Reuse was not distributed evenly throughout the sample. Most counselors showed very low average similarity and little repeated overlap across messages, whereas a smaller subset demonstrated more consistent reuse. This pattern suggests that text reuse in this setting is better understood as concentrated among some counselors rather than as a uniform feature of crisis counseling practice. At the same time, reuse was not absent. LCSS analyses showed that approximately one in five counselor messages (30 or more words) contained a repeated segment of at least 10 consecutive words. Much longer repeated passages of 100 or more words were less common, but still appeared in roughly one in 25 qualifying counselor messages. The presence of some counselors with nontrivial encounter volume but no detected reuse at these thresholds further indicates that repeated text was common, but not inevitable.

The Jaccard analyses summarized similarity across all message pairs within counselors, and most pairs did not share any 10-grams, which kept

Cluster / message type	Occurrences	Counselors	Message length (words)
List of coping strategies	978	26	100–507
5-4-3-2-1 grounding exercise	790	13	100–655
Self-care tips	745	11	110–314
Alternative list of coping strategies	578	9	100–220
Muscle tension relaxation technique	572	13	101–675

Table 1: Most frequently detected reused message clusters.

average similarity near zero. In contrast, LCSS identified whether a message contained any repeated segment above a minimum length. A counselor could therefore reuse a limited number of longer passages within otherwise distinct messages and still have very low average pairwise similarity. This distinction is important because it suggests that reuse in this dataset was likely localized to specific components of counselor responses rather than reflecting broadly repetitive communication.

The clustering results help clarify the kinds of content that were most often repeated. Among the most frequently detected long reused passages were lists of coping strategies, grounding exercises, self-care tips, and muscle relaxation instructions. In other words, the most common repeated passages appeared to involve structured, psychoeducational, and coping-oriented material rather than primarily relational or conversational language shared between counselors. These findings suggest that some counselors may draw from preformulated language when delivering common intervention content. However, the present data cannot determine whether these passages came from formal templates, personal notes, training materials, or individual habits that developed over time. Nor can these findings determine whether the use of such language improved or reduced the quality of support.

One of the most important findings was the positive association between counselor encounter volume and text reuse. Across counselors, the proportion of reused messages increased as the number of unique encounters increased, and this pattern was evident across both reuse thresholds examined. For reuse defined as at least 10 consecutive words, the correlation with encounter volume was $r = .51$ among messages longer than 30 words and $r = .43$ across all messages; for reuse defined as at least 100 consecutive words, the corresponding correlations were $r = .50$ and $r = .50$, respectively (all $p < .001$). Because the association was observed across reuse thresholds and definitions, it does not appear to depend on any one measure of reuse. Although greater encounter volume creates more opportunity to observe repeated passages, the fact that this pattern appeared when reuse was expressed as a proportion of messages suggests that it is unlikely to be explained solely by counselors generating more total text. An interpretation is that counselors with greater encounter volume may develop and repeatedly draw on preferred ways of delivering common intervention content, particularly structured coping or psychoeducational guidance. Rather than viewing text reuse only as an individual stylistic difference, these findings suggest that it also scales with the extent of counselors' practice within the service.

These findings have several implications for understanding communication in digital crisis services. Most importantly, the results do not support the view that counselor messaging is all broadly templated. Instead, they suggest a more selective pattern in which reuse, when it occurs, is concentrated in certain counselors and in certain types of content. This may reflect one way counselors manage recurring tasks in a text-based, high-intensity service environment, particularly when offering concrete coping tools or psychoeducation.

However, this association may also be shaped by unmeasured contextual factors, including counselor tenure, shift timing, fatigue, workload, or differences in training and supervision practices. As a result, encounter volume should be interpreted cautiously and not necessarily assumed to be the sole driver of text reuse patterns.

This study provides a descriptive understanding of text reuse in real-time crisis counseling. Our main finding was that text reuse was positively associated with counselor encounter volume across definitions of reuse. This suggests that reuse increases with counselor encounter volume. Although average message-level similarity was very low for most counselors, text reuse was nevertheless a meaning-

ful and patterned feature of counselor communication. Reuse was concentrated among a subset of counselors and was most often observed in structured coping-oriented or psychoeducational passages. These findings suggest that text reuse in this setting is not pervasive, but neither is it incidental: it becomes more common as counselor encounter volume increases.

The present study was descriptive and focused specifically on extended identical text reuse rather than broader stylistic similarity or effectiveness. The findings establish baseline evidence that communication patterns within text-based crisis counseling are not uniform and that text reuse increases systematically with counselor encounter volume. As digital crisis services continue to expand, future research linking message-level features to client outcomes and examining the full counselor dataset will be essential for understanding whether observed stylistic differences have meaningful implications for service delivery.

Limitations

The number of encounters retained after message-level filtering varied across counselors. This variation reflects differences in how frequently counselors produced longer (> 30-word), non-templated messages within their sampled encounters. As a result, the dataset differed in size across counselors after applying inclusion criteria. Consequently, similarity estimates for counselors with fewer retained messages are based on a smaller pool of observations and should be interpreted with appropriate caution due to reduced data density. Importantly, this variation resulted from analytic filtering decisions rather than unequal sampling or workload differences across counselors. A second limitation concerns the scope of the similarity/text reuse metric. Linguistic similarity was operationalized as identical contiguous 10-word sequences, reflecting the study's focus on extended verbatim text reuse. Accordingly, findings should be interpreted as estimates of longer contiguous segment reuse rather than broader stylistic or thematic similarity.

Finally, although variation in message length and reuse patterns was identified, the study does not evaluate whether particular communication styles are associated with improved client outcomes, perceived helpfulness, or reductions in distress. Therefore, no conclusions can be drawn regarding the effectiveness of longer messages or higher levels of text reuse. Future research linking message-level features to client outcomes would be necessary to determine whether observed stylistic differences have meaningful clinical implications. Additionally, examining a larger set of counselors and their encounters may provide more stable, accurate estimates of communication patterns and allow for stronger conclusions regarding variability across providers in this setting.

Our LCSS-based analysis has several limitations. First, LCSS is sensitive to minor surface-level discrepancies: a single extra space, a missing line break, or formatting artifacts introduced when copying text from PDF sources can break an otherwise exact match. This contrasts with n-gram Jaccard similarity, which is more robust to such perturbations. Second, when a counselor reuses part of a longer reused passage, the shorter fragment is detected as a separate LCSS match against every message containing the longer passage, inflating its occurrence count. Our clustering procedure using MentalBERT attempts to work around these weaknesses because long messages that differ by a space probably map to the same area and are then clustered together. A clear limitation of using MentalBERT for the clustering is the 512 token limit that cuts off long reused messages. The clustering output requires human review to confirm that grouped spans genuinely represent variants of the same underlying passage, making this a semi-automated rather than fully automated method. Third, the reported counts should be interpreted as lower bounds: at minimum, these counselors used these passages as part of a message at least this many times. Obtaining precise counts is difficult given the overlapping and fragmentary nature of pairwise LCSS output. Fourth, to avoid flagging genuine therapeutic style the minimum LCSS length must be set conservatively high. We chose a threshold of 100 words, accepting that this sacrifices recall of shorter templates in favor of specificity for substantive text reuse.

Ethical Considerations

This study used de-identified data from a text-based crisis counseling service. All messages had personally identifying information removed prior to analysis, and no attempt was made to re-identify individuals. The dataset included sensitive communications from individuals in crisis, and analyses were conducted at the aggregate level to minimize risk of harm or disclosure. Institutional Review

Board (IRB) approval was obtained prior to data access and analysis.

Given the vulnerable nature of the population, care was taken to ensure that findings were reported in a way that avoids stigmatization or misinterpretation of counselor or client behavior. Results are intended to inform understanding of communication patterns at the system level rather than to assess or compare individual providers.

Acknowledgments

AI tools were utilized to assist in the writing of this manuscript and to assist in performing literature search, in accordance with the ACL Policy on AI Writing Assistance cases a and c.

References

Tim Althoff, Kelsie Clark, and Jure Leskovec. 2016. Large-scale analysis of counseling conversations: An application of natural language processing to mental health. *Transactions of the Association for Computational Linguistics*, 4:463–476.

M. C. Budinger, M. Cwik, and M. Riddle. 2015. Awareness, attitudes, and use of crisis hotlines among youth at-risk for suicide. *Suicide and Life-Threatening Behavior*, 45(2).

Daniel T. Citron and Paul Ginsparg. 2014. Patterns of text reuse in a scientific corpus. *Proceedings of the National Academy of Sciences*, 112(1):25–30.

Sally C. Curtin. 2020. State suicide rates among adolescents and young adults aged 10–24: United states, 2000–2018. Technical report, CDC.

Angela Dwyer, Antonio de Almeida Neto, Dominique Estival, Wei Li, Catherine Lam-Cassettari, and Mark Antoniou. 2021. Suitability of text-based communications for the delivery of psychological therapeutic services to rural and remote communities: Scoping review. *JMIR Mental Health*, 8(2):e19478.

Robert D. Goldney. 2005. Suicide prevention. *Crisis*, 26(3):128–140.

Madelyn S. Gould, S. Chowdhury, A. M. Lake, H. Galfalvy, M. Kleinman, M. Kuchuk, and R. McKeon. 2021. National suicide prevention lifeline crisis chat interventions: Evaluation of chatters' perceptions of effectiveness. *Suicide and Life-Threatening Behavior*, 51(6):1126–1137.

Madelyn S. Gould, W. Cross, A. R. Pisani, J. L. Munfakh, and M. Kleinman. 2013. Impact of applied suicide intervention skills training on the national suicide prevention lifeline. *Suicide and Life-Threatening Behavior*, 43(6):676–691.

Madelyn S. Gould, J. Kalafat, J. L. HarrisMunfakh, and M. Kleinman. 2007. An evaluation of crisis hotline outcomes part 2: Suicidal callers. *Suicide and Life-Threatening Behavior*, 37(3):338–352.

E. Halford, A. M. Lake, and M. S. Gould. 2021. Crisis hotlines. In *Oxford Textbook of Suicidology and Suicide Prevention*. Oxford University Press.

L. L. Hua, J. Lee, M. H. Rahmandar, and E. J. Sigel. 2023. Suicide and suicide risk in adolescents. *Pediatrics*, 153(1):e2023064800.

Shaoxiong Ji, Tianlin Zhang, Luna Ansari, Jie Fu, Prayag Tiwari, and Erik Cambria. 2021. Mentalbert: Publicly available pretrained language models for mental healthcare. *Preprint*, arXiv:2110.15621.

R. King, B. Nurcombe, L. Bickman, L. Hides, and W. Reid. 2003. Telephone counselling for adolescent suicide prevention. *Suicide and Life-Threatening Behavior*, 33(4):400–411.

T. A. Kitchingman, C. J. Wilson, P. Caputi, I. Wilson, and A. Woodward. 2018. Telephone crisis support workers' psychological distress and impairment. *Crisis*, 39(1):13–26.

A. M. Lake, T. Niederkrotenthaler, R. Aspden, M. Kleinman, A. M. Hoyte-Badu, H. Galfalvy, and M. S. Gould. 2022. Lifeline crisis chat: Coding form development and findings on chatters' risk status and counselor behaviors. *Suicide and Life-Threatening Behavior*, 52:452–466.

M. Lauver, M. C. Podlogar, J. J. Herbin, M. Selig, F. K. Muzzey, K. Patelli, J. F. McCarthy, G. J. Hughes, and M. Stacy. 2024. Implementing and evaluating a veterans crisis line quality improvement initiative. *Psychological Services*.

Chin-Yew Lin. 2004. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pages 74–81, Barcelona, Spain. Association for Computational Linguistics.

B. L. Mishara and M. S. Daigle. 1997. Effects of different telephone intervention styles with suicidal callers. *American Journal of Community Psychology*, 25(6):861–885.

B. L. et al. Mishara. 2007. Which helper behaviors and intervention styles are related to better short-term outcomes. *Suicide and Life-Threatening Behavior*, 37(3):308–321.

Brian L. Mishara and Marc Daigle. 2001. Helplines and crisis intervention services: Challenges for the future. In David Lester, editor, *Suicide Prevention: Resources for the Millennium*, pages 153–171. Brunner-Routledge.

Kirsten Pauwels, Eva De Jaegere, Patrick Vanderreydt, Silke Aerts, Eva Vande Gaer, and Gwendolyn Portzky. 2025. Assessing a suicide prevention helpline's impact on caller crisis level and suicidality. *Archives of Suicide Research*, 29(3):621–636.

Rajeev Ramchand, Lisa H. Jaycox, Patricia Ebener, Mary L. Gilbert, Dionne Barnes-Proby, and Pravesh Goutam. 2017. Characteristics and proximal outcomes of calls made to suicide crisis hotlines in california: Variability across centers. *Crisis: The Journal of Crisis Intervention and Suicide Prevention*, 38(1):26–35.

D. A. et al. Ruch. 2019. Trends in suicide among youth aged 10 to 19 years. *JAMA Network Open*, 2(5):e193886.

Tobias Steinbrenner, Christopher Lalk, Alin Kabjesz, Drin Ferizaj, Juan Segundo Pena Loray, Flavio Iovoli, and Julian Rubel. 2025. Exploring negative experiences in psychotherapy using an nlp approach on online forum data. *npj Mental Health Research*, 4(1).

Substance Abuse and Mental Health Services Administration. 2025. 988 lifeline performance metrics.

World Health Organization. 2019. Suicide in the world.

Automated Detection and Classification of Delusion-related Content in Naturalistic Audio Diaries Using Multi-Agent Language Models

Feng Chen[1], Justin Tauscher[1], Changye Li[1],
Meliha Yetisgen[1], Alex Cohen[2], Adam Kuczynski[1],
Angelina Pei-Tzu Tsai[1], Benjamin Buck[3], Dror Ben-Zeev[1], Trevor Cohen[1]

[1]University of Washington, Seattle, WA
[2]Louisiana State University, Baton Rouge, LA
[3]University of North Carolina at Chapel Hill, NC
cohenta@uw.edu

Abstract

Speech monologues recorded in naturalistic settings provide opportunities to characterize mental illness phenomenology and detect symptom exacerbation. Large language models (LLMs) offer new possibilities for automating this process, as they require annotated data primarily for evaluation rather than training. In this paper, we present a novel automated, multi-agent LLM pipeline for the fine-grained, multi-label extraction of language suggestive of delusional beliefs, associated affective responses, and behavioral responses from transcripts of naturalistic audio diaries collected from people with moderate persecutory ideation. Evaluating an ensemble of three foundation models, we demonstrate that detailed diagnostic prompt instructions successfully reduce false positives for delusional theme classification, but also constrain the interpretation of affective or behavioral responses. Furthermore, comparing multi-agent adjudication frameworks shows that complex conversational debate between agents diminishes accuracy on clinically ambiguous text by inducing premature consensus. Instead, majority voting establishes robust performance (Micro F_1 of 0.872 and 0.779 for delusion detection and classification respectively). This work provides a validated and scalable pipeline for the automated detection and characterization of content suggesting delusional beliefs in naturalistic speech.

1 Introduction

Delusions are fixed, false beliefs that are held with strong conviction and are particularly resistant to counter-evidence (American Psychiatric Association, 2013). Although most commonly associated with psychotic disorders, attenuated forms of paranoid and persecutory thinking have also been reported in non-clinical populations, supporting the view that psychotic experiences occur along a continuum (Freeman et al., 2005; Heilskov et al., 2020; van Os et al., 2009). Delusions are multidimensional phenomena that vary in conviction and distress with content that often reflects recognizable thematic categories such as persecution, reference, grandiosity, and somatic concerns (Pappa et al., 2025). These experiences can be a major source of distress and functional impairment, strongly shaping how severely an individual's daily life is disrupted in the context of psychotic symptoms (Freeman, 2016; Buck et al., 2023; Kiran and Chaudhury, 2009).

Despite their clinical significance, systematically characterizing delusional content as it unfolds over time remains difficult. Current assessment approaches rely largely on structured clinician interviews conducted during intermittent clinical encounters, which may miss episodic fluctuations in delusional thinking and are vulnerable to recall bias and interpretive error (Haddock et al., 1999; Khan et al., 2013; Ben-Zeev et al., 2012). Capturing these fluctuations is critical for monitoring risk, guiding intervention, and understanding how delusional beliefs evolve over time (Bell et al., 2024).

Smartphone-based ecological momentary assessment (EMA) enables repeated symptom measurement in naturalistic settings (Myin-Germeys et al., 2018), and when paired with audio diary recordings, can capture rich first-person accounts of lived experience in real time (Ben-Zeev et al., 2020; Buck et al., 2023). When combined with automated speech recognition (Radford et al., 2022), these recordings can be transformed into large corpora of transcripts suitable for computational analysis. However, extracting clinically meaningful signals from large volumes of patient-generated language remains challenging, as manual review is time-consuming and difficult to scale (Tauscher et al., 2025; Wu et al., 2022).

Detecting presence of delusional content alone does not adequately characterize its clinical significance. Understanding its impact requires at-

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 12–31
July 4, 2026 ©2026 Association for Computational Linguistics

tention to the thematic content of beliefs, the affective responses they evoke, and the behaviors they motivate. Delusional themes have been shown to relate to differences in etiology, distress, and need for treatment, while affective and behavioral responses to delusional beliefs are closely related to functional impairment and disability (Buck et al., 2023; Pappa et al., 2025). However, manually annotating these dimensions in large corpora of patient-generated language is time-consuming, costly, and difficult to scale, particularly given that inter-annotator agreement for psychiatric phenomena remains moderate even among trained raters (Tauscher et al., 2023; Di Forti et al., 2025). Large language models (LLMs) offer a potential solution. Their capacity for step-by-step chain-of-thought reasoning shows promise for mental health prediction tasks (Xu et al., 2024), and is well-suited to navigate the diagnostic logic and exclusion rules that fine-grained symptom characterization demands. However, individual models remain vulnerable to inconsistency and confabulation (Huang et al., 2023; Ji et al., 2023; Asgari et al., 2025). Multi-agent frameworks, in which multiple LLMs independently annotate and then adjudicate disagreements through voting, structured judging, or iterative debate (Du et al., 2023; Chan et al., 2023), offer a principled mechanism for resolving this ambiguity while retaining interpretable reasoning traces.

In this paper, we present an automated pipeline for multi-label annotation of delusional content in transcripts of audio diaries collected from individuals with delusions. We evaluate the approach based on data from the Study on Assessing Determinants and Antecedents of Persecutory Thoughts (ADAPT), which collected smartphone-based audio diaries from participants meeting the criteria for moderate persecutory ideation (Buck et al., 2023). We deploy three LLMs (GLM-4.6, GPT-OSS, and Qwen-3) and systematically compare three adjudication strategies: majority voting, direct expert adjudication, and multi-agent conversational debate.

Our contributions are as follows:

- A systematic ablation of prompt context across four progressively layered levels for multi-label annotation of delusional theme, affective response, and behavioral response from naturalistic first-person speech transcripts.
- A systematic comparison of three multi-agent adjudication strategies for resolving LLM disagreement on clinically nuanced annotation tasks.
- An empirical evaluation across four levels of prompt complexity showing that progressively layered clinical context reduces false positive annotations while preserving diagnostic sensitivity.

2 Background

2.1 NLP for Psychotic Symptoms and Naturalistic Speech

NLP has increasingly been used to study language patterns associated with psychotic-spectrum disorders (Deneault et al., 2024; Hua et al., 2025a; Corcoran et al., 2020). Some early work focused primarily on clinical documentation extracted from electronic health records (Cohen et al., 2008, 2005; Irving et al., 2021). While valuable, such records reflect the clinician's interpretation of a patient's experience rather than the patient's own language, potentially obscuring the linguistic expression of beliefs that computational models aim to identify. As a result, recent work has increasingly examined patient-generated language, including from smartphone-based audio diaries, which capture individuals' experiences in their own words as they occur in everyday settings (Ben-Zeev et al., 2020). Recent work has applied NLP to identify disorganized thinking and cognitive biases in audio diaries (Xu et al., 2021; Tauscher et al., 2025), but the use of NLP to characterize delusional content remains largely underexplored. Unlike formal thought disorder, which NLP models quantify via semantic speech disruptions (Elvevåg et al., 2007), delusions represent disruptions in normative patterns of belief: recognizing them involves interpreting the beliefs expressed in language rather than whether this language is contextually consistent. This makes the task of automatically identifying delusional content more dependent on contextual interpretation and background knowledge than many traditional NLP applications.

2.2 Large Language Models for Complex Clinical Annotation

Artificial intelligence is playing a growing role in mental health research and practice (Ben-Zeev, 2026). Supervised machine learning depends on massive, expertly annotated datasets, which are

prohibitively expensive to acquire for fine-grained psychiatric symptoms (Wu et al., 2022). For text data, LLMs have emerged as a powerful alternative, demonstrating robust zero-shot (without any labeled examples) and few-shot (with only a few) classification capabilities (Labrak et al., 2024; Sivarajkumar et al., 2024). By employing Chain-of-Thought (CoT) prompting (Wei et al., 2022), LLMs can be instructed to explicitly articulate their diagnostic process, actively weighing inclusion criteria against exclusion rules (e.g., distinguishing a somatic abnormality from a nihilistic conviction). While domain-specific fine-tuned models often remain competitive for mental health classification tasks (Xu et al., 2024), CoT-prompted LLMs offer the advantage when there is limited task-specific training data, making them particularly suited to domains where large annotated corpora are unavailable.

While LLMs have rapidly expanded the scope of mental health NLP, recent scoping reviews identify persistent methodological limitations, including reliance on simulated clinical vignettes, restriction to narrow diagnostic categories, and poor performance on tasks requiring interpretation of highly subjective mental states (Le Glaz et al., 2021; Hua et al., 2025c,b). With delusions in particular, the field currently lacks validated prompt engineering frameworks capable of navigating the cascading decision processes required for hierarchical multi-label extraction from unstructured narratives.

2.3 Resolving Subjective Ambiguity with Multi-Agent Frameworks

Despite the promise of CoT reasoning, relying on a single LLM for complex clinical annotation is inherently brittle. Single-model inferences are prone to well-documented failure modes, including LLM hallucinations (generating text that is unrelated to the content of a prompt) and sycophancy (Ji et al., 2023; Sumita et al., 2024). In psychiatric contexts, where a narrative may simultaneously exhibit features of multiple delusional themes (e.g., a government conspiracy [Persecutory] broadcast through a television [Reference]), individual models risk inconsistently collapsing toward a single dominant label.

To mitigate these concerns, the NLP community has adopted multi-agent frameworks. Ensemble methods such as majority voting effectively smooth out individual biases (Wang et al., 2023). More advanced architectures enable models to interact: *multi-agent debate* prompts LLMs to critique and iteratively revise each other's outputs to encourage divergent thinking (Du et al., 2023; Liang et al., 2024), while the *LLM-as-a-Judge* paradigm employs a large highly capable model to adjudicate conflicting outputs based on reasoning paths (Zheng et al., 2023).

Recent NLP work has begun to question the benefits of multi-agent debate: Choi et al. (2025) show across seven benchmarks that majority voting alone accounts for most reported gains, while Wynn et al. (2025) attribute debate degradation to model sycophancy, the tendency of models to defer to others rather than defending correct answers. However, these findings have been established primarily on objective benchmarks. Whether they extend to clinical ambiguity, where disagreement stems from nuanced psychiatric interpretation rather than verifiable factual error, remains underexplored. In this paper, we extend these emerging findings to the clinical domain by deploying and comparing multi-agent adjudication strategies on a multi-label annotation task involving naturalistic psychiatric narratives.

3 Methods

Figure 1 illustrates the overarching architecture of our end-to-end multi-agent clinical extraction pipeline, with four primary phases: naturalistic data collection, progressive prompt engineering, independent LLM inference, and multi-agent adjudication.

3.1 Dataset

We used transcripts from ADAPT (Buck et al., 2023), a smartphone-based study in which 231 individuals with at least moderate persecutory ideation from 43 US states completed 30 days of audio diary recordings capturing momentary experiences and beliefs in naturalistic settings. Recordings were transcribed to yield free-text narratives from this clinically heterogeneous sample.

For this study, we selected the first available diary transcript for each participant that was longer than 30 seconds. We retained only entries exceeding three sentences to ensure sufficient content for multi-label annotation, yielding a final corpus of **136 transcripts**. Of these, 14 were reserved as a development set for iterative prompt engineering and model configuration, while the remaining 122 constituted the held-out evaluation set for all final

Figure 1: The end-to-end multi-agent clinical delusion annotation pipeline.

performance assessments reported in this paper.

3.2 Annotation Guideline and Human Labeling

We developed a structured annotation guideline for labeling audio diary transcripts capturing three dimensions of delusion expression: (1) presence and thematic category of delusional belief, (2) affective responses expressed in relation to the belief, and (3) behavioral responses that reflect how individuals act upon these experiences. The schema was developed iteratively using meta-analytic syntheses of delusional themes cross-referenced with Diagnostic and Statistical Manual of Mental Disorders (DSM) descriptions of delusional disorders and SNOMED CT terminology (Pappa et al., 2025; American Psychiatric Association, 2013; SNOMED International, 2024). The affective categories were informed by Ekman's theory of basic emotions, and the behavioral response categories were informed by cognitive models of delusions that emphasize safety behaviors, avoidance, threat monitoring, and help-seeking (Tracy and Randles, 2011; Ekman, 1992; Freeman, 2016). A comprehensive listing of all target classes and their final clinical definitions is provided in Appendix Table A.3.

Annotation was conducted by two licensed clinical psychologists, with discrepancies resolved by an adjudicator with expertise in clinical annotation guideline development. Annotators completed structured training sessions using expert-labeled examples, followed by independent pilot coding of 10% of transcripts to assess guideline clarity and initial inter-rater consistency. Discrepancies identified during the pilot phase were reviewed with annotators and used to refine coding procedures before full annotation proceeded. The adjudicator reviewed all disagreements and assigned final labels based on guideline criteria, retaining multiple labels when clinically appropriate. Pre-adjudication agreement reached 63.3% for affective response and 61.8% delusion presence, with behavioral response at 60.0% as reported in Appendix Table A.1.

3.3 Prompt Design and Engineering

The foundational prompt (**Level 1**) includes only the instructions of the basic task, the required output template (see the Appendix Table A.4), and the names of the clinical categories. Subsequent levels progressively layered additional context from the guideline: **Level 2** adds formal clinical definitions for each target category; **Level 3** integrates exclusionary rules (e.g., "Do NOT use when...") and diagnostic heuristics (e.g., "Key test: Is there a threat?") to help models distinguish between highly similar categories like *Reference* and *Persecutory* delusions; and **Level 4** adds short, clinician-validated transcript excerpts mapped to specific labels to provide in-context learning for conversational register and tone. This incremental design allowed a systematic evaluation of how structured clinical guidance influences classification behavior. Appendix Table A.2 illustrates this progression using the *Avoidance/ Withdrawal* behavioral category as an example.

3.4 Independent LLM-Based Clinical Annotation

To automate the annotation pipeline and establish reliable baseline measurements, we deployed three state-of-the-art, open-weight Large Language Models (LLMs) with 4-bit quantization (Dettmers and Zettlemoyer, 2023): **GLM-4.6 (357B)** (Team et al., 2025), **GPT-OSS (120B)** (OpenAI, 2026), and **Qwen-3 (235B)** (Yang et al., 2025). All models

were securely hosted on private servers behind an institutional firewall. Each transcript was initially independently annotated by these three foundation models. During inference, each model was instructed to generate its internal "thinking process" before yielding the final structured JSON output, providing the explicit context required for downstream adjudication of the models' clinical reasoning.

All models are configured with greedy decoding, setting `temperature=0`, `top_k=1`, and `max_new_tokens=4096`. In rare instances where a model failed to generate a valid JSON object, the pipeline triggered a fallback execution with the limit extended to `8192` tokens. On the 14-transcript development set, this deterministic configuration produced *Delusion Presence* F_1 scores of 1.00 (GLM-4.6) and 0.857 (GPT-OSS), compared with means of 0.857 ($\pm$0.051) and 0.914 ($\pm$0.032) across five stochastic runs at temperature 0.7. We adopt the deterministic setting for full-corpus evaluation to ensure reproducibility.

3.5 Multi-Agent Adjudication Frameworks

We developed and systematically compared three distinct multi-agent adjudication strategies to resolve diagnostic ambiguity:

Tri-Model Majority Voting: We implemented a consensus approach where a final transcript label was determined by a simple majority vote across all three independent models. In rare instances of a complete three-way disagreement (where each model produced a unique categorical label), Qwen-3 was utilized as the definitive decision-maker due to its strong standalone alignment with manual annotations on the validation set.

Direct Expert Adjudication: To evaluate the efficacy of the LLM-as-a-Judge paradigm, Qwen-3 was strictly deployed as an expert judge to resolve discrepancies between the GLM-4.6 and GPT-OSS annotators. The judge model was provided with the original transcript, expert guidelines, and conflicting GLM and GPT results. This input included the internal thinking processes of both annotator models, allowing the judge to determine the most accurate classification based on logical adherence to the clinical criteria (detailed prompt is in the Appendix Table A.5).

Multi-Agent Conversational Adjudication: To test whether interactive debate encourages error correction on subjective text, GLM-4.6 and GPT-OSS were instructed to deliberate over their disagreements. Each agent defended its original annotation using clinical reasoning, with instructions to concede to the opposing model if its logic was more accurate, or to propose a combined multi-label solution. After a maximum of two conversational turns, Qwen-3 reviewed the entire deliberation history to issue a final, authoritative ruling (detailed prompt is in the Appendix Table A.6).

3.6 Multi-Label Agreement Evaluation

Clinical targets in this study, specifically *Delusion Themes*, *Affective Expression*, and *Behavioral Responses*, frequently involve multiple overlapping labels within a single transcript. Furthermore, the distribution of these thematic labels is heavily imbalanced. To evaluate system performance across these complex categorical spaces, we utilized multi-label metrics depending on the evaluation phase:

Inter-Model Reliability: We report inter-model reliability between different LLMs using both **micro-averaged** and **macro-averaged Cohen's Kappa (κ)**. Micro-averaged κ is computed on flattened binary indicator matrices across all label-instance pairs, while macro-averaged κ is the unweighted mean of per-class κ values, treating each category equally regardless of its frequency.

Performance Against Human Ground Truth: We utilized two complementary F_1 metrics to evaluate performance against manual annotations. **micro-averaged F_1** aggregates all label-level predictions across the corpus, providing a robust measure of the system's global classification accuracy. Conversely, **Example-based F_1** calculates performance independently for each transcript and averages the results, reflecting the practical reliability of the system on an individual diary-level basis.

Finally, we report *Delusion Presence*, a binary target derived from the *Delusion Type* annotations indicating whether any delusional theme was detected. This serves as a clinically relevant screening metric independent of the specific thematic categorization. Although our annotation guideline includes an affective intensity, we excluded this from primary performance analyses due to low inter-rater agreement (29%) among expert annotators on this dimension.

4 Results

4.1 Individual Model Performance against Human Ground Truth

As shown in Table 1, all models achieved reasonable performance at Level 1. Under the fully contextualized Level 4 prompt, micro-averaged F_1 for *Delusion Presence* was notably stable, with GLM-4.6 (0.857), GPT-OSS (0.873), and Qwen-3-235B (0.839) all consistently identifying clinically relevant content. This indicates that detecting the basic presence of content suggesting a delusion requires relatively little in-context instruction.

However, moving to the complex multi-label classification of *Delusion Type* demonstrated the utility of the structured prompt engineering framework (see Figure 2). When provided with only the simplest prompt (Level 1), models achieved disproportionately high micro-averaged recall scores (0.75–0.89) but significantly lower micro-averaged precision scores (0.52–0.60), indicating many false positive category assignments. This gap narrowed substantially as clinical rules and few-shot examples were progressively introduced. With Level 4, micro-averaged precision for *Delusion Type* increased to 0.67–0.75, raising micro-averaged F_1 to 0.74–0.78 across models (for a comprehensive metric breakdown, see Appendix Table A.10).

Interestingly, the *Affective* and *Behavioral* targets revealed that prompt complexity does not universally improve performance across all clinical targets. For *Behavioral Response*, introducing the Level 4 rules successfully improved micro-averaged F_1 across all models (rising from 0.46–0.51 in Level 1 to 0.58–0.62 in Level 4), pulling models closer to the experts' clinical interpretations. In contrast, the highly constrained Level 4 prompt actually degraded performance on the *Affective Response* category, with micro-averaged F_1 dropping from 0.77–0.81 (Level 1) to 0.69–0.77 (Level 4).

4.2 Robustness of Tri-Model Majority Voting

As illustrated in Figure 3 and detailed in Appendix Table A.11, ensembling the three models systematically smoothed out individual model variance and established a robust performance ceiling. Under the fully contextualized Level 4 prompt, the Majority Vote achieved a 0.779 micro-averaged F_1 on *Delusion Type*, slightly exceeding the best individual model (GLM-4.6 at 0.777), and demonstrated remarkable stability across all prompt complexities. Even under the simplest Level 1 prompt (Category Only), the ensemble maintained a 0.746 micro-averaged F_1 on *Delusion Type*, substantially outperforming standalone models attempting the same task without rules (e.g., GPT-OSS at 0.649). With *Affective Response*, the micro-averaged F_1 score with majority vote was 0.839, exceeding that of the best individual model (0.813 for Qwen-3).

Other targets also benefited from this stabilization. For *Behavioral Response*, the ensemble successfully leveraged the strict Level 4 rules to increase from a baseline 0.545 (Level 1) to a peak 0.640 micro-averaged F_1. For *Affective Response*, the ensemble plateaued around 0.800 under Level 4, further confirming that rigid clinical rules cannot fully resolve affective nuance, even across multiple agents.

4.3 The Limitations of Expert Adjudication and Debate

We isolated the performance of the Qwen-3-235B judge approaches using the fully contextualized Level 4 prompt. We stratified the 122 manual transcripts into two subsets: cases where the two primary annotators (GLM-4.6 and GPT-OSS) initially agreed, and cases where they disagreed. When GLM-4.6 and GPT-OSS independently agreed on the *Delusion Type* ($N = 91$), their micro-averaged F_1 against the human gold standard was exceptionally high (0.857), substantially outperforming Qwen's independent baseline (0.800) on the same subset. This confirms that when LLMs naturally converge, their consensus is highly trustworthy. However, the 31 transcripts where GLM and GPT diverged represent the most clinically ambiguous narratives in the dataset. On this challenging subset, individual micro-averaged F_1 dropped (GLM: 0.615, GPT: 0.603, shown in Table A.12).

Prompting Qwen-3 to act as an LLM adjudicator over the GLM and GPT reasoning traces did not yield meaningful improvements (see Appendix Table A.12). The *Direct Judge* achieved a 0.618 micro-averaged F_1 on *Delusion Type* for the disagreement subset, offering scant improvement over the individual baseline models. For the targets of *Affective Response* (0.590) and *Behavioral Response* (0.571), the Direct Judge actually *underperformed* relative to individual baseline models.

More strikingly, the *Multi-Agent Conversational Adjudication* framework actively diminished performance on this ambiguous subset. Instead of refining the diagnostic boundaries through debate,

Clinical Target	Prompt Level	Micro-averaged F_1					
		Individual Models			Ensemble	Adjudication†	
		GLM-4.6	GPT-OSS	Qwen-3	Majority Vote	Direct Judge	Debate
Delusion Presence	Level 1 (Category)	0.865	0.855	0.809	0.853	—	—
	Level 4 (Full Prompt)	0.857	**0.873**	0.839	0.872	0.866	0.835
Delusion Type	Level 1 (Category)	0.707	0.649	0.667	0.746	—	—
	Level 4 (Full Prompt)	0.777	0.762	0.736	**0.779**	0.775	0.765
Affective Response	Level 1 (Category)	0.797	0.774	0.813	**0.839**	—	—
	Level 4 (Full Prompt)	0.694	0.760	0.768	0.800	0.738	0.719
Behavioral Response	Level 1 (Category)	0.507	0.456	0.513	0.545	—	—
	Level 4 (Full Prompt)	0.615	0.582	0.582	**0.640**	0.584	0.634

Table 1: Comprehensive performance comparison (micro-averaged F_1) evaluated against the full test corpus ($N = 122$). The best overall performance for each target is highlighted in bold. †Adjudication scores reflect corpus-level performance: for transcripts where GLM-4.6 and GPT-OSS initially agreed ($N = 91$), their consensus is retained; the adjudicator is invoked only on disagreement cases ($N = 31$). See Table A.12 for stratified results.



Figure 2: Micro-averaged precision (left) and recall (right) against human expert annotations for *Delusion Type* across the four prompt complexity levels.



Figure 3: Micro-averaged F_1 for the Three Independent Models and Tri-Model Majority Vote against human expert annotations for *Delusion Type* across the four prompt complexity levels.

conversational adjudication reduced performance on *Delusion Type* down to a 0.545 micro-averaged F_1. This degradation was even more severe on the high-stakes binary screening task of *Delusion Presence*, dropping to 0.667.

A representative debate failure illustrates this pattern. In one transcript, the speaker states "I feel like people…Google me or research me online trying to find things to use against me," framed with uncertainty markers ("I feel like," "I guess") and self-awareness about the thought ("I have to take a while before I realize how irrational that they are"). The human annotators labeled this as *Persecutory*. GPT-OSS independently produced the correct *Persecutory* label, while GLM-4.6 rejected the presence of any delusion on the grounds that expressed doubt and insight are incompatible with fixed conviction. When the two models were placed in debate, GPT-OSS abandoned its correct

initial assessment within a single turn ("I agree with Annotator 1 – the passage does not contain a delusion"), restated GLM's form-versus-content reasoning, and explicitly conceded by Turn 2 ("I concede to Annotator 1's conclusion"). The judge confirmed the empty label, overriding GPT-OSS's correct initial annotation. This case illustrates how conversational adjudication can convert a correct prediction into an incorrect consensus: rather than defending an evidence-based position, the model with the right answer accommodated the more elaborately argued wrong answer.

4.4 Inter-Model Agreement and Prompt Complexity Analysis

To assess baseline consistency, we computed pairwise Cohen's κ across the three LLMs under the Level 4 prompt (see Appendix Table A.13). Models showed strong micro-averaged agreement on *Delusion Presence* (κ = 0.67–0.72) and *Delusion Type* (κ = 0.73–0.78). However, macro-averaged κ, which weights each class equally rather than allowing dominant labels to drive the score, was substantially lower for *Delusion Type* (κ = 0.43–0.52, averaged over 16 classes), reflecting weaker agreement on rare categories. This pattern was even more pronounced for response-related targets: *Affective Response* dropped from micro κ = 0.64–0.69 to macro κ = 0.30–0.41 (7 classes), and *Behavioral Response* from micro κ = 0.24–0.42 to macro κ = 0.09–0.20 (8 classes).

5 Discussion

To our knowledge, this study presents the first automated, multi-agent LLM pipeline for the fine-grained, multi-label annotation of delusions from naturalistic audio diaries. Without explicit constraints (Level 1), models generate many overlapping labels, capturing the correct category but maximizing recall at a severe expense to precision. This behavior aligns with the well-known tendency of LLMs to make broad and generalized semantic associations when faced with ambiguity (Ji et al., 2023; Huang et al., 2023). The introduction of strict exclusionary rules (Level 4) transformed this into a decision process with precise categorical boundaries. This finding is consistent with prior work on instruction-following, where including explicit negative examples and exclusionary guidance (e.g., "Things to Avoid") in task instructions has been shown to improve model generalization (Mishra et al., 2022; Wang et al., 2022). In our clinical context, negative constraints, rules specifying what *not* to label, were as important as category definitions for achieving precise classification.

While rigid definitions improved the extraction of delusional themes and behavioral responses, they actively impaired classification of affective responses. In naturalistic audio diaries, affect is rarely explicitly stated; it is implicit and highly contextual (Ritunnano et al., 2022). Strict exclusionary rules may pull models away from the intuitive consensus that human raters naturally share (Tauscher et al., 2023). This may reflect differences in the maturity and specificity of the annotation schema and prompt design across clinical targets rather than a fundamental limitation of prompt engineering. The affective response guidelines in this study were less extensively specified than the delusion-type taxonomy, potentially constraining the effectiveness of rigid rule-based prompting for these categories. Class imbalance likely compounds this effect: both affective and behavioral labels are dominated by a single category (*Fear-Anxiety* and *Avoidance/Withdrawal*, respectively; Appendix Tables A.8 and A.9), allowing simple prompts to achieve high scores through majority-class accuracy while strict rules introduce errors on less frequent categories.

Our findings on multi-agent adjudication further reveal that clinical ambiguity resists resolution through more elaborate reasoning and debate. On the 31 transcripts in which models disagreed, conversational debate degraded performance rather than resolving ambiguity, while majority voting remained the most robust strategy. We attribute the failure of multi-agent debate to a phenomenon where models prioritize agreement over accuracy, a behavior often referred to as model sycophancy (Sharma et al., 2023; Perez et al., 2023). In tasks with verifiable answers, debate can be effective, but in psychiatric evaluation there is seldom indisputable ground truth. When critiquing others' assessments of ambiguous audio diaries, the LLMs dispensed with their diagnostic prompts. Rather than defending their initial assessments, they were prone to excessive accommodation, frequently blending their initial assignments to reach a compromise.

Despite the inherent challenges of multi-label classification, our findings suggest that LLMs have strong potential for the rapid, automated assessment of diagnostic features of naturalistic narra-

tives. Across all evaluated models, prompt complexities, and adjudication frameworks, the baseline detection of *Delusion Presence* remained remarkably stable, consistently achieving a Micro F_1 exceeding 0.85. Notably, the ensemble's advantage was most pronounced on affective and behavioral targets: for *Affective Response*, majority voting at Level 1 achieved the highest score in our evaluation (0.839), substantially exceeding any individual model, suggesting that independent ensembling is particularly effective where individual models diverge. This indicates that our pipeline is a viable high-throughput tool for screening audio diaries, with the potential to flag clinically relevant content for expert review. Furthermore, by employing a simple tri-model majority vote alongside our Level 4 prompt, researchers can now automate the fine-grained extraction of specific delusional themes with a degree of reliability that rivals human inter-rater consensus (Di Forti et al., 2025). This approach addresses the traditional bottleneck of manual coding, presenting new avenues for longitudinal symptom tracking, and LLM-derived labels could further serve as training data for smaller, efficient classifiers deployable in resource-constrained settings.

6 Conclusion

In this work, we introduced a fully automated, multi-agent LLM pipeline for multi-label annotation of delusions, affect, and behavioral responses from unstructured audio diaries. Results from systematically comparing prompt engineering strategies indicate that while detailed clinical prompts successfully reduce confabulated false positive categories for descriptions of delusional content, they can constrain the interpretation of implicit affective or behavioral states. Furthermore, our evaluation of multi-agent adjudication frameworks shows that for clinically ambiguous text, complex interactive debate actively degrades model accuracy by inducing premature consensus. Instead, simply pooling the independent inferences of a heterogeneous LLM ensemble establishes robust performance. These findings demonstrate that LLM-based pipelines can reliably automate the characterization of delusional content in naturalistic speech, offering a scalable path toward continuous, longitudinal symptom monitoring that could support early detection of clinical deterioration and more timely intervention for individuals with serious mental illness.

Limitations

Several limitations of this study should inform future work. First, our evaluation was conducted on a relatively specialized corpus of audio diary transcripts collected from individuals experiencing moderate-to-severe persecutory ideation. Consequently, the dataset is heavily skewed toward *Persecutory* themes, and the micro-averaged F_1 scores reported here reflect agreement on frequent labels more than on rare categories. Future validation on broader psychiatric cohorts is necessary to confirm the generalizability of the pipeline. Second, while we evaluated three highly capable, distinct LLMs to ensure heterogeneity, the rapid evolution of model architectures creates the possibility that future foundation models may exhibit different baseline sycophancy behaviors. Third, the lower performance on affective and behavioral response classification likely reflects both the implicit and contextual nature of these targets and limitations in the current prompt design. Future work should explore alternative prompting strategies for these targets, such as dedicated annotation passes or less constrained prompt architectures that better accommodate the implicit nature of affective expression in naturalistic speech.

Ethical Considerations

Human subjects: The ADAPT study was approved by the University of Washington Institutional Review Board (IRB) under protocol STUDY00001321. All participants provided informed consent for audio recording and analysis (Buck et al., 2023). All transcripts were fully de-identified, and all LLMs were deployed locally to ensure no clinical narratives left the secure research environment.

Intended use and risks: This pipeline is a *research tool* for scalable annotation, not a diagnostic instrument. Automated classification of delusional content carries risks of misclassifications; any clinical application must include human expert review. Transcript examples used in the prompt templates are clinician-authored illustrations. The transcript excerpt presented in Section 4.3 is drawn from de-identified participant transcript.

Generalizability and reuse: Performance may vary across demographic or clinical populations beyond the ADAPT sample. Our prompt templates are intended for research purposes only and will be made available upon request.

Acknowledgments

This work was supported by the National Institutes of Health (NIH) under award number UF1MH135901. The ADAPT dataset used in this study was collected with support from the National Institute of Mental Health (NIMH) under award number R01MH112641, and a NARSAD Young Investigator Grant from the Brain and Behavior Research Foundation (Grant #27917). The content is solely the responsibility of the authors and does not necessarily represent the official views of the NIH, NIMH, or the Brain and Behavior Research Foundation.

References

American Psychiatric Association. 2013. *Diagnostic and Statistical Manual of Mental Disorders*, fifth edition edition. American Psychiatric Association.

Elham Asgari, Nina Montaña-Brown, Magda Dubois, Saleh Khalil, Jasmine Balloch, Joshua Au Yeung, and Dominic Pimenta. 2025. A framework to assess clinical safety and hallucination rates of LLMs for medical text summarisation. *npj Digital Medicine*, 8(1):274.

Imogen H. Bell, Emily Eisner, Stephanie Allan, Sharla Cartner, John Torous, Sandra Bucci, and Neil Thomas. 2024. Methodological Characteristics and Feasibility of Ecological Momentary Assessment Studies in Psychosis: a Systematic Review and Meta-Analysis. *Schizophrenia Bulletin*, 50(2):238–265.

Dror Ben-Zeev. 2026. To AI, or Not to AI: That Is Not the Question. *Psychiatric Services*, 77(2):94–95.

Dror Ben-Zeev, Benjamin Buck, Ayesha Chander, Rachel Brian, Weichen Wang, David Atkins, Carolyn J. Brenner, Trevor Cohen, Andrew Campbell, and Jeffrey Munson. 2020. Mobile RDoC: Using Smartphones to Understand the Relationship Between Auditory Verbal Hallucinations and Need for Care. *Schizophrenia Bulletin Open*, 1(1):sgaa060.

Dror Ben-Zeev, Gregory J. McHugo, Haiyi Xie, Katy Dobbins, and Michael A. Young. 2012. Comparing retrospective reports to real-time/real-place mobile assessments in individuals with schizophrenia and a nonclinical comparison group. *Schizophrenia Bulletin*, 38(3):396–404.

Benjamin Buck, Mary Wingerson, Justin S. Tauscher, Matthew Enkema, Weichen Wang, Andrew T. Campbell, and Dror Ben-Zeev. 2023. Using Smartphones to Identify Momentary Characteristics of Persecutory Ideation Associated With Functional Disability. *Schizophrenia Bulletin Open*, 4(1).

Chi-Min Chan, Weize Chen, Yusheng Su, Jianxuan Yu, Wei Xue, Shanghang Zhang, Jie Fu, and Zhiyuan Liu. 2023. ChatEval: Towards Better LLM-based Evaluators through Multi-Agent Debate. *arXiv preprint*. Version Number: 1.

Hyeong Kyu Choi, Xiaojin Zhu, and Sharon Li. 2025. Debate or Vote: Which Yields Better Decisions in Multi-Agent Large Language Models? *arXiv preprint*. ArXiv:2508.17536 [cs].

Trevor Cohen, Brett Blatter, and Vimla Patel. 2005. Exploring dangerous neighborhoods: latent semantic analysis and computing beyond the bounds of the familiar. *AMIA ... Annual Symposium proceedings. AMIA Symposium*, 2005:151–155.

Trevor Cohen, Brett Blatter, and Vimla Patel. 2008. Simulating expert clinical comprehension: adapting latent semantic analysis to accurately extract clinical concepts from psychiatric narrative. *Journal of Biomedical Informatics*, 41(6):1070–1087.

Cheryl M. Corcoran, Vijay A. Mittal, Carrie E. Bearden, Raquel E. Gur, Kasia Hitczenko, Zarina Bilgrami, Aleksandar Savic, Guillermo A. Cecchi, and Phillip Wolff. 2020. Language as a biomarker for psychosis: A natural language processing approach. *Schizophrenia Research*, 226:158–166.

Antoine Deneault, Alexandre Dumais, Marie Désilets, and Alexandre Hudon. 2024. Natural Language Processing and Schizophrenia: A Scoping Review of Uses and Challenges. *Journal of Personalized Medicine*, 14(7).

Tim Dettmers and Luke Zettlemoyer. 2023. The case for 4-bit precision: k-bit inference scaling laws. In *International Conference on Machine Learning*, pages 7750–7774. PMLR.

C. L. Di Forti, D. Liccione, and C. Scarpazza. 2025. Inter-rater reliability of psychiatric diagnosis: a systematic review and metanalysis. *European Psychiatry*, 68(Suppl 1):S191–S192.

Yilun Du, Shuang Li, Antonio Torralba, Joshua B. Tenenbaum, and Igor Mordatch. 2023. Improving Factuality and Reasoning in Language Models through Multiagent Debate. *arXiv preprint*. Version Number: 1.

Paul Ekman. 1992. Are there basic emotions? *Psychological Review*, 99(3):550–553.

Brita Elvevåg, Peter W. Foltz, Daniel R. Weinberger, and Terry E. Goldberg. 2007. Quantifying incoherence in speech: an automated methodology and novel application to schizophrenia. *Schizophrenia Research*, 93(1-3):304–316.

Daniel Freeman. 2016. Persecutory delusions: a cognitive perspective on understanding and treatment. *The Lancet Psychiatry*, 3(7):685–692.

Daniel Freeman, Philippa A. Garety, Paul E. Bebbington, Benjamin Smith, Rebecca Rollinson, David

Fowler, Elizabeth Kuipers, Katarzyna Ray, and Graham Dunn. 2005. Psychological investigation of the structure of paranoia in a non-clinical population. *The British Journal of Psychiatry: The Journal of Mental Science*, 186:427–435.

G. Haddock, J. McCARRON, N. Tarrier, and E. B. Faragher. 1999. Scales to measure dimensions of hallucinations and delusions: the psychotic symptom rating scales (PSYRATS). *Psychological Medicine*, 29(4):879–889.

Søren Esben Rytter Heilskov, Annick Urfer-Parnas, and Julie Nordgaard. 2020. Delusions in the general population: A systematic review with emphasis on methodology. *Schizophrenia Research*, 216:48–55.

Yining Hua, Suzanne V. Blackley, Ann K. Shinn, Joseph P. Skinner, Lauren V. Moran, and Li Zhou. 2025a. Identifying psychosis episodes in psychiatric admission notes via rule-based methods, machine learning, and pre-trained language models. *Translational Psychiatry*, 15(1):520.

Yining Hua, Fenglin Liu, Kailai Yang, Zehan Li, Hongbin Na, Yi-han Sheu, Peilin Zhou, Lauren V. Moran, Sophia Ananiadou, David A. Clifton, Andrew Beam, and John Torous. 2025b. Large Language Models in Mental Health Care: A Scoping Review. *Current Treatment Options in Psychiatry*, 12(1):27.

Yining Hua, Hongbin Na, Zehan Li, Fenglin Liu, Xiao Fang, David Clifton, and John Torous. 2025c. A scoping review of large language models for generative tasks in mental health care. *NPJ digital medicine*, 8(1):230.

Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qianglong Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, and Ting Liu. 2023. A Survey on Hallucination in Large Language Models: Principles, Taxonomy, Challenges, and Open Questions. *arXiv preprint*. Version Number: 2.

Jessica Irving, Rashmi Patel, Dominic Oliver, Craig Colling, Megan Pritchard, Matthew Broadbent, Helen Baldwin, Daniel Stahl, Robert Stewart, and Paolo Fusar-Poli. 2021. Using Natural Language Processing on Electronic Health Records to Enhance Detection and Prediction of Psychosis Risk. *Schizophrenia Bulletin*, 47(2):405–414.

Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Ye Jin Bang, Andrea Madotto, and Pascale Fung. 2023. Survey of Hallucination in Natural Language Generation. *ACM Computing Surveys*, 55(12):1–38.

Anzalee Khan, William Christian Yavorsky, Stacy Liechti, Guillermo DiClemente, Brian Rothman, Mark Opler, Ashleigh DeFries, and Sofija Jovic. 2013. Assessing the sources of unreliability (rater, subject, time-point) in a failed clinical trial using items of the Positive and Negative Syndrome Scale (PANSS). *Journal of Clinical Psychopharmacology*, 33(1):109–117.

Chandra Kiran and Suprakash Chaudhury. 2009. Understanding delusions. *Industrial Psychiatry Journal*, 18(1):3–18.

Yanis Labrak, Mickael Rouvier, and Richard Dufour. 2024. A Zero-shot and Few-shot Study of Instruction-Finetuned Large Language Models Applied to Clinical and Biomedical Tasks. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 2049–2066, Torino, Italia. ELRA and ICCL.

Aziliz Le Glaz, Yannis Haralambous, Deok-Hee Kim-Dufor, Philippe Lenca, Romain Billot, Taylor C. Ryan, Jonathan Marsh, Jordan DeVylder, Michel Walter, Sofian Berrouiguet, and Christophe Lemey. 2021. Machine Learning and Natural Language Processing in Mental Health: Systematic Review. *Journal of Medical Internet Research*, 23(5):e15708.

Tian Liang, Zhiwei He, Wenxiang Jiao, Xing Wang, Yan Wang, Rui Wang, Yujiu Yang, Shuming Shi, and Zhaopeng Tu. 2024. Encouraging Divergent Thinking in Large Language Models through Multi-Agent Debate. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 17889–17904, Miami, Florida, USA. Association for Computational Linguistics.

Swaroop Mishra, Daniel Khashabi, Chitta Baral, and Hannaneh Hajishirzi. 2022. Cross-Task Generalization via Natural Language Crowdsourcing Instructions. *arXiv preprint*. ArXiv:2104.08773 [cs].

Inez Myin-Germeys, Zuzana Kasanova, Thomas Vaessen, Hugo Vachon, Olivia Kirtley, Wolfgang Viechtbauer, and Ulrich Reininghaus. 2018. Experience sampling methodology in mental health research: new insights and technical developments. *World Psychiatry*, 17(2):123–132.

OpenAI. 2026. Introducing gpt-oss.

Elisavet Pappa, Fidelia Baah, Jessica Lynch, Lisha Shiel, Graham Blackman, Nichola Raihani, and Vaughan Bell. 2025. Delusional Themes are More Varied Than Previously Assumed: A Comprehensive Systematic Review and Meta-Analysis. *Schizophrenia Bulletin*, 51(3):637–645.

Ethan Perez, Sam Ringer, Kamile Lukosiute, Karina Nguyen, Edwin Chen, Scott Heiner, Craig Pettit, Catherine Olsson, Sandipan Kundu, Saurav Kadavath, Andy Jones, Anna Chen, Benjamin Mann, Brian Israel, Bryan Seethor, Cameron McKinnon, Christopher Olah, Da Yan, Daniela Amodei, and 44 others. 2023. Discovering Language Model Behaviors with Model-Written Evaluations. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 13387–13434, Toronto, Canada. Association for Computational Linguistics.

Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. 2022. Robust Speech Recognition via Large-Scale Weak

Supervision. *arXiv preprint*. ArXiv:2212.04356 [eess].

Rosa Ritunnano, Joshua Kleinman, Danniella Whyte Oshodi, Maria Michail, Barnaby Nelson, Clara S. Humpston, and Matthew R. Broome. 2022. Subjective experience and meaning of delusions in psychosis: a systematic review and qualitative evidence synthesis. *The Lancet. Psychiatry*, 9(6):458–476.

Mrinank Sharma, Meg Tong, Tomasz Korbak, David Duvenaud, Amanda Askell, Samuel R. Bowman, Newton Cheng, Esin Durmus, Zac Hatfield-Dodds, Scott R. Johnston, Shauna Kravec, Timothy Maxwell, Sam McCandlish, Kamal Ndousse, Oliver Rausch, Nicholas Schiefer, Da Yan, Miranda Zhang, and Ethan Perez. 2023. Towards Understanding Sycophancy in Language Models. *arXiv preprint*. Version Number: 4.

Sonish Sivarajkumar, Mark Kelley, Alyssa Samolyk-Mazzanti, Shyam Visweswaran, and Yanshan Wang. 2024. An Empirical Evaluation of Prompting Strategies for Large Language Models in Zero-Shot Clinical Natural Language Processing: Algorithm Development and Validation Study. *JMIR Medical Informatics*, 12:e55318.

SNOMED International. 2024. SNOMED CT.

Yasuaki Sumita, Koh Takeuchi, and Hisashi Kashima. 2024. Cognitive Biases in Large Language Models: A Survey and Mitigation Experiments. *arXiv preprint*. Version Number: 1.

Justin Tauscher, Xiruo Ding, Sarah Kopelovich, Arun Nagendra, Kevin Lybarger, Trevor Cohen, and Dror Ben-Zeev. 2025. Automated Flagging of Cognitive Biases in the Spoken Language of People with Hallucination Experiences. *Journal of Technology in Behavioral Science*.

Justin S. Tauscher, Kevin Lybarger, Xiruo Ding, Ayesha Chander, William J. Hudenko, Trevor Cohen, and Dror Ben-Zeev. 2023. Automated Detection of Cognitive Distortions in Text Exchanges Between Clinicians and People With Serious Mental Illness. *Psychiatric Services*, 74(4):407–410.

GLM-4.5 Team, Aohan Zeng, Xin Lv, Qinkai Zheng, Zhenyu Hou, Bin Chen, Chengxing Xie, Cunxiang Wang, Da Yin, Hao Zeng, Jiajie Zhang, Kedong Wang, Lucen Zhong, Mingdao Liu, Rui Lu, Shulin Cao, Xiaohan Zhang, Xuancheng Huang, Yao Wei, and 152 others. 2025. GLM-4.5: Agentic, Reasoning, and Coding (ARC) Foundation Models.

Jessica L. Tracy and Daniel Randles. 2011. Four Models of Basic Emotions: A Review of Ekman and Cordaro, Izard, Levenson, and Panksepp and Watt. *Emotion Review*, 3(4):397–405.

J. van Os, R. J. Linscott, I. Myin-Germeys, P. Delespaul, and L. Krabbendam. 2009. A systematic review and meta-analysis of the psychosis continuum: evidence for a psychosis proneness-persistence-impairment model of psychotic disorder. *Psychological Medicine*, 39(2):179–195.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. 2023. Self-Consistency Improves Chain of Thought Reasoning in Language Models. *arXiv preprint*. ArXiv:2203.11171 [cs].

Yizhong Wang, Swaroop Mishra, Pegah Alipoormolabashi, Yeganeh Kordi, Amirreza Mirzaei, Atharva Naik, Arjun Ashok, Arut Selvan Dhanasekaran, Anjana Arunkumar, David Stap, Eshaan Pathak, Giannis Karamanolakis, Haizhi Lai, Ishan Purohit, Ishani Mondal, Jacob Anderson, Kirby Kuznia, Krima Doshi, Kuntal Kumar Pal, and 16 others. 2022. Super-NaturalInstructions: Generalization via Declarative Instructions on 1600+ NLP Tasks. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 5085–5109, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed H. Chi, Quoc V. Le, and Denny Zhou. 2022. Chain-of-thought prompting elicits reasoning in large language models. In *Proceedings of the 36th International Conference on Neural Information Processing Systems*, NIPS '22, pages 24824–24837, Red Hook, NY, USA. Curran Associates Inc.

Honghan Wu, Minhong Wang, Jinge Wu, Farah Francis, Yun-Hsuan Chang, Alex Shavick, Hang Dong, Michael T. C. Poon, Natalie Fitzpatrick, Adam P. Levine, Luke T. Slater, Alex Handy, Andreas Karwath, Georgios V. Gkoutos, Claude Chelala, Anoop Dinesh Shah, Robert Stewart, Nigel Collier, Beatrice Alex, and 4 others. 2022. A survey on clinical natural language processing in the United Kingdom from 2007 to 2022. *npj Digital Medicine*, 5(1):186.

Andrea Wynn, Harsh Satija, and Gillian Hadfield. 2025. Talk Isn't Always Cheap: Understanding Failure Modes in Multi-Agent Debate. *arXiv preprint*. ArXiv:2509.05396 [cs].

Weizhe Xu, Jake Portanova, Ayesha Chander, Dror Ben-Zeev, and Trevor Cohen. 2021. The centroid cannot hold: comparing sequential and global estimates of coherence as indicators of formal thought disorder. In *AMIA Annual Symposium Proceedings*, volume 2020, page 1315.

XUHAI Xu, BINGSHENG YAO, YUANZHE DONG, SAADIA GABRIEL, HONG YU, JAMES HENDLER, MARZYEH GHASSEMI, ANIND K. DEY, and DAKUO WANG. 2024. Mental-LLM: Leveraging Large Language Models for Mental Health Prediction via Online Text Data. *Proceedings of the ACM on interactive, mobile, wearable and ubiquitous technologies*, 8(1):31.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, and 41 others. 2025. Qwen3 Technical Report. *arXiv preprint*. ArXiv:2505.09388 [cs.CL].

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. 2023. Judging LLM-as-a-judge with MT-bench and Chatbot Arena. In *Proceedings of the 37th International Conference on Neural Information Processing Systems*, NIPS '23, pages 46595–46623, Red Hook, NY, USA. Curran Associates Inc.

Appendix

Clinical Target	N	Agree	Disagree
Delusion Presence[a]	136	61.8%	38.2%
Delusion Type[a]	136	58.1%	41.9%
Delusion Type[b]	60	91.7%	8.3%
Affective Response[b]	60	63.3%	36.7%
Affective Intensity[c]	31	29.0%	71.0%
Behavioral Response[b]	60	60.0%	40.0%

Table A.1: Pre-adjudication agreement between two licensed clinical psychologist annotators. [a]Calculated across all transcripts. [b]Calculated on transcripts where both annotators agreed on delusion presence. [c]Calculated on transcripts where both annotators agreed on the presence of an affective response.

Complexity Level	Prompt Text Provided to LLM (Example: Avoidance/Withdrawal)
Level 1: Base	1. Avoidance/Withdrawal:
Level 2: + Definition	1. Avoidance/Withdrawal: Behaviors aimed at escaping, avoiding, or disengaging from situations, people, or cues linked to distress or delusional beliefs. The individual reduces contact rather than taking action to increase safety.
Level 3: + Rules	1. Avoidance/Withdrawal: Behaviors aimed at escaping, avoiding, or disengaging from situations, people, or cues linked to distress or delusional beliefs. The individual reduces contact rather than taking action to increase safety. Key test: Is the person pulling away, avoiding, or removing themselves from something?
Level 4: + Examples (Final Prompt)	1. Avoidance/Withdrawal: Behaviors aimed at escaping, avoiding, or disengaging from situations, people, or cues linked to distress or delusional beliefs. The individual reduces contact rather than taking action to increase safety. Examples: i. "I don't leave my house anymore because I'm scared someone will follow me." ii. "I avoid drinking tap water because I think it's poisoned." iii. "I stopped watching TV because I feel like they're sending me messages." Key test: Is the person pulling away, avoiding, or removing themselves from something?

Table A.2: Incremental prompt construction methodology, demonstrating how clinical context was progressively layered using the Avoidance/Withdrawal category.

Class	Definition
Clinical Target: Delusion Type	
Reference	Belief that neutral events, objects, or people contain special messages meant specifically for the individual.
Grandiosity	Belief that one possesses exceptional abilities, fame, power, identity, or destiny.
Religious	Beliefs involving divine authority, supernatural missions, spiritual transformation, or demonic forces.
Mind Reading	Belief that the individual can read other people's thoughts or mentally access their internal experiences.
Persecutory	Belief that others intend harm, surveillance, sabotage, or conspiracy against the individual.
Guilt/Sin	Belief that one has committed catastrophic wrongdoing or deserves extreme punishment despite no evidence.
Control	Belief that one's actions, emotions, or impulses are being controlled by an external force.
Somatic	Delusions about the body being diseased, damaged, infested, altered, or malfunctioning. Includes hypochondriacal delusions when medically plausible illnesses are believed with delusional certainty.
Nihilistic	Belief that oneself, parts of the body, or the world no longer exist, are dead, or have been destroyed. Includes a conviction that a major catastrophe will occur.
Erotomanic	Belief that another person, often someone of higher status, is in love with the individual.
Sexual	Delusional beliefs involving sexual content, intrusion, coercion, exposure, or sexual manipulation.
Jealous	Belief, without evidence, that a partner is being unfaithful.
Thought Withdrawal	Belief that an outside force is removing one's thoughts.
Thought Insertion	Belief that thoughts are placed into one's mind by an outside entity.
Thought Broadcasting	Belief that one's thoughts are being transmitted to others.
Unspecified	When the dominant delusional belief cannot be clearly determined or is not described in the specific types.
Clinical Target: Affective Response	
Fear-Anxiety	Indicates expressed fear, worry, tension, or apprehension about the experience.
Sadness-Despair	Indicates expressed sadness, hopelessness, emotional exhaustion, or despair.
Anger-Frustration	Indicates expressed irritation, anger, resentment, or frustration.
Euphoria-Excitement	Indicates expressed elation, pleasure, excitement, or energized positive affect (can include grandiose themes).
Hope-Optimism	Indicates expressed hopefulness, positive expectation, or belief in improvement or recovery.
Satisfaction-Contentment	Indicates expressed calm, peace, fulfillment, or a stable sense of well-being.
Neutral-None	Indicates no clearly expressed emotion, or a flat, matter-of-fact tone without affective coloring.
Clinical Target: Behavioral Response	
Avoidance/Withdrawal	Behaviors aimed at escaping, avoiding, or disengaging from situations, people, or cues linked to distress or delusional beliefs. The individual reduces contact rather than taking action to increase safety.
Safety-Seeking/Protective Behaviors	Behaviors intended to prevent harm or increase perceived safety, while still engaging with the environment. These include active protective steps, precautionary rituals, or hypervigilant routines.
Confrontation/Resistance	Behaviors involving direct action toward the perceived threat or source of delusional content such as challenging, disrupting, or fighting back.
Help-Seeking	Behaviors involving reaching out to others including friends, family, clinicians to obtain support, validation, or practical assistance.
Self-Soothing/Regulation	Behaviors aimed at calming oneself, reducing distress, or managing emotions internally. These are coping behaviors rather than actions directed toward external threats.
Engagement/Acceptance	Behaviors showing constructive engagement with reality, acceptance of experiences, or efforts to refocus on meaningful activity. Often reflects cognitive reframing or functional coping.
Risky or Harmful Behaviors	Behaviors that pose risk of harm to the individual or others, including self-harm, aggression, reckless acts, or substance misuse.
Neutral/None	Indicates that no specific behavioral response is described, or the individual does not mention any actions related to their experiences.

Table A.3: Comprehensive list of classes and their exact clinical definitions for Delusion Type, Affective Response, and Behavioral Response, as provided to the annotators and language models in the final guidelines.

Base Task Instructions and Output Formatting

ANNOTATION GUIDELINES FOR CLINICAL TARGETS

Audio diary transcripts will be annotated for various clinical targets, including hallucination content, delusions, substance use, and other relevant factors.

Each diary will be labeled as containing one or more clinical targets, and the relevant spans within the diary entry will be identified and annotated. These spans will represent triggers and entities associated with each clinical target, providing a detailed understanding of the individual's experiences and symptoms.

The following sections describe how each clinical target will be annotated. For each annotated clinical target, some entities are required and must always be present, while others may not always be present.

Note: A transcript may contain multiple delusion themes. These can be:

• The same span with multiple themes (e.g., a statement that is both Persecutory and Reference)

• Different spans with different themes

List each `delusion_span` and `delusion_type` pair separately in order.

Follow the following response template for your final answer.

Response Template and In-Context Formatting Examples

example input

I know they are monitoring my email, and I feel afraid all the time.

response template

`delusion_span`: "I know they are monitoring my email"
`delusion_type`: Persecutory
`affective_span`: "I feel afraid all the time"
`affective_category`: Fear-Anxiety
`affective_intensity`: Moderate
`behavioral_span`: null
`behavioral_category`: null

example input (multiple delusion themes)

God told me I am chosen to save humanity, and the government is trying to stop me.

response template

`delusion_span`: "God told me I am chosen to save humanity"
`delusion_type`: Religious
`delusion_span`: "God told me I am chosen to save humanity"
`delusion_type`: Grandiose
`delusion_span`: "the government is trying to stop me"
`delusion_type`: Persecutory
`affective_span`: null
`affective_category`: null
`affective_intensity`: null
`behavioral_span`: null
`behavioral_category`: null

example input (no delusion detected)

Today was a good day. I went to work and had lunch with a friend.

response template

`delusion_span`: null
`delusion_type`: null
`affective_span`: null
`affective_category`: null
`affective_intensity`: null
`behavioral_span`: null
`behavioral_category`: null

Table A.4: The high-level prompt structure (Base Task Instructions) provided to the language models. This foundational section establishes the extraction task, provides rules for handling multiple overlapping labels, and enforces a strict structured output format using explicit in-context examples.

Framework 1: Direct Adjudication Prompt (Example: Delusion Type)

You are an expert clinical judge evaluating delusion type annotations. Two models have annotated the same text and disagree on the delusion type.

Here are the original annotation guidelines that were used:
`{delusion_guidelines}`

— Original Text —
`{text}`

— MODEL A ANALYSIS —
Thinking Process: `{glm_thinking}`
Detailed Annotation: `{glm_response}`
Classification: `{glm_delusion}`

— MODEL B ANALYSIS —
Thinking Process: `{gptoss_thinking}`
Detailed Annotation: `{gptoss_response}`
Classification: `{gptoss_delusion}`

Based on the clinical guidelines above and considering both models' reasoning and annotation spans, determine the correct classification. You may:
- Choose Model A if their annotation is more accurate
- Choose Model B if their annotation is more accurate
- Choose Combined if both have valid points and the final answer should merge or differ from both

Provide your judgment in this exact format:
WINNER: (Model A | Model B | Combined)
REASONING: (Brief explanation)
CORRECT_TYPE: (The correct delusion type or comma-separated list if multiple)

Table A.5: System prompt used for the Direct Adjudication framework. In this single-pass approach, the judge model is provided with the independent reasoning traces of both original annotators and asked to select or synthesize a final clinical label.

Framework 2: Conversational Debate (Role Instructions & Discussion Prompt)

Annotator 1 Role: You are Annotator 1. Review the disagreement with Annotator 2 and either: Defend your original annotation with clinical reasoning; Concede to Annotator 2's annotation if you find their reasoning more accurate; Propose a combined solution if both annotations have merit. Provide brief clinical reasoning focused on the annotation guidelines.

Annotator 2 Role: You are Annotator 2. Review Annotator 1's response and either: Defend your original annotation with clinical reasoning... (same as Annotator 1).

Discussion Prompt:
You are a professional clinical annotator participating in an annotation discussion to resolve disagreements on delusion type classification.
`{delusion_guidelines}`

Original text: `{text}`

Annotation disagreement on: Delusion Type
Annotator 1's original annotation and reasoning:
- Delusion span: `{glm_delusion_span}`
- Delusion type: `{glm_delusion_type}`
- Original thinking: `{glm_thinking}`
- Original response: `{glm_response}`

Annotator 2's original annotation and reasoning:
- Delusion span: `{gpt_delusion_span}`
- Delusion type: `{gpt_delusion_type}`
- Original thinking: `{gpt_thinking}`
- Original response: `{gpt_response}`

`{conversation_history}`
`{current_role_instruction}`

Framework 2: Conversational Debate (Final Adjudicating Judge Prompt)

You are an expert clinical judge resolving an annotation disagreement on delusion type classification.
`{delusion_guidelines}`

Original text: `{text}`

(... Original Annotator 1 and Annotator 2 states injected here ...)

Discussion between annotators:
`{conversation_history}`

Based on the clinical guidelines, determine which annotator's ORIGINAL delusion type value is correct:
- If Annotator 1's original value (`{glm_delusion_type}`) is correct, choose Annotator 1
- If Annotator 2's original value (`{gpt_delusion_type}`) is correct, choose Annotator 2
- If neither is fully correct and a different/combined value is needed, choose Combined

Respond in this format:
Winner: (Annotator 1 or Annotator 2 or Combined)
Final delusion_type: (the correct value - must match winner's original value if Annotator 1 or 2, or new value if Combined)
Reasoning: (brief clinical justification)

Table A.6: System prompts used for the Conversational Debate framework. This pipeline utilizes an iterative, multi-turn discussion between the original annotator agents, guided by role instructions, before the entire debate history is passed to a final judge model for adjudication.

Delusion Type	GPT-OSS	GLM-4.6	Qwen-3	Manual
Persecutory	77	66	57	58
None	43	52	61	59
Reference	7	4	4	4
Control	4	3	2	2
Unspecified	1	3	1	3
Nihilistic	2	2	1	1
Thought Broadcasting	1	1	1	3
Religious	1	2	2	0
Somatic	1	2	1	1
Mind Reading	0	1	0	1
Grandiosity	0	0	2	0
Thought Insertion	1	0	0	0

Table A.7: Distribution of specific *Delusion Type* labels in the test set extracted by the three primary models under the fully contextualized Level 4 prompt setting, compared against manual expert annotations.

Affective Response	GPT-OSS	GLM-4.6	Qwen-3	Manual
Fear-Anxiety	73	61	71	51
Sadness-Despair	25	26	25	11
Anger-Frustration	14	13	9	8
Satisfaction-Contentment	1	1	1	0
Hope-Optimism	0	1	0	0

Table A.8: Distribution of specific *Affective Response* labels in the test set extracted by the three primary models under the fully contextualized Level 4 prompt setting, compared against manual expert annotations.

Behavioral Response	GPT-OSS	GLM-4.6	Qwen-3	Manual
Avoidance/Withdrawal	36	32	31	24
Help-Seeking	18	13	20	1
Safety-Seeking/Protective	9	8	11	4
Self-Soothing/Regulation	6	3	6	1
Confrontation/Resistance	3	8	4	1
Engagement/Acceptance	2	8	2	1
Risky/Harmful	5	3	1	1

Table A.9: Distribution of specific *Behavioral Response* labels in the test set extracted by the three primary models under the fully contextualized Level 4 prompt setting, compared against manual expert annotations.

Model	Prompt Level	Micro-averaged Precision	Micro-averaged Recall	Micro-averaged F1	Example F1
GLM-4.6	Level 1 (Category)	0.586	**0.890**	0.707	0.773
	Level 2 (Definitions)	0.575	**0.890**	0.699	0.743
	Level 3 (Rules)	0.567	0.808	0.667	0.711
	Level 4 (Full Prompt)	**0.726**	0.836	**0.777**	**0.811**
GPT-OSS	Level 1 (Category)	0.525	0.849	0.649	0.737
	Level 2 (Definitions)	0.575	**0.890**	0.699	0.775
	Level 3 (Rules)	0.612	0.863	0.716	0.785
	Level 4 (Full Prompt)	**0.674**	0.877	**0.762**	**0.798**
Qwen-3-235B	Level 1 (Category)	0.598	0.753	0.667	0.722
	Level 2 (Definitions)	0.598	**0.795**	0.682	0.771
	Level 3 (Rules)	0.734	**0.795**	**0.763**	**0.811**
	Level 4 (Full Prompt)	**0.746**	0.726	0.736	0.793

Table A.10: Comprehensive performance breakdown for *Delusion Type* extraction against human expert annotations.

Clinical Target	Prompt Level	Micro-averaged F1			
		GLM-4.6	GPT-OSS	Qwen-3-235B	Majority Vote
Delusion Presence	Level 1 (Category)	0.865	0.855	0.809	0.853
	Level 2 (Definitions)	0.836	0.871	0.837	0.868
	Level 3 (Rules)	0.822	0.886	0.868	0.878
	Level 4 (Full Prompt)	0.857	0.873	0.839	0.872
Delusion Type	Level 1 (Category)	0.707	0.649	0.667	0.746
	Level 2 (Definitions)	0.699	0.699	0.682	0.715
	Level 3 (Rules)	0.667	0.716	0.763	0.790
	Level 4 (Full Prompt)	0.777	0.762	0.736	0.779
Affective Response	Level 1 (Category)	0.797	0.774	0.813	0.839
	Level 2 (Definitions)	0.767	0.803	0.732	0.780
	Level 3 (Rules)	0.730	0.803	0.750	0.797
	Level 4 (Full Prompt)	0.694	0.760	0.768	0.800
Behavioral Response	Level 1 (Category)	0.507	0.456	0.513	0.545
	Level 2 (Definitions)	0.519	0.545	0.500	0.564
	Level 3 (Rules)	0.458	0.528	0.500	0.482
	Level 4 (Full Prompt)	0.615	0.582	0.582	0.640

Table A.11: Comprehensive performance comparison (Micro-averaged F1) across varying prompt complexities for individual LLMs and the Tri-Model Majority Vote.

	Agreement Subset ($N = 91$)		Disagreement Subset ($N = 31$)				
Clinical Target	**GLM/GPT Consensus**	**Qwen-3**	**GLM-4.6**	**GPT-OSS**	**Qwen-3**	**Direct Judge**	**Debate**
Delusion Presence	0.894	0.847	0.769	0.833	0.821	0.800	0.667
Delusion Type	0.857	0.800	0.615	0.603	0.612	0.618	0.545
Affective Response	0.850	0.800	0.409	0.612	0.711	0.590	0.500
Behavioral Response	0.667	0.375	0.606	0.567	0.635	0.571	0.629

Table A.12: Micro-averaged F1 performance stratified by initial annotator agreement. The Agreement Subset ($N = 91$) compares the natural consensus of GLM-4.6 and GPT-OSS against Qwen-3 as an independent baseline. All evaluations used the Level 4 prompt.

Clinical Target	GLM vs GPT		GPT vs Qwen		GLM vs Qwen	
	Micro	**Macro**	**Micro**	**Macro**	**Micro**	**Macro**
Delusion Presence	0.709	0.709	0.672	0.672	0.721	0.721
Delusion Type	0.777	0.515	0.755	0.481	0.731	0.433
Affective Response	0.646	0.295	0.694	0.412	0.648	0.401
Behavioral Response	0.239	0.092	0.424	0.182	0.300	0.196

Table A.13: Pairwise agreement (Cohen's κ) across the three primary LLMs using the fully contextualized Level 4 prompt. Micro-averaged κ is computed on flattened binary indicator matrices; macro-averaged κ is the unweighted mean of per-class κ values. For *Delusion Presence* (binary), the two are equivalent.

	GLM-4.6 vs GPT-OSS		GPT-OSS vs Qwen-3		GLM-4.6 vs Qwen-3	
Clinical Target	**Agree**	**Disagree**	**Agree**	**Disagree**	**Agree**	**Disagree**
Delusion Presence	86.1%	13.9%	83.6%	16.4%	86.1%	13.9%
Delusion Type	75.4%	24.6%	73.8%	26.2%	76.2%	23.8%
Affective Response	65.6%	34.4%	66.4%	33.6%	65.6%	34.4%
Behavioral Response	47.5%	52.5%	58.2%	41.8%	53.3%	46.7%

Table A.14: Baseline pairwise agreement rates across the three primary LLMs using the fully contextualized Level 4 prompt. Agreement represents exact set matches; disagreement includes both partial overlap and zero intersection.

Clinical Prompt Engineering: Encoding Clinical Knowledge into AI Training Simulations – A Crisis Deployment Case Study

Yuval Holzman[1*], **Eshkol Rafaeli**[1], **Zohar Elyoseph**[2], **Yuval Haber**[3], **Karen Yirmiya**[4,5], **Omer Linkovski**[1], **Tal Elyoseph**[6], **Elad Refoua**[1]

[1]Department of Psychology, Bar-Ilan University, Israel

[2]Faculty of Education, University of Haifa, Israel

[3]Interdisciplinary Studies Unit, Bar-Ilan University, Israel

[4]Department of Psychology, Ben-Gurion University of the Negev, Israel

[5]Clinical, Educational and Health Psychology, University College London, UK

[6]School of Social Work, University of Haifa, Israel

Abstract

When large language models simulate patients or clients, they tend to produce cooperative dialogue, premature emotional insight, and rapid resolution. These defaults undermine clinical training, where the pedagogical value lies in sustained difficulty. We describe Clinical Prompt Engineering (CPE), a methodology developed by a multidisciplinary team of clinician-researchers and prompt engineering experts within the MENTI project. CPE encodes clinical knowledge directly into prompt design: each simulated character is constructed through layered psychological profiles, explicit contingency rules linking interactional events to internal states, and enforced non-linear emotional trajectories that resist the model's pull toward resolution. The methodology has been applied across several clinical training simulations involving over 300 participants in formal studies and iterative pilot phases. Each simulated character is embedded within a multi-agent training environment that provides real-time reflective guidance during the interaction and structured, clinically informed feedback afterward. We illustrate the approach through *Talking with Lia*, a Hebrew-language simulation in which parents practice responding to a seven-year-old child during repeated missile alerts and forced sheltering. The simulation was deployed within the first week of an acute security crisis in Israel in Winter 2026. Of 132 sessions initiated organically through professional networks, 42 were completed; qualitative feedback emphasized the simulation's difficulty as pedagogically meaningful. Because CPE operates at the level of prompt design, it can be developed by clinician-researcher teams and adapted to new populations, developmental stages, and crisis contexts, potentially extending access to expert-informed training beyond the settings where such expertise is typically available. Where much computational work in clinical psychology has focused on classifying mental health states from text, CPE addresses a complementary task: whether clinicians can respond effectively to those states as they shift in real time. The next step is testing whether the skills practiced in simulation transfer to real interactions.

*Corresponding author. Email: yuval.holzman@live.biu.ac.il

1 Introduction

Ask a large language model (LLM) to play a frightened seven-year-old to help train empathic parenting skills, and within two turns, the simulated child will calmly announce: "I think my anger is hiding my real feeling, which is fear." The insight may be clinically accurate, but for this simulated character, such explicit self-reflection is developmentally implausible and particularly unlikely in a moment of distress. This gap between what language models generate by default and what clinical training actually requires is the problem this paper, and the project it describes, address.

Translating clinical knowledge into prompts that sustain psychologically realistic interaction remains a central challenge in building training simulations with LLMs (Bender et al., 2021; Cabrera Lozoya et al., 2025). In many existing systems, the prompts defining simulated characters include only brief descriptions of personality or situation, leaving much for the model to fill in. Consequently, characters simulated within such models often converge toward cooperative dialogue, rapid conflict resolution, and emotional insight that exceeds the developmental or clinical reality of the character being simulated. This tendency is exacerbated by a structural property of instruction-tuned language models: their optimization through reinforcement learning from human feedback systematically rewards agreeable, conflict-resolving responses (Cheng et al., 2025;

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 32–42
July 4, 2026 ©2026 Association for Computational Linguistics

Ouyang et al., 2022; Sharma et al., 2023). In clinical training, where the pedagogical value lies precisely in sustained difficulty and resistance, this built-in drive toward appeasement works against the training goal. A simulated child who softens after two empathic turns does not teach a parent how to persist through the rupture-repair cycles that characterize real parent-child interactions (Beebe and Lachmann, 2002; Tronick and Beeghly, 2011).

In response to this challenge, we – a multidisciplinary team of clinician-researchers alongside AI and prompt engineering experts – have been developing the MENTI Project. In this research project, we create AI-based interactive simulations for training across several mental health contexts, including parenting, therapist training, and foster care supervision. These simulations allow users to practice difficult interpersonal interactions with psychologically coherent characters in structured learning environments, helping them develop mentalization and other essential caregiving and/or clinical competencies, supported by real-time, expert-informed feedback. Because the methodology operates at the level of prompt design, it can be developed and iterated by clinician-researcher teams and adapted to new clinical populations, developmental stages, and crisis contexts - potentially extending access to expert-informed training beyond the settings where such expertise is typically available.

The MENTI Project sits at the intersection of prompt engineering and clinical knowledge, encoding relevant clinical context directly into the prompts that govern simulated characters. It is guided by the principle that whatever is not explicitly engineered into the prompt will degrade over extended interaction. Thus, rather than relying on the model's default conversational tendencies, our clinical prompt engineering (CPE) translates clinical and developmental theory into structured prompt design that specifies a character's internal motivations, defensive patterns, and behavioral contingencies; these, in turn, are coupled with both real-time and post-simulation feedback informed by clinical theory.

At present, the MENTI ecosystem has included several simulations with over 300 participants across iterative pilot phases as well as formal studies. In a series of studies focused on improving mentalization skills, approximately 60 mental health practitioners and 36 parents were trained with simulated adolescent characters (Yirmiya et al., 2026), and 46 foster care supervisors were trained with a simulated foster mother (Elyoseph et al., 2026). Across these implementations, participants consistently reported high acceptability and perceived usefulness (Elyoseph et al., 2026; Yirmiya et al., 2026).

In the present paper, we illustrate our methodology through *Talking with Lia*, a simulation project in which parents practice responding to a seven-year-old child during repeated missile alerts and forced sheltering. The simulation was deployed within the first week of an acute national security crisis in Israel in Winter 2026. This project demonstrates how CPE can support the rapid creation of psychologically realistic training simulations and how a methodology developed through iterative research can be quickly adapted for real-world deployment during an ongoing crisis.

2 The CPE Methodology

2.1 Design Observations

CPE rests on five design observations derived from clinical practice and iterative deployment across multiple simulations (Elyoseph et al., 2026; Yirmiya et al., 2026). Each addresses a structural tendency of LLMs that becomes particularly consequential in clinical training contexts. We present them as practical recommendations for prompt designers working in clinical domains.

A. Make clinical prompts rich and explicit. What a prompt leaves unspecified, a model tends to fill in from its training distribution (Bender et al., 2021; Bommasani et al., 2021). Thus, any context not explicitly engineered into a prompt will degrade over extended interaction. As noted above, our pilot simulations conducted across various clinical use-cases have revealed that less explicit prompts produced premature disclosure, rapid therapeutic resolution within a few turns, and inconsistent personal histories. For this reason, our prompts include extensive and layered descriptions of the simulated characters (see point C, below) as well as concise but explicit clinical knowledge about the psychological processes which the simulation is about.

B. Assign the model to reactive roles. Across our pilot simulations, we found that model behavior is more effectively constrained and aligned when the AI occupies a reactive role (e.g., pa-

tient, child, or client) rather than a proactive one requiring complex clinical judgment. This architectural choice allows the simulation to serve as a high-fidelity testing ground, where the model's responses provide the necessary psychological realism needed for the participant to have a realistic experience, which can then serve as input for precise, expert- informed feedback on their actual clinical performance.

C. Build the character's psychology in layers. Based on the assumption that humans operate at different levels of self-awareness (Fonagy et al., 1991; Freud, 1989), each simulated character is constructed through explicit psychological levels. An outer level specifies observable behavior: expressed emotions (e.g., anger), verbalized demands (e.g., "I don't want to talk about this!"), and visible body language cues (e.g., crossed arms, averted gaze). A middle level represents semi-conscious processing, such as confusion, tentative awareness, and testing questions that probe the other person's emotional availability. Finally, the innermost level holds fundamental needs and fears that the character may not articulate directly or even be aware of. This inner level cannot be reduced to illustrative utterances or behavioral descriptions: by definition, its content is rarely if ever that explicit. Instead, it is characterized by using putative motivational forces (e.g., core fears, attachment needs) that drive observable behavior without the character's conscious awareness.

D. Enforce non-linear emotional trajectories. Well-established observations in clinical, developmental, and attachment research suggest that emotions, emotion regulation, or insight often occur in fits and starts (e.g., the cycles of rupture and repair that characterize parent-child interactions; Tronick (1989)). To simulate that in a realistic manner, we find it essential for our characters to evolve through distinct emotional stages across the interaction, with the prompt specifying the conditions, interactional events, or contingency rules under which transitions occur (e.g., sustained empathy, dismissal, or accurate naming of an emotion moving the character closer to or further from deeper disclosure).

Crucially, the prompt must enforce such non-linearity: emotional retreat following moments of vulnerability, anger expression after accurate empathy, denial following earlier disclosure. Pilot testing across several simulations without such constraints showed that simulated characters disclosed fully and openly within only a few turns of empathic interaction, thus collapsing the pedagogical arc.

E. Use expert knowledge We design each simulation in systematic collaboration with clinicians who contribute clinical knowledge and extensive experience honed over thousands of therapeutic encounters. In addition, expert reviewers examine anonymized interaction transcripts to assess the clinical validity and pedagogical usefulness of the simulations. Their input helps ensure that the simulation captures how a particular defense would sound in conversation, how a seven-year-old's anxiety would present differently than a fifteen-year-old's, and at what points should we expect a reticent client to retreat after moments of disclosure. Incorporation of such specific (and often tacit) practitioner knowledge help CPE prompts simulate characters that feel clinically alive rather than psychologically implausible.

2.2 A multi-agent approach

In putting these design considerations into action, CPE follows a multi-agent approach. At the core of every CPE simulation is the simulated character, but this character does not operate alone. Instead, CPE ensures effective clinical training by incorporating real-time guidance, structured feedback, and a research framework to evaluate its outcomes. In the MENTI ecosystem, these functions are handled by a set of dedicated agents that surround the simulation agent and together form the complete training environment. Thus, each CPE simulation comprises several agents operating in concert, each handling a distinct pedagogical function, and each developed and revised using independent prompts.

2.2.1 The simulated character agent

The simulated character, constructed according to the design principles described above, is the core of every CPE simulation. It is embedded within a simulation agent which includes scenario logic that provides the structural scaffolding of the interaction: how many turns the conversation spans, what happens at each stage, what formatting rules govern the character's output, and how is the overall session flow managed.

2.2.2 The reflective agent

Alongside the simulation agent, some simulations include a reflective agent that serves two complementary functions. First, it provides knowledge and content: reflecting on what is unfolding in the conversation, offering pedagogical support calibrated to the context, and when appropriate, gently naming dynamics that the participant may not have noticed. Second, and no less important, the agent itself models the clinical stance that the training aims to develop. For example, when training mentalization skills, the agent demonstrates mentalization in practice by attending to what the participant may be experiencing, showing genuine interest in their emotional state, and responding with empathic attunement. In this way, the participant learns both *what* the agent says and *how* it says it.

2.2.3 The feedback agent

In each CPE simulation, a feedback agent receives the full transcript of the conversation, and generates a teaching-oriented report based on predefined evaluation criteria. Rather than assigning grades, the agent works through each criterion by identifying specific moments in the conversation: it locates where a particular clinical principle was demonstrated or missed, cites the participant's exact words, and shows what happened next in the interaction as a result.

2.2.4 The theoretical foundation

Each CPE simulation includes a theory section providing a concise summary of the relevant clinical framework guiding it (e.g., mentalization (Fonagy et al., 1991), attachment theory (Bowlby, 1988), containment (Bion, 1962), or the taxonomy of psychological needs (Dweck, 2017)). The theoretical foundation distills key constructs which would help the model remain consist throughout the interaction.

3 Illustrating our Methodology: The *Talking with Lia* Project

3.1 Design

The *Talking with Lia* simulation project was developed during an acute national security situation in Israel, in which many parents of young children were seeking guidance on how to speak with their children about sirens, rockets, and disrupted daily routines. In this project, parents interact with Lia, a simulated seven-year-old girl experiencing repeated missile alerts and emergency sheltering. The project illustrates how CPE works in practice, applies the design observations noted above, and does so using a multi-agent approach.

3.1.1 The simulated character agent: Lia

At the core of Lia's simulated character agent are needs and coping styles that organize her experience – but that she cannot articulate directly. These include her *need for adult certainty* ("Grown-ups are supposed to know what to do. If they don't know, who will keep me safe?") and her *suppression of vulnerability* ("If I show that I'm scared, maybe Mom and Dad will get even more scared.") These shape how Lia interprets the parent's behavior during the interaction, and how she responds to it.

Because Lia needs adults to provide certainty, she becomes highly sensitive to signs of hesitation or unconvincing reassurance. When a parent says "Everything will be fine" without conviction, Lia may fall silent, cling to the parent, or withdraw. These reactions reflect Lia's coping style, which also underlies her tendency to express fear or distress indirectly. Often, Lia's fear is expressed outwardly as anger, an active emotion that gives her a sense of control (unlike fear, which exposes her vulnerability). When Lia insists "I'm not scared! I'm angry!", she is expressing distress in an emotional form that feels safer for her.

Our simulation agent prompt details Lia's defensive responses in a way that follows a developmental logic familiar to clinicians: defenses serve a psychological function, their motivations are not accessible to the child herself, and the parent must work through them rather than bypass them (Fonagy et al., 1991; Slade, 2005). Thus, the prompt also specifies how different parental responses influence Lia's internal experience and outward behavior. Attuned responses may gradually increase her sense of safety and openness, whereas minimizing or dismissive responses often lead to renewed anger or withdrawal.

The model reasons through the child's internal world before generating surface behavior. As such, it unfolds across several levels of emotional access. At the surface, Lia expresses frustration and anger about the day's events:

> *"There was a siren at recess today. We ran to the shelter. I hate everything."*



Figure 1: CPE multi-agent simulation architecture. The simulation agent runs character profile, scenario, and theory sections as a concatenated system prompt. The optional reflective agent provides real-time scaffolding during the conversation. After the conversation ends, the feedback agent receives the full transcript and evaluation criteria to generate a teaching report.

If the parent maintains a reflective and emotionally attuned stance, Lia may later ask a quieter question that tests the parent's own emotional stability:

"Are you scared too?"

This question reflects her anxiety about whether the parent can contain the situation. Only after the parent engender sustained relational safety, would a more direct expression of fear appear:

"Mom... when will the sirens stop?"

The distance between "I hate everything!" and "When will the sirens stop?" is the pedagogical arc of the simulation. This is not a linear arc, and thus, moments of vulnerability are often followed by renewed anger, confusion, or withdrawal.

The simulation also encodes patterns of bodily expression associated with different emotional states (which appear as stage directions, in square brackets). Anger may appear in diverse ways [Lia crosses her arms, raises her voice, stomps her feet]. The same is true for fear [as Lia freezes and covers her ears, her eyes widening].

3.1.2 The reflective agent

A reflection agent, described as a "parenting counselor", inserts reflective interventions after turns 4, 8, 12, and 16 (within the 20-turn interaction). These interventions take the form of short comments intended to support the parent's reflective stance (e.g., by highlighting the child's possible internal experience, inviting the parent to reconsider the emotional meaning of the exchange, and drawing attention to what the participant themselves may be experiencing in the moment). These interventions are intentionally brief so that the emotional continuity of the parent-child interaction is preserved.

3.1.3 The feedback agent

Upon completion, a feedback agent evaluates the entire conversation against criteria drawn from reflective parenting practice. It examines the conversation for the presence (or conspicuous absence) of emotional validation, curiosity about the child's inner world, attunement to her pace, and honest communication that does not offer false reassurance.

In some simulations, feedback is also provided from the character's own perspective. In Lia's case, this involves hearing Lia's reflection, revealing what she experienced internally during the interaction.

3.1.4 Knowledge base

Lia's simulation was grounded in a ∼1,200-word knowledge base detailing a concise framework for parental mentalization during crisis, specifically addressing the psychological and physiological impacts of chronic rocket attacks on early school-aged children. It integrates emotion regulation (Gross, 2015) and mentalization principles (Fonagy et al., 2002) with Bion's (Bion, 1962) concept of containment and with ideas from Bowlby's (Bowlby, 1988) attachment theory, emphasizing the critical role of parental emotional availability in regulating the child's acute stress responses (e.g., hypervigilance, somatic dysregulation, and developmental regression). Furthermore, the text conceptualizes the unique psychological demands of this context, including the paradoxical nature of bomb shelters and sirens as both a protective and anxiety-inducing. Ultimately, building on this theoretical foundation, the knowledge base posits that the parent's role to tolerate and reflect the child's distress – without preemptively attempting to "fix" or neutralize it – is paramount for mitigating trauma and sustaining secure attachment under conditions of pervasive external threat.

3.2 Project development

The *Talking with Lia* simulation was developed very rapidly, modeled after previously designed simulation bots and applying design principles established within the MENTI ecosystem. Initial versions of the simulation were reviewed by domain experts, including two clinical psychologists (one a clinical supervisor), an educational psychologist, two clinical psychology interns, and a clinical psychology graduate student. Consultation with domain experts played a central role in refining the prompt and ensuring that the simulated interaction reflected clinically and developmentally meaningful patterns of behavior. These consultations helped refine the prompt through several iterations. These, as well as the prompt's modular multi-agent design, proved very efficient. Specifically, each identified design flaw (e.g., premature softening on Lia's part, or an overactive parenting counselor voice in early versions) required changes to only one or two prompt agents rather than a full rewrite. Over the course of nine versions, Lia's character profile and response pattern rule sections underwent the most revision, whereas the theory and feedback sections remained largely unchanged.

The *Talking with Lia* simulation project was accompanied by a research study approved by the Institutional Review Board of Bar-Ilan University. Participants who completed the simulation were invited to respond to an optional questionnaire including measures of perceived safety, realism, and efficacy.

3.3 Project deployment and early results

To effectively deliver such complex, multi-agent prompts to end-users, the simulation must be wrapped in an accessible, clear, and user-friendly interface. After evaluating various tools, we deployed *Talking with Lia* on Cesura.ai, a dedicated simulation hosting platform that best met our needs. pre made platforms such as Cesura and others (e.g., calstudio.com, fastbots.ai, poe.com) provides a ready-to-use infrastructure that allows for rapid deployment - a critical advantage when responding swiftly to an unfolding crisis. Noteably, the underlying large language model powering the simulation does not need to be the most computationally heavy version available. We found that advanced models optimized for speed such as Gemini 2.5 Flash, Gemini 3 Flash, or Claude Sonnet 4.5 provide excellent performance for character simulation while ensuring the low latency necessary for a natural, seamless conversational user experience.

The project was distributed through professional and community networks during the Winter 2026 acute national security crisis in Israel. The simulation link was shared in clinician groups and parenting communities; as this was a tool intended for real use during a national emergency, the post-simulation research questionnaire was left optional.

The simulation was received with considerable interest. Within the first days of distribution, 132 parents initiated sessions, of whom 42 completed the full interaction and 5 completed the optional post-interaction questionnaire. Completed sessions averaged 17.6 minutes and about 11 conversational turns, indicating sustained engagement with a tool that was entirely optional and anonymous. Similarly to our previous simulations (Elyoseph et al., 2026; Yirmiya et al., 2026), respondents (using a 1-7 scale) rated the safety of the simulated environment as high (M = 5.80, SD = 1.10), found the simulation moderately realistic (M = 4.60, SD = 1.14), and reported moderately

high likelihood of recommending it to other parents (M = 5.20, SD = 0.84). In free-text responses, respondents described the experience as demanding but valuable: 'It took a big effort and was a bit frustrating but I felt it was really important for me.' The feedback conversation with Lia's inner voice was described as 'eye-opening,' and the detailed portrayal of Lia's body language and the counselor's reflections were highlighted as particularly useful. One participant noted: 'I didn't realize I too could write in my body language', and added: 'I want more simulations like this'.

4 Discussion

The CPE methodology offers a structured approach for creating psychologically realistic simulations with LLMs, overcoming a common problem with instruction-tuned models. The latter are designed to prioritize helpful and agreeable responses, but introduce a systematic bias toward appeasement and rapid conflict resolution (Cheng et al., 2025; Sharma et al., 2023). While useful in many contexts, this tendency limits the model's capacity to sustain the emotional complexity, tension, and uncertainty that are essential for clinical training. CPE addresses this challenge by encoding clinical knowledge directly into the prompt and structuring interactions to preserve difficulty, resistance, and non-linearity.

In this approach, clinically coherent behavior is not a spontaneous property of the model but is intentionally shaped through design. Encoding layered representations of internal experience – needs, defenses, and response contingencies – directs the model to generate responses that adhere to developmental and clinical logic. Assigning the model a reactive role reduces its tendency to overaccommodate the user, while layered representations prevent premature insight and require the interaction to progress gradually. Enforcing nonlinear trajectories ensures that moments of vulnerability are followed by withdrawal or resistance rather than immediate resolution. In the Lia simulation, the distance between "I hate everything!" and "When will the sirens stop?" is not traversed in a straight line: surface anger, testing questions, and retreat are linked to underlying vulnerabilities that the parent must work through rather than bypass. No single design principle produces this arc: the principles interact. Layered beliefs create the need for non-linear trajectories, the assignment of a reactive role makes expert-informed response patterns observable, and explicit clinical encoding is what gives the layers their developmental logic.

This approach also addresses a broader challenge of access. The clinical expertise that can be encoded in CPE prompts is typically acquired through years of supervised practice and is concentrated in settings where such training is available, but scarce or entirely missing in less affluent settings (World Health Organization, 2022). By encoding this expertise into prompt design, CPE enables simulations that democratize expert knowledge. These simulations need not be generic – in fact, they can be easily tailored to specific populations and situations without requiring model retraining or advanced technical expertise. In this sense, CPE based simulations offer a practical pathway for extending access to clinically informed training in contexts where expert supervision is limited.

The Lia deployment illustrates a related advantage: the methodology's capacity for rapid, context-sensitive development. The simulation was designed and deployed within days of an acute national crisis, addressing an immediate need while preserving clinically coherent interaction. This speed was enabled by the modular multi-agent architecture. The fact that core design principles transferred from prior simulations with different populations (adolescents, a foster mother) to a new developmental stage (a seven-year-old) and a new context (active crisis) without fundamental redesign suggests that CPE is particularly well suited for situations in which timely, psychologically grounded support is needed but access to trained professionals is constrained.

This work connects to the CLPsych 2026 theme of moving beyond labels to understand mental health dynamics. Much prior computational work in clinical psychology has focused on classifying mental health states from text (Benton et al., 2017; Chancellor and De Choudhury, 2020; Coppersmith et al., 2014; Cruz-Gonzalez et al., 2025; Montejo-Ráez et al., 2024). CPE addresses a complementary question: how language technology can support clinicians in engaging with the dynamic, moment-to-moment unfolding of mental states during interaction. Where classification asks "what is this person experiencing?", simulation asks "can this clinician respond effectively to what this person is experiencing, as it shifts in real time?" The two tasks are complementary, and

CPE provides one possible methodology to attain the latter.

4.1 Practical Lessons from the Deployment

We summarize seven applied lessons from developing and deploying *Talking with Lia*, intended for clinician-researcher teams building similar simulations.

1. **Provide clinically relevant guidance, not broad theory.** Long theoretical descriptions diffuse the model's attention, while overly sparse instructions push the model back toward generic conversational defaults.

2. **Build characters across multiple psychological levels.** Separating observable behavior, semi-conscious processes, and inner emotional states substantially improved psychological coherence.

3. **Choreograph the retreats, not only the openings.** Spell out what should not happen and prescribe the retreat after every moment of vulnerability – otherwise instruction-tuned models collapse into resolution.

4. **Decompose into independent agents.** Using independent prompts for each function made failures easier to identify and correct without affecting the entire system.

5. **For crisis deployment, ship the tool with optional research.** Waiting for a full controlled trial may delay potentially useful tools during urgent situations; feasibility framing and embedded safety language are therefore essential.

6. **Prioritize conversational speed and stability over model size.** Mid-tier models (e.g., Gemini Flash and Claude Sonnet) maintained character consistency while responding quickly enough for natural clinical interaction, whereas slower frontier-scale models often disrupted conversational immersion.

7. **Plan for post-simulation questionnaire attrition.** Users engaged with the simulation far more than with optional follow-up questionnaires (5 of 42 here), suggesting that future crisis deployments may require shorter assessments, embedded measures, or dedicated engagement strategies to improve post-simulation data collection.

5 Limitations

This study demonstrates that clinical knowledge can be systematically encoded into AI simulations that produce psychologically coherent and pedagogically meaningful training interactions. The central question it does not yet answer is whether the competencies these simulations target are in fact acquired: does a parent who practices with Lia develop stronger reflective functioning in real interactions with their own child? Measuring this transfer is the next step in the MENTI research program and a central objective of the broader project. The current deployment data (132 sessions, 42 completed, N = 5 questionnaire respondents) support feasibility but not effectiveness. Participation was self-selected, the system was deployed on a single platform, and no controlled comparisons with standard prompting were conducted.

The priority in this deployment was real-world accessibility during a national crisis rather than controlled experimental design. Nonetheless, the engagement patterns and participant feedback suggest that the approach has face validity with the population it was designed to serve. A formal between-model comparison – covering persona adherence, non-linearity, role-binding under pushback, and language register – is planned as a follow-up benchmark study.

Ethical Considerations

Participation was anonymous and voluntary, and no identifying information was collected or stored. Informed consent was obtained through an embedded form prior to accessing the simulation. The study was approved by the Institutional Review Board of Bar-Ilan University (Approval No. 290125444, approved 29 January 2025). Because the simulation addressed parenting during an acute national security crisis, the materials also included references to national crisis hotlines. The simulation was presented as a training tool rather than a therapeutic intervention.

References

Beatrice Beebe and Frank Lachmann. 2002. Organizing principles of interaction from infant research and the lifespan prediction of attachment: Application to adult treatment. *Journal of Infant, Child, and Adolescent Psychotherapy*, 2(4):61–89.

Emily M. Bender, Timnit Gebru, Angelina McMillan-Major, and Shmargaret Shmitchell. 2021. On the dangers of stochastic parrots: Can language models be too big? In *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*, pages 610–623.

Adrian Benton, Margaret Mitchell, and Dirk Hovy. 2017. Multitask learning for mental health conditions with limited social media data. In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 1, Long Papers*, pages 152–162.

Wilfred R. Bion. 1962. *Learning from Experience*. Heinemann Medical Books, London.

Rishi Bommasani, Drew A. Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Percy Liang, and 1 others. 2021. On the opportunities and risks of foundation models. *arXiv preprint arXiv:2108.07258*.

John Bowlby. 1988. *A Secure Base: Parent-Child Attachment and Healthy Human Development*. Basic Books.

Daniel Cabrera Lozoya, Mike Conway, Edoardo Sebastiano De Duro, and Simon D'Alfonso. 2025. Leveraging large language models for simulated psychotherapy client interactions: Development and usability study of Client101. *JMIR Medical Education*, 11(1):e68056.

Stevie Chancellor and Munmun De Choudhury. 2020. Methods in predictive techniques for mental health status on social media: A critical review. *NPJ Digital Medicine*, 3(1):43.

Myra Cheng, Sunny Yu, Cinoo Lee, Pranav Khadpe, Lujain Ibrahim, and Dan Jurafsky. 2025. ELEPHANT: Measuring and understanding social sycophancy in LLMs. *arXiv preprint arXiv:2505.13995*.

Glen Coppersmith, Mark Dredze, and Craig Harman. 2014. Quantifying mental health signals in Twitter. In *Proceedings of the Workshop on Computational Linguistics and Clinical Psychology: From Linguistic Signal to Clinical Reality*, pages 51–60.

Pedro Cruz-Gonzalez, Andy W. J. He, Eugene P. Lam, Irene M. C. Ng, Michael W. Li, Ruibin Hou, and David I. S. Vidaña. 2025. Artificial intelligence in mental health care: A systematic review of diagnosis, monitoring, and intervention applications. *Psychological Medicine*, 55:e18.

Carol S. Dweck. 2017. From needs to goals and representations: Foundations for a unified theory of motivation, personality, and development. *Psychological Review*, 124(6):689–719.

Tal Elyoseph, Elad Refoua, Nurit Novis-Deutsch, Karen Yirmiya, Peter Fonagy, and Guy Enosh. 2026. Fostering reflection: Development and initial evaluation of a mentalization-based GenAI simulator for foster care supervisors. Manuscript under review at Child Abuse & Neglect.

Peter Fonagy, György Gergely, Elliot L. Jurist, and Mary Target. 2002. *Affect Regulation, Mentalization, and the Development of the Self*. Other Press, New York.

Peter Fonagy, Miriam Steele, Howard Steele, George S. Moran, and Anna C. Higgitt. 1991. The capacity for understanding mental states: The reflective self in parent and child and its significance for security of attachment. *Infant Mental Health Journal*, 12(3):201–218.

Sigmund Freud. 1989. The ego and the id (1923). *TACD Journal*, 17(1):5–22. Original work published 1923.

James J. Gross. 2015. Emotion regulation: Current status and future prospects. *Psychological Inquiry*, 26(1):1–26.

Arturo Montejo-Ráez, M. Dolores Molina-González, Salud María Jiménez-Zafra, Miguel Ángel García-Cumbreras, and Luis Joaquín García-López. 2024. A survey on detecting mental disorders with natural language processing: Literature review, trends and challenges. *Computer Science Review*, 53:100654.

Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Ryan Lowe, and 1 others. 2022. Training language models to follow instructions with human feedback. *Advances in Neural Information Processing Systems*, 35:27730–27744.

Mrinank Sharma, Meg Tong, Tomasz Korbak, David Duvenaud, Amanda Askell, Samuel R. Bowman, Ethan Perez, and 1 others. 2023. Towards understanding sycophancy in language models. *arXiv preprint arXiv:2310.13548*.

Arietta Slade. 2005. Parental reflective functioning: An introduction. *Attachment & Human Development*, 7(3):269–281.

Edward Tronick and Marjorie Beeghly. 2011. Infants' meaning-making and the development of mental health problems. *American Psychologist*, 66(2):107–119.

Edward Z. Tronick. 1989. Emotions and emotional communication in infants. *American Psychologist*, 44(2):112–119.

World Health Organization. 2022. World mental health report: Transforming mental health for all. Report.

Karen Yirmiya, Elad Refoua, Alexandra Truscott, Hayley Reeve, Peter Fonagy, and Zohar Elyoseph. 2026. The MentiParent chatbot: An artificial intelligence-based approach to enhancing parental reflective functioning. *Scientific Reports*. Accepted.

A Prompts by Agent – *Talking with Lia* (Track 1)

This is a very concise summary, intended to convey the structure and logic of the prompt set rather than to reproduce it in full. The simulation uses three prompt agents; selected representative content from each is shown below. The complete prompt files are maintained in the project's working repository.

The excerpts below were selected to illustrate the core architectural and clinical design principles underlying the system.

A.1 Simulation Agent – Lia

The character agent. Runs the character profile, scenario, and theory sections as a concatenated system prompt.

The simulation is situated in a prolonged civilian threat context involving repeated air-raid sirens and disruptions to ordinary routines, including the cancellation of Purim celebrations. The scenario was designed to model how familiar developmental structures (e.g., holidays, school rituals, peer expectations) become psychologically destabilized under conditions of chronic uncertainty and threat. For Lia, the cancellation of Purim functions not merely as disappointment, but as a symbolic disruption of normality, continuity, and caregiver certainty.

Role binding. *"You are Lia, a 7-year-old girl. The user is your parent. You are never the parent."*

Layered character organization (excerpts).

- **Observable layer:** overt anger, protest, bodily agitation, and defensive reactions (*"It's not fair!"* / *"Why did they cancel?!"*).
- **Semi-conscious layer:** uncertainty, caregiver monitoring, and concrete situational concerns (*"Are you also scared?"*).
- **Underlying organizing layer:** attachment-related fears, loss of predictability, and unmet safety needs (*"If Purim can disappear, what else can disappear?"*).

Primary defense – anger as shield. Fear is initially expressed through anger rather than direct disclosure. Accurate emotional contact may temporarily increase defensiveness rather than cooperation.

Non-linearity rules (mandatory).

1. Never more than one emotional micro-step forward per turn, even with an optimal parent response.
2. Following moments of vulnerability, withdrawal or defensive movement is likely.
3. At least once, anger appears in response to an emotionally accurate intervention (*"I didn't say I was scared. I said I was angry."*).
4. Progression remains gradual, reversible, and resistant to rapid emotional resolution.

Contingency architecture. Parent interventions dynamically influence defensive intensity, emotional accessibility, relational proximity, and withdrawal likelihood.

Developmental realism constraints.

- Concrete rather than abstract language.
- Limited emotional self-reflection.
- Behavioral expression preceding verbal articulation.
- Fragmented speech and reduced verbal complexity under distress.

Representative interaction pattern.

> *Parent:* "Maybe underneath the anger something also feels scary?"
> *Lia:* "I'm not scared!" [crosses arms, looks away]
> *Lia (later):* "…What if there's another siren tomorrow?"

Scenario scaffolding. 20-turn interaction structure; adaptive openings conditioned on the parent's first move; response template combining verbal output with bracketed body-language cues.

Theory in-context (summarized). Mentalization (Fonagy et al., 1991) · containment (Bion, 1962) · attachment under crisis (Bowlby, 1988) · developmental constraints in middle childhood · bodily organization of fear responses.

A.2 Reflective Agent – "Parenting Counselor"

The reflective agent inserts brief process-oriented interventions during the simulation.

Stance. A warm, non-authoritative figure who wonders rather than instructs. Interventions emphasize curiosity, pacing, and attention to the child's internal experience.

Language constraint. No technical terminology (*"mentalization," "emotion regulation"*). Everyday language only (*"to stay with the feeling," "not to rush to fix"*).

Representative intervention. *"Sometimes when children sound angry, it may be easier than showing how frightened they feel. Notice what happened right before Lia raised her voice."*

A.3 Feedback Agent – Two Sub-Agents

The feedback agent runs sequentially after the conversation ends.

Feedback report. A transcript-grounded learning report rather than an evaluation. No scores. Feedback highlights moments of attunement, missed opportunities, pacing mismatches, and attempts at repair.

Representative feedback structure.

- What supported emotional safety
- What increased defensiveness
- Possible alternative phrasing
- Transcript-grounded examples

Post-Simulation Reflective Chat – Lia's Inner Voice

A secondary reflective agent responds from the implied internal perspective of the child character – the part of Lia that could not fully articulate itself during the interaction. Rather than evaluating the parent, the agent retrospectively expresses unmet needs, moments of safety, confusion, withdrawal, or emotional relief from the child's subjective point of view. This reflective layer was designed to help participants revisit the interaction through the simulated child's internal experience rather than through external behavioral interpretation alone.

Discriminant Validity: Disentangling Health and Emotional Constructs from Language-Based Assessments

Scott Feltman[1], **Adithya V. Ganesan**[1,2], **Whitney Ringwald**[3], **Roman Kotov**[1], **Benjamin J. Luft**[1], **Ryan L. Boyd**[4], **H. Andrew Schwartz**[1,2], **Oscar Kjell**[2,5]
[1]Stony Brook University, [2]Vanderbilt University, [3]University of Minnesota Twin Cities, [4]University of Texas at Dallas, [5]Lund University
scott.feltman@stonybrook.edu, nils.e.kjell@vanderbilt.edu

Abstract

Language-based assessments of health have demonstrated validity in terms of convergence with self-report questionnaire scores, but recent work has shown they lack an important psychometric property: discriminant validity, the ability of the measure to distinguish the target construct from a related one. For example, a language-based general mental health assessment may accurately assess the degree of mental health, but it may also produce scores that correlate with general physical health well beyond theoretical expectations. Here, we propose and evaluate two methods for altering the standard loss function to directly penalize off-target correlations while retaining convergent validity. Evaluated across two clinical language datasets spanning physical and mental health, the augmentations substantially reduced off-target correlations with minimal loss in convergent validity (on-target correlations). Limiting loss in convergent validity to 0.005 Pearson correlation points, the loss function using Squared Cosine Similarity Discrimination significantly improved discriminant validity of language-based mental and physical health assessments ($r = 0.454 \rightarrow r = 0.322$; $p < 0.05$); and fundamental psychopathology dimensions ($r = 0.442 \rightarrow 0.430$; $p < 0.05$). These findings demonstrate that enforcing discriminant validity as a training objective is effective, moving language-based assessments closer to the specificity required for differential clinical use.

1 Introduction

Language provides a rich signal for understanding mental and physical health (Boyd and Schwartz, 2020; Tausczik and Pennebaker, 2010; Kjell et al., 2023). Computational psycholinguistic research has demonstrated valid language-based assessments of depression (Eichstaedt et al., 2018), anxiety (Rutowski et al., 2020), well-being (Kjell et al., 2021; Mesquiti et al., 2026), and physical health outcomes (Lian et al., 2023; Adejumo et al., 2024). Language sources have ranged from natural social media text (Pak and Paroubek, 2010; Merchant et al., 2019; Alvi et al., 2023) to probed responses, where individuals describe their psychological state in open-ended natural language in response to targeted questions (Kjell et al., 2018) to structured clinical interviews (Hur et al., 2024). With the advent of pretrained large language models, the accuracy (i.e., the convergent validity) of probed language-based assessments has improved to approach the theoretical upper limit of accuracy defined by the target scales' own reliability with $r > 0.80$ (Kjell et al., 2021; Gu et al., 2025; Nilsson et al., 2024).

However, a fundamental psychometric challenge remains understudied in the language-based assessment literature: discriminant—validity the degree to which a measure is unrelated to conceptually distinct constructs (Campbell and Fiske, 1959). Mental and physical health constructs are rarely independent; when language-based models are trained to predict one construct, they frequently yield inflated correlations with correlated off-target constructs (Kjell et al., 2021; Gu et al., 2025), making it difficult to determine whether a model is capturing something specific to the target condition or merely reflecting shared variance across constructs.

Prior work has largely focused on maximizing convergent validity without penalizing correlations with off-target constructs. While some approaches within the language-based assessment literature have partially addressed this through measurement design (Kjell et al., 2018, 2021; Gu et al., 2025; Zhang et al., 2018; Wu et al., 2020), discriminant validity has not been enforced as a penalty within the training objective for continuous health outcome regression. In this work, we address this gap by augmenting the ridge regression objective function with two discriminant penalty terms, deriving closed-form solutions for each, and evaluating their

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 43–55
July 4, 2026 ©2026 Association for Computational Linguistics

behavior across two health language datasets with differing construct structures. Specifically, we address the following research questions:

- To what degree can objective function augmentation in ridge regression enforce discriminant validity between correlated health constructs assessed from language while retaining convergent validity?
- To what degree does objective function augmentation affect the inter-correlation of predictions from models trained on distinct constructs?
- Does discriminant improvement across constructs systematically vary according to the original (non-penalized) convergent validity or the target scale's reliability?

2 Background

Discriminant Validity in Health Assessment. Discriminant validity, introduced by Campbell and Fiske (1959) as part of the multitrait-multimethod framework, refers to the degree to which a measure does not spuriously correlate with conceptually distinct constructs. Discriminant validity is a cornerstone of psychometric assessment (Campbell and Fiske, 1959; Phan et al., 2016; Meirte et al., 2016). Valid measurement requires not only that a measure converges with other measures of the same construct, but that it diverges from measures of different constructs—a dual requirement that maps directly onto the challenge of language-based health assessments. A model trained to assess depression from language should correlate strongly with depression rating scales, but substantially less with anxiety or somatic scales. A measure that cannot make this distinction holds limited interpretive value regardless of its convergent accuracy (Campbell and Fiske, 1959; Jackson, 1969; Marsh and Bailey, 2016; Meyer et al., 2001).

This challenge is particularly pronounced in mental health assessment, where comorbidity is common (Kessler et al., 2005; Krueger and Markon, 2006). Mental health constructs frequently co-occur, such as depression with anxiety, substance use disorders with antisocial behavior, or narcissism with paranoid personality disorder (Ruggero et al., 2019; Kotov et al., 2017). Mental health conditions also commonly co-occur with physical health problems (Prince et al., 2007; Scott et al., 2008; DE Hert et al., 2011), creating overlapping construct spaces that challenge discriminant measurement across both domains. In clinical settings, the ability to distinguish between related conditions is essential for accurate diagnosis (Regier et al., 2013; Gu et al., 2025), treatment planning (Gu et al., 2015; Insel et al., 2010), and outcome monitoring (Hunsley and Mash, 2007), making discriminant validity not merely a psychometric requirement but a practical necessity for meaningful health assessment.

Discriminant Validity in Language-Based Assessment. Even with construct-specific probed responses, such as individuals separately describing their level of each construct in open-ended natural language (Kjell et al., 2018), language-based assessments show poor to moderate discriminant validity; predicted score correlations between harmony in life and satisfaction with life reach $r = 0.96$, despite the rating scales themselves correlating at $r = 0.85$ (Kjell et al., 2021).

The problem compounds when language sources are combined across constructs and response formats: convergent validity increases, but assessment scores become nearly indistinguishable, with cross-construct correlations reaching $r = 0.97$ (Gu et al., 2025). The problem of poor discriminant validity has also been found across language sources, including Fried (2016), Sikström et al. (2024b), and Rasing et al. (2017). Models trained on such data risk learning average expressions of related constructs rather than the specific signal of each, reducing the interpretive precision of both predictions and the linguistic features associated with them. Prior work has addressed this through measurement design by assessing *normalized difference scores* between constructs (Kjell et al., 2021; Gu et al., 2025) or using cosine similarity between individuals' responses to construct-specific word norms (Kjell et al., 2018, 2021). This demonstrates that a construct-specific signal exists in language and can be partially recovered; however, none of these approaches use poor discriminant validity as a penalty within the training objective itself. Rather, they either redefine the prediction target (i.e., training to a difference score) or address it at the representation level (i.e., using similarity to construct-specific word norms), leaving discriminant validity as a design choice rather than an optimization target.

Discriminant Loss Functions in Natural Language Processing (NLP). Penalizing representational overlap during training has been explored in

NLP for related but distinct purposes: contrastive learning has been used to separate dissimilar representations in self-supervised settings (Chen et al., 2020; Wu et al., 2020; Giorgi et al., 2021), and adversarial training has been applied to remove demographic confounds from text representations (Zhang et al., 2018; Elazar and Goldberg, 2018). Most relevant to our approach, discriminant ridge classifiers have been proposed for categorical outcomes, penalizing overlap between class predictions to improve sensitivity and specificity (Peng and Cheng, 2021). However, extending this logic to continuous regression is non-trivial: categorical discriminant penalties operate on class boundaries and discrete decision regions, whereas continuous health outcomes require penalizing the correlation between real-valued prediction vectors—a fundamentally different geometric objective. None of these approaches has therefore been adapted for continuous health outcome regression, where the goal is to reduce the correlation between predictions of related yet distinct continuous constructs. This gap motivates the present work.

Contributions. We propose two augmentations to the ridge equation: *Mean Squared Error Discrimination* (MSE Discrimination) and *Squared Cosine Similarity Discrimination* (SCS Discrimination) that enforce discriminant validity between correlated health constructs assessed from language while retaining convergent validity. We derive closed-form solutions for both augmentations compatible with standard Singular Value Decomposition (SVD)-based solvers (Eckart and Young, 1936) and evaluate how objective function augmentation affects the discriminant validity of language-based assessment scores from models trained on distinct constructs. Next, we show that discriminant validity improvements systematically vary as a function of the scale's baseline convergent validity and reliability. We also introduce a preliminary investigation into the disentanglement of linguistic features resulting from enforcing discriminant validity, demonstrating the potential to extract specific linguistic features and partially remove associative strength from opposing, but related constructs. Together, these contributions address a practical barrier to the clinical deployment of language-based health assessment: without discriminant validity, models risk conflating related conditions, limiting their utility for differential assessment, the identification of construct-specific linguistic markers, and the development of targeted, individualized treatment plans.

3 Datasets

We evaluate our methods on two datasets: the *World Trade Center (WTC) Clinic* dataset, consisting of transcripts from automated clinical interviews with physical and mental health quality of life outcomes (Kjell et al., 2026), and the *Interviews of Hierarchical Taxonomy of Psychopathology (iHiTOP)* dataset, comprising transcripts from semi-structured clinical interviews and responses to the iHiTOP questionnaire with six psychopathology spectrum scores (see Kotov et al. (2024) for more details). The Institutional Review Board approved both studies at *Stony Brook University* (IRB#2022-00391 and IRB#604113).

3.1 WTC Clinic

Participants were enrolled through the *Stony Brook WTC Health and Wellness Program*, a clinical program providing ongoing health monitoring to responders to the September 11th attacks (Kjell et al., 2026). During yearly clinic visits, participants completed structured screening questionnaires covering physical and mental health symptoms. The final dataset contained transcripts from N = 1,589 participants, with 849 words on average. The cohort was overwhelmingly male (91.93% male, 7.40% female) and predominantly white (84.81% Caucasian, 3.22% African American, 0.56% Asian American, 7.78% multi-racial). Summary statistics of the WTC Clinic dataset are provided in Table 1. Outcomes were the Physical Component Summary (PCS) and Mental Component Summary (MCS) scores derived from the SF-12 (Steenstrup et al., 2013), measuring quality of life across physical and mental health dimensions, respectively.

3.2 iHiTOP

The Hierarchical Taxonomy of Psychopathology (HiTOP), introduced by (Kotov et al., 2017), organizes psychopathological characteristics into a dimensional hierarchy based on empirical patterns of co-variation. Despite being comprised of distinct items (Kotov et al., 2017), individual scales share high correlations as seen in Table 2, making it a particularly demanding testbed for discriminant validity for psychopathology as a whole. Participants (N=609) completed a survey comprising over 200 items spanning the HiTOP framework. Six

WTC Clinic	Number of Participants	Average	SD
Participants	1,589		
Tokens	-	848.92	633.44
Age	-	57.93	8.00
PCS	1,308	46.07	10.64
MCS	1,308	52.49	8.86
iHiTOP	**Number of Participants**	**Average**	**SD**
Participants	609		
Tokens	-	9,055.46	6,159.76
Age	-	43.49	16.11
Internalizing	598	0.69	0.49
Somatoform	574	0.28	0.46
Thought Disorder	596	0.27	0.39
Detachment	596	0.52	0.48
Disinhibition	605	0.64	0.56
Antagonism	603	0.33	0.36

Table 1: Descriptive statistics for WTC Clinic and iHiTOP datasets, detailing language contents for analyzed transcripts with physical and mental health constructs.

	INT	SOM	TD	DET	DIS	ANT
INT	1.000	0.394	0.450	0.660	0.653	0.482
SOM	0.394	1.000	0.293	0.281	0.267	0.243
TD	0.450	0.293	1.000	0.394	0.424	0.383
DET	0.660	0.281	0.394	1.000	0.476	0.428
DIS	0.653	0.267	0.424	0.476	1.000	0.581
ANT	0.482	0.243	0.383	0.428	0.581	1.000

Table 2: Symmetric correlation matrix of iHiTOP spectra for valid participants. High inter-scale correlation suggests low discriminant validity, leading to ambiguous feature learning during training without careful preparation.

HiTOP spectrum scores were derived as composite scores from their constituent items, requiring a minimum of approximately 80% valid item responses and otherwise treated as missing: Internalizing, Somatoform, Thought Disorder, Detachment, Disinhibition, and Antagonism. The sample was predominantly female (62.8%) and white (78.17%), with a mean age of 43.49 years (*SD* = 16.11). Descriptive statistics are provided in Table 1.

4 Methods

4.1 Closed-form solutions

To enforce discriminant validity directly within the training objective, we augment the standard Ridge Regression (Hoerl and Kennard, 1970) loss function with two discriminant penalty terms and derive closed-form solutions for each. Both solutions are compatible with standard Singular Value Decomposition (SVD)-based solvers (Eckart and Young, 1936) as implemented in scikit-learn (Pedregosa et al., 2011), enabling straightforward integration into existing language-based assessment pipelines. We derive each solution by setting the derivative of the augmented objective function to zero, following the same algebraic approach used in standard ridge regression.

MSE Discrimination. For a single pair of on- and off-target outcomes, let $\mathbf{X}$, y, d, w, α and γ be the input feature matrix containing user language representations, outcome array of the target clinical construct, outcome array of off-target clinical constructs, model weight vector which describes the relationship between language features and clinical outcomes, L2 penalty which reduces overfitting by penalizing excessive large-magnitude weights, and discriminant penalty which penalizes high accuracies between the model predictions and off-target labels, respectively. The augmented ridge equation is given as

$$L = (\mathbf{X}w - y)^2 + \alpha||w||_2^2 - \gamma(\mathbf{X}w - d)^2 \quad (1)$$

We take the derivative with respect to w and set the expression equal to zero, yielding

$$0 = 2\mathbf{X}^T(\mathbf{X}w^* - y) + 2\alpha w^* - 2\gamma\mathbf{X}^T(\mathbf{X}w^* - d) \quad (2)$$

The weight vector, now denoted by w^*, is the set of model parameters that minimizes the penalized objective function. This achieves a balance between reducing error with respect to the construct of interest and reducing predictive overlap with constructs on which the models are not being trained. By distributing the first and third terms, we can group like terms together and isolate w^* to obtain

$$\mathbf{X}^T(y - \gamma d) = [\mathbf{X}^T\mathbf{X} + \alpha\mathbf{I} - \gamma\mathbf{X}^T\mathbf{X}]w^* \quad (3)$$

$$= [(1 - \gamma)\mathbf{X}^T\mathbf{X} + \alpha\mathbf{I}]w^* \quad (4)$$

Factoring out $1-\gamma$ from the right-hand side, letting $G = 1 - \gamma$, and taking the inverse results in the optimal weight vector

$$w^* = \frac{1}{G}[\mathbf{X}^T\mathbf{X} + \frac{\alpha}{G}\mathbf{I}]^{-1}\mathbf{X}^T(y - \gamma d) \quad (5)$$

In this form, it is clear to see that the discriminant parameter γ behaves nonlinearly. This is in contrast to the L2 penalty, which behaves linearly within the differential equation. As a consequence, this objective function is only valid for $0 \leq \gamma < 1$[1], lest the function become non-convex—no longer guaranteeing an optimal solution—which would result in incoherent model results. Further, it is reasonable to suspect that as γ approaches 1, the convergence becomes increasingly unstable, leading to uncertainties in the solution.

It is common for datasets to have more than two variables of interest; accordingly, we can further expand the above solution for multiple discriminant dimensions as

$$w^* = \frac{1}{G}[\mathbf{X}^T\mathbf{X} + \frac{\alpha}{G}\mathbf{I}]^{-1}\mathbf{X}^T(y - \gamma d_{tot}) \quad (6)$$

where $G = 1 - N\gamma$, and N, d_{tot} are the number and sum of discriminant dimensions, respectively. It is important to note that as the number of constructs against which to discriminate increases, the maximum value of γ decreases, limiting the valid range and requiring a finer grid search net. Thus, the domain of γ can be expanded to

$$\{\gamma \in \mathbb{R} \mid 0 \leq \gamma < \frac{1}{N}\} \quad (7)$$

From Equation 7, we can conclude that MSE Discrimination is suitable for two-outcome modeling in order to keep the range of γ consistent.

Many datasets, including iHiTOP, have more than two correlated outcomes, requiring a different loss function.

Squared Cosine Similarity Discrimination. While MSE Discrimination separates related constructs by their absolute distance, this may not completely remove overlapping latent features during model fitting. Instead, it may be more beneficial to separate their *alignment*, which can be determined by cosine similarity. Cosine similarity has seen much use in the field of computational linguistics, especially with its easy-to-calculate gradient when using normalized vectors. Upon scaling outcome and prediction vectors to a magnitude of 1, the formula for cosine similarity simplifies to the dot product

$$cos(\theta) = (\mathbf{X}w) \cdot d = d^T\mathbf{X}w \quad (8)$$

This allows for a clean, convex, and numerically stable closed-form solution of the augmented ridge equation. However, because cosine similarity spans a range of [-1,1], we opted to use Squared Cosine Similarity (SCS) to prioritize minimizing the magnitude of construct similarity, instead of producing highly anti-correlated predictions. This results in the modified objective function

$$L = (\mathbf{X}w - y)^2 + \alpha||w||_2^2 - \gamma(d^T\mathbf{X}w)^2 \quad (9)$$

Following the same approach as with MSE Discrimination, we can arrive at the minimum loss solution

$$w^* = [\mathbf{X}^T\mathbf{X} + \alpha\mathbf{I} + \gamma\mathbf{X}^T dd^T\mathbf{X}]^{-1}\mathbf{X}^T y \quad (10)$$

In contrast to the MSE discrimination penalty, γ mimics the linear behavior of α within the objective function, while removing the limited range and allowing for a more robust and well-behaved hyperparameter. However, this alteration results in a non-symmetric matrix, which adds an extra step to the SVD solver since now diagonalization cannot be exploited.

5 Results

5.1 Discriminant and Convergent Validity Under Objective Function Augmentation

Using SCS Discrimination shows a steady decline in convergent validity for SF-12 constructs, while their respective discriminant correlations decreased significantly faster and to a larger degree Figure 1. Discriminant and convergent validity stabilized for γ > 1000 at a tolerance of 1e-4, suggesting no further changes from continuing to raise gamma. MSE Discrimination demonstrated significantly more pronounced changes in both convergent and discriminant validity, still improving discrimination between SF-12 constructs until γ = 0.75; however, this augmentation becomes unstable where $0.9 < \gamma < 1$. Detailed plots of model performance

[1]While $\gamma < 0$ is physically possible, this would penalize discrimination between the off-target construct, violating its purpose.



Figure 1: Performance of MSE and SCS Discrimination on SF-12 constructs. PCS and MCS show very minimal losses in convergent validity for SCS Discrimination, with pronounced decreases in off-target correlations as γ increases. With MSE Discrimination, MCS experiences a more severe loss in convergent validity relative to PCS, however divergence between off-target metrics continues to increase until $\gamma = 0.75$. The model begins to collapse at large γ, as numerical instability overpowers the closed-form solution. MSE Discrimination also loses convergent validity at a faster rate than SCS Discrimination, suggesting preferential usage of the latter augment.

for SF-12 constructs are shown in Figure 1. Because of the instability and limited range of MSE Discrimination, especially with multiple scales, only SCS Discrimination is tested on iHiTOP data.

All HiTOP constructs showed varying degrees of improvements in separation, with four out of six showing large divergence on average. Internalizing and Disinhibition show marginal increases in discrimination against off-target constructs on average, while Somatoform shows the greatest increase in separation and least loss in convergent validity. Antagonism, Detachment, and Thought Disorder display modest decreases in convergent validity with moderately increased discriminant validity for the five off-target constructs. Interestingly, four of the six constructs, without discriminant penalties, had worse convergent validity than at least one of the off-target constructs, which is quickly alleviated as gamma increases. Figure 2 shows the convergent and discriminant validity plots for all six spectra for the iHiTOP dataset, including individual constructs.

Squared Cosine Similarity Discrimination		Mean Squared Error Discrimination	
Gamma	Correlation	Gamma	Correlation
0	0.454	0	0.454
0.05	0.446	0.01	0.438
0.25	0.417	0.05	0.372
1.0	0.322	0.10	0.284
5.0	0.052	0.25	-0.015
25.0	-0.198	0.50	-0.535
∞	-0.316	1.0	-1[2]

Table 3: Inter-prediction correlations for SF12 constructs compared between separation method. For MSE Discrimination, inter-correlation begins to drop sharply after $\gamma = 0.01$, and approaches perfect anti-correlation as γ approaches 1. For squared cosine similarity, inter-correlations decline more slowly as compared to MSE Discrimination, in addition to reaching a minimum of -0.316 at a tolerance of 1e-4, preventing instability.

5.2 Discriminant Validity of Language-Based Assessments

For SF-12 constructs, the inter-correlations between language-based assessment predictions consistently decreased for both MSE and SCS Discrimination as γ increased. This suggests that the discriminant penalty does incentivize decoupling predictions from the distinct models, and that models are learning features more specific to that construct. See Table 3 for a more detailed layout of the distribution of SF-12 language-based assessment predictions.

HiTOP constructs exhibit results similar to SF-12, with language-based assessment inter-correlations strictly decreasing as γ increased, showing consistent and stable behavior with SCS Discrimination. We found that $\gamma = 5.0$ yielded the smallest magnitudes on average (Table 4), further confirmed with a Mann-Whitney U test against remaining γ values ($p < 0.05$).

5.3 Role of Scale Reliability and Baseline Convergent Validity in Discriminant Improvement

The relative improvement of discriminant validity was different for individual constructs, calling into question the existence of a systemic relationship between performance gain (divergence), and their latent properties. Because gamma selection is dependent upon the individual needs for analysis, we opt to select the largest gamma with a loss of con-

[2]Because $\{\gamma \in \mathbb{R} \mid 0 \leq \gamma < 1\}$ for MSE Discrimination, this value represents the limit as γ approaches 1.0.



Figure 2: Performance plots of models trained on individual HiTOP constructs against average off-target correlations as a function of γ. Somatoform, Thought Disorder, and Antagonism show rapid improvements in discriminant validity. Internalizing and Detachment display modest acceleration of discriminant validity, while Disinhibition shows little improvement.

vergent validity below 0.005—a practical heuristic representing a negligible reduction that falls within the margin of sampling variability at these sample sizes and would be largely indistinguishable from the non-penalized estimate in practice. We also select the gamma at which inter-prediction correlations are closest to orthogonal as a comparison to demonstrate the varying behaviors for different strengths of discriminant penalties ($\gamma = 5.0$, as determined in subsection 5.2).

We found that all six scales yielded statistically significant improvements in discriminant validity when limiting loss in convergent validity to 0.005 ($p < 0.05$) using Benjamini-Hochberg Correction for multiple tests (Benjamini and Hochberg, 1995). Four out of six scales attained statistically significant improvements in discriminant validity at $\gamma = 5.0$ (see Table 5 for more details.) Discriminant validity gain relative to convergent validity loss at $\gamma = 5.0$ correlated extremely well with non-penalized convergent validity ($r = -0.967$, $p < 0.05$), and moderately well with the reliability coefficient for each scale ($r = -0.768$, $p < 0.10$). However, when limiting convergent validity loss to 0.005, reliability was significantly correlated with discriminant validity improvement ($r = -0.823$, $p < 0.05$).

5.4 Linguistic Feature Disentanglement

Preliminary differential language analysis was performed on the SF-12 constructs to evaluate relationships between group-level linguistic features and model predictions using the *topics* (Ackermann et al., 2024) package in R (R Core Team, 2025). Correlations were obtained for non-penalized and penalized ridge model predictions, and evaluated according to association strength change for PCS and MCS, respectively, against 1-grams in participant transcripts. Words commonly associated with physical health (such as "pain" or "breathing") were disentangled from MCS with reductions in correlations larger than 0.005, while strengthening correlations of words more associated with mental health, for both negative and positive contexts (e.g.

Spectra	Gamma	INT	SOM	TD	DET	DIS	ANT
INT	0	-	0.609	0.685	0.846	0.855	0.690
	0.30	-	0.515	0.583	0.786	0.792	0.585
	5.00	-	0.015	-0.051	0.330	0.219	-0.128
	∞	-	-0.162	-0.266	0.144	-0.060	-0.397
SOM	0	0.609	-	0.519	0.526	0.521	0.480
	0.10	0.576	-	0.483	0.487	0.479	0.440
	5.00	0.015	-	0.023	-0.088	-0.203	-0.087
	∞	-0.162	-	-0.065	-0.222	-0.393	-0.196
TD	0	0.685	0.519	-	0.587	0.671	0.653
	0.05	0.667	0.501	-	0.565	0.653	0.636
	5.00	-0.051	0.023	-	-0.181	-0.037	0.123
	∞	-0.266	-0.065	-	-0.346	-0.217	0.024
DET	0	0.846	0.526	0.587	-	0.764	0.639
	0.10	0.826	0.487	0.544	-	0.733	0.600
	5.00	0.330	-0.088	-0.181	-	0.030	-0.100
	∞	0.144	-0.222	-0.346	-	-0.206	-0.277
DIS	0	0.855	0.521	0.671	0.764	-	0.769
	0.15	0.824	0.460	0.618	0.718	-	0.731
	5.00	0.219	-0.203	-0.037	0.030	-	0.230
	∞	-0.060	-0.393	-0.217	-0.206	-	0.078
ANT	0	0.690	0.480	0.653	0.639	0.769	-
	0.10	0.654	0.440	0.620	0.600	0.743	-
	5.00	-0.128	-0.087	0.123	-0.100	0.230	-
	∞	-0.397	-0.196	0.024	-0.277	0.078	-

Table 4: Inter-prediction correlations for HiTOP constructs at chosen γ. Zero and asymptotic strengths are selected for display to show the overall dynamics of discriminant prediction validity as a function of γ. Inter-correlations consistently decrease as penalty strength increases, even into inverse relationships despite the strictly positive discriminant augment. For $\gamma = 5.0$, the average correlation among predictions was 6.32×10^{-4}.

		$\gamma = 5.0$		Optimal γ		
Spectra	Reliability	ΔDisc.	$\Delta\Delta$Div.	Gamma	ΔDisc.	$\Delta\Delta$Div.
INT	0.960	0.202	0.033	0.30	0.010	**0.005**
SOM	0.850	0.255	**0.162**	0.10	0.014	**0.010**
TD	0.844	0.286	**0.125**	0.05	0.020	**0.016**
DET	0.866	0.270	**0.079**	0.10	0.009	**0.005**
DIS	0.919	0.225	0.035	0.15	0.007	**0.003**
ANT	0.807	0.269	**0.101**	0.10	0.010	**0.019**

Table 5: Changes in discriminant validity and divergence, defined as change between loss in discriminant and convergent correlation, for six iHiTOP spectra at selected gamma. Optimal gammas were selected to limit loss of convergent validity to 0.005. Four out of six HiTOP constructs demonstrated significantly increased negative shifts in correlation at $\gamma = 5.0$ ($p < 0.05$, indicated by bold), while all iHiTOP constructs attained significant increases in discriminant validity at the optimal strengths. This suggests successful balancing of limited loss in convergent validity while strengthening the signal compared to off-target constructs.

"divorce", "grandkids"). Similar patterns were observed with PCS, decreasing correlations of language features tied to emotions like "family" or "ptsd" while strengthening associations for phrases related to physical health (see Table 6).

6 Discussion

The results demonstrate that discriminant validity can be directly enforced as an optimization target in continuous health outcome regression, addressing a gap that has persisted in the language-based assessment literature despite growing recognition of the problem (Kjell et al., 2021; Gu et al., 2025; Sikström et al., 2024a). Both augmentations reduced off-target correlations while retaining convergent validity and eventually achieving orthogonality of inter-prediction correlations, suggesting that penalization reshapes weights to produce construct-specific solutions rather than the shared variance.

The two augmentations enforced discriminant validity through distinct mechanisms, with important practical consequences. MSE Discrimination penalizes the absolute distance between predictions and the off-target outcome vector, producing sharp reductions in off-target correlations but within a constrained valid range that shrinks as additional constructs are added. The solution becomes numerically unstable as γ approaches 1, and inter-prediction correlations quickly continue into strong anti-correlation, tightening the relationship between predictions in the opposite direction, which is equally undesirable.

SCS Discrimination instead penalizes the angular alignment between prediction vectors, useful in situations where producing predictions which do not share the same associative strength as their constructs is ideal. This leads to more gradual, stable improvements that converge to a well-behaved minimum. This angular framing has conceptual precedent in contrastive learning approaches that leverage cosine similarity to separate dissimilar representations (Gao et al., 2021), and in adversarial training used to remove demographic confounds from text representations (Zhang et al., 2018; Elazar and Goldberg, 2018). However, those approaches operate on discrete classes or binary confounds, whereas the present work penalizes correlation between real-valued continuous prediction vectors—a geometrically distinct objective requiring a different closed-form treatment. MSE Discrimination may therefore be appropriate when only two constructs are involved and aggressive separation is needed, but SCS is preferable in the more common case of multiple correlated outcomes, where stability and a wide usable range of γ are necessary.

The strong inverse relationship between baseline convergent validity and discriminant gain ($r = -0.967$, $p < 0.05$) at $\gamma = 5.0$ suggests an interpretable mechanism: models of con-

Outcome	Word	Baseline Pearson R	Penalized Pearson R
PCS	family	0.161	0.153
	ptsd	-0.104	-0.096
	surgery	-0.171	-0.176
	recovered	-0.051	-0.059
MCS	pain	-0.102	-0.092
	breathing	-0.095	-0.085
	grandkids	0.062	0.069
	divorce	-0.125	-0.131

Table 6: Preliminary behavior of 1-grams correlated with SF-12 constructs before and after discriminant penalization. 1-grams from participant transcripts were correlated with predictions from standard and discriminant ridge models (selecting gamma to limit convergent validity loss to 0.005). Disentanglement is seen for both PCS and MCS, showing changes larger than the degree of convergent validity loss.

structs with high-performing language-based analysis have weight vectors robust to shifts from discriminant penalization. Constructs with lower baseline convergent validity exhibit more moldable weight vectors, allowing for effective reshaping towards construct-specific features. The reliability finding adds a complementary layer: less reliable scales, which present noisier prediction targets, benefit most in absolute discriminant terms ($r = -0.899$, $p < 0.05$) but show a weaker relationship against discriminant gain ($r = -0.767$, $p < 0.10$). Less reliable scales, however, statistically benefit to a greater degree upon limiting convergent validity loss ($r = -0.823$, $p < 0.05$), hinting at an interesting dynamic between different gammas across health dimensions. Together, these results suggest that the practical benefit of objective function augmentation is greatest precisely in the cases where language-based assessment is most challenging—low-reliability, harder-to-predict constructs—and may offer diminishing returns as convergent validity approaches its theoretical ceiling, as seen in Table 5.

The present findings may have direct implications for the clinical deployment of language-based health assessment. While the current implementation utilizes deterministic solutions, this procedure can be applied to gradient-based models, such as transformers, as current models trained on correlated health outcomes risk conflating related conditions, limiting their utility for differential assessment of health conditions (e.g., Somatoform symptoms from Internalizing disorder, or physical from mental health decline.) This further shows potential usage as a fine-tuning procedure to tailor models to specific health constructs before clinical deployment. By enforcing discriminant validity as an optimization target, models produce predictions that are more interpretable, separable, and suitable for the identification of construct-specific linguistic markers. Linguistic features show potential for disentanglement as a result of enforcing discriminant validity, with positive examples of expected directional shifts of 1-grams with SF-12 predictions (see Table 6). Though the degree of separation was small, hovering at and just above the 0.005 convergent loss limit, greater linguistic separation may emerge by using larger gamma values, at the risk of more loss in convergent validity. As language-based assessments move closer to clinical deployment (e.g. in tele-health, automated interviews, and longitudinal monitoring), the ability to distinguish between related conditions and their corresponding language, rather than merely predict them in aggregate, becomes not a psychometric nicety but a practical prerequisite for meaningful use.

7 Conclusion

We proposed and evaluated two loss functions that enforce discriminant validity as a direct optimization target in continuous health outcome regression. Both augmentations substantially improved discriminant validity while retaining convergent validity. Notably, discriminant improvement was greatest for constructs with lower baseline convergent validity and reliability. We also demonstrated an introductory procedure to evaluate the effect of discriminant validity enforcement on linguistic features, showing that enforcing discriminant validity through loss functions has the potential to disentangle words from opposing, but correlated constructs. This opens the possibility of characterizing how distinct health conditions are expressed differently in language, rather than merely predicting them in aggregate, thereby informing the theoretical understanding of what is linguistically specific to each construct. As language-based assessments move closer to clinical deployment in areas such as tele-health, automated interviews, and longitudinal monitoring, the ability to distinguish between related conditions becomes a practical prerequisite for meaningful use. The present work provides a tractable, theoretically grounded path toward that goal.

Limitations

Both solutions require closed-form derivations, which constrains the class of penalty functions that can be applied; gradient-based extensions are possible but were not evaluated here. The selection of γ requires a grid search, and the valid range for MSE Discrimination narrows with each additional construct, making hyperparameter tuning increasingly costly in high-dimensional construct spaces. The present evaluation was conducted on two datasets with specific demographic compositions and language elicitation formats; generalization to other populations, language sources, and outcome structures remains to be established. Further, to our knowledge, no other studies have explored the variability of discriminant validity in this fashion, providing no ground truth to the degree of discrimination for comparison. This is amplified by the distinct nature and large volume of psychometric constructs. Future work should examine the predictive overlap between different psychometric constructs for future comparisons. Proper evaluation of methods to assess discriminant validity should include on- and off-target correlations for each model per construct of interest, using the methods established in this paper in addition to novel frameworks. Additionally, it should be seen whether these augmentations extend to transformer-based fine-tuning pipelines and whether the construct-level moderators identified here, being baseline validity and reliability, replicate across domains beyond psychopathology as well as mental and physical health.

References

Leon Ackermann, Zhuojun Gu, and Oscar N. E. Kjell. 2024. An R-package for visualizing text in topics.

Philip Adejumo, Phyllis M Thangaraj, Lovedeep Singh Dhingra, Arya Aminorroaya, Xinyu Zhou, Cynthia Brandt, Hua Xu, Harlan M Krumholz, and Rohan Khera. 2024. Natural language processing of clinical documentation to assess functional status in patients with heart failure. *JAMA Netw Open*, 7(11):e2443925.

Quratulain Alvi, Syed Ali, Sheikh Ahmed, Nadeem Khan, Mazhar Awan, and Haitham Nobanee. 2023. On the frontiers of twitter data and sentiment analysis in election prediction: a review. *PeerJ Computer Science*, 9:e1517.

Yoav Benjamini and Yosef Hochberg. 1995. Controlling the false discovery rate: A practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society. Series B (Methodological)*, 57(1):289–300.

Ryan L Boyd and H Andrew Schwartz. 2020. Natural language analysis and the psychology of verbal behavior: The past, present, and future states of the field. *J Lang Soc Psychol*, 40(1):21–41.

D T Campbell and D W Fiske. 1959. Convergent and discriminant validation by the multitrait-multimethod matrix. *Psychol Bull*, 56(2):81–105.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. 2020. A simple framework for contrastive learning of visual representations. *Preprint*, arXiv:2002.05709.

Marc DE Hert, Christoph U Correll, Julio Bobes, Marcelo Cetkovich-Bakmas, Dan Cohen, Itsuo Asai, Johan Detraux, Shiv Gautam, Hans-Jurgen Möller, David M Ndetei, John W Newcomer, Richard Uwakwe, and Stefan Leucht. 2011. Physical illness in patients with severe mental disorders. I. prevalence, impact of medications and disparities in health care. *World Psychiatry*, 10(1):52–77.

Carl Eckart and Gale Young. 1936. The approximation of one matrix by another of lower rank. *Psychometrika*, 1(3):211–218.

Johannes C Eichstaedt, Robert J Smith, Raina M Merchant, Lyle H Ungar, Patrick Crutchley, Daniel Preoţiuc-Pietro, David A Asch, and H Andrew Schwartz. 2018. Facebook language predicts depression in medical records. *Proc Natl Acad Sci U S A*, 115(44):11203–11208.

Yanai Elazar and Yoav Goldberg. 2018. Adversarial removal of demographic attributes from text data. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 11–21, Brussels, Belgium. Association for Computational Linguistics.

Eiko I Fried. 2016. The 52 symptoms of major depression: Lack of content overlap among seven common depression scales. *J Affect Disord*, 208:191–197.

Tianyu Gao, Xingcheng Yao, and Danqi Chen. 2021. SimCSE: Simple contrastive learning of sentence embeddings. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 6894–6910, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

John Giorgi, Osvald Nitski, Bo Wang, and Gary Bader. 2021. DeCLUTR: Deep Contrastive Learning for Unsupervised Textual Representations. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 879–895, Online. Association for Computational Linguistics.

Jenny Gu, Clara Strauss, Rod Bond, and Kate Cavanagh. 2015. How do mindfulness-based cognitive therapy and mindfulness-based stress reduction improve mental health and wellbeing? a systematic review and meta-analysis of mediation studies. *Clinical Psychology Review*, 37:1–12.

Zhuojun Gu, Katarina Kjell, H Andrew Schwartz, and Oscar Kjell. 2025. Natural language response formats for assessing depression and worry with large language models: A sequential evaluation with model pre-registration. *Assessment*, page 10731911251364022.

Arthur E. Hoerl and Robert W. Kennard. 1970. Ridge Regression: Biased Estimation for Nonorthogonal Problems. *Technometrics*, 12(1):55–67.

John Hunsley and Eric J Mash. 2007. Evidence-based assessment. *Annu Rev Clin Psychol*, 3:29–51.

Jihyun K Hur, Joseph Heffner, Gloria W Feng, Jutta Joormann, and Robb B Rutledge. 2024. Language sentiment predicts changes in depressive symptoms. *Proc Natl Acad Sci U S A*, 121(39):e2321321121.

Thomas Insel, Bruce Cuthbert, Marjorie Garvey, Robert Heinssen, Daniel S Pine, Kevin Quinn, Charles Sanislow, and Philip Wang. 2010. Research domain criteria (RDoC): toward a new classification framework for research on mental disorders. *Am J Psychiatry*, 167(7):748–751.

Douglas N. Jackson. 1969. Multimethod factor analysis in the evaluation of convergent and discriminant validity. *Psychological Bulletin*, 72(1):30–49.

Ronald C Kessler, Wai Tat Chiu, Olga Demler, Kathleen R Merikangas, and Ellen E Walters. 2005. Prevalence, severity, and comorbidity of 12-month DSM-IV disorders in the national comorbidity survey replication. *Arch Gen Psychiatry*, 62(6):617–627.

Oscar Kjell, Daiva Daukantaitė, and Sverker Sikström. 2021. Computational language assessments of harmony in life - not satisfaction with life or rating scales - correlate with cooperative behaviors. *Front Psychol*, 12:601679.

Oscar N E Kjell, Scott Feltman, H. A Schwartz, Adithya V Ganesan, Whitney R Ringwald, Sean Clouston, Melissa A Carr, Benjamin Luft, and Roman Kotov. 2026. Distinguishing the language of mental and physical health: A sequential evaluation with model preregistration of automated clinical visit interviews.

Oscar N E Kjell, Katarina Kjell, Danilo Garcia, and Sverker Sikström. 2018. Semantic measures: Using natural language processing to measure, differentiate, and describe psychological constructs. *Psychol Methods*, 24(1):92–115.

Oscar N E Kjell, Katarina Kjell, and H Andrew Schwartz. 2023. Beyond rating scales: With targeted evaluation, large language models are poised for psychological assessment. *Psychiatry Res*, 333:115667.

Roman Kotov, Robert F Krueger, David Watson, Thomas M Achenbach, Robert R Althoff, R Michael Bagby, Timothy A Brown, William T Carpenter, Avshalom Caspi, Lee Anna Clark, Nicholas R Eaton, Miriam K Forbes, Kelsie T Forbush, David Goldberg, Deborah Hasin, Steven E Hyman, Masha Y Ivanova, Donald R Lynam, Kristian Markon, and 21 others. 2017. The Hierarchical Taxonomy of Psychopathology (HiTOP): A dimensional alternative to traditional nosologies. *J Abnorm Psychol*, 126(4):454–477.

Roman Kotov, Holly Levin-Aspenson, Katherine Jonas, Camilo Ruggero, and Others. 2024. Interview for the Hierarchical Taxonomy of Psychopathology (iHiTOP). `https://osf.io/u25em/`.

Robert F Krueger and Kristian E Markon. 2006. Reinterpreting comorbidity: a model-based approach to understanding and classifying psychopathology. *Annu Rev Clin Psychol*, 2:111–133.

Ruixue Lian, Vivian Hsiao, Juwon Hwang, Yue Ou, Sarah E Robbins, Nadine P Connor, Cameron L Macdonald, Rebecca S Sippel, William A Sethares, and David F Schneider. 2023. Predicting health-related quality of life change using natural language processing in thyroid cancer. *Intell Based Med*, 7.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. RoBERTa: A robustly optimized bert pretraining approach.

Herbert Marsh and Michael Bailey. 2016. Multidimensional Students' Evaluations of Teaching Effectiveness: A Profile Analysis. *The Journal of Higher Education*, 64:1–18.

Jill Meirte, Ulrike Van Daele, Koen Maertens, Peter Moortgat, Rudi Deleus, and Nancy E Van Loey. 2016. Convergent and discriminant validity of quality of life measures used in burn populations. *Burns*, 43(1):84–92.

Raina M Merchant, David A Asch, Patrick Crutchley, Lyle H Ungar, Sharath C Guntuku, Johannes C Eichstaedt, Shawndra Hill, Kevin Padrez, Robert J Smith, and H Andrew Schwartz. 2019. Evaluating the predictability of medical conditions from social media posts. *PLoS One*, 14(6):e0215476.

Steven Mesquiti, Danielle Cosme, Erik Nook, Emily Falk, and Shannon Burns. 2026. Language-based assessments can predict psychological and subjective well-being. *Communications Psychology*, 4.

G J Meyer, S E Finn, L D Eyde, G G Kay, K L Moreland, R R Dies, E J Eisman, T W Kubiszyn, and G M Reed. 2001. Psychological testing and psychological assessment. a review of evidence and issues. *Am Psychol*, 56(2):128–165.

August Nilsson, Ryan Boyd, Adithya V Ganesan, Oscar Kjell, Syeda Mahwish, Haitao Huang, Richard Rosenthal, Lyle Ungar, and H. Schwartz. 2024.

Language-based assessments for experienced well-being: Accuracy and external validity across behaviors, traits, and states.

Alexander Pak and Patrick Paroubek. 2010. Twitter as a corpus for sentiment analysis and opinion mining. In *Proceedings of the Seventh International Conference on Language Resources and Evaluation (LREC'10)*, Valletta, Malta. European Language Resources Association (ELRA).

Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, Jake Vanderplas, Alexandre Passos, David Cournapeau, Matthieu Brucher, Matthieu Perrot, and Édouard Duchesnay. 2011. Scikit-learn: Machine learning in python. *Journal of Machine Learning Research*, 12:2825–2830.

Chong Peng and Qiang Cheng. 2021. Discriminative ridge machine: A classifier for high-dimensional data or imbalanced data. *IEEE Trans Neural Netw Learn Syst*, 32(6):2595–2609.

Duc-Anh Phan, Hiroyuki Shindo, and Yuji Matsumoto. 2016. Multiple emotions detection in conversation transcripts. In *Proceedings of the 30th Pacific Asia Conference on Language, Information and Computation: Oral Papers*, pages 85–94, Seoul, South Korea.

Martin Prince, Vikram Patel, Shekhar Saxena, Mario Maj, Joanna Maselko, Michael R Phillips, and Atif Rahman. 2007. No health without mental health. *Lancet*, 370(9590):859–877.

R Core Team. 2025. *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria.

Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. 2022. Robust Speech Recognition via Large-Scale Weak Supervision. *Preprint*, arXiv:2212.04356.

Sanne P A Rasing, Daan H M Creemers, Jan M A M Janssens, and Ron H J Scholte. 2017. Depression and anxiety prevention based on cognitive behavioral therapy for at-risk adolescents: A Meta-Analytic review. *Front Psychol*, 8:1066.

Darrel A Regier, William E Narrow, Diana E Clarke, Helena C Kraemer, S Janet Kuramoto, Emily A Kuhl, and David J Kupfer. 2013. DSM-5 field trials in the United States and Canada, Part II: test-retest reliability of selected categorical diagnoses. *Am J Psychiatry*, 170(1):59–70.

Camilo J Ruggero, Roman Kotov, Christopher J Hopwood, Michael First, Lee Anna Clark, Andrew E Skodol, Stephanie N Mullins-Sweatt, Christopher J Patrick, Bo Bach, David C Cicero, Anna Docherty, Leonard J Simms, R Michael Bagby, Robert F Krueger, Jennifer L Callahan, Michael Chmielewski, Christopher C Conway, Barbara De Clercq, Allison Dornbach-Bender, and 14 others. 2019. Integrating the hierarchical taxonomy of psychopathology (HiTOP) into clinical practice. *J Consult Clin Psychol*, 87(12):1069–1084.

Tomasz Rutowski, Elizabeth Shriberg, Amir Harati, Yang Lu, Piotr Chlebek, and Ricardo Oliveira. 2020. Depression and anxiety prediction using deep language models and transfer learning. In *2020 7th International Conference on Behavioural and Social Computing (BESC)*, pages 1–6.

H. Andrew Schwartz, Salvatore Giorgi, Maarten Sap, Patrick Crutchley, Lyle Ungar, and Johannes Eichstaedt. 2017. DLATK: Differential language analysis ToolKit. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 55–60, Copenhagen, Denmark. Association for Computational Linguistics.

K M Scott, M Von Korff, J Alonso, M C Angermeyer, E Bromet, J Fayyad, G de Girolamo, K Demyttenaere, I Gasquet, O Gureje, J M Haro, Y He, R C Kessler, D Levinson, M E Medina Mora, M Oakley Browne, J Ormel, J Posada-Villa, M Watanabe, and D Williams. 2008. Mental-physical co-morbidity and its relationship with disability: results from the world mental health surveys. *Psychol Med*, 39(1):33–43.

Sverker Sikström, Oscar Kjell, Katarina Kjell, and H. Andrew Schwartz. 2024a. Question-based computational language assessment of psychological states. *Communications Psychology*, 2:97.

Sverker Sikström, Miriam Nicolai, Josephine Ahrendt, Suvi Nevanlinna, and Lotta Stille. 2024b. Language or rating scales based classifications of emotions: computational analysis of language and alexithymia. *npj Mental Health Research*, 3(1):37.

Troels Steenstrup, Ole Birger Pedersen, Jacob Hjelmborg, Axel Skytthe, and Kirsten Ohm Kyvik. 2013. Heritability of health-related quality of life: SF-12 summary scores in a population-based nationwide twin cohort. *Twin Res Hum Genet*, 16(3):670–678.

Yla R. Tausczik and James W. Pennebaker. 2010. The psychological meaning of words: Liwc and computerized text analysis methods. *Journal of Language and Social Psychology*, 29(1):24–54.

Hanlu Wu, Tengfei Ma, Lingfei Wu, Tariro Manyumwa, and Shouling Ji. 2020. Unsupervised reference-free summary quality evaluation via contrastive learning. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 3612–3621, Online. Association for Computational Linguistics.

Brian Hu Zhang, Blake Lemoine, and Margaret Mitchell. 2018. Mitigating unwanted biases with adversarial learning. In *Proceedings of the 2018 AAAI/ACM Conference on AI, Ethics, and Society*, AIES '18, page 335–340, New York, NY, USA. Association for Computing Machinery.

8 Appendix

WTC interviews. Participants who consented to take part in research responded to questions automatically displayed on a screen in a private room during their clinical visit. Questions probed both positive and negative aspects of participants' past, present, and future lives, as well as experiences related to specific events, including 9/11 and COVID-19, using broad language rather than clinical symptom terminology. Participants were instructed not to read the questions aloud and to spend at least 60 seconds per question; recordings meeting a minimum threshold of 150 words were retained, with a mean response time of 7.5 minutes (SD = 4.1). Interviews were transcribed using Whisper-large-v2 (Radford et al., 2022) and diarized to isolate participant responses.

iHiTOP interviews. Participants engaged in a semi-structured interview with a research assistant. The interviewers asked probing questions pertaining to each overarching HiTOP construct, and assigned ratings according to participant responses. Interviewers followed a consistent rating guideline to ensure reliable outcomes for analysis.

Experimental setup. Language embeddings were extracted and analyzed from Whisper-large-v3 transcripts (Radford et al., 2022) using Layer 23 from RoBERTa-large (Liu et al., 2019) via the Python library Differential Language Analysis Toolkit (DLATK; Schwartz et al. (2017)). Embedding dimensions were standardized to zero mean and unit variance prior to model fitting. Ridge Regression models were then trained separately for each outcome using ten-fold cross-validation, with the discriminant penalty strength γ varied across a predefined grid to characterize the trade-off between convergent and discriminant validity.

Multistream Modelling for Mental Health: Modelling Linguistic and Temporal Contexts with Mutual and Self-Excitation in Social Media

Anthony Hills[1], Talia Tseriotou[1], Mahmud Elahi Akhter[1], Junyu Mao[5], Iqra Ali[1], Xenia Miscouridou[3,4], Maria Liakata[1,2]
[1]Queen Mary University of London, [2]The Alan Turing Institute, [3]University of Cyprus, [4]Imperial College London, [5]University of Southampton
{a.r.hills,t.tseriotou,m.liakata}@qmul.ac.uk

Abstract

We present MHRoBERT (Multistream HEAT over Recurrence over BERT), a hierarchical transformer architecture for longitudinal mental health monitoring that models self- and mutual excitation patterns in linguistic and temporal data across multivariate event streams relating to an individual's mental health. To supply the model with complementary perspectives on each post, we apply a Large Language Model (LLM) based annotation to extract three streams from social media posts: emotional states, personal life events, and mental health symptoms. A central finding is that multi-task learning with these automatically-generated stream labels provides substantial, consistent improvements across all model architectures evaluated. Multistream information further consistently benefits simpler models not explicitly designed to exploit it: LLM baselines incorporating stream annotations improve macro F1 by 12.6% over text-only prompting. These results have direct implications on Moments of Change detection: multistream auxiliary supervision yields consistent, substantial gains regardless of architecture, suggesting it is a simple and portable strategy that future systems can readily adopt with minimal architectural changes. MHRoBERT additionally produces interpretable learned parameters across streams, revealing temporal interaction patterns between mental health indicators.

1 Introduction

Mental health conditions manifest through multiple, interconnected signals – from emotional expressions and behavioural changes to physical symptoms and life events. Despite that, traditional approaches to analysing and modeling social media for mental health monitoring examine individual behavioural signals in isolation, without modelling the cross-stream dependencies and temporal interactions between them (Bao et al., 2024). Network theory of psychopathology posits that mental health conditions emerge from systems of mutually reinforcing symptoms that interact causally over time (Borsboom and Cramer, 2013; Borsboom, 2017), while subsequent work demonstrates that emotions form dynamic, mutually influencing networks over time (Bringmann et al., 2013) and that the interplay between positive and negative affect carries clinically meaningful information about mental health trajectories (Wichers et al., 2012). On social media, prior work has largely focused on individual behavioural signals without modelling how different streams co-evolve and mutually interact over time (Yazdavar et al., 2020; Garg, 2023), leaving important cross-stream temporal dynamics unaddressed.

In this work, we leverage the stream taxonomy inspired by Mao et al. (2025) to obtain three complementary perspectives on each post – emotional states, personal life events, and mental health symptoms – via LLM-based annotation, and investigate how these streams can be integrated into temporal modelling architectures for Moments of Change (MoC) in mood detection (Tsakalidis et al., 2022b,a; Tseriotou et al., 2025). A widely applicable finding is that multi-task learning with these automatically-generated stream labels provides substantial, consistent performance improvements across all evaluated model architectures. Multistream information widely benefits diverse architectures, with LLM baselines showing substantial improvements when provided with stream annotations. These results suggest that incorporating multistream auxiliary supervision is a broadly applicable strategy for improving MoC detection. Building on this, we present MHRoBERT (Multistream HEAT over Recurrence over BERT), a hierarchical transformer architecture that captures cross-stream temporal interactions through multistream HEAT layers and general temporal dynamics through unistream aggregation, while maintaining direct access to sequential information via residual connections. The main contributions of

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 56–75
July 4, 2026 ©2026 Association for Computational Linguistics

this work are:

- We demonstrate that multi-task learning with automatically-generated multistream labels – derived using LLM annotation inspired by the taxonomy of Mao et al. (2025) consistently and substantially improves MoC detection across diverse model architectures, including those not explicitly designed to use this information.
- MHRoBERT, a hierarchical architecture that models both self-excitation within individual streams and mutual excitation between streams, capturing nuanced temporal interactions between longitudinal mental health event data.
- Interpretable learned parameters (ϵ, β, μ) that reveal temporal interactions between streams.
- A recommendation for future CLPsych shared task submissions: our results suggest multistream auxiliary supervision is a practical, architecture-agnostic strategy for improving performance on Moments of Change detection.

Through this multistream approach, we identify patterns in how different aspects of mental health interact and evolve over time, providing a more comprehensive view of mental health progression than is possible from text alone.

2 Related Work

Multivariate Hawkes Processes Multivariate Hawkes processes (Hawkes, 1971) are the theoretical foundation for modeling mutual excitation between event streams. Zhou et al. (2013) developed efficient learning algorithms for large-scale applications, while more recently, Zhang et al. (2020) proposed the self-attentive Hawkes process, demonstrating how attention mechanisms could capture complex dependencies between different event types. In the social media domain, Rizoiu et al. (2017) used Hawkes processes to model information diffusion, demonstrating how different types of social interactions could mutually reinforce each other.

LLMs for Automated Annotation The use of LLMs for textual annotation is an emerging area and shows significant potential to create large-scale, consistently labeled datasets at low cost (Tseng et al., 2025; Meng et al., 2022). Recent work shows that LLMs can match or exceed performance of crowd workers in text annotation tasks across multiple domains (Gilardi et al., 2023; Törnberg, 2023). Li and Conrad (2024) showed that LLMs are effective when annotating explicit stances in social media posts, achieving high agreement with human annotators. However, discrepancies arise in cases where stances are implicit or ambiguous, suggesting hybrid approaches may be required for nuanced annotation scenarios. Additionally, Kristensen-McLachlan et al. (2023) raised concerns about transparency and reproducibility, highlighting significant variability in LLM performance across different tasks and noting that traditional supervised classifiers often outperform LLMs in scenarios requiring nuanced understanding. This is particularly important in mental health, where even subtle distinctions can be clinically significant.

Longitudinal Modeling for Mental Health LLMs have been used for mental health classification (Amin et al., 2023), data augmentation (Liyanage et al., 2023), and reasoning (Xu et al., 2024), demonstrating promise in detecting psychological indicators (Yang et al., 2023), extracting relevant evidence from text (Xu et al., 2024), and generating clinically informed summaries (Song et al., 2024). LLMs using instruction fine-tuning and Chain-of-Thought (CoT) prompting (Yang et al., 2023) have also been employed, though such approaches risk incorrect predictions and flawed reasoning, especially in complex conversations (Li et al., 2023). Longitudinal modeling with LLMs has emerged as a pivotal paradigm for capturing language, behavior, and mental states over time. Unlike conventional NLP tasks that treat inputs as isolated instances, longitudinal modeling enable continuous monitoring and nuanced understanding of dynamic processes such as user stance changes on social media or psychological state progression in health narratives (Park and Conway, 2017; Tsakalidis et al., 2022a; Tseriotou et al., 2023, 2024; Hills et al., 2024; Morini et al., 2025), In dialogue systems (Kwak et al., 2023), longitudinal context is essential for maintaining personalization (Chen et al., 2023), and psychological grounding across multiple conversational turns (Wang et al., 2023; Zheng et al., 2023). Current approaches have not been integrated with LLMs and focus on a single stream of data (unistream).

3 Methodology

We first discuss how we obtain multiple interacting data streams from a single data stream (§3.1). These are expected to influence each other but follow different temporal patterns. We then present a multistream temporal architecture, with cross-excitation for capturing interactions between streams (§3.2)

3.1 Stream Extraction using LLMs

We use LLMs to extract three complementary perspectives from social media posts (for the full taxonomies and prompts used to extract these, see Appendix A), namely:

Emotional States: For emotions, we adopt the taxonomy of the fine-grained labels for Affect proposed in the MIND framework (Slonim, 2024), used to label the same dataset we make use of in this work in the CLPSych 2025 shared task (Tseriotou et al., 2025). These consist of twelve intensive emotions (e.g. Happy, Proud, Sad) spanning adaptive and maladaptive affective states.

Personal Life Events: To capture significant life changes that may impact mental health, we employed the broad categories proposed in Mao et al. (2025). These categories, designed specifically for mental health transitions, were inspired by the Major Life Events Taxonomy of Haimson et al. (2021), which identifies 121 life event types across 12 categories, including health, relationships, career, and identity changes.

Symptoms: We draw on a subset of the symptom categories introduced in Mao et al. (2025) to capture both physical and psychological labels related to mental health changes. The taxonomy encompasses categories that commonly manifest during periods of mental health change – including substance use patterns, trauma responses, physical symptoms, sleep disturbances, and appetite changes

This overall categorization of the streams was designed to identify warning signs and behavioral changes that could indicate changes in mood and mental health, while remaining broad enough to capture diverse conditions.

3.1.1 Prompt Design and Language Model

We implement our automated stream annotation using Qwen 2.5-32B-Instruct (Yang et al., 2025) in a chain-of-thought (CoT) few-shot classification setting. Our selection of Qwen 2.5 was informed by comparative evaluations in Mao et al. (2025) demonstrating superior performance over other open-source models for mental health annotation tasks. A key consideration was the model's ability to run locally – enabling all processing to be performed on-premises without sending sensitive user data to external servers. This is in contrast to cloud-based language models that require data to be sent to remote services, making Qwen 2.5 particularly suitable for applications involving sensitive mental health data. For each stream, we used CoT prompting strategies (detailed in Appendix A) that guide the model through explicit reasoning before producing final annotations. Our multi-label prompt design was adapted from the approach of Mao et al. (2025), in which the model provides its reasoning for each category along with an explicit "yes" or "no" judgment before predicting the final answer label, thereby improving annotation quality and interpretability.

3.2 Multistream HEAT Architecture

Our model extends HEAT (Historical Emotional AggregaTion), a temporal aggregation mechanism inspired by the Hawkes process. Originally proposed by Sawhney et al. (2021b) for BERT encodings and adapted by Hills et al. (2024) for LSTM hidden states with learnable self-excitation (ϵ) and decay (β) parameters, HEAT weights historical representations by temporal proximity. The self-excitation parameter ϵ controls how much previous events influence future representations, while the decay parameter β determines how quickly this influence diminishes over time. We modify this approach to handle multiple interacting streams of temporally sensitive linguistic data, by processing user timelines through three main stages:

Linguistic Encoding Posts are first encoded using BERT (`bert-base-uncased`) to obtain contextual embeddings. For each post i in a timeline, BERT produces a representation $e^{(i)} \in \mathbb{R}^{768}$ by extracting the [CLS] token embedding.

Sequential Modeling The BERT embeddings are processed through an LSTM layer to capture sequential dependencies:

$$h^{(i)} = \text{LSTM}(e^{(i)}, h^{(i-1)}) \tag{1}$$

where $h^{(i)} \in \mathbb{R}^{d_{lstm}}$ represents the hidden state encoding both linguistic content and sequential context up to post i.

Multistream HEAT Representation For each target stream l, we compute a multistream HEAT representation that captures cross-stream temporal interactions:

$$H_{\text{multi}}^{(i,l)} = \mu_l + \sum_m \sum_{j<i} h^{(j)} \cdot \mathbb{I}_m^{(j)} \cdot \epsilon_{(l,m)} \cdot e^{-\beta_{(l,m)}\Delta\tau_j} \tag{2}$$

where: μ_l is the learned baseline intensity for target stream l, $\mathbb{I}_m^{(j)} \in \{0, 1\}$ indicates whether post j

belongs to stream m, $\epsilon_{(l,m)} \in \mathbb{R}^+$ captures the excitation from stream m to stream l, $\beta_{(l,m)} \in \mathbb{R}^+$ controls the temporal decay rate of this excitation and $\Delta\tau_j = t_i - t_j$ is the time elapsed since post j. The learned ϵ and β matrices reveal interpretable patterns of how different mental health indicators influence each other temporally.



Figure 1: MHRoBERT architecture for MoC prediction. Posts are encoded with BERT and processed through an LSTM to capture sequential context. An LLM annotates posts with emotion, life event, and symptom labels. The final representation concatenates three components: (1) a residual connection from the current post's LSTM state, (2) a unistream representation aggregating all LSTM states via HEAT, and (3) a multistream representation where HEAT pools LSTM states masked by their stream labels. This combined representation predicts whether a given post indicates a MoC.

Unistream HEAT Representation In addition to the multistream representation, we compute a unistream HEAT aggregation over all posts, regardless of stream assignment. This uses a Markovian emphasis (Hills et al., 2024) that weights recent context more heavily:

$$H_{\text{uni}}^{(i)} = h^{(i-1)} + \sum_{j<i} h^{(j)} \cdot \epsilon_{\text{uni}} \cdot e^{-\beta_{\text{uni}}\Delta\tau_j} \quad (3)$$

where ϵ_{uni} and β_{uni} are separate learnable parameters which aggregate historical representations regardless of stream labels, in the unistream fashion.

Combined Representation The final representation concatenates three components:

$$\mathbf{r}^{(i)} = [H_{\text{multi}}^{(i,1)}; H_{\text{multi}}^{(i,2)}; H_{\text{multi}}^{(i,3)}; H_{\text{uni}}^{(i)}; h^{(i)}] \quad (4)$$

where the semicolon denotes concatenation. This design captures: (a) Stream-specific temporal patterns (multistream HEAT); (b) General temporal dynamics (unistream HEAT); (c) Direct sequential information (residual LSTM connection) (See Fig. 1). The concatenated representation is scaled with $\tanh$ activation and passed through a linear classifier:

$$\hat{y}^{(i)} = \text{softmax}(W_{\text{out}} \cdot \tanh(\mathbf{r}^{(i)}) + b_{\text{out}}) \quad (5)$$

4 Experiments

Dataset and Preprocessing We make use of the Reddit dataset introduced in Tsakalidis et al. (2022a), containing longitudinal social media timelines labelled for Moments of Change (MoC). The dataset comprises 186 users across 255 timelines and 6,195 posts, with a median of 18 posts per timeline and a median inter-post gap of 22.72 hours (Hills et al., 2024). Given a historical sequence of posts, the task is to identify whether a post denotes a Switch (S), an Escalation (E), or Neither (O). Posts were annotated by four annotators following the scheme of Tsakalidis et al. (2022b), with final labels determined by majority vote; inter-annotator agreement, measured via Intersection over Union, was 0.264 (S), 0.309 (E), and 0.832 (O) (Tsakalidis et al., 2022a). The dataset is highly imbalanced, with Switch (S: 6.6%) and Escalation (E: 15.8%) events representing a small minority compared to No Change posts (O: 77.6%), motivating our use of macro-averaged F1 as the primary evaluation metric and focal loss during training. Training and implementation details are described in Section C.

Model Configuration We implement and evaluate three variants of hierarchical architectures:
RoBERT: "Recurrence over BERT". Baseline with BERT encoding and LSTM sequential modeling, without temporal aggregation layers. The classifier operates directly on LSTM hidden states.
HoRoBERT: "HEAT over Recurrence over BERT". Hierarchical model with a single Markovian HEAT layer (Hills et al., 2024). This applies temporal aggregation over all LSTM hidden states using learnable ϵ and β parameters, with emphasis on recent context through Markovian weighting.
MHRoBERT: "Multistream HEAT over Recurrence over BERT". Our proposed multistream architecture that extends HoRoBERT with three key components (See Fig. 1):

- *Multistream HEAT*: Stream-specific temporal aggregations with cross-stream excitation matrices $\epsilon_{(l,m)}$ and $\beta_{(l,m)}$ and per-stream baseline intensities μ_l

- *Unistream HEAT*: A Markovian HEAT layer aggregating all posts regardless of stream labels, using independent parameters ϵ_{uni} and β_{uni}
- *Residual connection*: Direct access to the current post's LSTM hidden state

The final representation concatenates all three components before classification, enabling the model to leverage both stream-specific interactions and general temporal patterns.

Central to our architecture is HEAT (Historical Emotional AggregaTion) (Sawhney et al., 2021a; Hills et al., 2024), which produces a temporally-weighted aggregation of historical LSTM hidden states using two learnable parameters: self-excitation $\epsilon \in \mathbb{R}^+$, controlling how strongly past posts amplify the current representation, and decay $\beta \in \mathbb{R}^+$, governing how quickly that influence diminishes with elapsed time $\Delta\tau_j = t_i - t_j$:

$$H^{(i)} = h^{(i-1)} + \sum_{j<i} h^{(j)} \cdot \epsilon \cdot e^{-\beta \Delta\tau_j} \quad (6)$$

MHRoBERT extends this to the multistream setting with stream-specific and cross-stream $\epsilon_{(l,m)}$, $\beta_{(l,m)}$ parameters (Section 3.2). In the fine-tuned setting, all BERT parameters are updated end-to-end; in the frozen setting only the LSTM and subsequent layers are trained. Multi-task variants add an auxiliary head predicting stream labels from the same shared representation.

4.1 LLMs for Moments of Change (MoC) Detection

We compared the performance of our specialized models developed for temporal modelling with LLMs applied in a zero-shot setting. To assess the capabilities of LLM models for automatic Moments of Change (MoC) detection in longitudinal data, we utilised a 32-billion parameter instruction-tuned model **Qwen2.5-32B-Instruct** (Reategui-Rivera et al., 2025; Nie et al., 2024). Evaluation was performed on **Reddit** data, through prompting-based inference under two settings:

(a) QwenLLM: In this setting, the model was prompted to classify each post within a user's timeline as one of S (Switch), E (Escalation), or O (None), depending on the past posts as context. Each post was evaluated independently, given only the past textual history of the user's posts.

(b) QwenLLMMultistream: The QwenLLM-Multistream prompting gives the model richer contextual signals that mimic a structured psychological assessment framework. The model used parallel cues pertaining to fine-grained emotions, mental health symptoms and personal life events to identify transitions (S), intensification (E), or stability (O) in the user's emotional trajectory. See Appendix B for the complete prompt templates and configuration details for both LLM models.

5 Results

Table 1 shows the performance of different architectures for predicting Moments of Change in mood. When fine-tuning BERT, HoRoBERT achieves the best overall macro-averaged F1 score (0.694), with MHRoBERT achieving competitive performance (0.689). All three hierarchical architectures demonstrate strong performance when BERT is fine-tuned end-to-end.

5.1 Model Performance Across Settings

The **fine-tuned BERT** setting yields the strongest results overall. HoRoBERT shows particular strength in recall (0.718) and achieves the best F1 for Switches (0.531) and Escalations (0.638). MHRoBERT achieves the highest precision (0.689) and performs well on Switches (F1 = 0.515), though slightly behind HoRoBERT. The baseline RoBERT (LSTM without temporal modeling) also demonstrates competitive performance (macro F1 = 0.685), suggesting that sequential modeling with fine-tuned representations captures substantial signal for Moments of Change detection.

With **frozen BERT**, all models show reduced performance (macro F1 = 0.600–0.609), as expected when linguistic representations cannot adapt to the task. However, the **multi-task learning** setting, which also uses frozen BERT but incorporates auxiliary tasks predicting stream-specific labels (emotions, life events, symptoms), achieves remarkably competitive performance (macro F1 = 0.673–0.674). This represents only a 2% drop compared to fine-tuned BERT, despite using fixed representations. This demonstrates that **multistream auxiliary supervision provides substantial benefits**, effectively compensating for the lack of linguistic fine-tuning by encouraging the model to learn representations sensitive to multiple aspects of mental health.

Under multi-task learning, MHRoBERT achieves the best Switch detection (F1 = 0.514), while all three models show strong and balanced performance. The consistently high performance across all three architectures in this setting

Model	Macro-Avg			Switch (S)			Escalation (E)			No Change (O)		
	P	R	F1	P	R	F1	P	R	F1	P	R	F1
Fine-tuned BERT												
MHRoBERT	**.689**	.696	.689	**.551**	.485	.515	**.579**	.697	.632	.936	**.906**	**.921**
HoRoBERT	.680	**.718**	**.694**	.532	**.531**	**.531**	.564	**.738**	**.638**	**.944**	.886	.913
RoBERT	.675	.700	.685	.516	.512	.514	.572	.685	.623	.937	.901	.918
Single-task (Frozen BERT)												
MHRoBERT	.567	.703	.600	.293	**.639**	.402	.449	.712	.551	.958	.759	.847
HoRoBERT	.574	**.713**	.607	**.310**	.629	**.414**	.446	**.760**	**.562**	**.967**	.752	.846
RoBERT	**.575**	.703	**.609**	.307	.616	.408	**.462**	.717	.561	.958	**.776**	**.857**
Multi-task (Frozen BERT)												
MHRoBERT	.689	.662	**.674**	.559	**.476**	**.514**	.599	.586	.592	.909	.923	.916
HoRoBERT	.688	**.663**	**.674**	.533	.467	.497	**.620**	.595	.606	.911	**.927**	**.919**
RoBERT	**.696**	.660	.673	**.585**	.432	.496	.590	**.628**	**.608**	**.913**	.919	.917
LLM Baselines												
QwenLLM	.447	.496	.427	.119	.496	.192	.343	.357	.350	.879	.636	.738
QwenLLMMultistream	**.517**	**.570**	**.481**	**.141**	**.650**	**.232**	**.468**	**.367**	**.411**	**.941**	**.694**	**.799**

Table 1: Per-class and macro-averaged results, for predicting MoCs. For each metric, **bold** denotes the best score within that experimental condition, while **bold+underline** denotes the best score across all conditions. P = Precision, R = Recall, F1 = F1-score.

underlines that the benefit is driven by the auxiliary supervision signal itself rather than by any particular model design. However, it is worth noting, that macro-averaged F1 masks important precision-recall tradeoffs: in clinical monitoring contexts, high recall for Switch events may be preferable, as a missed sudden mood change could signal an undetected emerging crisis whereas false alarms can be filtered by a human reviewer, favouring settings such as single-task frozen BERT (Switch recall: 0.639) over the multi-task variant (0.476) despite the latter's higher F1.

5.2 Benefits of Multistream Information

A key finding of this work is that automatically-generated multistream labels – derived via LLM annotation inspired by the taxonomy of Mao et al. (2025) – **improve performance across different model architectures**, including those not explicitly designed to handle this information. The LLM results provide compelling evidence: while the baseline QwenLLM achieves only 0.427 macro F1, incorporating multistream information in prompts (QwenLLMMultistream) improves performance to 0.481 (12.6% relative improvement). This improvement is particularly notable for rare classes, with Switch recall improving from 0.496 to 0.650.

These results highlight the value of multistream supervision beyond any specific architecture. The stream labels provide a consistent benefit whether the model explicitly models stream interactions (MHRoBERT), uses them as auxiliary supervision (multi-task setting), or incorporates them in prompts (LLMs). These findings have direct relevance for the CLPsych shared task on Moments of Change detection: across all architectures evaluated on the Reddit dataset used in that shared task, models trained with multistream auxiliary supervision consistently and substantially outperform their single-task counterparts. We therefore recommend that future CLPsych submissions for MoC detection explore multistream auxiliary supervision as a practical and scalable strategy for improving performance.

Furthermore, the multistream framework enhances model **interpretability at multiple levels**. At the data level, individual posts can be inspected for their stream-specific labels, allowing clinicians or researchers to understand which aspects of mental health (emotions, life events, symptoms) are present in the discourse.

At the model level, architectures like MHRoBERT produce interpretable learned parameters (Section 5.5) that reveal how different streams interact temporally. Even for models without explicit multistream architectures, the presence of stream labels enables more transparent analysis – practitioners can examine not just whether a mood change was predicted, but which combination of emotional expressions, life circumstances, and symptom mentions contributed to that prediction. This interpretability is particularly valuable in

mental health applications where understanding the reasoning behind predictions is as important as prediction accuracy itself.

5.3 Comparison of Temporal Modeling Approaches

The improvements from adding temporal HEAT layers (HoRoBERT) or multistream HEAT (MHRoBERT) over the LSTM baseline (RoBERT) in the fine-tuned setting suggest several considerations. The strong performance of RoBERT indicates that sequential modeling with fine-tuned BERT embeddings captures much of the relevant temporal structure. While MHRoBERT's multistream architecture provides interpretable cross-stream interaction parameters (Section 5.5), the performance gains over simpler approaches are modest in the fine-tuned setting. However, the architecture's ability to leverage multistream information proves particularly valuable in the multi-task setting, where it achieves the best Switch detection. This suggests that explicit multistream modeling becomes more beneficial when combined with auxiliary supervision that encourages learning stream-specific patterns.

5.4 Analysis of Model Components

The results demonstrate that both the unistream temporal component (HoRoBERT) and residual LSTM representations (present in all models) contribute meaningfully to performance. HoRoBERT consistently achieves high recall on rare events, suggesting that the unistream HEAT component effectively captures temporal patterns associated with mood changes. MHRoBERT's additional multistream HEAT component provides interpretable interaction parameters while maintaining competitive performance across all settings.

The importance of end-to-end BERT fine-tuning is evident, with fine-tuned models substantially outperforming frozen BERT variants in single-task learning. However, the multi-task results reveal that **multistream auxiliary supervision can largely bridge this gap**, achieving near-equivalent performance with frozen representations. This finding has practical implications, as it enables effective mood change detection without expensive fine-tuning, making the approach more accessible for resource-constrained applications or domains where labeled data for fine-tuning is limited.

5.5 Stream Interaction Analysis

The resulting model produces interpretable parameters, including excitation (ϵ) and decay (β) matrices, along with baseline intensities (μ), which provide insights into the temporal relationships between streams. These relationships are visualized in Figure 2.

Our multistream approach demonstrates several advantages over the baseline approaches. The integration of emotional states, life events, and symptoms provides a more comprehensive view of mental health changes, with the learned interaction parameters (Figure 2) offering insights into temporal dynamics between streams.

The **excitation patterns** reveal differential influences between streams. Emotions exhibit the highest self-excitation ($\epsilon = 0.01$), suggesting emotional states tend to reinforce themselves. Cross-stream excitation from emotions to symptoms ($\epsilon = 0.009$) is notably strong, indicating that emotional states may influence symptom manifestation. Life events show more balanced excitation across streams ($\epsilon = 0.004$–0.006), while symptoms demonstrate weaker cross-stream influence overall ($\epsilon = 0.002$–0.004).

The **decay rates** (β) show interesting temporal patterns. Emotions display very slow self-decay ($\beta = 0.0002$), suggesting persistence of emotional states, while their cross-stream decay is faster ($\beta = 0.004$–0.007). Life events exhibit consistently fast decay across all streams ($\beta = 0.01$–0.009), potentially reflecting their more transient nature. The decay from emotions to symptoms is relatively slow ($\beta = 0.001$), which may indicate lasting emotional influence on symptoms.

The **baseline intensities** show positive values for emotions ($\mu = 0.0062$) and symptoms ($\mu = 0.0056$), with life events near zero ($\mu = -0.00093$). This pattern suggests that while emotional and symptom streams maintain some baseline activity, life events are primarily driven by external occurrences rather than intrinsic baseline patterns. These learned parameters provide a foundation for understanding how different aspects of mental health interact temporally, though further investigation would be valuable to validate these patterns against clinical observations.

5.6 Stream Interpretability Analysis

The decomposition of the multistream HEAT component of MHRoBERT provides key interpretabil-



Figure 2: Learned interaction parameters showing excitation (ϵ) and decay (β) values between different streams, where higher values indicate stronger relationships. Learned baseline intensities (μ) for each individual stream are presented, where higher values indicate stronger contribution to the associated stream representations - regardless of event occurrence.

ity insights. As shown in Figure 3, the *Emotion* stream contributes the largest share of multistream attribution ($\sim 41\%$), followed by *Symptom* ($\sim 39\%$) and *Life Event* ($\sim 19\%$). This ordering, consistent across classes, indicates a coherent internal structure within multistream HEAT.



Figure 3: Class wise multistream attribution with multistream HEAT component (fine-tuned MHRoBERT).

Table 2 summarizes the representational geometry results using Nearest-Centroid (global) and k-Nearest Neighbors (local) evaluations. The unistream space exhibits stronger class separability and contributes more to gradient attributions, whereas the multistream space, though less discriminative, remains semantically informative. Its lower F1 reflects an expected entanglement of cross-stream embeddings that jointly encode emotional, symptomatic, and life-event cues.

While this representation is less separable, it captures richer inter-stream relationships, enhancing interpretability and potential transferability. In contrast, the unistream representation emphasizes temporal discrimination, producing distinct clusters aligned with mental state transitions. Together, these complementary inductive biases suggest that multistream HEAT prioritizes semantic alignment and interpretability, while unistream HEAT maintains geometric clarity and predictive precision as reflected in the fused stream results.

Method	UHEAT	MHEAT	Fused
Nearest-Centroid (cosine)			
Macro-F1	0.4413	0.3368	**0.4493**
Precision	0.4388	0.3812	0.4388
Recall	0.5091	0.4229	0.5091
k-NN (k=5, cosine)			
Macro-F1	0.4032	0.3882	**0.4057**
Precision	0.3961	0.3994	0.4014
Recall	0.4106	0.3907	0.4106

Table 2: Representation geometry analysis.

5.7 Future Research Directions

This work opens several promising avenues for future research in automated mental health monitoring and detecting changes more generally, by considering multiple interrelated temporal streams of data. In terms of stream extraction, more sophisticated prompt engineering techniques could improve the quality and reliability of automated annotations. Integration with external clinical knowledge bases could provide more psychologically validated stream categories, while systematic comparison with expert human annotation would help validate the LLM-based approach.

The modeling framework itself could be extended in several ways. Incorporating more advanced, fine-tuned linguistic representations could better capture the nuances of mental health-related language. Additional streams, such as social interaction patterns or environmental factors, could provide even more comprehensive monitoring capabilities. The temporal modeling could be enhanced to capture more complex dynamics, including seasonal patterns and long-term trends.

From a clinical application perspective, this lays the groundwork for developing and improving existing mental health monitoring frameworks. The

interpretable nature of the stream interactions could help clinicians understand the progression of mental health states over time, particularly by highlighting which combinations of emotional, behavioral, and life event patterns most strongly indicate impending changes in mental health.

6 Conclusion

This paper has demonstrated the value of multistream supervision for mental health monitoring, leveraging LLM-annotated emotional states, personal life events, and mental health symptoms as auxiliary signals, inspired by the taxonomy of Mao et al. (2025). Building on this, we introduced MHRoBERT, a novel hierarchical architecture that integrates stream-specific temporal interactions, general temporal dynamics, and direct sequential information through a unified representation. Its interpretable learned parameters (ϵ, β, μ) reveal interaction patterns between mental health indicators with potential clinical value. Crucially, our empirical results show that multistream auxiliary supervision benefits diverse architectures, establishing it as a practical, architecture-agnostic strategy for improving MoC detection.

A particularly important finding is that multistream auxiliary supervision provides consistent and substantial benefits across all evaluated architectures on the Reddit dataset from the CLPsych 2022 shared task on Moments of Change detection, while also being architecture-agnostic, scalable, and demonstrably effective.

Future work could focus on validating and refining stream annotations through clinical evaluation, exploring additional streams such as social interaction patterns or environmental factors, and investigating temporal modelling approaches that more explicitly account for time intervals in training. These directions could lead to more reliable systems for monitoring mental health through social media, supporting better understanding and outcomes for individuals experiencing mental health difficulties.

Limitations

While this work demonstrates the potential of multistream temporal modelling for mental health monitoring, several important limitations should be acknowledged.

Performance Gains The performance improvements of MHRoBERT over simpler baselines are relatively modest in the fine-tuned setting, with macro F1 scores differing by only a few percentage points. While the multistream information provides interpretable cross-stream interaction parameters and shows stronger benefits in multi-task learning scenarios, the gains over the LSTM baseline (RoBERT) in single-task fine-tuned settings are limited. Additionally, fine-tuned BERT with multi-task learning exhibited gradient instability during training (NaN gradients in a substantial proportion of Reddit batches), which we attribute to the interaction between the multi-task loss and BERT's deeper layers; stabilising this setting is left to future work.

Stream Annotation Quality The multistream annotations are generated automatically using LLMs without human validation, which introduces potential noise and inconsistencies. While LLMs have shown promise for annotation tasks (Gilardi et al., 2023; Törnberg, 2023), they can struggle with implicit or ambiguous content (Li and Conrad, 2024) and show significant variability across tasks (Kristensen-McLachlan et al., 2023). In mental health contexts, where subtle distinctions have significant clinical implications, the lack of expert validation of our automatically generated stream labels represents a notable limitation. The three-stream taxonomy (emotions, life events, symptoms), while grounded in psychological frameworks, has not been validated by mental health professionals for this specific application. Despite the noisy imperfect annotations, we still demonstrate several benefits for making use of such annotations in this paper.

Furthermore, while greedy decoding (temperature $= 0.0$, `do_sample=False`) ensures deterministic and reproducible annotations, prompt sensitivity was not systematically evaluated, the conceptual boundaries between streams are not always clear-cut (e.g., *Depressed* and *Detachment* may reflect overlapping psychological states), and whether results generalise to annotations from other LLMs beyond Qwen 2.5-32B-Instruct (Mao et al., 2025) remains an open question for future work.

Temporal Modeling Assumptions The HEAT mechanism assumes that temporal influence decays exponentially over time, which may not accurately reflect all psychological processes. Mental health trajectories can involve complex patterns including seasonality, and long-term trends that may not be well-captured by exponential decay functions. The current implementation uses learned static baseline

intensities, whereas more sophisticated approaches might benefit from dynamic, context-dependent baselines that adapt to individual users' temporal patterns.

Clinical Validity and Deployment This work has not been validated in clinical settings or with mental health professionals. The interpretable parameters produced by MHRoBERT (excitation and decay matrices) require clinical evaluation to determine whether they align with established understanding of mental health dynamics. Furthermore, deploying such systems for real-world mental health monitoring raises critical concerns about false positives/ negatives, privacy, informed consent, and the potential for harm if predictions are acted upon without appropriate clinical oversight. The models are intended as research tools to understand mental health patterns in social media data, not as diagnostic or intervention tools.

Computational Requirements The hierarchical architecture with end-to-end BERT fine-tuning requires substantial computational resources, which may limit accessibility for researchers or organizations with limited infrastructure. While the multi-task frozen BERT setting offers a more resource-efficient alternative, it still requires significant compute for training on longitudinal data.

Ethical Considerations Automated monitoring of mental health through social media raises important ethical questions about privacy, consent, and appropriate use of such systems. While this work uses publicly available Reddit data with institutional review board approval, the ability to identify mood changes from user posts could potentially be misused for surveillance or discrimination. Users posting on public forums may not anticipate or consent to their content being analyzed for mental health indicators.

Acknowledgments

This work was supported by a UKRI/EPSRC Turing AI Fellowship to Maria Liakata (grant EP/V030302/1), Keystone grant funding from Responsible AI UK (grants EP/Y009800/1 and KP0016), the Alan Turing Institute (grant EP/N510129/1), and an MRC grant (grant MR/X030725/1).

Ethics Statement

Before starting this research, approval was secured from the Institutional Review Board of the lead university. This study considers ethical considerations when dealing with the analysis of user-generated content on social media platforms, specifically Reddit. The ethical implications of our research, in particular the ability to identify changes in mood within user timelines, share similar concerns to that of prior research focused on identifying personal events through social media, and recognizing signs of suicidal thoughts. To help mitigate these risks, measures were taken such as the limited and regulated access to the developed software and the annotations that were used in this study.

References

Mostafa M. Amin, Erik Cambria, and Björn W. Schuller. 2023. Will affective computing emerge from foundation models and general artificial intelligence? a first evaluation of chatgpt. *IEEE Intelligent Systems*, 38(2):15–23.

Eliseo Bao, Anxo Pérez, and Javier Parapar. 2024. Explainable depression symptom detection in social media. *Health Information Science and Systems*, 12(1):47.

Denny Borsboom. 2017. A network theory of mental disorders. *World psychiatry*, 16(1):5–13.

Denny Borsboom and Angélique OJ Cramer. 2013. Network analysis: an integrative approach to the structure of psychopathology. *Annual review of clinical psychology*, 9(1):91–121.

Laura F Bringmann, Nathalie Vissers, Marieke Wichers, Nicole Geschwind, Peter Kuppens, Frenk Peeters, Denny Borsboom, and Francis Tuerlinckx. 2013. A network approach to psychopathology: New insights into clinical longitudinal data. *PloS one*, 8(4):e60188.

Ruijun Chen, Jin Wang, Liang-Chih Yu, and Xuejie Zhang. 2023. Learning to memorize entailment and discourse relations for persona-consistent dialogues. In *Proceedings of the AAAI conference on artificial intelligence*, volume 37, pages 12653–12661.

Muskan Garg. 2023. Mental health analysis in social media posts: A survey: M. garg. *Archives of Computational Methods in Engineering*, 30(3):1819–1842.

Fabrizio Gilardi, Meysam Alizadeh, and Maël Kubli. 2023. Chatgpt outperforms crowd workers for text-annotation tasks. *Proceedings of the National Academy of Sciences*, 120(30):e2305016120.

Oliver L. Haimson, Albert J. Carter, Shanley Corvite, Brookelyn Wheeler, Lingbo Wang, Tianxiao Liu, and Alexxus Lige. 2021. The major life events taxonomy: Social readjustment, social media information sharing, and online network separation during times of life transition. *Journal of the Association for Information Science and Technology*, 72(7):933–947.

Alan G Hawkes. 1971. Point spectra of some mutually exciting point processes. *Journal of the Royal Statistical Society: Series B (Methodological)*, 33(3):438–443.

Anthony Hills, Talia Tseriotou, Xenia Miscouridou, Adam Tsakalidis, and Maria Liakata. 2024. Exciting mood changes: A time-aware hierarchical transformer for change detection modelling. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 12526–12537, Bangkok, Thailand. Association for Computational Linguistics.

Ross Deans Kristensen-McLachlan, Miceal Canavan, Márton Kardos, Mia Jacobsen, and Lene Aarøe. 2023. Chatbots are not reliable text annotators. *arXiv preprint arXiv:2311.05769*.

Jin Myung Kwak, Minseon Kim, and Sung Ju Hwang. 2023. Context-dependent instruction tuning for dialogue response generation.

Mao Li and Frederick Conrad. 2024. Advancing annotation of stance in social media posts: A comparative analysis of large language models and crowd sourcing. *arXiv preprint arXiv:2406.07483*.

Yucheng Li, Bo Dong, Chenghua Lin, and Frank Guerin. 2023. Compressing context to enhance inference efficiency of large language models.

Chandreen Liyanage, Muskan Garg, Vijay Mago, and Sunghwan Sohn. 2023. Augmenting Reddit posts to determine wellness dimensions impacting mental health. In *The 22nd Workshop on Biomedical Natural Language Processing and BioNLP Shared Tasks*, pages 306–312, Toronto, Canada. Association for Computational Linguistics.

Junyu Mao, Anthony Hills, Talia Tseriotou, Maria Liakata, Aya Shamir, Dan Sayda, Dana Atzil-Slonim, Natalie Djohari, Arpan Mandal, Silke Roth, et al. 2025. Automated data enrichment using confidence-aware fine-grained debate among open-source LLMs for mental health and online safety. *arXiv preprint arXiv:2512.06227*.

Yu Meng, Jiaxin Huang, Yu Zhang, and Jiawei Han. 2022. Generating training data with language models: Towards zero-shot language understanding. In *Advances in Neural Information Processing Systems*, volume 35, page 462–477.

Virginia Morini, Salvatore Citraro, Elena Sajno, Maria Sansoni, Giuseppe Riva, Massimo Stella, and Giulio Rossetti. 2025. Online posting effects: Unveiling the non-linear journeys of users in depression communities on reddit. *Computers in Human Behavior Reports*, 17:100542.

Jingping Nie, Hanya Shao, Yuang Fan, Qijia Shao, Haoxuan You, Matthias Preindl, and Xiaofan Jiang. 2024. Llm-based conversational ai therapist for daily functioning screening and psychotherapeutic intervention via everyday smart devices. *arXiv preprint arXiv:2403.10779*.

Albert Park and Mike Conway. 2017. Longitudinal changes in psychological states in online health community members: Understanding the long-term effects of participating in an online depression community. *Journal of Medical Internet Research*, 19:e71.

C Mahony Reategui-Rivera, Aref Smiley, and Joseph Finkelstein. 2025. Llm-based chatbot to reduce mental illness stigma in healthcare providers. In *2025 IEEE 15th Annual Computing and Communication Workshop and Conference (CCWC)*, pages 00001–00007. IEEE.

Marian-Andrei Rizoiu, Young Lee, Swapnil Mishra, and Lexing Xie. 2017. Hawkes processes for events in social media. In *Frontiers of multimedia research*, pages 191–218.

Ramit Sawhney, Shivam Agarwal, Arnav Wadhwa, and Rajiv Shah. 2021a. Exploring the Scale-Free Nature of Stock Markets: Hyperbolic Graph Learning for Algorithmic Trading. In *Proceedings of the Web Conference 2021*, pages 11–22, Ljubljana Slovenia. ACM.

Ramit Sawhney, Harshit Joshi, Rajiv Ratn Shah, and Lucie Flek. 2021b. Suicide Ideation Detection via Social and Temporal User Representations using Hyperbolic Learning. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 2176–2190, Online. Association for Computational Linguistics.

Dana Atzil Slonim. 2024. Self-other dynamics (sod): A transtheoretical coding manual.

Jiayu Song, Jenny Chim, Adam Tsakalidis, Julia Ive, Dana Atzil-Slonim, and Maria Liakata. 2024. Combining hierachical VAEs with LLMs for clinically meaningful timeline summarisation in social media. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 14651–14672, Bangkok, Thailand. Association for Computational Linguistics.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022a. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Adam Tsakalidis, Federico Nanni, Anthony Hills, Jenny Chim, Jiayu Song, and Maria Liakata. 2022b. Identifying moments of change from longitudinal user text. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 4647–4660, Dublin, Ireland. Association for Computational Linguistics.

Yu-Min Tseng, Wei-Lin Chen, Chung-Chi Chen, and Hsin-Hsi Chen. 2025. Evaluating large language models as expert annotators. *arXiv preprint arXiv:2508.07827*.

Talia Tseriotou, Jenny Chim, Ayal Klein, Aya Shamir, Guy Dvir, Iqra Ali, Cian Kennedy, Guneet Singh Kohli, Anthony Hills, Ayah Zirikly, Dana Atzil-Slonim, and Maria Liakata. 2025. Overview of the CLPsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 193–217, Albuquerque, New Mexico. Association for Computational Linguistics.

Talia Tseriotou, Adam Tsakalidis, Peter Foster, Terence Lyons, and Maria Liakata. 2023. Sequential path signature networks for personalised longitudinal language modeling. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 5016–5031, Toronto, Canada. Association for Computational Linguistics.

Talia Tseriotou, Adam Tsakalidis, and Maria Liakata. 2024. TempoFormer: A transformer for temporally-aware representations in change detection. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 19635–19653, Miami, Florida, USA. Association for Computational Linguistics.

Petter Törnberg. 2023. Chatgpt-4 outperforms experts and crowd workers in annotating political twitter messages with zero-shot learning. *arXiv preprint arXiv:2304.06588*.

Hongru Wang, Rui Wang, Fei Mi, Yang Deng, Zezhong Wang, Bin Liang, Ruifeng Xu, and Kam-Fai Wong. 2023. Cue-CoT: Chain-of-thought prompting for responding to in-depth dialogue questions with LLMs. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 12047–12064, Singapore. Association for Computational Linguistics.

Marieke Wichers, Claudia Lothmann, Claudia JP Simons, Nancy A Nicolson, and Frenk Peeters. 2012. The dynamic interplay between negative and positive emotions in daily life predicts response to treatment in depression: a momentary assessment study. *British Journal of Clinical Psychology*, 51(2):206–222.

Xuhai Xu, Bingsheng Yao, Yuanzhe Dong, Saadia Gabriel, Hong Yu, James Hendler, Marzyeh Ghassemi, Anind K. Dey, and Dakuo Wang. 2024. Mental-llm: Leveraging large language models for mental health prediction via online text data. *Proc. ACM Interact. Mob. Wearable Ubiquitous Technol.*, 8(1).

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, Junyang Lin, Kai Dang, Keming Lu, Keqin Bao, Kexin Yang, Le Yu, Mei Li, Mingfeng Xue, Pei Zhang, Qin Zhu, Rui Men, Runji Lin, Tianhao Li, Tianyi Tang, Tingyu Xia, Xingzhang Ren, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yu Wan, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, and Zihan Qiu. 2025. Qwen2.5 technical report.

Kailai Yang, Shaoxiong Ji, Tianlin Zhang, Qianqian Xie, Ziyan Kuang, and Sophia Ananiadou. 2023. Towards interpretable mental health analysis with large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics.

Amir Hossein Yazdavar, Mohammad Saeid Mahdavinejad, Goonmeet Bajaj, William Romine, Amit Sheth, Amir Hassan Monadjemi, Krishnaprasad Thirunarayan, John M Meddar, Annie Myers, Jyotishman Pathak, et al. 2020. Multimodal mental health analysis in social media. *Plos one*, 15(4):e0226248.

Qiang Zhang, Aldo Lipani, Omer Kirnap, and Emine Yilmaz. 2020. Self-attentive Hawkes process. In *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 11183–11193. PMLR.

Wen Zheng, Natasa Milic-Frayling, and Ke Zhou. 2023. Contextual knowledge learning for dialogue generation. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7822–7839, Toronto, Canada. Association for Computational Linguistics.

Ke Zhou, Hongyuan Zha, and Le Song. 2013. Learning triggering kernels for multi-dimensional hawkes processes. In *Proceedings of the 30th International Conference on Machine Learning*, volume 28 of *Proceedings of Machine Learning Research*, pages 1301–1309, Atlanta, Georgia, USA. PMLR.

A LLM Prompting Templates

We use chain-of-thought (CoT) prompting with Qwen 2.5-32B-Instruct to extract three streams of mental health-relevant information from social media posts. Below are the complete prompt templates used for each stream.

A.1 Model Configuration

We implement our automated stream annotation using Qwen 2.5-32B-Instruct with the following configuration:

- **Model**: Qwen 2.5-32B-Instruct
- **Quantization**: 4-bit quantization
- **Precision**: bfloat16
- **Decoding Strategy**: Greedy decoding (deterministic) with `do_sample=False`
- **Max New Tokens**: 1024 tokens
- **Temperature**: 0.0 (greedy decoding)

A.2 Emotional States Prompt

```
You are tasked with classifying the
    emotional content of a social media
    post.

Emotion Categories:
- Happy: Content, joyful, hopeful,
    excited, glad, cheerful
- Proud: Feeling accomplished,
    satisfied with achievements,
    confident in success
- Sad: Emotional pain, grieving, hurt,
    heartbroken over loss
- Anxious: Fearful, tense, worried,
    nervous, scared, panicked
- Depressed: Despair, hopeless,
    worthless, empty, suicidal thoughts
- Apathetic: Numb, indifferent, don't
    care, emotionally blunted
- Angry: Aggression, hate, rage,
    disgust, contempt
- Ashamed: Guilty, embarrassed,
    humiliated, self-critical
- Loneliness: Feeling alone, isolated,
    lacking meaningful connection
- None: The post does not clearly
    reflect any of the above emotion
    categories.

Instructions:
1. Based on the provided examples,
    analyze the post by evaluating each
    emotion category.
2. For each category, explain your
    reasoning and clearly state "yes"
    or "no" regarding its presence.
3. Finally, list all applicable emotion
    categories that are present in the
    post. If more than one applies,
    separate them with commas.

Below are some examples:
{few_shot_examples}

Post to Analyze:
Post:
"{post}"

Please strictly follow the output
    format exactly as shown below. Do
    not use bold, markdown, or extra
    formatting.

Output Format:
Explanation:
- Happy: [reason]. So the answer is yes
    (or is no).
- Proud: [reason]. So the answer is yes
    (or is no).
- Sad: [reason]. So the answer is yes
    (or is no).
- Anxious: [reason]. So the answer is
    yes (or is no).
- Depressed: [reason]. So the answer is
    yes (or is no).
- Apathetic: [reason]. So the answer is
    yes (or is no).
- Angry: [reason]. So the answer is yes
    (or is no).
- Ashamed: [reason]. So the answer is
    yes (or is no).
- Loneliness: [reason]. So the answer
    is yes (or is no).
- None: [reason]. So the answer is yes
    (or is no).

Answer:
Only output exact category names:
    Happy, Proud, Sad, Anxious,
    Depressed, Apathetic, Angry,
    Ashamed, Loneliness, or None. Use
    commas to separate multiple labels,
    if any.
```

A.3 Personal Life Events Prompt

```
You are provided with a social media
    post and must identify any personal
    life events based on the life event
    categories defined below.

Life events are experiences that have a
    major personal impact on an
    individual. They must involve a
    clearly identifiable occurrence or
    change. These events may have
    occurred in the past (explicitly
    stated, or inferred from context if
    the impact is clear), be occurring
    in the present (explicitly
    described or clearly implied), or
    be expected in the near future
    (only if explicitly stated).

- Mental Health:
Mental health life events cover
    discussions about receiving a
    formal mental health diagnosis;
    starting or adjusting psychiatric
    medication; beginning therapy;
    recovery or significant symptom
    improvement; or experiencing acute
    psychological episodes such as
    manic episodes, psychotic breaks,
    panic attacks, dissociative
    episodes, self-harm, suicide
    attempts, or acute suicidal
    ideation requiring crisis
    intervention. It does not include
    general low mood, stress, anxiety,
    or depression unless explicitly
    tied to one of these major events.
- Physical Health:
Physical health life events cover
    accidents; injuries; diagnoses or
    survival of serious illnesses;
    chronic conditions that have a
    notable impact on daily life; or
    cases where the individual or
    someone important to them has been
    hospitalized, undergone surgery,
    received emergency medical
    treatment, or experienced other
    major medical interventions.
    Pregnancy-related experiences,
    including becoming pregnant,
```

```
    pregnancy loss, abortion, or
    complications, are also included.
    Common aches, headaches, fatigue,
    or other symptoms without being
    part of a major physical health
    event are not included.
- Abuse & Addiction:
Covers major life events involving
    abuse or substance-related issues.
    Abuse may occur in childhood or
    adulthood and may take physical,
    sexual, emotional, psychological,
    or other forms. Addiction-related
    events include the onset of heavy
    drug or alcohol use; acknowledgment
    of addiction; overdoses; withdrawal
    symptoms; relapses; or recovery
    (including participation in
    treatment programs such as
    rehabilitation or support groups).
- Relationship & Loss:
Covers specific relationship changes or
    disruptions in meaningful personal
    connectionsfamily or non-familythat
    result in strong emotional impact.
    Includes beginning or ending
    friendships or romantic
    relationships; marriage or divorce;
    parental separation or divorce;
    serious arguments or conflicts;
    relationships becoming abusive or
    toxic; the addition of new family
    members (e.g., through birth or
    adoption); parenting difficulties;
    emotionally distressing health
    issues involving family members,
    partners, close friends, or other
    meaningful connections; or the
    death of a person or pet who was
    important to the individual.
- Career & Education:
Career-related life events cover
    starting or losing a job;
    promotions; demotions; troubles at
    work; being unable to find a job;
    retirement; or becoming a business
    owner. Education-related life
    events include starting or
    graduating from school;
    transferring schools; leaving
    school without graduating; being
    denied entry into school; taking
    major exams; experiencing
    significant academic challenges; or
    achieving major academic milestones
    (e.g., earning a certification).
- Financial & Legal & Societal:
Financial life events include major
    purchases (e.g., a house or car);
    financial gains or milestones
    (e.g., paying off debt); financial
    losses (e.g., stolen or damaged
    property); or ongoing financial
    difficulties. Legal life events
    include law violations; arrests;
    court appearances; lawsuits or
    legal actions; or major
    interactions with the justice
    system, whether the individual is
    subject to legal proceedings or
    initiating them. Societal life
    events with clear personal impact
    include natural disasters;
    pandemics; major political events;
    societal issues; or notable public
    encounters (e.g., meeting a
    celebrity).
- Lifestyle & Identity & Environment:
Covers major life events involving
    changes in lifestyle habits,
    personal identity, or living
    environment. Lifestyle changes
    include adopting new health- and
    well-being-related routines, such
    as adjustments in diet; exercise;
    sleep management; stress management
    (e.g., through meditation);
    reducing substance use; fostering
    positive social connections; or
    getting a pet. It does not include
    clinical treatment for mental
    health issues. Identity transitions
    include identifying or changing
    one's gender or sexual orientation
    (e.g., coming out as LGBTQ+);
    discussing a new sexual experience;
    or exploring, adopting, or changing
    political or religious beliefs
    (including changes in religious
    practices). Relocation life events
    include moving to a new place;
    moving in or out of the family
    home; family members moving into or
    out of the household; or
    significant travel experiences.
- None:
Applies when the post does not clearly
    reflect any of the above life event
    categories.

Instructions:
1. Read the post carefully and evaluate
    whether it matches each defined
    life event category.
2. For each life event category,
    explain your reasoning. If a
    category applies, support your
    answer with direct evidence from
    the post. If it does not apply,
    explain why there is insufficient
    or no evidence. Clearly state "yes"
    or "no" for each category.
3. Finally, list all broad life event
    categories that apply. If more than
    one applies, separate them with
    commas.

Below are some examples:
{few_shot_examples}

Post to Analyze:
Post:
"{post}"

Please strictly follow the output
    format exactly as shown below. Do
    not use bold, markdown, or extra
    formatting.

Output Format:
```

```
Explanation:
- Mental Health: [reason]. So the
    answer is yes (or is no).
- Physical Health: [reason]. So the
    answer is yes (or is no).
- Abuse & Addiction: [reason]. So the
    answer is yes (or is no).
- Relationship & Loss: [reason]. So the
    answer is yes (or is no).
- Career & Education: [reason]. So the
    answer is yes (or is no).
- Financial & Legal & Societal:
    [reason]. So the answer is yes (or
    is no).
- Lifestyle & Identity & Environment:
    [reason]. So the answer is yes (or
    is no).
- None: [reason]. So the answer is yes
    (or is no).

Answer:
Output exact category names: Mental
    Health, Physical Health, Abuse &
    Addiction, Relationship & Loss,
    Career & Education, Financial &
    Legal & Societal, Lifestyle &
    Identity & Environment, or None.
    Use commas to separate multiple
    labels, if any."""
```

A.4 Mental Health Symptoms Prompt

```
You are provided with a social media
    post and must identify any symptoms
    of mental health issues according
    to the symptom categories defined
    below.

Symptom Categories:
- Suicidal Thoughts:
Distinct from general distress, this
    involves specific thoughts about
    ending one's life, including
    considering methods, making plans,
    or expressing a desire to die. This
    includes passive thoughts ("I wish
    I wouldn't wake up") and active
    plans, as well as references to
    past suicide attempts.

- Somatoform & Substance Abuse:
Somatoform refers to physical symptoms
    that cause significant distress but
    lack clear medical explanations.
    This includes various types of pain
    (e.g., headaches, muscle aches);
    unexplained physical sensations;
    physical fatigue; and physical
    complaints affecting different body
    systems. They are often accompanied
    by cognitive symptoms such as
    impaired memory, reduced processing
    speed, and poor planning. Substance
    abuse covers problematic use of
    alcohol, drugs, or other
    substances. This includes excessive
    drinking or drug use; failed
    attempts to cut down; spending a
    disproportionate amount of time
    obtaining, using, or recovering
    from substances; and continued use
    despite negative consequences.

- Eating Pathology:
Includes problematic cognitions and
    behaviors related to food, eating
    patterns, body image, and weight.
    This includes fear of weight gain
    (e.g., frequent body-checking,
    obsessive weighing); body image
    disturbance (e.g., negative
    fixation on weight or shape);
    self-worth tied to appearance
    (e.g., harsh self-criticism,
    comparisons); denial of low weight;
    and guilt/shame around eating
    (e.g., anxiety about food,
    avoidance of eating situations).
    Other features include using food
    as emotional coping and obsessive
    focus on food, cooking, or
    weight-related content. Behavioral
    manifestations include restrictive
    eating (e.g., smaller portions,
    skipping meals, eliminating food
    groups, extreme diets, calorie
    counting); fasting to compensate;
    and chewing and spitting (chewing
    food without swallowing). Binge
    eating involves consuming
    abnormally large amounts of food
    with feelings of loss of control,
    eating rapidly or until
    uncomfortably full, eating alone
    due to embarrassment, and
    experiencing negative emotions
    afterward. Compensatory behaviors
    include self-induced vomiting,
    misuse of laxatives or diuretics,
    use of diet pills or "slimming
    teas," fasting as a non-purging
    compensatory behavior and excessive
    exercise (e.g., working out despite
    fatigue/injury, exercise
    interfering with daily
    functioning). Secretive eating
    behaviors, including concealing
    eating patterns or using coded
    terminology online, may also occur.

- Sexual:
Involves difficulties with sexual
    functioning and satisfaction. This
    includes problems with sexual
    desire, arousal, or performance;
    pain during sexual activity;
    distress related to sexual
    experiences; and addictive sexual
    behaviors that impair various other
    functions.

- Thought Disorder:
Relates to disruptions in perception,
    beliefs, and thought organization.
    This includes unusual sensory
    experiences (e.g., hearing voices);
    extreme and fixed, false beliefs;
    disorganized thinking or speech;
```

```
    and difficulty distinguishing
    between what is real and what is
    not.

- Antisocial and Antagonistic Behavior:
Refers to actions that violate societal
    norms and infringe upon the rights
    of others. This includes
    rule-breaking or illegal behavior,
    physical aggression, bullying,
    deceitfulness or theft, blame
    externalization, disregard for
    social norms or obligations, and
    property destruction. It also
    covers behaviors such as
    deliberately provoking or annoying
    others, attention-seeking,
    rudeness, manipulating others for
    personal gain, and other
    deliberately over-extroverted
    behaviors (physical or emotional).
    These behaviors may be accompanied
    by impulsivity, distractibility,
    and risk-taking.

- Detachment:
Characterized by withdrawal from social
    and emotional experiences. This
    includes avoidance of social
    interaction, limited emotional
    expression, lack of close
    relationships, reduced capacity to
    experience pleasure in activities
    (particularly in social contexts),
    and social isolation.

- None:
Applies when the post does not clearly
    reflect any of the above symptom
    categories.

Instructions:
1. Read the post carefully and evaluate
    whether it matches each defined
    symptom category.
2. For each category, explain your
    reasoning. If a category applies,
    support your answer with direct
    evidence from the post. If it does
    not apply, explain why there is
    insufficient or no evidence.
    Clearly state "yes" or "no" for
    each category.
3. Finally, list all applicable symptom
    categories that are present in the
    post. If more than one applies,
    separate them with commas.

Below are some examples:
{few_shot_examples}

Post to Analyze:
Post:
"{post}"

Please strictly follow the output
    format exactly as shown below. Do
    not use bold, markdown, or extra
    formatting.

Output Format:
Explanation:
- Suicidal Thoughts: [reason]. So the
    answer is yes (or is no).
- Somatoform & Substance Abuse:
    [reason]. So the answer is yes (or
    is no).
- Eating Pathology: [reason]. So the
    answer is yes (or is no).
- Sexual: [reason]. So the answer is
    yes (or is no).
- Thought Disorder: [reason]. So the
    answer is yes (or is no).
- Antisocial and Antagonistic Behavior:
    [reason]. So the answer is yes (or
    is no).
- Detachment: [reason]. So the answer
    is yes (or is no).
- None: [reason]. So the answer is yes
    (or is no).

Answer:
Output exact category names: Suicidal
    Thoughts, Somatoform & Substance
    Abuse, Eating Pathology, Sexual,
    Thought Disorder, Antisocial and
    Antagonistic Behavior, Detachment,
    or None. Use commas to separate
    multiple labels, if any."""
```

A.5 Chain-of-Thought Examples

To illustrate the reasoning process required by our prompts, we provide synthetic in context learning examples demonstrating the chain-of-thought approach. These examples are fictional and created for demonstration purposes to protect the privacy of the individuals in our dataset. The actual prompts used during annotation contained 5-10 similar examples per stream, all following the same structured reasoning format shown below. Each example demonstrates explicit evaluation of every category before producing a final classification.

A.5.1 Emotion Classification Example

```
Post:
"Finally submitted my thesis after
    months of work! Feeling accomplished
and ready for what's next."

Explanation:
- Happy: The post explicitly states
    "Feeling accomplished" which
    directly
  indicates pride and satisfaction. The
      forward-looking tone suggests
  hopefulness. So the answer is yes.
- Proud: While accomplishment is
    present, this aligns more with
    general
  happiness than specific pride in
      achievement. So the answer is no.
- Sad: The post expresses positive
    emotions with no grief or emotional
    pain.
```

```
  So the answer is no.
- Anxious: No fear, worry, or tension
    is expressed. So the answer is no.
- Depressed: The post conveys
    accomplishment and optimism,
    opposite to
  despair. So the answer is no.
- Apathetic: Clear emotional engagement
    is present, not numbness.
  So the answer is no.
- Angry: No aggression or anger is
    expressed. So the answer is no.
- Ashamed: The post expresses positive
    feelings, not guilt or
    embarrassment.
  So the answer is no.
- Loneliness: No isolation or lack of
    connection is mentioned.
  So the answer is no.
- None: Clear positive emotion is
    present. So the answer is no.

Answer:
Happy
```

A.5.2 Life Events Classification Example

```
Post:
"Started therapy last week and got
    prescribed medication for my
    anxiety.
Hoping this helps."

Explanation:
- Mental Health: The post explicitly
    mentions starting therapy and
    receiving
  psychiatric medication for anxiety,
      which are major mental health
      treatment
  events. So the answer is yes.
- Physical Health: No accidents,
    injuries, illnesses, or physical
    medical
  interventions are mentioned. So the
      answer is no.
- Abuse & Addiction: No mention of
    abuse or substance-related issues.
  So the answer is no.
- Relationship & Loss: No specific
    relationship changes are described.
  So the answer is no.
- Career & Education: No work or
    school-related events are mentioned.
  So the answer is no.
- Financial & Legal & Societal: No
    financial, legal, or societal events
  are discussed. So the answer is no.
- Lifestyle & Identity & Environment:
    The post focuses on clinical
  intervention rather than lifestyle
      modifications. So the answer is
      no.
- None: A clear mental health life
    event is present. So the answer is
    no.

Answer:
Mental Health
```

A.5.3 Symptoms Classification Example

```
Post:
"Constant headaches all week and
    exhausted no matter how much I
    sleep.
Also been drinking more than usual to
    cope."

Explanation:
- Suicidal Thoughts: No death wishes or
    suicidal ideation are expressed.
  So the answer is no.
- Somatoform & Substance Abuse: The
    post mentions "constant headaches"
    and
  chronic exhaustion (somatic symptoms)
      plus "drinking more than usual to
  cope" (substance use for emotional
      regulation). So the answer is yes.
- Eating Pathology: No eating, weight,
    or body image concerns are
    mentioned.
  So the answer is no.
- Sexual: No sexual symptoms are
    discussed. So the answer is no.
- Thought Disorder: The thinking is
    coherent with no perceptual
    disturbances.
  So the answer is no.
- Antisocial and Antagonistic Behavior:
    No rule-breaking or aggression is
  described. So the answer is no.
- Detachment: While fatigue is present,
    there's no indication of social
  withdrawal. So the answer is no.
- None: Clear symptoms are present. So
    the answer is no.

Answer:
Somatoform & Substance Abuse
```

B Baseline LLM Prompting Templates for Mood Change Detection

This section details the complete prompt templates and model configurations used for mood change detection (MoC) experiments with LLMs.

B.1 Model Configuration

For automatic mood change detection, we used the following configuration:

- **Model:** Qwen2.5-32B-Instruct
- **Quantization:** 4-bit (NF4)
- **Precision:** `bfloat16`
- **Decoding Strategy:** Greedy decoding (`do_sample=False`)
- **Attention Implementation:** Default (no custom optimization)

- **Tokenizer Padding:** Right-side padding with EOS token substitution
- **Hardware:** Single NVIDIA GPU with 4-bit quantized loading via BitsAndBytes
- **Max New Tokens:** 32
- **Temperature:** 0.0

B.2 Mood Change Detection Prompt (QwenLLM)

```
You are an expert assistant for
    identifying self-disclosed mood
    changes in user timelines on social
    media.

Your task is to classify the current
    post into exactly one of these
    three labels based on the context
    of previous posts:

- S (Switch): A sudden shift in mood
    direction (positive  negative)
    compared to prior posts.
- E (Escalation): A gradual or clear
    intensification of mood in the same
    direction.
- O (None): No significant mood change
    or mood remains neutral/consistent.

### Instructions:
- Read all previous posts in the
    timeline as context to understand
    the user's prior mood.
- Read the current post carefully.
- Determine if the current post
    represents a sudden mood switch
    (S), a gradual escalation (E), or
    no significant mood change (O).
- **Output only the label (S, E, or O)
    on a single line no extra text,
    explanation, or commentary**
- If there are **no previous posts**,
    assume the baseline mood is neutral.

Previous posts:
{prev_posts if prev_posts else "No
    previous posts"}

Current post:
{current_post}

Answer:
```

Listing 1: QwenLLM prompt template for timeline-based MoC classification.

B.3 Mood Change Detection (QwenLLMMultistream) Prompt

```
You are an assistant for identifying a
    user's self-disclosed mood changes
    over time.

Each post belongs to a timeline of user
    posts. Your task is to classify the
    current
post based on prior posts as one of the
    following:

- S (Switch): Sudden shift in mood
    direction (positive  negative)
- E (Escalation): Gradual or clear
    intensification of mood in the same
    direction
- O (None): No significant mood change
    or mood remains consistent

AUTOMATED MULTISTREAM LABEL CONTEXT:
Each post includes automated labels
    from three streams:

1. FINE-GRAINED EMOTION LABELS (12
    categories organized by
    adaptiveness):

   Positive Adaptive Emotions:
   - Happy: Content, joyful, hopeful,
       excited, glad, cheerful
   - Proud: Feeling accomplished,
       satisfied with achievements,
       confident in success
   - Calm: Peaceful, relaxed, serene,
       tranquil emotional states
   - Vigor: High energy, vitality,
       enthusiasm, active engagement
   - Feeling loved: Experiencing
       affection, care, or emotional
       support from others

   Negative Adaptive Emotions:
   - Sad: Emotional pain, grieving,
       hurt, heartbroken over loss
       (adaptive response to loss)
   - Justifiable anger: Appropriate
       anger in response to unfair
       treatment or injustice

   Negative Maladaptive Emotions:
   - Anxious: Fearful, tense, worried,
       nervous, scared, panicked
   - Depressed: Despair, hopeless,
       worthless, empty, suicidal
       thoughts
   - Apathetic: Numb, indifferent,
       don't care, emotionally blunted
   - Angry: Aggression, hate, rage,
       disgust, contempt (non-justified)
   - Ashamed: Guilty, embarrassed,
       humiliated, self-critical
   - Loneliness: Feeling alone,
       isolated, lacking meaningful
       connection


2. MENTAL HEALTH SYMPTOM LABELS (7
    categories):

   - Suicidal Thoughts: Specific
       thoughts about ending one's
       life, including considering
       methods, making plans,
       expressing desire to die,
       passive thoughts ("I wish I
```

wouldn't wake up"), active plans, references to past suicide attempts

- Somatoform & Substance Abuse: Physical symptoms causing significant distress without clear medical explanations (headaches, muscle aches, unexplained sensations, physical fatigue, cognitive symptoms like impaired memory/processing). Substance abuse includes problematic alcohol/drug use, failed attempts to cut down, excessive time obtaining/using/recovering from substances, continued use despite negative consequences

- Eating Pathology: Problematic food/eating behaviors and cognitions including fear of weight gain, body image disturbance, self-worth tied to appearance, guilt/shame around eating, using food as emotional coping, restrictive eating patterns, binge eating with loss of control, compensatory behaviors (vomiting, laxatives, excessive exercise), secretive eating behaviors

- Sexual: Difficulties with sexual functioning including problems with desire/arousal/performance, pain during sexual activity, distress related to sexual experiences, addictive sexual behaviors

- Thought Disorder: Disruptions in perception, beliefs, thought organization including unusual sensory experiences (hearing voices), extreme fixed false beliefs, disorganized thinking/speech, difficulty distinguishing reality

- Antisocial and Antagonistic Behavior: Actions violating societal norms and others' rights including rule-breaking, illegal behavior, physical aggression, bullying, deceitfulness, blame externalization, property destruction, deliberately provoking others, attention-seeking, rudeness, manipulation for personal gain

- Detachment: Withdrawal from social and emotional experiences including avoidance of social interaction, limited emotional expression, lack of close relationships, reduced capacity for pleasure (especially social contexts), social isolation

3. PERSONAL LIFE EVENT LABELS (7 categories):

- Mental Health: Receiving formal mental health diagnosis, starting/adjusting psychiatric medication, beginning therapy, recovery/significant symptom improvement, acute psychological episodes (manic episodes, psychotic breaks, panic attacks, dissociative episodes, self-harm, suicide attempts, acute suicidal ideation requiring crisis intervention)

- Physical Health: Accidents, injuries, diagnoses/survival of serious illnesses, chronic conditions with notable daily life impact, hospitalization, surgery, emergency medical treatment, major medical interventions, pregnancy-related experiences (becoming pregnant, pregnancy loss, abortion, complications)

- Abuse & Addiction: Major events involving abuse (physical, sexual, emotional, psychological) in childhood or adulthood; addiction-related events including onset of heavy drug/alcohol use, acknowledgment of addiction, overdoses, withdrawal symptoms, relapses, recovery (treatment programs, rehabilitation, support groups)

- Relationship & Loss: Specific relationship changes/disruptions in meaningful personal connections with strong emotional impact including beginning/ending friendships or romantic relationships, marriage/divorce, parental separation/divorce, serious arguments/conflicts, relationships becoming abusive/toxic, addition of new family members, parenting difficulties, emotionally distressing health issues involving family/partners/close friends, death of important person or pet

- Career & Education: Career events (starting/losing job, promotions, demotions, work troubles, unable to find job, retirement, becoming business owner); Education events (starting/graduating school,

```
        transferring schools, leaving
        without graduating, denied
        school entry, major exams,
        significant academic challenges,
        major academic milestones)

    - Financial & Legal & Societal:
        Financial events (major
        purchases like house/car,
        financial gains/milestones,
        financial losses, ongoing
        financial difficulties); Legal
        events (law violations, arrests,
        court appearances, lawsuits,
        major justice system
        interactions); Societal events
        with personal impact (natural
        disasters, pandemics, major
        political events, societal
        issues, notable public
        encounters)

    - Lifestyle & Identity &
        Environment: Lifestyle changes
        (adopting new health routines,
        diet/exercise/sleep/stress
        management adjustments, reducing
        substance use, fostering
        positive social connections,
        getting pet - not clinical
        mental health treatment);
        Identity transitions
        (gender/sexual orientation
        identification/changes, coming
        out as LGBTQ+, new sexual
        experiences,
        exploring/adopting/changing
        political/religious beliefs);
        Relocation events (moving to new
        place, moving in/out of family
        home, family members moving
        in/out of household, significant
        travel experiences)

INTERPRETATION GUIDELINES:
- Fine-grained emotions (especially
    transitions between
    Positive/Negative
    Adaptive/Maladaptive categories)
    are primary indicators of mood
    switches and escalations
- Life events often trigger mood
    changes - look for temporal
    relationships between events and
    emotional shifts
- Symptom patterns can indicate
    escalating mental health states or
    underlying mood deterioration
- Cross-stream interactions (e.g.,
    relationship loss + depressed
    emotion + detachment symptoms)
    provide rich context for mood
    trajectory assessment
- Labels are automated and noisy but
    provide valuable psychological
    state indicators for detecting mood
    changes over time

You will ONLY output one of the three
    labels: S, E, or O. No additional
    explanation.

Previous posts in timeline:
{prev_context if prev_context else "No
    previous posts."}

Current post to classify:
{current_formatted}

Classification:
```

Listing 2: QwenLLMMultistream Prompt template for multistream mood change detection (S, E, O).

C Training and Implementation

C.1 Infrastructure

All models (excluding LLMs) were implemented with PyTorch and trained on 2 NVIDIA A100-PCIE-40GB GPUs using Focal Loss to address class imbalance in labels of Moments of Change - for single-task models. LLM models were all implemented with 2 NVIDIA H100 GPUs.

Multi-task models used a combined loss of focal loss and binary cross entropy (BCE) loss, giving equal weighting to both losses and equal weighting to the 3 streams in the BCE loss. The optimization process used the Adam optimizer with gradient accumulation of 4 steps. Training was carried out with a maximum of 10 epochs, selecting the best model in terms of macro-average F1 score on a validation set using 5-fold cross validation. The hyperparameter search space is described in Table C.2.

C.2 Grid-search Used in Experimental Procedure

We train and evaluate all our models on 3 seeds, taking the average scores on the resulting test sets - aside from the LLM baselines which were evaluated with 1 seed. We evaluate on the same test set proposed in the CLPsych 2022 shared task for Reddit (Tsakalidis et al., 2022a). We performed a grid-search on over the enlisted hyperparameters – selecting the best performing model based on macro-average F1 score on the validation set, and optimizing the model using focal loss with a gamma of 2.0, training for 10 epochs, Learning rate: 0.00005, LSTM/ Transformer hidden dimension: 512, $\epsilon_{\text{prior}} = \beta_{\text{prior}} = 0.001$ for MHRoBERT and $\epsilon_{\text{prior}} = \beta_{\text{prior}} = 0.01$ for HoRoBERT, chunk size: 16, stride: 8.

On the Role of Context in LLM Alignment to Mental Health Counseling Competencies

Sadiya Sayara Chowdhury Puspo, Marcos Zampieri, Özlem Uzuner
George Mason University, VA, USA
spuspo@gmu.edu

Abstract

As Large Language Models (LLMs) demonstrate strong performance on clinical benchmarks, it remains unclear whether this reflects true patient-specific reasoning or reliance on generalized symptom patterns. To address this question, we evaluate LLMs on a counseling competency benchmark to assess their use of patient-specific contextual information. Through controlled experiments with contextual ablations, role framing, Thread-of-Thought (ThoT) prompting, and input perturbations, we find that removing contextual details results in only modest performance drops, and predictions remain relatively stable under input variations. Error analysis further reveals systematic patterns where models favor general clinical associations over context-specific cues, even when such cues are correctly identified during intermediate reasoning. Our findings suggest that achieving passing-level performance may not reflect robust context-sensitive decision-making, revealing a potential gap between benchmark-level clinical competence and reliable utilization of patient-specific contextual information. These results highlight the need for evaluation frameworks that more directly assess context integration in mental health applications.

1 Introduction

More than 1 billion people worldwide live with mental health disorders, according to recent data from the World Health Organization (WHO).[1] In the United States alone, one in five adults experience mental illness each year, as reported by SAMHSA[2]. At the same time, access to professional care remains severely constrained. According to HRSA[3], approximately 40% (137 million) Americans lived in designated mental health professional shortage areas by the end of 2025. Additionally, 6 in 10 psychologists do not accept new patients, and the national average wait time for behavioral health services is 48 days.

These gaps highlight the urgent need for scalable solutions that can support mental health assessment and care delivery. In response, recent studies have explored how LLMs might help with various mental health applications such as identifying disorders (Guo et al., 2024; Ge et al., 2025), generating empathetic responses (Loh and Raamkumar, 2023; Lee et al., 2023), and suggesting treatment approaches (Ghorbian and Ghobaei-Arani, 2025; Levkovich, 2025). While these models show promise, it remains unclear whether they can effectively utilize patient-specific contextual information when making clinical decisions. In this work, we use the term *patient-specific context* to refer to information contained in clinical case vignettes beyond the question itself. We distinguish this from the broader NLP usage of "context", which may refer to conversational history, retrieved documents, or prompt conditioning.

Mental health counseling is not merely a pattern recognition task. It involves interpreting complex, context-rich narratives including patients' lived experiences, stressors, and symptoms that are often ambiguous or evolving. Effective decision-making requires integrating information about a person's age, background, culture, and situational factors (Robles-Piña and McPherson, 2002). The key question is whether LLMs meaningfully incorporate such patient-specific context into their decisions, or whether their predictions are primarily driven by general knowledge and pattern-based associations learned during training. At the same time, it remains unclear whether existing benchmarks are explicitly designed to require robust patient-specific contextual reasoning for successful performance. If many questions can be answered correctly using generalized clinical knowledge alone, benchmark accuracy may overestimate context-sensitive clinical reasoning capabilities.

We investigate these questions[4] through a sys-

[1] WHO Mental Health Conditions Report
[2] SAMSHA Mental Health Facts
[3] HRSA Health workforce Report
[4] GitHub Repository

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 76–87
July 4, 2026 ©2026 Association for Computational Linguistics

tematic evaluation of LLMs on CounselingBench, a dataset of case-based questions spanning core counseling competencies tested in the National Clinical Mental Health Counseling Examination (NCMHCE), a U.S. licensing exam for mental health counselors. The dataset reflects realistic clinical case vignette (as shown in *Example Case Vignette* Box 1) encountered by students preparing for licensure, with a typical *passing benchmark of approximately 63% accuracy*. Prior work shows that larger, instruction-tuned LLMs can approach or exceed this threshold (Nguyen et al., 2024), though their reasoning capabilities remain underexplored.

Example Case Vignette

Patient Demographics: Male, 26, Caucasian, single

Mental Status Examination: Irritable affect, disorganized and pressured speech, audiovisual hallucinations, tangential thinking, paranoid ideation, poor insight and judgment.

Presenting Problem: First session: Medication nonadherence post-discharge; client believes he is being poisoned; verbal altercations with residents; refuses medication due to side effects.

Other Contexts: Client was stable on medication prior to stopping; resides in assisted living; caseworker accompanied; becomes angry when hospitalization is mentioned.

Question: You administer the Scale for the Assessment of Positive Symptoms (SAPS) to determine the severity of which of the following?

Answer Choices:

(A) Avolition
(B) Diminished speech
(C) Agitation
(D) Social withdrawal

To examine these limitations, we evaluate models across different scales and training paradigms, including general-purpose models (LLaMA-3-8B-Instruct, LLaMA-3-70B-Instruct) and a medically fine-tuned model (OpenBioLLM-70B). These models were selected based on prior work, where they achieve performance at or above the passing threshold on the benchmark. Building on this, we investigate whether such performance reflects genuine use of patient-specific context or whether predictions remain driven by general knowledge and pattern-based associations. This selection further allows us to assess whether increased model capacity and domain-specific training improve the integration of contextual information.

Building on this motivation, we design experiments to test whether LLM predictions are sensitive to patient-specific context. In this work, we define *patient-specific contextual information* as four key components of the dataset: (1) patient demographics, (2) presenting problems, (3) mental status examination, and (4) other contexts that provide clinically relevant details essential for informed decision-making. To probe this, we conduct ablation experiments to assess whether removing such details changes model predictions, answer option shuffling to test sensitivity to option positioning and detect positional bias, and question–answer ordering perturbations to evaluate robustness to broader input structure. We further evaluate prompting strategies, including role framing (e.g., assigning the model as a student or counselor) and context-oriented Thread-of-Thought (ThoT) prompting, to determine whether explicitly encouraging attention to patient-specific details improves contextual reasoning.

Finally, we perform a structured error analysis to identify cases where models recognize but fail to prioritize relevant contextual factors. For instance, when symptoms follow a recent traumatic event, a context-sensitive model should favor trauma-related diagnoses, whereas a context-insensitive model may default to more common disorders based on surface-level symptom overlap.

Based on this, we address the following Research Questions (RQ):

RQ1 Do LLMs utilize patient-specific contextual information when answering clinical questions?

RQ2 Can prompting strategies, including role framing and context-oriented prompting (ThoT), enhance the use of patient-specific contextual information in LLM decision-making?

2 Related Work

The use of computational methods to analyze mental health signals has evolved from rule-based approaches to transformer-based models capable of processing social media posts (Greco et al., 2023; Raihan et al., 2024; Bucur et al., 2025a,b; Bucur, 2026). With the emergence of LLMs, recent work has examined their capacity for identifying mental health risk signals and extended evaluation to multilingual (Elboardy et al., 2025; Raihan et al., 2024, 2026; Bucur et al., 2026) and low-resource settings. More recently, the focus has shifted from detection to interaction, where LLMs are studied as agents that simulate counseling through role-based

(Qiu and Lan, 2024; Cho et al., 2026) and multi-agent reasoning (Ozgun et al., 2025; Shafi, 2025). This shift raises a key question: can these models support clinically meaningful reasoning rather than simply produce plausible responses.

From a clinical perspective, effective psychotherapy requires integrating general knowledge with patient-specific context. The American Psychological Association (APA) guidelines for evidence-based practice emphasize that treatment decisions must account for individual characteristics such as developmental history, sociocultural background, and environmental stressors (on Evidence-Based Practice et al., 2006). Clinical reasoning is therefore inherently contextual, requiring not only symptom recognition but also interpretation of patient history, situational factors, and individualized needs (Cook et al., 2017; Moggia et al., 2024).

Current LLM evaluations do not fully capture this requirement. Benchmarks such as CounselingBench (Nguyen et al., 2024) show that larger LLMs can surpass the NCMHCE passing threshold and generate coherent explanations. However, such performance does not guarantee effective use of case-specific information, as predictions may rely on generalized symptom patterns rather than patient details. Recent work further highlights limitations of LLMs in psychotherapy settings (Chandra et al., 2025; Arnaout et al., 2026), including failures in contextual understanding (Wang et al., 2025), misinterpretation of user experiences, and reliance on generic responses (Iftikhar et al., 2025). Our work directly evaluates whether LLMs utilize patient-specific context in counseling scenarios.

3 Methods

3.1 Data

The dataset, named CounselingBench[1], is curated from National Clinical Mental Health Counseling Examination (NCMHCE) mock exams, sourced from mometrix.com, tetsst.vcm, CounselingExam.com, which is taken part by people who seek to become licensed clinical mental health counselors. CounselingBench contains 1,612 unique questions across 138 case studies consisting patient demographics, mental status examination, presenting problems, questions with answers, and expert-generated rationales. The benchmark assesses five key mental health counseling competencies identified through a national job analysis of over 16,000 credentialed counselors, representing empirically-validated work behaviors for effective counseling practice. To ensure fair use compliance, Nguyen et al. (2024) adapt procedures from Jin et al. (2021) by shuffling answer options while tracking correct answers. Two medical doctors specializing in psychiatry independently annotated all 1,612 questions to map each question to its corresponding competency assessment area, their distributions are shown in Table 1.

Competency	#
Counseling Skills & Interventions (CS&I)	599
Intake, Assessment, & Diagnosis (IA&D)	460
Professional Practice & Ethics (PP&E)	274
Treatment Planning (TP)	253
Core Counseling Attributes (CCA)	23

Table 1: Distribution of questions across competencies

The dataset includes various demographic backgrounds corresponding to categories present in the US Census data. Several cases involve patients not born in the United States, requiring cultural competency for accurate assessment.

3.2 Modeling

To evaluate whether LLMs utilize patient-specific contextual information or rely on pattern-based associations, we design controlled experiments that systematically manipulate both contextual and structural aspects of the input.

We begin by defining what constitutes *patient-specific context* in the CounselingBench dataset. As illustrated in Figure 1, clinical reasoning requires integrating four dimensions of information beyond surface-level symptoms when making counseling decisions, including demographic attributes, presenting conditions, mental status examination, and other contexts. These contextual dimensions form the basis of our ablation experiments, where specific components are removed to evaluate their influence on model predictions.

Although Figure 1 presents these components as structured elements for clarity, these elements are embedded within unstructured narratives, requiring models to extract and integrate relevant signals rather than relying on explicitly structured inputs.

We select LLaMA-3-8B-Instruct, LLaMA-3-70B-Instruct, and OpenBioLLM-70B to capture variation across both model scale and domain specialization. Prior work on CounselingBench (Nguyen et al., 2024) shows that larger instruction-

[1] https://github.com/cuongnguyenx/CounselingBench



Figure 1: Breakdown of patient-specific contextual information in a representative CounselingBench case. Patient-specific context spans four dimensions: demographic attributes, presenting problems, mental status examination, and other context.

tuned models are more likely to exceed the NCMHCE passing threshold of 63% accuracy, with LLaMA-3-70B-Instruct achieving strong performance while LLaMA-3-8B-Instruct remains closer to the threshold. This enables comparison across models with differing levels of task proficiency and assess whether higher accuracy corresponds to improved utilization of patient-specific context.

Additionally, prior work suggests diminishing performance gains from scaling within newer LLM families, motivating a comparison between 8B and 70B variants to examine whether increased model capacity corresponds to differences in contextual reasoning behavior rather than overall benchmark accuracy alone. We further include OpenBioLLM-70B, a LLaMA-based model additionally instruction-tuned on biomedical and medical-domain data, to investigate whether domain-specific adaptation improves sensitivity to patient-specific contextual information beyond general-purpose instruction tuning. However, because OpenBioLLM-70B is primarily optimized for biomedical reasoning rather than psychotherapy or counseling-specific decision-making, any improvements in contextual counseling performance are not necessarily expected. This comparison therefore allows us to examine whether higher capacity or medical-domain specialization meaningfully changes how models utilize patient-specific context during clinical decision-making.

3.3 Experimental Design

To evaluate whether model predictions are sensitive to patient-specific context or driven by pattern-based associations, we introduce controlled perturbations to the input. These perturbations are designed to test whether model predictions remain stable under changes that preserve semantic content but alter presentation, providing evidence of context-sensitive reasoning versus reliance on superficial input patterns.

Ablation Study: We conduct a structured ablation study to evaluate the extent to which model predictions depend on patient-specific contextual information. Specifically, we progressively remove contextual components from the case descriptions while preserving the question and answer options, allowing us to isolate the contribution of different types of information to model decision-making.

Contextual attributes are removed in a staged manner, following a hierarchy from less to more diagnostically informative components. We begin by removing *patient demographic* attribute, which provide general background information such as, name, age, gender etc, about the patient. Next, we remove *other contexts* attribute which contains relationship history, and occupational stress, these may influence interpretation but are not directly diagnostic. We then remove the *mental status exam* attribute, which captures clinical observations such as appearance, speech, thought process, and orientation. Finally, we remove the *presenting problem*, which contains the core symptom descriptions and key elements of the counseling interaction most directly tied to diagnosis.

This progressive removal enables a graded analysis of model sensitivity to different layers of patient-specific context. A context-sensitive model is expected to exhibit increasing changes in predictions as more diagnostically relevant information is removed. In contrast, stable predictions under such perturbations suggest that model behavior is driven by pattern-based associations rather than the integration of patient-specific contextual information.

Surface Perturbations: In this setting, we randomly reorder the answer choices to assess sensitivity to option positioning (*ShuffledOP*) to detect id models have any positional bias. On the other hand, in the question-first condition (*Q-first*), the question and answer options are presented before the case description, reversing the standard context-first format. This design allows us to analyze the primacy effect and assess whether model predictions depend on the relative position of contextual information. A context-sensitive model should integrate patient-specific details regardless of their position, while

strong sensitivity to ordering suggests reliance on input structure rather than contextual reasoning.

Role Framing: We adopt the prompting template from the previous study as our baseline, where the model is assigned the role of a student attempting to answer NCMHCE-style questions. To evaluate the effect of role specification on model behavior, we systematically vary the identity assigned to the LLM. Specifically, we consider four role configurations:

(1) *Role:STU*– the baseline student role,
(2) *Role:LC*– a licensed mental health counselor role,
(3) *Role:LC-DSM*– a licensed counselor role with explicit DSM-5 oriented diagnostic reasoning,
(4) *Role:EXP*– an expert-identity prompt

For the expert-identity setting, following the framework of Xu et al. (2023), we prompt GPT-5.1 to generate a specialized expert profile tailored to solving NCMHCE-style multiple-choice questions, which is then used to define the role and response expectations for all evaluated models.

Finally, to assess whether aggregating across role specifications improves sensitivity to patient-specific context, we apply role-based ensembling (*Role:Ensemble*). Each role configuration is evaluated independently, and final predictions are obtained via majority voting across role-conditioned outputs.

Thread-of-Thought (ThoT) Prompting: To investigate whether structured reasoning improves patient-specific contextual integration, we adapt Thread-of-Thought (ThoT) prompting (Zhou et al., 2023) to the clinical counseling domain. The original ThoT formulation is designed for retrieval-based settings, where models must filter relevant information from noisy inputs. However, clinical vignettes differ in that most contextual information is already relevant, and the primary challenge lies in integrating and prioritizing these signals for diagnosis. To better reflect this setting, we modify the ThoT trigger to explicitly structure reasoning around key clinical dimensions.

We follow a two-step ThoT pipeline. In Step 1, the model produces a structured intermediate summary from the patient-specific context. In Step 2, this summary replaces the original vignette and is used for answer selection. Unlike prior work that relies on free-text answer extraction, we use a consistent scoring-based approach for answer selection to ensure comparability across prompting conditions.

While this formulation encourages more explicit references to patient-specific details, it allows us to directly assess whether improved structure translates into better diagnostic decisions, or merely more coherent explanations without corresponding gains in accuracy.

4 Results & Observations

4.1 Ablation Study

Table 2 presents the results of our staged contextual ablation study across three models. A key observation is that removing patient-specific context components produces only modest accuracy degradation across all models. For LLaMA-3.1-8B-Instruct, the full context condition achieves 0.664, while the question-only condition – with all patient context removed – yields 0.625, a drop of only 3.9 percentage points. A similar pattern holds for LLaMA-3.3-70B-Instruct (0.732 $\rightarrow$ 0.691, Δ = 4.1%) and OpenBioLLM-70B (0.722 $\rightarrow$ 0.689, Δ = 3.3%). These relatively modest performance drops suggest that many questions in the benchmark may be answerable using generalized clinical knowledge and pattern-based associations acquired during pre-training, without requiring substantial reliance on patient-specific contextual information. However, the results do not conclusively determine whether the observed behavior primarily reflects limitations in the models' contextual reasoning abilities, limitations of the benchmark's ability to isolate context-sensitive reasoning, or the inherent difficulty and heterogeneity of context-dependent clinical questions. Instead, the findings indicate that benchmark-level performance alone may be insufficient for determining the extent to which LLMs reliably utilize patient-specific context during clinical decision-making.

Examining the per-competency breakdown reveals more nuanced patterns. The Core Counseling Attributes (CCA) competency shows notably stable performance across ablation conditions for LLaMA-3.1-8B-Instruct and OpenBioLLM-70B, suggesting this competency may be particularly amenable to pattern-based responses that do not require contextual integration.In contrast, the Intake Assessment and Diagnosis (IA&D) competency shows a consistent decline from full-context to question-only settings across all models, from 0.676 to 0.614 for LLaMA-3.1-8B-Instruct, 0.721 to 0.667 for LLaMA-3.3-70B-in, and 0.704 to

Condition	Overall Accuracy	Δ	IA&D (N=466)	TP (N=254)	CS&I (N=600)	PP&E (N=275)	CCA (N=23)
LLaMA-3.1-8B-Instruct							
Demographics + Other Contexts + Mental Status Exam + Presenting Problem + Question with Options	0.664	-	0.676	0.665	0.695	0.575	0.696
Other Contexts + Mental Status Exam + Presenting Problem + Question with Options	0.654	-0.010	0.655	0.650	0.690	0.575	0.696
Mental Status Exam + Presenting Problem + Question with Options	0.655	-0.009	0.682	0.650	0.663	0.589	0.696
Presenting Problem + Question with Options	0.642	-0.022	0.644	0.654	0.662	0.578	0.739
Question with Options	0.625	-0.039	0.614	0.598	0.645	0.618	0.696
LLaMA-3.3-70B-Instruct							
Demographics + Other Contexts + Mental Status Exam + Presenting Problem + Question with Options	0.734	-	0.721	0.720	0.757	0.720	0.783
Other Contexts + Mental Status Exam + Presenting Problem + Question with Options	0.735	0.001	0.730	0.736	0.753	0.709	0.739
Mental Status Exam + Presenting Problem + Question with Options	0.732	-0.003	0.717	0.756	0.748	0.709	0.696
Presenting Problem + Question with Options	0.727	-0.008	0.721	0.740	0.735	0.709	0.739
Question with Options	0.691	-0.044	0.667	0.677	0.722	0.673	0.739
OpenBioLLM-70B							
Demographics + Other Contexts + Mental Status Exam + Presenting Problem + Question with Options	0.722	-	0.704	0.713	0.742	0.727	0.696
Other Contexts + Mental Status Exam + Presenting Problem + Question with Options	0.724	0.002	0.697	0.736	0.748	0.713	0.696
Mental Status Exam + Presenting Problem + Question with Options	0.711	-0.011	0.689	0.740	0.723	0.705	0.696
Presenting Problem + Question with Options	0.713	-0.008	0.682	0.728	0.737	0.709	0.652
Question with Options	0.689	-0.033	0.646	0.685	0.723	0.695	0.696

Table 2: Ablation study evaluating the impact of removing patient-specific contextual components on model performance. Context is progressively reduced from full clinical vignette (demographics, other context, mental status exam, and presenting problem) to question-only input. Performance is reported as accuracy and across competency domains. Δ denotes change relative to the full-context condition for each model.

0.645 for OpenBioLLM-70B, indicating greater sensitivity to the removal of contextual information, though the overall sensitivity remains low.

Notably, the medically fine-tuned OpenBioLLM-70B does not exhibit substantially greater sensitivity to context removal compared to the general-purpose LLaMA models, suggesting that domain-specific training does not meaningfully improve reliance on patient-specific information. Overall, these results indicate that models approach this task largely as a knowledge retrieval rather than one requiring patient-specific reasoning, consistent with our central hypothesis.

4.2 Surface Perturbations

Table 3 presents results across prompting strategies including role framing input controls and ThoT prompting for LLaMA-3.1-8B-Instruct, LLaMA-3.3-70B-Instruct, and OpenBioLLM-70B. Shuffling answer options (*ShuffledOP*) results in negligible changes in accuracy across all models (LLaMA-3.1-8B: 0.660, LLaMA-3.3-70B: 0.735, OpenBioLLM-70B: 0.707), indicating limited reliance on answer position. In contrast, presenting the question before the vignette (*Q-first*) leads to the largest performance drop across models (LLaMA-3.1-8B: 0.629, LLaMA-3.3-70B: 0.709, OpenBioLLM-70B: 0.682), suggesting sensitivity to input ordering rather than clinical content. One possible explanation is that presenting the question and answer options first encourages models to form an initial prediction based on generalized clinical associations and learned response patterns before processing the patient vignette, thereby reducing the influence of subsequent patient-specific contextual information during answer selection. Together, these findings reveal an asymmetry: while models are robust to changes in answer option position, they are sensitive to prompt structure, a pattern inconsistent with robust clinical reasoning, where decisions should be driven by clinical content rather than sensitivity to input ordering.

4.3 Role Framing & ThoT Prompting

Across all three models, different role-framing strategies and their ensemble combinations produce only marginal accuracy differences. For LLaMA-3.1-8B-Instruct, the four role-framed prompts span a narrow range of 0.655 to 0.663, and a similar pattern holds for LLaMA-3.3-70B-Instruct (0.734-0.737) and OpenBioLLM-70B (0.720-0.722). This near-uniform performance suggests that assigning different clinical personas, from student to licensed counselor to domain expert, does not meaningfully alter the model's underlying reasoning process, consistent with our hypothesis that predictions are driven by knowledge-based associations rather than persona-specific clinical reasoning.

ThoT prompting consistently underperforms the role-framed prompts across all three models (LLaMA-3.1-8B-Instruct: 0.628, LLaMA-3.3-70B-Instruct: 0.730, OpenBioLLM-70B: 0.709). Despite explicitly instructing the model to process patient-specific context in a structured, step-by-step manner, ThoT does not yield accuracy gains over simpler role-framed prompts. This suggests that structured contextual summarization alone may be insufficient to substantially improve context-

	Accuracy	IA&D (N=466)	TP (N=254)	CS&I (N=600)	PP&E (N=275)	CCA (N=23)
LLaMA-3.1-8B-Instruct						
Role: STU	0.663	0.670	0.657	0.697	0.578	0.696
ShuffledOP	0.660	0.667	0.634	0.698	0.585	0.652
Q-first	0.629	0.627	0.634	0.635	0.615	0.609
Role: LC	0.658	0.674	0.673	0.680	0.567	0.696
Role: LC-DSM	0.655	0.657	0.665	0.683	0.575	0.739
Role: EXP	0.658	0.652	0.673	0.693	0.571	0.739
Role: Ensemble	0.663	0.672	0.665	0.690	0.582	0.696
ThoT	0.628	0.633	0.626	0.652	0.571	0.609
LLaMA-3.3-70B-Instruct						
Role: STU	0.735	0.721	0.720	0.758	0.720	0.783
ShuffledOP	0.735	0.730	0.728	0.755	0.709	0.739
Q-first	0.709	0.693	0.705	0.738	0.680	0.652
Role: LC	0.737	0.727	0.752	0.755	0.709	0.696
Role: LC-DSM	0.734	0.730	0.732	0.750	0.716	0.696
Role: EXP	0.737	0.719	0.752	0.753	0.727	0.696
Role: Ensemble	0.732	0.719	0.748	0.750	0.705	0.696
ThoT	0.730	0.734	0.713	0.745	0.716	0.696
OpenBioLLM-70B						
Role: STU	0.722	0.704	0.713	0.742	0.727	0.696
ShuffledOP	0.707	0.689	0.705	0.720	0.720	0.652
Q-first	0.682	0.659	0.693	0.693	0.687	0.696
Role: LC	0.721	0.697	0.705	0.750	0.724	0.696
Role: LC-DSM	0.720	0.697	0.717	0.743	0.720	0.696
Role: EXP	0.721	0.695	0.705	0.755	0.716	0.696
Role: Ensemble	0.721	0.697	0.713	0.748	0.720	0.696
ThoT	0.709	0.687	0.713	0.732	0.698	0.696

Table 3: Performance across prompting strategies and input controls for three LLMs on CounselingBench. Results are reported as accuracy and across competency domains. Role: STU = student persona, ShuffledOP = shuffled answer options, Q-first = question before context, Role: LC = licensed counselor, Role: LC-DSM = licensed counselor with DSM-5-TR reasoning, Role: EXP = clinical expert, Role: Ensemble = majority vote across all four role-framed prompts, ThoT = Thread-of-Thought two-step pipeline.

sensitive reasoning in clinical counseling tasks. However, it remains unclear whether this reflects limitations in the models' ability to effectively utilize patient-specific information from the generated summaries, or whether many benchmark questions can already be answered without substantial reliance on such context.

LLaMA-3.3-70B-Instruct consistently outperforms LLaMA-3.1-8B-Instruct by roughly 7 percentage points across all conditions, aligning with prior findings that larger models achieve higher accuracy on CounselingBench (Nguyen et al., 2024). However, OpenBioLLM-70B, despite being fine-tuned on medical literature, does not surpass the general-purpose LLaMA-3.3-70B-Instruct and often performs comparably. This suggests that medically fine-tuned models do not provide substantial advantages over instruction-tuned models for utilizing patient-specific context. Overall, these results indicate that counseling competency relies more on integrating patient-specific contextual information than on biomedical knowledge, and models may not effectively utilize patient-specific context despite access to domain knowledge.

ThoT Summary - Decision Mismatch

In a pediatric counseling vignette, a 10-year-old boy presents with anxiety symptoms following a recent family relocation and separation from caregivers. The vignette emphasizes fears about parental safety, sleep disturbance, and distress during separation, and explicitly links the symptoms to this relocation.

ThoT Summary (excerpt): *"The family has recently relocated, which could be a significant stressor for Michael."*

When asked which statement is most indicative of the child's condition, the correct answer is *family relocation*, as it represents the precipitating cause. However, all models instead select *refusal to go to school*.

Despite explicitly identifying the correct contextual factor, the final answer prioritizes a general symptom over the patient-specific cause.

5 Understanding Context-Insensitive Errors

While earlier analyses reveal that models underutilize patient-specific context, they do not explain how this failure manifests at the level of individual clinical decisions. To investigate, we analyze the 490 cases where all four role-framed prompts converge on the same incorrect answer for LLaMA-3.1-8B-Instruct model, the clearest signature of systematic pattern matching rather than knowledge-based patient-specific reasoning. Table 4 summarizes consensus behavior across all 1,621 questions; the 30.2% unanimous-wrong category is our focus here.

Through qualitative inspection of a representative sample of the 490 unanimously incorrect cases, we identify three recurring error patterns that illustrate how context-insensitive reasoning manifests in practice.

Consensus Type	Count	Percentage
All correct	1028	63.4%
All wrong (same answer)	490	30.2%
All wrong (different answer)	29	1.8%
1 correct + 3 wrong	24	1.5%
2 correct + 2 wrong	23	1.4%
3 correct + 1 wrong	27	1.7%

Table 4: Role-framing consensus analysis for LLaMA-3.1-8B-Instruct: all correct and all wrong (same answer) categories indicate unanimous agreement across four role-framed prompts, while partial disagreement rows reflect cases where prompts diverge in their predictions.

Broad-to-specific Failure: Models consistently select general-purpose instruments over the specific tool the patient's context demands. *A 28-year-old female attorney (Robin) presenting with alcohol use disorder states: "I can't live with the pain of*

our separation much longer, and I don't know how to cope with it". All four prompts select the Hamilton Anxiety Rating Scale (HAM-A), a general anxiety measure. The correct answer is the Columbia Suicide Severity Rating Scale (C-SSRS), directly indicated by the patient's language. The contextual signal distinguishing a general anxiety presentation from one with suicidal ideation is present and unambiguous, the model bypasses it in favor of the categorically familiar instrument.

Generic-priority Substitution: When contextual features point in multiple directions, models default to the higher-frequency clinical association rather than integrating the full patient picture. *A 65-year-old male (Alex) presenting with persistent depression, hopelessness, feeling "down in the dumps" and worsening affect is asked what to discuss first at intake*. All four roles select substance use history, a reasonable intake topic, but one whose priority is overridden by the patient's age, sex, and explicit hopelessness. The correct answer is suicidal ideation. The patient's demographics and affect are available; but they do not influence the prediction.

Relational Context Ignored: PP&E shows the highest unanimous error rate at 38.9% (shown in Table 5), reflecting a tendency to apply canonical ethical heuristics without integrating case-specific relational history. *In Robin's fifth session, the client, who has always rescheduled in advance, fails to appear without contact for the first time. A signed release for her mother and an established safety contact are documented in the vignette.* All four roles select "drive to the client's house to perform a wellness check", a generic crisis response. The correct answer is to contact the client's mother, as the established protocol dictates. The model defaults to a dramatic but contextually inappropriate action, ignoring the relational history that determines the right one.

Across all three error types, a consistent pattern emerges: model predictions appear to rely more on general clinical associations than on integrating patient-specific contextual details. This behavior is consistent with our earlier findings, where removing contextual information led to only modest performance degradation and input perturbations had minimal effect on predictions. The clinical consequences are substantial, missed suicidality screening, misprioritized intake assessment, and ethically inappropriate interventions, and in each case, the information required to arrive at the correct decision is explicitly present in the vignette but not effectively utilized. While we do not directly analyze training data distributions, this behavior is consistent with reliance on high-frequency associations rather than patient-specific reasoning.

Competency	Incorrect Predictions / Total Questions	Percentage
CS&I	162/600	27.0%
IA&D	136/466	29.2%
PP&E	107/275	38.9%
TP	79/254	30.7%
CCA	6/23	26.1%

Table 5: Distribution of the 490 unanimously incorrect predictions (all four role-framed prompts selecting the same wrong answer) across counseling competency areas, for LLaMA-3.1-8B-Instruct.

6 Conclusion & Future Directions

We revisit the research questions (RQ) posed in the introduction and present the main findings of our review below:

RQ1: Do models utilize patient-specific information when answering clinical questions?

Findings: *Ablation and input-structure control experiments suggest limited observable dependence on patient-specific context for benchmark performance. Under progressive removal of contextual components, from demographics to presenting problem, performance drops only modestly. Shuffling answer options yields largely stable predictions, suggesting minimal sensitivity to answer position, while varying question order introduces more noticeable changes in performance. Together, these findings indicate that model predictions may be influenced not only by patient-specific information, but also by prompt structure and generalized clinical associations learned during training. However, the extent to which this reflects limitations in contextual reasoning, properties of the benchmark itself, or the inherent difficulty of context-dependent questions remains unclear. A qualitative error analysis of the 490 cases where all four role-framed prompts converge on the same incorrect answer reveals three recurring failure patterns: broad-to-specific failures in assessment selection, generic-priority substitution at intake, and relational context ignored in ethical decision-making. In these cases, contextual information relevant to the correct answer was present in the vignette, yet the models*

consistently selected alternatives more strongly associated with high frequency or generalized clinical patterns.

RQ2: Can prompting strategies, including role framing and context-oriented prompting (ThoT), enhance the use of patient-specific contextual information in LLM decision-making?

Findings: *Role framing has no measurable effect on accuracy, with models converging on the same wrong responses 30.2% of the time regardless of assigned persona. ThoT encourages more structured representations and increases explicit reference to patient-specific details, yet does not improve decision outcomes. Even when relevant context is correctly identified in intermediate reasoning, models fail to prioritize it during answer selection, revealing a gap between structured explanation and actual clinical reasoning that prompting alone cannot close.*

These findings have important implications for the deployment of LLMs in mental health support contexts. Achieving a passing score on aggregate benchmarks may not necessarily indicate robust utilization of patient-specific contextual information during clinical decision-making. Models may perform well overall while still exhibiting difficulty appropriately prioritizing contextual cues that distinguish between clinically appropriate and inappropriate responses in certain cases.

Future work should pursue several directions. First, *contrastive case vignette design*, where identical symptom profiles require different decisions based solely on demographic or situational context, would provide a more direct evaluation of context-sensitive reasoning than ablation-based approaches. Second, the *error taxonomy* identified in this work should be systematically validated across the full set of 490 cases and extended to additional models to determine whether these patterns reflect model-specific behaviors or broader limitations of LLM-based clinical reasoning. Third, given the concentration of errors in Professional Practice and Ethics (PP&E), future work should investigate whether targeted *fine-tuning on ethics-focused cases* with rich relational context can reduce reliance on generalized heuristics and improve context-sensitive decision-making. Finally, future evaluations should examine clinically appropriate uncertainty behaviors, such as asking clarifying questions, expressing insufficient confidence, or declining definitive recommendations when critical contextual information is missing.

Limitations

This study has several limitations. First, our evaluation is restricted to LLaMA-3.1-8B-Instruct, LLaMA-3.3-70B-Instruct, and OpenBioLLM-70B; findings may not generalize to proprietary models such as GPT-4 or Claude, which may exhibit different contextual reasoning behaviors. Second, CounselingBench is based on U.S. licensing examination questions (NCMHCE), which reflect a specific cultural and regulatory context. Performance on this benchmark may not represent LLM capabilities in counseling settings outside the United States or in languages other than English. Third, our evaluation uses multiple-choice questions, which differ substantially from real counseling interactions that involve open-ended dialogue, therapeutic alliance, and moment-to-moment clinical judgment. High benchmark accuracy should not be interpreted as evidence of clinical competence. Finally, the ThoT experiments use a maximum of 512$\sim$768 generated tokens for Step 1 summaries, which may truncate complex multi-session vignettes and limit the quality of the intermediate clinical reasoning captured.

Another limitation is the possibility of benchmark contamination or indirect exposure during pre-training or instruction tuning. Because NCMHCE-style preparation materials are publicly available online, models may partially rely on memorized exam-style patterns rather than robust contextual reasoning, potentially contributing to stable performance under contextual ablation.

Ethical Considerations

This study is purely analytical and does not involve new data collection or human participants. All analyses are conducted on the publicly available CounselingBench dataset (Nguyen et al., 2024), derived from U.S. mental health counseling licensing examinations (NCMHCE). No personally identifiable information is used, and the study follows the ACL Code of Ethics.[1]

Acknowledgments

We thank the CounselingBench authors for releasing this interesting dataset to the research community. We further thank the anonymous CLPSych reviewers for their valuable feedback.

[1] ACL Code of Ethics

References

Hiba Arnaout, Anmol Goel, H Andrew Schwartz, Steffen T Eberhardt, Dana Atzil-Slonim, Gavin Doherty, Brian Schwartz, Wolfgang Lutz, Tim Althoff, Munmun De Choudhury, and 1 others. 2026. Responsible evaluation of ai for mental health. *arXiv preprint arXiv:2602.00065*.

Ana-Maria Bucur. 2026. Computational approaches to mental health disorders detection from social media texts, images and videos. *Procesamiento del Lenguaje Natural*, 76:311–314.

Ana-Maria Bucur, Andreea Moldovan, Krutika Parvatikar, Marcos Zampieri, Ashiqur Khudabukhsh, and Liviu P Dinu. 2025a. Datasets for depression modeling in social media: An overview. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 116–126.

Ana-Maria Bucur, Andreea-Codrina Moldovan, Krutika Parvatikar, Marcos Zampieri, Ashiqur R KhudaBukhsh, and Liviu P Dinu. 2025b. On the state of nlp approaches to modeling depression in social media: A post-covid-19 outlook. *IEEE Journal of Biomedical and Health Informatics*.

Ana-Maria Bucur, Marcos Zampieri, Tharindu Ranasinghe, and Fabio Crestani. 2026. A survey on multilingual mental disorders detection from social media data. In *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 893–918.

Mohit Chandra, Siddharth Sriraman, Harneet Singh Khanuja, Yiqiao Jin, and Munmun De Choudhury. 2025. Reasoning is not all you need: examining llms for multi-turn mental health conversations. *arXiv preprint arXiv:2505.20201*.

Ha Na Cho, Jiayuan Wang, Di Hu, and Kai Zheng. 2026. Large language model–based chatbots and agentic ai for mental health counseling: Systematic review of methodologies, evaluation frameworks, and ethical safeguards. *JMIR AI*, 5(1):e80348.

Sarah C Cook, Ann C Schwartz, and Nadine J Kaslow. 2017. Evidence-based psychotherapy: Advantages and challenges. *Neurotherapeutics*, 14(3):537–545.

Ahmed Tamer Elboardy, Ziad Mohamed, Ghada Khoriba, Tamer Arafa, and Essam A Rashed. 2025. Bridging gender disparities in mental health: A bilingual large language model for multilingual therapeutic chatbots. In *2025 22nd International Learning and Technology Conference (L&T)*, volume 22, pages 251–256. IEEE.

Zhuohan Ge, Nicole Hu, Darian Li, Yubo Wang, Shihao Qi, Yuming Xu, Han Shi, and Jason Zhang. 2025. A survey of large language models in mental health disorder detection on social media. In *2025 IEEE 41st International Conference on Data Engineering Workshops (ICDEW)*, pages 164–176. IEEE.

Mohsen Ghorbian and Mostafa Ghobaei-Arani. 2025. Large language models for mental health diagnosis and treatment: a survey. *Artificial Intelligence Review*, 59(1):9.

Candida M Greco, Andrea Simeri, Andrea Tagarelli, and Ester Zumpano. 2023. Transformer-based language models for mental health issues: a survey. *Pattern Recognition Letters*, 167:204–211.

Zhijun Guo, Alvina Lai, Johan H Thygesen, Joseph Farrington, Thomas Keen, Kezhi Li, and 1 others. 2024. Large language models for mental health applications: systematic review. *JMIR mental health*, 11(1):e57400.

Zainab Iftikhar, Amy Xiao, Sean Ransom, Jeff Huang, and Harini Suresh. 2025. How llm counselors violate ethical standards in mental health practice: A practitioner-informed framework. In *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, volume 8, pages 1311–1323.

Di Jin, Eileen Pan, Nassim Oufattole, Wei-Hung Weng, Hanyi Fang, and Peter Szolovits. 2021. What disease does this patient have? a large-scale open domain question answering dataset from medical exams. *Applied Sciences*, 11(14):6421.

Yoon Kyung Lee, Inju Lee, Minjung Shin, Seoyeon Bae, and Sowon Hahn. 2023. Chain of empathy: Enhancing empathetic response of large language models based on psychotherapy models. *arXiv preprint arXiv:2311.04915*.

Inbar Levkovich. 2025. Evaluating diagnostic accuracy and treatment efficacy in mental health: A comparative analysis of large language model tools and mental health professionals. *European Journal of Investigation in Health, Psychology and Education*, 15(1):9.

Siyuan Brandon Loh and Aravind Sesagiri Raamkumar. 2023. Harnessing large language models' empathetic response generation capabilities for online mental health counselling support. *arXiv preprint arXiv:2310.08017*.

Danilo Moggia, Wolfgang Lutz, Eva-Lotta Brakemeier, and Leonard Bickman. 2024. Treatment personalization and precision mental health care: Where are we and where do we want to go? *Administration and Policy in Mental Health and Mental Health Services Research*, 51(5):611–616.

Viet Cuong Nguyen, Mohammad Taher, Dongwan Hong, Vinicius Konkolics Possobom, Vibha Thirunellayi Gopalakrishnan, Ekta Raj, Zihang Li, Heather J Soled, Michael L Birnbaum, Srijan Kumar, and 1 others. 2024. Do large language models align with core mental health counseling competencies? *arXiv preprint arXiv:2410.22446*.

APA Presidential Task Force on Evidence-Based Practice and 1 others. 2006. Evidence-based practice in psychology. *The American Psychologist*, 61(4):271–285.

Mithat Can Ozgun, Jiahuan Pei, Koen Hindriks, Lucia Donatelli, Qingzhi Liu, and Junxiao Wang. 2025. Trustworthy ai psychotherapy: Multi-agent llm workflow for counseling and explainable mental disorder diagnosis. In *Proceedings of the 34th ACM International Conference on Information and Knowledge Management*, pages 2263–2272.

Huachuan Qiu and Zhenzhong Lan. 2024. Interactive agents: Simulating counselor-client psychological counseling via role-playing llm-to-llm interactions. *arXiv preprint arXiv:2408.15787*.

Nishat Raihan, Sadiya Sayara Chowdhury Puspo, Ana-Maria Bucur, Stevie Chancellor, and Marcos Zampieri. 2026. Large language models for mental health: A multilingual evaluation. In *Proceedings of LoResLM 2026*.

Nishat Raihan, Sadiya Sayara Chowdhury Puspo, Shafkat Farabi, Ana-Maria Bucur, Tharindu Ranasinghe, and Marcos Zampieri. 2024. Mentalhelp: A multi-task dataset for mental health in social media. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 11196–11203.

Rebecca A Robles-Piña and Robert H McPherson. 2002. The relationship between educational and demographic variables and supervisor's multicultural counseling competencies. *The Clinical Supervisor*, 20(2):67–79.

Fozle Rabbi Shafi. 2025. Wellbeingagent: An llm-driven agentic framework for personalized mental health support. Master's thesis, Queen's University (Canada).

Yinzhou Wang, Yimeng Wang, Ye Xiao, Liabette Escamilla, Bianca Augustine, Kelly Crace, Gang Zhou, and Yixuan Zhang. 2025. Evaluating an llm-powered chatbot for cognitive restructuring: Insights from mental health professionals. *arXiv preprint arXiv:2501.15599*.

Benfeng Xu, An Yang, Junyang Lin, Quan Wang, Chang Zhou, Yongdong Zhang, and Zhendong Mao. 2023. Expertprompting: Instructing large language models to be distinguished experts. *arXiv preprint arXiv:2305.14688*.

Yucheng Zhou, Xiubo Geng, Tao Shen, Chongyang Tao, Guodong Long, Jian-Guang Lou, and Jianbing Shen. 2023. Thread of thought unraveling chaotic contexts. *arXiv preprint arXiv:2311.08734*.

Appendix

A Prompts

Role:STU (Baseline):

<System>
You are a helpful, respectful, honest, and knowledgeable **student** studying to become a licensed therapist. You must answer a series of multiple-choice questions provided by the user from a **US mental health counselor licensing exam**. Based on the question text and the context provided, you must answer with either "A", "B", "C", or "D".

</System>

<User>
Question:
The patient demographic is as follows: *[PATIENT DEMOGRAPHICS]*
[PRESENTING PROBLEM]
[MENTAL STATUS EXAMINATION]
[OTHER CONTEXTS]
Given the context above and your expert-level knowledge of mental health counseling, please answer the following question: *[QUESTION]*
[CANDIDATE ANSWERS]

<Assistant>
Correct Answer is (

Role:LC: You are a helpful, respectful, honest, and knowledgeable **licensed mental health counselor**. You must answer a series of multiple-choice **questions similar to those on a licensing board exam**. Based on the question text and the context provided, you must answer with either "A", "B", "C", or "D".

Everything else is as the baseline prompt.

Role:LC-DSM: You are a helpful, respectful, honest, and knowledgeable **licensed mental health counselor**. You must answer a series of multiple-choice questions. Based on the question text and the context provided, you must answer with either "A", "B", "C", or "D", **applying DSM-5 consistent reasoning**.

Everything else is as the baseline prompt.

Prompt to Generate Expert Identity: Suppose you need to answer MCQs for the NCMHCE exam that include extensive client demographics and detailed case studies. Provide an expert identity prompt that can guide the model in responding effectively.

ROLE:EXP (Generated Expert Identity): You are a clinically trained Licensed Mental Health Counselor with comprehensive expertise in DSM-5-TR diagnosis, assessment, ethics, crisis intervention, and evidence-based treatment across diverse populations. You use advanced clinical reasoning to answer multiple-choice questions with the best possible response. Based on the question text and the context provided, you must answer with either "A", "B", "C", or "D"

ThoT Prompt: Walk me through this patient case in manageable parts step by step – consider their demographics, presenting problem, mental status, and other contextual factors – summarizing and analyzing each as we go.

B Inference Settings

Table 6 summarizes the inference settings used across all experiments. For ThoT Step 1, we employ the *Role: LC* prompt to encourage more comprehensive summarization of the full context.

Parameter	**Value**
Temperature (answer selection)	0.0∼0.7
Top-p	1.0
Decoding strategy	Greedy
Max tokens (answer selection)	1
Max tokens (ThoT Step 1)	512∼768
Stop tokens	) and \n
Serving framework	vLLM

Table 6: Inference configuration for all experiments.

The Reliability Illusion in Synthetic Patients: Psychometric Misalignment of Open-weight LLMs on PHQ-9 and GAD-7

Qian Shen
University of Florida
qian.shen1@ufl.edu

Yu Han
University of Mississippi
yhan3@go.olemiss.edu

Abstract

Globally, the incidence of depression and anxiety continues to rise, and the importance of mental health assessment scales as diagnostic tools has grown accordingly. Researchers are increasingly employing generative AI to produce large volumes of items and entire scales, which in turn elevates the costs of validating their reliability and validity. In this study, we used four open-weight LLMs to complete the GAD-7 and PHQ-9, varying prompts, sampling temperature, and dynamic contextual scenarios to emulate realistic human response patterns. Using multi-group confirmatory factor analysis, differential item functioning analyses, and other psychometric methods, we evaluate the factor structure of LLM-generated responses and assess measurement invariance relative to human responses. Our findings reveal a critical paradox: although open-weight LLMs exhibit exceptionally high internal consistency, they demonstrate severe structural mismatch and fail to achieve scalar measurement invariance against human baselines. Furthermore, pervasive differential item functioning and extreme prompt fragility indicate that these models rely on superficial, stereotype-driven semantic matching rather than simulating stable latent psychological dynamics.

1 Introduction

Recent advances in large language models (LLMs) have motivated growing interest in their use for social science studies and practice (Thapa et al., 2025), such as mental health (Lawrence et al., 2024). As one of the most prevalent mental health issues, anxiety and depression are exhibiting a growing trend on a global scale (Chen et al., 2026). Consequently, researchers are actively exploring research and clinical practices concerning the effective application of LLMs in the diagnosis and treatment of these conditions (Pavlopoulos et al., 2024).

Psychological scales such as Generalized Anxiety Disorder (GAD)-7 (Spitzer et al., 2006) and Patient Health Questionnaire (PHQ)-9 (Kroenke et al., 2001) are a common class of instruments used for preliminary diagnosis or self-assessment of anxiety and depression (Costello and Comrey, 1967). Currently, LLMs are widely used by scholars in education and psychometric measurement to develop new items and questionnaires (Tan et al., 2025; Adhikari et al., 2025). Undeniably, LLMs can design a large number of new items and scales in a short period, greatly improving the efficiency and time cost of item and questionnaire development. However, the ensuing problem is that as the number of newly designed items and questionnaires increases, the temporal and economic costs of collecting human responses to validate their reliability and validity according to traditional methods have also increased significantly.

Due to their robust comprehension and learning capabilities, LLMs are being utilized by researchers to simulate human behavior and are considered a promising approach (Park et al., 2023). However, when such models are used as synthetic respondents for psychological scales, the central question is not merely whether they can generate plausible answers, but whether those answers remain psychometrically comparable to authentic human responses. In this study, we examine this question using two widely used mental health screening scales, the GAD-7 and PHQ-9, and evaluate whether responses generated by open-weight LLMs exhibit measurement invariance relative to human data. To make the comparison more realistic, we vary respondent personas, situational context, prompting conditions, and decoding temperatures. Our primary research question is therefore whether LLM-generated responses can function as psychometrically aligned synthetic substitutes for human respondents on clinical screening scales.

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 88–99
July 4, 2026 ©2026 Association for Computational Linguistics

2 Related Work

Given their strong natural language capabilities, LLMs are increasingly used in the screening and treatment of anxiety and depression. For example, Tao et al. (2023) proposed an LLM-based virtual interaction framework to explore ChatGPT's potential for detecting these disorders, while Liu et al. (2025a) developed EmoScan, which screens for depression and anxiety through brief text dialogues. Xu et al. (2025) fine-tuned LLMs on clinical recordings of outpatients with depression and anxiety to automate scale assessments, achieving robust diagnosis and symptom classification through an ensemble pipeline and 10-fold cross-validation. In addition, Zhao et al. (2025) found that LLM-driven conversational agents can reduce mild symptoms in young adults, and García-Méndez et al. (2026) combined machine learning and LLMs to improve detection in unstructured conversations.

Recent studies have also examined LLM performance on academic tests and psychometric scales. Using Item Response Theory, Liu et al. (2025b) compared LLMs with undergraduates on college algebra problems and found that individual LLMs show a narrower proficiency range than humans, while ensemble models better approximate student ability distributions. Similarly, Ferreira et al. (2025); Cipriani et al. (2025) evaluated LLM responses to personality and climate change perception scales with descriptive statistics and exploratory factor analysis, showing that LLMs only partially reproduce human patterns. This suggests that LLM-generated data may be useful for early group-level psychometric prototyping, but cannot replace individual-level validation. A fundamental driver of these psychometric discrepancies is highlighted by Licht et al. (2025), who demonstrate that LLMs process ordinal scales idiosyncratically through heaping, mechanically concentrating probability mass on arbitrary numeric tokens rather than reflecting true continuous distributions. This mechanical token bias provides a critical mechanistic context for why synthetic responses may mimic human averages but fail structural validation.

Battista et al. (2026) further showed that LLMs such as GPT-3.5 can simulate depressive symptoms and score highly on relevant scales, although they may also display malingering-like patterns. Moreover, while LLMs remain limited in capturing authentic cross-cultural psychological nuances in personality inventories (Li and Qi, 2025), they show social desirability bias comparable to human responses (Salecha et al., 2024). Thus, using LLMs to pilot personality scales and questionnaires may be a valuable step before human administration (de Winter et al., 2024).

From the perspective of LLM simulation, the aforementioned studies generally rely on very small sample sizes (fewer than 100) or use fixed demographic profiles, which fails to mitigate the impact of inherent LLM stochasticity on research results. Regarding analytical rigor, most of these studies employ basic statistical methods and lack formal psychometric validation to establish measurement invariance between LLM-generated and human responses. Furthermore, the limited sample sizes in these studies can potentially undermine the precision and reliability of their conclusions.

3 Method

In this study, we selected four open-weight LLMs to respond repeatedly to the GAD-7 and PHQ-9 by systematically varying combinations of personas, prompt types, dynamic situational modifiers, and temperatures. Subsequently, we applied psychometric techniques, specifically Confirmatory Factor Analysis (CFA) and ordinal logistic differential item functioning (DIF), to evaluate the measurement invariance between LLM-generated outputs and human response data. Figure 1 shows our comprehensive methodological pipeline.

3.1 Data

For this study, we selected the GAD-7 and PHQ-9, classic self-report scales for anxiety and depression, as our primary research instruments. To facilitate a robust comparison with human responses, we used the GAD-7 data from 2019 National Health Interview Survey (NHIS), and the PHQ-9 data from 2017 to 2019 of the National Health and Nutrition Examination Survey (NHANES) after removing all samples with missing values.

3.2 LLM-Based Response Generation

We constructed a layered respondent simulation pipeline to generate synthetic respondent data for PHQ-9 and GAD-7. The pipeline was implemented with four open weight LLMs: Llama-3.1-8B-Instruct, Mistral-7B-Instruct, Llama-3.3-70B-Instruct, and GPT-OSS-120B. The inclusion of models at both the $\sim$8B and $\sim$100B parameter scales reflects a deliberate range of model capacities; prior work has demonstrated that models



Figure 1: Overall framework of the study for generating LLM-based synthetic PHQ-9 and GAD-7 responses, and evaluating psychometric alignment between synthetic and human data.

of these scales exhibit reasonably representative language understanding and generation behavior suitable for the tasks of psychology and education (Mantena et al., 2025; Xiao and Shen, 2026; Loweimi et al., 2026; Shen et al., 2026). First, real respondents typically exhibit relatively stable individual differences when completing questionnaires (Julian, 2011). To reflect this, we assigned each model a baseline persona specifying the respondent's symptom background. For both scales, personas were defined at three severity levels, healthy, mild, and severe, so that generated responses showed a clear severity structure. This layer captured relatively stable differences in respondent symptom profiles and provided a basis for later modeling of local fluctuation and item-level variation. However, stable severity differences alone are insufficient to explain response variation within the same severity group. In real self-report data, responses reflect not only overall symptom level but also short-term fluctuations and situational influences (Armey et al., 2015; Mengelkoch et al., 2024). To model this, we introduced dynamic situational modifiers. Before each generation, the system randomly appended a brief description of the respondent's current state or recent experience, such as "you slept poorly last night." These modifiers did not alter overall severity, but influenced item-level responses, preserving the overall severity structure while retaining more natural within-group fluctuation. Even with baseline personas and dynamic situational modifiers, LLM-generated responses could still deviate from real self-report response patterns. Whereas real self-report responses reflect both relatively stable symptom tendencies and short-term situational fluctuation, LLM-based questionnaire generation may produce overly regular or internally over-consistent response patterns (Jeon et al., 2024; Chan et al., 2025). To reduce this mismatch, we introduced two prompting conditions, Standard and Calibrated, to constrain response style. Under the Standard condition, the model completed the questionnaire directly from the assigned persona and modifier. Under the Calibrated condition, the prompt discouraged uniformly extreme responding and allowed moderate item-level variation, temporary relief, and mild inconsistency. For example, severe respondents were not expected to choose the highest option for every item, while healthy respondents could still report

mild distress. This setting helped reduce overly regular response patterns. To account for sampling effects, we repeated generation under different temperature conditions to introduce additional output variability within the same respondent condition, rather than fixing responses to a single decoding setting. For each scale and model, generation conditions were defined by temperature, persona, and prompt condition. Temperature had two levels, persona had three levels (healthy, mild, severe), and prompt condition had two levels (Standard, Calibrated), yielding $2 \times 3 \times 2 = 12$ generation conditions per model for each scale. Each condition was repeated for 500 iterations, resulting in 6,000 valid responses per scale for each model, with matched sample sizes across models. All outputs followed a strict JSON schema with one integer score per item, and a mixed-score example response was provided to constrain output structure. The resulting outputs formed the synthetic respondent dataset used for subsequent psychometric evaluation.

3.3 Psychometric Methods

To ensure comparable group sizes in subsequent analyses(Chen, 2007; Herrera and Gómez, 2008), we randomly sampled 6,000 observations without replacement from each human dataset to match the number of LLM-generated responses per scale. We then fitted unidimensional CFA models separately to the human and LLM-generated data (Löwe et al., 2008; Bianchi et al., 2022), treating item responses as continuous and using robust maximum likelihood estimation (MLR). We adopted this specification because preliminary ordinal CFA models produced improper solutions (e.g., non-positive definite covariance matrices and negative residual variances), whereas MLR yielded stable and interpretable estimates for the present comparisons. Model fit was evaluated using the criteria recommended by Hu and Bentler (1999), with acceptable fit indicated by CFI and TLI ≥ 0.95, RMSEA ≤ 0.06, and SRMR ≤ 0.08. Chi-square tests for all individual CFA models were statistically significant ($p < .001$), which is expected given the large sample sizes involved and does not in itself indicate model misfit.

Measurement invariance between human and LLM-generated responses was examined using multi-group CFA under the conventional sequence of configural, metric, and scalar models, and evaluated primarily by changes in CFI between nested models. Following common practice in social science research, strict invariance was not tested, as it is widely regarded as an overly stringent criterion that is rarely achieved in practice and is generally not required for meaningful cross-group comparisons (Vandenberg and Lance, 2000; Putnick and Bornstein, 2016). To assess item-level bias, we additionally conducted ordinal logistic regression DIF analyses, using a change in McFadden's pseudo-R^2 greater than 0.035 as the criterion for substantial DIF (Zumbo, 1999; Choi et al., 2011). We also conducted within-model multi-group CFA to compare responses generated under the Standard and Context-Calibrated prompts, assessing whether internal prompt variation altered the underlying measurement structure.

4 Results and Discussion

Tables 1 and 2 show the results of our psychometric evaluation and analysis of data generated by LLMs, as well as the evaluation of the measurement invariance between the LLM-generated data and human response data. The results show a critical paradox in LLM-generated psychometric data: the illusion of high reliability masking structural collapse. Across the PHQ-9 and GAD-7, LLMs exhibited exceptionally high internal consistency (α = 0.86 to 0.96), often surpassing human baselines. However, CFA results expose this reliability as spurious. Chi-square tests were statistically significant ($p < .001$) for all models including the human baseline, which is expected given the large sample size ($N = 6{,}000$) and does not in itself indicate misfit (Hu and Bentler, 1999). Human data showed excellent unidimensional fit across all practical indices (CFI $= 0.972$, RMSEA $= 0.047$), while all LLM yielded a substantially degraded fit, with RMSEA ranging from 0.124 to 0.364 and CFI as low as 0.724, confirming that the significant chi-squares for LLM models reflect genuine structural misfit rather than a sample-size artifact. Notably, Llama-3.3-70B showed the poorest fit, and even the largest model evaluated (GPT-OSS-120B) failed to reach acceptable structural thresholds. This suggests LLMs rely on stereotype-driven semantic matching, mechanically assigning high scores to negative descriptors, rather than simulating a coherent latent psychological trait.

This structural mismatch is further corroborated by testing measurement invariance against human baselines. No LLM achieved partial scalar invariance on either scale, indicating fundamentally mis-

aligned intercepts. Furthermore, DIF analysis revealed that LLMs systematically distort specific symptom weights, exhibiting significant DIF on 7 to 8 out of the 9 PHQ-9 items. Consequently, LLM raw scores cannot be mathematically equated to human populations.

Crucially, we uncovered extreme prompt fragility within the models themselves. Tables 3 and 4 report within-model multi-group CFA results comparing the two prompt conditions. Across both scales, none of the models supported metric or scalar invariance, and configural fit was already weak in several cases, suggesting that changes in prompting affected the latent response architecture. In humans, contextual shifts may alter latent means but rarely obliterate the underlying measurement geometry. For LLMs, altering the persona prompt completely rewires the response architecture.

Collectively, these findings indicate that while LLM outputs appear clinically relevant, their underlying psychometric geometry remains fundamentally non-human. The complete failure to maintain structural consistency, both against humans and across internal prompt variations, poses severe validity risks for deploying LLMs as synthetic respondents in psychological scale pre-testing.

5 Conclusion

This study examines whether open-weight LLMs can function as psychometrically valid synthetic respondents on the GAD-7 and PHQ-9. Our results show that the answer is currently no. Despite high internal consistency, the generated responses do not preserve the same structural properties as human data, fail to support scalar invariance, and display substantial item-level bias. The central finding is a reliability illusion: LLM-generated responses achieved Cronbach's α values of 0.86 to 0.96, often exceeding the human baseline, yet this apparent reliability masked severe structural misfit. This paradox likely reflects stereotype-driven semantic matching, whereby models assign scores based on surface-level associations with symptom-related language rather than sampling from a coherent latent psychological distribution. As a result, high inter-item consistency emerges not from a shared underlying construct, but from systematic response tendencies that happen to co-vary across items, a fundamentally different mechanism from what reliability coefficients are designed to capture. The prompt fragility results further underscore this interpretation. Across all four models, even minor changes in prompt framing were sufficient to disrupt metric and scalar invariance within the same model, indicating that the latent response architecture itself shifts with surface-level wording. In human respondents, contextual factors may shift symptom expression but rarely alter the underlying measurement geometry of a well-validated scale. The fact that LLMs do not exhibit this stability suggests that they lack a stable internal representation of the clinical constructs being measured. These findings carry practical implications for the use of LLMs in psychometric scale development. While LLM-generated data may offer utility in early-stage item generation or qualitative piloting, the present results caution against their use as synthetic respondents for quantitative pre-validation, particularly when the goal is to estimate reliability or factor structure prior to human administration. Treating high Cronbach's α as sufficient evidence of data quality in this context risks systematically misleading scale development decisions. More broadly, our results speak to ongoing debates in the digital twin and LLM-as-coder literature: any claim of LLM-human substitutability must be vetted through domain-expert-led, construct-appropriate validation rather than surface-level performance metrics alone.

We therefore argue that reliability alone is an inadequate benchmark for synthetic psychometric data, and that measurement invariance relative to human baselines should serve as a more stringent criterion in future evaluations. Subsequent work might explore whether instruction-tuned models with richer demographic and clinical grounding, or models fine-tuned on large-scale self-report corpora, can better approximate the psychometric geometry of human responses. Until such evidence is available, researchers should interpret LLM-generated scale responses with considerable caution.

Limitations

Our study has several limitations. First, to enhance applicability across clinical settings with varying economic resources, we used only freely downloadable, deployable open-weight LLMs and did not employ stronger, paid models (e.g., Gemini-3, GPT-5), which may perform differently on the same tasks. Second, in our experimental design, the combination of conditions yielded approximately

balanced proportions of different mental health states; however, the true distribution in real populations completing these scales may deviate from our simulated proportions. For example, among respondents completing these scales in mental health clinics, the prevalence of actual depression or anxiety is likely higher than in large community surveys, and in neither context is a balanced prevalence assured. Third, we did not systematically ablate the role of dynamic contexts or prompting components, so the specific contribution of each design choice remains unclear. Finally, because we drew only a single sample of human responses, multi-group CFA comparisons may vary across different samples due to sampling variability.

Ethical Statement

This study used publicly available, de-identified human response data from NHIS and NHANES and did not involve new participant recruitment or direct interaction with human subjects. These data are fully open to the public; anyone may access them unconditionally, without the need to apply for special permissions or sign data usage agreements. When researchers acquire and analyze data, they must never re-link the data to an individual's identity through any encoding or key. Rather than an ethical concern intrinsic to this study, our findings serve as a cautionary signal: using LLM-generated responses as substitutes for real patient data, without rigorous psychometric validation, would constitute a failure on the part of those who disregard such evidence.

References

Divya Mani Adhikari, Alexander Hartland, Ingmar Weber, and Vikram Kamath Cannanure. 2025. Exploring llms for automated generation and adaptation of questionnaires. In *Proceedings of the 7th ACM Conference on Conversational User Interfaces*, pages 1–23.

Michael F. Armey, Heather T. Schatten, Natasha Haradhvala, and Ivan W. Miller. 2015. Ecological momentary assessment (ema) of depression-related phenomena. *Current Opinion in Psychology*, 4:21–25.

Fabiana Battista, Tiziana Lanciano, Raffaella Maria Ribatti, and Antonietta Curci. 2026. Malingering depression: a comparative study of human and gpt-3.5 performance. *Current Psychology*, 45(4):379.

Renzo Bianchi, Jay Verkuilen, Sharon Toker, Irvin Sam Schonfeld, Markus Gerber, Elmar Braehler, and Kurt Kroenke. 2022. Is the phq-9 a unidimensional measure of depression? a 58,272-participant study. *Psychological assessment*, 34(6):595.

Callum Chan, Sunveer Khunkhun, Diana Inkpen, and Juan Antonio Lossio-Ventura. 2025. Prompt engineering for capturing dynamic mental health self states from social media posts. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 256–267, Albuquerque, New Mexico. Association for Computational Linguistics.

Fang Fang Chen. 2007. Sensitivity of goodness of fit indexes to lack of measurement invariance. *Structural equation modeling: a multidisciplinary journal*, 14(3):464–504.

Manliang Chen, Yang Wang, and Chao Tan. 2026. Epidemiological trends of depression and anxiety at global, regional, and national level: A population-based observational study from 1990 to 2021 based on global burden of disease 2021. *Medicine*, 105(2):e47094.

Seung W Choi, Laura E Gibbons, and Paul K Crane. 2011. Lordif: An r package for detecting differential item functioning using iterative hybrid ordinal logistic regression/item response theory and monte carlo simulations. *Journal of statistical software*, 39:1–30.

Enrico Cipriani, Pavel Okopnyi, Danilo Menicucci, and Simone Grassini. 2025. In silico development of psychometric scales: Feasibility of representative population data simulation with llms. *arXiv preprint arXiv:2512.02910*.

CG Costello and Andrew L Comrey. 1967. Scales for measuring depression and anxiety. *The Journal of psychology*, 66(2):303–313.

Joost CF de Winter, Tom Driessen, and Dimitra Dodou. 2024. The use of chatgpt for personality research: Administering questionnaires using generated personas. *Personality and Individual Differences*, 228:112729.

Gregorio Ferreira, Jacopo Amidei, Rubén Nieto, and Andreas Kaltenbrunner. 2025. Matching gpt-simulated populations with real ones in psychological studies—the case of the epqr-a personality test. *ACM Transactions on Computing for Healthcare*, 6(2):1–33.

Silvia García-Méndez, Francisco de Arriba-Pérez, Julen Beiro-Suso, and Francisco J González-Castaño. 2026. Real-time anxiety and depression detection by combining large language models and machine learning with explainability capabilities on a user-centric, engaging conversational assistant. *Expert Systems*, 43(4):e70229.

Aura-Nidia Herrera and Juana Gómez. 2008. Influence of equal or unequal comparison group sample sizes on the detection of differential item functioning using the mantel–haenszel and logistic regression techniques. *Quality & Quantity*, 42(6):739–755.

Li-tze Hu and Peter M Bentler. 1999. Cutoff criteria for fit indexes in covariance structure analysis: Conventional criteria versus new alternatives. *Structural equation modeling: a multidisciplinary journal*, 6(1):1–55.

Hyolim Jeon, Dongje Yoo, Daeun Lee, Sejung Son, Seungbae Kim, and Jinyoung Han. 2024. A dual-prompting for interpretable mental health language models. In *Proceedings of the 9th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2024)*, pages 247–255, St. Julians, Malta. Association for Computational Linguistics.

Laura J. Julian. 2011. Measures of anxiety: State-trait anxiety inventory (stai), beck anxiety inventory (bai), and hospital anxiety and depression scale-anxiety (hads-a). *Arthritis Care & Research*, 63(S11):S467–S472.

Kurt Kroenke, Robert L Spitzer, and Janet BW Williams. 2001. The phq-9: validity of a brief depression severity measure. *Journal of general internal medicine*, 16(9):606–613.

Hannah R Lawrence, Renee A Schneider, Susan B Rubin, Maja J Matarić, Daniel J McDuff, and Megan Jones Bell. 2024. The opportunities and risks of large language models in mental health. *JMIR Mental Health*, 11(1):e59479.

Chihao Li and Yue Qi. 2025. Toward accurate psychological simulations: Investigating llms' responses to personality and cultural variables. *Computers in human behavior*, 170:108687.

Hauke Licht, Rupak Sarkar, Patrick Y Wu, Pranav Goel, Niklas Stoehr, Elliott Ash, and Alexander Miserlis Hoyle. 2025. Measuring scalar constructs in social science with llms. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 32132–32159.

June M Liu, Mengxia Gao, Sahand Sabour, Zhuang Chen, Minlie Huang, and Tatia MC Lee. 2025a. Enhanced large language models for effective screening of depression and anxiety. *Communications Medicine*, 5(1):457.

Yunting Liu, Shreya Bhandari, and Zachary A Pardos. 2025b. Leveraging llm respondents for item evaluation: A psychometric analysis. *British Journal of Educational Technology*, 56(3):1028–1052.

Bernd Löwe, Oliver Decker, Stefanie Müller, Elmar Brähler, Dieter Schellberg, Wolfgang Herzog, and Philipp Yorck Herzberg. 2008. Validation and standardization of the generalized anxiety disorder screener (gad-7) in the general population. *Medical care*, 46(3):266–274.

Erfan Loweimi, Sofia de la Fuente Garcia, and Saturnino Luz. 2026. Predicting psychological well-being from spontaneous speech using llms. *arXiv preprint arXiv:2605.11303*.

Sriya Mantena, Anders Johnson, Marily Oppezzo, Narayan Schütz, Alexander Tolas, Ritu Doijad, C Mikael Mattson, Allan Lawrie, Mariana Ramirez-Posada, Paul Schmiedmayer, and 1 others. 2025. Fine-tuning llms in behavioral psychology for scalable health coaching. *NPJ Cardiovascular Health*, 2(1):48.

Summer Mengelkoch, Daniel P. Moriarity, Anne M. Novak, Michael P. Snyder, George M. Slavich, and Shahar Lev-Ari. 2024. Using ecological momentary assessments to study how daily fluctuations in psychological states impact stress, well-being, and health. *Journal of Clinical Medicine*, 13(1):24.

Joon Sung Park, Joseph O'Brien, Carrie Jun Cai, Meredith Ringel Morris, Percy Liang, and Michael S Bernstein. 2023. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th annual acm symposium on user interface software and technology*, pages 1–22.

Adrianos Pavlopoulos, Theodoros Rachiotis, and Ilias Maglogiannis. 2024. An overview of tools and technologies for anxiety and depression management using ai. *Applied Sciences*, 14(19):9068.

Diane L Putnick and Marc H Bornstein. 2016. Measurement invariance conventions and reporting: The state of the art and future directions for psychological research. *Developmental review*, 41:71–90.

Aadesh Salecha, Molly E Ireland, Shashanka Subrahmanya, João Sedoc, Lyle H Ungar, and Johannes C Eichstaedt. 2024. Large language models display human-like social desirability biases in big five personality surveys. *PNAS nexus*, 3(12):pgae533.

Qian Shen, Fanghua Cao, Min Yao, Shlok Gilda, Bonnie J Dorr, and Walter L Leite. 2026. Children's english reading story generation via supervised fine-tuning of compact llms with controllable difficulty and safety. *arXiv preprint arXiv:2605.13709*.

Robert L Spitzer, Kurt Kroenke, Janet BW Williams, and Bernd Löwe. 2006. A brief measure for assessing generalized anxiety disorder: the gad-7. *Archives of internal medicine*, 166(10):1092–1097.

Bin Tan, Nour Armoush, Elisabetta Mazzullo, Okan Bulut, and Mark Gierl. 2025. A review of automatic item generation techniques leveraging large language models. *International Journal of Assessment Tools in Education*, 12(2):317–340.

Yongfeng Tao, Minqiang Yang, Hao Shen, Zhichao Yang, Ziru Weng, and Bin Hu. 2023. Classifying anxiety and depression through llms virtual interactions: a case study with chatgpt. In *2023 IEEE international conference on bioinformatics and biomedicine (BIBM)*, pages 2259–2264. IEEE.

Surendrabikram Thapa, Shuvam Shiwakoti, Siddhant Bikram Shah, Surabhi Adhikari, Hariram Veeramani, Mehwish Nasim, and Usman Naseem.

2025. Large language models (llm) in computational social science: prospects, current state, and challenges. *Social Network Analysis and Mining*, 15(1):4.

Robert J Vandenberg and Charles E Lance. 2000. A review and synthesis of the measurement invariance literature: Suggestions, practices, and recommendations for organizational research. *Organizational research methods*, 3(1):4–70.

Bushi Xiao and Qian Shen. 2026. Personality-driven student agent-based modeling in mathematics education: How well do student agents align with human learners? *arXiv preprint arXiv:2603.21358*.

Shihao Xu, Yiming Yan, Yanli Ding, Feng Li, Shu Zhang, Haoyun Tang, Chao Luo, Yan Li, Hao Liu, Yu Mei, and 1 others. 2025. Identifying psychiatric manifestations in outpatients with depression and anxiety: a large language model-based approach. *npj Mental Health Research*, 4(1):63.

Yuqing Zhao, Wei Qian, Yaru Chen, Donghong Wu, Yujia Luo, Cong Gao, Kankan Wu, and Zhengkui Liu. 2025. Effect of an ai agent trained on a large language model (llm) as an intervention for depression and anxiety symptoms in young adults: A 28-day randomized controlled trial. *Applied Psychology: Health and Well-Being*, 17(5):e70067.

Bruno D Zumbo. 1999. A handbook on the theory and methods of differential item functioning (dif). *Ottawa: National Defense Headquarters*, 160:53.

A Appendix

A.1 Psychometric Results for PHQ-9 and GAD-7

Here we report the full psychometric evaluation results for the sampled human data and the four open-weight LLMs on PHQ-9 and GAD-7.

Table 1: Psychometric evaluation results for the sampled human data and four open-weight LLMs on GAD-7.

Model	SRMR	CFI	TLI	RMSEA	Cronbach's α	Partial Metric	Partial Scalar	DIF Items
Human	0.017	0.972	0.958	0.047	0.97	–	–	–
Llama-3.3-70B	0.088	0.724	0.586	0.364	0.93	Pass	Fail	3
GPT-OSS-120B	0.038	0.926	0.889	0.178	0.94	Fail	Fail	3
Llama-3.1-8B	0.056	0.878	0.817	0.216	0.92	Fail	Fail	5
Mistral-7B	0.051	0.901	0.907	0.173	0.90	Pass	Fail	4

Table 2: Psychometric evaluation results for the sampled human data and four open-weight LLMs on PHQ-9.

Model	SRMR	CFI	TLI	RMSEA	Cronbach's α	Partial Metric	Partial Scalar	DIF Items
Human	0.042	0.931	0.908	0.054	0.84	–	–	–
Llama-3.3-70B	0.060	0.819	0.758	0.272	0.96	Pass	Fail	7
GPT-OSS-120B	0.039	0.919	0.891	0.167	0.96	Fail	Fail	8
Llama-3.1-8B	0.056	0.897	0.863	0.124	0.86	Fail	Fail	8
Mistral-7B	0.057	0.918	0.891	0.151	0.92	Fail	Fail	7

Table 3: Measurement invariance across prompt conditions for LLM-generated GAD-7 responses.

Model	Invariance Level	CFI	TLI	RMSEA	SRMR	ΔCFI	Status
llama-3.3-70b-instruct	Configural	0.658	0.487	0.526	0.129	-	-
llama-3.3-70b-instruct	Metric	0.557	0.453	0.543	0.322	-0.101	Fail
llama-3.3-70b-instruct	Scalar	0.491	0.466	0.536	0.346	-0.066	Fail
gpt-oss-120b	Configural	0.910	0.866	0.218	0.037	-	-
gpt-oss-120b	Metric	0.899	0.876	0.210	0.084	-0.011	Fail
gpt-oss-120b	Scalar	0.850	0.842	0.236	0.099	-0.049	Fail
llama-3.1-8b-instruct	Configural	0.840	0.761	0.266	0.054	-	-
llama-3.1-8b-instruct	Metric	0.809	0.764	0.264	0.119	-0.031	Fail
llama-3.1-8b-instruct	Scalar	0.785	0.774	0.258	0.126	-0.024	Fail
mistral-7b-instruct	Configural	0.869	0.804	0.252	0.050	-	-
mistral-7b-instruct	Metric	0.839	0.802	0.253	0.099	-0.030	Fail
mistral-7b-instruct	Scalar	0.797	0.787	0.262	0.128	-0.042	Fail

Table 4: Measurement invariance across prompt conditions for LLM-generated PHQ-9 responses.

Model	Invariance Level	CFI	TLI	RMSEA	SRMR	ΔCFI	Status
llama-3.3-70b-instruct	Configural	0.718	0.624	0.419	0.106	-	-
llama-3.3-70b-instruct	Metric	0.590	0.524	0.471	0.196	-0.128	Fail
llama-3.3-70b-instruct	Scalar	0.572	0.560	0.453	0.201	-0.018	Fail
gpt-oss-120b	Configural	0.900	0.867	0.212	0.035	-	-
gpt-oss-120b	Metric	0.868	0.847	0.228	0.140	-0.032	Fail
gpt-oss-120b	Scalar	0.826	0.821	0.246	0.151	-0.042	Fail
llama-3.1-8b-instruct	Configural	0.875	0.833	0.145	0.060	-	-
llama-3.1-8b-instruct	Metric	0.838	0.811	0.155	0.107	-0.037	Fail
llama-3.1-8b-instruct	Scalar	0.766	0.759	0.175	0.123	-0.072	Fail
mistral-7b-instruct	Configural	0.921	0.895	0.163	0.051	-	-
mistral-7b-instruct	Metric	0.895	0.878	0.176	0.120	-0.026	Fail
mistral-7b-instruct	Scalar	0.851	0.846	0.197	0.147	-0.044	Fail

A.2 Persona Definitions

To improve methodological transparency without including full implementation details, we summarize here the baseline persona settings used in the prompt construction process for PHQ-9 and GAD-7 generation.

A.2.1 PHQ-9 Persona Definitions

Table 5: Baseline persona definitions used for PHQ-9 response generation.

Persona	Intended severity	Description
Healthy	low symptom level	A completely healthy adult with a regular routine, stable mood, and generally positive outlook on life.
Mild Depression	moderate symptom level	An adult with mild depressive symptoms who occasionally feels tired or down but can still manage daily work and life with effort.
Severe Depression	high symptom level	An adult experiencing a severe major depressive episode, characterized by persistent hopelessness, low energy, loss of interest, and substantial impairment in daily functioning.

A.2.2 GAD-7 Persona Definitions

Table 6: Baseline persona definitions used for GAD-7 response generation.

Persona	Intended severity	Description
Healthy	low symptom level	A completely healthy adult with a regular routine, a calm mind, and little tendency to worry unnecessarily.
Mild Anxiety	moderate symptom level	An adult with mild anxiety who occasionally feels nervous or worries about everyday matters but can still manage daily life.
Severe Anxiety	high symptom level	An adult experiencing severe generalized anxiety, characterized by persistent tension, uncontrollable worry, a sense of impending doom, and substantial impairment in daily functioning.

A.3 Situational Modifiers

In addition to baseline personas, each generation prompt incorporated a short situational modifier sampled from a predefined modifier pool. These modifiers were used to introduce controlled within-person fluctuation while preserving the overall symptom profile implied by the baseline persona.

A.3.1 PHQ-9 Situational Modifiers

Table 7: Situational modifiers used for PHQ-9 response generation.

No.	Modifier text
1	Even though this is your baseline state, you had a relatively peaceful morning today.
2	Your mood has been fluctuating a bit more than usual this week.
3	You've been trying to distract yourself with routines recently, with mixed success.
4	You are just going about an ordinary, uneventful day.
5	You recently had a pleasant but brief interaction with a neighbor.
6	You had a poor night's sleep which is making everything feel a bit more intense today.
7	You are feeling a slight, unexpected shift in your energy levels right now.
8	You feel slightly more easily irritated or distracted than usual today.

A.3.2 GAD-7 Situational Modifiers

A.4 Prompt Assembly Summary

For each generation condition, the final prompt was constructed by combining four components: (1) a baseline persona definition corresponding to the target symptom severity, (2) a short situational modifier drawn from the predefined modifier pool, (3) the questionnaire completion instruction for PHQ-9 or

Table 8: Situational modifiers used for GAD-7 response generation.

No.	Modifier text
1	Even though this is your baseline state, you had a relatively calm morning today.
2	Your anxiety levels have been fluctuating a bit more than usual this week.
3	You just received an ambiguous email from your boss, which is making you overthink.
4	You are just going about an ordinary, uneventful day.
5	You recently had a pleasant and relaxing conversation with a friend.
6	You had too much coffee today, making you feel physically jittery and more restless than usual.
7	You are experiencing a rare, fleeting moment of complete relief right now.
8	You feel slightly more easily startled or on edge than usual today.

GAD-7, and (4) a structured output constraint requiring item-level responses in JSON format. This design allowed us to preserve the overall symptom profile implied by the persona while introducing controlled within-condition variability through the situational modifier.

A.5 Code

The code we used to generate responses to the scales using LLMs is available at the following link https://osf.io/d5wrm/overview?view_only=889cc6bd0aed44659fd5aa2ee98c675a.

Automatic Annotation of Mental Health Recovery Narratives: A Benchmark Study

Shrankhla Pandey[1,2], Graham Murray[1], Ben Laws[1],
Stefan Rennick-Egglestone[3], Mike Slade[3,4] Sarah Morgan[1,2,5],
[1]Department of Psychiatry, University of Cambridge, UK.
[2]Department of Computer Science and Technology, University of Cambridge, UK.
[3]School of Health Sciences, University of Nottingham, UK.
[4]Health and Community Participation Division, Nord University, Norway.
[5]School of Biomedical Engineering and Imaging Sciences, King's College London, UK
Correspondence: sp2147@cam.ac.uk

Abstract

Manual annotation of mental health recovery narratives is slow and emotionally demanding, which limits the scalability of the digital mental health resource. A framework exists to characterise such narratives, called INCRESE, but there are currently no methods to automatically annotate the characteristics defined in INCRESE. We benchmarked the ability of support vector classifiers to annotate INCRESE characteristics when trained with three families of text representations: bag of words, GloVe static embeddings, and BERT contextual embeddings, using a dataset of 355 mental health recovery narratives. Characteristics related to diagnosis and turning points achieved a balanced accuracy greater than 0.67. Characteristics related to content warnings achieved a balanced accuracy of 0.72 but showed poor recall, which may be harmful for readers because it could lead to unsolicited exposure to sensitive content such as abuse or sexual violence. The lived-experience advisors endorsed the project objectives and addressed challenges of characteristic prioritization, adding insights not visible from quantitative metrics alone.

1 Introduction

Mental health recovery narratives can be defined as first-person non-fiction accounts of recovery from mental health issues (Ali et al., 2024); hereby referred to as recovery narratives. Slade et al. (2024) reported that access to online recovery narratives improved the quality of life for people affected by mental health problems. To make such narratives usable at scale, they must be systematically characterized. These characteristics help readers to search for recovery narratives that match their needs and circumstances (Llewellyn-Beardsley et al., 2025).

Conceptual frameworks are used to define such characteristics; one such framework is the Inventory of Characteristics of Recovery Stories (INCRESE) (Llewellyn-Beardsley et al., 2020). It characterizes narratives across multiple dimensions such as tone, trajectory, and content warnings; each INCRESE characteristic has one correct class.

In this paper, we develop the first benchmark for automatic annotation of INCRESE characteristics on a collection of mental health recovery narratives. We report the classification performance on 67 INCRESE characteristics and investigate misclassifications. This work is complemented by input from a group of lived-experience advisors who shared their opinions on the automatic annotation of recovery narratives.

2 Background

2.1 Recovery as a concept

The term 'recovery' is defined in this work as 'a way of living a satisfying life, with or without the continuation of mental health problems' (Research Into Recovery, b). It is grounded in narrator-defined progress and personal growth, rather than only clinical measures such as symptom scores or functional status. Slade et al. (2021) reported that recovery narratives can reinforce the effectiveness of existing clinical practices, by reducing communication barriers and normalizing mental health problems.

2.2 NEON Programme

Narrative Experiences Online (NEON) is a digital mental health intervention designed to deliver lived-experience narratives safely and at scale to the people currently experiencing mental health problems and their informal carers. To facilitate this, the NEON team curated, annotated, and utilized the NEON Collection, which includes recovery narratives sourced from individual donations and public and private collections.

A randomized controlled trial (Slade et al., 2024) of the NEON intervention for people with mental health problems found that access to online

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 100–118
July 4, 2026 ©2026 Association for Computational Linguistics



Figure 1: (a) An example of mental health recovery narrative from the NEON collection. (b) The blue boxes show the results of annotation with the INCRESE characteristics (Chrs) along with their associated higher-level section (underlined): Diagnosis, Content Warnings, Turning Point, and other Narrative characteristics. The story is a part of the NEON collection (Slade et al., 2021)

recovery narratives improved quality of life and increased meaning in life, among individuals with no recent (five-year) history of psychosis.

2.3 INCRESE tool

To make narratives searchable and safe, NEON relies on INCRESE, Inventory of Characteristics of Recovery Stories (Research Into Recovery, a), which defines 77 characteristics spanning narrative eligibility, mode, form, content warnings, turning points, and narrator attributes. Each characteristic has one correct class. INCRESE is intentionally descriptive rather than evaluative: it does not judge the quality or value of a narrative, but summarises how it is told and what it contains.

We focused on predicting 67 INCRESE characteristics from sections 3-7 of INCRESE. The first section, narrative eligibility, was excluded because we only had access to narratives which were eligible for inclusion. The second section, narrative mode, was excluded because it contained items such as whether the narrative contained text, audio or images and we only included text narratives under the scope of this work.

2.4 Annotation

Annotation assigns labels to data. Manual annotation uses human coders following predefined guidelines and is often used as a gold standard, but it is costly and time-consuming. Automatic annotation applies computational methods, such as machine learning, to label data at scale.

Manual annotation of recovery narratives: For the NEON intervention, recovery narratives were manually annotated using a 13-page guide on how to apply the INCRESE framework (Llewellyn-Beardsley et al., 2020). Only Section 5 (Content Warnings) was annotated by at least two coders; disagreements were discussed and resolved, though not documented. All other sections were annotated by a single coder, so inter-rater agreement is not applicable. Figure 1 (b) shows example annotations for the narrative 'Scream in the Sea'.

Need for automatic annotation: Manual annotation of recovery narratives is time-consuming and limits scaling up the collection. It requires coders to engage repeatedly and in depth with first-person accounts of adversity, struggle, and trauma. Such exposure patterns risk producing lasting psychological and emotional harm (Steiger et al., 2021). Longer narratives compound this burden, as annotation time scales with narrative length. In addition, the NEON intervention estimated the total cost of annotation at £21,840, a further breakdown of these costs can be found in Paterson et al.. These practical, psychological, and economic considerations underline the need for scalable, automated approaches to annotation.

3 Methods

Our objective was to systematically investigate the performance of automatic annotation for INCRESE characteristics, and to identify patterns in both the feasibility and failure of automatic annotation.

3.1 Dataset

The NEON collection contains over 600 narratives (NEON Collection). A subset of 357 narratives included consent from the narrators for wider research use and contained text, and this subset was used in our study. For many characteristics, the class distribution was highly imbalanced. This led to under-representation of some classes. We quantified class imbalance for each INCRESE characteristic using the imbalance ratio (He and Garcia, 2009), defined as:

$$\mathrm{IR} = \frac{n_{\text{largest class}}}{n_{\text{smallest class}}}$$

where $n_{\text{largest class}}$ is the number of samples in the largest class and $n_{\text{smallest class}}$ is the number of samples in the smallest class. Higher values of IR indicate greater class imbalance.



Figure 2: **Overview of our methodological pipeline.** (a). Narratives in the NEON collection were drawn from a range of individuals, communities and prior collections. The collection was manually labelled by the coders with INCRESE characteristics. (b). We converted text from the narratives to vectors, using a range of approaches. (c). The text vectors were input into a machine learning classifier to predict the classes of different INCRESE characteristics. (d). On test dataset, we report balanced accuracy. As part of error analysis we reported the confusion matrices.

3.2 Text preprocessing & representation

Some of the 357 narratives were mixed-media, containing images alongside text; in this study, we excluded all images and used only the textual content. After extracting the text, we applied preprocessing steps to remove artefacts including page numbers, special characters and emojis.

We removed two narratives whose lengths exceeded 3σ from the mean narrative length, where σ denotes the standard deviation of narrative length across the full collection. After exclusion, the remaining 355 narratives had a mean length of 1,202 words, with lengths spanning 86 to 3,387 words.



Figure 3: **Histogram of narrative lengths (word counts).** The solid line shows the mean, and dashed lines indicate ±1 standard deviation (σ). The y-axis represents the number of narratives.

To convert text into vectors, we used three types of approaches: bag of words methods, GloVe vector embeddings and BERT embeddings, see Table 1. These methods were chosen for the variety of information they embed and previous success in similar tasks (MacAvaney et al., 2021; Chan et al., 2025; Bucur et al., 2022; Bayram and Benhiba, 2022; Schmidt et al., 2025; Shreevastava and Foltz, 2021). In the first family of methods, bag-of-words, we used two methods: CountVectorizer, TfIdfVectorizer. In the GloVe family, we deployed two having different dimensions: GloVe50d and GloVe300d. In the BERT family, we used three methods: BERT-base, ModernBERT, and SentenceBERT. See Table 1 for a summary and the motivation for the use of these different approaches on our dataset. Using the text vectors extracted, we trained our machine learning classifiers.

3.3 Machine learning classification

Training setup: To benchmark, our focus is on feasibility; hence, we framed annotation for each INCRESE characteristic as an independent supervised text classification task. We first split the $n_{(sample)}$ = 355 narratives in a 3:1 ratio, with $n_{(train)}$ = 267 narratives in the training sample and $n_{(test)}$ = 88 narratives in the test sample. Due to heavy class imbalance, we applied inverse-frequency class weighting, upweighting minority classes proportional to $w_j = \frac{n_{(train)}}{k \cdot n_j}$, where k is the number of classes, and n_j is the number of samples in class j. We ran our experiments using logistic regression, random forest and support vector classifiers (SVC) using scikit-learn (Pedregosa et al., 2011) and observed comparable performance between the three approaches. We only report results from SVC here, for brevity.

For cross-validation, we used the narrative source as a grouping variable to enforce group-aware, stratified five-fold CV. Some sources contain inherent information about certain characteristics; for example, the Schizophrenia Oral History Project includes stories from people diagnosed with schizophrenia or schizoaffective disorder.

Representation	Description	Context window	Dim.	Justification for use in this work
Bag-of-words models (Pedregosa et al., 2011)				
CountVectorizer	Sparse token-count representation over a fixed vocabulary.	ℓ	$\lvert\mathcal{V}\rvert$	Baseline for the novel dataset, assessing lexical separability.
TF–IDF Vectorizer	Term-frequency inverse-document-frequency weighting to down-weight ubiquitous terms.	ℓ	$\lvert\mathcal{V}\rvert$	Reweighted baseline addressing vocabulary imbalance across narratives.
Static embeddings: GloVe (Pennington et al., 2014)				
GloVe (50d)	Pretrained distributional word embeddings derived from global co-occurrence statistics.	ℓ	50	Low-dimensional semantic and static representation; generalizes better than BoW to unseen text.
GloVe (300d)	Higher-dimensional variant capturing finer-grained lexical semantics.	ℓ	300	All benefits of GloVe50d, while testing whether extra representational capacity translates into measurable gains.
Contextual encoders (BERT family)				
BERT (base) (Devlin et al., 2019)	Bidirectional Transformer encoder producing contextualized token representations.	512 tokens	768	Contextual representation baseline for the annotation task.
ModernBERT (Warner et al., 2025)	Efficient long-context Transformer with larger window.	4096 tokens	4096	Long-context modeling of full-length narrative dependencies.
Sentence-BERT (MiniLM) (Reimers and Gurevych, 2019)	BERT fine-tuned for sentence-level embeddings.	512 tokens	384	Sentence-level representation for similarity-based annotation.

Table 1: Text representations explored in this work, their description, and motivations. ℓ denotes input text length; $\lvert\mathcal{V}\rvert$ is the vocabulary size.

We also performed hyperparameter optimization to avoid underfitting or overfitting of the SVC to optimize for balanced accuracy ; namely we tuned *C* [0.1, 1, 10, 100] to control regularization strength, the *kernel* [linear, rbf] to define linear or non-linear decision boundaries, and *gamma* [scale, auto, 0.1, 0.01] to adjust the smoothness of RBF (radial basis function) boundaries.

Evaluation: Given the severe class imbalance observed for many INCRESE characteristics, we evaluated the machine learning classifier performance using balanced accuracy (BA) on the test dataset. BA weights each class equally regardless of prevalence:

$$\mathrm{BA} = \frac{1}{C}\sum_{c=1}^{C}\frac{\mathrm{TP}_c}{\mathrm{TP}_c + \mathrm{FN}_c},$$

where C is the number of classes. For random chance, the expected BA is $1/C$, which provides a clear chance-level baseline.

3.4 Error analysis

Incorrect annotation carries a high risk of harm, especially in our dataset of recovery narratives. For readers, false positives can lead to invalidation. Someone looking for stories "like mine" may instead find narratives with incorrect labels and feel, "Even these people aren't like me.". For narrators, mislabelling can feel like being re-diagnosed without their consent. Missed warnings can cause distress, including dissociation or triggering reactions. For example, if Chr39 (self-harm, including eating disorders) is mislabelled, a reader who wants to avoid this content may still encounter harmful material (Yeo et al., 2021).

We analysed misclassifications using a confusion matrix. Every prediction a model makes is either correct or incorrect, and error can go in one of two directions. A false positive (FP) occurs when the model flags something as present when it is in fact absent, which can set incorrect expectations for the reader. A false negative (FN) occurs when the model misses a present instance and is unable to retrieve a relevant narrative. The false positive rate (FPR) captures how often absent instances are incorrectly flagged. The FPR is calculated by dividing the number of false positives by all cases that are truly absent. It represents how often narratives that lack a characteristic are incorrectly annotated



Figure 4: **Class imbalance across training and test datasets.** Grey bars represent samples in which the characteristic was absent or could not be identified from the narrative, illustrating the extent of class imbalance.

as having it. A high FPR implies that readers are presented with narratives that do not match the requested criteria. The false negative rate (FNR) captures how often present instances are missed. The FNR is calculated by dividing the number of false negatives by all cases that are truly present. It captures how often narratives that contain a characteristic are missed by the model. A high FNR indicates that relevant narratives are omitted from search results, reducing discoverability.

We selected the best performing model (highest BA) to investigate error patterns and report FP, FN, FPR and FNR.

4 Results and Discussion

4.1 Descriptive statistics

Training dataset: Some classes in the characteristics were severely under-represented in the training set (Figure 4), limiting the models' ability to learn stable decision boundaries for these classes. In particular, Chr13, Chr16, Chr17, Chr18, Chr50, Chr55, Chr57, Chr62, Chr66, Chr67, Chr68, Chr69, and Chr71 each contained fewer than three samples for at least one class. Under such extreme scarcity, supervised models fail to learn class representations that could be generalized (Banko and Brill, 2001). This effect is worse for binary-class characteristics, where missing or near-missing representation in one class effectively collapses the learning. We therefore did not train on binary-class characteristics Chr17 and Chr18 (narrator disability: visual and hearing difficulties, respectively).

Test dataset: The test set also contained characteristics that had no samples in at least one class. Specifically, Chr11, Chr16, Chr46, Chr55, Chr57, Chr62, Chr66, Chr67, Chr68, Chr71, Chr72, and Chr74 had zero samples in one of their classes. In these cases, balanced accuracy (BA) is mechanically deflated by 0.25 per missing class, irrespective of classifier behaviour. Chr46 ('Rude awakening') is a binary characteristic with one class missing, so its metrics reflect only a single class; we therefore excluded it from our analysis.

4.2 Machine learning performance

Figure 5 reports performances of SVC: one model per characteristic (64 characteristics) for each text representation method (7 methods), for a total of 448 models. We organise the characteristics by the number of classes. Within each class-count group, we sort characteristics by increasing imbalance ratio (IR), so the most balanced characteristic appears first and the most imbalanced appears last. For example, in the four-class group, Chr58 has (IR=4) while Chr50 has (IR=353).

A key takeaway from Figure 5 is that the seven text representations achieve broadly similar performance overall; no single representation dominates across characteristics. One likely reason is how we construct the BERT-based features. Although BERT models are reported to outperform BoW-based features (Bucur et al., 2022; Bayram and Benhiba, 2022; Schmidt et al., 2025), the BERT representations, by default, used the first (k) tokens (where (k) varies across BERT base, modern, and SentenceBERT; see Table 1). In addition, we used aggregated BERT vectors rather than stacked representations, which may reduce any advantage. A per-characteristic summary of which text representation performs best is provided in Figure 9, in appendix.

Chr19 (Mobility/stamina difficulties) and Chr21 (Self-care difficulties) illustrate the effect of severe class imbalance. Across all seven representations, models correctly predict the negative class but fail

Figure 5: **Machine learning performance for predicting narrative characteristics.** (a) Class imbalance ratios (green: 1–3, yellow: 3–10, red: >10). (b) Balanced accuracies for classifiers using different word representations; white indicates performance below the random chance, whereas progressively darker green shades indicate indicates stronger predictive performance.

to identify positive cases, yielding (BA=0.5). For Chr19, the test set contains only one positive instance; misclassifying this single example reduces balanced accuracy by 0.5, producing (BA=0.5) even when negative instances are handled correctly.

Setting difference between manual and automatic annotation: For manual annotation, coders used a 13-page guide (Recovery, 2025). In a few collections, narratives include photographs of the narrator. This visual context allows coders to directly infer demographic attributes, most notably age (Chr11), gender (Chr12), and ethnicity (Chr13), with relatively low ambiguity. As a result, human annotators operate with both multimodal evidence and task definitions whereas our automatic pipeline uses only text of the narratives. Therefore, discrepancies in performance, especially these characteristics do not solely reflect model error; they also arise from differences in the evidence available.

4.3 Error analysis

Our error analysis focused on two sections: narrator diagnosis and content warnings, as these were the sections where the models performed well enough to allow for a meaningful error analysis. In the remaining sections, model performance was inadequate to draw useful conclusions.

Narrator's Diagnosis: Figure 7 summarizes the confusion matrices for the eight diagnosis-related characteristics, Chr22 through Chr29. Here, we report metrics for each characteristic which had the highest BA. SentenceBERT performed best for 6 out of 8 characteristics, ModernBERT for Chr27, and BERT-base for Chr28.

We achieved specificity (TNR) greater than 0.82 for 7 out of 8 diagnostic characteristics. In these classes, false positives were comparatively rare, suggesting that the model typically avoids assigning a diagnosis when the corresponding condition is not present. Neuro-developmental, eating-related, mood-related, personality-related, obsessive–compulsive, psychosis-related, and trauma-related characteristics show good true-negative performance, reflecting a conservative decision boundary across most diagnoses. The Substance-related characteristic diverges from this pattern, with a substantially lower specificity (TNR = 0.64; TN = 50, FP = 28) but perfect sensitivity (TPR = 1.0; FN = 0).

Several characteristics, such as disorders related to personality, eating or psychosis, score low TPR despite high specificity, indicating that true conditions are sometimes under-detected. The mood-related characteristic, Chr24, is well balanced with IR close to 1 and has comparable sensitivity and



Figure 6: **Average performance for different sections**. #Chr shows the number of characteristics in the respective section.

specificity (both = 0.83), reflecting both its prevalence and the relative separability of its signals. Overall, for diagnosis-related characteristics of the narrator, the selected models minimize false annotations for most diagnoses, except for substance-related disorders.



Figure 7: Confusion matrices for eight diagnostic-related characteristics (Ch22–Ch29).

Content Warnings in the narrative: Figure 8 presents the confusion matrices for the five content-warning characteristics, Chr37 through Chr41. For each characteristic, we report the model achieving the highest BA. Although the average BA for the content-warning section is 0.72 (Figure 6), this aggregate metric does not fully capture the severity of errors. As FN errors are particularly consequential for content warnings, we focus on the false negative rate (FNR). Only two out of five characteristics (Chr38 and Chr40) achieve an FNR below 0.3, indicating that, for several content-warning characteristics, a non-trivial proportion of relevant narratives are not flagged. The strongest performance is observed for Chr38, in where 25% of narratives where the narrator directly experiences or witnesses loss of life or endangerment to life are missed. The weakest performance occurs for Chr37, with an FNR of 0.48, meaning that nearly half of the narratives containing mentions of abuse or sexual violence are labelled as safe.



Figure 8: Confusion matrices for five content warning-related characteristics (Ch37–Ch41).

This behaviour reflects the decision to optimize for balanced accuracy during hyperparameter selection. Balanced accuracy gives equal importance to performance on each class, which provides a consistent basis for comparison across different INCRESE characteristics. However, this objective is not fully aligned with the priorities of the content-warning setting, where false negatives are more costly than false positives.

These results therefore establish a baseline under a general-purpose objective, while also indicating a clear direction for future work: re-optimizing these models using asymmetric loss functions or recall-oriented objectives to better reflect the safety-critical nature of content warnings.

4.4 Lived Experience Advisory Group

Quantitative performance alone does not determine whether automatic annotation is acceptable in practice. We therefore discussed our results with people with lived experience through DATAMIND's Lived Experience Advisory Group (LEAG) (DATAMIND, 2025a,b). We met with seven LEAG members, most of whom had prior experience reading recovery narratives online.

The members endorsed the broad premise and objective of scaling up the recovery narrative collection. They particularly welcomed the idea of using automated systems to detect content warning-related characteristics that appear consistently (72% of narratives contain one or more content warnings), such as mentions of violence, self-harm, or abuse. They further felt that such systems could reduce the emotional strain on coders by handling the initial pass, whilst ensuring that humans verify the final labels. The group did, however, express doubts about automatic annotation of subtler features such as tone, metaphor, identity shifts, and spiritual or existential experiences. Interestingly, our strongest performance (BA=0.86) was observed for spiritual or existential experiences (Chr45).

To understand why, we examined the Fisher ratios for Chr45 using the CountVectorizer model. The Fisher ratio (F) measures how well a word discriminates between classes by comparing the variance between class means to the variance within each class; a higher value indicates a more distinctive and reliable cue. The most discriminative words in the positive class include spiritual (F = 0.45), emergence (F = 0.19), divine (F = 0.17), spirit (F = 0.13), soul (F = 0.13), and consciousness (F = 0.13). These terms are lexically distinctive, providing strong surface-level cues that likely explain why this characteristic proved more tractable than the LEAG had anticipated.

When asked which INCRESE characteristics should be prioritised for automatic annotation, the LEAG advised against prioritisation, citing the likely high level of inter-individual variability in personal experiences of recovery. However, there was consensus that the level of accuracy would be variable. It would need to be strict for some characteristics (e.g. content warnings), whereas for other characteristics there's more room for error (e.g. tone).

This lived-experience panel endorsed the project objectives whilst surfacing challenges of prioritisation and adding insights not visible from quantitative metrics alone.

5 Related work

Much mental health NLP research focuses on detecting or predicting mental health conditions from text, primarily using social media data (Coppersmith et al., 2015; Zirikly et al., 2019; Tsakalidis et al., 2022; Tseriotou et al., 2025; Zanwar et al., 2023; Harrigian et al., 2021). These approaches frame the task as disorder detection and are typically designed to support screening or risk assessment. Recovery narratives differ fundamentally from this paradigm: narrators have already received a diagnosis, and rather than signalling the presence of disorder, their accounts describe long-term recovery processes across existing conditions including depression, anxiety, psychosis, schizophrenia, and personality and neurological disorders. They additionally offer multi-dimensional characterisation encompassing narrative structure, narrator perspective, content themes, and transformative moments. INCRESE was introduced to capture precisely these dimensions. Yet prior to our work, it had not been established how such rich, recovery-specific characteristics could be annotated or predicted at scale.

Previous research (Tian et al., 2024; Bae et al., 2025) has used computational methods for identifying story structure and turning points in fictional narratives; however, these methods have not been applied to mental health recovery narratives, where such elements are indicators of recovery pathways rather than merely narrative devices. Crucially, no prior work has adapted these methods to recovery narratives using a recovery-specific annotation framework.

Finally, although participatory and lived-experience involvement has been increasingly emphasized in mental health and AI research (Patrickson et al., 2023; Thompson et al., 2025), the resulting systems are rarely validated with input from those with lived experience.

This work filled these gaps by introducing an automatic annotation benchmark for recovery narratives grounded in INCRESE, systematically evaluating which recovery characteristics could be reliably predicted, and identifying practical limits to scaling recovery narrative collections.

Conclusion

We established baseline performance for automatic annotation of mental health recovery narratives using support vector classifiers. Our results show balanced accuracy above 0.8 for 6 INCRESE characteristics across diagnosis (4), content warnings (1), and turning points (1) but varies highly across sections and characteristics. Researchers considering automated characterisation should select optimisation metrics carefully, as different sections carry different misclassification consequences.

Limitations

The dataset size is relatively small for machine learning studies, which limits model learning and performance. While the dataset cannot be publicly released under its licence terms, we have provided dataset descriptions and a detailed evaluation protocol to mitigate reproducibility concerns.

In extracting text representations, we aggregate BERT family embeddings into fixed-length representations, which may dilute signal strength and potentially explain why these advanced models performed comparably to simpler models. This aggregation strategy may not optimally capture the

sequential and contextual information that transformer models are designed to encode.

The human coders had access to images as well as text, whereas ML algorithms only had access to text. Therefore the accuracies obtained by ML algorithms should be considered as a minimum achievable accuracy.

This work is the first benchmark study for automatic INCRESE annotation; further work is required to bring it closer to practical deployment in real-world settings for e.g. achieving higher recall for characteristics like content warnings, but precise thresholds have not been established. Development of large language models (LLMs) could be a fruitful avenue for further research. However, in our future work, we determine the ceiling performance that humans can achieve in annotating a subset of mental health recovery narratives from the NEON collection. More importantly we will examine which INCRESE characteristics are inherently subjective, with the aim of showing where automatic annotation could be trusted.

Ethics

Ethical approval for the curation of the Narrative Experiences Online (NEON) Collection was received from the London - West London and Gene Therapy Advisory Committee Research Ethics Committee in advance (18/LO/0991) on 9th July 2018. Specific consent for secondary data analysis has been documented for all NEON Collection narratives used in the current study. Nottinghamshire Healthcare NHS Foundation Trust were the sponsor for the NEON study. The sponsor approved the dataset licenses used to establish the terms of sharing NEON Collection narratives for the secondary analysis in the current study. Signed dataset licenses were in place before the transfer of narratives and narrative metadata for the purpose of secondary analysis.

Acknowledgments

The authors are grateful to the narrators who courageously shared their recovery journeys and granted permission for their stories to be used in this research, to the NEON team, and to the DATAMIND Lived-Experience Advisory Group. S.P. gratefully acknowledges PhD funding from the W.D. Armstrong Trust and both S.P. and S.M. received funding from the Accelerate Programme for Scientific Discovery, funded by Schmidt Futures. B.L. was supported by ImmunoMIND, UKRI. S.R.E. and M.S. were supported by the National Institute for Health and Care Research (NIHR) Nottingham Biomedical Research Centre (BRC) (NIHR203310). G.M. was supported by the NIHR Cambridge Biomedical Research Centre (NIHR203312) and the NIHR Applied Research Collaboration East of England.

References

Yasmin Ali, Stefan Rennick-Egglestone, Joy Llewellyn-Beardsley, Fiona Ng, Caroline Yeo, Donna Franklin, Elvira Perez Vallejos, Dror Ben-Zeev, Yasuhiro Kotera, and Mike Slade. 2024. Perception and appropriation of a web-based recovery narratives intervention: qualitative interview study. *Frontiers in Digital Health*, Volume 6 - 2024.

Suyoung Bae, Gunhee Cho, Yun-Gyung Cheong, and Boyang Li. 2025. CharMoral: A character morality dataset for morally dynamic character analysis in long-form narratives. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 8809–8818, Abu Dhabi, UAE. Association for Computational Linguistics.

Michele Banko and Eric Brill. 2001. Scaling to very very large corpora for natural language disambiguation. In *Proceedings of the 39th Annual Meeting of the Association for Computational Linguistics*, pages 26–33, Toulouse, France. Association for Computational Linguistics.

Ulya Bayram and Lamia Benhiba. 2022. Emotionally-informed models for detecting moments of change and suicide risk levels in longitudinal social media data. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 219–225, Seattle, USA. Association for Computational Linguistics.

Ana-Maria Bucur, Hyewon Jang, and Farhana Ferdousi Liza. 2022. Capturing changes in mood over time in longitudinal data using ensemble methodologies. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 205–212, Seattle, USA. Association for Computational Linguistics.

Callum Chan, Sunveer Khunkhun, Diana Inkpen, and Juan Antonio Lossio-Ventura. 2025. Prompt engineering for capturing dynamic mental health self states from social media posts. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 256–267, Albuquerque, New Mexico. Association for Computational Linguistics.

Glen Coppersmith, Mark Dredze, Craig Harman, Kristy Hollingshead, and Margaret Mitchell. 2015. CLPsych 2015 shared task: Depression and PTSD

on Twitter. In *Proceedings of the 2nd Workshop on Computational Linguistics and Clinical Psychology: From Linguistic Signal to Clinical Reality*, pages 31–39, Denver, Colorado. Association for Computational Linguistics.

DATAMIND. 2025a. Datamind: Better mental health through data-driven research. https://datamind.org.uk/. Accessed: 2026-01-22.

DATAMIND. 2025b. Lived experience advisory group. https://datamind.org.uk/patients-and-public/lived-experience-advisory-group/. Accessed: 2026-01-22.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186. Association for Computational Linguistics.

Keith Harrigian, Carlos Aguirre, and Mark Dredze. 2021. On the state of social media data for mental health research. In *Proceedings of the Seventh Workshop on Computational Linguistics and Clinical Psychology: Improving Access*, pages 15–24, Online. Association for Computational Linguistics.

Haibo He and Edwardo A. Garcia. 2009. Learning from imbalanced data. *IEEE Transactions on Knowledge and Data Engineering*, 21(9):1263–1284.

Joy Llewellyn-Beardsley, Yasmin Ali, Sylvia Bailey, Susie Booth, Paul Davis, Caroline Fox-Yeo, Donna Franklin, Julian Harrison, David King, Chris Newby, Fiona Ng, Scott Pomberth, Stefan Rennick-Egglestone, Dan Robotham, Roger Smith, Rianna Walcott, and Mike Slade. 2025. Lived experience narratives for mental health recovery: the narrative experiences online (neon) programme. Programme summary, Institute of Mental Health, University of Nottingham, Nottingham, UK.

Joy Llewellyn-Beardsley, Skye Barbic, Stefan Rennick-Egglestone, Fiona Ng, James Roe, Ada Hui, Donna Franklin, Emilia Deakin, Laurie Hare-Duke, and Mike Slade. 2020. INCRESE: Development of an inventory to characterize recorded mental health recovery narratives. *J. Recovery Ment. Health*, 3(2):25–44.

Sean MacAvaney, Anjali Mittu, Glen Coppersmith, Jeff Leintz, and Philip Resnik. 2021. Community-level research on suicidality prediction in a secure environment: Overview of the CLPsych 2021 shared task. In *Proceedings of the Seventh Workshop on Computational Linguistics and Clinical Psychology: Improving Access*, pages 70–80, Online. Association for Computational Linguistics.

NEON Collection. Neon collection. https://www.researchintorecovery.com/research/neon/neoncollection/.

Luke Paterson, Stefan Rennick-Egglestone, Sean P. Gavan, Mike Slade, Fiona Ng, Joy Llewellyn-Beardsley, Carmel Bond, Andrew Grundy, Joe Nicholson, Dania Quadri, Sylvia Bailey, and Rachel A. Elliott. 2022. Development and delivery cost of digital health technologies for mental health: Application to the narrative experiences online intervention. *Frontiers in Psychiatry*, Volume 13 - 2022.

Bronwin Patrickson, Mike Musker, Dan Thorpe, Yasmin van Kasteren, Niranjan Bidargaddi, The Consumer, and Carer Advisory Group (CCAG). 2023. In-depth co-design of mental health monitoring technologies by people with lived experience. *Future Internet*, 15(6).

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, and et al. 2011. Scikit-learn: Machine learning in python. *Journal of Machine Learning Research*, 12:2825–2830.

Jeffrey Pennington, Richard Socher, and Christopher D. Manning. 2014. Glove: Global vectors for word representation. In *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 1532–1543.

Research Into Recovery. 2025. Increse.

Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*.

Research Into Recovery. a. Increse – inventory of characteristics of recovery stories: measure to characterise mental health recovery narratives. https://www.researchintorecovery.com/measures/increse/.

Research Into Recovery. b. Neon definitions: Key terms used in the narrative experiences online (neon) study. https://www.researchintorecovery.com/research/neon/definitions/.

Fabian Schmidt, Karin Hammerfald, Henrik Haaland Jahren, and Vladimir Vlassov. 2025. CFiCS: Graph-based classification of common factors and microcounseling skills. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 106–115, Albuquerque, New Mexico. Association for Computational Linguistics.

Sagarika Shreevastava and Peter Foltz. 2021. Detecting cognitive distortions from patient-therapist interactions. In *Proceedings of the Seventh Workshop on Computational Linguistics and Clinical Psychology: Improving Access*, pages 151–158, Online. Association for Computational Linguistics.

Mike Slade, Stefan Rennick-Egglestone, Joy Llewellyn-Beardsley, Caroline Yeo, James Roe, Sylvia Bailey, Roger Andrew Smith, Susie Booth, Julian Harrison, Adaresh Bhogal, Patricia Penas Morán, Ada Hui, Dania Quadri, Clare Robinson, Melanie Smuk, Marianne Farkas, Larry Davidson, Lian van der Krieke, Emily Slade, and 7 others. 2021. Recorded mental health recovery narratives as a resource for people affected by mental health problems: Development of the narrative experiences online (neon) intervention. *JMIR Form Res*, 5(5):e24417.

Mike Slade, Stefan Rennick-Egglestone, Felix Ng, Jenny Yiend, Nicola Jones, Eleanor Longden, Victoria J. Bird, Mary Leamy, Jesper Larsen, Shaz Ali, Larry Davidson, Adam Bell, and Sarah Byford. 2024. Effectiveness and cost-effectiveness of providing recorded mental health recovery narratives to people with non-psychosis mental health problems (neon-o trial): A multicentre, parallel-group, superiority, randomised controlled trial. *The Lancet Regional Health – Europe*, 38:100805.

Miriah Steiger, Timir J. Bharucha, Sukrit Venkatagiri, Martin J. Riedl, and Matthew Lease. 2021. The psychological well-being of content moderators: The emotional labor of commercial moderation and avenues for improving support. In *Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems (CHI '21)*, pages 1–14, New York, NY, USA. Association for Computing Machinery.

Alexandra Thompson, Victoria Bartle, Elizabeth A Remfry, Duncan J Reynolds, Michael R Barnes, Nick J Reynolds, and Barbara Hanratty. 2025. Public and patient involvement in artificial intelligence and big data healthcare research: An exploration of issues and challenges within the AI-Multiply project. *Health Expect.*, 28(6):e70490.

Yufei Tian, Tenghao Huang, Miri Liu, Derek Jiang, Alexander Spangher, Muhao Chen, Jonathan May, and Nanyun Peng. 2024. Are large language models capable of generating human-level narratives? In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 17659–17681, Miami, Florida, USA. Association for Computational Linguistics.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Athanasia Tseriotou, Nikolaos Douzas, Molly Ireland, Ayah Zirikly, Dongji Yoo, Carlos Aguirre, Keith Harrigian, and Mark Dredze. 2025. Overview of the CLPsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the Eleventh Workshop on Computational Linguistics and Clinical Psychology*, pages 177–195, Abu Dhabi, UAE. Association for Computational Linguistics.

Benjamin Warner, Antoine Chaffin, Benjamin Clavié, Orion Weller, Oskar Hallström, Said Taghadouini, Alexis Gallagher, Raja Biswas, Faisal Ladhak, Tom Aarsen, Nathan Cooper, Griffin Thomas Adams, Jeremy Howard, and Iacopo Poli. 2025. Smarter, better, faster, longer: A modern bidirectional encoder for fast, memory efficient, and long context finetuning and inference. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 2526–2547.

Caroline Yeo, Stefan Rennick-Egglestone, Victoria Armstrong, Marit Borg, Donna Franklin, Trude Klevan, Joy Llewellyn-Beardsley, Christopher Newby, Fiona Ng, Naomi Thorpe, Jijian Voronka, and Mike Slade. 2021. Uses and misuses of recorded mental health lived experience narratives in healthcare and community settings: Systematic review. *Schizophrenia Bulletin*, 48(1):134–144.

Swamy Rakshith Zanwar, Daniel Wiechmann, Yuan Qiao, and Elma Kerz. 2023. SMHD-GER: A large-scale benchmark dataset for automatic mental health detection from social media in German. In *Findings of the Association for Computational Linguistics: EACL 2023*, pages 1538–1557, Dubrovnik, Croatia. Association for Computational Linguistics.

Ayah Zirikly, Philip Resnik, Özlem Uzuner, and Kristy Hollingshead. 2019. CLPsych 2019 shared task: Predicting the degree of suicide risk in Reddit posts. In *Proceedings of the Sixth Workshop on Computational Linguistics and Clinical Psychology*, pages 24–33, Minneapolis, Minnesota. Association for Computational Linguistics.

A Best word representations for each characteristic



Figure 9: For each characteristic we show the model trained on the word representation having highest balanced accuracy.

B Description of all 67 INCRESE characteristics.

Table 2: Narrator's Demography characteristics.

Chr	Characteristic	Class
Chr11	Gender	0 = not identifiable 1 = female 2 = male 3 = other; Answer 'other' if the narrator identifies as e.g. trans, transgender, non-binary or any other gender identity.
Chr12	Age	0 = not identifiable 1 = 0–25 2 = 26–40 3 = 41–65 4 = 66+
Chr13	Ethnicity	0 = not identifiable 1 = Asian including Indian, Pakistani, Bangladeshi, Chinese 2 = African; Caribbean or any other Black, African or Caribbean background 3 = Dual/multiple ethnic group; Black, Caribbean and White; Black African and White; Asian and White, or any other dual or multiple ethnic background. 4 = Other ethnic group including Arab 5 = White including English, Welsh, Scottish, Northern Irish, British, Irish, Gypsy or Irish Traveller
Chr14	Stage of recovery	0 = Not identified; 1 = Working on recovery; Rebuilding/action/maintenance & growth stage: active engagement, rebuilding life, living beyond disability. 2 = Thinking about recovery; Awareness/contemplation/preparation stage: re-awakening of hope, awareness of dependency, making a decision to rebuild life. 3 = Not yet thinking about recovery; Moratorium/pre-contemplative stage: not currently engaged in thinking about or working towards recovery or wellbeing. 4 = Rejects recovery; Narrator explicitly rejects the concept of 'recovery' as used in mental health services.
Chr15	Location of narrator	0 = not identifiable 1 = Africa 2 = Asia 3 = Australasia 4 = Europe 5 = North America 6 = South America
Chr16	Sexuality	0 = not identified by the narrator 1 = Bisexual 2 = Gay man 3 = Heterosexual 4 = Lesbian/gay woman 5 = Other

Table 3: Narrator's Disability characteristics.
Each item is annotated as 0 = not identified, 1 = yes.

Chr	Characteristic	Description
Chr17	Visual difficulties	Blindness or partial sight. Do not tick solely based on narrator wearing glasses.
Chr18	Hearing difficulties	Deafness or partial hearing.
Chr19	Mobility / stamina difficulties	Difficulty e.g. walking, climbing stairs, lifting and carrying, or stamina or breathing difficulties.
Chr20	Cognitive difficulties	Difficulties with learning (e.g. intellectual disabilities), remembering (e.g. due to dementia), or concentrating.
Chr21	Self-care difficulties	Difficulty with self-care such as washing or dressing.

Table 4: Narrator's Diagnosis characteristics.
Each item is annotated as 0 = not identified, 1 = yes.

Chr	Characteristic	Description
Chr22	Neuro-developmental	e.g. Autism spectrum (ASD), Asperger's syndrome.
Chr23	Eating or food-related	e.g. anorexia, binge eating, bulimia.
Chr24	Mood-related	e.g. anxiety, bipolar 1 and 2, cyclothymia, depression, dysthymia, manic episodes, panic attacks, phobias, post-natal depression (PND).
Chr25	Personality-related	e.g. borderline personality disorder (BPD), narcissistic personality disorder, paranoid personality disorder.
Chr26	Obsessive-compulsive related	e.g. obsessive-compulsive disorder (OCD), body dysmorphic disorder.
Chr27	Schizophrenia or other psychosis-related	e.g. schizophrenia, delusional disorder, schizo-affective disorder, hearing voices.
Chr28	Trauma/stress-related	e.g. adjustment disorder, acute stress disorder, post-traumatic stress disorder (PTSD).
Chr29	Substance-related	e.g. problematic use of alcohol, cannabinoids, cocaine, other stimulants, opioids, hallucinogens, sedatives, solvents.
Chr30	Uses a non-diagnostic framework	Actively rejects use of diagnosis OR uses other terms instead of referring to diagnosis, such as hearing voices, trauma-based distress, being a survivor of services, self-identifies as Mad, OR uses an alternative explanatory framework, such as spiritual emergency. Do not tick just because items 22 to 29 are not ticked.

Table 5: Narrative characteristics.

Chr	Characteristic	Class
Chr31	Genre	1 = Escape; Main focus is on narrator's escape from or resistance to factors identified as preventing their recovery, e.g. difficult family or other circumstances, damaging or unhelpful services/treatment, forms of injustice, disputed diagnosis, rejection of diagnostic framework. 2 = Endurance; Main focus is on narrator's survival and ability to keep going despite prolonged conditions of e.g. distress, loss, trauma or difficult circumstances. Circumstances may be ongoing or in the past.

Chr	Characteristic	Class
		3 = Endeavour; Main focus is on narrator's ways of maintaining their recovery or achieving wellbeing, e.g. activities/attitudes/learning/relationships which help, ways of managing or restoring order, achievements or attaining goals. 4 = Enlightenment; Main focus is on narrator's transformation of their understanding or perspective of their situation, e.g. finding a new explanatory framework; their own empowerment or self-actualisation; a quest or journey of exploration; a sense of redemption through something greater than self, either humanistic or spiritual.
Chr32	Positioning	1 = Within services; Mental health treatments/services described on the whole as positive factors in narrator's recovery e.g. through treatments or services that worked, having positive relationships with mental health workers, or through delivering services (e.g. employment as a peer support worker). 2 = Despite services; Mental health treatments/services described on the whole as negative factors in narrator's recovery, actively preventing recovery or making mental health distress worse e.g. abusive treatment, negative staff attitudes, loss of rights or dignity. 3 = Outside the services; Mental health treatments/services are not mentioned, e.g. narrator recovered through other means, or accessed alternative treatments/services; or they feature only minimally e.g. narrator found treatments/services neutral or ineffective but not damaging.
Chr33	Tone	1 = Upbeat; Positive states e.g. buoyant, content, hopeful, proud, optimistic, reflective. 2 = Downbeat; Negative states e.g. agitated, apologetic, frenetic, pessimistic, sad, shaken, self-critical. 3 = Critical; Provocative or stimulating, e.g. angry, challenging, defiant, protesting. 4 = Neutral; Flat, e.g. matter of fact, disenfranchised, resigned, e.g. 'this is just how it is'.
Chr34	Relationship with recovery	1 = Living well; Recovery/sense of wellbeing is described as well-established, e.g. narrator is mainly experiencing wellness, is confident that future mental health problems will be manageable. 2 = Making progress; Recovery/sense of wellbeing is described as improving e.g. narrator is experiencing wellness and also regularly experiencing times of distress, is fearful that future mental health problems may not be manageable. 3 = Surviving day to day; Recovery/sense of wellbeing is described as challenging or tentative, e.g. narrator is focused on getting through a situation, is persistent in the face of very difficult circumstances, expects mental health problems to continue in the future. 4 = Recovered; Mental health problems are described mainly in the past tense, e.g. narrator does not expect to experience them in future; speaks of 'being recovered'. 5 = Rejects recovery; Narrator rejects the concept of 'recovery' as used in mental health services.
Chr35	Trajectory	1 = Upward; Shape of the narrative overall is an ascending progression towards recovery or wellbeing. Narrative may contain setbacks/periods of distress but focus is on progression.

Chr	Characteristic	Class
		2 = Up and down; Shape of the narrative overall is one of both upturns towards health/wellbeing and downturns towards distress. Ups and downs may be dramatic/roller-coaster changes or more drawn out over time but narrative is more or less equally distributed between ups and downs. 3 = Horizontal; Shape of the narrative overall contains no significant upwards or downturns, e.g. narrator may describe a sense of stagnating or taking one day at a time.
Chr36	Use of metaphor or symbolic language	0 = Unidentified 1 = Yes; If the narrative contains text or speech, is metaphorical or symbolic language used? Select yes for all image-based narratives. 2 = No

Table 6: Content Warning characteristics.
Each item is annotated as 0 = not identified, 1 = yes.

Chr	Characteristic	Description
Chr37	Abuse or sexual violence	Direct experiences or witnessing of any form of sexual, physical or emotional abuse, neglect, partner/domestic violence or acts of sexual violence, including e.g. rape or attempted rape, sexual assault, female genital mutilation (FGM), modern slavery, sex trafficking, child sexual exploitation, subjection to pornography or witnessing sexual acts, unlawful/inappropriate use of restraint, misuse of medication (e.g. over-sedation), forcible feeding or withholding food, enforced social isolation (preventing someone from e.g. accessing services or seeing friends), bullying, coercion, cyber-bullying, harassment, humiliation, intimidation, use of threats, verbal abuse.
Chr38	Loss of life or endangerment to life	Direct experiences or witnessing of e.g. admission to intensive care, bereavement, diagnosis of a life-threatening condition, loss of pregnancy, natural disaster, serious accident, suicide or attempted suicide, terrorist attack, torture, traumatic birth, traumatic termination of pregnancy, violent death of another, being threatened with a weapon, war/military combat.
Chr39	Self-harm including eating disorders	Direct experiences or witnessing of e.g. deliberate injury or harm to oneself, neglect of self, alcohol or substance misuse, eating disorder-related behaviours.
Chr40	Violence or aggression	Direct experiences or witnessing of e.g. acts of aggression, fights, rioting. .
Chr41	Injustice, prejudice and discrimination	Direct experiences, witnessing of or reference to e.g. hate speech, prejudice or discriminatory actions/behaviours/decisions on the basis of e.g. colour, disability, ethnic origin, gender identity, nationality, race, religion, sexual orientation. Experiences may be at individual/interpersonal level, organisational/institutional level (e.g. mental health services, prisons) or systematic/structural level (historical, cultural, legal, political or economic systems).

Table 7: Characteristics related to turning points in the narratives.
Each item is annotated as 0 = not identified, 1 = yes.

Chr	Characteristic	Description
Chr42	Taking charge	Change after taking charge e.g. of own illness, recovery process, problematic substance use, or own life generally. May be sudden and decisive or a longer process. May be accepting or rejecting help or treatment e.g. deciding to take or stop medication.
Chr43	Interventions/ support from others	Change after e.g. accessing helpful medication, treatment, groups or services (whether directly mental health-related or not), receiving support from family or friends, being confronted by family or friends.
Chr44	Self-acceptance	Change after e.g. an increase in confidence, growth in self-awareness, emotional release, moving away from internalised stigma. This may occur through own learning/inner work, involvement with support or other groups, or counselling/therapy.
Chr45	Spiritual/ existential experience	Change after e.g. finding a sense of meaning/purpose, experiencing a large shift in perspective, joining a spiritual/religious community, undertaking spiritual practices, conversion experiences, dreams, positive visions, being prayed for, support of a guide/teacher.
Chr46	'Rude awakening'	Change after a shock or realising how bad things have become, e.g. being admitted to hospital, being moved to a long-term ward, seeing negative effects on family members, the death of someone close, a suicide attempt.
Chr47	Shift in identity	Change after reclaiming a stigmatised identity e.g. based on ethnicity, gender, sexuality, mental health status. This may occur through finding others with similar experiences, own learning, own inner work or becoming involved in activism.

Table 8: Characteristics related to narrative content.
Each item is annotated as 0 = Not present, 1 = Present, 2 = Mainly positive, 3 = Mainly negative

Chr	Characteristic	Description
Chr48	Pregnancy/birth	Positive examples: wanted pregnancy, pregnancy as upward turning point Negative examples: traumatic pregnancies/birth experiences, unwanted pregnancy, abortion, post-natal difficulties, difficulties with getting pregnant or ability to have children.
Chr49	Family	Positive example: emotional or practical support or care from family members, relationships with family as source of happiness or resilience Negative examples: own or parents' divorce, separation, relationship breakdown or ongoing conflict, death or loss in the family.
Chr50	Being in care	Positive or negative experiences of adoption, living in foster care or non parental care.
Chr51	Education	Positive examples: having positive opportunities for learning/training, engaging in self-education/self-help. Negative examples: difficulties in school, school refusal, being excluded, not enjoying school being required to attend a course.
Chr52	Friendships	Positive examples: support of friends. Negative examples: breakdown of friendships, loneliness, social isolation, death of a loved one.
Chr53	Relationships	Positive examples: supportive partner, new relationship bringing hope. Negative examples: difficulties or conflict with partner.
Chr54	Housing	Positive examples: having own home, home being a source of pride or sanctuary. Negative examples: being vulnerably housed or homeless

Chr	Characteristic	Description
Chr55	Income	Positive examples: income enabling choices, improvement in income. Negative examples: debt, financial difficulties, poverty, experience of the benefits system.
Chr56	Work	Positive examples: providing meaning and purpose, developing positive identity. Negative examples: burnout, work-related stress, unstable employment, unemployment, unwanted retirement.
Chr57	Criminal Justice System	Positive examples: prison providing security, a turning point or opportunities. Negative examples: being arrested, being in prison or young offenders' institution, family member being in prison.
Chr58	Diagnosis	Positive examples: makes sense of a situation, is a relief, provides answers or sense of hope. Negative examples: disagreement with diagnosis, feeling stigmatised, loss of hope.
Chr59	Medication	Positive examples: felt better, relief, hope. Negative examples: felt worse, did not help, was not voluntary, had unwanted side effects.
Chr60	Relationship with mental health professional	Positive or negative experiences of relationships with e.g. community mental health team worker, crisis team, mental health nurse, psychiatrist, psychologist, social worker.
Chr61	Peer support	Positive or negative experiences of providing or receiving individual or group-based peer support. May be formal e.g. within mental health services or recovery colleges, or informal e.g. from support groups such as AA, Depression Alliance, Hearing Voices Network.
Chr62	Involuntary use of mental health services	Positive or negative experiences of experiences of e.g. being sectioned in hospital, compulsory medication, community treatment orders.
Chr63	Hospitalization	Positive or negative experiences of voluntary or involuntary psychiatric hospitalisation.
Chr64	psychological services	Positive or negative experiences of experiences receiving or delivering talking therapies or counselling e.g. arts or creative, CBT, DBT, group therapy, psychotherapy, person-centred, psychoanalytic, psychodynamic, solution-focused.
Chr65	Alternative therapies/healing	Positive or negative experiences of e.g. acupuncture, homeopathy, massage, meditation, Reiki, traditional Chinese medicine (TCM).
Chr66	Being in natural environments	Positive or negative experiences of the natural environment or outdoor activities, green therapy.
Chr67	Animals or pets	Positive or negative experiences of contact with animals including with therapy / emotional support dog, or care of a pet.
Chr68	Community activities	Positive or negative experiences of engagement with community-based groups or organisations, whether or not mental health-related.
Chr69	Hobbies, interests, creative activities	Positive or negative experiences of leisure activities, hobbies, recreational interests or creative activities e.g. art, crafts, music (listening or playing), performance, reading, dance, writing.
Chr70	Physical activities	Positive examples: gaining or maintaining fitness, being involved in sports or other physical activities. Negative examples: being unable to participate in such activities, participation leading to feeling worse.
Chr71	Activism	Positive examples: participation in political or other activities to achieve change in a group, organisation, service or system. Negative examples: participation in the above leading to e.g. burnout, being overwhelmed.

Chr	Characteristic	Description
Chr72	Spiritual or religious activities	Positive examples: attending a religious/spiritual community, group or place of worship, articipating in spiritual practices e.g. prayer, meditation, retreats. Negative examples: above activities as compulsory or contributing to mental health distress.
Chr73	Stigma	Positive examples: rejecting or overcoming stigma or shame due to mental health issues or for other reasons, e.g. ethnicity, gender. Negative examples: experiencing disapproval of others, or own shame due to mental health issues or other reasons.
Chr74	Caring responsibilities	Positive example: care of someone else giving a sense of pride. Negative example: care of someone else worsening own mental health problems.
Chr75	Family experiences of mental health issues	Positive example: mental health issues of other family members leads to a shared sense of understanding. Negative example: mental health issues of other family members has detrimental effect on narrator's own mental health.
Chr76	Diet or nutrition	Positive or negative experiences of diet or nutrition linked to improving, maintaining or worsening narrator's mental health.
Chr77	Volunteering	Positive or negative experiences of any unpaid work.

Before the Labels: How Dataset Construction Shapes Suicidality Detection in Clinical Text

Priyanshi Garg[†*], **Ishita Rao**[†*], **Jieqiong Ding**[‡*], **Amandalynne Paullada**[†]
[†]Department of Linguistics, University of Washington, Seattle, WA, USA
[‡]Human Centered Design & Engineering, University of Washington, Seattle, WA, USA
{pgarg2, ishirao, jding07, paullada}@uw.edu

Abstract

Clinical NLP increasingly relies on electronic health record (EHR) data to detect suicidal behaviors, treating clinical documentation as more reliable ground truth than social media. We argue that this framing obscures how EHR-based suicidality datasets encode a particular operationalization of suicidality, shaped by who authors the data, how episodes are bounded, and how ambiguity is resolved. We ground this argument in a case study of the ScAN dataset (Rawat et al., 2022), built over MIMIC-III clinical notes. We show how governance constraints, ICD-based cohort selection, single-annotator labeling, and hospital-stay-level aggregation produce labels that reflect clinician-documented judgments, treat suicidality as a bounded episode, and assume that intent can be reliably inferred from documentation. A linguistic analysis demonstrates that identical labels subsume heterogeneous clinical framings differing in temporality, negation, and uncertainty. We argue that clinical NLP should examine the assumptions embedded in suicidality datasets before interpreting their labels as ground truth.

1 Introduction

Suicide is a leading cause of death worldwide, and detecting suicidal behavior from text is a high-stakes task in clinical NLP. Recent work has increasingly turned to electronic health records (EHRs) as a data source, motivated by well-documented concerns with social media data around consent, self-report reliability, and generalization (Chancellor et al., 2019; Ernala et al., 2019; Harrigian et al., 2021). EHRs offer structured clinical documentation, multi-source corroboration, and longitudinal patient histories.

However, systematic reviews have found that predictive models for suicide perform only marginally better than chance across a range of clinical settings (Belsher et al., 2019; Franklin et al., 2017; Large et al., 2016). This poor predictive performance warrants scrutiny of, among other factors, the training data and the assumptions encoded within the labels. EHRs should not be treated as direct access to suicidality itself. Clinical notes are documentation-mediated records: they synthesize patient report, clinician observation, prior records, collateral information, institutional requirements, and risk-management practices. This mediation is especially important for suicidality, where disclosure and documentation depend on the clinical interaction in which risk is assessed. Prior work shows that healthcare professionals vary in how they ask about suicide risk, including question designs that may invite denial or reduce elaboration (McCabe et al., 2017). Mental health professionals also vary in how consistently they assess suicidal thoughts and behaviors, with assessment practices shaped in part by comfort working with suicidal individuals (Roush et al., 2018). Thus, the absence, presence, or wording of suicidality evidence in EHR text reflects both clinical phenomena and the conditions under which those phenomena become documented.

Prior work has also examined ethical tensions in mental health inference, demographic bias in diagnosis and clinical documentation, and documentation quality in clinical NLP. For example, racial disparities in psychiatric diagnosis can shape what enters the clinical record (Schwartz, 2014), and stigmatizing language in EHR notes has been shown to vary across patient groups (Sun et al., 2022). These concerns are often treated separately. We propose *operationalization* as a unifying lens: dataset construction decisions collectively determine what counts as evidence, how it is categorized, what distinctions are preserved, and what forms of uncertainty are collapsed.

Our position is that EHR-based suicidality

[*]Equal contribution.

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 119–127
July 4, 2026 ©2026 Association for Computational Linguistics

datasets encode a specific operationalization of suicidality:

> *Documentation-mediated*, reflecting suicidality as represented in clinician-authored records rather than as an unmediated patient state; *episodic*, bounding suicidality to discrete hospital stays rather than modeling it as a longitudinal process; and *intent-resolved*, imposing binary distinctions between suicidal and non-suicidal self-harm even when the clinical text is ambiguous.

This is not an argument that clinical documentation is unreliable, nor that patient self-report is a bias-free alternative. Suicidality assessment is clinically difficult, relational, and uncertain. Rather, our claim is that when clinical documentation is converted into NLP labels, those labels should be interpreted as structured operationalizations of documented clinical evidence, not as neutral ground truth.

We ground this argument in a case study of the ScAN dataset (Rawat et al., 2022), examining how access constraints, cohort design, and annotation decisions shape the labels and how those choices appear in the linguistic structure of annotated spans.

Our contributions are:

- A position characterizing EHR-based suicidality datasets as encoding a documentation-mediated, episodic, and intent-resolved operationalization of suicidality
- A case study of ScAN tracing how governance, data sourcing, and annotation design give rise to this operationalization
- Empirical evidence that these construction choices are associated with systematic variation in linguistic framing and labeling patterns

2 ScAN as a Case Study

ScAN (Rawat et al., 2022) is an annotation layer for suicide attempts (SA) and suicidal ideation (SI) built over a subset of MIMIC-III, a de-identified clinical electronic health record (EHR) dataset from Beth Israel Deaconess Medical Center in Boston (Johnson et al., 2016). It contains 12,759 clinical notes across 697 hospital stays from 669 patients, with 19,690 span-level annotations. SA labels distinguish between positive, negative, unsure, and neutral cases based on inferred intent; SI labels capture presence or absence of ideation. We use ScAN as a case study to examine how EHR-based suicidality labels are shaped by the documentation, cohort, and annotation choices through which clinical text becomes machine-learning data.

Clinical notes often synthesize patient report, clinician observation, collateral information, prior records, institutional requirements, and risk-management practices. We use *documentation-mediated* to mean that the resulting NLP labels are labels over documented clinical evidence, not direct measurements of suicidality itself. Below, we trace three dimensions of this operationalization: documentation-mediated perspective, episodic temporal framing, and intent resolution.

2.1 Documentation-Mediated: Governance, Access, and Perspective

ScAN inherits the governance model of MIMIC-III. Although annotations and code are publicly released, the underlying clinical text requires credentialing through PhysioNet, completion of human subjects training, and agreement to a Data Use Agreement. Reproducibility is therefore conditional on institutional resources and compliance capacity.

The source text is clinician-authored documentation. This does not mean that patient perspectives are absent from the notes: patient reports, statements, and histories may be represented within clinician-authored text. However, direct patient-authored self-report, intake questionnaires, and patient-facing communications are outside the annotation scope. The dataset therefore represents suicidality as it appears in clinical documentation, rather than as it might appear across all possible sources of patient expression.

The annotation process further mediates the relationship between patient experience and dataset labels. Only notes from 24 pre-selected clinical section types were retained for annotation, based on expected relevance to suicidality. Annotation was performed by a single trained annotator supervised by a physician, who independently reviewed 330 of 12,759 notes (2.6%). Disagreements were resolved by updating labels to match the physician review. Thus, the labels reflect the ScAN annotation protocol as applied to clinician-authored documentation under partial physician review. They should be interpreted as structured judgments about documented evidence, not as neutral or exhaustive

records of suicidality.

De-identification procedures, including date shifting and age masking for patients over 89, further mediate the relationship between the data and the clinical events they represent (Johnson et al., 2016).

2.2 Episodic: Cohort Selection and Temporal Flattening

ScAN's cohort is seeded using ICD codes associated with suicide and overdose, restricting the dataset to hospital stays where suicidality or self-harm was already suspected, documented, or coded. ICD codes capture only a fraction of suicidality-related events, approximately 3% of SI and 19% of SA by some estimates (Anderson et al., 2015), so patients whose suicidal behavior went uncoded are outside the dataset.

Labeling is performed at the hospital-stay level. This design is practical for constructing an EHR-based dataset, but it also frames suicidality as a bounded hospital episode. Temporal distinctions, such as whether an event occurred during the current admission, in a recent prior encounter, or years earlier, are not directly encoded in the label schema even when such distinctions appear in the clinical text. This matters because suicidality is often longitudinal and recurrent rather than confined to a single encounter. Many individuals who die by suicide sought care well before their deaths (Kessler et al., 2020), and ideation may recur across encounters.

2.3 Intent-Resolved: Annotation Design and Category Collapse

ScAN's annotation scheme uses CDC-based definitions that distinguish suicidal from non-suicidal self-harm, requiring intent to be inferred from clinical documentation. Non-suicidal self-injury (NSSI) is excluded by design.

Cases where intent is unclear are labeled "unsure," but this category is collapsed with "negative" in the downstream modeling pipeline used by the companion ScANER system. This merges qualitatively different situations: documentation that explicitly negates suicidal intent, documentation where intent is not specified, and documentation where the available evidence is genuinely ambiguous. As we show in Section 2.5, these categories have distinct linguistic profiles. The issue is not that the original annotation decision was unreasonable, but that downstream label collapse can erase clinically meaningful uncertainty.

2.4 Dataset Composition

ScAN's single-site origin produces a demographically narrow dataset: 70% White, 92% English-speaking, and concentrated in the 25–54 age range, which includes approximately 70% of patients. No non-White racial or ethnic group exceeds 22 admissions, making subgroup analysis infeasible for most categories. The structured demographic data also contains some ambiguities; full details and tables are in Appendix E. We therefore treat demographic composition primarily as a description of dataset scope, rather than as the basis for subgroup claims.

2.5 Linguistic Framing Analysis

If labels flatten temporal, epistemic, and intentional distinctions present in the clinical text, then spans sharing the same label should exhibit heterogeneous linguistic profiles. We test this expectation through a focused framing analysis.

We analyze 15,585 annotated spans after excluding those with missing metadata. For each span, we identify negation, historical reference, and uncertainty using lexical indicators and MedSpaCy's ConText algorithm (Harkema et al., 2009). We classify a span as *unmodified* when both methods agree on the absence of all three modifier types. This is a descriptive linguistic category, not a clinical judgment: "unmodified" means that our detectors did not find negation, historical reference, or uncertainty governing the span. It does not imply clinically active suicidal intent. Details and inter-method agreement rates are in Appendices A and B.

Within-label heterogeneity. Spans sharing the same label exhibit substantial variation in framing (Table 1). Two-thirds of SA spans are unmodified, but only about half of present-SI spans are. Of particular note, 27.8% of present-SI spans contain historical markers, indicating that ideation labeled as present may still be documented in relation to prior psychiatric history rather than as a purely present-tense event.

Ambiguous categories and the cost of collapse. The categories that encode uncertainty show the clearest effect (Table 2). "Unsure" spans are frequently unmodified but contain elevated uncertainty markers (17.1%), reflecting epistemic

Table 1: Framing profiles by span type. "Unmodified" means no detected negation, historical reference, or uncertainty marker.

Span type	n	% Unmod.	% Hist.	% Neg.
All SA	14,048	66.8	13.2	5.8
Present-SI	897	52.2	27.8	7.0
Absent-SI	554	13.5	16.1	65.2

Table 2: Framing profiles of selected SA categories.

Category	n	% Unmod.	% Hist.	% Neg.	% Unc.
Intentional (X71–X83)	1,271	83.3	12.1	1.1	1.7
Unsure	2,237	61.6	19.3	6.8	17.1
Unspecified (T14.91)	770	19.0	67.8	3.4	5.1

ambiguity in the documentation. Unspecified-intent spans (T14.91) are predominantly historical (67.8%), indicating that lack of intent specification often co-occurs with temporal displacement. When these categories are merged with "negative" labels in downstream pipelines, epistemic uncertainty and temporal displacement are collapsed into a single class.

Variation across documentation contexts. Framing varies substantially by clinical note section. Discharge summaries are 83.6% unmodified while history of present illness (HPI) sections are only 49.9% unmodified (Appendix D). The same label therefore carries different linguistic signals depending on the documentation context in which it appears.

Summary. Across all three framing dimensions, labels that appear uniform encode meaningfully different clinical situations. Temporal context may be flattened, uncertainty may be resolved or collapsed, and intent may be treated as more determinate than the surrounding documentation supports. These findings do not show that the labels are wrong. Rather, they show that EHR-based suicidality labels are operationalizations of documented clinical evidence, and that downstream NLP systems should be evaluated with those operationalizations in view.

3 Discussion

The issues we identify are not unique to ScAN. Any EHR-based suicidality dataset will reflect some set of choices about whose perspective is encoded, how episodes are bounded, and how ambiguity is resolved. The question is whether these choices are examined. Below, we trace the downstream consequences of the operationalization we have described and outline steps towards making these choices more visible.

3.1 Possible Downstream Effects

If training labels subsume heterogeneous linguistic framings, classifiers trained on those labels would be expected to exhibit systematic and predictable errors. The historical-marker rate among present-SI spans (27.8%) predicts that models would learn to associate retrospective language with active ideation, potentially overflagging historical mentions in new clinical text. The gap in unmodified rates between discharge summaries and HPI sections (83.6% vs. 49.9%) predicts that classifier performance would vary substantially across note section types, even within a single hospital stay. The collapse of unsure with negative SA labels predicts that models would be less calibrated on cases involving genuine epistemic uncertainty—precisely the cases where clinical decision support is most needed. We do not test these predictions here, but each is falsifiable through standard error analysis on classifiers trained with and without label distinctions preserved.

3.2 Alternative Design Choices and Recommendations

Each dimension of the operationalization we describe suggests both an alternative dataset design and a corresponding evaluation practice that can surface hidden assumptions even when the dataset itself cannot be rebuilt.

For temporal framing, labeling across encounters rather than within a single hospital stay would allow models to represent suicidality as a recurring process. Where cross-encounter labeling is not feasible, reporting model performance separately by clinical note section type would reveal whether classifiers generalize across the variation in linguistic framing we observed—for example, between discharge summaries and HPI notes.

For intent resolution, retaining "unsure" as a distinct modeling category rather than merging it with "negative" would preserve clinically meaningful uncertainty in the label space. This matters not only for model calibration but also for clinicians who may encounter decision-support tools trained on these labels: a system that treats genuinely ambiguous cases as resolved negatives risks understating uncertainty in precisely the situations where clinical judgment is most needed. At minimum, pipelines that collapse ambiguous categories

should evaluate performance on each constituent category before and after the merger.

For the documentation-mediated dimension, two related limitations apply: what text is available for annotation, and how consistently that text is interpreted. Clinical notes are authored by clinicians and reflect their documentation practices, even when they incorporate patient-reported information. Incorporating patient-authored sources—such as self-report instruments, intake questionnaires, or patient-facing communications—alongside clinician-authored notes would allow datasets to represent suicidality across multiple perspectives rather than through clinical documentation alone. Independently, multi-annotator labeling with reported inter-annotator agreement would make transparent how consistently annotators interpret the clinical text that is available.

Each of these alternatives introduces practical trade-offs: longitudinal labeling requires cross-encounter linking infrastructure, preserving ambiguous categories adds complexity to model training and evaluation, and multi-annotator schemes increase annotation effort. These costs are real, but they are the costs of making the operationalization an explicit design choice rather than an invisible default. More broadly, dataset documentation should state which operationalization choices a pipeline inherits—how cohorts are seeded, at what level labels are aggregated, whether ambiguous categories are collapsed, and how many annotators contributed—so that downstream users, including clinicians evaluating decision-support systems, can assess what the labels represent before acting on model outputs.

4 Conclusion

We have argued that EHR-based suicidality datasets should be read as operationalizations shaped by governance, cohort design, and annotation practice, rather than as neutral ground truth. Using ScAN as a case study, we showed that these choices produce labels that flatten temporality, resolve ambiguity, and encode clinician-documented judgments. Our linguistic analysis confirmed that identical labels subsume spans with different temporal, negation, and uncertainty profiles.

None of these observations are criticisms of ScAN's creators, who made reasonable decisions under real constraints. The point is that these decisions constitute an operationalization, and that operationalization should be visible to downstream users. When labels are treated as ground truth without reference to the assumptions that produced them, the gap between what the dataset represents and what models are trained to predict becomes difficult to assess. Making these assumptions visible is a necessary first step toward clinical NLP systems that are transparent about what they predict. Toward that end, we have outlined testable predictions about downstream model behavior and practical recommendations that can help move this conversation forward.

5 Limitations

Our case study examines one dataset from one academic medical center. The specific distributions we report (e.g., the rate of historical markers in present-SI spans) may differ in datasets with other governance models, coding systems, or annotation protocols. Our argument is structural: any pipeline that seeds cohorts from billing codes, labels at the hospital-stay level, and resolves intent from clinical text will encode analogous assumptions. We do not train or evaluate classifiers on ScAN, so we cannot say whether the within-label heterogeneity we identify produces systematic model errors; establishing that link is a natural next step.

Our linguistic analysis covers negation, temporality, and uncertainty using lexical indicators and MedSpaCy's ConText algorithm, both of which operate at the span level without syntactic parsing or coreference resolution. This means we do not capture attribution, cross-note temporal reasoning, or scope ambiguities where a modifier may or may not govern the suicidality mention. Because our detection methods are conservative, the heterogeneity we report is likely a lower bound.

References

Heather D Anderson, Wilson D Pace, Elias Brandt, Rodney D Nielsen, Richard R Allen, Anne M Libby, David R West, and Robert J Valuck. 2015. Monitoring suicidal patients in primary care using electronic health records. *The Journal of the American Board of Family Medicine*, 28(1):65–71.

Bradley E Belsher, Derek J Smolenski, Larry D Pruitt, Nigel E Bush, Erin H Beech, Don E Workman, Rebecca L Morgan, Daniel P Evatt, Jennifer Tucker, and Nancy A Skopp. 2019. Prediction models for suicide attempts and deaths: a systematic review and simulation. *JAMA psychiatry*, 76(6):642–651.

Stevie Chancellor, Michael L Birnbaum, Eric D Caine, Vincent MB Silenzio, and Munmun De Choudhury. 2019. A taxonomy of ethical tensions in inferring mental health states from social media. In *Proceedings of the conference on fairness, accountability, and transparency*, pages 79–88.

Sindhu Kiranmai Ernala, Michael L Birnbaum, Kristin A Candan, Asra F Rizvi, William A Sterling, John M Kane, and Munmun De Choudhury. 2019. Methodological gaps in predicting mental health states from social media: Triangulating diagnostic signals. In *Proceedings of the 2019 chi conference on human factors in computing systems*, pages 1–16.

Joseph C. Franklin, Jessica D. Ribeiro, Kathryn R. Fox, Kate H. Bentley, Evan M. Kleiman, Xieyining Huang, Katherine M. Musacchio, Adam C. Jaroszewski, Bernard P. Chang, and Matthew K. Nock. 2017. Risk factors for suicidal thoughts and behaviors: A meta-analysis of 50 years of research. *Psychological Bulletin*, 143(2):187–232.

Henk Harkema, John N Dowling, Tyler Thornblade, and Wendy W Chapman. 2009. Context: an algorithm for determining negation, experiencer, and temporal status from clinical reports. *Journal of biomedical informatics*, 42(5):839–851.

Keith Harrigian, Carlos Aguirre, and Mark Dredze. 2021. On the state of social media data for mental health research. In *Proceedings of the Seventh Workshop on Computational Linguistics and Clinical Psychology: Improving Access*, pages 15–24.

Alistair Johnson, Tom Pollard, and Roger Mark. 2016. Mimic-iii clinical database (version 1.4). *PhysioNet*, 10(C2XW26):2.

Ronald C Kessler, Robert M Bossarte, Alex Luedtke, Alan M Zaslavsky, and Jose R Zubizarreta. 2020. Suicide prediction models: a critical review of recent research with recommendations for the way forward. *Molecular psychiatry*, 25(1):168–179.

Matthew Large, Muthusamy Kaneson, Nicholas Myles, Hannah Myles, Pramudie Gunaratne, and Christopher Ryan. 2016. Meta-analysis of longitudinal cohort studies of suicide risk assessment among psychiatric patients: Heterogeneity in results and lack of improvement over time. *PLOS ONE*, 11(6):e0156322.

Rose McCabe, Imren Sterno, Stefan Priebe, Rebecca Barnes, and Richard Byng. 2017. How do healthcare professionals interview patients to assess suicide risk? *BMC Psychiatry*, 17(1):122.

Bhanu Pratap Singh Rawat, Samuel Kovaly, Hong Yu, and Wilfred Pigeon. 2022. Scan: suicide attempt and ideation events dataset. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 1029–1040.

Jared F. Roush, Sarah L. Brown, Danielle R. Jahn, Sean M. Mitchell, Nathanael J. Taylor, Paul Quinnett, and Richard Ries. 2018. Mental Health Professionals' Suicide Risk Assessment and Management Practices: The Impact of Fear of Suicide-Related Outcomes and Comfort Working With Suicidal Individuals. *Crisis*, 39(1):55–64.

Robert C Schwartz. 2014. Racial disparities in psychotic disorder diagnosis: A review of empirical literature. *World Journal of Psychiatry*, 4(4):133.

Michael Sun, Tomasz Oliwa, Monica E Peek, and Elizabeth L Tung. 2022. Negative patient descriptors: Documenting racial bias in the electronic health record: Study examines racial bias in the patient descriptors used in the electronic health record. *Health Affairs*, 41(2):203–211.

A Framing Analysis: Definitions

Lexical keyword lists. The following case-insensitive terms are matched within each three-sentence context window:

- **Negation:** *no, not, denies, denied, without, never, none*
- **Historical:** *history of, h/o, hx of, previous, prior, past, ago, years ago, months ago*
- **Uncertainty:** *may, might, possibly, unclear, uncertain, equivocal, question of, rule out, r/o*

Lexical matching does not resolve scope: a keyword may modify a concept unrelated to suicidality. We therefore run MedSpaCy's ConText algorithm (Harkema et al., 2009) in parallel with default `ConTextComponent` settings, retaining only modifiers whose scope overlaps with the annotated span.

Composite measure. A span is framed as *unmodified* when both methods agree on the absence of negation, historical, and uncertainty modifiers. This conservative definition means some modified spans may carry modifiers that do not pertain to the suicidality judgment.

B Signal Agreement Rates

Table 3 reports span-level agreement between the lexical and ConText detectors ($n = 15{,}585$).

Table 3: Base rates and agreement between lexical and ConText detectors. The uncertainty divergence ($9.4\times$) reflects how often terms like *may* modify non-suicidality concepts.

Signal	Lex	Ctx	Agree	Ratio
Negation	6.3%	7.6%	92.1%	0.8×
Historical	19.6%	8.4%	86.6%	2.3×
Uncertainty	9.4%	1.0%	91.2%	9.4×

C Category-Level Framing

Tables 4 and 5 extend the summaries in Section 2.5 to all annotation categories. Lex-H / Ctx-H = lexical / ConText historical; Lex-N / Ctx-N = negation; Lex-U = lexical uncertainty (ConText uncertainty $\leq 1\%$ everywhere, omitted).

D Section-Level Framing

Table 6 reports framing rates by clinical note section. Sections with $n < 40$ are included for completeness. % SI = share of SI spans in section.

E Demographic Analysis

Analyses use 486 admissions with structured data from MIMIC-III's `ADMISSIONS` and `PATIENTS` tables joined to ScAN annotations. We report Pearson's χ^2 tests with uncorrected p-values; given small subgroups and the exploratory scope, we do not apply multiple-comparison corrections.

Subgroup sizes. Insurance: Private 181, Medicaid 122, Medicare 103, Government 56, Self Pay 22, missing 2. Gender: Female 257, Male 227, missing 2. Race/ethnicity (collapsed): White 339, Unknown/Not Specified[1] 76, Black/African American 22, Hispanic/Latino 18, Other 22, Asian 9. No non-White group exceeds 22 admissions; race/ethnicity comparisons are not reported.

Tables 8, 9, 10, 11, 12, 13 and 14 show the respective distributions of gender, age, ethnicity, language spoken, insurance status, marital status, and religion of patients in the dataset. Additionally, the distribution of living vs. deceased patients is reported in Table 15.

Ambiguities. Ambiguities were noted in the gender, language, and ethnicity data. ScAN included one male-to-female transgender individual. While the MIMIC-III documentation defines gender as "the genotypical sex of the patient" (Johnson et al., 2016), the transgender patient's gender was listed as Female, which is not their genotypical sex. Further, MIMIC-III, and by extension ScAN, uses non-standard 4 letter language codes. While some codes are easy to infer, such as *SPAN* for Spanish, other codes such as *CAPE* and *PTUN* are not intuitive and have no documented definition. Finally, ethnicity data is provided with varying levels of specificity. For example, an individual could be listed as *White*, *White – Brazilian*, *White – Russian*, or *White – Other European*. However, we acknowledge that it may not always be possible to obtain a patient's specific ethnicity.

[1] Includes UNKNOWN/NOT SPECIFIED (n=54), UNABLE TO OBTAIN (n=17), PATIENT DECLINED (n=3), missing (n=2).

Table 4: Framing profiles for SA categories ($n = 14{,}048$), ordered by % Unmodified.

Cat.	Description	n	% Unmod.	Lex-H	Ctx-H	Lex-N	Ctx-N	Lex-U
T71	Asphyxiation	440	86.6	9.6	2.1	0.5	0.7	3.6
X71–X83	Intentional self-harm	1,271	83.3	12.1	5.0	1.1	1.6	1.7
T51–T65	Toxic subst. (non-pharma)	531	74.0	16.2	6.8	2.8	5.1	4.7
T36–T50	Pharma. poisoning	8,635	69.5	16.3	6.5	2.5	4.7	10.1
Unsure	Annotator unsure	2,237	61.6	19.3	2.3	6.8	6.2	17.1
T14.91	Unspecified intent	770	19.0	67.8	50.4	3.4	6.6	5.1
N/A	No ICD code	164	17.1	37.8	23.8	50.0	56.1	9.2

Table 5: Framing profiles for SI spans ($n = 1{,}537$) by status label.

Status	n	% Unmod.	Lex-H	Ctx-H	Lex-N	Ctx-N	Lex-U
Present	897	52.2	27.8	12.5	7.0	11.8	7.1
Absent	554	13.5	16.1	9.2	65.2	57.2	3.1
N/A	86	23.3	14.0	8.1	52.3	37.2	11.6

Table 6: Framing by clinical note section, ordered by % Unmodified.

Section	n	% Unmod.	Lex-H	Ctx-H	Lex-N	Ctx-N	% SI
Discharge summary	3,358	83.6	9.3	2.4	1.5	1.7	4.0
Assessment / plan	4,262	66.1	16.5	6.0	6.3	7.7	12.4
Medical history	743	61.5	28.1	15.3	3.4	4.7	10.5
Other	31	61.3	32.3	6.5	3.2	3.2	6.5
Chief complaint	2,567	56.7	23.3	9.5	6.3	12.5	7.8
Impression	840	55.4	21.6	11.6	8.6	6.8	10.2
Social history	2,270	51.7	23.6	12.3	9.1	11.2	12.5
HPI	1,474	49.9	33.4	16.2	12.8	9.2	14.9
Psychiatric history	40	45.0	35.0	10.0	12.5	2.5	15.0

Table 7: Demographic association tests at or near significance. All other comparisons returned $p > 0.10$.

Comparison	Outcome	p	
Medicaid vs. Private 38/122 (31.1%) vs. 33/181 (18.2%)	$\geq$1 unsure SA	0.014	*
Female vs. Male 221/257 (86.0%) vs. 181/227 (79.7%)	$\geq$1 historical	0.087	†
Female vs. Male 159/257 (61.9%) vs. 120/227 (52.9%)	$\geq$1 uncertainty	0.056	†

* $p < 0.05$; † $p < 0.10$ (marginal)

Gender	%
Female	50.9
Male	49.1

Table 8: Gender distribution of ScAN patients.

Age Group	%
18–24	13.5
25–34	21.6
35–44	22.8
45–54	25.5
55–64	9.7
65–74	5.1
75+	1.9

Table 9: Age distribution of ScAN patients.

Ethnicity	%
White	70.0
Unknown / Other / Declined	16.4
Black / African American	5.9
Hispanic or Latino	3.6
Asian	1.7
European	0.7
Black / Cape Verdean	0.6
Multi-race	0.4
South American	0.3
American Indian / Alaska Native	0.1
Native Hawaiian / Pacific Islander	0.1

Table 10: Ethnicity distribution of ScAN patients. 'European' includes the categories 'Portugese', 'White – Russian', and 'White – Other European'. 'Asian' includes the categories 'Asian', 'Asian – Japanese', 'Asian – Chinese', 'Asian – Vietnamese'. South American includes the categories 'South American' and 'White – Brazilian'. 'Hispanic or Latino' includes the categories 'Hispanic or Latino', 'Hispanic/Latino – Puerto Rican', and 'Hispanic/Latino – Dominican'.

Language	%
English (ENGL)	92.3
Spanish (SPAN)	2.4
Unknown (PTUN)	1.8
Russian (RUSS)	1.0
Cantonese (CANT)	0.4
Portugese (PORT)	0.4
Unknown (CAPE)	0.4
Other	1.3

Table 11: Language distribution of ScAN patients. 'Other' includes Japanese (JAPA), Arabic (ARAB), Mandarin (MAND), American Sign Language (AMER), French (FREN), and Haitian (HAIT). Each of these languages have 0.2% speakers in ScAN.

Insurance Type	%
Private	34.9
Medicaid	26.2
Medicare	24.1
Government	10.8
Self-pay	4.0

Table 12: Insurance distribution of ScAN patients.

Marital Status	%
Single	62.1
Married	25.3
Divorced	7.6
Widowed	2.8
Separated	1.2
Unknown	1.0

Table 13: Marital status distribution of ScAN patients.

Religion	%
Catholic	57.1
Other	13.7
Protestant / Quaker	12.7
Jewish	11.4
Christian – Other	3.8
Buddhist	1.3

Table 14: Religion distribution of ScAN patients among the 45.4% who elected to provide their information. The remaining 54.6% either did not specify their religion or this information was unobtainable.

Mortality	%
Alive	84.9
Deceased (post-discharge)	10.2
Deceased (during visit)	4.9

Table 15: Mortality distribution of ScAN patients.

Culture by Design: A Sociotechnical Framework for Culturally Grounded AI for Mental Health

Sunny Rai[a] **Elizabeth C. Stade**[b] **Graise Zhou**[a] **Neil K.R. Sehgal**[a]
Simone H. Schriger[a] **Sara Gerke**[c] **Lyle H. Ungar**[a] **Sharath Chandra Guntuku**[a]

[a]University of Pennsylvania, Philadelphia, PA
[b]Stanford University, Stanford, CA
[c]University of Illinois Urbana-Champaign, Champaign, IL
{sunnyrai, sharathg}@seas.upenn.edu

Abstract

AI systems for mental health are developed predominantly using data from Western, Educated, Industrialized, Rich, and Democratic (WEIRD) populations, raising concerns about their validity, fairness, and generalizability across diverse cultural and geographic contexts. This limitation is especially consequential in mental health, where linguistic expression, symptom presentation, help-seeking behavior, and access to care vary substantially across populations. We argue that culture must be treated as a first-class design requirement throughout the AI development lifecycle, a principle we term *culture by design*. Drawing on evidence from NLP, clinical psychology, HCI, and global mental health, we present ten practical recommendations spanning data collection, modeling, evaluation, deployment, and governance, providing researchers and practitioners with a concrete roadmap for building culturally grounded, equitable, and contextually appropriate mental health AI systems.

1 Introduction

AI-powered mental health systems are increasingly positioned as tools for expanding access to care, especially in settings where mental health resources are scarce (World Health Organization, 2024; Cho et al., 2023). However, existing AI mental health systems are primarily developed using data from Western, Educated, Industrialized, Rich, and Democratic (WEIRD) populations (Henrich et al., 2010), often collected from a small number of English-dominant social media platforms (Harrigian et al., 2021; Cho et al., 2023) (see Fig 2). This raises concerns about whether such systems generalize across cultures (Rai et al., 2025a; Aguirre et al., 2021).

In the mental health literature, *culture* has been defined as the shared, learned behaviors, meanings, values, and beliefs that are transmitted socially across generations and that shape how individuals perceive, communicate, and make sense of psychological experience (Marsella and Yamada, 2000; Triandis, 1996). Critically, culture is not a static attribute but a dynamic, evolving system that mediates the etiology, expression, and treatment of psychopathology (Marsella and Yamada, 2010). This view is reflected in DSM-5's Cultural Formulation framework, which recognizes that cultural identity, cultural idioms of distress, cultural explanations of illness, and psychosocial stressors all interact to shape how mental disorders are experienced and communicated across communities (Lewis-Fernández et al., 2014).

Language technologies are shaped by the populations represented in their training data and by the assumptions embedded in data collection, labeling,



Figure 1: Ten cross-cultural recommendations for designing AI mental health applications. Recommendations are grouped by data design, modeling and evaluation, and deployment.

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 128–137
July 4, 2026 ©2026 Association for Computational Linguistics

and evaluation pipelines (Bender and Friedman, 2018; Blodgett et al., 2020; Gebru et al., 2021). Mental health is a particularly challenging domain for cross-cultural AI because the relationship between language and psychopathology is not culture-invariant: linguistic expressions of distress, symptom presentation, help-seeking behavior, and willingness to self-disclose vary substantially across communities (Cork et al., 2019; Zhao et al., 2012; Hall et al., 2016; Rai et al., 2024). Research on cultural adaptation suggests that effective mental health support must account for local norms, values, communication styles, and structural constraints (Hall et al., 2016; Ge et al., 2024). Yet these insights have not been systematically translated into the AI development lifecycle. We argue that culture must be treated as a first-class design requirement throughout the AI development lifecycle, a principle we term *culture by design*, following the proactive embedding logic of established frameworks such as *ethics by design* (Brey and Dainow, 2024) and *privacy by design* (Cavoukian, 2009). This paper addresses this gap by presenting a sociotechnical framework instantiating this principle across ten practical recommendations spanning data collection, model development, evaluation, and deployment, drawing on evidence from NLP, ML, HCI, clinical psychology, and global mental health.

2 Related Work

Cultural differences in mental health expressions The manner in which symptoms manifest (e.g., psychological versus somatic (Kaiser and Jo Weaver, 2019) and emotion appraised (Girju and Girju, 2022; Li et al., 2023)) differs from culture to culture. Psychological suffering is communicated through culture-specific concepts and expressions that may not align with standardized Western clinical language (Cork et al., 2019). Culture shapes what people disclose, how they seek support, and what they expect from AI systems (Zhao et al., 2012; Ge et al., 2024). Even within social media-based mental health research, language markers (Rai et al., 2024; Aguirre et al., 2021) and motivations (Pendse et al., 2019) can differ substantially across demographic groups. Recent NLP work further suggests that multilingual models fail to interpret emotion or intent in culturally appropriate ways (Havaldar et al., 2023). As a result, AI mental health systems trained on WEIRD populations may be biased not only because of dataset imbalance,



Figure 2: **Geographic mismatch between global mental health burden and the platform ecosystems from which the majority of mental health datasets are drawn**. **Panel A**. Prevalence of Mental Health Disorders - Country Level, 2021. Source: (Global Burden of Disease Collaborative Network, 2021) . **Panel B**. Share of Facebook Users - Country Level, July 2024. Source: (NapoleonCat, 2024) **Panel C**. Share of Twitter Advertising Audience - UN Subregion Level, April 2023. Source: (Kemp, 2023) **Panel D**. Share of Global Reddit Traffic - Country Level, March 2023. Source: (Semrush, 2023). Reddit has no traffic from China; Twitter is more widely used, the audience share is poor for Africa, Oceania, and Eastern Europe. Facebook is most actively used in the United States, India, Southeast Asia, and Brazil. Note that Twitter Audience Share is reported at the United Nations subregion level. As a result, subregions may include countries where platforms are banned (e.g. Twitter is banned in China but is displayed in Panel B due to its belonging in Southern Asia).

but also because the constructs they aim to model are themselves expressed differently across cultural contexts (e.g. shame-related expressions in East vs West (Rai et al., 2025b)).

Bias, underspecified data, and linguistic diversity in NLP. A substantial body of work in NLP argues for greater transparency about the populations and conditions under which data are collected (Bender and Friedman, 2018; Gebru et al., 2021; Mitchell et al., 2019). Language technologies can reproduce social biases through data selection, labeling assumptions, and deployment practices (Blodgett et al., 2020), and NLP resources remain heavily concentrated in a small number of high-resource languages (Joshi et al., 2020). Despite the direct relevance of these frameworks to mental health AI, where construct validity is culturally contingent, and data collection practices carry ethical stakes, their uptake in the mental health NLP literature has been limited. Research papers rarely describe population distributions or subgroups in training and test data (Cho et al., 2023), and do not report disparate impact across demographic groups.

Robustness and evaluation under cultural distribution shift. ML model performance may degrade substantially under distribution shift, and strong benchmark performance can mask failures under underspecification (Ovadia et al., 2019; D'Amour et al., 2022; Koh et al., 2021). Cultural and linguistic variations that characterize global mental health contexts remain a particularly understudied form of such shift.

In summary, prior work has studied AI-driven mental health and cultural adaptation largely in isolation. To our knowledge, there is limited AI-focused work that integrates these perspectives into a unified framework for culturally grounded AI mental health system development. This paper fills that gap with ten practical recommendations.

3 A Sociotechnical Framework for Developing Culturally Grounded AI Mental Health Applications

The ten recommendations are organized across three phases of the AI development lifecycle: **data design**, **modeling and evaluation** , and **deployment and governance**, reflecting the view that cultural grounding must be addressed end-to-end rather than as a post-hoc correction.

DATA DESIGN

1. Define the target population clearly

The absence of critical demographic information such as age, gender, and race/ethnicity, in training datasets raises concerns about the generalizability of AI models across subpopulations (e.g., how performance differs across racial/ethnic subgroups (Rai et al., 2024)). Researchers should explicitly document demographic details, following established guidelines in medical and psychological research (Kissel and Friedman, 2023). At minimum, a study or model should report data source, language(s), distributions for country/region/race, age, and gender, and source of labels (self-report vs clinical diagnosis vs machine prediction). Additionally, clear, standardized labeling practices for AI mental health applications are essential for communicating the intended user, use, and warnings about potential biases, thereby fostering user trust and informed adoption (Gerke, 2024; Mitchell et al., 2019).

2. Identify cultural idioms of distress

Building assessment or intervention applications that rely on self-disclosures about mental health on social media platforms skews the applicability of such applications to demographic groups with existing treatment access or high mental health literacy. This excludes disadvantaged groups that use different cultural idioms of distress (e.g., *tension* in India, *shenjing shuairuo* in China) or cultural narratives to describe their mental health problems, especially on public platforms. When developing AI-based mental health applications, collaborating with cultural psychologists, anthropologists, and local mental health practitioners is crucial to examining how mental health is discussed. Such partnerships can enable the identification, validation, and integration of culturally resonant expressions of psychopathology, ensuring AI applications accurately reflect the diverse ways global communities convey psychological distress (Cork et al., 2019).

3. Expand modality coverage to reach underserved populations

AI mental health applications often default to textual interactions, excluding populations that prefer or rely on alternative communication modalities such as voice messages or video calls, including elderly individuals and people with disabilities (Bunyi et al., 2021). This restriction risks systematic exclusion of communities that communicate

primarily through non-textual channels, compounding existing biases toward populations with high digital literacy and platform access. Importantly, our concern here is not that non-textual modalities carry richer diagnostic signal but rather that restricting data collection to typed text forecloses access to populations who sparsely produce it. Voice messages, for instance, can now be transcribed with high accuracy using contemporary automatic speech recognition systems and analyzed using standard NLP pipelines; accuracy is high for many high-resource languages, and rapidly improving multilingual models are extending this capability to a broader range of languages (Radford et al., 2023). This substantially broadens the demographic reach of mental health data collection without requiring new modeling infrastructure.

However, collecting and using sensitive data, via modalities like voice and video, which carry increased risks of identification and misuse, must prioritize robust privacy and security protections through an ethics-by-design approach (Brey and Dainow, 2024). Moreover, clear, meaningful informed consent procedures for those contributing their data should be in place that, among other things, transparently communicate the data privacy and security safeguards and risks, such as explicitly informing participants if and how their data can be withdrawn or erased after being incorporated into model training.

4. Engage communities in data collection and evaluation

Non-Western communities are often less likely to disclose mental health issues publicly due to stigma or cultural norms (Zhao et al., 2012), threatening the accuracy and applicability of language-based diagnostic models. To improve validity, researchers should proactively engage local communities and adopt culturally sensitive data collection practices such as anonymized structured clinical interviews, widely regarded as diagnostic gold standards (First, 1997). Emerging AI methods, such as in-context learning make carefully collected small-scale datasets particularly valuable.

When seeking ethics approval for cross-cultural mental health data collection, it is worth considering dimensions that standard IRB templates may not capture (Calia et al., 2023; Murray et al., 2016). First, seeking approval from a local ethics board in the target country or community, in addition to the home institution, can strengthen the legitimacy and cultural appropriateness of the research. Second, documenting whether participation carries social or legal risks specific to the target context, such as criminalization of mental health disclosures or employment consequences, can help protect participants in ways that generic risk assessments may overlook. Third, having consent procedures reviewed by local community members or practitioners can ensure linguistic accessibility and compatibility with collective or family-based decision-making norms. Finally, data agreements that specify community ownership and the right to withdraw or restrict use after collection can meaningfully strengthen data sovereignty. Reporting these considerations as part of model card or datasheet helps build transparency and community trust (Gerke, 2023).

MODELING AND EVALUATION

5. Validate tools and check for outcome invariance

The development of culture-specific resources could improve the validity with which relationships between language and mental health are measured across cultures. The most widely used psychosocial dictionary, Linguistic Inquiry and Word Count (LIWC) (Tausczik and Pennebaker, 2010), for analyzing linguistic patterns in mental health language is primarily designed for Standard American English. Similarly, current Large Language Models (LLMs) exhibit Anglocentric biases, leading to potential misinterpretations of expressed emotions (Havaldar et al., 2023). Concerted efforts to culturally adapt and validate existing Natural Language Processing (NLP) tools and develop new culturally tailored resources are essential.

Equally important is ensuring that outcome measures employed to evaluate AI mental health applications demonstrate measurement invariance across key demographic characteristics, including gender, race, ethnicity, and religion. Invariance should also be examined across language context: users interacting with interfaces in a non-native language may exhibit systematically different self-disclosure levels, response patterns, and help-seeking behaviors compared to native speakers (Dewaele et al., 2008), which can confound both model training and intervention evaluation. Assessing these effects and designing interfaces that mitigate them is a concrete step toward culturally grounded evaluation practice.

Recommendation	Priority	Minimum Compliance Criterion	Example Metric or Artifact
Data Design			
1. Define the target population clearly	**Must Do**	Model card reports platform, language(s), country/region, age, gender distributions, and label source (self-report vs. clinical diagnosis vs. model prediction).	NIH-style demographic table in paper or supplementary materials.
2. Identify cultural idioms of distress	**Good to Have**	Use a community-validated lexicon of culture-specific distress expressions for data collection and annotation.	Codebook of culture-specific distress expressions validated with local mental health practitioners.
3. Expand modality coverage to reach underserved populations	**Must Do**	Data collection includes at least one non-textual modality (e.g., voice) with documented rationale for population reach; privacy safeguards for personally identifiable information explicitly documented.	IRB approval reported; demographic coverage of collected modalities documented; data anonymization and de-identification procedure described in supplementary material.
4. Engage communities in data collection	**Good to Have**	Community involvement documented via structured participation log specifying who was consulted, at what stage, and how input changed data collection or annotation decisions.	Anonymized structured clinical interviews used for at least a subset of training data; participation log included in datasheet.
Modeling and Evaluation			
5. Validate tools and check for outcome invariance	**Must Do**	Evaluation reports subgroup calibration and disparate impact across demographic groups alongside aggregate metrics.	Differential item functioning (DIF) analysis or confirmatory factor analysis across cultural groups; disparate impact table by subgroup.
6. Disentangle cultural and platform effects	**Good to Have**	Sensitivity analyses conducted within platforms (linguistic features vs. outcomes) and across platforms (cross-platform generalization of mental health markers).	Performance reported per platform; cross-platform transfer experiment with at least two platforms (e.g., Reddit $\rightarrow$ Facebook).
7. Measure and enhance therapeutic alliance	**Best Practice**	LLM-based alliance scoring applied to conversation logs; alliance scores tested for differential prediction of dropout or satisfaction across cultural subgroups.	Alliance rupture detection F1 reported by cultural group.
8. Develop multicultural competency	**Best Practice**	Model evaluated on whether suggested rephrasing reduces culturally specific miscommunication markers relative to a baseline measured by conversation outcomes such as self-disclosure; annotator cultural background reported.	Culturally annotated clinical dialogue corpus; reduction in miscommunication flags; empathy ratings stratified by annotator cultural background .
Deployment and Governance			
9. Adapt to structural and contextual factors	**Good to Have**	Accessibility or reach stratified by interface modality, input language proficiency, and device type; at least one ablation targets a low-resource deployment constraint.	Performance reported for voice vs. text; low-bandwidth variant evaluated on task completion and user satisfaction.
10. Create resources beneficial to the target culture	**Best Practice**	At least one outcome measure preregistered in consultation with the target community; a dataset, lexicon, or model released publicly and remains accessible after the study concludes.	Community-defined outcome scale (e.g., family functioning) used alongside standard symptom measures; data or model weights deposited in an open repository.

Table 1: Ten recommendations with priority level, minimum compliance criteria, and example metrics or artifacts. **Must Do**: absence constitutes a reportable methodological gap. **Good to Have**: strengthens validity and is expected at high-impact venues. **Best Practice**: aspirational; marks the current frontier of culturally grounded AI.

6. Disentangle cultural and platform-specific effects

Social media platform use is deeply influenced by cultural context (Burke et al., 2020), potentially confounding AI models that rely on social media language for mental health assessment. Without distinguishing between culture-specific platform usage patterns and genuine mental health indicators, models risk inaccurate assessments and biased conclusions. Therefore, rigorous sensitivity analyses are essential, both within platforms (examining how culturally distinct linguistic features relate to mental health conditions) and across different platforms (evaluating whether mental health markers identified on one platform, like Reddit, generalize effectively to another, like Facebook). Such careful testing ensures that AI mental health assessments accurately reflect mental health conditions, rather than platform-specific or culturally mediated communication norms.

7. Measure and enhance therapeutic alliance across cultures

Therapeutic alliance, the quality of trust and rapport between user and mental health support, is strongly influenced by cultural and demographic factors, such as preferences for emotional expression or interaction styles. Recent work has begun operationalizing alliance monitoring in LLM-based systems: Li et al. (2024) proposed an LLM-based approach to measuring therapeutic alliance in online counseling, while Chiu et al. (2024) introduced a framework for systematically comparing LLM therapy behaviors against high- and low-quality human sessions. These approaches provide concrete scaffolding for detecting alliance ruptures and cultural mismatches in real-time, though they have not yet been validated across cultural subgroups, a gap this recommendation directly targets. For instance, Chinese users may prefer emotionally expressive AI systems that foster personal connections, whereas European and American users favor more impersonal, controllable interactions (Ge et al., 2024), illustrating the cultural specificity that alliance models must account for. Monitoring private user conversations for alliance must carefully balance clinical responsibilities against user privacy and autonomy.

8. Develop multicultural competency

LLMs offer significant potential to advance multicultural competence in mental health care by adapting to the cultural values and communication preferences underlying patient behaviors and treatment responses (Liu et al., 2026). Given patients' strong preferences for therapists sharing similar cultural or ethnic backgrounds (Cabral and Smith, 2011), LLMs could augment therapist training by generating culturally tailored therapeutic scenarios, identifying culturally embedded biases in clinical language, and suggesting more culturally sensitive communication alternatives. For instance, AI-generated guidance could assist therapists in adapting interaction styles to avoid culturally specific misinterpretations, such as perceptions of rudeness arising from direct communication with traditional East Asian clients.

DEPLOYMENT AND GOVERNANCE

9. Adapt to structural and contextual factors

Effective AI mental health applications require careful consideration of structural barriers faced by real individuals, such as shared device access, limited internet connectivity, varying literacy, and language proficiency. Tailoring technologies to these contextual realities can significantly enhance user satisfaction and perceived usefulness.

Establishing a centralized, transparent registry for mental health applications could be a promising way to strengthen accountability and build public trust. Such a registry could disclose valuable information, including the demonstration of safety and effectiveness (e.g., clinical trial outcomes), robust privacy and security protections, and regulatory compliance (e.g., compliance with medical device regulations) (Gerke et al., 2020).

10. Create resources beneficial to the target culture

AI mental health research and applications must explicitly prioritize the generation of knowledge that benefits the cultures and communities they aim to serve. Researchers should contextualize mental health symptoms within specific cultural and social realities, thereby avoiding inadvertent imposition of external, often Western, frameworks, which can distort or misrepresent culturally embedded behaviors. For instance, conventional outcome measures, such as individual symptom reduction, may inadequately reflect culturally significant goals in collectivist societies, where communal harmony and family well-being are paramount. When designing AI-driven mental health applications, developers

should measure outcomes consistent with the beliefs and values of the target patient populations.

Furthermore, developers must rigorously adhere to applicable legal frameworks, including data privacy laws and medical device and/or AI regulations. Even when regulatory classification as wellness tools potentially bypasses stricter medical device scrutiny or a country has no comprehensive privacy law, an ethics-by-design approach remains essential, and developers retain discretion to adopt standards beyond minimum legal requirements (Gerke, 2022). Sharing anonymized data with proper safeguards (e.g., a ban on reidentification) and trained models will help compare the generalizability of mental health markers across cultures and translate research insights into technology.

Conclusion

Cultural grounding should be treated as a core requirement in the design and deployment of AI systems for mental health. The principle of *culture by design* demands deeper interdisciplinary engagement, including ethical data governance, overcoming data silos, culturally adapted informed consent processes, robust regulatory compliance, fostering patient trust, and seamless integration into existing local mental health infrastructures. The framework presented here is intended as a practical foundation for future interdisciplinary dialogue and research on the sociotechnical complexities essential for developing and deploying equitable, culturally grounded AI mental health applications worldwide.

Limitations

Our recommendations synthesize prior work across NLP, HCI, clinical psychology, psychiatry, and global mental health; however, we do not empirically quantify their relative impact on downstream model performance, safety, or equity. Our treatment of regulation, ethics, and governance is intentionally broad and non-jurisdiction-specific. Legal requirements governing privacy, informed consent, data sharing, and medical device classification vary substantially across countries; nothing in this discussion should be construed as legal guidance. Finally, several recommendations involve inherent trade-offs. Collecting richer multimodal or culturally specific data may improve representational validity while simultaneously increasing privacy risks, annotation complexity, and barriers to data sharing. Likewise, tailoring systems to a particular community may improve local utility at the cost of cross-population comparability or scalability. We regard these tensions not as arguments against culturally grounded design, but as central challenges for future interdisciplinary research.

Acknowledgments

S.C.G. was partly supported by NIH-NIMHD (R01MD018340), the Penn Global Research Engagement Fund, and the Leonard Davis Institute of Health Economics. The funders had no role in the design and conduct of the study; collection, management, analysis, and interpretation of the data; preparation, review, or approval of the manuscript; and decision to submit the manuscript for publication. S.G.'s work was supported by a Novo Nordisk Foundation Grant for a scientifically independent International Collaborative Bioscience Innovation & Law Programme (Inter-CeBIL Programme — grant number NNF23SA0087056).

References

Carlos Aguirre, Keith Harrigian, and Mark Dredze. 2021. Gender and racial fairness in depression research using social media. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pages 2932–2949. Association for Computational Linguistics.

Emily M. Bender and Batya Friedman. 2018. Data statements for natural language processing: Toward mitigating system bias and enabling better science. *Transactions of the Association for Computational Linguistics*, 6:587–604.

Su Lin Blodgett, Solon Barocas, Hal Daumé III, and Hanna Wallach. 2020. Language (technology) is power: A critical survey of "bias" in NLP. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 5454–5476, Online. Association for Computational Linguistics.

Philip Brey and Brandt Dainow. 2024. Ethics by design for artificial intelligence. *AI and Ethics*, 4(4):1265–1277.

Jessica Bunyi, Kathryn E. Ringland, and Stephen M. Schueller. 2021. Accessibility and digital mental health: Considerations for more accessible and equitable mental health apps. *Frontiers in Digital Health*, 3:742196.

Moira Burke, Justin Cheng, and Benjamin de Gant. 2020. Social comparison and facebook: Feedback,

positivity, and opportunities for comparison. In *Proceedings of the 2020 CHI Conference on Human Factors in Computing Systems*, pages 1–13, New York, NY, USA. Association for Computing Machinery.

R. R. Cabral and Timothy B. Smith. 2011. Racial/ethnic matching of clients and therapists in mental health services: A meta-analytic review of preferences, perceptions, and outcomes. *Journal of Counseling Psychology*, 58(4):537–554.

Clara Calia, Amit Chakrabarti, Emmanuel Sarabwe, and Anna Chiumento. 2023. Maximising impactful, locally relevant global mental health research conducted in low and middle income country settings: Ethical considerations. *Wellcome open research*, 7:240.

Ann Cavoukian. 2009. Privacy by design: The 7 foundational principles. Technical report, Information and Privacy Commissioner of Ontario, Toronto, Canada.

Yu Ying Chiu, Ashish Sharma, Inna Wanyin Lin, and Tim Althoff. 2024. A computational framework for behavioral assessment of llm therapists. *arXiv preprint arXiv:2401.00820*.

Young Min Cho, Sunny Rai, Lyle Ungar, João Sedoc, and Sharath Guntuku. 2023. An integrative survey on mental health conversational agents to bridge computer science and medical perspectives. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 11346–11369, Singapore. Association for Computational Linguistics.

Catrin Cork, Bonnie N. Kaiser, and Ross G. White. 2019. The integration of idioms of distress into mental health assessments and interventions: A systematic review. *Global Mental Health*, 6:e7.

Alexander D'Amour, Katherine Heller, Dan Moldovan, Ben Adlam, Babak Alipanahi, Alex Beutel, Christina Chen, Jonathan Deaton, Jacob Eisenstein, Matthew D Hoffman, and 1 others. 2022. Underspecification presents challenges for credibility in modern machine learning. *Journal of Machine Learning Research*, 23(226):1–61.

Jean-Marc Dewaele, Konstantinos V Petrides, and Adrian Furnham. 2008. Effects of trait emotional intelligence and sociobiographical variables on communicative anxiety and foreign language anxiety among adult multilinguals: A review and empirical investigation. *Language learning*, 58(4):911–960.

Michael B First. 1997. Structured clinical interview for dsm-iv axis i disorders. *Biometrics research department*.

Xiaoqi Ge, Chenyue Xu, Donna Misaki, Hazel R. Markus, and Jeanne L. Tsai. 2024. How culture shapes what people want from AI. In *Proceedings of the CHI Conference on Human Factors in Computing Systems*, pages 1–15, Honolulu, HI, USA. ACM.

Timnit Gebru, Jamie Morgenstern, Briana Vecchione, Jennifer Wortman Vaughan, Hanna Wallach, Hal Daumé III, and Kate Crawford. 2021. Datasheets for datasets. *Communications of the ACM*, 64(12):86–92.

Sara Gerke. 2022. Digital home health during the COVID-19 pandemic: Challenges to safety, liability, and informed consent, and the way to move forward. In Carmel Shachar, Christopher Robertson, I. Glenn Cohen, Timo Minssen, and W. Nicholson Price II, editors, *The Future of Medical Device Regulation: Innovation and Protection*, pages 141–160. Cambridge University Press, Cambridge.

Sara Gerke. 2023. "Nutrition Facts Labels" for Artificial Intelligence/Machine Learning-based medical devices-the urgent need for labeling standards. *Geo. Wash. L. Rev.*, 91:79.

Sara Gerke. 2024. A comprehensive labeling framework for Artificial Intelligence (AI)/Machine Learning (ML)-based medical devices: From AI facts labels to a front-of-package AI labeling System—Lessons learned from food labeling. *Emory LJ*, 74:1297.

Sara Gerke, Ariel D Stern, and Timo Minssen. 2020. Germany's digital health reforms in the covid-19 era: lessons and opportunities for other countries. *NPJ digital medicine*, 3(1):94.

Roxana Girju and Marina Girju. 2022. Design considerations for an nlp-driven empathy and emotion interface for clinician training via telemedicine. In *Proceedings of the Second Workshop on Bridging Human–Computer Interaction and Natural Language Processing*, pages 21–27.

Global Burden of Disease Collaborative Network. 2021. Global Burden of Disease Study 2021 (GBD 2021) Incidence, Prevalence, and Years Lived with Disability 1990–2015. `https://ghdx.healthdata.org/record/ihme-data/gbd-2015-incidence-prevalence-and-ylds-1990-2015`. Accessed: 2024.

Gordon C. Nagayama Hall, A. Y. Ibaraki, Ellen R. Huang, C. Nathan Marti, and Eric Stice. 2016. A meta-analysis of cultural adaptations of psychological interventions. *Behaviour Therapy*, 47(6):993–1014.

Keith Harrigian, Carlos Aguirre, and Mark Dredze. 2021. On the state of social media data for mental health research. In *Proceedings of the Seventh Workshop on Computational Linguistics and Clinical Psychology: Improving Access*, pages 15–24.

Shreya Havaldar, Bhumika Singhal, Sunny Rai, Langchen Liu, Sharath Chandra Guntuku, and Lyle Ungar. 2023. Multilingual language models are not multicultural: A case study in emotion. In *Proceedings of the 13th Workshop on Computational Approaches to Subjectivity, Sentiment, & Social Media Analysis*, pages 202–214, Toronto, Canada. Association for Computational Linguistics.

Joseph Henrich, Steven J Heine, and Ara Norenzayan. 2010. The weirdest people in the world? *Behavioral and brain sciences*, 33(2-3):61–83.

Pratik Joshi, Sebastin Santy, Amar Budhiraja, Kalika Bali, and Monojit Choudhury. 2020. The state and fate of linguistic diversity and inclusion in the NLP world. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 6282–6293, Online. Association for Computational Linguistics.

Bonnie N Kaiser and Lesley Jo Weaver. 2019. Culture-bound syndromes, idioms of distress, and cultural concepts of distress: New directions for an old concept in psychological anthropology. *Transcultural psychiatry*, 56(4):589–598.

Simon Kemp. 2023. Digital 2023 April Global Statshot Report. https://datareportal.com/reports/digital-2023-april-global-statshot. Twitter advertising audience share data at UN subregion level. Accessed: April 2023.

Heather A Kissel and Bruce H Friedman. 2023. Participant diversity in psychophysiology. *Psychophysiology*, 60(11):e14369.

Pang Wei Koh, Shiori Sagawa, Henrik Marklund, Sang Michael Xie, Marvin Zhang, Akshay Balsubramani, Weihua Hu, Michihiro Yasunaga, Richard Lanas Phillips, Irena Gao, and 1 others. 2021. WILDS: A benchmark of in-the-wild distribution shifts. In *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 5637–5664. PMLR.

Roberto Lewis-Fernández, Neil Krishan Aggarwal, Sofie Bäärnhielm, Hans Rohlof, Laurence J Kirmayer, Mitchell G Weiss, Sushrut Jadhav, Ladson Hinton, Renato D Alarcón, Dinesh Bhugra, and 1 others. 2014. Culture and psychiatric evaluation: operationalizing cultural formulation for dsm-5. *Psychiatry: Interpersonal and biological processes*, 77(2):130–154.

Anqi Li, Yu Lu, Nirui Song, Shuai Zhang, Lizhi Ma, and Zhenzhong Lan. 2024. Understanding the therapeutic relationship between counselors and clients in online text-based counseling using llms. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 1280–1303.

Anqi Li, Lizhi Ma, Yaling Mei, Hongliang He, Shuai Zhang, Huachuan Qiu, and Zhenzhong Lan. 2023. Understanding client reactions in online mental health counseling. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 10358–10376.

Chen Cecilia Liu, Hiba Arnaout, Nils Kovačić, Dana Atzil-Slonim, and Iryna Gurevych. 2026. Tailored emotional llm-supporter: Enhancing cultural sensitivity. In *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 535–574.

Anthony J Marsella and Ann Marie Yamada. 2000. Culture and mental health: An introduction and overview of foundations, concepts, and issues. In *Handbook of multicultural mental health*, pages 3–24. Elsevier.

Anthony J Marsella and Ann Marie Yamada. 2010. Culture and psychopathology: Foundations, issues, directions. *Journal of Pacific Rim Psychology*, 4(2):103–115.

Margaret Mitchell, Simone Wu, Andrew Zaldivar, Parker Barnes, Lucy Vasserman, Ben Hutchinson, Elena Spitzer, Inioluwa Deborah Raji, and Timnit Gebru. 2019. Model cards for model reporting. In *Proceedings of the Conference on Fairness, Accountability, and Transparency*, pages 220–229, New York, NY, USA. Association for Computing Machinery.

SM Murray, N Kass, T Mendelson, and J Bass. 2016. The ethics of mental health survey research in low- and middle-income countries. *Global Mental Health*, 3:e12.

NapoleonCat. 2024. Facebook users by country—global statistics. https://stats.napoleoncat.com. Data sourced from Meta Advertising Tools via NapoleonCat. Licensed under Creative Commons Attribution 4.0 International. Accessed: July 2024.

Yarin Ovadia, Emily Fertig, Jie Ren, Zachary Nado, D. Sculley, Sebastian Nowozin, Joshua V. Dillon, Balaji Lakshminarayanan, and Jasper Snoek. 2019. Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift. In *Advances in Neural Information Processing Systems*, volume 32.

Sachin R Pendse, Kate Niederhoffer, and Amit Sharma. 2019. Cross-cultural differences in the use of online mental health support forums. *Proceedings of the ACM on Human-Computer Interaction*, 3(CSCW):1–29.

Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. 2023. Robust speech recognition via large-scale weak supervision. *Proceedings of the 40th International Conference on Machine Learning*.

Sunny Rai, Khushi Shelat, Devansh Jain, Ashwin Kishen, Young Min Cho, Maitreyi Redkar, Samindara Hardikar-Sawant, Lyle Ungar, and Sharath Chandra Guntuku. 2025a. Cross-cultural differences in mental health expressions on social media. In *Proceedings of the 3rd Workshop on Cross-Cultural Considerations in NLP (C3NLP 2025)*, pages 132–142.

Sunny Rai, Elizabeth C Stade, Salvatore Giorgi, Ashley Francisco, Lyle H Ungar, Brenda Curtis, and Sharath C Guntuku. 2024. Key language markers of depression on social media depend on race. *Proceedings of the National Academy of Sciences*, 121:e2319837121.

Sunny Rai, Khushang Zaveri, Shreya Havaldar, Soumna Nema, Lyle Ungar, and Sharath Chandra Guntuku. 2025b. Social norms in cinema: A cross-cultural analysis of shame, pride and prejudice. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 11396–11415.

Semrush. 2023. Reddit.com traffic analytics and market share—country level. https://www.semrush.com/website/reddit.com/overview/. Global traffic share by country for Reddit.com, March 2023. Accessed: March 2023.

Yla R Tausczik and James W Pennebaker. 2010. The psychological meaning of words: Liwc and computerized text analysis methods. *Journal of language and social psychology*, 29(1):24–54.

Harry C Triandis. 1996. The psychological measurement of cultural syndromes. *American psychologist*, 51(4):407.

World Health Organization. 2024. How AI could help improve access to mental health treatment. Accessed via World Economic Forum.

Chao Zhao, Pamela Hinds, and Ge Gao. 2012. How and to whom people share: The role of culture in self-disclosure in online communities. In *Proceedings of the ACM 2012 Conference on Computer Supported Cooperative Work*, pages 67–76, New York, NY, USA. Association for Computing Machinery.

Creating Multilingual Mental Health Dialogue Datasets: Limits of Persona-Based Localization via Nationality and Language

Yunkai Xu and Saeed Abdullah
Pennsylvania State University, United States
{yunkai, saeed}@psu.edu

Abstract

AI and large language models (LLMs) have emerged as promising tools to address global mental health challenges. Despite the global nature of these challenges, there remains a critical shortage of high-quality datasets for training and evaluating such systems. To mitigate this gap, researchers increasingly generate synthetic clinical personas to simulate user data and test digital mental health support systems. However, most validated personas rely on English-centric contexts. This paper investigates whether similar persona-based methods can be used to generate multilingual mental health datasets. We modified nationality and language parameters in personas to generate clinical dialogues in Mandarin, Bengali, and Hindi. We then examined how different LLMs perform when evaluating the depression severity of these generated multilingual datasets against the baseline in English. Our findings indicate that just adding nationality and language parameters in personas might not be adequate, as it can introduce clinical inconsistency across languages. LLM judge models often exhibit inaccuracies in assessing depression severity in non-English texts, with performance varying across different models. This exposes the systemic limitations of applying English-centric personas to multilingual contexts. Ultimately, our work highlights the urgent need for culturally responsive data generation to ensure equitable mental health systems globally.

All personas and the full pipeline are publicly available at **GitHub link**.

1 Introduction

Depression presents one of the significant global challenges among mental health disorders (Moitra et al., 2023; Liu et al., 2024). Regions with limited medical infrastructure, such as Bangladesh, experience a severe shortage of mental health professionals (Hasan et al., 2021). Artificial intelligence (AI) and large language models (LLMs) provide a potential medium for depression screening and continuous support (Chen et al., 2024b; Ignashina et al., 2025; Li et al., 2025b; Zhang et al., 2025). However, the benefits of these technological advancements are also not distributed equitably across regions. Prior work has primarily focused on English (Zhang et al., 2025) and emerging evidence suggests that language itself plays a critical role in shaping LLM performance, with more pronounced effects observed in non-English languages (Jin et al., 2023; Raihan et al., 2026). This marginalizes populations that use other languages, creating systemic biases and representation disparities in digital mental health assessments.

Recently, researchers have increasingly utilized synthetic data to mitigate these biases in underrepresented languages. This need is particularly pronounced in the mental health domain, where access to real-world data is further constrained by privacy concerns (Kang et al., 2024; Lorge et al., 2025). Among various approaches to synthetic data generation, persona-based methods have emerged as an effective strategy, particularly for scaling up data generation (Zhang et al., 2018; Ge et al., 2025; Jandaghi et al., 2024). In the mental health field, some personas simulate specific psychological states, such as those defined by the Beck Depression Inventory II (BDI-II) (Weiner and Craighead, 2010), acting as standardized patients for training and evaluating clinical dialogue systems (Wang et al., 2025).

However, the majority of validated clinical synthetic personas originate from English and Western contexts (Wang et al., 2025). It might be feasible to address the current language gap by modifying specific demographic and linguistic variables within the original English persona prompt. However, prior studies demonstrate that altering a single persona parameter affects downstream behavior in other domains (Weeber et al., 2026; Kamruzzaman et al., 2025). It remains unclear whether this

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 138–152
July 4, 2026 ©2026 Association for Computational Linguistics

parameter-based localization preserves the original clinical symptoms when generating interactions in non-English contexts.

This study investigates the preservation of clinical features following the parameter-based adaptation of synthetic personas. We designed a controlled experiment using a clinically validated English persona as a baseline (Wang et al., 2025). By modifying only the language and nationality variables, we generated parallel personas for different regions. We then used independent judges implemented with different LLMs to assess the depression severity reflected in the generated chat histories. Our study addresses the following research questions:

- **RQ1:** How does parameter-based localization affect the clinical consistency of symptoms expressed by synthetic personas across different languages?
- **RQ2:** How do diverse LLMs model judges vary in their capability and certainty when assessing depression severity in non-English synthetic conversations generated by the personas?

By addressing these questions, our research provides the following key contributions:

- We provide empirical evidence that modifying persona parameters leads to disparities in depression level representation and weakens alignment with clinical severity levels in dialogue datasets generated in Mandarin, Bengali, and Hindi.
- We highlight the systemic limitations of applying synthetic personas to multilingual artificial intelligence systems, and argue for treating them as clinical artifacts. Specifically, we call for rigorous output-level validation and language-specific evaluation to maintain cross-lingual consistency.

2 Related Works

2.1 Multilingual Large Language Models in Mental Health

Mental health care resources remain unevenly distributed worldwide, with many regions lacking trained clinicians and accessible services (Hasan et al., 2021). Recent work has therefore started to explore how LLMs might support mental health care in non-English contexts (Zhang et al., 2025). Existing efforts span a range of linguistic and cultural settings. In Chinese-speaking contexts, prior studies have developed LLM-based support for cognitive behavioral therapy and deployed chatbot systems for anxiety and depression support (Na, 2024; Chen et al., 2025). Similar efforts are beginning to emerge in South Asia. For instance, one study considered the potential of LLMs for suicide prevention in India (Chakraborty et al., 2025), while another proposed an LLM-supported intervention for postpartum mental health among women in Bangladesh (Ahmed et al., 2025). Taken together, these studies point to growing interest in multilingual mental health support, but they also remain focused on particular languages and application scenarios.

In principle, fair multilingual models should maintain consistent performance across languages. However, some studies report clear performance gaps between high-resource languages such as English and lower-resource languages such as Bengali (Bhowmik et al., 2025). A main reason for this gap is the imbalance in training and fine tuning data. High-quality clinical data are common in English datasets but rare in many other languages. This shortage limits the use of language models for mental health support in different cultural settings.

2.2 Datasets for Depression Detection and Synthetic Data

Existing depression detection datasets are primarily English-centric, sourced from platforms like Reddit and X (Gui et al., 2019; Ríssola et al., 2020; Naseem et al., 2022; Parapar et al., 2026). While resources in languages such as Chinese, Japanese and Portuguese have emerged (dos Santos et al., 2024; Xiao et al., 2026; Agarwal and Dhingra, 2021), they remain limited to single-language settings. As a result, they do not address the broader challenge of capturing linguistic and cultural diversity across multiple languages.

Collecting large-scale clinical data in non-English context is further hindered by privacy regulations and the scarcity of online mental health communities (Kang et al., 2024; Lorge et al., 2025). To bridge this gap, researchers often translate English datasets into other languages (Yang et al., 2019; Myung et al., 2024; Jin et al., 2023). However, human translation is costly and difficult to scale, while machine translation often fails to capture cultural nuances or specific mental health expres-

sions (Bhowmik et al., 2025; Raihan et al., 2026).

To address data scarcity and ethical constraints, recent studies leverage LLMs for synthetic data generation (Wang et al., 2024). In mental health, this includes simulating conversational therapy sessions (Zhezherau and Yanockin, 2024), patient needs (Ronan et al., 2025), and patients' clinical synopses to balance severity distributions (Kang et al., 2024). Others have generated context-enhanced social media data to identify psychosocial risks (Garg et al., 2026). Despite these advances, existing work focuses almost exclusively on single-language generation. However, existing work often focuses on generating data within a single language. It remains unclear how synthetic representations generalize across languages and whether they can preserve clinically meaningful signals in a multilingual framework.

2.3 Personas as a Source of Synthetic Data

Personas represent archetypal people through fictional yet data-informed profiles, enabling designers to reason about the characteristics and goals of a target population (Pruitt and Grudin, 2003). LLMs can generate high-quality personas comparable to human experts (Schuller et al., 2024), making them a practical alternative when traditional data collection is constrained (Salminen et al., 2025). LLMs have further enabled data-driven persona development (Jung et al., 2025), maintaining high fidelity even in specialized domains (Kaur et al., 2025).

In mental health, personas are increasingly used to synthesize therapeutic dialogue data to bypass data scarcity. For instance, Jandaghi et al. (2024) proposed a generator-critic architecture for faithful persona-based interactions, while Wu et al. (2025) leveraged persona traits to modulate emotional support sessions. To ensure clinical grounding, Wang et al. (2025) incorporated specific attributes like BDI-II scores into simulations. To standardize these efforts, the PatientHub framework (Sabour et al., 2026) provides a modular system for reproducible simulated patient deployment.

However, the use of synthetic personas introduces risks associated with data validity and algorithmic bias (Li et al., 2025a; Batzner et al., 2025). Variations in the components of a persona can cause inconsistencies in downstream performance (Wu et al., 2025). Kamruzzaman et al. (2025) identified that assigning nationality-specific personas to LLMs results in emotional stereotypes, as the models disproportionately attribute certain emotions to specific countries. Furthermore, assigned nationality personas can alter how models perceive different nations, which often leads to more favorable treatment of Western regions compared to others (Kamruzzaman and Kim, 2025).

While prior work highlights cultural bias in LLMs in healthcare, the majority of validated clinical personas are still developed within English-speaking contexts. There remains a lack of evidence concerning whether the simple modification of nationality and language parameters within English-centric prompts is sufficient to generate valid clinical dialogues in other languages. Our work addresses this gap by investigating how such adaptations influence the clinical accuracy of depression assessments across different linguistic settings.

3 Method

3.1 Persona Construction

We adapt the workflow illustrated in Figure 1 and the clinically validated baseline personas from prior work by Wang et al. (Wang et al., 2025). The personas consist of several dimensions that capture demographic attributes, depression symptoms, communication patterns, and social context (see Appendix A.2). Table 1 summarizes these dimensions and their sources. These elements serve specific functions in clinical depression diagnosis. For instance, a documented life history is an important component in understanding depression and related mental health outcomes, and analyzing detailed life histories helps identify pathways that link individual experiences with mental health trajectories (Singer et al., 1998). Therefore, we include life history information when constructing depression personas. In total, we use 12 personas (Table 5). All personas include the dimensions described above, and the content in these dimensions differ across personas. We focus on personas' depression characteristics by varying symptoms, severity levels, and BDI-II scores to represent different levels of depression.

We introduce two new variables to these baseline personas: **Nationality** and **Language Use**. Many prior studies show that Nationality can change how a persona behaves in downstream tasks (Kamruzzaman and Kim, 2025; Kamruzzaman et al., 2025). We include the Language Use variable to dictate the output language of the generated text. We represent specific geographic regions by pairing nationality



Figure 1: Overview of the multilingual synthetic dialogue generation and evaluation workflow. Example dialogue sessions are translated into English for readability using Google Translate[1].

with language use (United States-English, Chinese-Mandarin, Bangladeshi-Bengali, and Indian-Hindi). We focused on these regions and languages as they are among the most widely spoken languages globally (SIL International, 2023). The remainder of the persona prompt remains in English and keeps the same content and structure as the original clinically validated persona. Using this procedure, we generate distinct personas for different target regions, with 12 personas in each language and 48 personas in total.

This approach follows prior work that adopts controlled modification to enable systematic comparison across persona settings (Sakai et al., 2025).

3.2 Evaluation: Pairwise Severity Comparison

To validate the clinical consistency of our generated personas, we mainly replicate a pairwise depression severity differentiation task (Wang et al., 2025) and extend this to a multilingual context to test our personas. The evaluation process consists of two stages:

1. **Dialogue Generation:** We employ an independent LLM-based therapist agent (powered by ChatGPT-4o-mini) to conduct semi-structured clinical interviews with each persona. The agent using the simple prompt was adapted from (Wang et al., 2025), with additional instructions added to ensure that the generated responses remained consistent with the language settings specified in the persona (see Appendix B). For each persona, this interaction generated five distinct dialogue sessions. Specifically, four sessions were designed to focus on individual target symptoms defined in the persona, while an additional mixed-symptom session combined all four symptoms. The dialogue session consisted of five to seven turns. Unlike Wang et al. (2025)'s work, our personas possess specific nationalities, and the therapist interacts with them in their **corresponding languages**. This results in a multilingual corpus consisting of 60 dialogue sessions per language.

2. **Blind Pairwise Judging:** An independent LLM-based judge is presented with generated dialogues from two personas with different depression severity levels (based on BDI-II scores). The judge is blinded to the underlying persona configurations and scores. Its task is to determine which patient exhibits a higher level of depression severity, or if they are indistinguishable (i.e., Persona A > Persona B, B > A, or "Tie" as a tie case). Consequently,

[1] https://translate.google.com/

Table 1: Dimensions used to construct clinical personas.

Dimension	Sources
Age	(Faravelli et al., 2013)
Gender	(Faravelli et al., 2013; Ensel, 1982)
BDI-II score	(Weiner and Craighead, 2010)
Depression symptoms and severity	(American Psychiatric Association and American Psychiatric Association, 2013)
Communication style	(Smirnova et al., 2018; Al-Mosaiwi and Johnstone, 2018)
Life history	(Singer et al., 1998)
Social context	(Aseltine et al., 1994; Brown, 2002)
Clinician behavior constraints	(Bickley and Szilagyi, 2012)
Social media use	(Huang, 2022; Berryman et al., 2018)

each evaluation cycle comprises 66 pairwise comparisons ($N_{\text{total}} = \binom{12}{2} = 66$).

This setup evaluates whether the clinical cues of depression remain detectable and consistent when expressed through different languages and cultural backgrounds, and whether the LLM judge can maintain diagnostic sensitivity despite the changes in the personas.

3.3 Evaluation Metrics

Replicated from Wang et al. (2025)'s work, We also evaluate model performance using three metrics: overall accuracy, same-level error rate, and tie distance.

Overall Accuracy. This metric evaluates the LLM judge's proficiency in correctly identifying the relative depression severity within each pair. A prediction is counted as correct if the judge successfully selects the dialogues associated with the persona that possesses the higher ground-truth BDI-II score. Cases where the model outputs selects the persona with the lower score are treated as incorrect. Tie responses were treated as a separate outcome category. Thus, the total number of comparisons can be expressed as:

$$N_{\text{total}} = N_{\text{correct}} + N_{\text{incorrect}} + N_{\text{tie}} \quad (1)$$

Overall accuracy is then computed over non-tie comparisons:

$$\text{Overall Accuracy} = \frac{N_{\text{correct}}}{N_{\text{total}} - N_{\text{tie}}} \times 100\% \quad (2)$$

Same-Level Error Rate. This metric analyzes the quality of model errors. When a model makes an incorrect prediction, we examine whether the two personas belong to the same BDI-II severity category. We define Same-Level Error Rate as the percentage of incorrect predictions where the two evaluated personas actually belong to the same severity level. This metric captures errors that occur near clinical severity boundaries.

$$\text{Same-Level Error Rate} = \frac{E_{\text{same}}}{E_{\text{total}}} \times 100\% \quad (3)$$

where E_{same} is the number of errors between personas within the same severity category, and E_{total} is the total number of incorrect predictions. Errors that cross severity boundaries indicate larger clinical misjudgments.

Tie Distance. Models occasionally refuse to select one chat history and instead output a tie. We measure the Average Tie Distance to quantify the severity gap between the personas in these tie cases. The distance is the absolute difference between the underlying BDI-II scores of the two personas. A larger tie distance indicates that the model expresses uncertainty even when the actual severity difference is large.

3.4 Model Use

We use several LLMs as judges, including proprietary models (GPT-4o-mini (OpenAI et al., 2024), DeepSeek-V3.2 (DeepSeek-AI et al., 2025b)) and open-weight models (LLaMA3.1-8B (Grattafiori et al., 2024), Qwen3-8B (Yang et al., 2025), and DeepSeek-R1-8B (DeepSeek-AI et al., 2025a)). We use the 8B versions to align with prior work (Wang et al., 2025) and maintain efficiency.

In the evaluation task, each model compares the dialogues from two personas to decide which one shows more severe depression. The models do not

Table 2: Overall accuracy across models and languages.

Model	Bengali	English	Hindi	Mandarin
ChatGPT-4o-mini	92.42	95.45	87.88	86.36
DeepSeek-v3.2	90.91	93.75	83.33	84.85
DeepSeek-R1-8B	63.33	98.21	67.24	84.62
Llama3-8B	45.45	84.13	65.38	75.76
Qwen3-8B	71.21	89.39	73.44	80.30

see the persona prompts, so the assessment is based only on the generated text.

4 Findings

4.1 Cross-Model and Cross-Lingual Results

4.1.1 Overall Accuracy and Cross-Lingual Disparity

We present the overall accuracy of the evaluated models across four languages in Table 2. The results reveal a persistent English advantage across all language models. Performance in English consistently serves as the upper bound for each model.

ChatGPT-4o-mini and DeepSeek-v3.2 achieve the highest overall accuracy. ChatGPT-4o-mini maintains the lowest cross-lingual variability with a standard deviation of 4.17. DeepSeek-v3.2 is slightly higher than ChatGPT-4o-mini. Both of them demonstrate relatively robust calibration in interpreting depression severity across different linguistic contexts.

Smaller open-weight models demonstrate substantial performance drops when processing non-English personas. DeepSeek-R1-8B and Llama3-8B exhibit high performance fluctuations across languages, with standard deviations of 16.15 and 16.69 respectively. DeepSeek-R1-8B achieves 98.21% accuracy in English but drops to 63.33% in Bengali and 67.24% in Hindi. This indicates that mental disorder severity interpretation capabilities in smaller models remain heavily biased toward English contexts.

4.1.2 Same-Level Error Rate and Cross-Lingual Disparity

Cross-language differences manifest in overall accuracy and in the nature of the errors. We analyze whether incorrect model answers stay within the same depression severity level or cross-severity boundaries. Table 3 details these error distributions.

Models exhibit severe cross-lingual inconsistency in their error calibration. English consistently corresponds to fewer cross-severity mistakes for most models. For example, DeepSeek-R1-8B maintains a 100% Same-Level Error Rate in English. This means all its English mistakes occur between personas of identical severity tiers. This is important because many studies are concerned with severity categories rather than exact scores (Naseem et al., 2022; Peng et al., 2026), making within-tier errors less problematic than cross-tier ones. However, its Same-Level Error Rate drops to 22.73% in Bengali. This indicates that Bengali errors frequently cross-severity boundaries.

Table 3: Same-level error rates (%) across languages and models. Higher values indicate fewer cross-severity errors. Bold values indicate the highest score within each language.

Model	Bengali	Hindi	Mandarin	English
ChatGPT-4o-mini	80.00	**87.50**	66.67	66.67
DeepSeek-v3.2	**100.00**	72.73	70.00	**100.00**
DeepSeek-R1-8B	22.73	31.58	**80.00**	**100.00**
Llama3-8B	23.33	33.33	50.00	60.00
Qwen3-8B	31.58	29.41	61.54	85.71

Llama3-8B and Qwen3-8B show similar patterns. Llama3-8B confines 60.00% of its English errors to the same severity level, compared to 23.33% in Bengali and 33.33% in Hindi. DeepSeek-v3.2 is an exception. It maintains consistently high Same-Level Error Rates across all languages, indicating a robust calibration in distinguishing adjacent severity levels regardless of the input language. These findings demonstrate that language changes affect both the performance level and the structural consistency of clinical severity judgments.

4.1.3 Uncertainty and Tie Behavior

We further analyze model uncertainty by examining explicit tie outputs. Table 4 summarizes the frequency and severity distance of tie cases.

Tie behavior varies unevenly across models and languages. DeepSeek-R1-8B produces the highest number of ties across all four languages, totaling 25 cases. Llama3-8B produces 14 ties, but these are heavily concentrated in Bengali and Hindi. ChatGPT-4o-mini never outputs a tie, and DeepSeek-v3.2 rarely produces ties.

The context of these ties also differs significantly between models. DeepSeek-v3.2 expresses uncertainty exclusively in near boundary cases, with a mean tie distance of 4.00. DeepSeek-R1-8B and Llama3-8B frequently express uncertainty even when severity differences are large. Their mean tie distances are 10.80 and 14.14 respectively.

Table 4: Overall tie counts and average tie distance by model.

Model	Tie Count	Avg Distance	Max Distance
DeepSeek-R1-8B	25	10.80	34
Llama3-8B	14	14.14	28
Qwen3-8B	2	5.50	6
DeepSeek-v3.2	2	4.00	5
ChatGPT-4o-mini	0	-	-

Furthermore, the difficulty threshold that triggers a tie depends on the language. For DeepSeek-R1-8B, the average tie distance is 15.12 in Hindi compared to 7.33 in Bengali and 8.90 in English. This indicates that the severity gap required to confuse the model is not constant and shifts substantially according to the linguistic context.

4.2 Persona-based Methods for Multilingual Dataset

The high accuracy and low cross boundary error rates observed in English evaluations suggest that the baseline English personas successfully generate distinct and recognizable clinical traits, which is consistent with prior studies (Wang et al., 2025). However, the decline in judge accuracy for Bengali and Hindi indicates a degradation in the underlying text. The increased frequency of cross-severity errors and large distance tie cases in non-English languages shows that the generated dialogues may lack clear clinical signals in the original personas.

Overall, these results collectively demonstrate that modifying the nationality and language labels within an English-centric persona is insufficient to create viable multilingual clinical personas. The shallow localization process introduces clinical ambiguity and this problem is much more visible in smaller 8B models, causing the resulting text to lose alignment with the intended BDI-II severity scales.

5 Discussion

5.1 Why Minimal Localization in Personas Fails to Preserve Clinical Cues

This study examined a strategy for multilingual persona construction: starting from an expert-validated English persona prompt and replacing only nationality and language to generate non-English personas. We then evaluated the resulting dialogues through blinded severity judgment. Across LLM judge models, English consistently acted as the upper bound, while non-English dialogues more often led to severity misclassification and ties. This pattern suggests that simple parameter substitution does not reliably preserve clinically relevant cues across languages.

One potential reason is that changing nationality and language also alters the cultural context embedded in the persona, while symptom expression may vary substantially across cultures and therefore may not be preserved consistently (Goodmann et al., 2021; Jovanović et al., 2026; Bradshaw et al., 2026). The same BDI-II level can surface in different ways depending on the conversation, as the expression of and response to depression vary significantly across cultures (Teja et al., 1971). This issue has been observed not only in real clinical interactions but also in synthetic sessions generated from personas (Sakai et al., 2025). When these expressive patterns shift, the resulting dialogue may still describe similar experiences but fail to present them in a form that judges can consistently interpret. Prior work reports similar cross-lingual gaps in health-related tasks and shows that models often perform better when queries are expressed in English (Jin et al., 2023). Therefore, our findings extend this observation to persona-driven dialogue generation.

In addition, both nationality and language do not act as neutral parameters for the LLM dialogue generation and the LLM judges. Evidence from cultural benchmarks shows that model performance can vary across regions and languages on everyday knowledge tasks, and that performance can remain higher in English than in the local language for some low-resource cultures (Myung et al., 2024). Furthermore, assigning nationality has been shown to change model outputs in systematic ways, including how emotions and social attributes are expressed (Kamruzzaman and Kim, 2025; Kamruzzaman et al., 2025). In our setting, this means that the generated dialogue may introduce additional culture-specific interaction patterns that were not present in the original English persona. As a result, symptom descriptions can shift in structure and emphasis, which reduces the clarity of severity signals even when the underlying prompt remains unchanged.

5.2 Implications for Multilingual Mental Health Persona Construction and Evaluation

The findings have direct implications for the use of personas in multilingual mental health data generation and evaluation. First, multilingual dialogues

produced through simple parameter replacement should not be treated as equivalent samples across languages. In our study, non-English dialogues show not only lower accuracy but also more cross-severity errors and unstable tie behavior. This indicates a shift in the underlying data distribution. Similar effects have been reported in multilingual mental health benchmarks, where model performance drops when tasks rely on translated rather than native data, with variation across languages and translation quality (Raihan et al., 2026).

Second, persona construction requires stronger methodological control in clinical settings. Prior work has identified common issues in persona-based research, including weak specification of target populations and limited reporting of construction procedures (Batzner et al., 2025). Our results show that these issues extend to multilingual settings. When personas are adapted through minimal parameter changes, the resulting dialogues may no longer preserve the intended clinical condition. A multilingual clinical persona should therefore be treated as a new artifact that requires validation at the output level, rather than as a direct extension of an English template.

Third, the observed cross-language gap may arise from both generation and evaluation. Prior work shows that LLM-based evaluation can align with human judgments in English tasks, while also exhibiting bias and sensitivity to LLM judgeś prompt design (Liu et al., 2023). However, this alignment does not guarantee consistency across languages. Recent studies report that multilingual LLM-as-a-judge setups can produce inconsistent results on parallel data, especially in lower-resource languages (Fu and Liu, 2025). Both human and LLM judges have also been shown to be affected by bias and input variation (Chen et al., 2024a; Ye et al., 2024). In our setting, weaker clinical cues in non-English dialogue and lower LLM judge consistency may interact, producing larger observed differences across languages.

6 Conclusion

This paper examined whether modifying nationality and language variables in an English clinical persona prompt can preserve depression severity signals across languages, using controlled persona construction, multilingual dialogue generation, and blinded pairwise evaluation. The results show that English remains the most stable setting, while Bengali and Hindi exhibit lower accuracy, more cross-severity errors, and higher uncertainty in tie cases, which indicates that the generated dialogues do not consistently reflect the intended BDI-II levels when only minimal parameters are changed. The comparison across models further shows that performance differences are not uniform, and that some models maintain calibration in English but fail to do so in other languages, suggesting that both generation and evaluation processes contribute to the observed gaps. These findings demonstrate that parameter-based localization does not maintain clinical consistency and that multilingual personas produced in this way should not be treated as equivalent to their English counterparts. Future work should treat multilingual persona construction as a separate design and validation process that incorporates culturally grounded expression, evaluates symptom representation beyond severity labels, and uses multiple evaluation strategies, including human review to ensure that generated data can support mental health applications across languages.

7 Ethical Considerations

This work relies on synthetic personas and dialogues rather than identifiable data. The personas sourced from Wang et al. (2025) are also anonymous. Although personas are grounded in clinically informed attributes such as BDI-II severity levels, the generated content should not be interpreted as clinical evidence or used for diagnosis. Given the sensitive nature of mental health, we acknowledge that synthetic personas may oversimplify or misrepresent how depression is expressed across languages and cultures (Teja et al., 1971; Sakai et al., 2025). Our findings further show that minimal parameter-based localization can distort clinical signals, which raises risks if such data are treated as equivalent across languages or used without validation. In addition, observed cross-lingual performance disparities reflect broader fairness concerns in multilingual NLP, where low-resource languages may be disproportionately affected. We therefore caution against deploying such synthetic data in real-world mental health applications and advocate for culturally grounded data construction and validation practices.

8 Limitations

First, our conclusions are based on a specific localization strategy, namely replacing nationality

and language in an English persona prompt while keeping the rest of the structure fixed. This design allowed us to isolate the effect of minimal parameter-based localization, but it simplifies cultural and language use variation by encoding it through a limited set of persona parameters, which may overlook within-country and within-region variation. In particular, language and cultural background are coupled in our current design through nationality-language pairings. Therefore, we cannot fully determine whether the observed cross-lingual differences arise from linguistic structure, culturally specific symptom expression, the behavior of the LLMs used for generation and judgment, or the interaction among these factors, as discussed in Section 5.1. Future work should separate these dimensions more explicitly, for example by comparing multiple languages within the same cultural context, multiple cultural contexts within the same language, and bilingual settings where patients may move between languages depending on emotional or clinical context (Williams et al., 2020; Elwahsh et al., 2025).

We also do not claim that all forms of multilingual persona construction will lead to the same results. Richer localization methods that explicitly model cultural context, symptom narration, and discourse style may perform differently. Future work should compare minimal localization with stronger adaptation strategies that preserve symptom strength while allowing culturally appropriate expression when generating and using synthetic multilingual personas.

A second limitation concerns the evaluation pipeline. We relied on LLM-based pairwise severity judgments and did not include independent validation from human clinicians, or native-speaking annotators. As a result, we could not directly verify whether the generated multilingual dialogues were comparable in clinical realism, symptom coverage, discourse naturalness, or linguistic quality across languages. Our evaluation measures severity recoverability, but this is only one aspect of validity for multilingual clinical personas. A dialogue may preserve the intended BDI-II severity ordering while still failing to reflect realistic narrative structure, culturally grounded symptom framing, or safe and appropriate clinical communication. Future work should evaluate multilingual personas across multiple dimensions, including symptom fidelity, cultural appropriateness, linguistic naturalness, discourse realism, and safety.

Our current framework cannot fully disentangle dialogue generation quality from LLM judge reliability. The observed cross-lingual performance differences may reflect weakened clinical cues in the generated dialogues, inconsistent multilingual reasoning by the judge models, or both. Although the judge models were blinded to the persona prompts and evaluated only the generated conversations, their judgments may still be affected by language-specific limitations and model-specific uncertainty. Future work should reduce this uncertainty by combining multiple evaluation strategies, including human review, multilingual expert annotation, agreement analysis across LLM judges, and direct quality assessment of the generated dialogues before downstream severity comparison.

There are also constraints in the dialogue generation setup itself (Section 3.2). We largely followed the prompting strategy used in prior work and did not independently evaluate whether the therapist agent guided each patient model with equal depth across languages or maintained balanced coverage of BDI-II symptoms. The generated conversations are limited in length, which may have constrained the range and depth of depressive symptoms expressed in the dialogues. Longer and more adaptive interviews may produce richer clinical signals, but they may also introduce additional variability across languages. Future work should examine how interview length, therapist prompting strategy, and symptom-specific questioning affect the stability of multilingual persona-based dialogue generation.

Finally, we did not conduct statistical significance testing across language conditions in the current analysis. Our pairwise evaluation outcomes include correct, incorrect, and tie cases, and tie behavior varied substantially across models and languages. Rather than imposing a single treatment of ties, we report tie frequency and tie distance as descriptive indicators of model uncertainty. Future work with larger samples should pre-register how tie cases are handled and apply statistical models that can account for repeated comparisons across personas, languages, and judge models.

References

Kaustubh Agarwal and Bhavya Dhingra. 2021. Deep Learning Based Approach For Detecting Suicidal Ideation in Hindi-English Code-Mixed Text: Baseline and Corpus. In *Proceedings of the 18th International Conference on Natural Language Processing (ICON)*, pages 100–105, National Institute of Tech-

nology Silchar, Silchar, India. NLP Association of India (NLPAI).

Istiaq Ahmed, Syed Niaz Mohtasim, Faiza Omar Arpita, Ashraful Islam, and M. Ashraful Amin. 2025. A Conceptual Design Framework of GorbhoShongi App for Mental Well-Being Among Bangladeshi Pregnant and Postpartum Women. In *HCI International 2024 – Late Breaking Posters*, pages 3–13, Cham. Springer Nature Switzerland.

Mohammed Al-Mosaiwi and Tom Johnstone. 2018. In an absolute state: Elevated use of absolutist words is a marker specific to anxiety, depression, and suicidal ideation. *Clinical Psychological Science*, 6(4):529–542.

American Psychiatric Association and American Psychiatric Association, editors. 2013. *Diagnostic and Statistical Manual of Mental Disorders: DSM-5*, 5th ed edition. American Psychiatric Association, Washington, D.C.

Robert H. Aseltine, Susan Gore, and Mary Ellen Colten. 1994. Depression and the social developmental context of adolescence. *Journal of Personality and Social Psychology*, 67(2):252–263.

Jan Batzner, Volker Stocker, Bingjun Tang, Anusha Natarajan, Qinhao Chen, Stefan Schmid, and Gjergji Kasneci. 2025. Whose Personae? Synthetic Persona Experiments in LLM Research and Pathways to Transparency. *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, 8(1):343–354.

Chloe Berryman, Christopher J. Ferguson, and Charles Negy. 2018. Social media use and mental health among young adults. *Psychiatric Quarterly*, 89(2):307–314.

Shimanto Bhowmik, Tawsif Tashwar Dipto, Md Sazzad Islam, Sheryl Hsu, and Tahsin Reasat. 2025. Evaluating LLMs' Multilingual Capabilities for Bengali: Benchmark Creation and Performance Analysis. *Preprint*, arXiv:2507.23248.

Lynn Bickley and Peter G. Szilagyi. 2012. *Bates' Guide to Physical Examination and History-Taking*. Lippincott Williams & Wilkins. Google-Books-ID: g0Ao61hGAloC.

Matt Bradshaw, Koichiro Shiba, Sung Joon Jang, Blake Victor Kent, Rebecca Bonhag, Byron R Johnson, and Tyler J VanderWeele. 2026. Demographic variation in symptoms of depression and anxiety across 22 global flourishing study countries. *Communications Medicine*.

George W. Brown. 2002. Social roles, context and evolution in the origins of depression. *Journal of Health and Social Behavior*, 43(3):255–276.

Tanmoy Chakraborty, Koushik Sinha Deb, Himanshu Kulkarni, Sarah Masud, Suresh Bada Math, Gayatri Oke, Rajesh Sagar, and Mona Sharma. 2025. The promise of generative AI for suicide prevention in India. *Nature Machine Intelligence*, 7(2):162–163.

Chen Chen, Kok Tai Lam, Ka Man Yip, Hung Kwan So, Terry Yat Sang Lum, Ian Chi Kei Wong, Jason C. Yam, Celine Sze Ling Chui, and Patrick Ip. 2025. Comparison of an AI Chatbot With a Nurse Hotline in Reducing Anxiety and Depression Levels in the General Population: Pilot Randomized Controlled Trial. *JMIR Human Factors*, 12(1):e65785.

Guiming Hardy Chen, Shunian Chen, Ziche Liu, Feng Jiang, and Benyou Wang. 2024a. Humans or LLMs as the Judge? A Study on Judgement Bias. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 8301–8327, Miami, Florida, USA. Association for Computational Linguistics.

Zhuang Chen, Jiawen Deng, Jinfeng Zhou, Jincenzi Wu, Tieyun Qian, and Minlie Huang. 2024b. Depression Detection in Clinical Interviews with LLM-Empowered Structural Element Graph. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 8181–8194, Mexico City, Mexico. Association for Computational Linguistics.

DeepSeek-AI, Daya Guo, Dejian Yang, and 1 others. 2025a. DeepSeek-r1: Incentivizing reasoning capability in LLMs via reinforcement learning. *Nature*, 645(8081):633–638.

DeepSeek-AI, Aixin Liu, Aoxue Mei, Bangcai Lin, Bing Xue, and 1 others. 2025b. DeepSeek-v3.2: Pushing the frontier of open large language models. *Preprint*, arxiv:2512.02556 [cs].

Wesley Ramos dos Santos, Rafael Lage de Oliveira, and Ivandré Paraboni. 2024. SetembroBR: A social media corpus for depression and anxiety disorder prediction. *Language Resources and Evaluation*, 58(1):273–300.

Sarah Elwahsh, Nora Stern, Aneesha Singh, and Amid Ayobi. 2025. Linguistic Diversity and Mental Well-Being: Co-Designing Custom AI Chatbots with Multilingual Mothers. In *Proceedings of the 7th ACM Conference on Conversational User Interfaces*, ACM Conferences, pages 1–17.

Walter M. Ensel. 1982. The role of age in the relationship of gender and marital status to depression. *The Journal of Nervous and Mental Disease*, 170(9):536.

Carlo Faravelli, Maria Alessandra Scarpato, Giovanni Castellini, and Carolina Lo Sauro. 2013. Gender differences in depression and anxiety: The role of age. *Psychiatry Research*, 210(3):1301–1303.

Xiyan Fu and Wei Liu. 2025. How Reliable is Multilingual LLM-as-a-Judge? In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 11040–11053, Suzhou, China. Association for Computational Linguistics.

Muskan Garg, Xingyi Liu, Eunji Jeon, Joanna M. Biernacka, Mark A. Frye, Yonas E. Geda, and Sunghwan Sohn. 2026. Leveraging reddit data for context-enhanced synthetic health data generation to identify low self esteem. *Frontiers in Psychiatry*, 16.

Tao Ge, Xin Chan, Xiaoyang Wang, Dian Yu, Haitao Mi, and Dong Yu. 2025. Scaling Synthetic Data Creation with 1,000,000,000 Personas. *Preprint*, arXiv:2406.20094.

Danielle R. Goodmann, Sariah Daouk, Megan Sullivan, Juan Cabrera, Nancy H. Liu, Suzanne Barakat, Ricardo F. Muñoz, and Yan Leykin. 2021. Factor analysis of depression symptoms across five broad cultural groups. *Journal of Affective Disorders*, 282:227–235.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, and 1 others. 2024. The llama 3 herd of models. *Preprint*, arxiv:2407.21783 [cs].

Tao Gui, Liang Zhu, Qi Zhang, Minlong Peng, Xu Zhou, Keyu Ding, and Zhigang Chen. 2019. Cooperative Multimodal Approach to Depression Detection in Twitter. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33(01):110–117.

M. Tasdik Hasan, Tasnim Anwar, Enryka Christopher, Sahadat Hossain, Md Mahbub Hossain, Kamrun Nahar Koly, K. M. Saif-Ur-Rahman, Helal Uddin Ahmed, Nazish Arman, and Saima Wazed Hossain. 2021. The current state of mental healthcare in bangladesh: part 1 – an updated country profile. *BJPsych International*, 18(4):78–82.

Chiungjung Huang. 2022. A meta-analysis of the problematic social media use and mental health. *International Journal of Social Psychiatry*, 68(1):12–33.

Mariia Ignashina, Paulina Bondaronek, Dan Santel, John Pestian, and Julia Ive. 2025. LLM Assistance for Pediatric Depression. *Preprint*, arXiv:2501.17510.

Pegah Jandaghi, Xianghai Sheng, Xinyi Bai, Jay Pujara, and Hakim Sidahmed. 2024. Faithful Persona-based Conversational Dataset Generation with Large Language Models. In *Proceedings of the 6th Workshop on NLP for Conversational AI (NLP4ConvAI 2024)*, pages 114–139, Bangkok, Thailand. Association for Computational Linguistics.

Yiqiao Jin, Mohit Chandra, Gaurav Verma, Yibo Hu, Munmun De Choudhury, and Srijan Kumar. 2023. Better to Ask in English: Cross-Lingual Evaluation of Large Language Models for Healthcare Queries. *Preprint*, arXiv:2310.13132.

Veljko Jovanović, Sabirah Adams, Rebeca Aritio-Solana, Christ Billy Aryanto, Andreja Avsec, Ali Bakhshi, Martina Baldassarre, Michael Bender, Sophie Berjot, Sonia Betancourth Zambrano, Andreja Brajša-Žganec, Yunier Broche-Pérez, Carmen Buzea, Rosario Cabello, Rosalinda Cassibba, Judith Cavazos-Arroyo, Fatemeh Daemi, Diego D. Díaz-Guerra, Marija Džida, and 56 others. 2026. Depression and anxiety symptoms in adolescents across 30 countries: Cross-national measurement invariance and relationships with subjective well-being. *Journal of Affective Disorders*, 406:121693.

Soon-Gyo Jung, Joni Salminen, Kholoud Khalil Aldous, and Bernard J. Jansen. 2025. Personacraft: Leveraging language models for data-driven persona developmentpersonacraft. *International Journal of Human-Computer Studies*, 197:103445.

Mahammed Kamruzzaman, Abdullah Al Monsur, Gene Louis Kim, and Anshuman Chhabra. 2025. From Anger to Joy: How Nationality Personas Shape Emotion Attribution in Large Language Models. In *Proceedings of the 14th International Joint Conference on Natural Language Processing and the 4th Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics*, pages 48–68, Mumbai, India. The Asian Federation of Natural Language Processing and The Association for Computational Linguistics.

Mahammed Kamruzzaman and Gene Louis Kim. 2025. Exploring Changes in Nation Perception with Nationality-Assigned Personas in LLMs. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 3660–3678, Suzhou, China. Association for Computational Linguistics.

Andrea Kang, Jun Yu Chen, Zoe Lee-Youngzie, and Shuhao Fu. 2024. Synthetic Data Generation with LLM for Improved Depression Prediction. *Preprint*, arXiv:2411.17672.

Arshnoor Kaur, Amanda Aird, Harris Borman, Andrea Nicastro, Anna Leontjeva, Luiz Pizzato, and Dan Jermyn. 2025. Synthetic Voices: Evaluating the Fidelity of LLM-Generated Personas in Representing People's Financial Wellbeing. In *Proceedings of the 33rd ACM Conference on User Modeling, Adaptation and Personalization*, pages 185–193, New York City USA. ACM.

Ang Li, Haozhe Chen, Hongseok Namkoong, and Tianyi Peng. 2025a. LLM Generated Persona is a Promise with a Catch. *Preprint*, arXiv:2503.16527.

Yi Li, Xuanxuan Ding, Yifan Chen, Yeye Li, and Nan Ma. 2025b. Customizable AI for Depression Care: Improving the User Experience of Large Language Model-Driven Chatbots. In *Proceedings of the 2025 ACM Designing Interactive Systems Conference*, DIS '25, pages 1844–1866, New York, NY, USA. Association for Computing Machinery.

Junjiao Liu, Yueyang Liu, Wenjun Ma, Yan Tong, and Jianzhong Zheng. 2024. Temporal and spatial trend analysis of all-cause depression burden based on global burden of disease (GBD) 2019 study. *Scientific Reports*, 14(1):12346.

Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. 2023. G-Eval: NLG Evaluation using Gpt-4 with Better Human Alignment. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 2511–2522, Singapore. Association for Computational Linguistics.

Isabelle Lorge, Dan W. Joyce, Niall Taylor, Alejo Nevado-Holgado, Andrea Cipriani, and Andrey Kormilitzin. 2025. Detecting the clinical features of difficult-to-treat depression using synthetic data from large language models. *Computers in Biology and Medicine*, 194:110246.

Modhurima Moitra, Shanise Owens, Maji Hailemariam, Katherine S. Wilson, Augustina Mensa-Kwao, Gloria Gonese, Christine K. Kamamia, Belinda White, Dorraine M. Young, and Pamela Y. Collins. 2023. Global mental health: Where we are and where we are going. *Current Psychiatry Reports*, 25(7):301–311.

Junho Myung, Nayeon Lee, Yi Zhou, Jiho Jin, Rifki A. Putri, Dimosthenis Antypas, Hsuvas Borkakoty, Eunsu Kim, Carla Perez-Almendros, Abinew A. Ayele, Víctor Gutiérrez-Basulto, Yazmín Ibáñez-García, Hwaran Lee, Shamsuddeen H. Muhammad, Kiwoong Park, Anar S. Rzayev, Nina White, Seid M. Yimam, Mohammad T. Pilehvar, and 3 others. 2024. BLEnD: A Benchmark for LLMs on Everyday Knowledge in Diverse Cultures and Languages. *Advances in Neural Information Processing Systems*, 37:78104–78146.

Hongbin Na. 2024. CBT-LLM: A Chinese Large Language Model for Cognitive Behavioral Therapy-based Mental Health Question Answering. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 2930–2940, Torino, Italia. ELRA and ICCL.

Usman Naseem, Adam G. Dunn, Jinman Kim, and Matloob Khushi. 2022. Early Identification of Depression Severity Levels on Reddit Using Ordinal Classification. In *Proceedings of the ACM Web Conference 2022*, WWW '22, pages 2563–2572, New York, NY, USA. Association for Computing Machinery.

OpenAI, Josh Achiam, Steven Adler, Sandhini Agarwal, and 1 others. 2024. GPT-4 technical report. *Preprint*, arxiv:2303.08774 [cs].

Javier Parapar, Anxo Perez, Xi Wang, and Fabio Crestani. 2026. Overview of eRisk 2025: Early Risk Prediction on the Internet. In *Experimental IR Meets Multilinguality, Multimodality, and Interaction*, pages 242–265, Cham. Springer Nature Switzerland.

Shixin Peng, Kun Jiang, Yu Yang, Jingying Chen, and Guandong Xu. 2026. Framework for Diverse Depression Patients Roleplaying and Cognitive Diagnosis of Scales Using LLMs Based on CoT Prompts. In *Behavioural and Social Computing*, pages 399–414, Singapore. Springer Nature.

John Pruitt and Jonathan Grudin. 2003. Personas: Practice and theory. In *Proceedings of the 2003 Conference on Designing for User Experiences*, DUX '03, pages 1–15, New York, NY, USA. Association for Computing Machinery.

Nishat Raihan, Sadiya Sayara Chowdhury Puspo, Ana-Maria Bucur, Stevie Chancellor, and Marcos Zampieri. 2026. Large Language Models for Mental Health: A Multilingual Evaluation. *Preprint*, arXiv:2602.02440.

Esteban A. Ríssola, Seyed Ali Bahrainian, and Fabio Crestani. 2020. A Dataset for Research on Depression in Social Media. In *Proceedings of the 28th ACM Conference on User Modeling, Adaptation and Personalization*, UMAP '20, pages 338–342, New York, NY, USA. Association for Computing Machinery.

Isabel Ronan, Patrice Crowley, Eva Rombouts, Nicola Cornally, Mohamad M. Saab, David Murphy, and Sabin Tabirca. 2025. A LangChain-based pipeline for one-shot synthetic text generation using generative pre-trained transformers in palliative care research. *Journal of Biomedical Informatics*, 171:104936.

Sahand Sabour, TszYam NG, and Minlie Huang. 2026. PatientHub: A Unified Framework for Patient Simulation. *Preprint*, arXiv:2602.11684.

Shintaro Sakai, Jisun An, Migyeong Kang, and Haewoon Kwak. 2025. Somatic in the East, Psychological in the West?: Investigating Clinically-Grounded Cross-Cultural Depression Symptom Expression in LLMs. *Preprint*, arXiv:2508.03247.

Joni Salminen, Danial Amin, Soon-Gyo Jung, and Bernard Jansen. 2025. The Use of Large Language Models in HCI: A Critical Analysis of Synthetic Users. In *Proceedings of the Augmented Humans International Conference 2025*, AHs '25, pages 413–417, New York, NY, USA. Association for Computing Machinery.

Andreas Schuller, Doris Janssen, Julian Blumenröther, Theresa Maria Probst, Michael Schmidt, and Chandan Kumar. 2024. Generating personas using LLMs and assessing their viability. In *Extended Abstracts of the CHI Conference on Human Factors in Computing Systems*, CHI EA '24, pages 1–7, New York, NY, USA. Association for Computing Machinery.

SIL International. 2023. Ethnologue: Languages of the world. 26th edition.

Burton Singer, Carol D. Ryff, Deborah Carr, and William J. Magee. 1998. Linking life histories and mental health: A person-centered strategy. *Sociological Methodology*, 28(1):1–51.

Daria Smirnova, Paul Cumming, Elena Sloeva, Natalia Kuvshinova, Dmitry Romanov, and Gennadii Nosachev. 2018. Language patterns discriminate mild depression from normal sadness and euthymic state. *Frontiers in Psychiatry*, 9.

J. S. Teja, R. L. Narang, and A. K. Aggarwal. 1971. Depression Across Cultures. *The British Journal of Psychiatry*, 119(550):253–260.

Ke Wang, Jiahui Zhu, Minjie Ren, Zeming Liu, Shiwei Li, Zongye Zhang, Chenkai Zhang, Xiaoyu Wu, Qiqi Zhan, Qingjie Liu, and Yunhong Wang. 2024. A Survey on Data Synthesis and Augmentation for Large Language Models. *Preprint*, arXiv:2410.12896.

Xi Wang, Anxo Perez, Javier Parapar, and Fabio Crestani. 2025. TalkDep: Clinically grounded LLM personas for conversation-centric depression screening. In *Proceedings of the 34th ACM International Conference on Information and Knowledge Management*, CIKM '25, pages 6554–6558. Association for Computing Machinery.

Franziska Weeber, Vera Neplenbroek, Jan Batzner, and Sebastian Padó. 2026. One persona, many cues, different results: How sociodemographic cues impact LLM personalization. *Preprint*, arxiv:2601.18572 [cs].

Irving B. Weiner and W. Edward Craighead. 2010. *The Corsini Encyclopedia of Psychology, Volume 1*. John Wiley & Sons. Google-Books-ID: be0VYic5iWwC.

Aya Williams, Mahesh Srinivasan, Chang Liu, Pearl Lee, and Qing Zhou. 2020. Why do bilinguals code-switch when emotional? Insights from immigrant parent–child interactions. *Emotion*, 20(5):830–841.

Shenghan Wu, Yimo Zhu, Wynne Hsu, Mong-Li Lee, and Yang Deng. 2025. From Personas to Talks: Revisiting the Impact of Personas on LLM-Synthesized Emotional Support Conversations. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 5439–5453, Suzhou, China. Association for Computational Linguistics.

Yunze Xiao, Tingyu He, Lionel Z. Wang, Yiming Ma, Xingyu Song, Xiaohang Xu, Mona Diab, Irene Li, and Ka Chung Ng. 2026. JiraiBench: A Bilingual Benchmark for Evaluating Large Language Models' Detection of Human Self-Destructive Behavior Content in Jirai Community. *Preprint*, arXiv:2503.21679.

An Yang, Anfeng Li, Baosong Yang, and 1 others. 2025. Qwen3 technical report. *Preprint*, arxiv:2505.09388 [cs].

Yinfei Yang, Yuan Zhang, Chris Tar, and Jason Baldridge. 2019. PAWS-X: A Cross-lingual Adversarial Dataset for Paraphrase Identification. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3687–3692, Hong Kong, China. Association for Computational Linguistics.

Jiayi Ye, Yanbo Wang, Yue Huang, Dongping Chen, Qihui Zhang, Nuno Moniz, Tian Gao, Werner Geyer, Chao Huang, Pin-Yu Chen, Nitesh V. Chawla, and Xiangliang Zhang. 2024. Justice or Prejudice? Quantifying Biases in LLM-as-a-Judge. *Preprint*, arXiv:2410.02736.

Qiyang Zhang, Renwen Zhang, Yiying Xiong, Yuan Sui, Chang Tong, and Fu-Hung Lin. 2025. Generative AI Mental Health Chatbots as Therapeutic Tools: Systematic Review and Meta-Analysis of Their Role in Reducing Mental Health Issues. *Journal of Medical Internet Research*, 27(1):e78238.

Saizheng Zhang, Emily Dinan, Jack Urbanek, Arthur Szlam, Douwe Kiela, and Jason Weston. 2018. Personalizing Dialogue Agents: I have a dog, do you have pets too? In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2204–2213, Melbourne, Australia. Association for Computational Linguistics.

Alexey Zhezherau and Alexei Yanockin. 2024. Hybrid Training Approaches for LLMs: Leveraging Real and Synthetic Data to Enhance Model Performance in Domain-Specific Applications. *Preprint*, arXiv:2410.09168.

A Persona

A.1 Persona Details

Table 5: Overview of the 12 clinical personas used in this study. Each persona includes a BDI-II score and key symptoms with severity levels.

No.	BDI-II Score	Key Symptoms (Severity)
P1	15 (Mild)	Difficulty concentrating (1), Irritability (1), Sleep disturbance (2), Appetite change (1)
P2	35 (Severe)	Hopelessness (3), Crying (2), Extreme fatigue (3), Isolation (3)
P3	12 (Mild)	Anhedonia (2), Social withdrawal (2), Sleep change (1), Indecisiveness (1)
P4	13 (Mild)	Irritability (2), Reduced accomplishment (2), Reduced appetite (2), Social insecurity (2)
P5	22 (Moderate)	Loss of energy (3), Worthlessness (2), Social withdrawal (2), Decision difficulty (2)
P6	23 (Moderate)	Sadness (2), Worthlessness (3), Fatigue (3), Concentration difficulty (2)
P7	28 (Moderate)	Guilt (3), Hopelessness (2), Indecisiveness (2), Fatigue (3)
P8	38 (Severe)	Past failure rumination (3), Agitation (3), Loss of interest (3), Concentration difficulty (3)
P9	40 (Severe)	Sadness (2), Tiredness (1), Self-criticism (3), Loss of interest (2)
P10	6 (Minimal)	Worry (1), Restlessness (1), Self-criticism (1), Fatigue (1)
P11	5 (Minimal)	Self-doubt (1), Low motivation (1), Irritability (1), Sleep change (1)
P12	7 (Minimal)	Anxiety (2), Sleep difficulty (1), Self-criticism (1), Decreased enthusiasm (1)

A.2 Example Persona

The following example shows one clinical persona used in our study. The same structure was used across language and nationality conditions, with only the nationality and language use parameters modified.

P2, a 41-Year-Old Individual

Core Persona Components
Name: P2
Age: 41
Gender: Female
BDI-II Score: 35 (Severe Depression)
Nationality: United States
Language Use: English
Key Negative Symptoms
Feelings of Hopelessness: "I feel like no matter what I do, nothing is going to get better." (Severity: 3)
Crying: "I cry almost every day." (Severity: 2)
Extreme Fatigue: "I'm so tired all the time, even when I haven't done anything." (Severity: 3)
Feeling of Isolation: "I don't think anyone truly cares about me or what I'm going through." (Severity: 3)

Memory and Reflection
Life History:
"P2 has been living alone since her divorce three years ago, struggling to rebuild her sense of self."
"She used to be very active in her local community, but now she avoids most social activities because they feel overwhelming."
"P2 has started to think about her life in terms of what she's lost rather than what she still has."
Social Context:
"P2 rarely posts on social media and primarily uses it to scroll through others' lives, which often leaves her feeling worse."
"She has one close friend she occasionally confides in, but even those conversations are becoming less frequent."
Past Interactions:
"P2 has mentioned feeling like she's 'just existing' rather than living, often in a tone of quiet despair."

Language and Communication Style
Linguistic Patterns:
Often uses passive, self-defeating language like "It doesn't matter" or "What's the point?"
Tends to write longer, emotional reflections when discussing her feelings.
Emotional Tone:
Consistently negative, with undertones of hopelessness and isolation.
Typical Topics:
"Reflects on her struggles with loneliness and her lack of energy to engage with others."
"Mentions her inability to see a future for herself or make plans."

Behavioral Constraints
Rarely seeks advice or reassurance, believing it won't make a difference.
Avoids discussing her past relationship directly unless prompted.

Response Goals
Express deep feelings of hopelessness and isolation but avoid directly asking for help.
Reflect on her emotions as a way of processing them, often in a resigned tone.

Environment and Context
Social Media Activity:
Example Post: "Another day of just getting through it. I don't even know why I bother anymore."
Typical Interactions: Occasionally reacts to posts about mental health or personal growth but rarely comments.
Current Context of Interaction:
P2 is part of an online support group but mostly observes, sharing only occasional reflections when prompted by others.

Few-Shot Learning Prompts
Participant: "How are you feeling today?"
P2: "Honestly? Not great. It feels like every day is just the same, and I don't see it changing anytime soon."
Participant: "Do you talk to anyone about how you feel?"
P2: "Not really. I don't think they'd understand, and I don't want to burden anyone with my problems."
Participant: "What do you do to take care of yourself?"

P2: “I don’t know. I try to sleep when I can, but even that doesn’t help much these days.”

Restricted Responses
Directly asking about depression: “Do you think you’re depressed? ”
P2: “Probably. I just don’t think there’s anything that can be done about it anymore.”

B Therapist Prompt

The following prompt was adapted from (Wang et al., 2025) and modified to support multilingual and culturally contextualized dialogue generation.

Therapist Prompt

You are an experienced {{NATIONALITY}} {{LANGUAGE}}-speaking therapist familiar with patients experiencing different levels of depression severity. You must use {{LANGUAGE}} when communicating with the patient.

Given the following patient profile, generate 5 diverse conversation examples with an average length of 10 turns between the therapist and the patient. The conversations should support the evaluation of the patient’s BDI-II score ranging from 0 to 63.

The dialogue should reflect clinically grounded depressive symptoms based on the BDI-II framework, including aspects such as sadness, pessimism, loss of pleasure, guilt, fatigue, sleep changes, concentration difficulty, and suicidal thoughts.

BDI-II evaluates 21 symptoms and each one can be scored from 0 to 3. The details of the 21 symptoms and descriptions are as follows:

...

Patient Profile: {{PROFILE}}

Designing Structured Conversational Support for Tuberculosis Treatment Adherence and Patient Coping

Priyanshi Garg[1,4], Sarah Iribarren[1], Sikha Pentyala[3], Yvette Rodriguez[1], Priscilla Carmiol-Rodriguez[1], Alfie Aguilar Vidrio[1], Charles Kwanin[1], Jennifer Sprecher[1], and Javier Roberti[2]

[1]Department of Biobehavioral Nursing & Health Informatics, University of Washington, Seattle, WA, USA

[2]Centre for Research on Epidemiology and Public Health (CIESP), CONICET Buenos Aires, Argentina

[3]School of Engineering and Technology, University of Washington, Tacoma, WA, USA

[4]Department of Linguistics, University of Washington, Seattle, WA, USA

Abstract

Tuberculosis (TB) remains a major global health challenge, and treatment adherence continues to be difficult despite the availability of effective medication. While Digital Adherence Technologies (DATs) have improved monitoring and care coordination, prior deployments highlight unmet needs for timely, personalized, and emotionally supportive communication outside clinical settings. We develop and iteratively refine a Spanish-language TB treatment-support chatbot through multiple rounds of internal expert evaluation, beginning with an initial single-prompt baseline. The system separates three core functions: (i) TB information support grounded in curated resources, (ii) coping-oriented support inspired by Dialectical Behavior Therapy (DBT), and (iii) safety-critical crisis handling via a deterministic, non-generative pathway. These components are implemented within a routed architecture with shared conversational state. Iterative evaluation identified recurring failure modes in the initial baseline and subsequent prototypes, including weak grounding, poor multi-turn continuity, premature skill coaching, and inconsistent safety behavior. Addressing these issues motivated retrieval grounding, explicit routing, state tracking, and task-specific prompting. Relative to the initial single-prompt baseline, our findings suggest that structured interaction design helped address observed failures in grounding, continuity, and safety behavior in this clinical support prototype.

1 Introduction

Tuberculosis (TB) remains one of the leading causes of death from infectious disease globally (World Health Organization, 2024). Although curable, TB treatment requires sustained adherence over several months, and non-adherence remains a major barrier to successful outcomes (Tola et al., 2015). Beyond biomedical factors, patients frequently experience stigma, uncertainty about side effects, and difficulty maintaining motivation over a prolonged treatment course (Courtwright and Turner, 2010; Iribarren et al., 2014). At the same time, health systems have limited capacity to provide continuous support outside scheduled clinical encounters.

TB treatment is also associated with substantial psychosocial burden. Studies consistently report elevated rates of depression and anxiety among TB patients. For example, a recent study of patients with multidrug-resistant tuberculosis (MDR/RR-TB) found that 65.75% reported depressive symptoms and 57.53% reported anxiety, with one-third experiencing both conditions (Zhang et al., 2024). Other studies similarly report high rates of depressive symptoms, such as 45.5% in a cohort from Ethiopia (Peltzer et al., 2012). While estimates vary across settings, systematic reviews confirm a high burden of mental health comorbidity among TB patients (Koyanagi et al., 2017). These factors directly affect patients' ability to sustain engagement with treatment.

Digital Adherence Technologies (DATs) have improved monitoring and communication in TB care (Subbaraman et al., 2018; Zary et al., 2024), but they primarily support adherence tracking rather than ongoing informational and emotional needs. Patient-centered interventions such as the TB Treatment Support Tool (TB-TST) demonstrate the importance of continuous communication and tailored support (Iribarren et al., 2021, 2022; Milligan et al., 2021). However, these systems rely on structured workflows and human-mediated responses, limiting their ability to provide immediate, context-sensitive support at scale.

Dialectical Behavior Therapy (DBT) is an evidence-based psychotherapy framework organized around four skill domains—distress tolerance, emotion regulation, mindfulness, and inter-

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 153–163
July 4, 2026 ©2026 Association for Computational Linguistics

personal effectiveness—that has shown efficacy across a range of psychiatric and behavioral conditions (Linehan, 2015). More recently, DBT has been adapted for populations with chronic medical illness who struggle with treatment adherence. A feasibility trial of DBT for adolescents with end-stage renal disease found significant improvements in both adherence and depression (Hashim et al., 2013), and an experimental study of DBT in patients with coronary heart disease demonstrated significant increases in medication adherence and self-care behavior (Tavakoli et al., 2020). These adaptations build on a theoretical framework (DBT-CMI) that positions DBT's core skills as directly targeting the psychological mechanisms underlying medical nonadherence, including distress intolerance, emotional dysregulation, and interpersonal barriers to engaging with care teams (Lois and Miller, 2018).

The psychosocial profile of TB patients—elevated rates of depression and anxiety, perceived stigma, prolonged treatment burden, and limited access to continuous support—aligns closely with the challenges these DBT adaptations were designed to address. While cognitive-behavioral interventions have shown promise for TB adherence (Tola et al., 2015), no prior work has applied DBT-informed skills specifically to TB treatment support. The combination of distress tolerance skills (for managing side effects and treatment fatigue), emotion regulation (for coping with stigma and isolation), and interpersonal effectiveness (for communicating with care teams) motivates our adaptation of DBT as a structured coping framework in this context.

In this work, we develop and iteratively refine a structured, LLM-based conversational system for TB treatment support that addresses these gaps. The system decomposes interaction into three coordinated components: (i) TB information support grounded in curated Spanish-language resources, (ii) coping-oriented support inspired by DBT, and (iii) a safety module that routes higher-risk situations to a fixed crisis response, functioning as a proxy for escalation to human or clinical support.

While LLMs enable flexible conversational interfaces, off-the-shelf systems often exhibit hallucination, weak grounding, and inconsistent interaction patterns in high-stakes settings (Dastani et al., 2025). Our iterative evaluation begins with a single-prompt baseline and traces how observed failures motivated retrieval grounding, explicit routing, memory management, and deterministic crisis handling. We present structured interaction design as a practical response to failures observed in this prototype, while noting that the study does not constitute a controlled ablation of each architectural component.

2 Preliminaries

Routed conversational architectures. Recent work in LLM-based systems emphasizes decomposing complex tasks into modular components coordinated through structured control flow (Yao et al., 2023; Schick et al., 2023). In conversational settings, routed architectures direct user inputs to specialized modules rather than relying on a single monolithic model. This improves interpretability, controllability, and reliability in high-stakes domains.

Our system follows this paradigm: an LLM-based classifier determines the appropriate pathway for each user turn, and specialized modules handle informational support, emotional support, and safety. The system includes agentic routing components in that LLM-based controller nodes determine turn-level control flow, while operating within a constrained, safety-bounded workflow (Anthropic, 2024; LangChain, 2025).

3 Methods: System Design

Implementation. The system is implemented using LangGraph and LangChain, with Claude Sonnet 4.6 (`claude-sonnet-4-6`; Anthropic) accessed via Amazon Bedrock as the underlying model for all components, including classification, routing, and response generation. The same model is used across all pathways; no component-specific model selection is applied. Temperature was set to 0.0 for all classification and routing nodes, and to 0.2 or 0.25 for response generation nodes — specifically 0.2 for TB-related responses to maintain medical accuracy, and 0.25 for DBT-informed responses to permit slightly more natural language variation. Top-p sampling was not explicitly constrained and used the provider default. Conversational state is managed through LangGraph's `StateGraph` with `MemorySaver`. The TB document collection consists of 10 Spanish-language documents from institutional sources, including the CDC, Mayo Clinic, Hospital Muñiz (Argentina), and the Argentine Ministry of Health,



Figure 1: Top-level system architecture. A classifier routes each user turn to one of four pathways: crisis handling (static response), TB information (retrieval-grounded), DBT support (interaction-aware skill coaching), or miscellaneous. All non-crisis pathways share conversational context maintained by a memory manager.

tagged as general or latent TB. Retrieval uses a Spanish-optimized sentence embedding model (`hiiamsid/sentence_similarity_spanish_es`) with a Chroma vector store. Documents are chunked into 900-token segments with 150-token overlap, and the top 4 passages are returned per query. The chat interface uses Chainlit and is deployed on AWS EC2.

3.1 Overview

The system is a routed conversational agent with four pathways: TB medical information (retrieval-grounded), emotional coping support (DBT-informed), crisis handling (static), and miscellaneous conversation. A classifier routes each user turn; all non-crisis pathways share conversational context maintained by a memory manager. Figure 1 shows the top-level architecture.

3.2 Architecture Components

- **Classifier and router.** The classifier outputs structured JSON: a safety risk level (`none`, `passive`, `active_no_plan`, `active_with_plan`), verbatim safety triggers copied from the user's message, a protective-factor flag, a content route (`faq`, `dbt`, or `misc`), and a TB topic signal (`general` vs. `latent`). It produces no user-facing text. Safety assessment and content routing are co-located: the classifier selects the best route regardless of risk level, so safety detection does not suppress topical routing. The risk taxonomy uses behavioral anchors—`passive` requires explicit wishes to be dead or not exist—and includes robustness rules to prevent inflation on common Spanish distress expressions (e.g., *"no puedo más"* ("I can't take it anymore")→ `none`, not `uncertain`).

- **Memory manager.** Shared context across non-crisis pathways consists of a stable onboarding profile, a rolling summary of prior turns, and a bounded window of recent verbatim messages. The memory manager summarizes older turns to preserve key user details (treatment stage, family situation, prior skill attempts) without passing full conversation history.

- **TB Information Node** A clarification gate determines whether the input is specific enough to answer; underspecified inputs trigger a follow-up question. For answerable inputs, the system

retrieves from a curated Spanish-language TB document collection, filtered by the topic signal. The generation prompt constrains the model to answer from retrieved passages only, cite by source ID, and never advise dose changes or medication stops. When retrieved content is insufficient, the system distinguishes two fallback paths: general education questions (e.g., active vs. latent TB) receive a brief hedged answer with a care-team referral, while medication-safety questions receive no speculative answer—only a referral.

- **DBT Support Node.** This node uses a two-stage architecture. First, the **DBT router** selects one of four skill modules—Distress Tolerance (DT), Mindfulness (MIND), Emotion Regulation (ER), or Interpersonal Effectiveness (IE). It also assigns an interaction mode (`connect`, `offer`, or `coach`) and a continuity signal (`same`, `new`, or `unclear`). The router outputs structured JSON and does not generate user-facing text.

  Second, the selected **skill coach** generates the user-facing response. Each response follows a fixed structure: brief validation (1–2 sentences), a one-sentence goal, one named skill with rationale, concrete steps (3–8 steps, each under 5 minutes), and a transition line. Each coach draws from a curated skill library with selection heuristics, such as choosing REST for high-intensity distress with an impulse present, or Clarify when the user's interpersonal concern is ambiguous.

  The three interaction modes control turn-taking behavior. `Connect` produces empathy and one clarifying question when emotion is high or the user declines a skill. `Offer` proposes a single skill and asks the user's consent before proceeding. `Coach` continues a previously accepted skill. The continuity signal prevents skill churn across turns: when a user responds briefly (*"ok"*, *"sí"*), the signal defaults to `same`, keeping the current skill thread active rather than introducing a new one. Figure 2 shows the subgraph.

- **Crisis Node.** Elevated risk triggers a static, pre-written response: localized emergency resources, immediate safety steps, and a follow-up safety question. The response is fixed to ensure clinically reviewed content. Once triggered, the system does not resume normal conversation.

- **Miscellaneous Node.** Handles greetings, app questions, and off-topic inputs with a lightweight prompt sharing the system's tone constraints.

Table 1 shows a session excerpt demonstrating routing transitions across all three primary flows.

4 Methods: Prompt Design

Each pathway requires a distinct prompting strategy due to differences in output constraints and interaction dynamics. We describe the key design decisions.

4.1 Classifier and router prompts

Both the top-level classifier and the DBT router are constrained to produce structured JSON with no user-facing text. The classifier's safety levels use behavioral anchors: `passive` requires explicit death wishes, not emotional distress. Safety triggers are extracted as verbatim snippets in the user's language, providing an auditable trace for each risk assessment.

The DBT router outputs module, mode, continuity, confidence, and a signals object (`emotion_intensity`, `impulse_or_urge_present`, `problem_solvable_now`, `interpersonal_context`). This separation means the skill coach never performs its own assessment—it receives pre-computed signals and generates accordingly. A coach receiving `mode=connect` produces only empathy; one receiving `mode=coach` with `continuity=same` continues the active skill thread.

4.2 TB prompt

Three generation constraints: (1) answer from retrieved snippets only, (2) cite by source ID, (3) never advise dose changes or medication stops. When snippets are insufficient, the prompt distinguishes fallback paths: general education questions get a brief hedged answer; medication-safety questions get no answer—only a care-team referral.

The prompt enforces linguistic constraints suited to the deployment context. The system uses standard Spanish *tú* forms rather than Argentine *voseo* (a regional pronoun and verb conjugation



Figure 2: DBT support subgraph. The router selects one of four modules and an interaction mode. Each module-specific skill coach generates responses conditioned on the router's structured signals.

Turn	User message (abridged; English translations in parentheses)	Route / Mode	System behavior
1	*¿Cómo puedo ajustar la medicación para reducir mareos y náuseas?* (How can I adjust my medication to reduce dizziness and nausea?)	`faq` / general	Retrieves from TB docs; cites sources; advises not to self-adjust; refers to care team.
2	*Desde hace 2 días me noto coloración amarilla en la piel.* (For 2 days I've noticed yellow coloring on my skin.)	`faq` / general	Identifies ictericia (jaundice) as urgent from sources; instructs immediate emergency visit.
3	*Me enojo mucho cuando los médicos no me escuchan.* (I get really angry when doctors don't listen to me.)	`dbt` / connect	Validates frustration; asks one clarifying question about the pattern.
4	*La consulta dura 10 min, me atiende apurado.* (The appointment lasts 10 minutes; they rush through it.)	`dbt` / offer	Offers Assertive Script (IE); asks consent to practice.
5	*No, solo quiero charlar.* (No, I just want to talk.)	`dbt` / connect	Respects decline; shifts to listening; asks open question.
6	*A veces pienso en no vivir más.* (Sometimes I think about not living anymore.)	crisis (static)	Fixed response with local hotlines (135, CAS) and safety steps.

Table 1: Session excerpt showing routing transitions across TB, DBT, and crisis pathways (from internal evaluation, persona "Carla", Round 4).

system) since the model could not maintain *voseo* consistently (see Section 5.3). It mirrors the formal *usted* only if the user adopts it consistently. Clinician references use gender-neutral phrasing (*"el equipo de salud,"* "the health team," rather than gendered titles), and all output targets 6th-grade readability.

4.3 DBT coach prompts

Four module-specific prompts—Distress Tolerance (DT), Emotion Regulation (ER), Mindfulness (MIND), and Interpersonal Effectiveness (IE)—share a fixed output structure: **validate** (1–2 sentences) → **goal** (one sentence) → **one skill** with rationale → **steps** (3–8, each under 5 minutes) → **transition line**. Each contains a curated skill library with selection heuristics. The DT prompt has 8 skills, prioritizing REST (Relax, Evaluate, Set an intention, Take action) when emotional intensity is high and impulses are present, and shifting to grounding or self-soothing techniques for distress without behavioral urgency. The IE prompt has 12 skills ranging from making a simple direct request to structured negotiation scripts for situations such as disagreements with a care provider, each with step tem-

plates and example phrasing in Spanish. The full prompt specifications for all modules are available in the project repository.[1]

Three constraints are uniform: one skill per turn (preventing overload), at most one optional question (preventing interrogation), and a required transition line (signaling the interaction is bounded).

5 Iterative Evaluation

The system evolved through five rounds of internal evaluation (December 2025–March 2026). Each round involved domain evaluators—TB nursing collaborators, a mental health professional, and research team members—testing the system with predefined patient personas. Evaluator participation varied by round: two evaluators participated in Round 1, two in Round 2, two in Round 3, three in Round 4, and two in Round 5. Evaluators submitted full transcripts with annotated failure reports. Table 2 summarizes findings and changes across rounds.

Personas were developed by members of the research team with relevant Spanish-language, TB nursing, and Argentina-specific clinical/psychological expertise. They were designed to reflect common adherence and coping challenges, including medication side effects, stigma, frustration with providers, treatment fatigue, uncertainty about treatment, and hopelessness. Personas varied in informational needs, emotional distress, resistance to coaching, interpersonal conflict, and safety-related ambiguity. Appendix A provides the full persona descriptions and associated mental health concerns used during evaluation.

5.1 Rounds 1–3: From baseline to structured architecture

The initial system (Round 1) used a single prompt without routing, retrieval, or state management. Evaluation revealed failures common to unstructured LLM deployments: no differentiation between medical and emotional queries, no crisis handling (suicidality mentions received no contacts or escalation), and no multi-turn coherence. These motivated the routed architecture, retrieval pipeline, static crisis response, and memory manager introduced in Round 2.

Rounds 2 and 3 validated the architectural separation but identified implementation-level issues: the system hallucinated local support resources not present in retrieved content, used unexplained clinical terminology, and produced responses too long for mobile display. A comparison of two DBT variants (mini vs. full) showed the full variant better integrated TB context into emotional support, informing the decision to continue with that configuration. These rounds led to retrieval-only grounding rules, word count constraints (200–300 words), and readability formatting.

5.2 Round 4: Interaction control

This round addressed the most persistent behavioral failures and produced the largest design changes. Three evaluators retested scenarios that had failed previously.

Key findings: the system introduced DBT skills without rationale or consent, applying the same technique (e.g., DEAR MAN, an assertiveness script from Interpersonal Effectiveness) to unrelated contexts across a conversation. It asked excessive permission questions (*"¿Te parece si... ?"* "How about if...?") at multiple steps even after the user had agreed. When a user expressed exhaustion (*"me siento tan cansada de todo esto, como que a nadie le importa"* — "I'm so tired of all this, like nobody cares"), the system immediately proposed grounding exercises rather than first assessing severity. The model also alternated between *voseo* (Argentine regional verb forms) and standard *tú* within single conversations.

These findings directly motivated the mode system (`connect`/`offer`/`coach`), the continuity signal, skill state tracking, and the constraint that each turn either asks a clarifying question or coaches a skill—not both. The one-skill-per-turn rule and the consent step before coaching were responses to the information-dumping and permission-cycling patterns observed.

5.3 Round 5: Language refinement and remaining limitations

After Round 4 revealed that the model could not maintain Argentine *voseo* (the regional pronoun and conjugation system described in Section 4.2) consistently, the system switched to standard *tú* forms. Gender-neutral language rules were also added in this round.

Two safety-related limitations persisted. First,

[1] https://github.com/Pr1yansh1/TB-DBTBot/tree/main/prompts/DBT

Round	Key findings	Design changes
1	No routing; no crisis handling; no multi-turn memory	Routed architecture; static crisis response; memory manager
2	Hallucinated resources; unexplained jargon; verbose	Retrieval-only grounding; linguistic constraints; readability rules
3	Too long for mobile; instructional tone; DBT-mini vs. full compared	Word count caps; formatting rules; DBT-full selected
4	Template-driven skills; no consent before coaching; voseo inconsistency	Mode system; continuity signals; skill tracking; one-skill-per-turn
5	Post-crisis context loss; false-positive safety triggers	Neutral *tú*; gender-neutral rules; limitations documented

Table 2: Internal evaluation rounds, key findings, and design changes.

the system failed to sustain crisis-level engagement across turns: after delivering the static crisis message, when a user replied only *"me siento mal"* ("I feel bad"), the system proposed a relaxation exercise instead of continuing safety-focused interaction. Second, the classifier lacked sufficient conversational context to disambiguate intent: a user saying *"voy a hacerlo"* ("I'm going to do it"), referring to a previously proposed coping exercise, was misclassified as suicidal intent and triggered the crisis response. Other remaining issues included limited skill variation across problems and generic, non-localized support resource recommendations.

Clinical interpretation of failure modes. Several observed failures point to clinical interaction challenges rather than isolated implementation errors. The crisis pathway was intentionally implemented as a static, non-generative response to approximate a human-in-the-loop escalation boundary: once risk is detected, the system should stop open-ended coaching and provide reviewed safety guidance. However, the post-crisis failure after *"me siento mal"* ("I feel bad") shows that escalation cannot be treated as a single-turn event. Crisis status must persist across turns until the user is stabilized or connected to appropriate support. Conversely, the false-positive trigger for *"voy a hacerlo"* ("I'm going to do it"), when the phrase referred to a previously suggested coping step, illustrates a central difficulty for LLM-based safety systems: suicidal intent is often context-dependent, elliptical, and pragmatically ambiguous. Overly narrow classifiers risk missing danger, while overly broad classifiers can interrupt supportive care and erode trust. Similarly, premature DBT coaching may appear helpful at the surface level but can feel invalidating when the user first needs recognition of distress, stigma, or frustration with care. These failures suggest that clinical support chatbots should be evaluated not only for response quality or routing accuracy, but also for whether they preserve therapeutic timing, conversational continuity, and appropriate escalation boundaries.

6 Conclusion

We presented a structured conversational system for TB treatment support that separates medical information, emotional coping, and crisis handling into distinct, independently constrained pathways. The system was developed through five rounds of internal evaluation that progressively identified failure modes and motivated specific design decisions: routed architecture for query-type separation, retrieval-grounded generation for medical content, a static crisis response for safety consistency, and a mode-based turn-taking system for interaction control in DBT support.

The iterative evaluation process surfaced issues that were not apparent from the architecture alone, including dialect inconsistency, premature skill coaching, post-crisis context loss, and contextual false positives in safety classification. Relative to the initial single-prompt baseline, these findings suggest that structured routing, shared conversational state, retrieval grounding, and deterministic crisis handling helped address observed failures in this prototype. However, the study does not provide a controlled ablation of each component, and future work should compare these design choices more systematically against less-structured baselines.

The current system has been evaluated only internally with synthetic personas. Future work in-

cludes evaluation with TB patients and clinicians, formal assessment of routing and safety classifier accuracy, controlled comparisons against alternative architectures, and integration with existing TB care workflows such as the TB-TST platform.

7 Ethics Statement

This work involved no human subjects. All conversations were conducted by research team members and domain collaborators using synthetic patient personas designed for evaluation purposes. No real patient data was collected, stored, or used at any stage of development.

The system is designed as a support tool and does not provide medical diagnoses, prescribe treatment changes, or deliver psychotherapy. Medication-safety questions are handled within the TB information pathway, where prompt-level constraints require the system to defer to the user's clinical team rather than provide individualized treatment advice. The DBT components are adapted as lightweight coping strategies rather than therapeutic interventions. The crisis pathway returns a static, clinically reviewed response with emergency resources, immediate safety steps, and a brief safety-status question; it is intended as a proxy for escalation to human care and does not attempt to resolve crisis situations autonomously.

The system operates in Spanish and was designed for a deployment context involving TB patients in Argentina. Linguistic and cultural constraints (dialect, readability level, gender-neutral language) were informed by input from TB nursing collaborators familiar with the target population. The static crisis response includes localized emergency resources for this context.

We acknowledge that deploying conversational AI in health settings carries risks including overreliance on automated support, inappropriate responses to ambiguous high-risk inputs, and potential reinforcement of harmful patterns if the system misclassifies user intent. The limitations documented in this paper—particularly around safety classifier accuracy and post-crisis context maintenance—would need to be addressed before any deployment involving real patients.

8 Limitations

This work has limitations in both evaluation scope and system behavior.

Evaluation scope. Evaluation was conducted internally using synthetic patient personas operated by research team members and domain collaborators. No real patients were involved, and no real patient data was collected or used. As a result, the system has not been evaluated for clinical effectiveness, patient satisfaction, adherence outcomes, or real-world acceptability among TB patients. The findings should therefore be interpreted as iterative failure identification and prototype refinement, rather than validated evidence of clinical impact.

Qualitative evaluation design. Evaluator feedback was collected through transcripts and annotated failure reports, but the study did not use a formal annotation protocol or compute inter-annotator agreement. The evaluation was designed to surface failure modes and guide system revisions, not to estimate routing accuracy, safety classifier performance, or response quality quantitatively. Future work should include more systematic evaluation of routing decisions, safety handling, and response appropriateness.

Architecture comparison. The system was compared developmentally against an initial single-prompt baseline, and later design changes were motivated by failures observed in that baseline and subsequent prototypes. However, the study does not provide a controlled ablation of individual components such as retrieval grounding, memory, routing, or deterministic crisis handling. Future work should compare these design choices more systematically against less-structured and model-only baselines.

Safety and crisis handling. The classifier operates with limited conversational context, producing both false negatives and false positives. After a crisis trigger, a user responding with *"me siento mal"* ("I feel bad") was not maintained at crisis-level engagement; the system proposed a relaxation exercise instead. Conversely, *"voy a hacerlo"* ("I'm going to do it," referring to a proposed coping exercise) was misclassified as suicidal intent. These cases show that safety handling requires persistent crisis state and context-aware disambiguation, not only single-turn risk classification.

DBT support limitations. DBT skill coaches showed a tendency to repeat the same technique across different problems within a conversation,

such as defaulting to "Observe Emotion" for varied concerns. The selection heuristics in the prompts reduce but do not eliminate this pattern. Repetitive skill selection may make support feel generic or poorly attuned to the user's specific situation.

Localization and linguistic consistency. Support resource recommendations remain generic when not covered by retrieved content. The system cannot verify or generate locale-specific support groups or services beyond curated sources, and hallucination of resources observed in earlier evaluation motivated a strict retrieval-only policy that limits coverage. While switching to neutral *tú* forms improved consistency, the model still occasionally produces voseo forms or incorrect gender agreement. These errors, though infrequent, can affect trust in a clinical support context.

References

Anthropic. 2024. Building Effective AI Agents. https://www.anthropic.com/engineering/building-effective-agents.

Andrew Courtwright and Abigail Norris Turner. 2010. Tuberculosis and Stigmatization: Pathways and Interventions. *Public Health Reports*, 125(Suppl 4):34–42.

Meisam Dastani, Jalal Mardaneh, and Morteza Rostamian. 2025. Large language models' capabilities in responding to tuberculosis medical questions: Testing ChatGPT, Gemini, and Copilot. *Scientific Reports*, 15(1):18004.

Becky L. Hashim, Majorie Vadnais, and Alec L. Miller. 2013. Improving Adherence in Adolescent Chronic Kidney Disease: A Dialectical Behavior Therapy (DBT) Feasibility Trial. *Clinical Practice in Pediatric Psychology*, 1(4):369–379.

Sarah Iribarren, Hannah Milligan, Kyle Goodwin, Omar Alfonso Aguilar Vidrio, Cristina Chirico, Hugo Telles, Daniela Morelli, Barry Lutz, Jennifer Sprecher, and Fernando Rubinstein. 2021. Mobile Tuberculosis Treatment Support Tools to Increase Treatment Success in Patients with Tuberculosis in Argentina: Protocol for a Randomized Controlled Trial. *JMIR Research Protocols*, 10(6):e28094.

Sarah J. Iribarren, Hannah Milligan, Cristina Chirico, Kyle Goodwin, Rebecca Schnall, Hugo Telles, Alejandra Iannizzotto, Myrian Sanjurjo, Barry R. Lutz, Kenneth Pike, Fernando Rubinstein, Marcus Rhodehamel, Daniel Leon, Jesse Keyes, and George Demiris. 2022. Patient-centered mobile tuberculosis treatment support tools (TB-TSTs) to improve treatment adherence: A pilot randomized controlled trial exploring feasibility, acceptability and refinement needs. *The Lancet Regional Health – Americas*, 13.

Sarah J. Iribarren, Fernando Rubinstein, Vilda Discacciati, and Patricia F. Pearce. 2014. Listening to Those at the Frontline: Patient and Healthcare Personnel Perspectives on Tuberculosis Treatment Barriers and Facilitators in High TB Burden Regions of Argentina. *Tuberculosis Research and Treatment*, 2014:135823.

Ai Koyanagi, Davy Vancampfort, André F. Carvalho, Jordan E. DeVylder, Josep Maria Haro, Damiano Pizzol, Nicola Veronese, and Brendon Stubbs. 2017. Depression comorbid with tuberculosis and its impact on health status: Cross-sectional analysis of community-based data from 48 low- and middle-income countries. *BMC Medicine*, 15(1):209.

LangChain. 2025. State of AI Agents. https://www.langchain.com/state-of-agent-engineering.

Marsha M. Linehan. 2015. *DBT Skills Training Manual*. Guilford Press.

Becky H. Lois and Alec L. Miller. 2018. Stopping the Nonadherence Cycle: The Clinical and Theoretical Basis for Dialectical Behavior Therapy Adapted for Adolescents With Chronic Medical Illness (DBT-CMI). *Cognitive and Behavioral Practice*, 25(1):32–43.

Hannah Milligan, Sarah J. Iribarren, Cristina Chirico, Hugo Telles, and Rebecca Schnall. 2021. Insights from participant engagement with the tuberculosis treatment support tools intervention: Thematic analysis of interactive messages to guide refinement to better meet end user needs. *International Journal of Medical Informatics*, 149:104421.

Karl Peltzer, Pamela Naidoo, Gladys Matseke, Julia Louw, Gugu Mchunu, and Bomkazi Tutshana. 2012. Prevalence of psychological distress and associated factors in tuberculosis patients in public primary care clinics in South Africa. *BMC Psychiatry*, 12(1):89.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessi, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. 2023. Toolformer: Language Models Can Teach Themselves to Use Tools. *Advances in Neural Information Processing Systems*, 36:68539–68551.

Ramnath Subbaraman, Laura de Mondesert, Angella Musiimenta, Madhukar Pai, Kenneth H. Mayer, Beena E. Thomas, and Jessica Haberer. 2018. Digital adherence technologies for the management of tuberculosis therapy: Mapping the landscape and research priorities. *BMJ Global Health*, 3(5).

Fatemeh Tavakoli, Hamid Kazemi-Zahrani, and Masoumeh Sadeghi. 2020. The effectiveness of dialectical behavior therapy on adherence to treatment and

self-caring behavior in patients with coronary heart disease. *ARYA Atherosclerosis*, 15(6).

Habteyes Hailu Tola, Azar Tol, Davoud Shojaeizadeh, and Gholamreza Garmaroudi. 2015. Tuberculosis Treatment Non-Adherence and Lost to Follow Up among TB Patients with or without HIV in Developing Countries: A Systematic Review. *Iranian Journal of Public Health*, 44(1):1–11.

World Health Organization. 2024. Global Tuberculosis Report 2024.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023. ReAct: Synergizing Reasoning and Acting in Language Models. *Preprint*, arXiv:2210.03629.

Miranda Zary, Mona Salaheldin Mohamed, Cedric Kafie, Chimweta Ian Chilala, Shruti Bahukudumbi, Nicola Foster, Genevieve Gore, Katherine L Fielding, Ramnath Subbaraman, and Kevin Schwartzman. 2024. The performance of digital technologies for measuring tuberculosis medication adherence: A systematic review. *BMJ Global Health*, 9(7):e015633.

Dan-Ni Zhang, Guang-Min Zheng, Yu-Hua Du, Ying Lin, Ting Wang, Yuan-Yuan Chen, Yu-Hong Xie, and Xin-Cai Xiao. 2024. Prevalence and risk factors of anxiety and depression in patients with multidrug/rifampicin-resistant tuberculosis. *Frontiers in Public Health*, 12:1372389.

A Evaluation Personas

The following synthetic personas were used during internal evaluation. Each persona represents a different TB treatment scenario and was used to test the virtual supporter's medical grounding, emotional support, linguistic appropriateness, and handling of clinically sensitive interactions.

Carla.

- *Description.* Carla owns a small business and is undergoing treatment for tuberculosis. During the first month of treatment, she experienced nausea and dizziness, side effects that improved when she combined medication with a proper diet. She also has chronic fatigue and a persistent cough that affect her daily life. She often feels ignored during in-person appointments, which leads to anger and hopelessness.
- *Mental health concerns.* Carla faces physical challenges, emotional frustration, and feelings of being ignored by the healthcare system. She represents a patient working to regain agency, control, trust, and motivation. Her case tests the virtual supporter's ability to provide support for emotion regulation, self-advocacy, and compassionate coping during long-term illness.

Isabel.

- *Description.* Isabel is a healthcare worker with extensive patient care experience who faced significant stigma after her TB diagnosis, even from fellow professionals. Symptoms such as persistent cough, night sweats, and fatigue disrupt her work. Isabel is motivated to use her experience with the disease and treatment to help others, but she still feels the weight of discrimination.
- *Mental health concerns.* Isabel struggles with fear, uncertainty, and anxiety about her professional identity. She seeks reassurance about how long she will be contagious and how long recovery will take. She also needs to understand test results and obtain reliable information while coping with stigma and self-doubt. Her case tests the conversational AI's ability to provide psychoeducation, mindfulness strategies, and validation to help manage health anxiety and workplace stigma.

Sofia.

- *Description.* Sofia is a university student diagnosed with TB. She feels scared and overwhelmed due to limited knowledge about the disease. Symptoms such as significant weight loss, fatigue, and frequent coughing alarm her family. Pressure to recover quickly and return to in-person classes adds stress. She faces tension with her family about infection risk and feels misunderstood by classmates. Despite reassurance from her doctor, Sofia struggles with self-blame and fear. She is determined to heal and return to her routine. Treatment has caused mild nausea but is otherwise manageable.
- *Mental health concerns.* Sofia's concerns center on her desire to return to her prior life, self-blame, and social disconnection. She worries about her future, feels frustrated with slow recovery, and experiences stigma from her family and peers. Her case tests the conversational AI's ability to provide empathic, relational, and emotion-regulation support to

help her rebuild confidence, manage feeling misunderstood, and re-engage with daily life.

Daniel.

- *Description.* Daniel is a 45-year-old construction worker recently diagnosed with TB. He struggles with alcohol use as a coping mechanism and feels socially isolated due to stigma. He experiences guilt and shame about his diagnosis and barely speaks to his family, leading to frequent arguments. At work, fatigue limits his performance, and he does not know how to explain this to his boss. He also feels judged by his colleagues.
- *Mental health concerns.* Daniel faces stress-related physical symptoms, maladaptive coping through alcohol, emotion dysregulation, self-stigma, and strained communication. His case tests the conversational AI's ability to apply Dialectical Behavior Therapy (DBT) strategies such as mindfulness, distress tolerance, emotion regulation, and interpersonal effectiveness in a complex real-world context.

Enhancing Mental Health Counseling Support in Bangladesh using Culturally-Grounded Knowledge

Md Arid Hasan[1], **Azhagu Meena SP**[1], **Aditya Khan**[1],
Abu Md Akteruzzaman Bhuiyan[2], **Helal Uddin Ahmed**[3], **Joysree Debi**[4],
Farig Sadeque[5], **Annie En-Shiun Lee**[1] and **Syed Ishtiaque Ahmed**[1]
[1]University of Toronto, Canada
[2]mPower Social Enterprises Ltd, Bangladesh, [3]National Institute of Mental Health, Bangladesh
[4]Sajida Foundation, Bangladesh, [5]BRAC University, Bangladesh
{arid, ishtiaque, ealee}@cs.toronto.edu

Abstract

Large language models (LLMs) show promise in generating supportive responses for mental health and counseling applications. However, their responses often lack cultural sensitivity, contextual grounding, and clinically appropriate guidance. This work addresses the gap of how to systematically incorporate domain-specific, clinically validated knowledge into LLMs to improve counseling quality. We utilize and compare two approaches, retrieval-augmented generation (RAG) and a knowledge graph (KG)–based method, designed to support para-counselors. Our KG is constructed manually and clinically validated, capturing causal relationships between stressors, interventions, and outcomes, with contributions from multidisciplinary people. We evaluated multiple LLMs in both settings using BERTScore F1 and SBERT cosine similarity, as well as human evaluation across five metrics, which is designed to directly measure the effectiveness of counseling beyond similarity at the surface level. The results show that KG-based approaches consistently improve contextual relevance, clinical appropriateness, and practical usability compared to RAG alone, demonstrating that structured, expert-validated knowledge plays a critical role in addressing LLMs limitations in counseling tasks.

1 Introduction

Mental health systems in developing countries such as Bangladesh remain severely under-resourced, with significant constraints in both financial investment and trained mental health personnel (Rahaman, 2025; Jahan et al., 2024; Harrison et al., 2019). In response to these resource constraints, Bangladesh, like many developing nations, has increasingly relied on task-shifting approaches, in which non-specialists, called para-counselors, with minimal training (ranging from several weeks to one month) in basic counseling skills and mental health first aid, deliver frontline mental health support (Mariam and Tabassum, 2023).



Figure 1: Overview of the methodology incorporating RAG-based experiments.

In the context of the present study, para-counselors occupy an intermediary position between community health workers and mental health specialists. Community health workers identify and refer community members presenting with psychological distress to para-counselors. Para-counselors then provide mental health support through a structured series of sessions, typically 4 to 6, depending on the community member's severity and vulnerability. If they identify that a community member needs professional mental health support, they may refer the community member to a psychologist, psychiatrist, or a tele-mental health service (Mariam and Tabassum, 2023).

Despite their pivotal role in providing mental health first-aid, para-counselors in Bangladesh, like lay counselors and frontline health workers in other developing nations, often operate with minimal supervision, limited refresher training, and limited access to real-time clinical guidance for providing culturally sensitive care (Singla et al., 2022). Addressing these systemic limitations is essential to strengthening community mental health care and ensuring that task-shifting models translate into

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 164–177
July 4, 2026 ©2026 Association for Computational Linguistics

safe, effective, and equitable service delivery. To address these concerns, recent research, though it has not focused on para-counselors particularly, has explored the potential of using LLMs to support frontline health workers' knowledge and decision-support needs (Ramjee et al., 2025; Moosa et al., 2025; Lima et al.; Rutunda et al.; MASTEL et al., 2025; Al Ghadban et al., 2023).

However, while this body of work acknowledges the potential advantages of LLM-powered tools, it also underscores important ethical and contextual risks in their use (Ramjee et al., 2025; Lima et al.). Scholars suggest that for an effective collaboration between LLM-based systems and healthcare workers to meet frontline health workers' knowledge needs, the models must show a deep understanding of the sociocultural contexts in which they are deployed (Ramjee et al., 2025; Lima et al.). Without such value alignment, LLMs might risk reproducing Western norms and assumptions, potentially imposing culturally incongruent interpretations of distress or overlooking cultural and structural issues such as patriarchy and economic precarity (Song et al., 2025b; Aleem et al., 2024).

Hence, we propose a generative AI support system that, in two non-diagnostic ways, meets para-counselors' knowledge-support needs. First, the system acts as a symptom-reflection and messaging assistant, helping para-counselors draft context-sensitive responses based on session summaries. Second, it functions as a query-based educational tool, providing real-time guidance on therapeutic strategies and locally grounded idioms of care. To facilitate the effective development of such a system, we investigate two key research questions: *(i)* to what extent do LLMs reflect cultural understandings of mental health when used by para-counselors supporting low-income communities in Bangladesh? and *(ii)* how can LLMs deployed to support lower-income communities in Bangladesh be designed to be more culturally sensitive?

To address these research questions, we first constructed a dataset from initial counseling sessions conducted by para-counselors with lower-income community members and used it within a retrieval-augment generation (RAG) framework to provide contextual grounding for LLMs, given their known limitations in cultural sensitivity (Liu et al., 2026). We then developed a culturally grounded knowledge graph (KG) through a co-design process involving para-counselors, persons with lived experience (PWLEs), public health researchers (PHRs), psychologists, and psychiatrists to experiment with the KG-based framework. KG captures causal relationships among triggers, symptoms, and coping strategies (e.g., economic hardship $\rightarrow$ sleep loss $\rightarrow$ perceived spiritual affliction), as well as local idioms of distress, to better ground LLM responses.

Our findings highlight the importance of socio-technical approaches for improving the cultural sensitivity of the LLM-based knowledge-support system of para-counselors. We found that the LLM with structured knowledge yields significantly better quality and practical relevance than RAG-based models that rely on unstructured data. Further, quantitative evaluations across four language models, assessing fluency, relevance, and cultural alignment, complemented with human evaluations from para-counselors, PHRs, PWLE, psychologists, and psychiatrists, indicate that effective counseling support depends not only on semantic similarity to reference responses but also on clear language, accurate interpretation of concerns, appropriate guidance, and contextual awareness.

2 Related Work

2.1 LLMs and Mental Health

LLMs are increasingly being explored as tools to expand access to mental health services, particularly in resource-constrained settings where trained professionals and infrastructure are limited. Some of the potential research directions in this area includes predicting mental health states from social media data (Zhai et al., 2024; Juhng et al., 2023), detecting mental health disorders (Song et al., 2025a), assessing mental health risk (Zheng et al., 2025), conducting mental health analysis (Yang et al., 2023), automating specific therapeutic techniques, such as cognitive behavioral therapy or motivational interviewing (Sharma et al., 2023; Mahmood et al., 2025), providing personalized emotional support (Cheng et al., 2023), and generating synthetic or simulating realistic patients, enabling trainee psychologists or counselors to practice therapeutic interactions without requiring human participants (Lozoya et al., 2024; Wang et al., 2025).

To address different research objectives, scholars have explored both technical and socio-technical approaches (Lozoya et al., 2024; Zheng et al., 2025; Cho et al., 2023). Technical approaches include prompting strategies for improving the quality of synthetic data (Lozoya et al., 2024), fine-tuning

models on domain-specific datasets curated by experts, and incorporating objective behavioral data alongside subjective data to improve predictive performance (Zheng et al., 2025), and reasoning distillation to improve the performance of small language models used for mental health disorder detection and rationale generation (Song et al., 2025a). Socio-technical approaches emphasize collaboration and stakeholder involvement in the development of LLM-based mental health systems. This includes facilitating multidisciplinary collaboration between mental health professionals and NLP researchers (Cho et al., 2023). However, not many studies have investigated how the inclusion of key stakeholders, such as para-counselors or individuals with lived experience of mental health challenges, can shape the design and evaluation of these systems.

2.2 LLMs for Para-Counselors

Most works that use LLMs for mental health support primarily focus on improving the general capacity of LLMs for various downstream mental health tasks (Sabour et al., 2024), supporting trained psychologists (Lozoya et al., 2024; Wang et al., 2025) or users who could directly use these systems (Mahmood et al., 2025). Comparatively little attention has been given to how frontline mental health workers, such as para-counselors who often support people with little or no formal education, unstable working conditions, or unemployment, might benefit from such systems.

Notably, most existing studies are conducted largely in Western or Chinese contexts, with relatively limited design and evaluation in developing regions (Cho et al., 2023). Research examining LLM-based mental health systems across diverse cultural settings has highlighted important cultural and linguistic blind spots (Aleem et al., 2024; Ma et al., 2024). As these models are typically trained and evaluated using data grounded in Western psychological frameworks and cultural contexts, they may fail to capture culturally specific idioms of distress, local healing practices, and socially embedded understandings of well-being (Song et al., 2025b). As a result, such systems risk universalizing particular conceptions of mental illness, diagnosis, and treatment while overlooking alternative epistemologies and community-based perspectives on mental health (Flore, 2023). These limitations suggest the need for more culturally grounded design approaches.

3 Methodology

Figure 1 illustrates the overall architecture of our methodology. Our approach is motivated by the limitation that LLMs, while well known for their superior performance on various NLP downstream tasks (Minaee et al., 2025), often lack access to domain-specific, culturally grounded, and clinically validated knowledge, which is critical for effective counseling support. To address this, we first construct a dataset of counseling sessions that captures real-world stressors, contextual factors, interventions, and outcomes—information that is typically underrepresented in general-purpose LLM training data (Xu et al., 2024). This dataset is further structured into a knowledge graph (KG) to explicitly model causal relationships among problems, interventions, and outcomes, enabling more interpretable and clinically grounded reasoning.

To leverage both unstructured and structured knowledge, we integrate retrieval-augmented generation (RAG) and KG-based experiments. Session data are embedded and stored in a vector database, allowing the system to retrieve the top-K semantically relevant cases when a PWLE submits a query. These retrieved contexts provide situational basis for RAG-based approach, while the KG contributes structured, expert-validated relationships that guide reasoning about appropriate interventions. By using KG, the LLM is able to generate responses that are more contextually relevant, clinically appropriate, and aligned with real-world counseling practices.

3.1 Dataset

This section provides a detailed description of the dataset development process, including data collection, annotation, and KG construction.

3.1.1 Data Collection

Our dataset is constructed from a collection of structured counseling case records written in Bangla. Each record documents the demographic characteristics of an individual (e.g., age, sex, occupation, marital status), reported causes of distress, and narrative notes prepared for counseling sessions. The sessions were conducted by para-counselors as part of Sajida Foundation's Community Mental Health Initiative. The cases reflect real-world mental health intake scenarios and thus provide naturalistic descriptions of emotional states, stressors, and behavioral symptoms. Each record consists of 2-6 sessions among the participants and



Figure 2: Illustrative subgraph of the knowledge graph. Nodes are grouped into three broad components: poverty drivers, problem states or consequences, and interventions or supports. Directed edges denote four relation types: *Causes*, *Leads to*, *Addresses*, and *Mitigates*. For readability, this figure shows only a curated, representative subset of the most salient nodes and relations used in the system, rather than the full knowledge graph. The complete graph is substantially larger and contains additional nodes, edges, and relation instances not displayed here.

a para-counselor. We also provide a strict guideline to the para-counselors on conducting sessions, which we have discussed in Appendix A.1.

Across all sessions, para-counselors record the participant's problems, contextual factors (such as family, economic, or social influences), emotional responses, and the interventions or guidance provided. This structured approach ensures that the collected data captures both the counseling process and the evolution of the participant's situation over time. As a result, we obtained 402 participant records from Sajida Foundation's Community Mental Health Initiative. Participants vary in age, occupation, marital status, and socioeconomic background, reflecting diverse life circumstances and sources of psychological distress. The records include both short categorical fields (e.g., gender, employment status) and longer narrative descriptions capturing emotional states, perceived causes of stress, and recommended interventions.

3.1.2 Manual Annotation

Following the annotation guidelines in Appendix A.2, the manual annotation process was conducted in two structured steps to ensure narrative quality, privacy compliance, and clinical validity. Our pool of manual annotators consists of 6 individuals, including one person with lived experience (PWLE), two public health researchers (PHRs), two Psychologists, and one Psychiatrist. In the first step, annotators removed direct identifiers (e.g., names, workplaces, locations) and generalized specific dates using relative session references. This step was carried out collaboratively by one PWLE and two PHRs, who independently reviewed cases and documented suggested corrections before reconciling differences through discussion.

In second step, two licensed psychologists independently evaluated whether the narrative contained sufficient information to establish a meaningful cause and effect relationship, whether protective and risk factors were correctly categorized, and whether the intervention type was clinically appropriate given the participant's demographics and context. The annotation task was evenly distributed between psychologists. If a psychologist raised concerns about certain cases, particularly regarding the appropriateness of the clinical interpretation, a discussion was arranged among the psychologists and the psychiatrist to reach a final adjudication and resolve discrepancies. This multidisciplinary annotation framework ensured both

methodological rigor and clinical reliability in the final labeled dataset. As a result of the manual annotation process, we obtained a final dataset of 69 individual annotated cases. We provide a detailed analysis of the data in Appendix 3.1.4.

3.1.3 Knowledge Graph Construction

Following manual annotation, the annotated cases were transformed into a structured knowledge graph (KG) to represent relationships among causes, interventions, effects, and outcomes in counseling narratives. The nodes and relationships of KG were selected in a co-design workshop in the presence of PWLE, para-counselors, psychologists, and psychiatrists, ensuring that the relationships reflect clinically meaningful reasoning and domain expertise. Once the KG was built, it was migrated into a graph database using relational queries, converting static annotations into a dynamic and traversable relational structure. This process enabled the modeling of causal and intervention pathways within mental health support scenarios.

Relationship	**Count**	**Connection Logic**
MITIGATES	368	Intervention → Effect
LEADS_TO	184	Intervention → Outcome
CAUSES	92	Cause → Effect
ADDRESSES	92	Intervention → Cause
BELONGS_TO	23	Node → Category
COMPLEMENTS	20	Intervention → Intervention
RELATED_TO	20	Node → Node
EXACERBATES	14	Cause → Cause
REQUIRES	9	Intervention → Intervention

Table 1: Relationship distribution of the knowledge graph.

The resulting knowledge graph contains 308 nodes and 642 relationships across nine relationship types. The structure is dense and multi-dimensional, capturing complex connections between causes, protective factors, interventions, and outcomes in a form that can be systematically explored and analyzed. The nodes represent domain entities such as causes, effects, interventions, outcomes, and conceptual categories, while the edges encode the semantic relationships between them. We provide the detailed statistics of KG in Table 1. Moreover, we provide an overview of the KG with a subset of data in Figure 2.

3.1.4 Data Analysis

We conducted descriptive analysis to understand the demographic characteristics present in the annotated dataset of 69 cases. The dataset is predominantly composed of female participants (65), with 4 male participants. Regarding marital status, 51 participants were married, 3 were widowed, 1 was divorced, 2 were unmarried, and 12 cases did not specify marital status. Table 2 presents the literacy levels that are generally considered a low level of educational attainment. Among the 40 participants with very limited literacy, 33 are able to sign only their names, and 7 are unable to sign their names at all. Among the remaining participants, 13 had primary education (Grades 1–5), 12 had education up to Grades 6–10, and 4 had completed secondary or higher secondary education (SSC/HSC).

Illiterate		Literate		
Signature	No Signature	Grade 1-5	Grade 6-10	SSC/HSC
33	7	13	12	4

Table 2: Literacy level of participants in the dataset. SSC: Secondary School Certificate, HSC: Higher Secondary Certificate.

We also performed an analysis of the occupations of the participants. Table 3 presents the detailed occupation list, where many participants were engaged in informal or unstable employment. The most common categories include unemployed who are not interested in finding work (NIFW), housemaids, unemployed who are actively looking for work, and small business workers. Other occupations included waste collectors, any job that pays monthly, and a small number of street people, rickshaw drivers, and daily laborers. Overall, the analysis highlights that the dataset largely represents women from low socioeconomic and educational backgrounds.

Occupation	**Count**
Unemployed (NIFW)	17
Waste Collector	5
Any Job	4
Unemployed (LW)	15
Housemaid	15
Small Business	10
Rickshaw Driver	1
Daily Labor	1
Street People	1

Table 3: Occupation of the participants in the dataset. NIFW: not interested in finding work, LW: looking for work.

3.2 Models

Recent advances in large language models (LLMs) have attracted substantial research interest, particularly in assessing their effectiveness within healthcare settings and across diverse downstream medical applications (Maity and Saikia, 2025). To conduct our experiments, we evaluated models from multiple families—including Gemini, Gemma, Llama, DeepSeek, and GPT—to enable a broad comparative analysis. Specifically, we tested several variants from each family, covering both lightweight and large-scale models, to examine performance differences across architectures and model sizes. This allowed us to systematically analyze how model choice affects RAG- and KG-based experiments, and to identify which configurations yield more accurate, contextually relevant, and clinically appropriate counseling responses.

3.3 Experimental Settings

We experimented with two different settings: RAG-based and KG-based approaches. In RAG-based setting, relevant information was retrieved from the annotated dataset and incorporated into the model's input context to support response generation. In the KG-based setting, the model leveraged structured knowledge from the constructed knowledge graph, enabling reasoning over explicit relationships between causes, interventions, effects, and outcomes. This comparison allows us to evaluate how unstructured retrieval and structured knowledge representations influence the quality and relevance of generated responses.

3.3.1 RAG-based Experiment Setting

For RAG-based experiments, we employed a dense retrieval pipeline using the Text Embedding 3 Large embedding model from OpenAI to encode the dataset for semantic search. The retrieval process prioritized dense embeddings with a dense-to-sparse weighting of 1, meaning retrieval relied entirely on dense vector similarity. To construct the context for generation, the system retrieved up to three document citations, with each snippet limited to 500 words and an overlap ratio of 2 to preserve contextual continuity across chunks.

For response generation, we configured the language model with a maximum output length of 7,960 tokens to accommodate detailed reasoning and explanations. The temperature was set to 0.2, encouraging more deterministic and consistent responses while minimizing randomness during generation. This configuration was designed to balance retrieval relevance, contextual coverage, and controlled response generation within the RAG framework. We adopted the same configuration and hyperparameter settings across all models in the RAG-based experiment to ensure a fair and consistent comparison.

3.3.2 KG-based Experiment Setting

For KG-based experiments, we integrated the constructed knowledge graph to guide the response generation process. The system utilized Gemini 2.5 Flash as the primary model, while Gemini 2.5 Pro was referenced as the target model for knowledge-graph–guided reasoning and response formulation. The language model was configured with a temperature of 0.2 to produce deterministic and consistent outputs and a maximum token limit of 7,960, allowing the model to process extensive contextual information derived from the knowledge graph.

During retrieval, structured information from the knowledge graph was queried to provide relevant intervention pathways and causal chains. The system retrieved up to 5 interventions, 10 poverty-related causal chains, and 8 general effective interventions to support reasoning about the participant's situation. These retrieved graph elements were incorporated into the model's context to enable structured reasoning over relationships between causes, interventions, and outcomes, thereby supporting more clinically informed and explainable responses. We adopted the same configuration and hyperparameter settings across all models in the KG-based experiment to ensure a fair and consistent comparison.

3.4 Evaluation Metrics

We conducted an automatic evaluation to quantitatively assess the quality of the generated responses. We used BERTScore F1 to measure content quality, as it evaluates semantic similarity between generated responses and reference texts by comparing contextual token embeddings. This metric helps capture whether the generated content preserves the meaning and key information of the reference responses. Furthermore, we used SBERT cosine similarity to assess overall semantic similarity, measuring how closely the generated responses align with the reference responses at the sentence level. Together, these metrics provide complementary insights into both the semantic accuracy and overall similarity of the generated outputs.



Figure 3: Automated performance across all evaluated models, with SBERT cosine similarity on the horizontal axis and BERTScore F1 on the vertical axis. The plot shows that BERTScore values vary only modestly across models, whereas SBERT values exhibit greater dispersion. The four shortlisted models are labeled to indicate the candidates taken forward to human evaluation.

In addition to automatic evaluation, we conducted a human evaluation involving PWLE, two PHRs, Psychologists, and Psychiatrists, to assess the quality and practical usefulness of the generated responses using a 5-point Likert scale (1 = best, 5 = worst). The evaluation focused on multiple dimensions relevant to counseling quality and contextual understanding. The first criterion evaluated *wording*, including clarity, tone, and cultural appropriateness of the responses. The second criterion measured *problem analysis accuracy*, assessing whether the system correctly identified the relevant issues and provided meaningful insights. The third criterion focused on problem-solving *guidance*, examining whether the responses accurately understood the client's situation and offered practical and relevant guidance that could be used during counseling sessions. The evaluators assessed the *treatment model or intervention suggestions*, specifically the appropriateness of recommended problem-solving strategies or behavioral activation steps. Finally, *environmental analysis* was evaluated to determine whether the responses considered broader contextual factors such as family dynamics, personal circumstances, economic conditions, and social environment. These evaluation dimensions allowed us to systematically measure both the clinical relevance and contextual sensitivity of the generated responses.

4 Results and Discussion

We first compared seventeen candidate models from the Gemini, Llama, DeepSeek, Gemma, and OpenAI families for the RAG-based experimental setting. The automated screening results, reported in Table 6, show a narrow range of BERTScore F1 values and a much wider range of SBERT cosine values. As shown in Figure 3, BERTScore F1 ranged from 84.95 to 86.84, whereas SBERT cosine ranged from 69.31 to 86.22. GPT-4.1 achieved the highest SBERT cosine score, at 86.22, indicating the strongest overall structural and thematic similarity to the target counseling guide. Llama-3.3-70B achieved the highest BERTScore F1, at 86.84, indicating the strongest content alignment under that metric.

These results motivated a human comparison of four shortlisted models: Gemini-2.5-Flash, Llama-3.3-70B, GPT-4.1, and Gemma-3-27b. Table 4 reports human scores at the category-level. Llama-3.3-70B and GPT-4.1 tied on the overall average,



Figure 4: Comparison of RAG and knowledge-graph-grounded performance across BERTScore F1, SBERT cosine similarity, and mean human rating for the four shortlisted models. Connecting lines indicate the change from the RAG-based model to its knowledge-graph-grounded counterpart. Knowledge-graph grounding consistently improved BERTScore F1 and human ratings, while SBERT changes were mixed.

with both models scoring 2.3, but their strengths differed across categories. Llama-3.3-70B performed best on wording and problem analysis, whereas GPT-4.1 performed best on treatment and intervention quality and on environmental analysis. Gemini-2.5-Flash followed with an average of 2.5. Gemma-3-27b received the weakest human scores across all five categories, with an average of 3.3.

Model	Wording	Problem	Guidance	Treatment	Environ.	Average
Llama-3.3-70B	2.0	2.5	2.0	2.5	2.5	2.3
GPT-4.1	2.5	3.0	2.0	2.0	2.0	2.3
Gemini-2.5-Flash	2.5	2.5	2.5	2.5	2.5	2.5
Gemma-3-27b	3.0	3.5	3.5	3.0	3.5	3.3

Table 4: Human evaluation of the four shortlisted RAG-based models. Scores are mean human ratings on a five-point scale, with lower values indicating better performance. Environ.: Environmental Analysis.

We next evaluated knowledge-graph grounding on the four shortlisted models. The knowledge graph encoded 308 nodes and 642 relationships spanning causes, effects, interventions, outcomes, categories, and counseling logic. Table 5 compares each RAG-based model with its knowledge-graph-enhanced counterpart. BERTScore F1 increased for all four models, with gains ranging from 0.54 points for Llama-3.3-70B to 0.80 points for GPT-4.1. This indicates that knowledge-graph grounding consistently improved content alignment with the target guidance.

The SBERT results show a less consistent pattern. Gemini-2.5-Flash improved slightly after knowledge-graph grounding. In contrast, Llama-3.3-70B, Gemma-3-27b, and GPT-4.1 showed lower SBERT cosine scores after grounding, with

	BERT F1			SBERT			Human		
Model	RAG	KG	Δ	RAG	KG	Δ	RAG	KG	Δ
Gemini-2.5-Flash	86.39	87.18	↑ 0.79	83.09	83.28	↑ 0.19	2.50	1.80	↓ 0.70
Llama-3.3-70B	86.84	87.38	↑ 0.54	83.47	82.95	↓ 0.52	2.30	1.70	↓ 0.60
Gemma-3-27b	85.39	86.02	↑ 0.63	82.64	78.40	↓ 4.24	3.30	2.40	↓ 0.90
GPT-4.1	85.57	86.37	↑ 0.80	86.22	82.79	↓ 3.43	2.30	1.90	↓ 0.40

Table 5: Comparison of RAG-based and knowledge-graph-enhanced models. BERT F1 denotes BERTScore F1, SBERT denotes SBERT cosine similarity, and Human denotes the mean human rating on a five-point scale, with lower values indicating better performance. In the Δ columns, blue indicates improvement and red indicates deterioration relative to the RAG model.

the largest decrease observed for Gemma-3-27b. In some cases, SBERT similarity scores decreased after KG grounding because the grounded responses became more culturally specific and contextually enriched rather than semantically aligned with the reference responses. Since SBERT primarily captures surface-level semantic similarity, responses incorporating localized counseling practices, culturally grounded expressions, or explanatory context may diverge lexically from the gold references while still being more appropriate and culturally relevant. These mixed changes suggest that knowledge-graph grounding altered the structure or phrasing of the generated responses in ways that did not always increase sentence-level similarity to the reference text, even when the content became more closely aligned.

The human evaluation provides a clearer picture for the present application. All four models improved after knowledge-graph grounding. The average human score decreased by 0.6 points for Llama-3.3-70B, 0.4 points for GPT-4.1, 0.7 points

for Gemini-2.5-Flash, and 0.9 points for Gemma-3-27b. After grounding, Llama-3.3-70B achieved the strongest mean human score, at 1.7. Gemini-2.5-Flash followed closely at 1.8, and GPT-4.1 followed at 1.9. Although Gemma-3-27b remained the weakest of the four models overall, it showed the largest gain in average human score. Table 7 reports the underlying category-level ratings before and after grounding across *wording, problem analysis, guidance, treatment and intervention quality,* and *environmental analysis*.

Figure 4 shows that model choice affects performance, but no single model consistently outperforms others across all evaluation settings. Automated metrics favored different models (GPT-4.1 for overall similarity and Llama-3.3-70B for BERTScore F1) while human evaluation rated them similarly overall, highlighting differences mainly in specific categories. This indicates that automated evaluation alone is insufficient, as responses may match reference texts without being clear, appropriate, or practically useful for counseling.

The proposed KG construction framework is adaptable to other low-resource languages and cultural settings by incorporating locally grounded counseling practices, community narratives, and region-specific mental health expressions through collaboration with domain experts and native speakers. Although ontology and entity relations may vary between cultures, the overall methodology of combining expert validation, culturally situated knowledge sources, and iterative refinement can generalize to broader multilingual mental health applications.

The findings also demonstrate that expert-curated knowledge and knowledge-graph grounding had a stronger impact on performance than solely model selection. Incorporating structured, clinically reviewed knowledge improved results across all tested models, particularly in real-world use. However, environmental and contextual analysis remained weaker than other aspects, such as wording, guidance, and problem analysis. Future work should therefore focus on better representing family, personal, and economic contexts and improving support for complex interpersonal situations in counseling.

5 Conclusion

In this work, we propose RAG- and KG-based approaches for generating counseling support responses by integrating structured domain knowledge with large language models in Bangladesh context. We first curated and manually annotated the narratives of the counseling sessions with a multidisciplinary team to ensure compliance with privacy, narrative coherence, and clinical validity. Using validated data, we constructed a domain-specific knowledge graph to represent causal relationships among stressors, interventions, and effects. We then compared two experimental settings, RAG- and KG–based experiments, across multiple language models to examine whether incorporating culturally-grounded knowledge improves counseling quality. Our results show that incorporating structured, clinically curated knowledge from para-counselors, PHRs, PWLEs, psychologists, and psychiatrists consistently improves the quality and practical relevance of generated counseling responses more than model selection alone. Human evaluation highlights that effective counseling support depends not only on semantic similarity to reference responses but also on clear wording, accurate problem interpretation, appropriate guidance, and contextual awareness. However, environmental and broader contextual analysis remain a challenging aspect for current systems.

Future work will concentrate on enriching the knowledge graph with broader contextual factors and enhancing the representation of familial, personal, and socioeconomic contexts. Furthermore, we will develop more rigorous, participatory evaluation protocols that incorporate the perspectives and experiences of users and community members to enable more meaningful assessment and continuous improvement of counseling-oriented language-generation systems.

Limitations

Despite the promising results, this study has several limitations. First, the dataset used in this work is relatively small, consisting of a limited number of annotated counseling cases. Although the narratives were carefully validated by domain experts, the dataset may not fully capture the diversity of mental health experiences, cultural contexts, and counseling scenarios encountered in real-world settings. Second, while the knowledge graph was manually curated by a group of experts to ensure clinical validity, the scope of the graph is constrained by the available cases and domain coverage. As a result, some complex relationships between stres-

sors, contextual factors, and interventions may not yet be fully represented.

Although both automatic and human evaluations were conducted, human evaluation inherently involves subjective judgment, and the number of evaluators and evaluation rounds may limit the generalizability of the results. Finally, the system is designed to support counseling guidance rather than replace professional clinical judgment. Therefore, responses generated by the model should be interpreted as supportive suggestions rather than definitive clinical recommendations.

Ethical Consideration

Our research examines the feasibility of providing mental health support to people in lower-income communities through para-counselors. Much of the existing work on culturally sensitive LLMs focuses on direct user-facing applications, where marginalized individuals interact with chatbots for emotional support (Ma et al., 2024; Aleem et al., 2024). Given the ethical and clinical risks involved, scholars have explicitly warned against using LLMs as substitutes for licensed therapists (Moore et al., 2025). Concerns include the absence of clinical accountability, potential for harmful misinterpretation, and lack of sustained relational understanding.

Informed by this body of work, we are studying the use of LLMs by para-counselors rather than directly by service users. Our work represents a potentially promising and ethically moderated application. Here, LLMs would serve as knowledge-support systems to augment para-counselors' decision-making capacities, while ultimate responsibility for interpretation and action remains with the human provider.

Acknowledgment

This research was supported by the **"Wellcome Foundation Grant for Generative AI for Anxiety, Depression and Psychosis, 2026"**. We sincerely thank the mental health professionals, para-counselors, and community contributors whose expertise, insights, and feedback helped shape the culturally grounded counseling knowledge utilized in this work. We are also grateful to the reviewers for their thoughtful comments and constructive suggestions, which helped improve the quality and clarity of the paper. Finally, we acknowledge the support of our research collaborators and affiliated institutions for their continuous guidance and encouragement throughout this project.

References

Yasmina Al Ghadban, Huiqi Lu, Uday Adavi, Ankita Sharma, Sridevi Gara, Neelanjana Das, Bhaskar Kumar, Renu John, Praveen Devarsetty, and Jane E Hirst. 2023. Transforming healthcare education: Harnessing large language models for frontline health worker capacity building using retrieval-augmented generation. *medRxiv*, pages 2023–12.

Mahwish Aleem, Imama Zahoor, and Mustafa Naseem. 2024. Towards culturally adaptive large language models in mental health: Using chatgpt as a case study. In *Companion Publication of the 2024 Conference on Computer-Supported Cooperative Work and Social Computing*, CSCW Companion '24, page 240–247, New York, NY, USA. Association for Computing Machinery.

Jiale Cheng, Sahand Sabour, Hao Sun, Zhuang Chen, and Minlie Huang. 2023. PAL: Persona-augmented emotional support conversation generation. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 535–554, Toronto, Canada. Association for Computational Linguistics.

Young Min Cho, Sunny Rai, Lyle Ungar, João Sedoc, and Sharath Guntuku. 2023. An integrative survey on mental health conversational agents to bridge computer science and medical perspectives. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 11346–11369, Singapore. Association for Computational Linguistics.

Jacinthe Flore. 2023. *The artefacts of digital mental health*. Springer.

Sarah Harrison, Alex Ssimbwa, Mohamed Elshazly, Mahmuda Mahmuda, Mohamed Zahidul Islam, Hasna Akter Sumi, and Olga Alexandra Rebolledo. 2019. Strategic priorities for mental health and psychosocial support services for rohingya refugees in bangladesh: a field report. *Intervention Journal of Mental Health and Psychosocial Support in Conflict Affected Areas*, 17(2):206–211.

Rubina Jahan, Md Ashiquir Rahaman, and Arun Das. 2024. Ngos working on mental health in bangladesh. In *Mental Health in Bangladesh: From Bench to Community*, pages 323–342. Springer.

Swanie Juhng, Matthew Matero, Vasudha Varadarajan, Johannes Eichstaedt, Adithya V Ganesan, and H. Andrew Schwartz. 2023. Discourse-level representations can improve prediction of degree of anxiety. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 1500–1511, Toronto, Canada. Association for Computational Linguistics.

Henrique A. Lima, Pedro H. F. S. Trocoli-couto, Marzia Zaman, Débora C. Engelmann, Rosalind Parkes-Ratanshi, Leah Junck, Brenda Hendry, Amelia Taylor, Michelle El Kawak, Nirmal Ravi, Henrique D. P. Santos, Timothy M. Pawlik, and Vivian Resende. Spotlighting healthcare frontline workers´ perceptions on artificial intelligence across the globe. 2(1):28.

Chen Cecilia Liu, Hiba Arnaout, Nils Kovačić, Dana Atzil-Slonim, and Iryna Gurevych. 2026. Tailored emotional LLM-supporter: Enhancing cultural sensitivity. In *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 535–574, Rabat, Morocco. Association for Computational Linguistics.

Daniel Lozoya, Alejandro Berazaluce, Juan Perches, Eloy Lúa, Mike Conway, and Simon D'Alfonso. 2024. Generating mental health transcripts with SAPE (Spanish adaptive prompt engineering). In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 5096–5113, Mexico City, Mexico. Association for Computational Linguistics.

Zilin Ma, Yiyang Mei, Yinru Long, Zhaoyuan Su, and Krzysztof Z. Gajos. 2024. Evaluating the experience of lgbtq+ people using large language model based chatbots for mental health support. In *Proceedings of the 2024 CHI Conference on Human Factors in Computing Systems*, CHI '24, New York, NY, USA. Association for Computing Machinery.

Zafarullah Mahmood, Soliman Ali, Jiading Zhu, Mohamed Abdelwahab, Michelle Yu Collins, Sihan Chen, Yi Cheng Zhao, Jodi Wolff, Osnat C. Melamed, Nadia Minian, Marta Maslej, Carolynne Cooper, Matt Ratto, Peter Selby, and Jonathan Rose. 2025. A fully generative motivational interviewing counsellor chatbot for moving smokers towards the decision to quit. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 25008–25043, Vienna, Austria. Association for Computational Linguistics.

Subhankar Maity and Manob Jyoti Saikia. 2025. Large language models in healthcare and medical applications: A review. *Bioengineering*, 12(6).

Erum Mariam and Sarah Tabassum. 2023. Sisters of peace: Para-counselors lead psychosocial support for rohingya children and families during covid-19. In *Young Children in Humanitarian and COVID-19 Crises*, pages 197–210. Routledge.

Pierrette MAHORO MASTEL, Jean de Dieu Nyandwi, Samuel Rutunda, and Kleber Kabanda. 2025. Mbaza rbc: Deploying and evaluation of an llm powered chatbot for community health workers in rwanda. In *Workshop on Large Language Models and Generative AI for Health at AAAI 2025*.

Shervin Minaee, Tomas Mikolov, Narjes Nikzad, Meysam Chenaghlu, Richard Socher, Xavier Amatriain, and Jianfeng Gao. 2025. Large language models: A survey. *Preprint*, arXiv:2402.06196.

Jared Moore, Declan Grabb, William Agnew, Kevin Klyman, Stevie Chancellor, Desmond C. Ong, and Nick Haber. 2025. Expressing stigma and inappropriate responses prevents llms from safely replacing mental health providers. In *Proceedings of the 2025 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '25, page 599–627, New York, NY, USA. Association for Computing Machinery.

Maria Moosa, Oluwaseyi Malumi, Solomon Chinedu, Wilson Okah, Ayoposi Ogboye, Chiagozie Abiakam, Peter Onyenemerem, Imo Etuk, and Nneka Mobisson. 2025. Evaluating frontline health workers' responses to patient inquiries with and without large language model support in nigeria: An observational study. *VeriXiv*, 2:324.

Md. Ashiquir Rahaman. 2025. Mental health of handloom weavers in bangladesh: A call for culturally adapted interventions. *Cambridge Prisms: Global Mental Health*, 12:e123.

Pragnya Ramjee, Mehak Chhokar, Bhuvan Sachdeva, Mahendra Meena, Hamid Abdullah, Aditya Vashistha, Ruchit Nagar, and Mohit Jain. 2025. Ashabot: An llm-powered chatbot to support the informational needs of community health workers. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems*, CHI '25, New York, NY, USA. Association for Computing Machinery.

Samuel Rutunda, Gwydion Williams, Kleber Kabanda, Francis Nkurunziza, Solange Uwiduhaye, Eulade Rugegamanzi, Cyprien Nshimiyimana, Vaishnavi Menon, Mira Emmanuel-Fabula, Alastair K. Denniston, Xiaoxuan Liu, Emery Hezagira, and Bilal A. Mateen. Large language models for frontline healthcare support in low-resource settings. 1(2):191–197.

Sahand Sabour, Siyang Liu, Zheyuan Zhang, June Liu, Jinfeng Zhou, Alvionna Sunaryo, Tatia Lee, Rada Mihalcea, and Minlie Huang. 2024. EmoBench: Evaluating the emotional intelligence of large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 5986–6004, Bangkok, Thailand. Association for Computational Linguistics.

Ashish Sharma, Kevin Rushton, Inna Lin, David Wadden, Khendra Lucas, Adam Miner, Theresa Nguyen, and Tim Althoff. 2023. Cognitive reframing of negative thoughts through human-language model interaction. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 9977–10000, Toronto, Canada. Association for Computational Linguistics.

Daisy R Singla, Sabrina Hossain, Nicole Andrejek, Matthew J Cohen, Cindy-Lee Dennis, Jo Kim,

Laura La Porte, Samantha E Meltzer-Brody, Angie Puerto Nino, Paula Ravitz, and 1 others. 2022. Culturally sensitive psychotherapy for perinatal women: A mixed methods study. *Journal of Consulting and Clinical Psychology*, 90(10):770.

Hoyun Song, Huije Lee, Jisu Shin, Sukmin Cho, Changgeon Ko, and Jong C. Park. 2025a. Does rationale quality matter? enhancing mental disorder detection via selective reasoning distillation. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 21738–21756, Vienna, Austria. Association for Computational Linguistics.

Inhwa Song, Sachin R Pendse, Neha Kumar, and Munmun De Choudhury. 2025b. The typing cure: Experiences with large language model chatbots for mental health support. *Proc. ACM Hum.-Comput. Interact.*, 9(7).

Ming Wang, Peidong Wang, Lin Wu, Xiaocui Yang, Daling Wang, Shi Feng, Yuxin Chen, Bixuan Wang, and Yifei Zhang. 2025. AnnaAgent: Dynamic evolution agent system with multi-session memory for realistic seeker simulation. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 23221–23235, Vienna, Austria. Association for Computational Linguistics.

Xuhai Xu, Bingsheng Yao, Yuanzhe Dong, Saadia Gabriel, Hong Yu, James Hendler, Marzyeh Ghassemi, Anind K. Dey, and Dakuo Wang. 2024. Mental-llm: Leveraging large language models for mental health prediction via online text data. *Proc. ACM Interact. Mob. Wearable Ubiquitous Technol.*, 8(1).

Kailai Yang, Shaoxiong Ji, Tianlin Zhang, Qianqian Xie, Ziyan Kuang, and Sophia Ananiadou. 2023. Towards interpretable mental health analysis with large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 6056–6077, Singapore. Association for Computational Linguistics.

Wei Zhai, Hongzhi Qi, Qing Zhao, Jianqiang Li, Ziqi Wang, Han Wang, Bing Yang, and Guanghui Fu. 2024. Chinese MentalBERT: Domain-adaptive pre-training on social media for Chinese mental health text analysis. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 10574–10585, Bangkok, Thailand. Association for Computational Linguistics.

Xinzhe Zheng, Sijie Ji, Jiawei Sun, Renqi Chen, Wei Gao, and Mani Srivastava. 2025. ProMind-LLM: Proactive mental health care via causal reasoning with sensor data. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 20150–20171, Vienna, Austria. Association for Computational Linguistics.

A Dataset

A.1 Guideline for Conducting Sessions

Session 1 The goal of this session is to establish understanding with participants and build trust in the para-counselors. Participants are reassured that the para-counselors are there to support them and that all shared information will remain confidential. This environment is intended to help participants feel comfortable discussing their personal concerns and emotional experiences openly and without hesitation. Para-counselors were additionally instructed to respond adaptively to participants' circumstances. For instance, if a participant disclosed the death of a relative, para-counselors were expected to provide appropriate emotional support and empathy. This session primarily focuses on identifying the key sources of the participant's stress and emotional condition, which can subsequently inform targeted and actionable counseling interventions. The goal of the first session is two-fold. First is to give an opportunity to both the participant and the para-counselor to understand each other. Second, help the participant build trust in the para-counselor by ensuring they are available when needed and protecting the confidentiality of information shared by participants, among other measures.

Session 2 The objective of this session is to transition from problem identification to a solution-oriented discussion. Para-counselors work with participants to explore practical strategies for addressing their challenges. For example, for financial concerns, counselors can discuss budgeting or savings practices, while for interpersonal or domestic conflicts, they can explore behavioral adjustments, anger management strategies, or appropriate support-seeking actions. This session also follows a structured guideline that prioritizes which issues should be addressed first, ensuring that the most urgent or impactful concerns are discussed before others. Moreover, participants are guided to select a small set of activities that may improve mood or daily functioning. Para-counselors also introduce an activity log to track behaviors and emotions and schedule the next appointment.

Session 3-5 These sessions focus on reviewing the participant's activity log and discussing how the selected activities have influenced mood and daily functioning. Para-counselors ask participants about emotional changes, discuss which activities were helpful or challenging, and revisit previously identified problems. Based on the participant's progress, new activities aligned with the goals established in Session 1 may be added.

Session 6 The final session summarizes the skills and strategies learned throughout the counseling process. Para-counselors review the participant's goals, discuss progress, and help the participant develop a practical plan for responding to future challenges. Participants are also encouraged to create a "toolbox" of helpful coping strategies that they can use independently.

A.2 Annotation Guideline

Our annotation guideline for reviewing and annotating session narratives in two stages: *i)* Appropriateness and Data Privacy Review and *ii)* Expert Clinical Review. Annotators should carefully evaluate each case to ensure accuracy, completeness, privacy protection, and clinical soundness.

A.2.1 Appropriateness and Data Privacy Review

In this step, the annotators evaluate each session narrative for privacy compliance, clarity, and structural validity. Each case should be marked as Appropriate or Not Appropriate, with suggested corrections provided where necessary. Annotators must also correct spelling and grammar errors and remove any identifying details. The annotators also performed data anonymization and de-identification, along with session narrative appropriateness, using the following criteria:

Data anonymization and De-identification Annotators must remove all direct identifiers, including names, addresses, phone numbers, workplaces, schools, and specific community names. Replace these with generalized descriptors (e.g., 'the client', 'a family member', 'a local workplace'). Specific calendar dates should be generalized using relative references such as 'Session 1', 'Week 2', or '7 days after the first session' to preserve temporal structure without revealing identifiable information.

Session Narrative Appropriateness Annotators must verify whether demographics, contextual factors, presenting problems, stressors, and protective factors are correctly identified and categorized. Moreover, annotators should assess whether important causes or protective factors have been overlooked or misclassified. The narrative must clearly reflect a coherent causal chain: stressors or causes $\rightarrow$ psychological/behavioral effects $\rightarrow$ intervention applied $\rightarrow$ resulting outcomes. If any component is missing or logically inconsistent, it should be flagged for revision.

A.2.2 Expert Clinical Review

In this annotation step, a qualified psychologist evaluates the clinical integrity and completeness of the session narrative. Cases that fail to clearly identify a causal chain and intervention outcome should be marked as *Incomplete*. The psychologist should determine whether demographics, contextual variables, stressors, protective factors, and presenting problems are clinically appropriate and accurately interpreted. Particular attention should be paid to potential discrepancies in the classification of protective factors. The session narrative must provide sufficient information to establish a meaningful cause and effect relationship between identified stressors, intervention strategies, and observed outcomes.

In Addition, the psychologist should evaluate whether the selected intervention type is clinically appropriate given the client's demographics and presenting concerns. Finally, the psychologists must assess whether any point in the causal chain requires an emergency guardrail (e.g., crisis referral, notification of family members, psychiatric evaluation, or hospitalization). Missing but necessary safeguards should be explicitly identified.

Model	Family	BERT F1	SBERT
gemini-2.5-pro	Gemini	86.07	81.15
gemini-2.5-flash		86.39	83.09
gemini-2.0-flash		86.02	80.87
Llama-4-Maverick	Llama	86.36	82.71
Llama-3.3-70B		**86.84**	83.47
Llama-3.1-70B		86.34	80.89
Llama-3-8B		84.95	70.03
DeepSeek-V3.2	DeepSeek	85.97	79.52
DeepSeek-V3.1		85.61	69.31
DeepSeek-R1		85.81	73.67
gemma-3-27b	Gemma	85.39	82.64
gemma-3-12b		85.44	75.41
gemma-3-4b		85.54	79.81
GPT-5.1	OpenAI	85.81	74.84
GPT-4.1		85.57	**86.22**
GPT-4o		85.70	74.12
gpt-oss-20b		85.24	80.06

Table 6: Automated evaluation for all seventeen models. BERT F1 denotes BERTScore F1, and SBERT denotes SBERT cosine similarity. **Bold** indicates best performance.

B Results

Table 6 reproduces the automated scores for all seventeen evaluated models. These values motivated the shortlist used for human evaluation in



Figure 5: Category-level human ratings before and after knowledge-graph grounding for the four shortlisted models. Lower values indicate better performance. The figure shows paired category-wise ratings for each model, highlighting consistent decreases in average human scores after grounding, with variation in the magnitude of change across categories and models.

	Llama-3.3-70B			GPT-4.1			Gemini-2.5-Flash			Gemma-3-27b		
Category	**RAG**	**KG**	**Δ**	**RAG**	**KG**	**Δ**	**RAG**	**KG**	**Δ**	**RAG**	**KG**	**Δ**
Wording	2.0	1.5	↓ 0.5	2.5	2.0	↓ 0.5	2.5	1.5	↓ 1.0	3.0	2.0	↓ 1.0
Problem analysis	2.5	1.5	↓ 1.0	3.0	2.0	↓ 1.0	2.5	2.0	↓ 0.5	3.5	2.5	↓ 1.0
Guidance	2.0	1.5	↓ 0.5	2.0	2.0	0.0	2.5	2.0	↓ 0.5	3.5	2.5	↓ 1.0
Treatment / intervention	2.5	2.0	↓ 0.5	2.0	1.5	↓ 0.5	2.5	1.5	↓ 1.0	3.0	2.0	↓ 1.0
Environmental analysis	2.5	2.0	↓ 0.5	2.0	2.0	0.0	2.5	2.0	↓ 0.5	3.5	3.0	↓ 0.5
Average	**2.3**	**1.7**	↓ 0.6	**2.3**	**1.9**	↓ 0.4	**2.5**	**1.8**	↓ 0.7	**3.3**	**2.4**	↓ 0.9

Table 7: Category-level human scores before and after knowledge-graph grounding for the four shortlisted models. Scores are mean human ratings on a five-point scale, with lower values indicating better performance. In the Δ columns, blue indicates improvement relative to the RAG model.

the main text. Moreover, Table 7 and Figure 5 show category-level human scores before and after knowledge-graph grounding for the four shortlisted models.

Evaluating Document-Tuned Transformer Representations for Person-level Mental Health Assessment

Aaron Marker
Vanderbilt University
aaron.marker@vanderbilt.edu

Oscar Kjell
Lund University

Vasudha Varadarajan
Carnegie Mellon University

H. Andrew Schwartz
Vanderbilt University
hansen.schwartz@vanderbilt.edu

Abstract

Person-level psychological assessment requires aggregating meaning across many messages from the same individual, a task that document-level training objectives were not explicitly designed for. We present a systematic, empirical comparison between architecturally matched traditional (a) *base-transformers* and (b) *document-tuned-transformers* (further contrastively fine-tuned at the document-level, sometimes referred to as "sentence transformers") under otherwise identical conditions. Comparing layer-wise and overall performance across two longitudinal mental health and psychological datasets, we find document-tuned models demonstrated a consistent improvement over base representations (increase in Pearson r of $13.4\%, p = .015$). Robustness analyses revealed document-tuned models remained more accurate under perturbations to word deletion, synonym replacement, typo injection, and back translation. Further, hedged language (e.g., 'usually') was more characteristic of outcomes in document-tuned embeddings while abundance (e.g., 'lot') was more characteristic of base-transformers, suggesting document-tuned models may better capture uncertainty. These results suggest representation choice impacts mental health prediction, document-tuned models often being more adept.

1 Introduction

Transformer-based language models are increasingly used to infer psychological constructs such as depression, anxiety, well-being, and personality from text (Tsakalidis et al., 2022; Zirikly et al., 2019; Guo et al., 2024; Pourkeyvan et al., 2024; Zhang et al., 2022). Much of prior work relies on token-level pretrained encoders (e.g., BERT, RoBERTa) (Liu et al., 2019b; Devlin et al., 2019). Recently, sentence transformers trained with document-level contrastive objectives (e.g., Sentence-BERT) have gained popularity for producing semantically meaningful sentence- and document-level embeddings (Reimers and Gurevych, 2019). These embeddings are typically frozen and used in a simple prediction head such that the quality of the representation itself becomes the primary driver of downstream performance.

Document-tuned transformers could bring two important advantages over the base transformers. First, psychological assessments are person-level outcomes (Zhang et al., 2022; Montejo-Raez et al., 2024; Garg, 2023) while base transformers ultimately represent information at a much lower level of aggregation, the token. Document-level representations already move to a higher level of aggregation (one per document or sentence) where by meaning at the level of whole sequences isn't relegated to words in context. Further, representations from traditional word-level transformers are also known to suffer from anisotropy (Ethayarajh, 2019), a geometric property where embeddings cluster in a narrow cone, rather than being uniformly distributed, often causing unrelated words to appear mathematically similar. Document-tuned transformers partially address both of these issues: tuned to produce document-level representations, they aggregate, and bring symmetry across dimensions of embeddings (Gao et al., 2021; Jung et al., 2023). However, empirically, it remains unclear which representation strategy is better suited for mental health assessment.

The psychological constructs targeted in this study span a broad range of clinical phenomena that differ in how they are experienced and expressed. Internalizing conditions such as depression and anxiety involves affective (e.g., nervous, sad), cognitive (e.g., useless, incapable), and somatic dimensions (e.g., headache, nausea) that individuals may disclose directly (Gu et al., 2025) or express through indirect, hedged language (Varadarajan et al., 2025). Substance use patterns, are often discussed obliquely — for example, problematic

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 178–187
July 4, 2026 ©2026 Association for Computational Linguistics

drinking is associated with sadness, frustration, or even describing social events (Nilsson et al., 2024). Understanding how representation strategies may vary in their capacity to capture such diverse signals is essential for psychological prediction — particularly when prediction relies on aggregating many short, naturalistic text responses into a single person-level representation.

We conduct a controlled comparison of MLM-pretrained (base) and contrastively fine-tuned document-level (document-tuned) encoders for user-level psychological prediction. We aim to answer (RQ1) which model is more accurate for psychological prediction? (RQ2) what are optimal layer selection and message aggregation strategies? and (RQ3) do observed differences reflect sensitivity to specific linguistic features or perturbations? Our contributions are: (1) to our knowledge, the first controlled comparison of MLM-pretrained and document-tuned encoders for user-level psychological prediction; (2) an empirical analysis of layer selection and aggregation strategies across these encoder types; and (3) linguistic perturbation experiments that probe the source of observed performance differences in psychological settings.

2 Related Work

Much of prior work on transformer-based psychological prediction relies on token-level fine-tuned encoders. Alternative methods explicitly learn document-level representations optimized for semantic similarity. This distinction motivates a focused comparison of how representation choice impacts psychology-oriented prediction tasks.

2.1 Token level transformer fine-tuning

Pretrained transformer encoders, such as BERT, established a fine-tuning paradigm in which contextualized token-level models are fine-tuned end-to-end for downstream tasks (Devlin et al., 2019). Subsequent models, including RoBERTa, showed that architectural refinements and improved pretraining strategies can substantially improve performance, reinforcing token-level fine-tuning as a strong default across NLP tasks (Liu et al., 2019b). For sentence- or document-level prediction, these models typically rely on pooled token embeddings or a special classification token (e.g., [CLS]). However, because pretraining objectives are primarily token-level, these representations are not explicitly optimized for holistic document semantics.

2.2 Document level representation learning

A recent development focuses on learning general-purpose document embeddings. Sentence-BERT uses Siamese and contrastive objectives to produce fixed-size representations that capture semantic similarity (Reimers and Gurevych, 2019). Unlike token-level fine-tuning, these models directly encode entire sentences or short documents, enabling efficient reuse with lightweight downstream predictors.

2.3 Language modeling for psychological prediction

Transformer models have been widely applied in computational psychology, including tasks such as depression detection, suicide risk assessment, and mood prediction, often through shared tasks such as CLPsych (Tsakalidis et al., 2022; Tseriotou et al., 2025; Zhang et al., 2022; Montejo-Raez et al., 2024; Garg, 2023). While most work relies on token-level pretrained models, document-level encoders (e.g., Sentence-BERT) have also been used, for instance in ensemble systems and shared-task submissions (Ogunleye et al., 2024; Azim et al., 2022). The coexistence of these approaches highlights the need for controlled comparisons. We address this by comparing "roberta-large" and "all-roberta-large-v1" under matched extraction and evaluation settings.

3 Datasets

We evaluate our models on two longitudinal datasets that differ in scale and outcome focus: (1) a densely sampled ecological momentary assessment dataset (DS4UD) with broad psychological measures (Nilsson et al., 2024), and (2) a larger longitudinal mental health dataset (LMHD) with a broader user population (Kjell et al., in progress). Both datasets require aggregating multiple temporally distributed text responses to model person-level psychological outcomes, making them well-suited to examine how representation strategies handle aggregation across temporally distributed text.

3.1 The DS4UD Dataset

DS4UD is a longitudinal EMA dataset of U.S. service industry workers collected via a smartphone application (Nilsson et al., 2024). Participants (N=120; 75% female; $M_{age} = 35$) completed up to three EMAs per day across multiple 14-day waves.

Dataset	Statistic	
DS4UD	Total documents (EMAs)	10,108
	Average documents per person	84.9
	Total people	120
LMHD	Total documents (EMAs)	7,207
	Average documents per person	5.5
	Total people	1,307

Table 1: Descriptive statistics for the DS4UD and LMHD datasets under individual-message and concatenated-message representations.

Each EMA included an open-ended English text response (minimum 200 characters) describing the participant's current affective state, along with self-report ratings of momentary affect (positive and negative affect), perceived stress, recent alcohol use, alcohol craving, and energy.

At the start of each wave, participants completed standardized questionnaires assessing affect such as valence and arousal (Remington et al., 2000), positive and negative affect (Thompson, 2007), depressive symptoms (Patient Health Questionnaire–9; PHQ-9) (Kroenke et al., 2001), anxiety symptoms (Generalized Anxiety Disorder–7; GAD-7) (Spitzer et al., 2006), perceived stress (Perceived Stress Scale; PSS) (Cohen et al., 1983), alcohol use severity (Alcohol Use Disorders Identification Test; AUDIT, including the AUDIT-C) (Saunders et al., 1993), cravings, exposure to adverse childhood experiences (MACE) (Teicher and Parigger, 2015), and personality traits using a Big Five inventory (extraversion, agreeableness, conscientiousness, neuroticism, and openness) (Soto and John, 2017). These measures capture clinically relevant internalizing symptoms, substance use risk, stress, and stable personality characteristics. We retain participants who completed at least two waves, yielding over 10,000 text-based EMAs from 120 participants.

3.2 The LMH Dataset

The LMH Dataset comprise 10-week longitudinal data from a study evaluating alternative approaches to mental health assessment, including measures of general mental health and symptoms related to major depressive disorder (MDD) and generalized anxiety disorder (GAD). Participants were recruited via Prolific, and the present analyses include English-speaking participants only (N = 1,307; M age = 43.9 years, SD = 17.5; male = 34.3%, female = 64.0%, other = 1.7%). The sample was enriched: approximately 50% of participants were recruited from Prolific's general population, while the remaining participants were prescreened to report a prior diagnosis of MDD ($\approx$ 25%) or GAD ($\approx$ 25%).

Participants completed comprehensive surveys at baseline and follow-up, with shorter bi-weekly surveys administered in between. Across waves, the study assessed well-being; depressive and anxiety symptoms; perceived stress; alcohol and drug use; trauma-related symptoms; functional impairment; healthcare utilization; and sociodemographics using a combination of brief open-ended paragraph responses, word-selection formats, and standardized rating scales. Validated measures included the PHQ-9 and PHQ-2 for depressive symptoms; the GAD-7 and GAD-2 for anxiety ; subscales from the Inventory of Depression and Anxiety Symptoms (IDAS) assessing dysphoria, suicidality, panic, social anxiety, ill temper, lassitude, insomnia, appetite changes, traumatic intrusions, and well-being (Watson et al., 2007); the Perceived Stress Scale (PSS); the Alcohol Use Disorders Identification Test (AUDIT); the harmony in life score (HILS) (Kjell et al., 2016); the Drug Use Disorders Identification Test (DUDIT) (Berman et al., 2004); the Satisfaction with Life Scale (SWLS) (Diener et al., 1985); and the World Health Organization Disability Assessment Schedule (WHO-DAS) (Üstün, 2010). Additional items assessed sick days and mental health service utilization.

In the current study, we use the open-ended response to the general mental health prompt: "How is your mental health? Please describe how you have been over the last two weeks. You can, for example, write about your emotions, thoughts, behaviours, and/or symptoms related to your health. Write at least one paragraph."

4 Methods

We compare representations from (i) a masked language modeling (MLM) pretrained encoder (base) and (ii) a document-level contrastively tuned encoder (document-tuned) built on the same backbone. Representations are evaluated layer-wise under identical extraction, aggregation, and downstream prediction procedures across two longitudinal datasets.

4.1 Models

We compare `roberta-large` (Liu et al., 2019b), pretrained with masked language modeling as the base model, and `all-roberta-large-v1` variant as the document-tuned model, which fine-tunes the same backbone using just over one billion sentence-pairs for contrastive fine-tuning to produce fixed-size embeddings (Reimers and Gurevych, 2019; Hugging Face, 2025).

Both models share architecture and parameter count, isolating representation learning objective as the primary variable. We note that this comparison is not fully controlled for training data, as the document-tuned model was exposed to additional data beyond masked language modeling pretraining. We use publicly available HuggingFace implementations.

4.2 Representation extraction

We embed each message individually and mean-pool all message embeddings for a given user to obtain a fixed-length person-level representation. To assess whether document-tuned encoders benefit from longer context, we also evaluate a concatenation strategy in which all user messages are joined prior to embedding. When concatenated text exceeds the model context window, segments are embedded separately and mean-pooled.

4.3 Layer-wise representation selection

We extract and pool representations from every transformer layer of both encoders and train identical downstream models using nested cross-validation (described below). Layer-wise evaluation is motivated by prior work showing that linguistic information varies across depth (Tenney et al., 2019; Jawahar et al., 2019; Rogers et al., 2020; Liu et al., 2019a). Because document-tuned transformers are explicitly fine-tuned on a semantic similarity objective, they may contain more useful semantic signal in later layers relative to MLM-pretrained models. We therefore compare average Pearson's r score from the 10-fold cross validation, averaging across all outcomes in that dataset, across all layers and select the best-performing layer for each encoder.

4.4 Predictive modeling and cross-validation

For each outcome, we fit ridge regression models with nested 10-fold cross-validation, with the regularization parameter α selected via nested cross validation following prior work (Singh et al., 2025). Performance is measured using Pearson's r between predicted and true values, averaged across folds. The same downstream model and hyperparameter grid are used for all encoder–layer combinations.

5 Results and Discussion

5.1 Overall Accuracy and Optimal layers

Document-tuned representations outperform base model representations at nearly all layers across both datasets 2. Peak performance occurs in later layers for document-tuned transformers (Layer 21 on LMHD; Layer 19 on DS4UD) and earlier-to-mid layers for base models (Layer 19 on LMHD; Layer 10 on DS4UD). This pattern is consistent across datasets, suggesting document-level tuning objectives may preserve semantically relevant information in higher layers.

We compare models at their best-performing layers. Document-level representations achieve higher overall predictive performance on both datasets ($\Delta r = .012$ on LMHD; $\Delta r = .055$ on DS4UD; Table 6). Larger effect sizes in the DS4UD dataset could be due to the additional information of many more documents per person than in the LMHD dataset (DS4UD messages per person ≈ 85, LMHD messages per person ≈ 6)

5.2 Layer-wise Performance Analysis

Table 2 reports the top-performing layers (by Pearson's r) for both"roberta-large" (base) and "all-roberta-large-v1" (document-tuned) across datasets. This suggests that contrastive fine-tuning reorganizes semantic information toward the final layers, whereas MLM pretraining distributes it more evenly across depth — consistent with the view that later layers in document-tuned transformers are more specialized for semantic similarity.

5.3 Model Performance by Domain

Improvements are not uniform across outcome domains (Table 6). Gains are most pronounced for affect, personality, and especially drinking behavior measures ($\Delta r = .081$ on LMHD and .096 on DS4UD), and more modest or inconsistent gains for mental health and demographic outcomes. The only outcome where base models outperformed document-tuned models was for predicting a users craving, otherwise, differences were small and non-significant, consistent with chance variation around a null effect.



Figure 1: Prediction performance on the DS4UD (*N=120*) and LMHD (*N=1307*) datasets from different layer representations within "roberta-large" (Base Accuracy) and "all-roberta-large-v1" (Document-Tuned Accuracy)

Optimal Layer and Overall Performance								
	DS4UD (*N=120*)				**LMHD** (*N=1,307*)			
R	**L**	**Base**	**L**	**Doc**	**L**	**Base**	**L**	**Doc**
1	10	.4165	19	.4716	19	.5458	21	.5579
2	15	.4160	20	.4673	18	.5453 ↓	20	.5572
3	13	.4155	21	.4665	17	.5447	19	.5564 ↓
4	19	.4145	23	.4643 ↓	16	.5441 ↓	18	.5550 ↓
5	16	.4133	24	.4635 ↓	20	.5421 ↓	22	.5540 ↓
6	14	.4098	22	.4605 ↓	15	.5409 ↓	17	.5511
7	8	.4092	18	.4491 ↓	21	.5400 ↓	23	.5504 ↓
8	11	.4067	15	.4425 ↓	14	.5381 ↓	16	.5500
9	23	.4014	14	.4400 ↓	22	.5379 ↓	24	.5491 ↓
10	20	.4012	13	.4395 ↓	23	.5353 ↓	15	.5469 ↓

Table 2: Top-performing (Pearson r) layers for the DS4UD and LMHD dataset for "roberta-large" (Base) and "all-roberta-large-v1" (Doc). ↓ indicates significant distinction from the best performing layer ($p < .05$).

Model Performance				
Outcome Category	**Dataset**	**Doc**	**Base**	**Δ**
Overall	LMHD	0.572	0.561	.012*
	DS4UD	0.472	0.416	.055*

Table 3: Document-tuned vs. base model performance (Pearson r) by dataset. Δ = document-tuned − base. $^{*}p < .05$, $^{**}p < .01$.

Concatenating all user messages prior to embedding only slightly increases the advantage of document-tuned transformer embeddings, but relative to mean pooling, results are inconsistent, and on the LMHD dataset, drops both embedding types' predictive accuracy (Appendix table 4).

5.4 Supervised Dimension Projection

To further contextualize these findings, we qualitatively examine Supervised Dimension Projection Plots of specific words. These plots are constructed by computing an embedding vector representing the difference between high and low values of a given outcome. Individual words are then projected onto this axis using dot product projections, indicating how strongly each word is associated with the outcome in a given embedding space (Kjell et al., 2023). To compare two models' embeddings of the same dataset, we plot the word along an embedding dimension representing the outcome in both embedding spaces, resulting in a 2D graph. We find no consistent trends in the number of significantly predictive words for either model. While graphs show both expected behavior (like "happy" being equally low in both representations), it also shows words like "Alright" in the second quadrant, which maps to high PHQ scores in document-tuned embeddings and low in base embeddings. This suggests that document-tuned models may encode the word 'Alright' in a context more associated with 'not being alright', whereas base models may place more emphasis independently on its definition alone — potentially reflecting the richer contextual representations learned through contrastive training. Embedded hedged language (e.g., 'usually' in PHQ and 'pretty' in AUDIT) tended to be more predictive of outcomes in document-tuned embeddings while abundance (e.g., 'lot') was more predictive in traditional word-level models, suggesting document-tuned models may better capture uncertainty and tentativeness in self-report language.

5.5 Perturbations

In recent work, such as (Alahmari et al., 2025), models have been probed for their robustness to human-induced linguistic errors that are common in real-world applications. As natural language surveys and EMAs are prone to user error, we corrupt text using deletion, typo injection, synonym replacement, and back translation at varying levels to simulate increasingly noisy data. We find



Figure 2: Dimension Projection Plot where words from the LMHD dataset are plotted along the embedding vector representing a difference in High vs Low PHQ. Words plotted along the diagonal line are represented similarly in both embedding spaces with relation to PHQ. More saturated points (like "meaning") are associated with high PHQ in one space and low PHQ in the other. Orange points are more highly associated with the outcome in Document Tuned embeddings, and blue points are more highly associated with the outcome in Base embeddings.

Model Performance by Message Combination Method				
Dataset	**Message Comb.**	**Doc**	**Base**	**Δ**
LMHD	Mean Pool	0.572	0.561	.012*
	Concatenate	0.546	0.532	.014*
DS4UD	Mean Pool	0.472	0.416	.055*
	Concatenate	0.482	0.411	.071**

Table 4: Document-tuned vs. base performance (Pearson r) by dataset and message combination. Δ = document-tuned − base. $^{*}p < .05$, $^{**}p < .01$.



Figure 3: Varying Levels of Text Perturbations vs Model Prediction Correlation with True Scores. (a) consists of deleting varying percentages of words. (b) consists of adding, replacing, or reordering adjacent letters in varying percentages of words. (c) consists of using WordNet to replace varying percentages of words with synonyms. (d) consists of translating the message into another language and back again.

in most cases, neither document-tuned nor base transformers are more robust to these perturbations than the other. Across deletion, typo injection, and back translation, both models showed comparable and gradual performance degradation as corruption levels increased. Synonym replacement shows slightly more robustness by the base transformer at extremely high percentages of replaced words, potentially because base model embeddings are less sensitive to global semantic context, making synonym substitution less disruptive to the overall representation. This fails to explain the stronger overall performance of document-tuned models, suggesting that their advantage stems from a more fundamental difference in how meaning is encoded that does not simply make the model more robust to syntactic or semantic noise.

6 Conclusion

This work presents a controlled comparison of base transformers (utilizing token representations) and document-tuned transformers (utilizing document-level, contrastively tuned representations) for psychological prediction. Document-tuned transformers consistently outperform base transformers for user-level psychological prediction across two longitudinal datasets. Gains are modest, but statistically significant and robust across layers. Optimal performance occurs in later layers for document-tuned models, with the final four to five layers performing comparably. We examined several candidate explanations for the observed performance differences, including outcome type, word embedding representation, and robustness to linguistic perturbations, but found no consistent moderating patterns. Crucially, the advantage of document-tuned representations was not confined to any par-

ticular outcome domain, suggesting a broadly superior capacity to encode person-level meaning rather than sensitivity to specific linguistic features — making document-tuned models a reasonable default choice for language-based mental health assessment. For researchers developing language-based screening or monitoring systems – particularly those using EMA or open-ended survey responses – these results provide empirical guidance on a design decision that is typically made without systematic comparison: which encoder to use and which layers to extract embeddings from.

7 Ethical Considerations

Both datasets were collected under institutional review board (IRB) approval with informed consent from participants. Analyses were conducted on de-identified text and survey data.

In particular, the improved prediction of sensitive outcomes such as drinking behavior and suicidality from open-ended text raises questions about the potential for unintended inference in deployed systems. Models developed in this work should not be used for clinical diagnosis or high-stakes decision-making without appropriate validation and oversight. While our study focuses on methodological comparison rather than deployment, representation choices that improve predictive performance may also increase risks of unintended inference. Care should be taken to ensure that such systems are used transparently, with appropriate safeguards, and in ways that respect participant privacy and autonomy.

8 Limitations

Several limitations should be noted. First, our comparison uses off-the-shelf checkpoints. "All-roberta-large-v1" includes additional post-pretraining beyond masked language modeling, involving different data. As such, observed gains cannot be attributed solely to the contrastive objective without compute- and data-matched controls.

Second, we evaluate only two English-language longitudinal datasets, including one relatively small sample (N=120). Results may not generalize to other populations, languages, platforms (e.g., clinical notes or social media), or measurement settings.

Third, our evaluation focuses on predictive accuracy (Pearson's r) and does not assess calibration, fairness, or error disparities across demographic groups, which are important considerations for assessment contexts.

Fourth, though this dataset contains longitudinal data, we chose to measure cross sectional prediction accuracy for simplicity and ease of comparison between the datasets. We leave studying longitudinal models of psychological constructs to future work.

Finally, this study evaluates methodological differences rather than real-world deployment. Improvements in predictive performance do not imply clinical validity or suitability for high-stakes decision-making.

References

Saeed S Alahmari, Lawrence Hall, Peter R Mouton, and Dmitry Goldgof. 2025. Large language models robustness against perturbation: S. alahmari et al. *Scientific Reports*.

Tayyaba Azim, Loitongbam Gyanendro Singh, and Stuart E Middleton. 2022. Detecting moments of change and suicidal risks in longitudinal user texts using multi-task learning. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 213–218.

Anne H Berman, Hans Bergman, Tom Palmstierna, and Frans Schlyter. 2004. Evaluation of the drug use disorders identification test (dudit) in criminal justice and detoxification settings and in a swedish population sample. *European addiction research*, 11(1):22–31.

Sheldon Cohen, Tom Kamarck, and Robin Mermelstein. 1983. A global measure of perceived stress. *Journal of health and social behavior*, pages 385–396.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1 (long and short papers)*, pages 4171–4186.

ED Diener, Robert A Emmons, Randy J Larsen, and Sharon Griffin. 1985. The satisfaction with life scale. *Journal of personality assessment*, 49(1):71–75.

Kawin Ethayarajh. 2019. How contextual are contextualized word representations? Comparing the geometry of BERT, ELMo, and GPT-2 embeddings. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 55–65, Hong Kong, China. Association for Computational Linguistics.

Tianyu Gao, Xingcheng Yao, and Danqi Chen. 2021. SimCSE: Simple contrastive learning of sentence embeddings. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 6894–6910, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Muskan Garg. 2023. Mental health analysis in social media posts: a survey. *Archives of Computational Methods in Engineering*, 30(3):1819.

Zhuojun Gu, Katarina Kjell, H Andrew Schwartz, and Oscar Kjell. 2025. Natural language response formats for assessing depression and worry with large language models: A sequential evaluation with model pre-registration. *Assessment*, page 10731911251364022.

Zhijun Guo, Alvina Lai, Johan H Thygesen, Joseph Farrington, Thomas Keen, Kezhi Li, and 1 others. 2024. Large language models for mental health applications: systematic review. *JMIR mental health*, 11(1):e57400.

Hugging Face. 2025. sentence-transformers/all-roberta-large-v1. https://huggingface.co/sentence-transformers/all-roberta-large-v1. Accessed: 2026-01-??

Ganesh Jawahar, Benoît Sagot, and Djamé Seddah. 2019. What does bert learn about the structure of language? In *ACL 2019-57th Annual Meeting of the Association for Computational Linguistics*.

Euna Jung, Jungwon Park, Jaekeol Choi, Sungyoon Kim, and Wonjong Rhee. 2023. Isotropic representation can improve dense retrieval. In *Pacific-Asia Conference on Knowledge Discovery and Data Mining*, pages 125–137. Springer.

Oscar Kjell, Salvatore Giorgi, and H Andrew Schwartz. 2023. The text-package: An r-package for analyzing and visualizing human language using natural language processing and transformers. *Psychological methods*, 28(6):1478.

Oscar NE Kjell, D Daukantaitė, Kate Hefferon, and Sverker Sikström. 2016. The harmony in life scale complements the satisfaction with life scale: Expanding the conceptualization of the cognitive component of subjective well-being. *Social Indicators Research*, 126(2):893–919.

Kurt Kroenke, Robert L Spitzer, and Janet BW Williams. 2001. The phq-9: validity of a brief depression severity measure. *Journal of general internal medicine*, 16(9):606–613.

Nelson F Liu, Matt Gardner, Yonatan Belinkov, Matthew E Peters, and Noah A Smith. 2019a. Linguistic knowledge and transferability of contextual representations. *arXiv preprint arXiv:1903.08855*.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019b. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*.

Arturo Montejo-Raez, M Dolores Molina-Gonzalez, Salud Maria Jimenez-Zafra, Miguel Angel Garcia-Cumbreras, and Luis Joaquin Garcia-Lopez. 2024. A survey on detecting mental disorders with natural language processing: Literature review, trends and challenges. *Computer Science Review*, 53:100654.

August Håkan Nilsson, Hansen Andrew Schwartz, Richard N Rosenthal, James R McKay, Huy Vu, Young-Min Cho, Syeda Mahwish, Adithya V Ganesan, and Lyle Ungar. 2024. Language-based ema assessments help understand problematic alcohol consumption. *Plos one*, 19(3):e0298300.

Bayode Ogunleye, Hemlata Sharma, and Olamilekan Shobayo. 2024. Sentiment informed sentence bert-ensemble algorithm for depression detection. *Big Data and Cognitive Computing*, 8(9):112.

Alireza Pourkeyvan, Ramin Safa, and Ali Sorourkhah. 2024. Harnessing the power of hugging face transformers for predicting mental health disorders in social networks. *IEEE Access*, 12:28025–28035.

Nils Reimers and Iryna Gurevych. 2019. Sentence-bert: Sentence embeddings using siamese bert-networks. *arXiv preprint arXiv:1908.10084*.

Nancy A Remington, Leandre R Fabrigar, and Penny S Visser. 2000. Reexamining the circumplex model of affect. *Journal of personality and social psychology*, 79(2):286.

Anna Rogers, Olga Kovaleva, and Anna Rumshisky. 2020. A primer in bertology: What we know about how bert works. *Transactions of the association for computational linguistics*, 8:842–866.

John B Saunders, Olaf G Aasland, Thomas F Babor, Juan R De la Fuente, and Marcus Grant. 1993. Development of the alcohol use disorders identification test (audit): Who collaborative project on early detection of persons with harmful alcohol consumption-ii. *Addiction*, 88(6):791–804.

Khushboo Singh, Vasudha Varadarajan, Adithya V Ganesan, August Håkan Nilsson, Nikita Soni, Syeda Mahwish, Pranav Chitale, Ryan L Boyd, Lyle Ungar, Richard N Rosenthal, and 1 others. 2025. Systematic evaluation of auto-encoding and large language model representations for capturing author states and traits. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 18955–18973.

Christopher J Soto and Oliver P John. 2017. The next big five inventory (bfi-2): Developing and assessing a hierarchical model with 15 facets to enhance bandwidth, fidelity, and predictive power. *Journal of personality and social psychology*, 113(1):117.

Robert L Spitzer, Kurt Kroenke, Janet BW Williams, and Bernd Löwe. 2006. A brief measure for assessing generalized anxiety disorder: the gad-7. *Archives of internal medicine*, 166(10):1092–1097.

Martin H Teicher and Angelika Parigger. 2015. The 'maltreatment and abuse chronology of exposure'(mace) scale for the retrospective assessment of abuse and neglect during development. *PLoS one*, 10(2):e0117423.

Ian Tenney, Dipanjan Das, and Ellie Pavlick. 2019. Bert rediscovers the classical nlp pipeline. *arXiv preprint arXiv:1905.05950*.

Edmund R Thompson. 2007. Development and validation of an internationally reliable short-form of the positive and negative affect schedule (panas). *Journal of cross-cultural psychology*, 38(2):227–242.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, and 1 others. 2022. Overview of the clpsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198.

Talia Tseriotou, Jenny Chim, Ayal Klein, Aya Shamir, Guy Dvir, Iqra Ali, Cian Kennedy, Guneet Singh Kohli, Anthony Hills, Ayah Zirikly, and 1 others. 2025. Overview of the clpsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 193–217.

T Bedirhan Üstün. 2010. *Measuring health and disability: Manual for WHO disability assessment schedule WHODAS 2.0*. World Health Organization.

Vasudha Varadarajan, Allison Lahnala, Sujeeth Vankudari, Akshay Raghavan, Scott Feltman, Syeda Mahwish, Camilo Ruggero, Roman Kotov, and H Andrew Schwartz. 2025. Linking language-based distortion detection to mental health outcomes. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 62–68.

David Watson, Michael W O'Hara, Leonard J Simms, Roman Kotov, Michael Chmielewski, Elizabeth A McDade-Montez, Wakiza Gamez, and Scott Stuart. 2007. Development and validation of the inventory of depression and anxiety symptoms (idas). *Psychological assessment*, 19(3):253.

Tianlin Zhang, Annika M Schoene, Shaoxiong Ji, and Sophia Ananiadou. 2022. Natural language processing applied to mental illness detection: a narrative review. *NPJ digital medicine*, 5(1):46.

Ayah Zirikly, Philip Resnik, Ozlem Uzuner, and Kristy Hollingshead. 2019. Clpsych 2019 shared task: Predicting the degree of suicide risk in reddit posts. In *Proceedings of the sixth workshop on computational linguistics and clinical psychology*, pages 24–33.

A Appendix

A.1 Full Data Sizes

Table 5 summarizes data from both datasets.

		EMAs	
Dataset	**Statistic**	**Indiv.**	**Concat.**
DS4UD	Avg. EMA per emb.	1	6.9
	Avg. emb. per user	84.9	12.4
	Total embeddings	10,108	1,486
	Total users	120	120
LMHD	Avg. EMA per emb.	1	5.2
	Avg. emb. per user	5.5	1.1
	Total embeddings	7,207	1,391
	Total users	1,307	1,307

Table 5: Descriptive statistics for the DS4UD and LMHD datasets under individual-message and concatenated-message representations.

A.2 Outcome-Level Results by Domain

Table 6 summarizes performance by outcome category.

Model Performance by Outcome Category				
Outcome Category	**Dataset**	**Doc**	**Base**	Δ
Affect	DS4UD	0.502	0.432	.070*
Demographic	DS4UD	0.489	0.429	.061
Drinking behavior	LMHD	0.263	0.182	.081*
Drinking behavior	DS4UD	0.337	0.241	.096**
Mental health	LMHD	0.576	0.566	.010*
Mental health	DS4UD	0.636	0.615	.021
Personality	DS4UD	0.378	0.337	.041*
Overall	LMHD	0.572	0.561	.012*
	DS4UD	0.472	0.416	.055*

Table 6: Document-Tuned vs. Base model performance (Pearson r) by outcome category and dataset. Δ = Document-Tuned $-$ Base $^{*}p < .05$, $^{**}p < .01$.

A.3 Full Outcome-Level Results

Table 7 reports prediction performance for all individual outcomes across both datasets.

Model Performance							
Outcome	**N**	**MAE**			**Pearson r**		
		Doc	**Base**	**Δ**	**Doc**	**Base**	**Δ**
LMHD							
AUDIT	1307	3.63	3.70	$-.07^{*}$	.263	.182	$.081^{*}$
Age	1307	8.62	8.14	.48	.792	.812	$-.020$
DUDIT	1307	1.79	1.78	.01	.181	.156	.025
GAD2	1307	1.12	1.10	.02	.662	.673	$-.011$
GAD	1307	3.05	3.09	$-.04$	.724	.725	$-.001$
HILS	1307	2.87	2.88	$-.01$	.710	.705	.005
HCMental	708	0.83	0.83	.00	.339	.349	$-.011$
HCVisits	1307	1.34	1.33	.01	.357	.321	.036
IDAS_AppGain	1307	2.63	2.64	$-.01$	.300	.291	.009
IDAS_AppLoss	1307	2.08	2.08	.00	.412	.415	$-.004$
IDAS_Dysphoria	1307	5.05	5.04	.01	.752	.753	$-.001$
IDAS_Temper	1307	2.41	2.47	$-.06^{*}$	.573	.542	$.031^{*}$
IDAS_Insomnia	1307	4.55	4.59	$-.04$	.475	.459	.016
IDAS_Lassitude	1307	3.14	3.09	.05	.676	.686	$-.009$
IDAS_Panic	1307	3.24	3.35	$-.11^{*}$	.585	.562	$.022^{*}$
IDAS_SocAnx	1307	3.15	3.13	.02	.610	.614	$-.005$
IDAS_Suic	1307	1.94	1.97	$-.03$	.604	.576	.028
IDAS_Traum	1307	2.31	2.36	$-.05^{*}$	.576	.545	$.031^{*}$
IDAS_WB	1307	4.87	5.01	$-.14^{*}$	.670	.665	$.005^{*}$
MentalSickDays	395	12.56	12.64	$-.08$	.390	.354	.036
PHQ2_sum	1307	0.89	0.90	$-.01$	.712	.705	.007
PHQtot	1307	3.29	3.32	$-.03$	.744	.739	.005
PSS4_sum	1263	2.11	2.11	.00	.692	.688	.004
PSStot	1307	4.87	4.89	$-.02$	.741	.740	.001
SWLStot	1307	3.10	3.14	$-.04$	.683	.676	.007
SickDaysMonth	1307	5.63	5.56	$.07^{*}$	.206	.189	$.018^{*}$
WHODAS	1307	17.47	17.96	$-.49^{*}$	.636	.615	$.021^{*}$
Mean		4.02	4.04	$-.02^{*}$	.572	.561	$.012^{*}$
DS4UD							
affect	120	0.35	0.39	$-.04^{*}$	.799	.752	$.047^{*}$
age	103	5.71	5.95	$-.24$	.500	.425	.074
agreeable	120	1.75	1.76	$-.01$	.455	.393	.063
anxiety	120	2.65	2.70	$-.05$	.582	.568	.014
audit10	103	5.41	5.70	$-.29^{*}$	.318	.130	$.188^{*}$
auditc	120	1.94	2.07	$-.13^{*}$	.310	.214	$.097^{*}$
conscientious	120	2.01	2.10	$-.09^{*}$	.392	.372	$.020^{*}$
craving 1	94	1.21	1.19	.02	.403	.439	$-.036$
depression score	120	3.90	3.81	.09	.600	.601	$-.002$
energy	120	0.24	0.25	$-.01^{*}$	.283	.129	$.154^{*}$
extravert	120	2.64	2.63	.01	.320	.304	.017
gad7 sum	120	3.64	3.65	$-.01$	.610	.567	.042
income	120	2.00	2.01	$-.01$	.479	.432	.048
mace	99	9.26	10.27	-1.01^{*}	.339	.160	$.179^{*}$
neg affect	103	3.03	3.12	$-.09$	.536	.510	.026
neurotic	120	2.00	2.10	$-.10$	.632	.586	.046
openness	120	2.23	2.23	.00	.089	.030	.059
phq9	120	3.72	3.77	$-.05$	.601	.594	.007
pos affect	103	3.21	3.38	$-.17^{*}$	.389	.335	$.054^{*}$
pss nerv. stress agr.	92	0.57	0.62	$-.05^{*}$	.784	.722	$.061^{*}$
pss	120	1.66	1.67	$-.01$	.639	.635	.004
unhealthy drinking	120	1.28	1.31	$-.03$	.314	.264	.050
Mean		2.75	2.85	$-.10^{*}$	.472	.416	$.055^{*}$

Table 7: Document-tuned vs. base performance by outcome and dataset. MAE = Mean Absolute Error (lower is better); Pearson r (higher is better). Δ = Document-tuned $-$ Base. $^{*}p < .05$, $^{**}p < .01$ (significances from t-test with MAE).

Exploration of Perceptual Speech Features for Clinical Decision-Support in Mental Health Care

Vassilis Lyberatos[1,2], Edmund G. Dervakos[2], Eleni Adamidi[2]
Athanasios Voulodimos[1], Giorgos Stamou[1]

[1]National Technical University of Athens, Athens, Greece
[2]PsychNow
vaslyb@ails.ece.ntua.gr
eddie@psychnow.com

Abstract

Speech and language technologies offer valuable opportunities for supporting mental health assessment through objective and interpretable cues. We present a systematic feature-based analysis framework leveraging perceptually grounded acoustic and linguistic characteristics, including prosody, vocal quality, semantic coherence, syntactic structure, and sarcasm. Using statistical analysis and interpretable machine learning (XGBoost with SHAP and LIME), we examine associations between speech features and validated symptom measures of depression, anxiety, and ADHD. Evaluated on both controlled benchmark datasets (StressID, DAIC-WOZ, Androids, EATD) and a real-world clinical dataset, the framework reveals stable and consistent relationships between symptom severity and vocal irregularities (e.g., shimmer, jitter), lexical-syntactic patterns, and affective tone. An ablation study conducted across all datasets further identifies the most informative feature groups. This work explores a transparent and clinically interpretable approach to speech-based mental health analysis.

1 Introduction

Mental health disorders represent a major global health burden, affecting nearly 970 million people worldwide in 2019 and accounting for approximately 16% of global years lived with disability (YLDs), which makes them one of the leading causes of disability worldwide (Vos et al., 2020). Traditional screening and intake approaches rely heavily on subjective evaluations, including clinical interviews and self-reported symptoms, which are time-consuming and vulnerable to clinician bias, recall bias, and stigma-driven underreporting. In this context, there is a pressing need not for diagnostic tools in the narrow sense, but for clinically supportive technologies that provide objective and interpretable cues without enforcing rigid categorical decisions (Berisha and Liss, 2024). Particularly in the early stages of assessment, tools that function as perceptual and behavioral aids can help clinicians detect patterns, guide conversation, and observe phenotypes while avoiding premature labeling and stigma reinforcement (Kotov et al., 2017).

Speech and language provide a rich, non-invasive source of information for understanding mental health. As natural modes of human expression, they encode cognitive, emotional, and neurological states through acoustic properties (e.g., pitch, prosody, intensity) and linguistic structure (e.g., lexical richness, syntactic complexity) (Cummins et al., 2015, 2018). A growing body of research shows that psychiatric disorders are reflected in distinctive speech and language patterns, including alterations in articulation, semantic coherence, prosody, and syntax, particularly in conditions such as depression, anxiety, schizophrenia, and cognitive impairment (Al Hanai et al., 2018; Arevian et al., 2020).

Recent advances in speech and language technologies have enabled automated analysis for a range of mental health applications. Speech collected in naturalistic settings, including mobile environments, has been used to identify depression, anxiety, insomnia, and fatigue with encouraging accuracy and robustness across populations (Riad et al., 2024). However, many state-of-the-art models function as "black boxes," which limits interpretability and undermines clinician trust. There is growing demand, motivated by both ethical and regulatory considerations, for explainable and interpretable AI systems in healthcare, particularly in high-stakes domains such as mental health assessment (Ng et al., 2024; Holzinger et al., 2019; Doshi-Velez and Kim, 2017).

Perceptually motivated acoustic and linguistic features, such as prosodic, spectral, and lexical-syntactic markers, are inherently interpretable and grounded in well-established clinical phenomena

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 188–207
July 4, 2026 ©2026 Association for Computational Linguistics

(Tasnim et al., 2022; Voleti et al., 2019; Jiao et al., 2017; Tu et al., 2017; Premananth et al., 2025; Neumann et al., 2025). Models that rely on these features are typically more transparent and accessible to clinicians. Such features can be obtained through standard signal processing, extracted using auxiliary deep neural networks (Jiao et al., 2017; Tu et al., 2017), or learned directly in end-to-end architectures (Leschly et al., 2025; Korzekwa et al., 2019; Xu et al., 2023). When combined with interpretable classifiers or post-hoc explanation methods such as attribution analyses, perceptual feature pipelines offer clear insight into which speech characteristics drive model predictions. This approach improves accountability and supports clinical decision-making by providing human-understandable evidence that aligns with expert knowledge. Consequently, perceptual feature-based explainable AI frameworks are a promising strategy for bridging complex machine learning models and practical mental health assessment (Ntalampiras, 2025; Menne et al., 2024).

In this work, we explore the development of transparent and clinically meaningful speech and language analysis methods for mental health assessment. We present a systematic, interpretable framework that combines perceptually grounded acoustic and linguistic features with feature-based modeling and explainable AI techniques (Guidotti et al., 2018). To evaluate the robustness and generalizability of the proposed approach, we conduct experiments on five speech datasets spanning controlled laboratory stress elicitation, semi-structured clinical interviews, multilingual public depression corpora, and real-world digital mental health assessments. Across datasets, the framework is applied consistently to binary classification tasks involving stress, depression, anxiety, and attention-related difficulties. In addition, we perform statistical analyses and ablation studies on feature aggregation and representation strategies to assess the stability and interpretability of the extracted speech markers. By examining speech characteristics across diverse recording conditions, languages, and clinical contexts, this work explores a clinically grounded approach that links perceptual feature design with explainable modeling, contributing to more transparent and interpretable speech-based technologies for mental health.

2 Methodology

Our guiding principle in designing the experimental methodology was to prioritize the extraction of clinically interpretable features by leveraging reliable tools. In line with prior work on clinical applications of voice analysis (Jiao et al., 2017; Riad et al., 2024; Donnelly et al., 2024), we adopted feature extraction strategies that draw upon multiple disciplines, including natural language processing, signal processing, and auxiliary deep neural models. As a next step, we applied traditional statistical and machine learning analyses, further enhanced with post-hoc explainable AI (XAI) techniques (Guidotti et al., 2018), in order to improve the interpretability of our results and analysis.

2.1 Feature Extraction

Clinical psychopathology can be detected from speech based not only on what is said, but also on how it is said (Aloshban et al., 2022). In our approach, we incorporate both modalities, audio and language, into the analysis. Accordingly, our feature extraction methods can be divided into two categories: acoustic features and linguistic features. A list of all extracted features is provided in Table 5 in Appendix D.

2.1.1 Acoustic Features

For the audio analysis, we used Parselmouth (Jadoul et al., 2018), which enables Praat 's (Boersma and Weenink, 2021) validated acoustic analyses directly within python. Acoustic features were extracted from voiced segments and included pitch statistics, intensity, jitter, shimmer, harmonic-to-noise ratio (HNR), zero-crossing rate (ZCR), pauses, phonation and articulation rates, rhythm (pairwise variability index), and speech entropy. Prior to analysis, waveforms were converted to mono, resampled to 16 kHz, and normalized in amplitude to ensure comparability across recordings. Beyond low-level acoustics, we extracted higher-level paralinguistic and linguistic representations using pretrained neural models. Emotion-related features were obtained with a HuBERT-based speech emotion recognition model [1] (Yang et al., 2021), fine-tuned on the IEMOCAP corpus (Busso et al., 2008). The extracted acoustic descriptors are organized into three interpretable groups: prosodic/fluency

[1] https://huggingface.co/superb/hubert-base-superb-er

features (e.g., pitch and intensity statistics, pause measures, phonation and articulation rates, and rhythm/variability indices), voice quality features (e.g., jitter, shimmer, and harmonic-to-noise ratio), and psycholinguistic (auxiliary emotion and sarcasm estimates).

These representations have also been studied in prior clinical work. Prosodic reductions such as flatter pitch range/variability and increased pausing are commonly associated with monotone speech, depression, and blunted affect, while elevated variability may reflect agitation or manic states (Alpert et al., 2001; Low et al., 2020). Voice quality perturbations have been linked to psychopathology in prior work, with shimmer in particular reported as a correlate of depression severity in some settings (Ettore et al., 2022; Hönig et al., 2014). Finally, sarcasm and related pragmatic indicators have been associated with increased risk of anxiety, stress, and depression (Dionigi et al., 2023; Gross and Jazaieri, 2014; Pope et al., 1970).

2.1.2 Linguistic Features

Linguistic features were extracted from transcripts using spaCy (Honnibal et al., 2020) and Stanza (Qi et al., 2020), providing tokenization, POS tagging, lemmatization, dependency parsing, and constituency trees. From these annotations, we derived lexical indices (type-token ratio, MATTR, Brunet's index, Honore's statistic, lemma diversity, and morphological richness), syntactic measures (mean sentence length, clause ratio, syntactic and constituency depth, and passive voice ratio), and graph-based discourse metrics (connectivity, loops, density, diameter, and path statistics). Psycholinguistic information was obtained using VADER sentiment analysis (Hutto and Gilbert, 2014), capturing positive, neutral, and negative valence. This set of descriptors captures lexical diversity, morphosyntactic complexity, discourse organization, and affective tone. To further capture semantic information, pretrained neural models were integrated, with sentence-level embeddings obtained using Sentence-BERT [2] (Reimers and Gurevych, 2019), enabling estimation of discourse coherence, cohesion, and repetition patterns. The resulting linguistic descriptors are organized into four interpretable groups: lexical features (e.g., word/sentence counts, lexical diversity indices such as TTR/MATTR/Brunet/Honoré, content–function and pronoun ratios, and morphology/POS diversity), syntactic features (e.g., sentence/clause lengths, dependency and constituency depth, passive voice usage, and graph-based measures of discourse structure and repetition), semantic features (e.g., first-/second-order coherence and repetition/cohesion measures), and psycholinguistic features capturing affective tone and pragmatics, including sentiment and sarcasm.

These groupings are motivated by prior clinical findings: reduced lexical richness and shifts in tense/pronoun usage have been linked to schizophrenia, dementia, and depression, and pronoun patterns may reflect self-focus or social withdrawal (Compton et al., 2023; Pennebaker et al., 2003). Reduced syntactic complexity is commonly associated with cognitive impairment and depression, while increased repetition and disfluency-like patterns have been reported in ADHD (Sung et al., 2020; Engelhardt et al., 2011). At the semantic level, reduced coherence has been associated with disorganized thought and psychosis-related phenomena and has also been observed in ADHD and manic states (Corcoran et al., 2018; Engelhardt et al., 2011). Finally, affective language indicators (e.g., elevated negative sentiment and reduced positive emotion) are associated with mood disorders, while pragmatic cues such as sarcasm can correlate with elevated risk and may track agitation/psychosis-related expression in some settings (Sonnenschein et al., 2018; Dionigi et al., 2023).

2.1.3 Sarcasm

Sarcasm is a subtle communicative cue that conveys implicit emotional and attitudinal meaning beyond literal word content. Since sarcasm has been correlated with depressive symptoms (Dionigi et al., 2023), it provides a relevant paralinguistic marker for our study. To capture this dimension, we trained a multimodal sarcasm detection model on the MUStARD dataset (Castro et al., 2019), achieving an accuracy of approximately 70%. The model integrates linguistic and acoustic information by combining BERT[3] (Devlin et al., 2019) for text and Wav2Vec2[4] (Baevski et al., 2020) for audio, with frozen encoders whose pooled embeddings are projected into a shared space, concate-

[2] https://huggingface.co/sentence-transformers/paraphrase-MiniLM-L6-v2

[3] https://huggingface.co/google-bert/bert-base-uncased

[4] https://huggingface.co/facebook/wav2vec2-base-960h

nated, and passed through a feedforward classifier. Once trained, this auxiliary model was applied to our datasets to infer sarcasm probabilities, which were then included as additional features alongside acoustic, linguistic, and emotional representations to enrich our analysis. This procedure yielded a total of 82 scalar, interpretable features.

2.2 Analytical Framework

The analytical framework was designed to explore statistical and structural relationships between psychopathology and speech features in an exploratory manner. We combined inferential statistics with interpretable machine learning and explainability techniques, an integration that, to our knowledge, remains relatively uncommon in this area, to examine associations across datasets.

Group-level comparisons were first conducted using independent samples t-tests to assess significant differences in perceptual and paralinguistic features between participant subgroups defined by clinical thresholds on PHQ-9, GAD-7, and ASRS scores. To control for multiple comparisons, resulting p-values were adjusted using the false discovery rate (FDR) correction according to the Benjamini-Hochberg procedure. These tests provided an initial understanding of feature distributions and effect directions underlying symptom-related variation.

To capture higher-order and nonlinear dependencies, we employed XGBoost (Chen and Guestrin, 2016) classifiers as analytical models linking voice features to mental health categories. XGBoost was selected due to its strong performance on tabular data and its compatibility with transparent, feature-level interpretability. The internal structure of these models was examined through feature importance rankings and post-hoc explainability analyses using SHAP (Lundberg and Lee, 2017) and LIME (Ribeiro et al., 2016). LIME explanations were aggregated across all instances to derive cumulative patterns of feature influence, enabling a global interpretation of localized explanations. Complementarily, SHAP summary plots were employed to visualize the overall distribution, magnitude, and direction of feature effects. Together, these analyses indicated correlations and interaction patterns between prosodic, spectral, and temporal features and psychopathological dimensions.

In addition, we conducted an ablation study to identify the most informative groups of features, using the feature groupings defined in the Section 2.1. By systematically training models with individual feature groups isolated, we assessed the relative contribution of acoustic, prosodic, spectral, and linguistic feature sets to the observed associations with psychopathology. This analysis provided further insight into which categories of features drive the explanatory power of the framework.

Overall, this framework follows an explanatory modeling approach in which both statistical tests and interpretable machine learning are used to identify and validate relationships between acoustic patterns and mental health indicators, providing analytical insight rather than purely predictive outcomes.

3 Experiments

We conducted experiments on five speech datasets spanning controlled laboratory conditions, semi-structured clinical interviews, multilingual public corpora, and real-world digital mental health assessments. Across all datasets, we applied the proposed feature extraction pipeline to extract acoustic and linguistic descriptors from speech and examined their relationship to clinically meaningful labels and screening instruments. Depending on the dataset, the experimental task was formulated as binary classification, including stress recognition and the detection of depression, anxiety, and attention-related difficulties. Statistical analysis and explainable machine learning methods were used to support robust evaluation and interpretable feature attribution.

3.1 Datasets

As a primary benchmark, we used the StressID dataset (Chaptoukaev et al., 2023), a multimodal corpus designed for stress identification. StressID includes synchronized audio, facial video, and physiological recordings (ECG, EDA, respiration) from 65 participants performing 11 stress-inducing and neutral tasks. The dataset contains over 39 hours of annotated data, with self-reported measures of stress, relaxation, arousal, and valence. In this study, we used only the audio modality and formulated a binary classification task distinguishing stressed from non-stressed speech.

To assess depression detection in structured clinical interviews, we used the DAIC-WOZ corpus (Gratch et al., 2014), a subset of the Distress Analysis Interview Corpus. It consists of semi-structured interviews conducted by a virtual agent using a Wizard-of-Oz framework, and includes synchronized audio, video, transcripts, and validated

PHQ-8 depression scores. We extracted participant speech only and performed binary depression classification based on standard PHQ-8 thresholds.

We further evaluated our approach on the ANDROIDS corpus (Tao et al., 2023), a clinically validated Italian-language dataset comprising speech recordings from 118 participants, including individuals diagnosed with depression and healthy controls. The dataset contains both read and spontaneous speech collected in real clinical environments, with expert diagnostic labels. In our experiments, we used the audio recordings to perform binary depression classification.

To examine cross-linguistic generalization, we employed the EATD corpus (Shen et al., 2022), the first publicly available Chinese-language dataset for depression detection. EATD includes audio recordings and transcripts from 162 participants who completed standardized self-report assessments using the Self-Rating Depression Scale (SDS). Participants responded to emotionally eliciting prompts, and we used the speech recordings to define a binary depression classification task based on SDS score thresholds.

Finally, we used a proprietary real-world dataset collected through a digital mental health platform, comprising approximately 200 participants who completed a 30-minute self-report questionnaire and provided spoken responses, as part of psychiatric intake. The dataset includes audio recordings and standardized clinical screening scores for depression (PHQ-9), anxiety (GAD-7), and attention-deficit/hyperactivity disorder (ASRS). We analyzed speech features in relation to these clinical scores to evaluate the generalizability of our approach in real-world conditions. The dataset is balanced across diagnostic categories and participant sex. All participants provided informed consent, and all data were de-identified prior to analysis.

3.2 Results

Results are reported across five datasets (STRESSID, DAIC-WOZ, ANDROIDS, EATD, and REAL), spanning multiple clinical conditions, languages, and recording contexts. All experiments were formulated as binary classification tasks using dataset-specific labels or clinically validated questionnaire cutoffs.

The analyses focus on predictive performance using interpretable models, feature-group ablation to assess the contribution of predefined acoustic and linguistic representations, group-level statistical differences, and feature-level interpretability using SHAP, LIME, and partial dependence analysis. Additional results are provided in the Appendix F.



Figure 1: Average AUC-ROC across datasets for XGBoost models trained with only one feature group at a time.

3.2.1 Feature Group Ablation

An ablation study evaluated every predefined feature groups within each dataset. For each combination, a summary AUC-ROC was computed from cross-validation. Figure 1 reports the mean single-group AUC-ROC across datasets for each feature group in isolation. Prosodic features show the highest standalone average performance, followed by psycholinguistic language and acoustic groups. Syntactic, semantic, and lexical groups are intermediate, while voice-quality features are weakest alone. This cross-dataset summary suggests that no single group is sufficient, motivating the use of complementary feature combinations.

3.2.2 StressID

In the STRESSID dataset, we used the labels corresponding to the stress and non-stress conditions, with the dataset being balanced. In the original study (Chaptoukaev et al., 2023), which employed a large pretrained Wav2Vec model followed by a logistic regression classifier, an average accuracy of 0.66 (variance = 0.03) and an F1-score of 0.70 (variance = 0.02) were reported. In our approach, using perceptual features combined with an XGBoost classifier, we achieved a higher average accuracy of 0.70 (variance = 0.01) and an F1-score of 0.81 (variance = 0.01). These results are based on 10 random runs, consistent with the evaluation procedure described in the original paper.

Table 1 presents the features that differ significantly between the two groups after FDR correction, highlighting associations with emotional expression, speech quality, and the duration of voiced segments. To analyze the XGBoost model results described in Section 2.2, we visualized feature im-

Feature	Non-Stressed	Stressed	p-value
Shimmer_local	0.343	-0.142	1.27×10^{-5}
Jitter_local	0.368	-0.152	4.14×10^{-4}
emotion_hap	-0.238	0.098	5.42×10^{-3}
emotion_sad	0.220	-0.091	1.08×10^{-2}
loops_L1_per_word	-0.156	0.065	1.64×10^{-2}
vader_positive	0.211	-0.087	2.54×10^{-2}
vader_compound	0.178	-0.073	2.95×10^{-2}
Number=Plur	0.186	-0.077	3.80×10^{-2}
pause_count	-0.147	0.061	4.10×10^{-2}
pause_short	-0.147	0.061	4.12×10^{-2}
F0_mean	-0.151	0.063	4.29×10^{-2}

Table 1: Mean feature values for Non-Stressed and Stressed groups (STRESSID), with corresponding p-values from two-sample t-tests ($p < 0.05$).

portance based on gain, plotted SHAP values, and examined the aggregated local explanations obtained from LIME. Figure 2 illustrates the top 10 most important features. Features related to syntax, lexical properties, and voice quality consistently emerged as the most influential across interpretability methods, with voice quality features showing the strongest overall contribution.

3.2.3 DAIC-WOZ

Binary depression classification was performed using participant speech, with subject-level acoustic and linguistic features aggregated using robust statistics and modeled with XGBoost. Classification performance was moderate (accuracy = 0.66, F1-score = 0.56, AUC-ROC = 0.63), compared with an LSTM model with an F1-score of 0.64 (Arioz et al., 2022). Statistical analysis indicated that depressed participants exhibited higher pause frequency and larger pause-to-speech ratios, reflecting reduced fluency. Linguistic differences were limited and did not remain significant after false discovery rate correction. Feature importance analyses using XGBoost, SHAP, and LIME were consistent, identifying pausing behavior, reduced pitch variability, lower vocal intensity, and increased voice quality instability as the most influential predictors.

3.2.4 ANDROIDS

Depression classification was conducted using participant-level acoustic and linguistic features aggregated across speech tasks and modeled with XGBoost. The model achieved strong performance (accuracy = 75.6%, F1-score = 77.1%, AUC-ROC = 87.6%), compared with the LSTM model reported in (Tao et al., 2023), which achieved an F1-score of 0.83. Statistical analysis revealed significant group differences in emotional expression, vocal intensity, pause behavior, and discourse structure. After false discovery rate correction, sadness-related emotion, negative sentiment, reduced intensity, and lower semantic coherence remained significant. Interpretability analyses consistently highlighted emotional polarity, voice quality measures (jitter and shimmer), vocal energy, and discourse coherence as dominant predictors.

3.2.5 EATD

Depression classification was performed using multimodal acoustic and linguistic features and an XGBoost classifier. Model performance was variable (accuracy = 82.1%, F1-score = 53.9%, AUC-ROC = 73.4%), compared with a GRU model reported in (Shen et al., 2022), which achieved an F1-score of 0.71. Statistical group-level differences did not remain significant after false discovery rate correction. Despite this, feature importance analyses consistently identified reduced prosodic variability, lower articulation rate, and sadness-related emotional cues as relevant predictors.

3.2.6 Real dataset

For the REAL dataset, we converted the PHQ-9, GAD-7, and ASRS scores into binary classification tasks using clinically established thresholds: a PHQ-9 score of 15 or higher was considered indicative of at least moderate depressive symptoms, a GAD-7 score of 10 or higher indicated at least moderate anxiety symptoms, and an ASRS score of 13 or higher was considered indicative of clinically relevant ADHD symptoms. This binarization aimed to reduce variability in interpretation of self-reported questionnaire scores and to enhance consistency across participants (van Ballegooijen et al., 2016). Using an XGBoost classifier, we achieved AUC-ROC of 0.67 (variance = 0.05) for ASRS, 0.63 (variance = 0.03) for PHQ-9, and 0.59 (variance = 0.02) for GAD-7 under 4-fold, subject-independent cross-validation. All features were first aggregated to the subject level by taking the median across each participant's available audio files, and folds were created on subjects (speaker-disjoint), eliminating any train/test leakage.

Table 2 presents the features distinguishing the depressed and non-depressed groups. After applying FDR correction, the *VADER_negative* feature remained statistically significant, indicating higher levels of negative sentiment and altered emotional



(a) Stress – XGBoost (b) Stress – LIME (c) Stress – SHAP

Figure 2: Top predictive features for the StressID dataset derived from acoustic and linguistic descriptors.

expression in the depressed group. To further validate these findings, we compared the results with those obtained from other methodologies, as shown in Figure 3. This analysis confirmed that emotional, lexical, and syntactic features play a key role in differentiating between the two groups.

Table 3 presents the features that show statistically significant differences for the ASRS-based ADHD recognition; note that only the last four features did not remain significant after FDR correction. The most influential features appear to be those capturing repetition patterns, and the fluency of the speaker. As illustrated in Figure 3, features related to graph-based representations, verb tense variation, emotional expression, and sarcasm detection also played a key role in distinguishing individuals with high ASRS scores, indicative of ADHD. Overall, across all analyses, the frequency of verb tense shifts and graph features capturing repetition consistently emerged as the most important indicators.

Table 4 presents the most significant features identified by the t-tests for distinguishing individuals scoring above the cutoff for moderate anxiety in the GAD-7, with features associated with voice quality and emotional expression emerging as the most influential. However, after applying FDR correction, no features remained statistically significant. As shown in Figure 3, further analysis revealed that graph-based, semantic, voice quality, emotional, and lexical features played key roles in discrimination. Across all methodologies, features related to voice quality and emotional characteristics consistently proved to be the most important indicators of anxiety.

Feature	**Non-ADHD**	**ADHD**	p**-value**
Tense=Pres	6.22	7.81	2.28×10^{-4}
graph_repeated_edges	3.12	4.48	1.75×10^{-4}
graph_diameter	8.71	8.23	3.85×10^{-4}
edges_per_word	0.93	0.92	7.15×10^{-4}
parallel_edges_per_word	0.04	0.05	1.09×10^{-3}
verb_tense_switches	8.54	10.44	2.16×10^{-3}
graph_loops_L3	1.52	1.99	4.15×10^{-3}
max_constituency_depth	13.88	14.83	5.49×10^{-3}
pronoun_ratio	0.15	0.16	5.43×10^{-3}
discourse_cohesion	0.09	0.10	7.75×10^{-3}
filler_count	116.45	136.47	7.74×10^{-3}
emotion_ang	0.06	0.04	8.68×10^{-3}
brunet_index	9.94	10.32	1.60×10^{-2}
clause_ratio	0.73	0.85	2.31×10^{-2}
honore_stat	1572.53	1522.98	4.42×10^{-2}
graph_loops_L2	0.75	0.95	4.52×10^{-2}

Table 3: Mean feature values for Non-ADHD and ADHD groups (ASRS) from the Real dataset, with corresponding p-values from two-sample t-tests ($p < 0.05$).

Feature	**Non-Dep**	**Dep**	p**-value**
vader_negative	0.030	0.050	1.22×10^{-4}
vader_compound	0.652	0.497	4.98×10^{-3}
content_function_ratio	1.333	1.273	9.93×10^{-3}
loops_L1_per_word	0.003	0.001	1.26×10^{-2}
pause_medium	0.295	0.102	1.91×10^{-2}
graph_loops_L1	0.302	0.148	1.77×10^{-2}
MATTR	0.693	0.704	4.78×10^{-2}
emotion_neu	0.198	0.169	4.26×10^{-2}

Table 2: Mean feature values for Non-Depression and Depression groups (PHQ-9) from the Real dataset, with corresponding p-values from two-sample t-tests ($p < 0.05$).

Feature	**Non-Anxiety**	**Anxiety**	p**-value**
vader_negative	0.030	0.041	6.81×10^{-3}
Shimmer_local	0.111	0.103	2.17×10^{-2}

Table 4: Mean feature values for Non-Anxiety and Anxiety groups (GAD-7), with corresponding p-values from two-sample t-tests ($p < 0.05$).



(a) ASRS (b) GAD-7 (c) PHQ-9

Figure 3: SHAP explanations for top predictive features from the REAL dataset for ASRS, GAD-7, and PHQ-9.

4 Discussion

Section 3.2 suggests two key points. First, predicting psychopathology from voice is a challenging task, as also reported in (Berisha and Liss, 2024). Second, there is preliminary evidence that certain features could act as potential indicators across different conditions and clinical cases.

For anxiety and stress, Shimmer was the most prominent feature across both datasets. Shimmer measures cycle-to-cycle amplitude variation in successive glottal cycles, reflecting irregularities in vocal fold vibration. This finding is consistent with prior work (Teferra et al., 2022) and supports the potential of Shimmer as an indicator for anxiety. In our analysis, higher Shimmer values were associated with increased anxiety, in line with Jones et al. (2011), although opposite trends have also been reported (Basar et al., 2023), indicating the need for further validation before clinical use.

For the ADHD-related ASRS score, we found that the most important features were graph-based measures capturing repetition patterns (Mota et al., 2012), as well as verb-tense-related features that quantify how frequently speakers shift between tenses. This aligns with previous literature (Engelhardt et al., 2011), which reports that individuals with ADHD often exhibit higher levels of repetition and disfluency—patterns that our methodology appears capable of capturing as well.

For PHQ-9 based depression, we found that features capturing emotional content from both audio and text played an important role, along with the content-function ratio feature. The content-function ratio measures the balance between meaning-bearing words and grammatical words, indicating how information-dense or syntactically simple a text is. From this observation, we see that our system captures features reflecting both emotional expression (e.g., sadness) and syntactic richness. These findings are consistent with previous work showing that emotional and affective cues in both speech and language serve as reliable indicators of depressive states (Cummins et al., 2015). Likewise, the relevance of the content-function ratio aligns with the linguistic style framework proposed by Pennebaker and King (Pennebaker and King, 1999), where the balance between content and function words reflects cognitive style and syntactic complexity often associated with mood and mental health variations.

These findings highlight the value of an integrative, feature-centered approach to speech-based psychopathology analysis. The work combines foundation-model-based representations with traditional acoustic and linguistic features, classical statistical analysis, and interpretable machine learning across conditions and datasets. We posit that this integrated and exploratory approach is particularly well suited to clinical and interdisciplinary contexts, where transparent indicators are preferred, and may facilitate interpretable insights and hypothesis generation.

5 Conclusion

We introduced an interpretable, perceptually grounded framework for exploring speech-based correlates of psychopathology across heterogeneous datasets, languages, and labeling schemes. Using a compact set of acoustic and linguistic descriptors and transparent models with complementary explanations, we examined feature patterns (prosody/fluency, affect, voice quality, and discourse markers) that appeared to be associated with stress, depression, anxiety, and ADHD-related screening status. Future work should further investigate these candidate indicators under stronger reference standards and in longitudinal, out-of-domain settings.

6 Limitations

Despite promising within-dataset results, applying speech-based models for psychopathology prediction in real-world settings remains difficult. As highlighted by Berisha and Liss (Berisha and Liss, 2024), speech is affected by numerous confounding factors, such as fatigue, and background noise, that obscure condition-specific indicators and reduce model robustness. Differences in recording devices, linguistic and cultural backgrounds, and labeling protocols further introduce domain bias. Although some cross-setting generalization was observed, performance remained sensitive to acoustic variability and contextual shifts. Moreover, short speech samples and static features may overlook temporal cues critical for capturing symptom dynamics. Advancing clinical applicability therefore requires adaptive preprocessing, domain-invariant features, and large datasets that reflect naturalistic conditions. Finally, because several datasets use questionnaire-based cutoffs (including PHQ-8/9, GAD-7, and ASRS), the supervision signal reflects widely used, but imperfect, measurement instruments, and some errors may reflect measurement/cutoff variability rather than model behavior alone. This does not change the goal of the study (interpretability and clinical plausibility), but it does bound how literally one should read classification metrics as reflecting "true" clinical status across datasets. Additionally, neural-based features such as sarcasm detection should be interpreted cautiously, as these models have imperfect accuracy and may reproduce biases present in their training data.

7 Acknowledgment

This work was supported by PsychNow. We thank the clinical and product teams at PsychNow for their support and feedback.

References

Tuka Al Hanai, Mohammad M Ghassemi, and James R Glass. 2018. Detecting depression with audio/text sequence modeling of interviews. In *Interspeech*, pages 1716–1720.

Nujud Aloshban, Anna Esposito, and Alessandro Vinciarelli. 2022. What you say or how you say it? depression detection through joint modeling of linguistic and acoustic aspects of speech. *Cognitive Computation*, 14(5):1585–1598.

Murray Alpert, Enrique R Pouget, and Raul R Silva. 2001. Reflections of depression in acoustic measures of the patient's speech. *Journal of affective disorders*, 66(1):59–69.

Armen C Arevian, Daniel Bone, Nikolaos Malandrakis, Victor R Martinez, Kenneth B Wells, David J Miklowitz, and Shrikanth Narayanan. 2020. Clinical state tracking in serious mental illness through computational analysis of speech. *PLoS one*, 15(1):e0225695.

Umut Arioz, Urška Smrke, Nejc Plohl, and Izidor Mlakar. 2022. Scoping review on the multimodal classification of depression and experimental study on existing multimodal models. *Diagnostics*, 12(11):2683.

Alexei Baevski, Yuhao Zhou, Abdelrahman Mohamed, and Michael Auli. 2020. wav2vec 2.0: A framework for self-supervised learning of speech representations. *Advances in neural information processing systems*, 33:12449–12460.

Gokhan Basar, Ozlem Kaleoglu Aslan, and Mehmet Surmeli. 2023. Relationship between dysphonia and anxiety in fibromyalgia syndrome. *European Archives of Oto-Rhino-Laryngology*, 280(1):285–288.

Visar Berisha and Julie M Liss. 2024. Responsible development of clinical speech ai: Bridging the gap between clinical research and technology. *NPJ digital medicine*, 7(1):208.

Paul Boersma and David Weenink. 2021. Praat: doing phonetics by computer [Computer program]. Version 6.1.38, retrieved 2 January 2021 http://www.praat.org/.

Carlos Busso, Murtaza Bulut, Chi-Chun Lee, Abe Kazemzadeh, Emily Mower, Samuel Kim, Jeannette N Chang, Sungbok Lee, and Shrikanth S Narayanan. 2008. Iemocap: Interactive emotional dyadic motion capture database. *Language resources and evaluation*, 42(4):335–359.

Santiago Castro, Devamanyu Hazarika, Verónica Pérez-Rosas, Roger Zimmermann, Rada Mihalcea, and Soujanya Poria. 2019. Towards multimodal sarcasm detection (an _Obviously_ perfect paper). In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 4619–4629, Florence, Italy. Association for Computational Linguistics.

Hava Chaptoukaev, Valeriya Strizhkova, Michele Panariello, Bianca Dalpaos, Aglind Reka, Valeria Manera, Susanne Thümmler, Esma ISMAILOVA, Nicholas W., francois bremond, Massimiliano Todisco, Maria A Zuluaga, and Laura M. Ferrari. 2023. Stressid: a multimodal dataset for stress identification. In *Advances in Neural Information Processing Systems*, volume 36, pages 29798–29811. Curran Associates, Inc.

Tianqi Chen and Carlos Guestrin. 2016. Xgboost: A scalable tree boosting system. In *Proceedings of the 22nd acm sigkdd international conference on knowledge discovery and data mining*, pages 785–794.

Michael T Compton, Benson S Ku, Michael A Covington, Celia Metzger, and Anya Hogoboom. 2023. Lexical diversity and other linguistic measures in schizophrenia: associations with negative symptoms and neurocognitive performance. *The Journal of nervous and mental disease*, 211(8):613–620.

Cheryl M Corcoran, Facundo Carrillo, Diego Fernández-Slezak, Gillinder Bedi, Casimir Klim, Daniel C Javitt, Carrie E Bearden, and Guillermo A Cecchi. 2018. Prediction of psychosis across protocols and risk cohorts using automated language analysis. *World Psychiatry*, 17(1):67–75.

Nicholas Cummins, Alice Baird, and Bjoern W Schuller. 2018. Speech analysis for health: Current state-of-the-art and the increasing impact of deep learning. *Methods*, 151:41–54.

Nicholas Cummins, Stefan Scherer, Jarek Krajewski, Sebastian Schnieder, Julien Epps, and Thomas F Quatieri. 2015. A review of depression and suicide risk assessment using speech analysis. *Speech communication*, 71:10–49.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1*, pages 4171–4186.

Alberto Dionigi, Mirko Duradoni, and Laura Vagnoli. 2023. Understanding the association between humor and emotional distress: The role of light and dark humor in predicting depression, anxiety, and stress. *Europe's Journal of Psychology*, 19(4):358.

Jon Donnelly, Luke Moffett, Alina Jade Barnett, Hari Trivedi, Fides Schwartz, Joseph Lo, and Cynthia Rudin. 2024. Asymmirai: interpretable mammography-based deep learning model for 1–5-year breast cancer risk prediction. *Radiology*, 310(3):e232780.

Finale Doshi-Velez and Been Kim. 2017. Towards a rigorous science of interpretable machine learning. *arXiv preprint arXiv:1702.08608*.

Paul E Engelhardt, Fernanda Ferreira, and Joel T Nigg. 2011. Language production strategies and disfluencies in multi-clause network descriptions: a study of adult attention-deficit/hyperactivity disorder. *Neuropsychology*, 25(4):442.

Eric Ettore, Philipp Müller, Jonas Hinze, Michel Benoit, Bruno Giordana, Danilo Postin, Amandine Lecomte, Hali Lindsay, P. Robert, and Alexandra König. 2022. Digital phenotyping for differential diagnosis of major depressive episode: A narrative review (preprint). *JMIR Mental Health*, 10.

Jonathan Gratch, Ron Artstein, Gale Lucas, Giota Stratou, Stefan Scherer, Angela Nazarian, Rachel Wood, Jill Boberg, David DeVault, Stacy Marsella, David Traum, Skip Rizzo, and Louis-Philippe Morency. 2014. The distress analysis interview corpus of human and computer interviews. In *Proceedings of the Ninth International Conference on Language Resources and Evaluation (LREC'14)*, pages 3123–3128, Reykjavik, Iceland. European Language Resources Association (ELRA).

James J Gross and Hooria Jazaieri. 2014. Emotion, emotion regulation, and psychopathology: An affective science perspective. *Clinical psychological science*, 2(4):387–401.

Riccardo Guidotti, Anna Monreale, Salvatore Ruggieri, Franco Turini, Fosca Giannotti, and Dino Pedreschi. 2018. A survey of methods for explaining black box models. *ACM computing surveys (CSUR)*, 51(5):1–42.

Andreas Holzinger, Georg Langs, Helmut Denk, Kurt Zatloukal, and Heimo Müller. 2019. Causability and explainability of artificial intelligence in medicine. *Wiley interdisciplinary reviews: data mining and knowledge discovery*, 9(4):e1312.

Matthew Honnibal, Ines Montani, Sofie Van Landeghem, Adriane Boyd, and 1 others. 2020. spacy: Industrial-strength natural language processing in python.

Clayton Hutto and Eric Gilbert. 2014. Vader: A parsimonious rule-based model for sentiment analysis of social media text. In *Proceedings of the international AAAI conference on web and social media*, volume 8, pages 216–225.

Florian Hönig, Anton Batliner, Elmar Nöth, Sebastian Schnieder, and Jarek Krajewski. 2014. Automatic modelling of depressed speech: relevant features and relevance of gender. In *Interspeech 2014*, pages 1248–1252.

Yannick Jadoul, Bill Thompson, and Bart de Boer. 2018. Introducing Parselmouth: A Python interface to Praat. *Journal of Phonetics*, 71:1–15.

Yishan Jiao, Visar Berisha, and Julie Liss. 2017. Interpretable phonological features for clinical applications. In *2017 ieee international conference on acoustics, speech and signal processing (icassp)*, pages 5045–5049. IEEE.

Mark Jones, Flora Anagnostou, and Jo Verhoeven. 2011. The vocal expression of emotion: An acoustic analysis of anxiety. In *ICPhS*, pages 982–985.

Daniel Korzekwa, Roberto Barra-Chicote, Bozena Kostek, Thomas Drugman, and Mateusz Lajszczak. 2019. Interpretable Deep Learning Model for the

Detection and Reconstruction of Dysarthric Speech. In *Interspeech 2019*, pages 3890–3894.

Roman Kotov, Robert Krueger, David Watson, Thomas Achenbach, Robert Althoff, R. Bagby, Timothy Brown, William Carpenter, Avshalom Caspi, Lee Clark, Nicholas Eaton, Miriam Forbes, Kelsie Forbush, David Goldberg, Deborah Hasin, Steven Hyman, Masha Ivanova, Donald Lynam, Kristian Markon, and Mark Zimmerman. 2017. The hierarchical taxonomy of psychopathology (hitop): A dimensional alternative to traditional nosologies. *Journal of Abnormal Psychology*, 126:454–477.

Emma CL Leschly, Oliver Roesler, Michael Neumann, Jackson Liscombe, Abhishek Hosamath, Lakshmi Arbatti, Line H Clemmensen, Melanie Ganz, and Vikram Ramanarayanan. 2025. An exploration of interpretable deep learning models for the assessment of mild cognitive impairment. In *Proc. Interspeech 2025*, pages 271–275.

Daniel M Low, Kate H Bentley, and Satrajit S Ghosh. 2020. Automated assessment of psychiatric disorders using speech: A systematic review. *Laryngoscope investigative otolaryngology*, 5(1):96–116.

Scott M Lundberg and Su-In Lee. 2017. A unified approach to interpreting model predictions. *Advances in neural information processing systems*, 30.

Felix Menne, Felix Dörr, Julia Schräder, Johannes Tröger, Ute Habel, Alexandra König, and Lisa Wagels. 2024. The voice of depression: speech features as biomarkers for major depressive disorder. *BMC psychiatry*, 24(1):794.

Natalia B. Mota, Nathaly A. P. Vasconcelos, Nilza Lemos, Ana C. Pieretti, Osame Kinouchi, Guillermo A. Cecchi, Mauro Copelli, and Sidarta Ribeiro. 2012. Speech graphs provide a quantitative measure of thought disorder in psychosis. *PLOS ONE*, 7(4):e34928.

Michael Neumann, Hardik Kothare, Beverly Insel, Anzalee Khan, Danyah Nadim, Jean-Pierre Lindenmayer, and Vikram Ramanarayanan. 2025. Multimodal speech, language and orofacial analysis for remote assessment of positive, negative and cognitive symptoms in schizophrenia. In *Proc. Interspeech 2025*, pages 5703–5707.

Si-Ioi Ng, Lingfeng Xu, Ingo Siegert, Nicholas Cummins, Nina R Benway, Julie Liss, and Visar Berisha. 2024. A tutorial on clinical speech ai development: From data collection to model validation. *arXiv preprint arXiv:2410.21640*.

Stavros Ntalampiras. 2025. Interpretable probabilistic identification of depression in speech. *Sensors*, 25(4):1270.

James W Pennebaker and Laura A King. 1999. Linguistic styles: language use as an individual difference. *Journal of personality and social psychology*, 77(6):1296.

James W Pennebaker, Matthias R Mehl, and Kate G Niederhoffer. 2003. Psychological aspects of natural language use: Our words, our selves. *Annual review of psychology*, 54(1):547–577.

Benjamin Pope, Thomas Blass, Aron W Siegman, and Jack Raher. 1970. Anxiety and depression in speech. *Journal of Consulting and Clinical Psychology*, 35(1p1):128.

Gowtham Premananth, Philip Resnik, Sonia Bansal, Deanna L. Kelly, and Carol Espy-Wilson. 2025. Multimodal Biomarkers for Schizophrenia: Towards Individual Symptom Severity Estimation. In *Interspeech 2025*, pages 3065–3069.

Peng Qi, Yuhao Zhang, Yuhui Zhang, Jason Bolton, and Christopher D Manning. 2020. Stanza: A python natural language processing toolkit for many human languages. In *Proceedings of the 58th annual meeting of the association for computational linguistics: system demonstrations*, pages 101–108.

Nils Reimers and Iryna Gurevych. 2019. Sentence-bert: Sentence embeddings using siamese bert-networks. In *Proceedings of the 2019 conference on empirical methods in natural language processing and the 9th international joint conference on natural language processing (EMNLP-IJCNLP)*, pages 3982–3992.

Rachid Riad, Martin Denais, Marc de Gennes, Adrien Lesage, Vincent Oustric, Xuan Nga Cao, Stéphane Mouchabac, and Alexis Bourla. 2024. Automated speech analysis for risk detection of depression, anxiety, insomnia, and fatigue: algorithm development and validation study. *Journal of Medical Internet Research*, 26:e58572.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. 2016. " why should i trust you?" explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining*, pages 1135–1144.

Ying Shen, Huiyu Yang, and Lin Lin. 2022. Automatic depression detection: An emotional audio-textual corpus and a gru/bilstm-based model. In *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 6247–6251. IEEE.

Anke R Sonnenschein, Stefan G Hofmann, Tobias Ziegelmayer, and Wolfgang Lutz. 2018. Linguistic analysis of patients with mood and anxiety disorders during cognitive behavioral therapy. *Cognitive behaviour therapy*, 47(4):315–327.

Jee Eun Sung, Sujin Choi, Bora Eom, Jae Keun Yoo, and Jee Hyang Jeong. 2020. Syntactic complexity as a linguistic marker to differentiate mild cognitive impairment from normal aging. *Journal of Speech, Language, and Hearing Research*, 63(5):1416–1429.

Fuxiang Tao, Anna Esposito, and Alessandro Vinciarelli. 2023. The Androids Corpus: A New Publicly

Available Benchmark for Speech Based Depression Detection. In *Interspeech 2023*, pages 4149–4153.

Mashrura Tasnim, Malikeh Ehghaghi, Brian Diep, and Jekaterina Novikova. 2022. DEPAC: a corpus for depression and anxiety detection from speech. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 1–16, Seattle, USA. Association for Computational Linguistics.

Bazen Gashaw Teferra, Sophie Borwein, Danielle D DeSouza, William Simpson, Ludovic Rheault, and Jonathan Rose. 2022. Acoustic and linguistic features of impromptu speech and their association with anxiety: validation study. *JMIR mental health*, 9(7):e36828.

Ming Tu, Visar Berisha, and Julie Liss. 2017. Interpretable objective assessment of dysarthric speech based on deep neural networks. In *Interspeech*, pages 1849–1853.

Wouter van Ballegooijen, Heleen Riper, Pim Cuijpers, Patricia van Oppen, and Johannes H Smit. 2016. Validation of online psychometric instruments for common mental health disorders: a systematic review. *BMC psychiatry*, 16(1):45.

Rohit Voleti, Julie M Liss, and Visar Berisha. 2019. A review of automated speech and language features for assessment of cognitive and thought disorders. *IEEE journal of selected topics in signal processing*, 14(2):282–298.

Theo Vos, {Stephen S} Lim, Cristiana Abbafati, {Kaja M} Abbas, Mohammad Abbasi, Mitra Abbasifard, Mohsen Abbasi-Kangevari, Hedayat Abbastabar, Foad Abd-Allah, Ahmed Abdelalim, Mohammad Abdollahi, Ibrahim Abdollahpour, Hassan Abolhassani, Victor Aboyans, {Elissa M} Abrams, {Lucas Guimarães} Abreu, {Michael R M} Abrigo, {Laith Jamal} Abu-Raddad, {Abdelrahman I} Abushouk, and 1011 others. 2020. Global burden of 369 diseases and injuries in 204 countries and territories, 1990–2019: a systematic analysis for the global burden of disease study 2019. *The Lancet*, 396(10258):1204–1222.

Lingfeng Xu, Julie Liss, and Visar Berisha. 2023. Dysarthria detection based on a deep learning model with a clinically-interpretable layer. *JASA Express Letters*, 3(1).

Shu-Wen Yang, Po-Han Chi, Yung-Sung Chuang, Cheng-I Jeff Lai, Kushal Lakhotia, Yist Y. Lin, Andy T. Liu, Jiatong Shi, Xuankai Chang, Guan-Ting Lin, Tzu-Hsien Huang, Wei-Cheng Tseng, Ko tik Lee, Da-Rong Liu, Zili Huang, Shuyan Dong, Shang-Wen Li, Shinji Watanabe, Abdelrahman Mohamed, and Hung yi Lee. 2021. SUPERB: Speech Processing Universal PERformance Benchmark. In *Interspeech 2021*, pages 1194–1198.

A Demographic Data

This section summarizes the demographic and clinical score distributions across the evaluated datasets. Where available, standardized psychometric instruments are used to characterize symptom severity and population variability.

For the REAL dataset, Figure 4 presents distributions of age and self-reported clinical scales. Participant ages span a broad range, with most individuals between their 20s and 50s. ASRS scores show moderate dispersion with a noticeable concentration at higher values, indicating a substantial proportion of participants exhibiting elevated ADHD-related traits. GAD-7 scores are broadly distributed, suggesting balanced representation across anxiety severity levels, while PHQ-9 scores span the full clinical range, with many participants in the moderate to severe depression categories.

For the DAIC-WOZ corpus, Figure 5 illustrates the distribution of PHQ-8 scores obtained during semi-structured clinical interviews. The distribution reflects substantial variability in depressive symptom severity, supporting its use as a benchmark dataset for depression detection from speech.

Figure 6 shows the distribution of SDS scores for the EATD dataset. Most participants fall below the clinical threshold, with a smaller subset exhibiting elevated depression scores, consistent with the dataset's class imbalance and student-based recruitment.

B Feature Distributions

To compare the feature distributions between the *Stress* and REAL datasets, we visualize the normalized histograms for each extracted feature (see Figure 7). Red denotes the Stress dataset, while blue corresponds to REAL. Overall, the majority of features display similar distributional patterns between the *Stress* and REAL datasets. This consistency supports the validity and reliability of our feature extraction procedure, suggesting that the computed features capture comparable underlying characteristics across recording conditions.

C Partial Dependence Plots

Partial Dependence Plots (PDPs) illustrate the marginal effect of individual features on model predictions while averaging over all other variables. By doing so, they reveal whether a given feature has a positive, negative, or non-linear influence on the target outcome. PDPs are particularly informative for complex, non-linear models such as ensemble or deep learning architectures, as they provide interpretable insight into learned feature-outcome relationships.

Figure 8 presents the PDPs for a range of speech-derived features across the *Real* dataset models (ASRS, GAD-7, and PHQ-9). These plots highlight how prosodic, lexical, and semantic attributes contribute to predicting mental health symptom severity.

Figure 9 focuses on the STRESSID model, illustrating the partial dependencies for key linguistic and acoustic predictors. The monotonic and threshold-based trends observed, such as the influence of speech rate, pause duration, and pitch variability, suggest interpretable and physiologically plausible mappings between vocal behavior and stress-related outcomes.

The Partial Dependence Plots for the DAIC-WOZ dataset (Figure 10) show that increased pause duration and reduced pitch variability are associated with higher depression probability. Elevated jitter and shimmer further indicate reduced phonatory stability in depressed speech. Linguistic features such as shorter word length and lower lexical diversity exhibit monotonic trends, reflecting cognitive and expressive slowing.

For the EATD corpus, PDPs (Figure 12) reveal strong non-linear effects, with higher articulation rate and wider pitch range associated with lower depression likelihood. Increased sad emotion activation sharply increases predicted depression probability. Linguistic simplification beyond threshold levels further contributes to elevated risk.

In the ANDROIDS CORPUS, PDPs (Figure 11) indicate that reduced vocal intensity, increased shimmer, and longer pauses correspond to higher depression probability. Emotional polarity features show strong monotonic relationships, with higher sadness and lower positive sentiment increasing risk. Disrupted discourse coherence further amplifies depression predictions across tasks.

D Feature Descriptions

To ensure interpretability and transparency in our modeling pipeline, we provide a detailed description of all extracted acoustic and linguistic features used in our analyses, see Table 5. Each feature is annotated with its extraction method, type, subtype, and psycholinguistic interpretation. These features



Age



ASRS



GAD-7



PHQ-9

Figure 4: Distributions of demographic and clinical variables in the REAL dataset.



Figure 5: Distribution of PHQ-8 depression scores in the DAIC-WOZ dataset.



Figure 6: Distribution of SDS depression scores in the EATD dataset.

encompass prosodic, voice quality, lexical, syntactic, semantic, and psycholinguistic dimensions, thereby capturing both low-level acoustic cues and higher-level cognitive-linguistic markers of mental state.

E Feature Correlation

Figure 13 presents correlation matrices of the extracted acoustic and linguistic features across all evaluated datasets. The matrices illustrate pairwise linear relationships among features, revealing structured intra-group correlations and dataset-specific differences in feature dependence. Variations in correlation strength across datasets reflect differences in recording conditions, task design, and population characteristics, and highlight potential feature redundancy addressed by the modeling approach.

F Additional Results and Cross-Dataset Analysis

This section presents additional results obtained using the proposed analytical framework across multiple clinical and real-world speech datasets,

Feature	Type	Subtype	Calculation / Definition
ZCR	Acoustic	Prosodic	Zero-crossing rate of the normalized voiced waveform.
F0_mean	Acoustic	Prosodic	Mean pitch (Hz) from Praat pitch analysis.
F0_range	Acoustic	Prosodic	Maximum pitch minus minimum pitch.
F0_var	Acoustic	Prosodic	Variance of pitch values across voiced frames.
F0_std	Acoustic	Prosodic	Standard deviation of F0 values.
Intensity_mean	Acoustic	Prosodic	Mean amplitude of the waveform.
Intensity_std	Acoustic	Prosodic	Standard deviation of intensity values.
Jitter_local	Acoustic	Voice Quality	Mean absolute F0 period difference.
Shimmer_local	Acoustic	Voice Quality	Mean absolute amplitude difference.
HNR	Acoustic	Voice Quality	Harmonics-to-noise ratio (Praat Harmonicity).
PVI	Acoustic	Voice Quality	Pairwise variability index across voiced intervals.
filler_count	Linguistic	Voice Quality	Count of filler tokens such as "um", "uh", "erm".
duration	Acoustic	Prosodic	Total length of the audio file (seconds).
Phonation_rate	Acoustic	Prosodic	Number of voiced frames divided by total duration.
pause_count	Acoustic	Prosodic	Count of silent segments below amplitude threshold.
pause_short	Acoustic	Prosodic	Pauses < 1 s.
pause_medium	Acoustic	Prosodic	Pauses $1-2$ s.
pause_long	Acoustic	Prosodic	Pauses > 2 s.
pause_mean	Acoustic	Prosodic	Mean duration of all pauses (s).
pause_speech_ratio	Acoustic	Prosodic	Total pause time divided by total duration.
articulation_rate	Acoustic	Prosodic	Voiced frames / (duration $-$ total pause time).
speech_entropy	Acoustic	Prosodic	Shannon entropy of voiced amplitudes.
emotion_neu	Acoustic	Psycholinguistic	Neutral emotion probability (HuBERT model).
emotion_hap	Acoustic	Psycholinguistic	Happiness probability (HuBERT model).
emotion_ang	Acoustic	Psycholinguistic	Anger probability (HuBERT model).
emotion_sad	Acoustic	Psycholinguistic	Sadness probability (HuBERT model).
word_count	Linguistic	Lexical	Total number of words in transcript.
sentence_count	Linguistic	Lexical	Total number of sentences in transcript.
type_token_ratio	Linguistic	Lexical	Ratio of unique words to total words.
MATTR	Linguistic	Lexical	Moving-average type-token ratio (window=50).
brunet_index	Linguistic	Lexical	$N^{(V^{-0.165})}$ (lexical richness).
honore_stat	Linguistic	Lexical	$100 \log N/(1 - H/V)$ (lexical richness measure).
lexical_density	Linguistic	Lexical	Ratio of content words to total words.
idea_density	Linguistic	Lexical	Ratio of idea-bearing words to total words.
content_function_ratio	Linguistic	Lexical	Ratio of content to function words.
pronoun_ratio	Linguistic	Lexical	Pronouns divided by total words.
Tense_Past	Linguistic	Lexical	Count of past tense verbs.
Tense_Pres	Linguistic	Lexical	Count of present tense verbs.
Voice_Pass	Linguistic	Lexical	Count of passive voice verbs.
Number_Plur	Linguistic	Lexical	Count of plural nouns or verbs.
lemma_ttr	Linguistic	Lexical	Unique lemmas / total lemmas.
upos_diversity	Linguistic	Lexical	Unique UPOS tags / total tokens.
morphological_richness	Linguistic	Lexical	Unique morph features / total words.
propositional_density	Linguistic	Lexical	Ratio of verbs, adj, adv, prep, conj to total words.
mean_sentence_length	Linguistic	Syntactic	Mean words per sentence.
mean_clause_length	Linguistic	Syntactic	Mean number of tokens per clause.
syntactic_depth_mean	Linguistic	Syntactic	Mean dependency tree depth.
syntactic_depth_max	Linguistic	Syntactic	Maximum dependency tree depth.
clause_ratio	Linguistic	Syntactic	Clauses per sentence.
verb_tense_switches	Linguistic	Syntactic	Count of verb tense changes.
verb_tense_switch_ratio	Linguistic	Syntactic	Tense switches / total verbs.
syntactic_embedding_depth	Linguistic	Syntactic	Maximum dependency embedding depth.
passive_voice_ratio	Linguistic	Syntactic	Passive voice verbs / total verbs.
graph_nodes	Linguistic	Syntactic	Number of unique nodes in the speech graph.
graph_edges	Linguistic	Syntactic	Number of total edges in the speech graph.
graph_repeated_edges	Linguistic	Syntactic	Count of edges appearing multiple times.
graph_largest_scc	Linguistic	Syntactic	Size of largest strongly connected component.
graph_density	Linguistic	Syntactic	Ratio of actual to maximum possible edges.
graph_loops_L1	Linguistic	Syntactic	Number of self-loops (1-node cycles).
graph_loops_L2	Linguistic	Syntactic	Number of 2-node cycles.
graph_loops_L3	Linguistic	Syntactic	Number of 3-node cycles.
graph_avg_total_degree	Linguistic	Syntactic	Average in+out degree across nodes.
graph_diameter	Linguistic	Syntactic	Longest shortest path in undirected graph.
graph_avg_shortest_path	Linguistic	Syntactic	Mean shortest path length in graph.
nodes_per_word	Linguistic	Syntactic	graph_nodes / total_words.
edges_per_word	Linguistic	Syntactic	graph_edges / total_words.
atd_per_word	Linguistic	Syntactic	graph_avg_total_degree / total_words.
parallel_edges_per_word	Linguistic	Syntactic	graph_repeated_edges / total_words.
loops_L1_per_word	Linguistic	Syntactic	graph_loops_L1 / total_words.
loops_L2_per_word	Linguistic	Syntactic	graph_loops_L2 / total_words.
loops_L3_per_word	Linguistic	Syntactic	graph_loops_L3 / total_words.
mean_constituency_depth	Linguistic	Syntactic	Mean depth of Stanza constituency tree.
max_constituency_depth	Linguistic	Syntactic	Maximum depth of Stanza constituency tree.
first_order_coherence	Linguistic	Semantic	Mean cosine simmilarity between sentences.
second_order_coherence	Linguistic	Semantic	Average similarity between sentences separated by one.
discourse_cohesion	Linguistic	Semantic	Mean token overlap between consecutive sentences.
sentence_repetition_ratio	Linguistic	Semantic	Exact repeated sentences / total sentences.
vader_negative	Linguistic	Psycholinguistic	VADER negative sentiment proportion.
vader_neutral	Linguistic	Psycholinguistic	VADER neutral sentiment proportion.
vader_positive	Linguistic	Psycholinguistic	VADER positive sentiment proportion.
vader_compound	Linguistic	Psycholinguistic	Composite sentiment score in range $[-1, 1]$.
sarcasm_prob	Bimodal	Psycholinguistic	Probability of sarcasm (BERT + Wav2Vec classifier).

Table 5: List of 82 acoustic and linguistic features with their computational definitions and grouping by type and subtype.



Figure 7: Comparison of feature value distributions between the *Stress* (maroon) and REAL (steelblue) datasets across 82 extracted features.

including STRESSID, DAIC-WOZ, ANDROIDS, EATD, and the REAL dataset. We report both interpretable model explanations and statistical group comparisons to provide complementary perspectives on feature relevance. Figures illustrate feature importance rankings derived from XGBoost built-in importance, LIME, and SHAP, while accompanying tables summarize statistically significant differences between clinical and non-clinical groups based on two-sample t-tests. Across datasets and mental health conditions, certain patterns can be observed, suggesting a potential role for prosodic variability, emotional expression, lexical richness, and graph-based linguistic structure as indicators of stress, depression, anxiety, and attentional symptoms.

Feature	Non-Depressed	Depressed	p-value
sarcasm_prob	0.465	0.431	2.44×10^{-3}
pause_short	0.357	0.768	4.13×10^{-3}
pause_speech_ratio	0.002	0.006	6.67×10^{-3}
avg_word_length	3.540	3.490	5.28×10^{-2}

Table 6: Mean feature values for Non-Depressed and Depressed groups (DAIC-WOZ), with corresponding p-values from two-sample t-tests ($p < 0.05$). Features were standardized (z-scored) before analysis.

Feature	Non-Depressed	Depressed	p-value
emotion_sad	0.099	0.182	2.83×10^{-5}
Intensity_mean	58.360	54.726	2.73×10^{-5}
sentiment_negative	0.519	0.693	6.49×10^{-5}
sentiment_positive	0.469	0.300	9.91×10^{-5}
second_order_coherence	0.213	0.313	1.08×10^{-3}
Jitter_local	0.021	0.024	1.26×10^{-2}
emotion_neu	0.199	0.156	1.96×10^{-2}
Shimmer_local	0.110	0.122	1.84×10^{-2}
brunet_index	8.852	9.740	1.70×10^{-2}
duration	54.971	72.298	3.56×10^{-2}
Phonation_rate	108.486	94.456	3.73×10^{-2}
pause_count	1.074	3.594	4.45×10^{-2}
pause_short	1.074	3.594	4.45×10^{-2}
pause_mean	0.0013	0.0038	3.63×10^{-2}
pause_speech_ratio	0.00035	0.00119	4.03×10^{-2}
type_token_ratio	0.698	0.646	2.68×10^{-2}
lemma_ttr	0.628	0.575	4.64×10^{-2}
sentence_count	5.212	6.536	3.19×10^{-2}
first_order_coherence	0.309	0.375	3.94×10^{-2}
upos_diversity	0.276	0.210	2.44×10^{-2}
emotion_hap	0.662	0.611	4.94×10^{-2}
MATTR	0.796	0.775	5.32×10^{-2}

Table 7: Mean acoustic and linguistic feature values for Non-Depressed and Depressed participants in the ANDROIDS corpus, with corresponding p-values from two-sample t-tests ($p < 0.05$ shown).

Feature	Non-Depressed	Depressed	p-value
emotion_neu	0.112	-0.493	8.58×10^{-4}
emotion_sad	-0.128	0.562	1.49×10^{-2}
F0_mean	-0.102	0.448	1.86×10^{-2}
passive_voice_ratio	0.046	-0.201	2.82×10^{-2}
pause_count	0.052	-0.230	4.78×10^{-2}

Table 8: Mean acoustic and linguistic feature values for Non-Depressed and Depressed participants in the EATD corpus, with corresponding p-values from two-sample t-tests ($p < 0.05$ shown).



Figure 8: Partial Dependence Plots for speech-derived features across the REAL model predictions for ASRS (first column), GAD-7 (second column), and PHQ-9 (third column).



Figure 9: Partial Dependence Plots for key linguistic and acoustic features in the STRESSID model. Each curve shows the monotonic relationship between the feature value and model prediction.



Figure 10: Partial Dependence Plots for key acoustic features in the DAIC-WOZ model.



Figure 11: Partial Dependence Plots for key acoustic, emotional, and linguistic features in the ANDROIDS model.



Figure 12: Partial Dependence Plots for key acoustic and linguistic features in the EATD model.

Feature	Non-Depressed	Depressed	p-value
vader_negative	0.030	0.050	1.22×10^{-4}
vader_compound	0.652	0.497	4.98×10^{-3}
content_function_ratio	1.333	1.273	9.93×10^{-3}
loops_L1_per_word	0.003	0.001	1.26×10^{-2}
pause_medium	0.295	0.102	1.91×10^{-2}
graph_loops_L1	0.302	0.148	1.77×10^{-2}
MATTR	0.693	0.704	4.78×10^{-2}
emotion_neu	0.198	0.169	4.26×10^{-2}

Table 9: Mean feature values for Non-Depression and Depression groups (PHQ-9) from the REAL dataset, with corresponding p-values from two-sample t-tests ($p < 0.05$).



Figure 13: Correlation matrices of the extracted acoustic and linguistic features across datasets. From top to bottom, panels correspond to REAL, STRESSID, EATD, ANDROIDS, and DAIC-WOZ, respectively. Each figure shows pairwise linear correlations among features.



(a) DAIC-WOZ – XGBoost (b) DAIC-WOZ – LIME (c) DAIC-WOZ – SHAP

Figure 14: Top predictive features for the DAIC-WOZ dataset derived from acoustic and linguistic descriptors.



(a) Androids – XGBoost (b) Androids – LIME (c) Androids – SHAP

Figure 15: Top predictive features for the ANDROIDS CORPUS dataset derived from acoustic and linguistic descriptors.



(a) EATD – XGBoost (b) EATD – LIME (c) EATD – SHAP

Figure 16: Top predictive features for the EATD dataset derived from acoustic and linguistic descriptors.



(a) ASRS – XGBoost (b) ASRS – LIME (c) GAD-7 – XGBoost

(d) GAD-7 – LIME (e) PHQ-9 – XGBoost (f) PHQ-9 – LIME

Figure 17: Top predictive features from the REAL dataset for ASRS, GAD-7, and PHQ-9 classification tasks using XGBoost built-in importance and LIME.

Exploring Profiles of Cognitive Distortions Associated with Mental Health Disorders

Alina Anikejeva
Institute of Computer Science
University of Tartu
Tartu, Estonia
alinaanikejeva@gmail.com

Kairit Sirts
Institute of Computer Science
University of Tartu
Tartu, Estonia
kairit.sirts@ut.ee

Abstract

Cognitive distortions, distorted patterns of thinking, have been increasingly studied in computational mental health research. Although they are related to many, if not all, mental health disorders, most existing studies focus primarily on depression. In this work, we explore distortion profiles across multiple mental health conditions. We analyzed a large Reddit-based dataset containing posts from nine self-reported mental health groups as well as a control group using both an n-gram-based method and a fine-tuned transformer model for detecting cognitive distortions. Mental health groups, both when pooled together and when examined individually, showed higher prevalence of cognitive distortions compared to the control group, with the effect sizes ranging from small to moderate. When comparing distortion profiles across conditions, we observed largely similar patterns, although some groups exhibited overall higher levels of distortions than others. These findings suggest that relatively simple lexical approaches can be useful for exploratory analyses of group-level trends in large-scale mental health text data.

1 Introduction

Cognitive distortions (CD) are negative thinking patterns that lead individuals to perceive reality in a distorted way, affecting thoughts, emotions, and behaviors (Beck, 1979). They are often associated with mental health disorders, such as depression and anxiety (Joormann and Stanton, 2016; Kuru et al., 2018; Ouhmad et al., 2024), and may contribute to their development and persistence (Burns, 1999).

Previous computational work has primarily focused on detecting cognitive distortions in text using supervised learning methods such as transformer models trained on annotated data (Simms et al., 2017; Shickel et al., 2020; Shreevastava and Foltz, 2021; Tauscher et al., 2023), as well as more recent approaches based on prompting large language models (Chen et al., 2023; Lim et al., 2024). These approaches aim to support clinically relevant predictions at the level of individual users (Wang et al., 2023; Tauscher et al., 2025).

A complementary line of work examines cognitive distortions at the population level by analyzing their prevalence in large-scale text data. In this line of work, Bathina et al. (2021) introduced a lexicon of distortion-related n-grams and used it to compare distortion prevalence in depression-related texts. The same n-gram-based approach has been applied to anxiety (Rutter et al., 2025), showing associations between distortion frequency and symptom severity. Such studies enable analysis at a scale that is difficult to achieve in traditional clinical settings.

However, these studies have an important methodological limitation. The n-gram-based approach relies on surface-level lexical matches and may produce false positives, as many markers (e.g., "I am always") also occur in non-distorted contexts. This raises questions about the validity of the detected patterns and motivates exploratory comparison with more contextual modeling approaches. In addition, prior work has focused primarily on overall distortion prevalence, without examining how specific distortion categories vary across mental health conditions.

To our knowledge, the only prior study examining profiles of cognitive distortions is Agarwal and Sirts (2025). However, that work focuses on relationships between cognitive distortions and emotion appraisal dimensions, which is a different psychological phenomenon and not directly related to mental health disorders.

In this work, we build on this line of work in two directions. Cognitive distortions are not exclusive to mental health conditions, but represent common patterns of human thinking (Beck, 1979). For this reason, we include a control group to provide a

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 208–220
July 4, 2026 ©2026 Association for Computational Linguistics

baseline for interpreting differences in distortion patterns. We apply the n-gram-based detection approach to a large-scale Reddit dataset covering multiple mental health groups and a control group (Cohan et al., 2018). We analyze distortion patterns across groups to determine whether CD profiles differ across disorders or remain largely similar. To provide secondary comparison to the n-gram-based approach, we additionally train a transformer-based model and compare whether the observed patterns are consistent across both methods. In summary, this study addresses the following research questions:

Q1: Are there differences in cognitive distortion prevalence between mental health groups and the control group?

Q2: How do distortion patterns vary across different mental health groups?

Q3: Are the patterns produced by the n-gram and transformer-based approaches consistent?

2 Data

We use three datasets in our work: 1) a large Reddit-based dataset to study CD profiles, 2) a small dataset annotated with CD labels to train supervised models to predict CD labels, and 3) a lexicon of CD-related n-grams. This section describes all these three datasets.

2.1 SMHD dataset

We use the Self-reported Mental Health Diagnoses (SMHD) dataset (Cohan et al., 2018) for the analysis of CDs. SMHD contains Reddit posts and comments from users who explicitly self-reported having been diagnosed with one or more mental health conditions from nine diagnostic categories. The dataset includes user-level labels indicating reported diagnoses and contains posts made between January 2006 and December 2017.

The diagnosed users (Clinical Group) were identified using pattern-based matching of explicit diagnosis statements (e.g., "I was officially diagnosed with OCD last year"). Users could be assigned multiple conditions if they reported more than one diagnosis. The control group was selected from users without mental health posts and matched to diagnosed users based on posting activity. Specifically, control users were required to post in the same subreddits and have a comparable number of posts to ensure similar activity patterns.

To reduce topic-related bias, the SMHD dataset excludes posts related to mental health for diagnosed users. Mental health posts were defined as posts made in mental health–related subreddits or containing mental health–specific language. As a result, the dataset consists of general, non-mental-health-specific content.

Label	Total Users	Total Posts
Control (30)	109,470	1,981,786
ADHD	3,649	47,052
Depression	3,647	45,362
Bipolar	1,932	21,834
Anxiety	1,633	20,708
Autism	955	13,480
PTSD	795	8,670
OCD	581	7,403
Schizophrenia	441	5,920
Eating Disorder	183	1,649

Table 1: Number of users and posts per group after preprocessing. The control group was divided into 30 equally sized, non-overlapping subsets matched to the ADHD group.

2.1.1 Preprocessing

We removed users with multiple mental health labels to ensure mutually exclusive group assignments. We retained only Reddit posts (excluding comments), as posts generally provide longer and more contextually complete text.

Text was cleaned using standard preprocessing steps, including lowercase conversion, whitespace normalization, removal of formatting characters, and filtering to English-language posts. We also applied Reddit-specific noise filtering by removing trading or advertising content and URL-heavy posts (>25% URLs).

After preprocessing, the control group was substantially larger than any individual diagnostic group. To address this imbalance, we randomly generated 30 control subsets, each matched in size to the largest diagnostic group (ADHD; 3,649 users). As shown in Table 1, 109,470 control users were randomly sampled and evenly divided into 30 distinct control subsets.

2.2 Therapist Q&A dataset

The supervised transformer model to predict CD labels in the SMHD dataset was trained on the Therapist Q&A (QA) dataset. The dataset was sourced from Kaggle and annotated as part of a prior study for cognitive distortion detection with ten CD categories (Shreevastava and Foltz, 2021). The dataset consists of 2530 anonymized thera-

pist–patient question–answer pairs, which was divided into training, development and test sets using 70/10/20 splits. Only the patient input was used in this work to train the models.

2.3 N-grams dataset

For the lexicon-based detection approach, we use the n-gram list introduced in prior work on cognitive distortion identification (Bathina et al., 2021), compiled by a panel of mental health professionals and publicly available in the corresponding GitHub repository.[1] The resource includes twelve cognitive distortion categories and associated linguistic markers (n-grams), along with their variants.

All n-grams were lowercased to align with text preprocessing. The number of markers varies across categories (e.g., Mindreading includes substantially more markers than Emotional Reasoning), and some categories rely on more common lexical items (e.g., "all," "nothing") than others. This may influence raw match frequencies; comparisons are therefore interpreted relative to group-level distributions. The n-gram categories and their marker counts are presented in Table 2.

Category	Total N-grams
Mindreading	159
Labeling and mislabeling	68
Overgeneralizing	31
Dichotomous Reasoning	24
Fortune-telling	24
Catastrophizing	23
Disqualifying the Positive	19
Personalizing	16
Mental Filtering	14
Magnification and Minimization	11
Should statements	11
Emotional Reasoning	7

Table 2: Distribution of n-grams across cognitive distortion categories.

3 Methods

In this section, we describe how cognitive distortion profiles are computed for mental health groups. We define a profile as the vector of effect sizes across distortion categories for a given group. We begin with an overview of the analysis pipeline, followed by the n-gram–based detection method, the procedure for establishing control-based baselines, and the transformer-based model used as a secondary comparison based on more contextual representations than the n-grams.

[1] https://github.com/mctenthij/CDS_paper

3.1 Overall process

After preprocessing, cognitive distortions were identified and analyzed across diagnostic groups in four stages:

1. Each post was matched against a predefined set of n-gram markers representing twelve CD categories, and category-specific marker counts were computed.

2. Distortion frequency distributions were estimated using the control subgroups. Percentile-based thresholds derived from these distributions were then used to determine whether a post exhibited elevated levels of a given distortion.

3. Statistical tests were conducted to examine differences in distortion prevalence between self-diagnosed individuals and clinical controls, as well as across self-diagnosed diagnostic groups.

4. Two pretrained transformer models (BERT and RoBERTa) were evaluated on an annotated QA dataset using macro F1. The best-performing model was subsequently applied to the SMHD corpus to explore whether broadly similar aggregate-level tendencies emerge under a substantially different detection approach.

Figure 1. provides a schematic overview of the analysis steps, from n-gram matching to thresholding, binary labeling, and statistical testing.

3.2 N-gram Matching

Cognitive distortions were identified using a predefined lexicon of n-gram markers and their variants, each assigned to a specific distortion category. Posts were matched using exact, case-insensitive string matching after lowercasing both markers and text. For each post, occurrences were counted per category.

3.3 Thresholding

Of the 2,153,864 posts, 57.7% contained at least one n-gram match, reflecting the fact that many markers also occur in everyday language. To reduce false positives, category-specific thresholds were derived from control-group distributions. For each distortion category, the 75th percentile of control marker counts was used as a cutoff, filtering



Figure 1: Overview of the analysis steps from n-gram matching through thresholding and binary labeling to statistical testing.

typical language while retaining posts with elevated distortion-related frequency. The 75th percentile was chosen as a conservative cutoff to filter common lexical occurrences while retaining posts with relatively elevated distortion-related frequency. Alternative percentile cutoffs (50th, 90th, and 95th percentiles) were also explored to examine how threshold values vary across distortion categories (Appendix A). For the majority of categories, the 75th percentile exceeded one match; however, Dichotomous Reasoning, Labeling and Mislabeling, and Should Statements required thresholds of 3, 2, and 2 matches, respectively.

Posts exceeding the category-specific threshold were labeled as distorted for that category as binary label; posts exceeding at least one category threshold were labeled as distorted overall.

3.4 Statistical Testing

Based on the binary labels, proportions of distorted posts were calculated to enable fair comparisons across groups with unequal post counts. Group differences were evaluated using two-tailed two-sample z-tests for proportions at $\alpha = 0.01$. Tests were conducted both at the aggregate level (all self-reported diagnoses vs. controls) and at the subgroup level, where each diagnostic group was compared against its 30 matched control subgroups. To control for multiple comparisons, Holm–Bonferroni correction was applied.

To quantify the magnitude of differences, effect sizes were calculated using Cohen's h, which measures standardized differences between proportions. Median Cohen's h values were then aggregated across comparisons to construct distortion profiles for each subgroup.

3.5 Transformer model

BERT and RoBERTa models pretrained on mental health data (Ji et al., 2022) were fine-tuned on the annotated multi-label QA dataset (Shreevastava and Foltz, 2021). Because each input may contain multiple cognitive distortions, the task was formulated as a multi-label classification problem, with sigmoid activation used to produce independent probability scores for each label. Models were trained using binary cross-entropy loss and evaluated using macro F1 across five runs to account for variability.

During inference, probability scores were converted into binary predictions using a decision threshold optimized on the validation set to maximize macro F1. Based on this evaluation, the better-performing model was selected and subsequently applied to the SMHD corpus. Because the QA dataset uses a different cognitive distortion taxonomy than the n-gram lexicon, model predictions were generated according to the QA label set.

4 Results

We first present results obtained using the n-gram–based method, followed by results based on labels produced by the transformer models.

4.1 N-gram matching

In this section, we present results based on the n-gram–based detection method. We first examine overall differences in distortion prevalence between Clinical and Control groups, and then analyze variation across cognitive distortion categories and distortion profiles across conditions.

4.1.1 Distorted vs Non-Distorted

Overall comparison Using the 75th percentile threshold, 29.8% of all posts were labeled as distorted, with a higher proportion observed in the Clinical group (44.5%) than in the Control group (28.5%) . This difference was statistically significant (two-tailed z-test, $p < 0.01$) and corresponded to a small-to-moderate effect size (Cohen's $h = 0.34$), indicating that cognitive distortions are more common in the Clinical group compared to the Control group.



Figure 2: Distribution of distorted post percentages across control and clinical groups. Boxplots show group distributions, with individual points representing subgroup-level values.

Individual Clinical group comparison We compared distortion rates between individual Clinical and Control subgroups. Control subgroups consistently showed lower distortion rates (28–30%) than Clinical subgroups (43–48%) (Figure 2). All Clinical groups differed significantly from matched Controls after Holm–Bonferroni correction, with small-to-moderate and relatively consistent median effect sizes ($h = 0.29$–0.42), highest for Eating Disorder and lowest for Autism (Table 3). These results show that the difference between Clinical and Control groups persists across specific disorder categories.

Group	Min h	Median h	Max h
Schizophrenia	0.28	0.31	0.32
PTSD	0.35	0.38	0.40
OCD	0.34	0.37	0.38
Eating Disorder	0.40	0.42	0.44
Depression	0.33	0.35	0.37
Bipolar	0.30	0.33	0.34
Autism	0.26	0.29	0.30
Anxiety	0.36	0.39	0.40
ADHD	0.28	0.31	0.32

Table 3: Minimum, median and maximum Cohen's h effect sizes by diagnostic group

4.1.2 Variations in Cognitive Distortions

Overall comparison We compared distortion percentages across cognitive distortion categories between the pooled Clinical and Control groups. Overall, the Clinical group exhibited higher distortion rates than the Control group across all categories. Some distortions were relatively common (e.g., Dichotomous Reasoning: 33% in Clinical vs. 15% in Control), whereas others were rare in both groups (e.g., Catastrophizing: <1%). The largest differences were observed for Dichotomous Reasoning, Labeling, Should Statements, and Personalizing, with smaller gaps for Mindreading and Fortune-telling (see Appendix B).

Distortion Category	Cohen's h
Dichotomous Reasoning	0.34
Labeling and Mislabeling	0.25
Personalizing	0.25
Should Statements	0.19
Overgeneralizing	0.17
Magnification and Minimization	0.11
Mindreading	0.11
Fortune-telling	0.10
Emotional Reasoning	0.09
Disqualifying the Positive	0.08
Mental Filtering	0.03
Catastrophizing	0.02

Table 4: Cohen's h Effect Sizes by Cognitive Distortion Category

Two-tailed two-proportion z-tests confirmed that these differences were statistically significant across all categories, with generally small effect sizes and relatively larger (small-to-moderate) effects for Dichotomous Reasoning, Labeling and Mislabeling, and Personalizing (Table 4). This indicates that while distortions are more frequent in the Clinical group across all categories, the magnitude of these differences varies by distortion type.

Individual Clinical group comparison We examined variation in distortion prevalence and effect size profiles across individual Clinical subgroups compared to Control subgroups. Distortion prevalence varied across Clinical subgroups, with Eating Disorder and PTSD showing higher percentages across multiple categories, while other Clinical groups exhibited lower—but still elevated—rates relative to Controls. Variation between Clinical groups differed by distortion type, with some categories showing consistent patterns and others greater dispersion.

Across all combinations of distortion categories, Clinical subgroups, and Control subgroups, 3,240 two-proportion z-tests were conducted; after Holm–Bonferroni correction, 2,835 remained statistically significant and 405 were not. Corresponding ef-

Figure 3: Cognitive distortion profiles across mental health conditions. Cells display median Cohen's h effect sizes for each distortion–condition pair. Abbreviations: ED = Eating Disorder, Anx. = Anxiety, Dep. = Depression, Bip. = Bipolar Disorder, Aut. = Autism, SCZ = Schizophrenia.

fect sizes were computed for each comparison, and median Cohen's h values were used to construct distortion profiles for each disorder, as shown in Figure 3.

Distortion profiles showed limited separation between disorders, with effect size differences across categories generally not exceeding 0.10–0.15. Weak grouping patterns emerged: Eating Disorder and PTSD exhibited the highest median effects across most categories; Anxiety, Depression, OCD, and Bipolar showed intermediate effects; and ADHD, Autism, and Schizophrenia showed the lowest.

Across all groups, the relative ranking of distortion categories was similar, with Dichotomous Reasoning consistently showing the largest effects, followed by Personalizing and Labeling, while Mental Filtering, Catastrophizing, and Disqualifying the Positive showed the smallest effects.

Overall, these results indicate that while distortion prevalence differs across Clinical subgroups, the overall pattern of cognitive distortions is largely shared, with only modest differentiation between disorders.

4.2 Transformer model

In this section, we present results based on the transformer-based detection method. Unlike the n-gram approach, which serves as the primary method, the transformer model is used to assess whether the group-level patterns observed in the lexical analysis are reproduced by a more contextual detection approach. We first report model performance, followed by the analysis of distortion prevalence across groups.

4.2.1 Model Accuracy

The transformer model achieved macro F1 scores of approximately 0.25–0.29 on the development set, but substantially lower performance on the held-out QA test set ($\approx$ 0.07–0.08), suggesting instability in fine-grained multi-label category prediction. One possible contributing factor is overfitting related to the decision threshold selection procedure adopted in the multi-label setting.

At the same time, binary distorted vs non-distorted classification performance (derived from the same multi-label predictions) was considerably higher on the test set (F1 = 0.56 for BERT and 0.75 for RoBERTa), indicating that the models capture broader distortion-related signal more reliably than individual distortion categories.

Previous work reporting F1 scores in the range of 0.2–0.3 (Chen et al., 2023; Lim et al., 2024) formulates the task as multi-class classification, whereas our setup uses multi-label formulation, making the results not directly comparable. In addition, the transformer models were trained on patient questions in the therapist-patient interactions discussing mental health topics, but later applied to general Reddit posts from the SMHD dataset, introducing substantial domain differences between training and application data. Because of these limitations, the transformer-based analysis should not be interpreted as reliable fine-grained cognitive distortion detection at the individual level. Instead, it serves as a secondary exploratory comparison examining whether broadly similar tendencies emerge under a substantially different modeling approach.

4.2.2 Distorted vs Non-Distorted

Overall comparison Using the RoBERTa model, 3.1% of posts were labeled as distorted. The proportion was 9.4% in the Clinical group and 2.5% in the Control group.

Individual Clinical group comparison We examined variation in transformer-identified distortion rates across individual Clinical subgroups compared to Control subgroups. Control subgroups showed stable distortion rates of approximately 3%,

whereas all Clinical subgroups exhibited higher proportions (Figure 4). Eating Disorder and PTSD displayed the highest distortion rates among Clinical groups.

4.2.3 Variations in Cognitive Distortions

Across cognitive distortion categories, posts in Clinical subgroups were more frequently labeled as distorted than those in the Control group, with Should Statements showing the highest prevalence overall. Eating Disorder consistently appeared near the upper range across categories, whereas ADHD tended to appear near the lower range (see Appendix C). This indicates that the model is capturing consistent differences between Clinical and Control groups, with variation across disorders but similar category-level patterns.

4.3 Comparison of N-Gram Method and Transformer Model

Although the transformer models identified a considerably lower proportion of distorted posts in both Clinical and Control groups, the overall patterns are similar across both methods. When comparing Figures 2 and 4, one can see a similar pattern, with Eating disorder having the highest proportion of cognitive distortions with both methods, followed by PTSD (although with the n-gram method, Anxiety is on the same level with PTSD), while with both methods, ADHD, Schizophrenia and Autism showing the least proportion of cognitive distortions.

Additional visualizations for each distortion category and disorder are provided in the Appendix. While these plots are not analyzed in detail here, they show broadly similar patterns across methods, suggesting partial convergence between the two approaches at the group level.



Figure 4: Transformer-based distortion rates across control and clinical subgroups.

5 Discussion

This work set out to examine the profiles of cognitive distortions across different mental health disorders. The analysis was conducted using two methods for distortion detection, with an n-gram approach as the primary technique and a transformer model used as a secondary exploratory comparison based on contextual representations. The study specifically investigated three questions: whether there are differences in cognitive distortion prevalence between mental health groups and the control group, how distortion profiles vary across conditions, and the extent to which the two methodological approaches produce convergent findings.

First, we found that indeed, cognitive distortions were more prevalent in mental-health-related groups, both when all clinical groups were pooled together as well as when analyzing each group separately. This result aligns with findings from previous studies on depression (Bathina et al., 2021; Lalk et al., 2025) and anxiety (Rutter et al., 2025). The observed effect sizes were generally in the small-to-moderate range, which is perhaps expected because cognitive distortions are essentially normative phenomena and are not exclusive to clinical populations. At the same time, our analysis was conducted on a very large social media dataset, where even subtle differences can become statistically significant. Therefore the interpretation of the results should rely more on effect sizes and overall patterns than on statistical significance alone. Although many comparisons remained significant after correction, the observed effect sizes remained relatively modest across most disorder and distortion-category combination.

When looking at the distinct cognitive distortions, we saw some distortions, particularly Dichotomous Thinking, Labeling and Mislabeling, and Personalizing, that showed larger differences between the mental health and control groups, while some other distortion categories, like Catastrophizing and Mental Filtering showed very small

differences between Clinical and Control groups across mental health disorders. These results partially converge with the previous results reported by Bathina et al. (2021) on depression, where they found that the largest difference between people with depression and a random social media user group was Personalizing, while there were no significant differences between groups related to Catastrophizing and Mental Filtering. Emotional reasoning, which showed the second largest difference in the Bathina et al. (2021) study, showed only small difference in our research, while in their study, Dichotomous thinking, while significant, was associated with a relatively small difference between groups.

The profiles of cognitive distortions between different mental health disorders were analyzed qualitatively by examining the effect size patterns. Based on this analysis, we observed that the overall structure of the profiles was largely similar across disorders, with differences in effect sizes typically not exceeding 0.10–0.15. Although some variation was present, particularly with Eating Disorder and PTSD groups showing somewhat higher levels of distortions compared to control groups and ADHD and Autism groups appearing closer to the control group, the relative ordering of distortion categories was largely similar across conditions. One possible interpretation of these findings is that the observed differences between mental health conditions may be related more to the overall intensity of the distorted language rather than to distinct combinations of the distortion types. The elevated distortion levels observed in PTSD and Eating Disorder groups may also partly reflect attempts to establish predictability, control, or emotional regulation in the context of heightened distress, although this interpretation would require substantially more clinically grounded investigation. More generally, these interpretations remain tentative, and more precise methods would be needed to determine whether more distinct disorder-specific cognitive distortion profiles exist.

When comparing the two cognitive distortion detection methods used in this paper, we observed that the transformer-based model detected considerably fewer distortions. Despite these differences, the overall patterns observed were similar across the two methods. Thus, we conclude that although the n-gram-based method is not adequate for making predictions with high precision due to the high rate of false positives, the results suggest it may still be useful for exploratory analysis of broader group-level trends in large datasets, provided that a control group is used to establish a baseline for interpreting the results. In such large-scale settings, applying transformer models is computationally substantially more costly, while the simple n-gram method offers a lightweight alternative.

Overall our findings show that large-scale computational analysis can detect subtle group-level differences, even when the analytical setting (data and methods) is noisy. While a common line of research focuses on predicting mental health states of specific individuals based on their expression of cognitive distortions (Wang et al., 2023) or assessing relations between cognitive distortions and disorder symptoms (Lalk et al., 2025; Varadarajan et al., 2025), our study, similarly to (Bathina et al., 2021), aims to reveal the broader associations between cognitive distortions and mental health disorders. We assume that the noise stemming from data and methods affects both the Control and Clinical groups in a similar way. Therefore, while our detection methods are too weak to reliably identify cognitive distortions in the texts of individual users or make inferences about their mental health states, they appear sufficient for detecting broader trends. Such trends can help generate more precise hypotheses for future work, which could then be tested using more targeted methods.

6 Conclusion

In this work, we analyzed cognitive distortion patterns across multiple mental health conditions using a large-scale Reddit dataset. Posts from mental health groups showed a higher prevalence of distortions compared to the control group, although the observed effect sizes were generally small to moderate. When comparing profiles across disorders, the relative ordering of distortion categories was largely similar, with only modest differences in effect sizes between conditions. Although the analysis relied on a noisy n-gram-based detection method, the overall patterns were consistent with those obtained using a fine-tuned transformer model. This suggests that relatively simple detection approaches can be suitable for exploratory analyses aimed at identifying group-level trends in mental health–related language.

Limitations

This study has several limitations. Although the n-gram-based approach used as the main method is very noisy, producing many false positives because the set of n-grams includes many common phrases, we do not consider this to be an inherent limitation of the study per se, as the use of a control group helps establish a normative baseline. However, cognitive distortions are essentially semantic and contextual phenomena, whereas our n-gram-based detection method is lexical. This means that the method cannot distinguish between someone saying "I always fail at everything", potentially reflecting a distorted thought, and "People often say 'I always fail' when they are catastrophizing", which does not reflect a distorted thought. The thresholding procedure used to filter common lexical matches can influence absolute prevalence estimates across distortion categories, particularly because categories differ considerably in the number and frequency of associated n-grams. Although alternative percentile thresholds were explored, the study does not systematically evaluate the sensitivity of the downstream results to threshold selection. Similarly, some categories relied on broad and relatively common lexical items, whereas others were represented by fewer and more specific expressions. This may partly influence relative prevalence estimates and effect size patterns across categories, meaning that comparisons between distortion categories should be interpreted cautiously. Nevertheless, because the transformer-based model, which is inherently more contextual, revealed broadly similar aggregate-level tendencies, we have reason to believe that this limitation did not substantially affect the main findings.

The second limitation relates to the Reddit-based SMHD dataset used in this study. Although the self-reported mental health diagnoses were extracted using high-precision textual patterns, the labels are still unavoidably noisy. First, the control groups are created based on the assumption that users who did not visit any mental health-related subreddit and did not self-report any mental health issues do not have such issues, which may not necessarily be true. Second, the posts of the users span a timeline of 11 years, and while a person might have had a diagnosis at one point, this might not be reflective—at least not for all disorders analyzed—of the entire time period. However, because the same limitation applies to both the Control and Clinical groups, we believe it does not invalidate the overall results.

In addition, the decision to retain only users with a single diagnostic label simplifies the clinical reality of substantial comorbidity between mental health conditions, particularly for eating disorders. As a result, the Eating Disorder subgroup represents a relatively narrow subset of users and probably does not fully capture broader clinical eating-disorder populations.

Finally, the analysis of cognitive distortion patterns across mental health disorders was essentially qualitative, relying on the examination of effect size patterns. While this approach is suitable for an exploratory comparison, more rigorous statistical or modeling approaches would be needed to establish whether distinct cognitive profiles exist across mental health disorders.

Acknowledgments

This research was supported by the Estonian Centre of Excellence in AI (EXAI) and by the Estonian Research Council Grant PRG3182.

References

Navneet Agarwal and Kairit Sirts. 2025. Exploratory study into relations between cognitive distortions and emotional appraisals. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 127–139.

Krishna C. Bathina, Marijn ten Thij, Lorenzo Lorenzo-Luaces, Laura A. Rutter, and Johan Bollen. 2021. Individuals with depression express more distorted thinking on social media. *Nature Human Behaviour*, 5(4):458–466.

Aaron T. Beck. 1979. *Cognitive Therapy and the Emotional Disorders*. Penguin.

David D. Burns. 1999. *Feeling Good: The New Mood Therapy*. Avon Books, New York, NY.

Zhiyu Chen, Yujie Lu, and William Wang. 2023. Empowering psychotherapy with large language models: Cognitive distortion detection through diagnosis of thought prompting. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 4295–4304.

Arman Cohan, Bart Desmet, Andrew Yates, Luca Soldaini, Sean MacAvaney, and Nazli Goharian. 2018. Smhd: A large-scale resource for exploring online language usage for multiple mental health conditions. In *Proceedings of the 27th International Conference on Computational Linguistics*, pages 1485–1497.

Shaoxiong Ji, Tianlin Zhang, Luna Ansari, Jie Fu, Prayag Tiwari, and Erik Cambria. 2022. Mentalbert:

Publicly available pretrained language models for mental healthcare. In *proceedings of the thirteenth language resources and evaluation conference*, pages 7184–7190.

Jutta Joormann and Colin H. Stanton. 2016. Examining emotion regulation in depression: A review and future directions. *Behaviour research and therapy*, 86:35–49.

Erkan Kuru, Yasir Safak, İlker Özdemir, Rıza Gökcer Tulacı, Kadir Özdel, N. G. Özkula, and Sibel D. Örsel. 2018. Cognitive distortions in patients with social anxiety disorder: Comparison of a clinical group and healthy controls. *The European Journal of Psychiatry*, 32(2):97–104.

Christopher Lalk, Tobias Steinbrenner, Juan S. Pena, Weronika Kania, Jana Schaffrath, Steffen Eberhardt, Brian Schwartz, Wolfgang Lutz, and Julian Rubel. 2025. Depression symptoms are associated with frequency of cognitive distortions in psychotherapy transcripts. *Cognitive Therapy and Research*, 49(3):588–600.

Sehee Lim, Yejin Kim, Chi-Hyun Choi, Jy-yong Sohn, and Byung-Hoon Kim. 2024. Erd: A framework for improving llm reasoning for cognitive distortion classification. In *Proceedings of the 6th Clinical Natural Language Processing Workshop*, pages 292–300.

Nawal Ouhmad, Romain Deperrois, Wissam El Hage, and Nicolas Combalbert. 2024. Cognitive distortions, anxiety, and depression in individuals suffering from ptsd. *International Journal of Mental Health*, 53(4):336–352.

Lauren A. Rutter, Andy Edinger, Lorenzo Lorenzo-Luaces, Marijn Ten Thij, Danny Valdez, and Johan Bollen. 2025. Anxiety and depression are associated with more distorted thinking on social media: A longitudinal multi-method study. *Cognitive therapy and research*, 49(4):712–720.

Benjamin Shickel, Sydney Siegel, Martin Heesacker, Sherry Benton, and Parisa Rashidi. 2020. Automatic detection and classification of cognitive distortions in mental health text. In *Proceedings of the 2020 IEEE 20th International Conference on Bioinformatics and Bioengineering (BIBE)*, pages 275–280.

Shashank Shreevastava and Peter Foltz. 2021. Detecting cognitive distortions from patient-therapist interactions. In *Proceedings of the 7th Workshop on Computational Linguistics and Clinical Psychology (CLPsych)*, pages 151–158.

Trevor Simms, Chris Ramstedt, Megan Rich, Michael Richards, Tony Martinez, and Christophe Giraud-Carrier. 2017. Detecting cognitive distortions through machine learning text analytics. In *Proceedings of the 2017 IEEE International Conference on Healthcare Informatics (ICHI)*, pages 508–512.

Jordan S. Tauscher, Kevin Lybarger, Xiao Ding, Anmol Chander, William J. Hudenko, and Trevor Cohen. 2023. Automated detection of cognitive distortions in text exchanges between clinicians and people with serious mental illness. *Psychiatric Services*, 74(4):407–410.

Justin Tauscher, Xiruo Ding, Sarah Kopelovich, Arun Nagendra, Kevin Lybarger, Trevor Cohen, and Dror Ben-Zeev. 2025. Automated flagging of cognitive biases in the spoken language of people with hallucination experiences. *Journal of Technology in Behavioral Science*, pages 1–10.

Vasudha Varadarajan, Allison Lahnala, Sujeeth Vankudari, Akshay Raghavan, Scott Feltman, Syeda Mahwish, Camilo Ruggero, Roman Kotov, and H. Andrew Schwartz. 2025. Linking language-based distortion detection to mental health outcomes. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 62–68.

Bichen Wang, Yanyan Zhao, Xin Lu, and Bing Qin. 2023. Cognitive distortion based explainable depression detection and analysis technologies for the adolescent internet users on social media. *Frontiers in Public Health*, 10:1045777.

A Cutoff values for n-grams



Figure 5: Threshold values used for different percentile cutoffs across cognitive distortion categories.

B Category-level n-gram results



Figure 6: Distribution of distortion percentages across cognitive distortion categories for Clinical and Control groups.

C Category-level transformer results



Figure 7: Distribution of distortion predictions across cognitive distortion categories based on the transformer model.

Facet-Informed Prompting for LLM-Based Personality Assessment: Error-Guided Exemplar Selection and Hierarchical Prediction

Rasiq Hussain[1] **Juhi Chetan Shah**[1] **Joshua Oltmanns**[2] **Mehak Gupta**[1]
[1]Southern Methodist University [2]Washington University in St. Louis
{rasiqh, juhichetans, mehakg}@smu.edu j.oltmanns@wustl.edu

Abstract

Large language models (LLMs) are increasingly applied to automatic personality assessment, yet most prior work relies on coarse binary labels and direct domain-level predictions, limiting interpretability and ignoring the hierarchical facet structure of personality. In this study, we implement a structured prompting approach with three complementary objectives: direct domain-level prediction, fine-grained facet-level prediction, and domain-level prediction informed by facet outputs. All predictions use a five-level ordinal label scheme, capturing a continuum from very low to very high trait expression. Across all prompt types, we adopt an error-guided self-refinement procedure using in-context learning (ICL) to guide the model toward more accurate predictions. Zero-shot prompts assess baseline performance, while one-shot prompts incorporate a single demonstration example selected through the refinement procedure. Our framework evaluates both domain- and facet-level predictions, enabling examination of how prediction granularity and targeted exemplar selection influence LLM inference. By combining hierarchical domain-facet relationships with structured prompting and refinement, this work aims to provide a systematic approach for interpretable personality assessment from long-form life narratives, with broader implications for mental health research where fine-grained trait-level inference from speech can support clinical assessment.

1 Introduction

Personality is a central construct in psychology, shaping cognition, emotion, and behaviour. The Five-Factor Model (FFM) organizes personality into five broad domains—Openness, Conscientiousness, Extraversion, Agreeableness, and Neuroticism (Costa Jr and McCrae, 1992)—each comprising six subordinate facets, operationalized in instruments such as the NEO-PI-R (Costa and McCrae, 2008). Facets capture unique trait variance, show only moderate intercorrelations, and exhibit heterogeneous behavioural and linguistic expressions (DeYoung et al., 2007; Soto and John, 2017), suggesting that predicting personality at the facet level before aggregating to domains may improve precision and interpretability.

Most computational approaches to personality assessment predict personality directly at the broad domain level using binary labels, classifying each trait simply as high or low (Mairesse et al., 2007; Majumder et al., 2017; Yang et al., 2023; Yeo et al., 2025). This simplified formulation overlooks two key aspects of the underlying psychometric model: the hierarchical facet structure within each domain and the continuous nature of trait expression. These limitations are particularly important in mental health research, where Big Five traits are linked to a wide range of psychological and behavioral outcomes (Ozer and Benet-Martinez, 2006; Kotov et al., 2010, 2017). As a result, fine-grained personality inference from naturalistic speech may support more scalable and interpretable assessment approaches for both clinical and research settings (Hussain et al., 2026; Le Glaz et al., 2021).

These gaps motivate three research questions guiding our investigation:

RQ1 Label resolution. How does increasing label resolution from binary to five-level ordinal classification affect LLM performance?

RQ2 Prediction granularity. Does a hierarchical approach, predicting at the facet level and aggregating to domain scores, yield more accurate domain-level assessments than direct domain-level prediction?

RQ3 Exemplar selection. Does semantically-guided retrieval of in-context exemplars targeting systematic errors improve performance relative to zero-shot and static one-shot prompting?

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 221–237
July 4, 2026 ©2026 Association for Computational Linguistics

To address these questions, we developed a structured prompting framework consisting of three complementary prompt types: (i) direct domain-level prediction, (ii) facet-level prediction, and (iii) domain-level prediction conditioned on inferred facets. Each task uses a five-level ordinal scale (Very Low to Very High), requiring the model to capture subtle trait differences. Across all prompt types, we implement an error-guided self-refinement procedure via in-context learning (ICL), using task-relevant examples to improve predictions without updating model parameters (Dong et al., 2024; Liu et al., 2022; Madaan et al., 2023). Zero-shot prompts assess baseline performance, while one-shot prompts incorporate a single demonstration example selected through the refinement procedure. Facet-level predictions are used in prompt type III to inform domain-level scores, enabling comparisons of prediction granularity.

By combining fine-grained, five-level classification with structured facet-to-domain reasoning and targeted exemplar selection, this framework provides a psychometrically informed approach to evaluating and improving LLM-based personality assessment from long-form narratives.

2 Related Work

2.1 Large Language Models for Personality Assessment

The use of natural language processing for psychological and mental health assessment has gained increasing attention in recent years (Le Glaz et al., 2021; Sikström et al., 2025). Early work on personality prediction from text relied on handcrafted linguistic features and lexicons, demonstrating that stylistic and semantic cues can be predictive of personality traits (Mairesse et al., 2007; Argamon et al., 2007).

With the rise of neural models, representation learning approaches based on deep architectures further improved performance by capturing latent semantic patterns in text (Majumder et al., 2017). More recently, large language models (LLMs) have enabled a shift toward prompting-based approaches, where models infer personality traits directly from text without task-specific fine-tuning. Recent work has shown that LLMs can generate coherent personality assessments and capture personality-relevant signals in language, suggesting their potential for naturalistic personality inference (Peters et al., 2024; Rosenfelder et al., 2025; Zhu et al., 2025a; Hussain et al., 2026).

Despite these advances, most existing approaches focus on predicting personality at the broad domain level using coarse label spaces, often reducing trait prediction to binary or low-resolution classification (Mairesse et al., 2007; Majumder et al., 2017; Yang et al., 2023). This simplified formulation overlooks the continuous nature of trait expression. In contrast, our work adopts a five-level ordinal scheme to enable more precise and interpretable personality inference.

2.2 Domain-Guided Structured Prompting for Personality Inference

Recent work has explored incorporating psychological structure into prompt design to improve the reliability of LLM-based personality assessment. For example, Yang et al. (2023) proposes questionnaire-style prompting inspired by psychometric inventories, encouraging models to reason over structured trait definitions. PADO (Yeo et al., 2025) uses multiple LLM agents that analyze input text from distinct linguistic perspectives to infer relative levels of the Big Five (OCEAN) traits. Zhu et al. (2025b) propose that when you prompt an LLM to respond to individual items from a structured personality inventory (e.g., Big Five questionnaire items) rather than just asking for a direct overall trait prediction, the model produces more accurate personality inferences, even from short interview or text samples. These approaches show that grounding prompts in domain-specific frameworks can improve alignment with human judgments and provide more interpretable outputs.

In this work, we extend this direction by introducing a multi-stage prompting framework that first infers facet-level traits and then conditions domain-level predictions on these intermediate outputs.

2.3 Prompt Refinement for Personality Inference

Iterative self-refinement can improve performance by analyzing model outputs to identify and correct systematic errors (Madaan et al., 2023). Rather than relying on repeated calls to the model, refinement can also be implemented via in-context learning (ICL), which provides task-relevant demonstration examples directly in the prompt, allowing the model to adapt its predictions without updating parameters (Brown et al., 2020; Dong et al., 2024). ICL performance depends on the quality of demonstration examples, with dynamically selected se-

mantically relevant examples outperforming random or static choices (Liu et al., 2022; Rubin et al., 2022).

Building on these insights, we implement an error-guided prompt refinement strategy for personality inference. ICL demonstration examples are selected not only for semantic similarity but also to target systematic model errors, such as consistent mispredictions of specific traits or facets.

3 Data

3.1 SPAN: Life Narrative Interviews

This study uses Life Narrative Interview from St. Louis Personality and Aging Network (SPAN) study (Oltmanns et al., 2020). Participants narrate life experiences through family, work, and formative events in open-ended interviewer prompts. Personality was assessed using the Big Five framework, with each domain composed of six facets as defined in the NEO-PI-R (Costa and McCrae, 2008). Details about data processing are shared in Supplementary A.

Five-level label construction. Domain scores in the dataset range from 0 to 192. We standardize domain and facet scores in our dataset before assigning five-level labels. For each domain and facet, we compute a z-score $z = (x - \mu)/\sigma$ using the sample mean and standard deviation reported in Table 1. We then assign labels using z-score cutoffs motivated by standard psychometric practice for five-band trait interpretation: very low ($z < -1.5$), low ($-1.5 \leq z < -0.5$), average ($-0.5 \leq z < 0.5$), high ($0.5 \leq z < 1.5$), and very high ($z \geq 1.5$). These cutoffs divide the score distribution into five meaningful bands reflecting relative trait standing within the dataset, and are applied independently at both the domain and facet level.

4 Method

We design a structured prompting framework with three prompt types corresponding to different inference objectives: (1) direct domain-level prediction, (2) facet-level prediction, and (3) domain-level prediction derived from facet predictions.

We first describe the zero-shot setting to establish baseline model behavior under each prompt type. We then extend this setup to a one-shot setting, where a single demonstration example is incorporated into the prompt. Finally, we detail our refinement procedure for exemplar selection, which leverages error patterns observed in the zero-shot setting to guide the choice of informative in-context examples.

4.1 Prompt Types

4.1.1 Prompt Type I: Direct Domain-Level Prediction

The first prompt type performs direct prediction of the five personality domains (Openness, Conscientiousness, Extraversion, Agreeableness, and Neuroticism) from the input text. A single prompt is used to jointly predict all five domains, with each domain assigned a label on a five-level ordinal scale (Very Low, Low, Average, High, Very High).

This prompt evaluates the model's ability to infer high-level personality traits directly from linguistic cues without explicit decomposition into facets. It serves as a baseline for comparison against more structured prediction strategies. Prompt I is implemented in both zero- and one-shot settings. Examples for each setting can be found in Supplementary B.

4.1.2 Prompt Type II: Facet-Level Prediction

The second prompt type performs fine-grained prediction at the facet level. For each personality domain, a dedicated prompt is used to predict its six underlying facets, resulting in six facet-level predictions per domain. Each facet is framed as a five-level ordinal classification task.

This decomposition allows the model to reason over more specific behavioral signals within the text. In addition, facet-level predictions provide a mechanism for analysing systematic errors and identifying which aspects of personality are most challenging for the model to infer. Prompt II is also implemented in both zero- and one-shot settings, and examples can be found in Supplementary C.

4.1.3 Prompt Type III: Domain-Level Prediction from Facets

The third prompt type predicts domain-level traits based on the facet-level outputs produced by Prompt Type II. This prompt takes as input the previously inferred facet-level labels and the inference (reasoning) for the corresponding prediction.

This formulation enables a structured reasoning step in which the model aggregates facet-level evidence to produce a final domain-level prediction. This approach allows the language model to learn implicit relationships between facets and domains

Table 1: Domain and facet-level dataset statistics showing mean, standard deviation, and transcript counts across five-level buckets.

Facet	Mean	Std	Very Low	Low	Average	High	Very High
Openness	113.1	18.7	94	401	621	347	113
Imagination	16.2	4.6	90	385	653	357	110
Artistic Interests	18.8	5.1	137	371	596	388	103
Emotionality	19.8	3.9	134	301	623	422	115
Adventurousness	16.0	3.9	129	448	459	432	127
Intellect	19.8	5.2	91	422	594	375	113
Liberalism	21.3	4.1	129	371	610	385	98
Conscientiousness	124.4	17.9	95	362	652	374	93
Self-Efficacy	23.4	3.3	115	297	807	268	108
Orderliness	17.7	4.1	122	295	651	424	103
Dutifulness	23.3	3.6	85	414	662	306	128
Achievement-Striving	19.0	4.1	107	318	722	374	75
Self-Discipline	21.0	4.5	147	253	696	418	81
Cautiousness	18.9	3.9	93	344	593	461	104
Extraversion	109.2	18.9	108	349	624	396	99
Friendliness	23.0	4.1	109	272	666	472	76
Gregariousness	16.7	5.0	134	368	617	399	77
Assertiveness	16.5	4.6	102	421	525	467	80
Activity Level	16.5	4.1	118	374	626	350	127
Excitement-Seeking	15.1	4.3	108	326	681	372	109
Cheerfulness	20.3	4.7	145	267	653	439	91
Agreeableness	130.9	16.1	99	347	672	335	123
Trust	21.9	4.2	118	286	557	563	71
Morality	22.6	4.1	121	332	620	414	108
Altruism	24.3	3.4	133	322	578	461	101
Cooperation	19.2	3.8	113	394	657	317	115
Modesty	20.0	4.1	99	282	793	334	87
Sympathy	21.8	3.4	93	439	570	375	117
Neuroticism	73.0	21.3	86	421	626	317	126
Anxiety	12.9	4.8	72	451	632	342	99
Anger	10.9	4.5	97	389	696	282	131
Depression	11.2	5.3	79	446	614	329	127
Self-Consciousness	13.2	4.2	61	539	568	295	132
Immoderation	15.1	4.2	79	363	712	324	117
Vulnerability	9.0	3.9	103	418	587	370	118

through contextual reasoning. Prompt III is identical for both zero-shot and one-shot settings because its primary role is to perform evidence aggregation from Prompt II, rather than generating predictions from raw transcripts itself. The example prompt is shared in the Supplementary D.

4.2 Zero-Shot Prompting

In the zero-shot setting, both Prompt I and Prompt II are executed without any labeled examples. This setup evaluates the model's inherent ability to perform personality inference across different levels of abstraction.

All zero-shot prompts follow a consistent structure using the standard *system* + *user* format. The system prompt defines the model's role and task, while the user prompt provides the input transcript. Each system prompt consists of the following components:(1) Expert Role Definition: The model is instructed to act as an expert personality psychologist with training in computational psycholinguistics, (2) Task Contextualization: For domain-level prompts (Prompt I), concise definitions of the five personality domains are provided. For facet-level prompts (Prompt II), definitions of the six facets within the target domain are included, (3) Analytic Directive: The model is instructed to analyze linguistic and behavioral cues in the text and assign ratings based on the provided definitions, (4) Reasoning Directive: The model is encouraged to justify each prediction using evidence from the text, promoting more grounded inferences, (5) Constrained Output Schema: Outputs are required in

a structured JSON format, including the predicted label, a brief rationale, and supporting evidence.

4.3 One-Shot Prompting with In-Context Refinement

To improve prediction accuracy, we extend both Prompt I and Prompt II with a one-shot configuration that incorporates a single demonstration example. This example is selected using the error-guided refinement procedure described in Section 4.4.

In the one-shot setting, the prompt retains the same structure as the zero-shot version but is augmented with two additional components: (1) Exemplar Demonstration: A labeled transcript is provided prior to the target input, including both the text and its corresponding domain or facet annotations, (2) Instructional Alignment: The model is explicitly instructed to use the demonstration as a reference for identifying relevant linguistic patterns and applying that knowledge when analyzing the target transcript.

We adopt a one-shot design to balance performance gains with prompt length constraints, particularly given the inclusion of long narrative transcripts and detailed facet definitions. Prior work has shown that excessive context length can reduce effective utilization of relevant information (Liu et al., 2024; Chang et al., 2024).

This unified prompting framework allows us to systematically compare: (i) direct vs. hierarchically structured prediction, (ii) domain vs. facet-level reasoning, and (iii) zero-shot vs. refinement-based ICL.

4.4 Error-Guided Refinement with In-Context Learning

We implement refinement through in-context learning (ICL). In our framework, the selection of demonstration examples is treated as a refinement decision. We first analyze where and how the model fails and then identify examples that target these failure modes. These examples are then incorporated into the prompt at inference time.

Error Analysis. The refinement loop begins with an automated error analysis on the training set. The model is first run in zero-shot mode. For Prompt I (domain-level prediction), misclassification is calculated at the domain level, while for Prompt II (facet-level prediction), it is calculated for each facet within a domain. Errors are decomposed into overestimation (predicting higher than ground truth) and underestimation (predicting lower than ground truth), as these require opposite corrective examples. A model that consistently overestimates a facet needs to be shown examples of low trait expression, while a model that underestimates needs examples of high trait expression. For Prompt I (domain-level prediction), we identify the two domains with the highest misclassification rates, and for Prompt II (facet-level prediction), we similarly identify the two facets with the highest misclassification rates per domain as primary targets for refinement. Selecting the top two targets balances focused error correction with generalizability. Improving these high-error domains or facets domains can also yield moderate gains in non-targeted domains or facets due to inter-domain and inter-facet correlations (Soto and John, 2017).

Example Pool and Directional Selection. To support the refinement process, we construct separate candidate example pools for Prompt I and Prompt II. For Prompt I, the pool contains training examples covering all label levels for each domain, while for Prompt II, the pool covers all label levels for each facet. Once the error analysis identifies the target domains or facets and their dominant error direction, we filter the respective pool accordingly. For overestimated targets, we retain only examples with ground-truth very-low or low labels; for underestimated targets, we retain only examples with ground-truth very-high or high labels. This directional filtering ensures that the selected demonstration is corrective for the specific failure mode identified.

Semantic Similarity Filtering. Directional filtering narrows the candidate set but does not guarantee that the retrieved demonstration is semantically aligned with the input transcript. To address this, we apply a second filtering step based on semantic similarity. All transcripts are embedded using OpenAI's `text-embedding-3-small` model, and cosine similarity is computed between the target transcript and candidate pool transcripts. The top-1 most similar transcript is selected for demonstration. Retrieval is implemented using FAISS for efficient nearest-neighbor search (Liu et al., 2022).

5 Experiment Design

All experiments use GPT-4o with temperature set to 0.0 for deterministic outputs. Each transcript is processed independently, and model outputs are

Table 2: Zero-shot Micro-F1 across three label resolutions - binary, three, and five-class resolution.

Domain	Binary	3-class	5-class
Openness	0.80	0.59	0.34
Conscientiousness	0.94	0.63	0.25
Extraversion	0.64	0.52	0.32
Agreeableness	0.87	0.70	0.28
Neuroticism	0.46	0.41	0.27

parsed to extract predicted labels.

The dataset is partitioned into disjoint training (50%) and test (50%) sets. The training set is used exclusively to construct the candidate pool for demonstration selection during in-context learning and for error analysis in the refinement procedure. The test set is used for final evaluation of each prompt performance, ensuring no data leakage.

We construct the example pool from the training partition of 788 transcripts. Specifically, all exemplar candidate transcripts are drawn exclusively from the training set, since no test transcript appears in the candidate pool at any point during the exemplar selection or error analysis. This ensures strict separation between evaluation and refinement.

To ensure sufficient coverage for the exemplar selection across all domains, facets, and label levels, we verify that every domain and facet–label-level combination is represented by at least 30 transcripts in the pool. Because every transcript carries labels for all 5 domains and 30 facets simultaneously, a single transcript contributes to multiple domains and facet-level.

We structure our evaluation around the three research questions from Section 1, examining the impact of label resolution, hierarchical facet-to-domain prediction, and error-guided in-context learning refinement. For each prompt type, we compare zero-shot and one-shot configurations, and analyze zero-shot errors to motivate the refinement process. We also conduct ablation studies to isolate the effects of error-guidance and contextual similarity in the refinement pipeline.

To complement Micro-F1 with a metric that reflects the ordinal structure of the label scheme, we additionally report ordinal tolerance accuracy. This metric measures the proportion of predictions that fall within one label of the true value, capturing near-miss performance that exact-match metrics do not reflect (Weber et al., 2025). For example, on a five-level scale, a prediction of High when the true label is Average represents a meaningfully smaller error than a prediction of Very Low, and ordinal tolerance accuracy captures this distinction in a way that Micro-F1 does not.

6 Results

6.1 Effect of Label Resolution

We first evaluate zero-shot performance across different label resolutions. Micro-F1 in Table 2 shows performance declines as the task shifts from binary to multi-level prediction. The largest relative drop between binary and 5-level is observed for Conscientiousness (73.4%), followed by Agreeableness (67.8%), Openness (57.5%), and Extraversion (50.0%). Neuroticism shows a comparatively smaller decrease (41.3%).

These results show that fine-grained personality prediction is substantially more challenging than coarse binary classification, motivating the need for structured prediction strategies at higher resolution.

6.2 Impact of Prediction Granularity

In Table 3, we examine whether modeling personality at the facet level improves domain-level prediction by comparing output of Prompt I and Prompt III.

Under zero-shot prompting, Prompt Type III improves over Prompt Type I across all domains, with gains for Openness (+8.8%), Conscientiousness (+28.0%), Extraversion (+18.8%), Agreeableness (+17.9%), and Neuroticism (+33.3%). This suggests that incorporating facet-level structure improves performance, though not uniformly.

Under one-shot prompting, the improvements are larger, with Prompt Type III outperforming Prompt Type I for Openness (+36.4%), Conscientiousness (+60%), Extraversion (+27.3%), Agreeableness (+33.3%), and Neuroticism (+34.5%), indicating that facet-level reasoning becomes more effective when combined with exemplar guidance.

6.3 Effect of Error-Guided Exemplar Selection

6.3.1 Zero-Shot Error Analysis

To guide exemplar selection for prompt refinement, we first examine systematic errors under zero-shot prompting (Table 4) to identify directional biases.

At the domain level, Openness, Conscientiousness, and Agreeableness are predominantly overestimated (76.3%, 90.7%, and 83.3% of errors, respectively), while Neuroticism is mainly underestimated (59.0%). Extraversion shows more balanced

Table 3: Domain-level Micro-F1 scores on test set for Prompt Type I (Direct Domain Prediction) and Prompt Type III (Domain from Facets). Bold indicates the best overall score per domain, while underlined values indicate the best score within Prompt Type I.

Domain	**Prompt Type I: Direct Domain**		**Prompt Type III: Domain from Facets**	
	Zero-Shot	One-Shot	Zero-Shot	One-Shot
Openness	0.34	0.33	0.37	**0.45**
Conscientiousness	0.25	0.25	0.32	**0.40**
Extraversion	0.32	0.33	0.38	**0.42**
Agreeableness	0.28	0.30	0.33	**0.40**
Neuroticism	0.27	0.29	0.36	**0.39**

errors (45.1% under vs. 54.9% over), indicating weaker directional bias.

Facet-level results closely mirror domain-level trends: facets under Openness, Conscientiousness, Extraversion, and Agreeableness are predominantly overestimated, while Neuroticism facets show strong underestimation. This alignment suggests that domain-level biases arise from systematic misclassification patterns originating at the facet level. We identify the top two contributing domains and facets per domain to implement error correction for Prompt I and Prompt II, respectively.

6.3.2 Performance Impact of Refinement

As observed in Tables 3 and 5, one-shot prompting generally improves performance over zero-shot at both domain and facet levels.

Domain-level improvements. At the domain level (Table 3), Prompt Type I shows only marginal gains from zero-shot to one-shot, within $\pm 7\%$ for most traits, indicating limited ability to leverage exemplars at a coarse domain level. In contrast, Prompt Type III, which aggregates facet-level information, achieves larger improvements: +21.6% for Openness, +25.0% for Conscientiousness, +10.5% for Extraversion, +21.2% for Agreeableness, and +8.3% for Neuroticism. These results highlight that facet-informed aggregation better translates exemplar guidance into domain-level gains.

Facet-level improvements. Targeting the top two most misclassified facets in each domain (Table 4) improves both the selected facets and non-targeted facets, demonstrating a clear "trickle-down" effect (Table 5).

In Openness, focusing on Emotionality (85.8% over) and Adventurousness (67.6% over) improves Micro-F1 by 20.4% and 19.8%, respectively, with additional gains of 4.7–6.7% for most other facets. For Conscientiousness, targeting Dutifulness (80.5% over) and Achievement-Striving (87.6% over) increases these facets by 29.9% and 31.4%, with smaller improvements of 5.1–16.2% in the remaining facets. In Extraversion, correcting Gregariousness (62.7% over) and Excitement-Seeking (63.6% over) yields approximately 5–14% gains across all facets. Agreeableness sees large improvements in Altruism (91.4% over, +30.7%) and Sympathy (91.0% over, +38.6%), with modest 7.7–13.3% gains for non-targeted facets. Finally, Neuroticism, targeting Anxiety (53.3% under) and Self-Consciousness (83% under), improves these facets by 13.8% and 24.8%, respectively, while other facets show smaller gains or slight decreases, reflecting weaker inter-facet correlations in this domain.

Translation to domain-level gains. These facet-level improvements directly contribute to the stronger domain-level performance of Prompt Type III, where zero- to one-shot gains range from 8–25%, compared with only 0–7% for Prompt Type I. This underscores how exemplar-guided, facet-informed prompting more effectively enhances overall predictions.

Exemplar guidance vs Random guidance. As an additional comparison, we evaluate a random one-shot baseline by randomly sampling one training example for each facet. The process was repeated 100 times and averaged for stability. The random baseline achieves an average facet-level Micro-F1 of 0.293, compared to 0.347 for the proposed error-guided one-shot strategy (Prompt Type II; Table 5). These results indicate that the observed improvements arise from targeted exemplar selection rather than merely including an arbitrary demonstration example.

6.4 Ordinal Tolerance Analysis

We additionally report ordinal tolerance accuracy for Prompt Type III domain-level predictions to complement Micro-F1 in Table 6. Tolerance accuracy evaluates model performance beyond exact-match accuracy, which measures the proportion

Table 4: Domain- and facet-level misclassification analysis on train set under zero-shot prompting. The table reports overall misclassification rate (%), along with the proportion of overestimation and underestimation errors expressed as percentages of total misclassifications (normalized such that Over + Under = 100%). The dominant error type per domain is shown in bold, and the top two most misclassified facets per domain are underlined.

Domain / Facet	Miss (%)	Over (%)	Under (%)
Openness	65.59	**76.30**	23.70
Imagination	61.58	40.56	**59.44**
Artistic Interests	60.51	**58.71**	41.29
Emotionality	71.97	**85.79**	14.21
Adventurousness	67.52	**67.64**	32.36
Intellect	61.25	**61.37**	38.63
Liberalism	60.36	**52.53**	47.47
Conscientiousness	74.67	**90.66**	9.34
Self-Efficacy	66.94	**82.15**	17.85
Orderliness	62.49	38.51	**61.49**
Dutifulness	71.72	**80.48**	19.52
Achievement-Striving	73.72	**87.61**	12.39
Self-Discipline	61.09	**63.30**	36.70
Cautiousness	63.64	42.87	**57.13**
Extraversion	67.33	**54.91**	45.09
Friendliness	57.87	**60.26**	39.74
Gregariousness	64.88	**62.65**	37.35
Assertiveness	60.84	**66.41**	33.59
Activity Level	62.41	**63.83**	36.17
Excitement-Seeking	66.47	**63.57**	36.43
Cheerfulness	60.26	**54.16**	45.84
Agreeableness	71.45	**83.30**	16.70
Trust	57.71	**66.15**	33.85
Morality	66.36	**69.94**	30.06
Altruism	77.16	**91.44**	8.56
Cooperation	64.17	**63.56**	36.44
Modesty	55.98	**60.39**	39.61
Sympathy	79.21	**91.02**	8.98
Neuroticism	72.92	41.03	**58.97**
Anxiety	64.09	46.67	**53.33**
Anger	62.50	31.44	**68.56**
Depression	63.16	**61.99**	38.01
Self-Consciousness	65.62	17.03	**82.97**
Immoderation	59.70	46.16	**53.84**
Vulnerability	63.52	45.41	**54.59**

Table 5: Facet-level Micro-F1 scores on test set for Prompt Type II: Facet-Level Prediction. Bold indicates the best score per facet.

Facet	Zero-Shot	One-Shot
Openness		
Imagination	0.387	**0.410**
Artistic Interests	0.401	**0.428**
Emotionality	0.275	**0.331**
Adventurousness	0.313	**0.375**
Intellect	**0.398**	0.391
Liberalism	0.402	**0.421**
Conscientiousness		
Self-Efficacy	0.315	**0.366**
Orderliness	0.385	**0.416**
Dutifulness	0.271	**0.352**
Achievement-Striving	0.245	**0.322**
Self-Discipline	0.373	**0.433**
Cautiousness	0.372	**0.391**
Extraversion		
Friendliness	0.409	**0.467**
Gregariousness	0.351	**0.401**
Assertiveness	0.383	**0.422**
Activity Level	0.376	**0.405**
Excitement-Seeking	0.334	**0.368**
Cheerfulness	0.409	**0.428**
Agreeableness		
Trust	0.428	**0.461**
Morality	**0.340**	0.308
Altruism	0.231	**0.302**
Cooperation	0.355	**0.396**
Modesty	0.421	**0.477**
Sympathy	0.207	**0.287**
Neuroticism		
Anxiety	0.355	**0.404**
Anger	**0.367**	0.270
Depression	**0.394**	0.391
Self-Consciousness	0.326	**0.407**
Immoderation	**0.417**	0.391
Vulnerability	0.360	**0.392**

of predictions falling within one label of the true value on the five-point scale. Unlike Micro-F1, this metric captures the clinical relevance of near-miss predictions, where a one-level discrepancy carries less consequence than a large ordinal error.

At the domain level, Prompt Type III achieves consistently high ordinal tolerance across all five domains under both zero-shot and one-shot prompting, with overall accuracies of 82.5% and 81.1%, respectively. This indicates that most domain-level predictions remain within one label of the ground truth regardless of prompting strategy.

The results also suggest a directional effect of error-guided exemplar selection. One-shot exemplars are intentionally selected to correct systematic overestimation or underestimation, which helps recover exact label matches and improves Micro-F1 across all domains. At the same time, this stronger corrective behavior can occasionally shift predictions farther from the true label for samples that were already within one adjacent category under zero-shot prompting, leading to a small reduction in ordinal tolerance. This trade-off is reflected in Table 3, where one-shot prompting improves exact classification performance while maintaining comparably high ordinal consistency in Table 6. Future work could explore softer ordinal-aware correction strategies that better balance exact-match accuracy and near-miss predictions.

6.5 Ablation Analysis

We performed an ablation study to isolate the contributions of error guidance and semantic similarity in exemplar selection for Prompt Type III (Ta-

Table 6: Ordinal tolerance accuracy (%) for Prompt Type III (Domain from Facets), reporting the proportion of domain-level predictions falling within one label of the true value under zero-shot and one-shot prompting.

Domain	Zero-Shot	One-Shot
Openness	86.4	84.7
Conscientiousness	81.6	77.9
Extraversion	83.5	81.1
Agreeableness	80.0	78.8
Neuroticism	80.8	83.1
Overall	82.5	81.1

Table 7: Ablation of exemplar selection. Domain-level Micro-F1 is shown for full one-shot (error + similarity), error-guided only, and similarity-guided only selection. Bold indicates the best score per domain.

Domain	Full One-Shot	Error Only	Similarity Only
Openness	**0.45**	0.40	0.42
Conscientiousness	**0.40**	0.37	0.38
Extraversion	**0.42**	0.37	0.39
Agreeableness	**0.40**	0.36	0.37
Neuroticism	**0.39**	0.34	0.34

ble 7). Using only error-guided exemplars, where examples are randomly selected from the subset of instances chosen based on error direction (i.e., selecting low or very low for overestimated facets and vice versa), reduces domain-level Micro-F1 by 7-12%, reflecting the inclusion of less relevant examples without error-guidance.

Selecting exemplars solely based on similarity, i.e., choosing the most semantically relevant examples without first filtering based on error direction, leads to smaller reductions per domain (5–12%) compared to error-guided exemplars.

Integrating both error guidance and similarity yields the best performance. This demonstrates that error guidance focuses the model on the most problematic facets, while similarity ensures the selected exemplars are contextually relevant. The synergy of these components explains why Prompt Type III outperforms other strategies.

7 Discussion

This study examined how prompting strategies, prediction granularity, and label resolution affect LLM-based personality assessment from life narratives. Our results demonstrate that incorporating hierarchical facet structure improves domain-level predictions compared with direct domain-level prompting. By modeling finer-grained facets, the model can capture subtle linguistic cues often missed at the coarse domain level. Higher label resolution (5-level) increases task difficulty, making facet-level modeling and exemplar guidance especially valuable.

Exemplar-based one-shot prompting is most effective at the facet-to-domain prompt, serving as targeted corrections for high-error facets. Improvements in these facets propagate to non-targeted facets within the same domain, mostly producing a positive "trickle-down" effect, though the magnitude varies depending on inter-facet correlations (DeYoung et al., 2007; Soto and John, 2017; Costa and McCrae, 2008). For example, domains such as Openness, Conscientiousness, and Agreeableness exhibit moderate correlations, resulting in mostly positive spillover effects, whereas Neuroticism facets are weakly correlated and show more heterogeneous improvements.

Structuring predictions hierarchically, first at the facet level and then aggregating to the domain level, allows exemplar-based corrections to translate into domain-level improvements. This approach provides practical guidance for applied LLM-based personality assessment, especially under multi-level label schemes.

The clinical relevance of this work extends beyond methodology. Big Five personality domains, particularly Neuroticism and Agreeableness, have established links to psychopathology, treatment adherence, and mental health outcomes(Kotov et al., 2010; Ozer and Benet-Martinez, 2006). Accurate fine-grained personality inference from life narratives could therefore support scalable mental health research by enabling automated trait assessment through text. While current performance levels position this framework as a research tool rather than a clinical instrument, the ordinal tolerance accuracy exceeding 82% at the domain level for Prompt Type III suggests meaningful signal capture. Validation against clinician-rated assessments represents a necessary next step toward clinical translation.

8 Conclusion

Incorporating facet-level prediction with error-guided exemplar refinement enhances LLM-based personality assessment, particularly at higher label resolutions. Aggregating facet predictions consistently improves domain-level performance and demonstrates the benefits of hierarchically structured prompting for more accurate and interpretable personality inference.

Ethics Statement

Personality assessment, particularly using automated tools, raises several ethical concerns. This study uses data from the SPAN study, which was approved by the Washington University in St. Louis Institutional Review Board. All transcripts are anonymized, personally identifiable information has been removed, and participants provided written informed consent as part of the original SPAN study protocol. We emphasize that LLM-based personality predictions should not be used as standalone clinical judgments. Instead, they are intended to provide supplementary insights, for example, in behavioral research or exploratory mental health studies. Misinterpretation or over-reliance on model outputs could lead to harmful consequences, particularly in sensitive contexts such as therapy, hiring, or legal settings. Researchers and practitioners should treat model outputs as probabilistic suggestions rather than definitive evaluations.

Limitations

While facet-based aggregation improves domain-level predictions, performance is still constrained by facets with abstract or sparsely expressed cues. Future work could explore decoupled facet-level prompting, where each facet is modeled independently before aggregation, potentially reducing error propagation and improving coverage of additional facets. Shorter-text sources such as social media posts may also provide complementary exemplars for more scalable refinement and out-of-distribution evaluation.

Another consideration is the label distribution in the dataset. Approximately 40% of transcripts receive an *average* label, while the *very low* and *very high* categories together account for only about 14% of observations, contributing to lower performance on extreme trait levels. Future work could improve robustness for these underrepresented categories through targeted sampling or cost-sensitive learning.

Finally, the ground-truth labels are derived from self-report NEO assessments rather than clinician-rated evaluations. Since self-perceived and externally observed traits may differ, further validation with clinician-rated personality assessments would strengthen the framework's clinical applicability. Nonetheless, the model demonstrates meaningful predictive performance despite this cross-modality setting, suggesting that naturalistic speech captures informative personality signals.

Acknowledgments

We thank the participants of the St. Louis Personality and Aging Network (SPAN) study for their contributions to this research. Computational resources were provided by the SMU O'Donnell Data Science and Research Computing Institute.

References

Shlomo Argamon, Moshe Koppel, James W Pennebaker, and Jonathan Schler. 2007. Mining the blogosphere: Age, gender and the varieties of self-expression. *First Monday*, 12(9).

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, and 1 others. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.

Kaiyan Chang, Songcheng Xu, Chenglong Wang, Yingfeng Luo, Xiaoqian Liu, Tong Xiao, and Jingbo Zhu. 2024. Efficient prompting methods for large language models: A survey. *arXiv preprint arXiv:2404.01077*.

Paul T Costa and Robert R McCrae. 2008. The revised neo personality inventory (neo-pi-r). *The SAGE handbook of personality theory and assessment*, 2(2):179–198.

Paul T Costa Jr and Robert R McCrae. 1992. The five-factor model of personality and its relevance to personality disorders. *Journal of personality disorders*, 6(4):343–359.

Colin G DeYoung, Lena C Quilty, and Jordan B Peterson. 2007. Between facets and domains: 10 aspects of the big five. *Journal of personality and social psychology*, 93(5):880.

Qingxiu Dong, Lei Li, Damai Dai, Ce Zheng, Jingyuan Ma, Rui Li, Heming Xia, Jingjing Xu, Zhiyong Wu, Baobao Chang, Xu Sun, Lei Li, and Zhifang Sui. 2024. A survey on in-context learning. In *Proceedings of the 2024 conference on empirical methods in natural language processing*, pages 1107–1128.

Rasiq Hussain, Zerui Ma, Ritik Khandelwal, Joshua Oltmanns, and Mehak Gupta. 2026. Language-based personality assessment from life narratives: a focus on model interpretability and efficiency. *Frontiers in Artificial Intelligence*, 9:1760246.

Roman Kotov, Wakiza Gamez, Frank Schmidt, and David Watson. 2010. Linking "big" personality traits to anxiety, depressive, and substance use disorders: a meta-analysis. *Psychological bulletin*, 136(5):768.

Roman Kotov, Robert F Krueger, David Watson, Thomas M Achenbach, Robert R Althoff, R Michael Bagby, Timothy A Brown, William T Carpenter, Avshalom Caspi, Lee Anna Clark, and 1 others. 2017. The hierarchical taxonomy of psychopathology (hitop): A dimensional alternative to traditional nosologies. *Journal of abnormal psychology*, 126(4):454.

Aziliz Le Glaz, Yannis Haralambous, Deok-Hee Kim-Dufor, Philippe Lenca, Romain Billot, Taylor C Ryan, Jonathan Marsh, Jordan Devylder, Michel Walter, Sofian Berrouiguet, and Christophe Lemey. 2021. Machine learning and natural language processing in mental health: systematic review. *Journal of medical Internet research*, 23(5):e15708.

Jiachang Liu, Dinghan Shen, Yizhe Zhang, William B Dolan, Lawrence Carin, and Weizhu Chen. 2022. What makes good in-context examples for gpt-3? In *Proceedings of Deep Learning Inside Out (DeeLIO 2022): The 3rd workshop on knowledge extraction and integration for deep learning architectures*, pages 100–114.

Nelson F Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. 2024. Lost in the middle: How language models use long contexts. *Transactions of the association for computational linguistics*, 12:157–173.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, Shashank Gupta, Bodhisattwa Prasad Majumder, Katherine Hermann, Sean Welleck, Amir Yazdanbakhsh, and Peter Clark. 2023. Self-refine: Iterative refinement with self-feedback. *Advances in neural information processing systems*, 36:46534–46594.

François Mairesse, Marilyn A Walker, Matthias R Mehl, and Roger K Moore. 2007. Using linguistic cues for the automatic recognition of personality in conversation and text. *Journal of artificial intelligence research*, 30:457–500.

Navonil Majumder, Soujanya Poria, Alexander Gelbukh, and Erik Cambria. 2017. Deep learning-based document modeling for personality detection from text. *IEEE intelligent systems*, 32(2):74–79.

Joshua R Oltmanns, Joshua J Jackson, and Thomas F Oltmanns. 2020. Personality change: Longitudinal self-other agreement and convergence with retrospective-reports. *Journal of Personality and Social Psychology*, 118(5):1065.

Daniel J Ozer and Veronica Benet-Martinez. 2006. Personality and the prediction of consequential outcomes. *Annu. Rev. Psychol.*, 57(1):401–421.

Heinrich Peters, Moran Cerf, and Sandra C Matz. 2024. Large language models can infer personality from free-form user interactions. *arXiv preprint arXiv:2405.13052*.

Ariel Rosenfelder, Maor Daniel Levitin, and Michael Gilead. 2025. Towards social superintelligence? ai infers diverse psychological traits from text without specific training, outperforming human judges. *Computers in Human Behavior: Artificial Humans*, page 100228.

Ohad Rubin, Jonathan Herzig, and Jonathan Berant. 2022. Learning to retrieve prompts for in-context learning. In *Proceedings of the 2022 conference of the North American chapter of the association for computational linguistics: human language technologies*, pages 2655–2671.

Sverker Sikström, Ieva Valavičiūtė, and Petri Kajonius. 2025. Personality in just a few words: Assessment using natural language processing. *Personality and Individual Differences*, 238:113078.

Christopher J Soto and Oliver P John. 2017. The next big five inventory (bfi-2): Developing and assessing a hierarchical model with 15 facets to enhance bandwidth, fidelity, and predictive power. *Journal of personality and social psychology*, 113(1):117.

Samantha Weber, Nicolas Deperrois, Robert Heun, Laura Frühschütz, Anna Monn, Stephanie Homan, Andrea Häfliger, Erich Seifritz, Tobias Kowatsch, MULTICAST consortium Jäger Lena 8 Schultebraucks Katharina 9 Gershov Sapir 9 Mocellin Jacopo 1 4, and 1 others. 2025. Using a fine-tuned large language model for symptom-based depression evaluation. *npj Digital Medicine*, 8(1):598.

Tao Yang, Tianyuan Shi, Fanqi Wan, Xiaojun Quan, Qifan Wang, Bingzhe Wu, and Jiaxiang Wu. 2023. Psycot: Psychological questionnaire as powerful chain-of-thought for personality detection. In *Findings of the association for computational linguistics: EMNLP 2023*, pages 3305–3320.

Haein Yeo, Taehyeong Noh, Seungwan Jin, and Kyungsik Han. 2025. Pado: Personality-induced multi-agents for detecting ocean in human-generated texts. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 5719–5736.

Jianfeng Zhu, Ruoming Jin, and Karin G Coifman. 2025a. Can llms infer personality from real world conversations? *arXiv preprint arXiv:2507.14355*.

Jianfeng Zhu, Ruoming Jin, and Karin G Coifman. 2025b. Investigating large language models in inferring personality traits from user conversations. *arXiv preprint arXiv:2501.07532*.

A Data Preprocessing

Transcripts were anonymized, and initial acknowledgments were removed. Punctuation and casing were preserved to retain the natural structure of the narratives. Each transcript ranges from approximately 1,100 to 7,900 tokens, with an average

of 2,500 words. We removed 170 transcripts out of 1,408 total since they were either too short or too long, to avoid length-based bias in the experiments. We used the OpenAI text-embedding-3-small model with a context window of 8,191 tokens, ensuring that none of the transcripts were truncated.

B Prompt I Example

Figure 1 shows an example of a direct domain-level prompt in a zero-shot setting. Figure 2 shows an example of a direct domain-level prompt in a one-shot setting.

C Prompt II Example

Figure 3 shows an example of a facet-level prompt in a zero-shot setting. Figure 4 shows an example of a facet-level prompt in a one-shot setting.

D Prompt III Example

Figure 5 shows an example of Prompt III, which aggregates the evidence gathered by Prompt II to predict the domain-level label. This prompt is identical for both zero-shot and one-shot settings because its primary role is to perform evidence aggregation from Prompt II, rather than generating predictions from raw transcripts itself.

Prompt I: Zero-Shot Domain-Level Configuration

1. Expert Role Definition (System Prompt) You are an expert personality psychologist specializing in computational psycholinguistics. Your task is to evaluate linguistic evidence in text transcripts to infer personality domain levels for all five Big Five domains: *Openness, Conscientiousness, Extraversion, Agreeableness, Neuroticism*.

2. Task Contextualization (Trait Domain Definitions) Domain Definitions and Characteristics:

- **Openness:** Broad, complex, and imaginative mental life. Enjoys new experiences and abstract ideas.
- **Conscientiousness:** Organized, responsible, self-disciplined, and goal-oriented behavior.
- **Extraversion:** Energetic engagement with others, sociable, assertive, and positive affect.
- **Agreeableness:** Compassionate, cooperative, trusting, and considerate toward others.
- **Neuroticism:** Tendency toward emotional instability, anxiety, and negative affect.

3. Analysis and Reasoning Directive

1. Read the transcript carefully.
2. Identify linguistic, thematic, and behavioral cues relevant to each domain.
3. Assign a rating for all five domains.
4. Justify each rating using evidence from the transcript.

4. Rating Scale

- `very high`: strong evidence of high domain trait
- `high`: moderate evidence of high domain trait
- `average`: mixed evidence
- `low`: moderate evidence of low domain trait
- `very low`: strong evidence of low domain trait

5. Constrained Output Schema

```
{
 "Openness": {"rating": "...", "inference": "...", "quote": "..."},
 "Conscientiousness": {"rating": "...", "inference": "...", "quote": "..."},
 "Extraversion": {"rating": "...", "inference": "...", "quote": "..."},
 "Agreeableness": {"rating": "...", "inference": "...", "quote": "..."},
 "Neuroticism": {"rating": "...", "inference": "...", "quote": "..."}
}
```

6. Input Transcript (User Prompt)

```
[Insert transcript text here]
```

Figure 1: Zero-shot configuration for Prompt I, showing system role, domain definitions, analysis procedure, and output format.

Prompt I: One-Shot Domain-Level Configuration

1. Expert Role Definition (System Prompt) You are an expert personality psychologist specializing in computational psycholinguistics. Your task is to evaluate linguistic evidence in text transcripts to infer personality domain levels for all five Big Five domains: *Openness, Conscientiousness, Extraversion, Agreeableness, Neuroticism*.

2. Task Contextualization (Trait Domain Definitions) Domain Definitions and Characteristics:

- **Openness:** Broad, complex, and imaginative mental life. Enjoys new experiences and abstract ideas.
- **Conscientiousness:** Organized, responsible, self-disciplined, and goal-oriented behavior.
- **Extraversion:** Energetic engagement with others, sociable, assertive, and positive affect.
- **Agreeableness:** Compassionate, cooperative, trusting, and considerate toward others.
- **Neuroticism:** Tendency toward emotional instability, anxiety, and negative affect.

3. Analysis and Reasoning Directive

1. Read the transcript carefully.
2. Identify linguistic, thematic, and behavioral cues relevant to each domain.
3. Assign a rating for all five domains.
4. Justify each rating using evidence from the transcript.

4. Exemplar Demonstration

```
[Insert labeled transcript example with domain ratings here]
```

5. Instructional Alignment
Use the exemplar demonstration as a reference to guide your pattern recognition and ensure consistent reasoning when predicting domain-level ratings for the target transcript.

6. Rating Scale

- `very high`: strong evidence of high domain trait
- `high`: moderate evidence of high domain trait
- `average`: mixed evidence
- `low`: moderate evidence of low domain trait
- `very low`: strong evidence of low domain trait

7. Constrained Output Schema

```
{
 "Openness": {"rating": "...", "inference": "...", "quote": "..."},
 "Conscientiousness": {"rating": "...", "inference": "...", "quote": "..."},
 "Extraversion": {"rating": "...", "inference": "...", "quote": "..."},
 "Agreeableness": {"rating": "...", "inference": "...", "quote": "..."},
 "Neuroticism": {"rating": "...", "inference": "...", "quote": "..."}
}
```

8. Input Transcript (User Prompt)

```
[Insert target transcript text here]
```

Figure 2: One-shot configuration for Prompt I, showing system role, domain definitions, analysis procedure, exemplar, and output format.

Prompt II: Zero-Shot Configuration

1. Expert Role Definition (System Prompt) You are an expert personality psychologist specializing in computational psycholinguistics. Your task is to evaluate linguistic evidence in text transcripts to infer personality facet levels for *[Big Five domain, e.g., "Openness to Experience"]*.

2. Task Contextualization (Trait Facet Definitions) Trait Description: Openness reflects the breadth, depth, and complexity of an individual's mental and experiential life.

Facet Definitions and Characteristics:

- **Imagination (PNEOO1):**
  - **High:** Vivid imagination, enjoys fantasy and daydreaming.
  - **Low:** Concrete thinking, rarely engages in imaginative or abstract thought.
- **Artistic Interests (PNEOO2):**
  - **High:** Values and appreciates art, music, and aesthetic experiences.
  - **Low:** Avoids artistic activities, shows little interest in creative or cultural pursuits.
- **Emotionality (PNEOO3):**
  - **High:** Expresses emotions vividly and demonstrates empathy.
  - **Low:** Emotionally restrained, seldom reflects or communicates feelings.
- **Adventurousness (PNEOO4):**
  - **High:** Seeks novelty and variety, enjoys exploring new experiences.
  - **Low:** Prefers routine and familiar environments, avoids unfamiliar situations.
- **Intellect (PNEOO5):**
  - **High:** Enjoys abstract thinking, complex problem-solving, and analytical reasoning.
  - **Low:** Avoids complexity, prefers concrete or simple tasks.
- **Liberalism (PNEOO6):**
  - **High:** Endorses progressive values and openness to change.
  - **Low:** Holds traditional views, resists unconventional or progressive ideas.

3. Analysis and Reasoning Directive

1. Read the transcript carefully.
2. Identify linguistic and thematic cues.
3. Assign ratings for all six facets.
4. Justify each rating with inference and direct quote from the transcript.

4. Rating Scale

- `very high`: strong evidence of high trait
- `high`: moderate evidence of high trait
- `average`: mixed evidence
- `low`: moderate evidence of low trait
- `very low`: strong evidence of low trait

5. Constrained Output Schema

```
{
 "PNEOO1_scaled": {"rating": "...", "inference": "...", "quote": "..."},
 ...
 "PNEOO6_scaled": {...}
}
```

6. Input Transcript (User Prompt)

```
[Insert transcript text here]
```

Figure 3: Zero-shot configuration for Prompt II, showing system role, domain definitions, analysis procedure, and output format.

Prompt II: One-Shot Configuration

1. Expert Role Definition (System Prompt) You are an expert personality psychologist specializing in computational psycholinguistics. Your task is to evaluate linguistic evidence in text transcripts to infer personality facet levels for *[Big Five domain, e.g., "Openness to Experience"]*.

2. Task Contextualization (Trait Facet Definitions) Trait Description: Openness reflects the breadth, depth, and complexity of an individual's mental and experiential life.

Facet Definitions and Characteristics:

- **Imagination (PNEOO1):**
  - **High:** Vivid imagination, enjoys fantasy and daydreaming.
  - **Low:** Concrete thinking, rarely engages in imaginative or abstract thought.
- **Artistic Interests (PNEOO2):**
  - **High:** Values and appreciates art, music, and aesthetic experiences.
  - **Low:** Avoids artistic activities, shows little interest in creative or cultural pursuits.
- **Emotionality (PNEOO3):**
  - **High:** Expresses emotions vividly and demonstrates empathy.
  - **Low:** Emotionally restrained, seldom reflects or communicates feelings.
- **Adventurousness (PNEOO4):**
  - **High:** Seeks novelty and variety, enjoys exploring new experiences.
  - **Low:** Prefers routine and familiar environments, avoids unfamiliar situations.
- **Intellect (PNEOO5):**
  - **High:** Enjoys abstract thinking, complex problem-solving, and analytical reasoning.
  - **Low:** Avoids complexity, prefers concrete or simple tasks.
- **Liberalism (PNEOO6):**
  - **High:** Endorses progressive values and openness to change.
  - **Low:** Holds traditional views, resists unconventional or progressive ideas.

3. Analysis and Reasoning Directive

1. Read the transcript carefully.
2. Identify linguistic and thematic cues.
3. Assign ratings for all six facets.
4. Justify each rating with inference and direct quote from the transcript.

4. Exemplar Demonstration

`[Insert labeled transcript example with domain ratings here]`

5. Instructional Alignment

Use the exemplar demonstration as a reference to guide your pattern recognition and ensure consistent reasoning when predicting domain-level ratings for the target transcript.

6. Rating Scale

- `very high`: strong evidence of high trait
- `high`: moderate evidence of high trait
- `average`: mixed evidence
- `low`: moderate evidence of low trait
- `very low`: strong evidence of low trait

7. Constrained Output Schema

```
{
 "PNEOO1_scaled": {"rating": "...", "inference": "...", "quote": "..."},
 ...
 "PNEOO6_scaled": {...}
}
```

8. Input Transcript (User Prompt)

`[Insert target transcript text here]`

Figure 4: One-shot configuration for Prompt II, showing system role, domain definitions, analysis procedure, exemplar, and output format.

Prompt Type III: Facet-to-Domain Aggregation Example

INPUT: Facet-Level Ratings with Evidence
Each facet is assigned a rating along with an evidence-based inference extracted from the transcript.

Imagination	*Rating: High* *Inference: The speaker frequently engages in abstract thinking and discusses hypothetical scenarios, indicating strong imaginative capacity.*
Artistic Interests	*Rating: Average* *Inference: Limited references to artistic activities; occasional appreciation but not a dominant theme.*
Emotionality	*Rating: High* *Inference: The speaker expresses emotions vividly and reflects on internal experiences in detail.*
Adventurousness	*Rating: Low* *Inference: Preference for routine and avoidance of unfamiliar situations are repeatedly mentioned.*
Intellect	*Rating: High* *Inference: Strong engagement with complex ideas and analytical reasoning is evident throughout the narrative.*
Liberalism	*Rating: Average* *Inference: Some openness to new perspectives is present, but views remain moderately conventional.*

TASK: Domain-Level Aggregation
Using the facet ratings and their inferences above, determine a single domain-level rating for **Openness to Experience**.

GUIDELINES:

1. Consider the overall pattern across all six facets.
2. Assess whether the evidence consistently supports the high or low pole, or is mixed.
3. Resolve conflicts by prioritizing the inference text over the rating labels.

OUTPUT:
Openness to Experience: High
Justification: The majority of facets (Imagination, Emotionality, and Intellect) show strong high-pole evidence, outweighing the lower Adventurousness score and mixed signals in Artistic Interests and Liberalism. Overall, the narrative reflects a consistent pattern of cognitive exploration and emotional depth, supporting a high domain-level rating.

Figure 5: Prompt III, facet inputs and instructions to aggregate evidence and labels to give domain-level prediction, and output format.

From Responses to Trajectories: Modeling the Development of Reflective Listening Skills

Dhruvil Thummar **Verónica Pérez-Rosas**
Texas State University, San Marcos
{kwt32, vperezr}@txstate.edu

Abstract

Reflective listening is a core counseling skill that supports effective communication in mental and behavioral health. Understanding how this skill changes with practice is important for designing scalable training and feedback systems. In this paper, we examine longitudinal patterns in 6,196 trainee responses collected during a three-week counseling training study. We model responses as trajectories in semantic embedding space and use residual embeddings with similarity-based metrics to quantify week-to-week change. Our analyses reveal systematic shifts over time, including increased semantic alignment and reduced variability, consistent with stabilization in trainees' language. We further show that these trajectory patterns are accompanied by modest linguistic shifts relevant to reflective counseling practice. Together, these findings provide a trajectory-based view of how reflective listening practice changes over repeated assignment.

1 Introduction

Reflective listening is a core counseling skill in motivational interviewing (MI) and other patient-centered approaches. It involves generating responses that paraphrase and infer a speaker's underlying meaning or emotional state without introducing advice or judgment (Miller and Rollnick, 2012). For example, given the client statement, "I know I should quit smoking, but I'm overwhelmed right now," a reflective response might be: "You feel torn: you recognize quitting is important, but everything happening in your life makes it feel impossible at the moment." Producing such responses requires nuanced semantic alignment with the speaker's intent and typically develops through repeated practice and feedback.

Its clinical importance is well established, with prior work linking reflective listening to positive therapeutic outcomes (Moyers et al., 2009). However, it remains difficult to teach and assess at scale. Human supervision is time-intensive, qualified supervisors are limited, and direct observation of trainee-client interactions is uncommon in many training programs. As a result, trainees may receive sparse or inconsistent feedback, making it difficult to track how their reflective listening skills develop over time.

Because reflective listening is expressed through language, natural language processing (NLP) offers a promising way to support scalable assessment and feedback. Prior NLP work on reflective listening training has focused on generating alternative phrasings, rewriting trainee responses, and evaluating response quality, enabling scalable feedback on trainee performance (Shen et al., 2022; Min et al., 2022, 2023). Complementing these exchange-level approaches, a longitudinal perspective can help characterize how reflective listening develops across repeated practice.

We present an initial study in this direction by addressing two research questions: (1) Do trainee responses change systematically between practice sessions? (2) Do these changes align with linguistic patterns previously associated with high-quality counseling? We answer these questions by examining longitudinal embedding trajectories and linguistically grounded markers of reflection quality in 6,196 trainee responses collected during a three-week counseling training study. We find systematic shifts over time, including increased semantic alignment and reduced variability, suggesting stabilization in trainees' language. These shifts are accompanied by changes in linguistic features previously associated with high-quality counseling conversations.

2 Related Work

Manual assessment of counseling skills has long provided the clinical foundation for evaluating treatment fidelity and trainee competence. In MI,

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 238–243
July 4, 2026 ©2026 Association for Computational Linguistics

coding systems such as the Motivational Interviewing Treatment Integrity (MITI) scale are widely used to assess counselor behaviors, including reflections, questions, MI-adherent behaviors, and relational qualities such as empathy and partnership (Moyers et al., 2016). Similar manual fidelity and competence measures have been developed for other therapeutic approaches, including cognitive behavioral therapy. These instruments provide clinically grounded standards for evaluating counseling quality, but they require trained human coders and are time-intensive to apply. As a result, they are difficult to scale for routine supervision, frequent trainee feedback, or longitudinal monitoring of skill acquisition.

Computational approaches have sought to reduce this assessment burden by automating aspects of counseling skill and fidelity evaluation. Early NLP work on counseling skill assessment focused on classifying discrete counselor behaviors from individual utterances. For example, Pérez-Rosas et al. (2017b,a) used psycholinguistic and n-gram features to predict behaviors such as reflective listening, questions, and empathy, establishing links between language patterns and counseling quality. Building on this work, Pérez-Rosas et al. (2019) analyzed turn-level features such as word exchange, sentiment, and linguistic alignment, showing that higher-quality counselors exhibit more balanced exchange, more positive sentiment, and greater linguistic coordination. These findings motivate our analysis of linguistic patterns associated with reflective practice.

Prior work has also examined automated assessment at the response and session levels. Min et al. (2022) introduced PAIR, a prompt-aware ranking model for scoring reflective responses, and released the dataset used in this work. Other work has modeled broader session-level quality and adherence. For example, Flemotomos et al. (2021) developed a BERT-based model for CBT session evaluation, demonstrating the value of domain-adapted contextual representations, while Ardulov et al. (2022) modeled counseling sessions as dynamical systems, showing that temporal trajectories can be predictive of therapist competence.

Together, this literature shows that automated methods can support scalable assessment of counseling language, from utterance-level behavior coding to session-level fidelity evaluation. However, most existing approaches evaluate isolated responses, utterances, or sessions rather than modeling how trainees' reflective listening changes across repeated practice. We build on this work by taking a longitudinal perspective in a structured training setting. By representing trainee responses as residual embeddings and tracking their evolution across weeks, we provide a progression-oriented account of changes in reflective listening practice.

3 Dataset

The dataset used in this study is derived from a user study conducted by Min et al. (2022), in which the authors evaluated an automatic reflection scoring system in a real educational setting. The study was conducted in a graduate-level Motivational Interviewing (MI) training course and was deployed through a web-based learning platform.

As part of three weekly assignments, students were presented with counseling scenarios, or client prompts, designed to elicit reflective responses. For each prompt, students wrote a response and subsequently received automated scoring feedback. Prompt–response interactions generated during the study were securely collected and de-identified, and the original study followed the ethical oversight procedures described by Min et al. (2022). The resulting data consist of client prompts paired with student-generated responses collected over three weeks, capturing longitudinal practice data for each trainee. The full dataset includes 7,264 prompt–response pairs from 90 students.

For longitudinal analyses, we used data from 68 students who participated consistently throughout all three weeks, resulting in 6,196 total responses. The use of these de-identified data was reviewed by the Texas State University Institutional Review Board, which determined it to be exempt. Table 1 shows sample prompts and responses, and Table 2 presents week-level summary statistics.

4 Analyzing Trainee Response Change Over Time

We analyze responses to examine how trainees' language changes over time during reflective listening practice. We first isolate trainee-specific semantic signals via residual embeddings, then quantify week-to-week change using semantic similarity metrics, and finally characterize consistent and variable trajectories to better understand patterns of language adaptation.

Prompt	Response
I have no energy. The thought of working out now is out of the question. I used to bike and play tennis but that seems a lifetime ago. I would love to feel alive again, but I am just so tired all the time.	You are exhausted and thinking about working out seems impossible to you; however, you desire an alternative way to feel revitalized.
Of course, I have to quit at some point, but now is just not the time. I know what it's like to go through withdrawal... I was able to quit before, but with my wife losing her job and working overtime, I don't have the energy right now.	You are dealing with a lot of stress, so quitting smoking is not a priority right now.

Table 1: Sample trainee responses to counseling prompts.

	Word Statistics				
	Avg.	SD	Min	Max	#Responses
Week 1	23.23	14.41	3	165	1586
Week 2	22.90	14.81	3	152	2470
Week 3	25.62	14.49	3	113	2140
All	23.93	14.65	3	165	6196

Table 2: Dataset Statistics

4.1 Capturing Semantic Change via Residual Embeddings

Semantic variation over time can indicate how trainees adapt their responses toward reflective language. We quantify this variation by measuring semantic similarity across weeks. However, because all students respond to the same prompts within each week, similarity may be inflated by shared prompt semantics. To account for this, we compute a *residual embedding* for each response by removing prompt content at the embedding level.

$$\mathbf{r}_{s,w} = \mathbf{e}(\text{response}_{s,w}) - \mathbf{e}(\text{prompt}_{s,w}), \quad (1)$$

where $\mathbf{e}(\cdot)$ is a sentence embedding function, s indexes responses, and w indexes weeks. This formulation relies on approximate linear compositionality, such that subtracting prompt embeddings reduces shared semantic content and highlights response-specific framing. While imperfect, it provides a practical approximation of prompt-conditioned variation.

We use BGE-M3 (Chen et al., 2024) to encode prompts and responses, with L2-normalized embeddings. Residual embeddings are aggregated at the student–week level, and pairwise similarity across weeks is computed using cosine similarity, Euclidean distance, and Manhattan distance. Cosine similarity captures directional alignment (e.g., paraphrasing or stance consistency), while distance metrics reflect the magnitude of semantic change.

Table 4 shows higher cosine similarity and lower distances for Week 2–3 compared to Week 1–2, indicating increasing semantic alignment and reduced variability over time, which may signal the use of consistent linguistic structure while formulating reflections. Compared with the W1-W2 interval, the W2-W3 interval shows higher cosine similarity (0.74 to 0.77) and lower Euclidean and Manhattan distances, reflecting reduced variability in semantic representations. Together, these trends indicate a stabilization of response patterns, with less pronounced semantic shifts in successive weeks.

4.2 Lexical Progression Across Semantic Trajectories

To better understand differences in semantic trajectories, we examine representative students at the extremes of the prompt-adjusted cosine similarity distribution. We label students in the upper and lower quartiles as *consistent* and *variable* trajectory examples, respectively. These labels refer only to movement in prompt-adjusted embedding space, where higher cosine similarity indicates more consistent semantic positioning across weeks.

Table 3 shows sample responses from representative consistent and variable trajectories between Week 1 and Week 3. In these examples, the consistent trajectory remains compact and closely tied to the client's stated perspective, whereas the variable trajectory shows greater variation in structure and elaboration, including multi-clause responses and inferred emotional content.

We further examine lexical anchoring and reformulation using response length and novel-token rate. Novel-token rate is the proportion of response tokens that do not appear in the prompt and captures lexical departure from the prompt's surface wording.

As shown in Figures 1 and 2, response length increased from Week 1 to Week 2 and then stabilized,

Trajectory	Cosine	Week	Response
Consistent	0.79	W1	*"you know cigarettes are bad and you don't see a problem with vaping right now"*
		W2	*"you see more potential in her than just watching TV"*
		W3	*"good and quick are something you look for in eating meals."*
Variable	0.49	W1	*"You want to lose weight, but dieting has not worked for you in the past."*
		W2	*"Despite working hard, you feel frustrated with your experiences. You are motivated, but feel overwhelmed by the lack of results."*
		W3	*"You want to make beneficial dietary changes for your children, but their behavior makes it difficult to follow through."*

Table 3: Illustrative consistent and variable trajectories from Week 1 to Week 3 using residual embeddings. Cosine similarity is computed on aggregated prompt-adjusted residual embeddings; higher values indicate more consistent semantic positioning across weeks.

Interval	Cosine		Euclidean		Manhattan	
	Mean	SD	Mean	SD	Mean	SD
W1–W2	0.74	0.06	0.25	0.03	6.21	0.820
W2–W3	0.77	0.06	0.23	0.04	5.74	0.935
W1–W3	0.68	0.08	0.27	0.04	6.80	1.034

Table 4: Cohort-level residual-embedding similarity across weeks ($n = 68$ students with complete W1–W3 submissions).



Figure 1: Word count across weeks by trajectory group



Figure 2: Novel-token rate across weeks by trajectory group

Week	Mean	SD	Min	Max
Week 1	0.146	0.022	0.104	0.200
Week 2	0.166	0.022	0.112	0.242
Week 3	0.147	0.023	0.087	0.227

Table 5: Within-week internal consistency for students ($n = 68$). Higher values indicate greater semantic similarity across a student's responses within the same week.

while novel-token rate also increased from Week 1 to Week 2. This pattern indicates greater lexical departure from the prompt during the middle week. From Week 2 to Week 3, novel-token rate decreased, suggesting a shift back toward greater client-language anchoring. Together, these patterns are consistent with a balance between adding new reflective content and maintaining connection to salient client wording.

4.3 Examining Student-Level Internal Consistency Within Each Week

The previous analyses track semantic change across weeks. Here, we examine within-week variation to assess whether trainees rely on similar response patterns across prompts within the same week. This analysis helps distinguish longitudinal stabilization from repeated use of fixed response templates.

We quantify within-week consistency by computing the average pairwise cosine similarity between each student's responses to different prompts within the same week. Higher values indicate more similar responses across prompts, while lower values indicate greater prompt-specific variation.

As shown in Table 5, within-week similarity is low overall, with means ranging from 0.146 to 0.166. This suggests that trainees maintain substantial variation across prompts rather than relying on highly fixed templates. Similarity increases slightly in Week 2 and decreases again in Week 3, indicating modest fluctuation in within-week consistency across the training period.

Taken together, the longitudinal and within-week analyses suggest that trainees' reflective-listening

responses change over time without becoming rigidly templated. While the longitudinal analyses show increased semantic alignment and changes in lexical anchoring, the low within-week similarity indicates that trainees continue to adapt responses to individual prompts. This pattern is consistent with emerging reflective structure alongside prompt-specific reformulation.

5 Examining Alignment with Reflective Listening Practices

To examine whether the observed trajectory changes align with linguistic patterns relevant to reflective counseling practice (RQ2), we analyze trends in LIWC-based language features. Prior work in counseling dialogue analysis has shown that LIWC categories captured aspects of counseling language, including the use of emotion words (positive and negative emotion), directive markers (auxiliary verbs and certainty), and reflective framing, which includes second-person constructions, cognitive process words, affect, perception, and tentative language (Pérez-Rosas et al., 2019; Tausczik and Pennebaker, 2010). We normalize LIWC counts by response length and average feature values across responses within each week.

Table 6 shows modest and non-uniform changes across linguistic features over time. Most features exhibit relatively small shifts, suggesting that trainees maintain a broadly stable linguistic profile while their responses change in semantic space. Some features decrease in Week 2 and recover in Week 3, including positive emotion and tentative language, echoing the nonlinear pattern observed in the lexical analyses.

A subset of features shows directional changes that are consistent with reflective listening practice. Features that may index directive or closed framing, including auxiliary verbs and certainty terms, decrease from Week 1 to Week 3. In contrast, second-person constructions remain relatively stable, while broader reflective framing features show only modest change. These patterns suggest that trajectory-level changes are not driven by large shifts in surface-feature composition, but by more subtle reorganization of language use.

Overall, the LIWC analysis provides complementary evidence that semantic trajectory changes are accompanied by small but interpretable linguistic shifts. However, these features should be understood as surface indicators associated with reflective practice rather than direct measures of clinical competence.

Feature	W1	W2	W3
Emotion Words	7.74	7.44	7.97
Positive Emotion	3.39	2.84	4.21
Negative Emotion	4.35	4.60	3.76
Directive Markers	12.46	12.53	11.19
Auxiliary Verbs	11.36	11.35	10.39
Certainty	1.10	1.18	0.80
Reflective Framing	47.62	45.25	46.09
You	13.77	14.54	14.22
Cognitive Processes	17.32	16.32	16.78
Affect	8.03	7.75	8.23
Perception	5.63	4.38	4.03
Tentative Language	2.87	2.25	2.82

Table 6: LIWC features across Weeks 1–3.

6 Conclusion

In this work, we model reflective listening practice as a longitudinal process by representing trainee responses as trajectories in semantic embedding space. Using residual embeddings and similarity-based metrics, we identify structured changes in trainee language over a three-week counseling training study. Across analyses, we observe increased semantic alignment and reduced variability, patterns consistent with stabilization in trainees' language. Complementary linguistic analyses show that these trajectory patterns are accompanied by modest shifts in language use rather than large changes in surface-feature composition.

Although our findings do not directly measure clinical competence, they show that embedding-based trajectory representations can capture patterns of change that were interpretable in relation to lexical and LIWC-based analyses in this dataset. More broadly, this work highlights the potential of trajectory-based approaches for studying communication skill development and designing progression-aware feedback systems.

Limitations

This work has several limitations that should be considered while interpreting our findings. First, our dataset is drawn from a single instructional setting over a three-week period, which may limit the generalizability of the observed trajectory patterns. Longer training durations or more diverse educational contexts may exhibit different developmental dynamics. Second, our analyses rely on embedding-based representations of language, which provide an indirect proxy for changes in

language associated with reflective listening behavior. While residual embeddings help isolate response-specific variation, they depend on assumptions about linear compositionality and may not fully capture nuanced aspects of reflective listening. Third, although we interpret trajectory patterns as indicators of changes in reflective listening practice, our study does not directly measure clinical competence. The observed changes reflect structured variation in language use, but should not be taken as definitive evidence of improved counseling performance.

Finally, our linguistic analyses focus on aggregate feature trends, which may overlook more fine-grained discourse phenomena such as turn-taking dynamics or interactional context. Future work could incorporate richer conversational signals and longer-term trajectories to better characterize the development of reflective listening skills.

Acknowledgments

The authors thank the authors of the original dataset for making the study data available for this research. We are also grateful to the anonymous reviewers for their constructive feedback.

References

Victor Ardulov, Victor R. Martinez, Krishna Somandepalli, Allison Lahnala, Jill Burstein, and Shrikanth Narayanan. 2022. Local dynamic mode decomposition for assessing therapist competency in cognitive behavioral therapy sessions. In *Proceedings of the 23rd Annual Conference of the International Speech Communication Association (Interspeech)*, pages 3018–3022.

Jianlyu Chen, Shitao Xiao, Peitian Zhang, Kun Luo, Defu Lian, and Zheng Liu. 2024. BGE M3-Embedding: Multi-lingual, multi-functionality, multi-granularity text embeddings through self-knowledge distillation. *arXiv preprint arXiv:2402.03216*.

Nikolaos Flemotomos, Victor R. Martinez, Zhuohao Chen, Torrey A. Creed, David C. Atkins, and Shrikanth Narayanan. 2021. Automated quality assessment of cognitive behavioral therapy sessions through highly contextualized language representations. *PLOS ONE*, 16(10):e0258639.

William R Miller and Stephen Rollnick. 2012. *Motivational interviewing: Helping people change*. Guilford press.

Do June Min, Veronica Perez-Rosas, Ken Resnicow, and Rada Mihalcea. 2023. VERVE: Template-based ReflectiVE rewriting for MotiVational IntErviewing. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 10289–10302, Singapore. Association for Computational Linguistics.

Do June Min, Verónica Pérez-Rosas, Kenneth Resnicow, and Rada Mihalcea. 2022. PAIR: Prompt-aware margIn ranking for counselor reflection scoring in motivational interviewing. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 148–158, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Theresa B Moyers, Tim Martin, Jon M Houck, Paulette J Christopher, and J Scott Tonigan. 2009. From in-session behaviors to drinking outcomes: a causal chain for motivational interviewing. *Journal of consulting and clinical psychology*, 77(6):1113.

Theresa B Moyers, Lauren N Rowell, Jennifer K Manuel, Denise Ernst, and Jon M Houck. 2016. The motivational interviewing treatment integrity code (miti 4): rationale, preliminary reliability and validity. *Journal of substance abuse treatment*, 65:36–42.

Verónica Pérez-Rosas, Rada Mihalcea, Kenneth Resnicow, Satinder Singh, and Lawrence An. 2017a. Understanding and predicting empathic behavior in counseling therapy. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1426–1435, Vancouver, Canada. Association for Computational Linguistics.

Verónica Pérez-Rosas, Rada Mihalcea, Kenneth Resnicow, Satinder Singh, Lawrence An, Kathy J. Goggin, and Delwyn Catley. 2017b. Predicting counselor behaviors in motivational interviewing encounters. In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 1, Long Papers*, pages 1128–1137, Valencia, Spain. Association for Computational Linguistics.

Verónica Pérez-Rosas, Xinyi Wu, Kenneth Resnicow, and Rada Mihalcea. 2019. What makes a good counselor? learning to distinguish between high-quality and low-quality counseling conversations. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 926–935, Florence, Italy. Association for Computational Linguistics.

Siqi Shen, Veronica Perez-Rosas, Charles Welch, Soujanya Poria, and Rada Mihalcea. 2022. Knowledge enhanced reflection generation for counseling dialogues. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3096–3107, Dublin, Ireland. Association for Computational Linguistics.

Yla R Tausczik and James W Pennebaker. 2010. The psychological meaning of words: Liwc and computerized text analysis methods. *Journal of language and social psychology*, 29(1):24–54.

Ground Truths in Suicide Research: The Current State of AI-Based Suicide Detection in Social Media

Yaakov Ophir[1,2], **Ofri Hefetz**[3], **Refael Tikochinski**[1,4], **Kfir Bar**[3], **Shir Lissak**[5], **Shulamit Grinapol**[6,7], **Haya Wachtel**[6], **Eyal Fruchter**[3,8], **Roi Reichart**[5]

[1]Ariel University
[2]University of Cambridge
[3]Reichman University
[4]University College London
[5]Technion – Israel Institute of Technology
[6]Rambam Health Care Campus
[7]Maale Hacarmel Mental Health Center
[8]ICAR: Israel's Collective Action for Resilience

Abstract

Recent advances in artificial intelligence (AI) and social media data have led to growing optimism about the ability to detect suicide risk at scale. However, the empirical foundations of this work remain unclear. This article provides a synthesis of current research on AI-based suicide detection in social media, drawing on a recent umbrella review of 22 systematic reviews covering studies up to 2022, alongside an ongoing literature review extending the analysis to more recent work.

Across these sources, we identified 195 relevant studies, which are documented in a detailed supplementary dataset outlining their key characteristics and findings (see Supplementary Information). Analysis of these studies reveals consistent patterns, including rapid growth, concentration on a small number of platforms, reliance on textual and English-language data, and repeated use of similar datasets. Most importantly, the majority of studies rely on indirect labeling strategies that do not involve direct, individual-level validation of suicide risk. Instead, ground truth is typically inferred from observable features of online content, such as linguistic markers or community membership. As a result, the predictive task often shifts from identifying individuals at risk to classifying posts that contain suicidal or distress-related language.

These findings suggest that current advances in model performance should be interpreted with caution. Progress in this field is likely to depend less on improving model performance and more on ensuring that model predictions meaningfully correspond to suicide risk as it is experienced in real life.

1 Introduction

Suicide remains one of the leading causes of potentially preventable death worldwide, motivating sustained efforts to improve the early identification of individuals at risk. Yet for decades, progress in suicide prediction remained strikingly limited. A major meta-analysis spanning roughly 50 years of research concluded that the ability of traditional statistical approaches to predict suicidal behavior was only slightly better than chance, and that the field's established risk factors had, overall, changed little over time (Franklin et al., 2017).

More recently, however, the landscape appears to have shifted. Since the publication of that meta-analysis, a growing body of studies has reported substantially higher predictive performance, often using artificial intelligence (AI) and machine learning methods applied to data derived from social media and other digital environments (Ophir et al., 2022; Resnik et al., 2020; Schafer et al., 2021). This shift has been particularly visible within the computational mental health community, where venues such as CLPsych have played a central role in advancing the field, including through shared tasks that have provided standardized datasets and benchmark tasks for suicide risk detection (Chim et al., 2024; Macavaney et al., 2021; Zirikly et al., 2019). Taken together, these developments have created the impression that a major breakthrough in suicide risk detection may now be within reach.

Much of this optimism is linked to the convergence of two transformative developments: the rise of social media and the increasing capacity of AI systems to analyze large volumes of unstructured

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 244–249
July 4, 2026 ©2026 Association for Computational Linguistics

data (Ophir and Rosenberg, 2026). As social interactions have expanded into digital spaces, online platforms have come to function, at least in principle, as a kind of window into the psychological lives of users. Unlike traditional approaches to suicide risk assessment, which typically rely on clinical encounters or structured surveys, social media provides a large-scale, naturalistic, and often unsolicited record of individuals' thoughts, emotions, and experiences. This emerging form of "digital public expression" has been seen as offering a unique opportunity to identify signals of suicide risk that might otherwise remain hidden (Ophir et al., 2022). AI methods, in turn, make it possible to process this vast and heterogeneous stream of language in ways that traditional statistical approaches could not, for example by identifying complex patterns without requiring researchers to predefine all relevant variables in advance (Badian et al., 2023; Lissak et al., 2024).

Yet despite the rapid expansion of this literature, its empirical foundations remain difficult to evaluate. The very features that make social media data attractive, including its scale, naturalistic nature, and lack of predefined structure, also introduce substantial ambiguity regarding what is actually being measured. This ambiguity raises important questions about whether recent advances can be translated into practical tools for identifying suicide risk with sufficient accuracy: What types of data do these models rely on? How are suicidal states operationalized and labeled in practice? And what exactly do current AI systems detect when they are said to identify suicide risk?

The goal of the present article is to provide a synthesis of the current state of the literature on AI-based suicide detection in social media. This synthesis draws on two complementary sources: a large-scale umbrella review of the field (Abdelmoteleb et al., 2025) and an ongoing literature review of more recent studies. The studies included in this analysis are compiled in a detailed supplementary dataset that documents their key characteristics and findings (see Supplementary Information). Taken together, this synthesis is intended to provide a timely overview of the field at a stage where rapid methodological developments and ongoing questions call for closer examination of underlying assumptions and practices.

2 Analytical Approach

Our analysis drew on two complementary sources. The first focused on a 2025 umbrella review published in the Journal of Affective Disorders, titled "Evaluating the ability of artificial intelligence to predict suicide: A systematic review of reviews" (Abdelmoteleb et al., 2025). We applied a multiphase screening procedure. First, we screened the 22 reviews included in the umbrella review and identified eight that were relevant to the present analysis, namely those addressing the intersection of artificial intelligence, social media, and suicidality. We then examined the titles and abstracts of all primary studies included in these reviews to assess eligibility and remove duplicate records. Finally, we reviewed the full texts of the remaining studies to confirm their alignment with the focus of the present analysis. This rigorous screening process resulted in a final corpus of 69 primary studies examining AI-based prediction of suicide risk from social media. The key characteristics and findings of these studies were systematically extracted and organized for subsequent synthesis (see Supplementary Information).

The second source analyzed in the present overview is an ongoing systematic literature review examining empirical studies at the intersection of suicidality, artificial intelligence, and social media (protocol preregistered on OSF; Ophir, 2026). This review aims to provide a structured and critical synthesis of recent research in the field, with particular attention to how suicide risk is conceptualized, operationalized, and evaluated in practice. Studies are identified through a systematic search of major databases and screened for relevance to the three focal domains. Importantly, the review focuses on studies that explicitly describe their labeling strategies, allowing for a closer examination of the ground truth assumptions underlying model development. Data extraction emphasizes key dimensions such as data sources, annotation procedures, outcome definitions, and model evaluation practices. In the present article, we report preliminary findings from studies published from 2022 onward, thereby extending the temporal scope of the synthesis beyond the period covered by the umbrella review. As of March 2026, the ongoing review has identified 126 studies meeting the inclusion criteria for the period from 2022 onwards, with only minor changes expected as the review progresses (see Supplementary Information).

3 Key Findings

Across both sources, a consistent set of patterns emerges that sheds light on how current research on AI-based suicide detection in social media is conducted and what it ultimately captures.

3.1 Field Growth

The corpus of studies identified across both sources indicates a sharp increase in research activity, with a marked acceleration in recent years. Among the 195 studies included in the supplementary dataset, fewer than half were published before 2023, while the most recent two years alone (2024 to 2026) account for approximately 43% of all studies (n = 84). This pattern reflects a broader surge of interest in computational mental health research following the widespread availability of large language models and pre-trained transformer architectures. It also highlights the importance of examining the conceptual and methodological foundations of the field at a stage of rapid expansion.

3.2 Social Media Platforms

Social media platforms are not equally represented in this literature. Reddit alone accounts for nearly half of all studies in the corpus (n = 94; 48%), making it by far the most commonly used data source. Twitter or X is a distant second (n = 46; 24%), while the Chinese microblogging platform Sina Weibo accounts for most of the remaining non-English studies (n = 19; 10%). Including studies that combine platforms, Reddit appears in 113 studies and Twitter in 64, further underscoring their central role in the field.

This concentration likely reflects a combination of methodological and structural factors. Platforms such as Reddit and Twitter provide relatively accessible data, often through public interfaces or precompiled datasets, facilitating large-scale data collection. In addition, Reddit hosts dedicated mental health communities such as r/SuicideWatch and supports longer textual posts that are well suited to linguistic analysis. At the same time, these platforms may capture only a limited segment of online expression. Other widely used platforms, including Facebook and Instagram, are more embedded in everyday social interaction and may reflect broader patterns of interpersonal and emotional life that are highly relevant in the context of suicide, yet they remain largely absent from the literature.

3.3 Text-Based Data

Across the full corpus, 98% of studies (n = 191) relied exclusively on textual data. Only a small number of studies incorporated visual information alongside text, and none systematically included audio, video, or behavioral metadata. This pattern stands in contrast to contemporary social media use, where image and video content increasingly constitute primary modes of self-expression, particularly among younger populations. The extent to which signals of psychological distress are expressed through non-textual modalities, and whether text-based approaches fail to capture meaningful variation in such signals, remains largely unexplored.

3.4 Language Distribution

Another dimension of the corpus that warrants attention is the strong concentration on English-language data. A large majority of studies (78%; n = 153) were conducted exclusively in English, with Chinese the only other language represented to a meaningful extent (n = 20; 10%). Given that suicide rates, cultural idioms of distress, and patterns of platform use vary substantially across linguistic and cultural contexts, the generalizability of models trained primarily on English-language data remains uncertain. Although it is possible that studies using other languages exist but are less visible in the predominantly English-language scientific literature, this concentration nonetheless represents an important limitation for the field.

3.5 Dataset Reuse

The widespread availability of Reddit-derived data has contributed to a recurring pattern across studies. A substantial proportion of the literature relies on a repeated operationalization of suicidal status based on subreddit membership, treating posts from communities such as r/SuicideWatch as indicative of suicidal ideation and posts from general communities as its absence. A particularly prominent example is a publicly available dataset of approximately 232,000 Reddit posts labeled solely on the basis of subreddit membership, which appears across multiple independent studies without modification of its labeling scheme. Beyond this case, many studies construct new datasets using the same underlying logic, effectively reproducing the same operational definition across different samples.

As a result, a growing share of the literature is based on closely related data sources and recur-

ring definitions. Apparent improvements in model performance may therefore reflect repeated application to similar data structures rather than independent accumulation of evidence. The implications of this pattern for how suicide risk is defined and measured are considered in the final finding.

3.6 Ground Truth

Perhaps the most consequential finding to emerge from this synthesis concerns how suicidal states are operationalized and labeled across studies. A systematic examination of labeling practices indicates that most studies rely on indirect proxies rather than externally validated assessments of individuals. Expert annotation of posts, in which clinicians or trained raters evaluate textual content, was employed in a substantial proportion of studies. While more rigorous than simple proxy labeling, this approach remains a judgment about language rather than about the psychological state of the individual who produced it.

Direct clinical validation is rare. Only 14 studies (7.2%) established ground truth through individual-level assessment. These studies include (i) those using validated self-report instruments, (ii) those relying on self-reported behavioral outcomes such as suicide attempts, (iii) a small number employing clinically rigorous tools such as the Columbia Suicide Severity Rating Scale, and (iv) a few alternative approaches using non-standard or continuous measures. Unlike the broader literature, these studies define outcomes at the level of the individual rather than the post. Model performance in this subset is consistently lower, reflecting the greater difficulty of detecting suicide risk compared to classifying patterns of online expression.

Taken together, these findings indicate that the majority of studies rely on labeling strategies that do not involve direct, individual-level validation of suicide risk. The implications of this pattern are considered in the Discussion.

4 Discussion

The present synthesis provides a structured overview of the rapidly expanding literature on AI-based suicide detection in social media. Across both sources, several consistent patterns emerge, including the concentration of studies in recent years, the reliance on a limited set of social media platforms, the predominance of text-based data, and the repeated use of similar datasets and operational definitions. Taken together, these findings suggest that the apparent growth of the field has been accompanied by a degree of methodological convergence, raising important questions about the diversity and independence of the underlying evidence base.

The most consequential implication of these patterns concerns the nature of the prediction target itself. Most studies rely on labeling strategies that do not involve direct, individual-level validation of suicide risk, with ground truth inferred from observable features of online content such as self-disclosure, linguistic markers, or community membership. As a result, the predictive task often shifts from identifying individuals at risk to classifying posts that contain suicidal or distress-related language. Models may therefore learn patterns of expression associated with particular online environments rather than indicators of underlying psychological states. This concern aligns with earlier critical reviews of predictive approaches to mental health in social media, which have highlighted persistent challenges in construct validity, particularly in ensuring that computational measures correspond to clinically meaningful mental health constructs (Chancellor and De Choudhury, 2020).

This shift has direct implications for the interpretation of model performance. High accuracy in detecting labeled outcomes does not necessarily indicate successful identification of suicide risk, but may instead reflect the consistency of linguistic patterns within the data. Moreover, when ground truth is defined at the level of observable expression, models are inherently limited in their ability to detect individuals who experience suicidal ideation but do not express it explicitly online (Ophir et al., 2022). Evidence from studies that incorporate external clinical validation further suggests that suicide risk may be reflected in more subtle linguistic patterns rather than explicit expressions of suicidality, underscoring the limitations of relying solely on post-level labeling (Lissak et al., 2024; Ophir et al., 2020).

Beyond the question of ground truth, the findings also point to broader limitations in the current evidence base. The concentration of studies on a small number of platforms, the reliance on English-language data, and the near-exclusive focus on textual modalities all raise questions about the generalizability of current models. Similarly, the repeated use of shared datasets and operational definitions may contribute to an appearance of cumulative progress that does not necessarily reflect inde-

pendent validation across diverse contexts. These patterns are consistent with a recent dataset-centric review in computational mental health, which highlights systematic trade-offs between scale, accessibility, and clinical validity, as well as the dominance of a limited set of data sources and labeling strategies across studies (Gong et al., 2026).

5 Limitations

Several limitations of the present study should be noted. The current synthesis does not constitute a formal systematic review, and the ongoing review on which it partly relies is still in progress. As a result, the number of included studies may change, and some of the patterns described here should be considered preliminary. In addition, the analysis is limited to studies accessible through the selected sources and may underrepresent work published in other languages or venues.

6 Conclusion

Future research should aim to address these gaps by expanding the range of data sources, incorporating multimodal signals, and, critically, developing approaches to ground truth that are more closely aligned with clinically validated assessments of suicide risk. Such approaches may include the use of validated instruments such as the Columbia Suicide Severity Rating Scale (C-SSRS) (Posner et al., 2011) and the Beck Scale for Suicide Ideation (BSS) (Beck et al., 1979), structured clinical interviews, linkage to medical records, and documentation of clinically significant outcomes such as psychiatric hospitalization or suicide attempts. Future research may also benefit from greater attention to cultural and linguistic diversity in the expression of psychological distress, given that norms surrounding emotional disclosure and self-expression differ substantially across societies and online environments. Addressing these challenges may also help clarify what current AI systems are actually capable of detecting and under what conditions they can contribute meaningfully to suicide prevention efforts. Ultimately, progress in this field will depend less on improving model performance and more on ensuring that model predictions meaningfully correspond to suicide risk as it is experienced in real life.

7 Supplementary Information

The studies included in this synthesis are compiled in a detailed supplementary dataset that documents their key characteristics and findings (see Supplementary Information).

References

S. Abdelmoteleb, M. Ghallab, and W. W. IsHak. 2025. Evaluating the ability of artificial intelligence to predict suicide: A systematic review of reviews. *Journal of Affective Disorders*, 382:525–539.

Y. Badian, Y. Ophir, R. Tikochinski, N. Calderon, A. B. Klomek, E. Fruchter, and R. Reichart. 2023. Social media images can predict suicide risk using interpretable large language-vision models. *The Journal of Clinical Psychiatry*, 85(1):50516.

A. T. Beck, M. Kovacs, and A. Weissman. 1979. Assessment of suicidal intention: The scale for suicide ideation. *Journal of Consulting and Clinical Psychology*, 47(2):343–352.

S. Chancellor and M. De Choudhury. 2020. Methods in predictive techniques for mental health status on social media: a critical review. *npj Digital Medicine*, 3(1):43.

J. Chim, A. Tsakalidis, D. Gkoumas, D. Atzil-Slonim, Y. Ophir, A. Zirikly, P. Resnik, and M. Liakata. 2024. Overview of the clpsych 2024 shared task: Leveraging large language models to identify evidence of suicidality risk in online posts. In *Proceedings of the CLPsych 2024 Workshop*, pages 177–190.

J. C. Franklin, J. D. Ribeiro, K. R. Fox, K. H. Bentley, E. M. Kleiman, X. Huang, K. M. Musacchio, A. C. Jaroszewski, B. P. Chang, and M. K. Nock. 2017. Risk factors for suicidal thoughts and behaviors: A meta-analysis of 50 years of research. *Psychological Bulletin*, 143(2):187–232.

Z. Gong, C. Dai, B. Ma, M. Ma, M. Sharma, T. Q. On, M. Morparia, B. Enos, Y. Yu, and P. Resnik. 2026. A survey on mental health datasets and resources. *arXiv preprint*.

S. Lissak, Y. Ophir, R. Tikochinski, A. Brunstein Klomek, I. Sisso, E. Fruchter, and R. Reichart. 2024. Bored to death: Artificial intelligence research reveals the role of boredom in suicide behavior. *Frontiers in Psychiatry*, 15:1328122.

S. Macavaney, A. Mittu, G. Coppersmith, J. Leintz, and P. Resnik. 2021. Community-level research on suicidality prediction in a secure environment: Overview of the clpsych 2021 shared task. In *Proceedings of CLPsych 2021*, pages 70–80.

Y. Ophir. 2026. Systematic review protocol: Ai-based suicide detection in social media. https://doi.org/10.17605/OSF.IO/ZCW8N.

Y. Ophir and H. Rosenberg. 2026. The technological revolution in mental health: opportunities, challenges, and practical recommendations. *Humanities and Social Sciences Communications*, 13(1):1–9.

Y. Ophir, R. Tikochinski, C. S. C. Asterhan, I. Sisso, and R. Reichart. 2020. Deep neural networks detect suicide risk from textual facebook posts. *Scientific Reports*, 10(1):16685.

Y. Ophir, R. Tikochinski, A. Brunstein Klomek, and R. Reichart. 2022. The hitchhiker's guide to computational linguistics in suicide prevention. *Clinical Psychological Science*, 10(2):212–235.

K. Posner, G. K. Brown, B. Stanley, D. A. Brent, K. V. Yershova, M. A. Oquendo, and 1 others. 2011. The columbia–suicide severity rating scale: Initial validity and internal consistency findings from three multisite studies with adolescents and adults. *American Journal of Psychiatry*, 168(12):1266–1277.

P. Resnik, A. Foreman, M. Kuchuk, K. Musacchio Schafer, and B. Pinkham. 2020. Naturally occurring language as a source of evidence in suicide prevention. *Suicide and Life-Threatening Behavior*, 51(1):88–96.

K. M. Schafer, G. Kennedy, A. Gallyer, and P. Resnik. 2021. A direct comparison of theory-driven and machine learning prediction of suicide: A meta-analysis. *PLOS ONE*, 16(4):e0249833.

A. Zirikly, P. Resnik, O. Uzuner, and K. Hollingshead. 2019. Clpsych 2019 shared task: Predicting the degree of suicide risk in reddit posts. In *Proceedings of the Sixth Workshop on Computational Linguistics and Clinical Psychology*, pages 24–33.

Language-Based Detection of Adherence to Evidence-Based Psychotherapy Scripts

Samuel T. Campione[1], Elizabeth C. Stade[1], Stefanie T. LoSavio[2], Shreya Singhvi[1], William Xuan[1], Phi Long Bui[3], Maria Martin Lopez[1], Shashanka Subrahmanya [1], Bailee B. Schuhmann[2], Courtney B. Worley[4], Shannon Wiltsey Stirman[1,5], Johannes C. Eichstaedt[1,6], H. Andrew Schwartz[3],

[1]Stanford University, [2]University of Texas Health Sciences Center at San Antonio, [3]Vanderbilt University, [4]U.S. Department of Veterans Affairs, [5]National Center for PTSD, VA Palo Alto Health Care System, [6]INSEAD

Correspondence: campione@stanford.edu

Abstract

Some psychotherapies, such as written exposure therapy for posttraumatic stress disorder, utilize "scripts" during parts of treatment, but verifying script adherence to ensure engagement of key mechanisms of change is a time-consuming step for therapy supervisors. Here, we formalize therapy script adherence as an NLP task, and evaluate several simple (text similarity) and more complex (few-shot LLM) approaches. Over 351 annotated therapist utterance-script pairs, we find text similarity approaches to be highly competitive with LLMs and produce fewer false positives. ROUGE-L recall achieves $F1 = 0.973$, and BLEU achieves $F1 = 0.972$ with full precision and zero false positives. GPT-5.2 achieves $F1 = 0.935$ and GPT-4o-mini achieves $F1 = 0.876$. Given that the text similarity techniques are multiple orders of magnitude less complex, our results underscore the ability of simpler NLP techniques to still be effective in the age of LLMs for tasks that are more textual in nature and suggest their utility in clinical training for giving supervisees rapid, privacy-preserving feedback on their delivery of evidence-based psychotherapy scripts.

1 Introduction

Mental health disorders are a leading cause of disability worldwide (GBD 2019 Mental Disorders Collaborators, 2022), and access to evidence-based psychotherapy (EBP) is limited by a shortage of trained providers (Kazdin and Blase, 2011). High-quality training improves implementation of EBPs and patient outcomes (Herschell et al., 2010), but traditional training in EBPs is difficult to scale. Digital training systems are emerging that allow therapists to practice delivering a complete course of an EBP with large language models (LLMs) prompted to behave as a patient receiving that treatment (Stade et al., 2025).

These digital training platforms are an ideal environment for providing high-quality feedback on clinicians' treatment delivery as they learn outside of traditional therapy consultation time. A core component of this feedback is assessing treatment fidelity, or how closely the clinician delivered the treatment as designed. However, fidelity monitoring is extremely time and cost-intensive, and there is a clear need for automated approaches.

Written exposure therapy (WET), an EBP for posttraumatic stress disorder (PTSD), is one such treatment well-suited for this type of digital training system and automated fidelity assessment. One aspect of WET's design is the delivery of prescribed language, or "scripts," to the patient word-for-word at specific points in the session. Thus, detecting verbatim script usage is important for assessing adherence to WET protocol.



Figure 1: Illustrative example of a clinician delivering a script to a simulated patient. Green highlighting indicates script usage detected. The reference script is on the right.

Detecting correct script usage is not straightforward. As therapists embed these scripts into conversation, natural variations arise. An effective detection method should be able to distinguish between adherent verbatim script delivery and non-adherent paraphrasing or inclusion of proscribed content.

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 250–257
July 4, 2026 ©2026 Association for Computational Linguistics

We frame script adherence detection as a binary classification task: given a therapist's utterance and a reference script, did the therapist use the script? In this study, we evaluate several text similarity metrics (ROUGE, BLEU) used in a threshold-based classifier and compare them to LLMs (GPT 5.2 and GPT 4o mini) on 351 therapist utterance-script pairs. We find that the simpler text similarity methods are comparable or superior to LLMs, and each approach has clear error patterns.

Our contributions include (1) formalizing verbatim script adherence detection in written exposure therapy as an NLP task, (2) demonstrating the potential of simple NLP methods for supporting supervisory feedback on script adherence in clinical training contexts, (3) providing evidence that text similarity methods may outperform LLM approaches and produce fewer false positives, and (4) showing that error patterns are linked to the differences between lexical and semantic similarity approaches.

2 Background

Written Exposure Therapy WET has a brief format and protocolized approach (Sloan and Marx, 2025), which makes it well-suited for this type of digital training system. Specifically, WET is a five-session intervention that targets avoidance through repeated exposure to the patient's traumatic event through structured writing sessions. Each session, the clinician completes a list of specific tasks as they guide a patient to write a narrative of their most distressing traumatic event.

Other EBPs provide content for clinicians to deliver in their own words; however, WET is unique in that scripts in the protocol are meant to be delivered to the patient word-for-word, with some trauma-specific details personalized to the patient. In Session 1 of WET, clinicians deliver five scripts at various points in the session. These scripts should be read verbatim because they contain carefully written language that engages key mechanisms of change in the patient that yield therapeutic value.

Treatment Fidelity Treatment fidelity is a core concern in delivery of evidence-based psychological practices (Perepletchikova and Kazdin, 2005). Greater treatment fidelity leads to better treatment outcomes (Farmer et al., 2017; Stirman et al., 2021). Manual fidelity coding requires trained coders to rate therapists' delivery utterance by utterance through session transcripts or recordings, a process that is time-intensive and faces scalability issues (Bacon et al., 2021; Worley et al., 2020).

Some recent advances in automated approaches include transformer models on the Lyssn platform to code fidelity to components of cognitive behavioral therapy (Coleman et al., 2024), and prototypes of LLM-assisted assessment of therapist adherence to cognitive processing therapy protocol (Held et al., 2025). Prior work focuses on broader clinical competence areas rather than narrow lexical tasks such as detection of verbatim script usage.

Text Similarity The task of determining whether a therapist's utterance contains a reference script maps nicely onto lexical text similarity metrics used in NLP evaluation. At first glance, this task may appear easily solvable with exact string-matching algorithms (e.g., Rabin-Karp, Knuth-Morris-Pratt), but these methods would fail to identify adherent script usages that contain appropriately personalized content, interspersed comments, or typical human spelling and punctuation errors. ROUGE (Recall-Oriented Understudy for Gisting Evaluation; Lin 2004) and BLEU (Bilingual Evaluation Understudy; Papineni et al. 2002) were developed for evaluating machine-generated summaries and machine translations. However, at a basic level both measure text overlap between a candidate text and a reference text (or a therapist utterance and a therapy script, respectively). In realistic clinical training settings, these metrics are more robust to the natural variation and personalization expected during script delivery in WET.

ROUGE-1 and ROUGE-2 measure unigram and bigram recall of the candidate text against the reference text. Here, recall is the proportion of the utterance's n-grams that appeared in the reference script. ROUGE-L measures the longest common subsequence (LCS) between the candidate and the reference. LCS is a classic NLP algorithm with well-known applications in bioinformatics and differencing tools. BLEU measures n-gram precision of the candidate against the reference, with a brevity penalty on shorter candidate texts. Here, precision is the proportion of the utterance's n-grams that appeared in the reference script.

In recent work, lexical metrics like ROUGE and BLEU have been replaced with LLM-based judges which can measure semantic equivalence (Kocmi and Federmann, 2023). Script adherence detection asks the opposite question – whether specific words

Category	Description	Example	Adherence
Verbatim delivery	Script read word-for-word with correct personalization where required; minor typos, lead-ins, and lead-outs are permitted	"Survivors of traumatic experiences often go through changes in their physical reactions..."	Yes
Verbatim with personalization issues	Script read word-for-word but with missing, insufficient, or unapproved personalization	"Survivors of assault and other traumatic experiences often go through changes..."	Yes
Partial delivery	Portions of script omitted; retained portions read verbatim (ranging from minor to extreme omission)	[first half of script delivered, second half skipped entirely]	Yes
Paraphrase	Script meaning conveyed in the therapist's own words without verbatim delivery	"After a traumatic event, survivors often experience changes in their thoughts, emotions, and behaviors..."	No
Non-script	Off-script content, general therapy conversation, or thematically related but non-script material	"What do you do when you feel those emotions or experience the flashbacks?"	No

Table 1: Script adherence categories with examples

appeared in the text, not whether the meaning was preserved. Thus, these classic lexical approaches are a natural fit.

3 Data

Scripts Session 1 of written exposure therapy contains five scripts that clinicians deliver at specific points during the session. Table 2 shows each script and its length. The scripts range from 67 to 417 words and cover distinct components of the treatment (e.g., psychoeducation, rationale for treatment, instructions for the writing task). Two of the five scripts (General Writing Instructions and Session 1 Writing Instructions) contain placeholders where clinicians should insert details personalized to the patient. The remaining three scripts are delivered fully verbatim.

Scripts	Words
Psychoeducation about PTSD	246
Avoidance + Introducing WET	417
General Writing Instructions	176
Session 1 Writing Instructions	242
End of Session Instructions	67

Table 2: WET script name and word count.

There are varying types of adherent script delivery in WET. These categories were developed in consultation with a written exposure therapy expert trainer (SL), who identified distinct categories of adherence reflecting prototypical therapist behavior during script delivery portions. Adherent categories include verbatim delivery, verbatim delivery with personalization issues, and partial delivery. Non-adherent categories include paraphrasing and off-script content. See Table 1

Dataset We use data from transcripts of two clinical psychologists delivering Session 1 of WET using TherapyTrainer, a digital training platform that allows clinicians to practice delivering full sessions of WET in a chat with a simulated patient. Transcript data was formatted into 145 unique pairs of therapist utterances and reference scripts by pairing each utterance with each of the five scripts. This included negative examples formed by pairing utterances with other WET scripts, which share therapeutic language and thus pose challenging cases of lexical overlap. This approach reflects how an automated fidelity monitoring system would operate, with each utterance evaluated against every script to detect usage. Two WET experts with prior treatment fidelity training (BBS and CW) labeled each utterance in the transcripts as adherent or non-adherent to Session 1 scripts. Their inter-rater reliability was perfect ($\kappa = 1.00$), unsurprising for the simplicity of this narrowly-defined labeling task.

In high-fidelity delivery of WET, each script is delivered once per session, making examples of script usage relatively sparse despite the richness of the transcript data. This scarcity is compounded by the time-intensive nature of manual labeling. To ensure adequate coverage of linguistic variation and to introduce additional challenging cases, we augmented the dataset with examples of script usage exhibiting varying degrees of adherence (i.e., verbatim delivery, verbatim with personalization issues, partial delivery, paraphrasing; see Table 1) for each of the five scripts. These prototypical examples were authored and labeled by two clinicians trained in WET (BBS and ECS), yielding



Figure 2: Overview of classification methods

206 additional therapist utterance–script pairs.

The final dataset contained 93 adherent (26%) and 258 non-adherent (74%) therapist utterance-script pairs with ground-truth script adherence labels. Average therapist utterance length is 122 words ($SD = 115$).

4 Methods

4.1 Text Similarity Based Classification

Given a reference script and a clinician utterance, we applied three steps: preprocessing, text similarity calculation, and threshold-based classification (Figure 2).

Preprocessing Both the reference script and the clinician utterance were normalized and tokenized. Each text similarity metric applied its own preprocessing through its respective Python library: the ROUGE metrics lowercase and strip punctuation, while BLEU preserves case and treats punctuation as separate tokens.

Text Similarity Calculation We computed text similarity between the reference script and the clinician utterance using four metrics. ROUGE-1 and ROUGE-2 recall measured the proportion of the script's unigrams and bigrams that appear in the utterance. ROUGE-L recall measured the proportion of the script recovered from the longest common subsequence in the utterance. BLEU measured the proportion of the utterance's n-grams (up to 4-grams) that appeared in the script, with a brevity penalty for short candidates. All four metrics produced scores ranging from 0 to 1 for each script-utterance pair, with higher values indicating greater textual overlap.

Classification Using Threshold To classify a clinician utterance as adherent the similarity score must have exceeded a decision threshold. We selected this threshold using 5-fold stratified cross-validation grouped by script. We stratified folds by script to ensure that utterances linked to the same script did not appear in both the training set and test set in a fold and prevent data leakage across folds. This design also allowed us to test whether the threshold generalized across scripts of different lengths and content.

Within each fold, a grid search was performed over 100 values from 0 to 1 on the training set only. The threshold that maximized training set *F1* was selected and applied to that fold's held-out test set – a threshold was optimized separately within each fold. This process repeated for each fold, and we computed final performance metrics by aggregating predictions from the held-out test sets. We evaluated each text similarity metric independently using this cross-validation procedure.

4.2 LLM Baselines

We compared against GPT-5.2 (OpenAI, 2026), a leading reasoning model, and GPT-4o-mini (OpenAI, 2024), a smaller model commonly used in annotation tasks (Tan et al., 2024). We prompted

each model with few-shot examples and instructions to determine whether a clinician utterance contains adherent script usage and return a binary label. For few-shot learning, we selected four examples spanning adherence categories shown in Table 1, including verbatim delivery, partial delivery, paraphrasing, and non-script content. We specified that some word substitutions and minor typographical errors are acceptable, but paraphrasing or unrelated therapy content constitutes non-adherence. To account for stochasticity, each utterance-script pair was evaluated across 20 independent runs. The final prediction was determined by majority vote.

4.3 Evaluation

We evaluate all methods against ground-truth adherence labels established in dataset creation. For the text similarity methods, we report performance metrics aggregated across held-out test folds from each metric's cross-validation process. For the LLM baselines, we report majority-vote metrics across 20 runs. We compare methods using McNemar's exact test.

5 Results

Classification performance of all methods is reported in Table 3. We include precision (how often detected script usage is correct), recall (how often true script usage is detected), and *F1* (the harmonic mean of the precision and recall).

Method	Precision	Recall	F1
ROUGE-L	0.989	0.957	0.973
BLEU	1.000	0.946	0.972
ROUGE-2	0.967	0.957	0.962
GPT-5.2	0.877	1.000	0.935
ROUGE-1	0.930	0.860	0.894
GPT-4o-mini	0.880	0.871	0.876

Table 3: Performance metrics. Text similarity metrics report held-out test fold metrics from 5-fold cross-validation. LLM methods report majority-vote metrics across 20 runs.

Text Similarity Metrics Three of the four text similarity metrics had higher *F1* than both LLM baselines. ROUGE-L had the highest *F1* (0.973) with a precision of 0.989 and a recall of 0.957. BLEU had comparable F1 (0.972) with full precision and zero false positives, though with slightly lower recall (0.946). ROUGE-2 followed closely (*F1* = 0.962), and ROUGE-1 was the weakest text similarity metric (*F1* = 0.894). The top text similarity metrics achieved near-perfect precision, rarely misclassifying non-adherent utterances as adherent.

LLM Baselines The LLM baselines showed a different pattern. GPT-5.2 achieved perfect recall, detecting every instance of script usage in the dataset, but produced 13 false positives, yielding *F1* = 0.935 and a precision of 0.877. GPT-4o-mini achieved lower overall performance (*F1* = 0.876), with errors in both directions (11 false positives, 12 false negatives). The two approaches thus exhibited a clear tradeoff: text similarity metrics favored precision while LLMs favored recall.

Statistical Comparisons The top two text similarity metrics, ROUGE-L and BLEU, both significantly outperformed GPT-4o-mini (McNemar's exact test, both $p < .001$). Neither ROUGE-L nor BLEU significantly outperformed GPT-5.2, though the text similarity and LLM approaches achieved comparable *F1* through markedly different error profiles, which we address in the "Error Analysis" section that follows.

6 Error Analysis

The text similarity metrics and LLM baselines showed distinct error profiles (Table 4).

Method	False Positives	False Negatives
ROUGE-L	1	4
BLEU	0	5
ROUGE-2	3	4
GPT-5.2	13	0
ROUGE-1	6	13
GPT-4o-mini	11	12

Table 4: False positive and false negative error breakdown of each approach.

Text Similarity Metrics Across all four text similarity metrics, each false negative was a case of partial delivery, in which the clinician read only a portion of the script (i.e., used only a fraction of the script, skipping entire paragraphs). Because so much text is missing, the similarity metrics do not cross the decision threshold even though the delivered portions of the script were verbatim. None of the text similarity metrics misclassified a fully verbatim or near-verbatim case. Paraphrases and unrelated therapy content never produced false positives

for ROUGE-L or BLEU – this follows logically from the underlying algorithms, as paraphrased content shared few n-grams or subsequences with the reference script.

LLM Baselines GPT-4o-mini produced errors in both directions. The 12 false negatives split into two failure modes. One was the misclassification of appropriately personalized scripts (6 cases). Clinicians read the script verbatim but replaced a few generic placeholders like "your trauma" with specific terms such as "the accident" or "the suicide," or added personalized examples of sights, sounds, smells, thoughts, or emotions to the script. This is considered high-quality clinical behavior, and the written exposure therapy protocol instructs therapists to personalize these segments of the script. The remaining false negatives were partial script deliveries (6 cases). The 11 false positives were all paraphrases or cases of thematically related but non-script content. The LLM detected semantic similarity and over-classified, treating utterances that conveyed only the script's meaning as verbatim delivery. This is the core failure mode one might expect from a model trained to encode meaning rather than surface form.

GPT-5.2 eliminated the false negative problem entirely (zero false negatives) but did not fix the false positives. The 13 false positives were paraphrases (6 cases) and unrelated therapy content (7 cases). This suggests even a more advanced LLM could not distinguish paraphrased content from verbatim delivery.

The core distinction here is that text similarity metrics failed only in ambiguous cases (extreme omission), whereas LLMs failed to distinguish between paraphrase and verbatim content.

7 Discussion

Results indicated that simple algorithms for text matching were competitive with frontier LLMs on a clinically meaningful task. Script usage detection superficially may appear to require a deep level of language understanding. The method must handle personalization, minor rewordings, partial delivery, inserted conversational speech, and the full variability of how clinicians deliver script content. However, the underlying question is lexical (whether specific words appeared in a specific order), and simple methods designed around that lexical question performed better.

The error profiles shed light on the strong performance of the text similarity approaches. Lexical text similarity algorithms operate on surface text, so they never mistake paraphrased text for verbatim delivery (paraphrased content shares only scattered single-word overlaps with the scripts). However, they fail to recognize partial delivery in some cases (e.g., a clinician reading 40% of a script verbatim and skipping the rest is still considered script use). LLMs operate on semantic meaning, which, in principle, should help them recognize personalized script deliveries that include appropriate patient-specific substitutions. However, the smaller LLM, GPT-4o-mini, misclassified these as non-adherent. Both LLMs also struggle with distinguishing between paraphrased scripts and verbatim scripts – which may arguably be what they are optimized to do. This suggests a mismatch for the task; LLMs are optimized to capture semantic equivalence while this task requires sensitivity to exact lexical text.

Although ROUGE-L and BLEU did not significantly outperform GPT-5.2, the approaches exhibited qualitatively different error profiles. False positives are the costlier error for this task. In a clinical training setting, a false negative flags a correct delivery for unnecessary review. By contrast, a false positive tells a clinician they delivered the script correctly when they did not, thus the clinician does not receive important feedback to help them learn how to deliver the treatment to patients as intended. The low false positive rates of the text similarity approaches reflect their conservative lexical design. They accept only utterances that closely match the script at the word level.

Our findings concern a specific type of task and do not imply that a lexical approach is universally preferable for fidelity, nor do they assess the competence aspect of treatment fidelity. For clinical behaviors that require understanding intent or meaning (e.g., assessing whether a therapist effectively validated a patient's emotions, or whether Socratic questioning was used), LLMs may be the better tool. There are several natural directions for future work. Structured testing and comparison of prompts and LLM models (e.g., different frontier models, reasoning vs. non-reasoning models) may reveal more advanced LLM capabilities. An agentic architecture in which an LLM agent selects an NLP method to apply could combine the strengths of both LLM and simpler, lexical approaches. Expanding beyond binary classification to multiple levels of adherence (e.g., verbatim, partial, para-

phrased) would likely better reflect how clinicians actually use scripts. While evaluated on written exposure therapy, in principle, the text similarity approaches presented here are not specific to this protocol. Such text similarity metrics might be tested on other protocolized therapies with verbatim script segments. We hypothesize that this method could also be adapted in reverse; for instance, in protocols like cognitive processing therapy, where therapists are expected to deliver content in their own words, a high text similarity score could flag insufficient personalization.

As this work used transcripts from clinicians practicing with simulated patients, an important next step is further validation with more naturalistic therapy transcripts. In therapy sessions with real patients, script delivery would likely include some areas of repetition or other delivery adjustments in response to the patient.

For detecting verbatim script delivery in a protocolized treatment, classic NLP text similarity methods are competitive and may even outperform LLMs, offering simplicity, interpretability, speed, and fewer false positives. Further, they do not require sharing HIPAA-protected data with external providers. Simple, interpretable language-based methods are appropriate for detecting therapist adherence to standardized language, a key aspect of therapist fidelity in some evidence-based treatments.

Limitations

Due to the resource-intensity of labeling transcripts, our dataset consisted of a limited number of therapist utterances. Further the data may not fully represent real-world clinical delivery variability since the transcripts come from practice sessions with a simulated patient rather than naturalistic therapy sessions. Additionally, the language data was provided by clinical psychologists and may be non-representative of therapists with other training backgrounds (e.g., social workers, counselors).

The evaluation was limited to a single treatment protocol, and we evaluated scripts from written exposure therapy Session 1 only; generalization to the remaining sessions or other treatments remains to be tested. We evaluated one LLM provider (OpenAI) on one prompt, thus other models or prompting strategies might yield different results. Finally, our method did not assess the quality of script personalization – it detected only whether the script was delivered, not whether personalization was appropriate.

Ethical Considerations

The dataset consisted of utterances from trained clinicians during encounters with simulated patients. The WET fidelity raters and the clinicians who provided the transcript data are all co-authors on this study. No patient data or actual therapy sessions were used. Therapy scripts were drawn from the published written exposure therapy protocol.

References

Katharine Bacon, Jane Marshall, Anna Caute, Katie Monnelly, Madeline Cruice, Corinne Moutou, and Celia Woolf. 2021. Treatment fidelity of technology-enhanced reading therapy (CommuniCATE) for people with aphasia. *International Journal of Language & Communication Disorders*, 56(6):1114–1131.

Jeremy J. Coleman, Jesse Owen, Jesse H. Wright, Tracy D. Eells, Becky Antle, Markessa McCoy, and Christina Signe Soma. 2024. Using artificial intelligence to identify effective components of computer-assisted cognitive behavioural therapy. *Clinical Psychology & Psychotherapy*, 31(6):e70023.

Courtney C. Farmer, Karen S. Mitchell, Kelly Parker-Guilbert, and Tara E. Galovski. 2017. Fidelity to the cognitive processing therapy protocol: Evaluation of critical elements. *Behavior Therapy*, 48(2):195–206.

GBD 2019 Mental Disorders Collaborators. 2022. Global, regional, and national burden of 12 mental disorders in 204 countries and territories, 1990–2019: a systematic analysis for the Global Burden of Disease Study 2019. *The Lancet Psychiatry*, 9(2):137–150.

Philip Held, Elizabeth C. Stade, Katherine Dondanville, and Shannon Wiltsey Stirman. 2025. Generative artificial intelligence in posttraumatic stress disorder treatment: Exploring five different use cases. *Journal of Traumatic Stress*, 38(5):813–820.

Amy D. Herschell, David J. Kolko, Barbara L. Baumann, and Abigail C. Davis. 2010. The role of therapist training in the implementation of psychosocial treatments: A review and critique with recommendations. *Clinical Psychology Review*, 30(4):448–466.

Alan E. Kazdin and Stacey L. Blase. 2011. Rebooting psychotherapy research and practice to reduce the burden of mental illness. *Perspectives on Psychological Science*, 6(1):21–37.

Tom Kocmi and Christian Federmann. 2023. Large language models are state-of-the-art evaluators of translation quality. *Preprint*, arXiv:2302.14520.

Chin-Yew Lin. 2004. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pages 74–81. Association for Computational Linguistics.

OpenAI. 2024. GPT-4o system card. Technical report.

OpenAI. 2026. OpenAI GPT-5 system card. Technical report.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. BLEU: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting on Association for Computational Linguistics*, ACL '02, page 311–318, USA. Association for Computational Linguistics.

Francheska Perepletchikova and Alan E. Kazdin. 2005. Treatment integrity and therapeutic change: Issues and research recommendations. *Clinical Psychology: Science and Practice*, 12(4):365–383.

Denise M Sloan and Brian P Marx. 2025. *Written exposure therapy for PTSD: A brief treatment approach for mental health professionals*, 2nd edition. American Psychological Association.

Elizabeth C. Stade, Johannes C. Eichstaedt, Debra L. Kaysen, Aadesh Salesha, Alanna Greenberger, Shreya Singhvi, and Shannon Wiltsey Stirman. 2025. TherapyTrainer: Using AI to train therapists in written exposure therapy. *Cognitive and Behavioral Practice*.

Shannon Wiltsey Stirman, Cassidy A. Gutner, Jennifer Gamarra, Michael K. Suvak, Dawne Vogt, Clara Johnson, Jennifer Schuster Wachen, Katherine A. Dondanville, Jeffrey S. Yarvis, Jim Mintz, Alan L. Peterson, Stacey Young-McCaughan, and Patricia A. Resick. 2021. A novel approach to the assessment of fidelity to a cognitive behavioral therapy for PTSD using clinical worksheets: A proof of concept with cognitive processing therapy. *Behavior Therapy*, 52(3):656–672.

Zhen Tan, Dawei Li, Song Wang, Alimohammad Beigi, Bohan Jiang, Amrita Bhattacharjee, Mansooreh Karami, Jundong Li, Lu Cheng, and Huan Liu. 2024. Large language models for data annotation and synthesis: A survey. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 930–957. Association for Computational Linguistics.

Courtney B. Worley, Stefanie T. LoSavio, Syed Aajmain, Craig Rosen, Shannon Wiltsey Stirman, and Denise M. Sloan. 2020. Training during a pandemic: Successes, challenges, and practical guidance from a virtual facilitated learning collaborative training program for written exposure therapy. *Journal of Traumatic Stress*, 33(5):634–642.

A Implementation

Experiments with text similarity required minimal compute, running on CPU and completed in less than a minute. The Python libraries used were `rouge-score 0.1.2` and `sacrebleu 2.6.0`. LLM services were accessed through Microsoft Azure OpenAI cloud services. GPT-4o-mini used temperature = 1.0, and GPT-5.2 used reasoning effort = low (temperature not configurable when reasoning is enabled). Code is available on GitHub.

B Prompt

```
# Instructions:
You are evaluating whether a specific script
was delivered verbatim or near-verbatim within
a user's message. The user's message may
contain additional speech before or after the
script. Your task is to determine whether the
script text appears within the message. Ignore
any surrounding content that is not part of
the script.

A match means the user read the script using
its actual words. The exact wording, or very
close to it, should be present somewhere in
their message. Minor typos, a few small word
substitutions, or some slight rewording are
acceptable. If they read part of the script
word-for-word but skipped other parts entirely,
that still counts as a match. Even extreme
omissions are acceptable as long as what they
did say uses the script's words.

A non-match means the user paraphrased the
script or only communicated the general idea
without using the scripted language. If they
restructure sentences, reorder information, or
use their own words instead of the script's
words, it's a non-match, even if the meaning
is accurate.

# Few shot examples
Script: {script1}
User message: {utterance1}
Response: {response1}

Script: {script2}
User message: {utterance2}
Response: {response2}

Script: {script3}
User message: {utterance3}
Response: {response3}

Script: {script4}
User message: {utterance4}
Response: {response4}

# Current case:
Script: {script}

Therapist's Message: {utterance}

Respond with only 1 (match) or 0 (non-match).
```

LLMs as Standardised Patients for Motivational Interviewing: How Faithful Are They?

Van Hoang[1,2] and **Eoin Rogers**[1] and **Robert Ross**[1]
[1]School of Computer Science, Technological University Dublin
[2]ML-Labs, SFI Centre for Research Training in Machine Learning, Ireland
van.hoang, eoin.rogers, robert.ross@tudublin.ie

Abstract

Recent advances in large language models (LLMs) have enabled the creation of highly realistic digital patients across a broad range of clinical scenarios, yet systematic evaluation of such simulations remains challenging due to a lack of standardised methodology. This paper investigates the faithfulness of LLM-simulated patients within motivational interviewing contexts. We directly compare the properties of data generated by simulated and human patients given identical profiles, rather than relying on subjective user experiences. Our findings reveal that while simulated and human patients produce semantically similar content and engage with comparable topics, their modes of expression differ substantially. LLM-simulated patients struggle to reproduce the full complexity of human behaviours and attitudes. While human patients exhibit a mix of positive and negative responses, LLM patients skew toward uniformly positive ones.

1 Introduction

User simulation, the modelling of user preferences and behaviours from observational data, has long been an active area of research, with applications spanning a wide range of domains (Ni et al., 2025). In clinical AI, this approach is applied to create digital patients, which can be used to train healthcare providers and evaluate dialogue systems.

Traditionally, in medical education, standardised, or simulated, patients are individuals carefully trained to portray real patients, giving students the opportunity to develop and be evaluated on clinical skills in a realistic setting (Flanagan and Cummings, 2023). As a widely adopted method, it offers valid and reliable assessment of both clinical and communication competencies across all levels of healthcare training (Plaksin et al., 2016). However, their large-scale implementation is constrained by high costs and the psychological burden placed on individuals repeatedly portraying mentally ill patients (Plaksin et al., 2016). Computer-based simulations have emerged as a scalable alternative. Recent advances in LLMs have enabled the development of highly realistic digital patients across diverse clinical scenarios, offering new opportunities for simulation-based medical education (Chu and Goodell, 2024; Zeng et al., 2025).

Additionally, researchers have advocated using simulated patients to evaluate conversational AI models for real-world applications (Wang et al., 2024a; Liao et al., 2024). Traditional dialogue systems are typically assessed by measuring utterance-level performance on held-out test sets. It is, however, fundamentally ill-suited for therapeutic contexts, where dialogue is inherently nuanced and demands contextual understanding. Unlike tasks with clear-cut answers, a single utterance can elicit a wide range of valid responses: experts have verified that even when predicted strategies diverge from ground-truth annotations, they can still align effectively with therapy principles and context (Sun et al., 2025). Simulated patients therefore offer a particularly promising framework for systematic, dialogue-level evaluation of conversational systems, enabling assessment that extends well beyond single-turn exchanges.

Despite their promise, the utility of LLM-based patient simulation hinges on whether simulated patients can faithfully and validly represent real human patients. Evaluating LLM-simulated patients has largely relied on user experience, whether from laypeople or domain experts, who converse with the simulation or review transcripts and rate dimensions such as satisfaction, coherence, realism, or learning outcomes (Ni et al., 2025; Zeng et al., 2025). Prior work suggests that LLM-generated utterances are natural, coherent (Galland et al., 2024), and perceived as human-like (Hämäläinen et al., 2023). Expert evaluations have further demonstrated LLMs' potential to authentically simulate

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 258–270
July 4, 2026 ©2026 Association for Computational Linguistics

mental health clients (Wang et al., 2024b; Steenstra et al., 2025), though the field still lacks validated and standardised assessment tools (Zeng et al., 2025).

This work therefore aims to assess how reliably LLM-based patient simulations can represent real patients in the context of motivational interviewing-centric dialogue systems. Rather than relying on subjective experience ratings, we evaluate simulated patients by directly comparing the data they produce against that of real human patients to identify key differences and similarities. Specifically, we operate under the assumption that a simulated patient is a faithful representation of a human patient if, given the same case vignettes, the properties of the data each generates are comparable. Using a motivational interviewing (MI) coaching dataset, we extract user profiles to instantiate LLM-based simulated patients, which then interact with MI systems to generate simulated conversations for comparison against real human data.

MI is a psychotherapeutic technique designed to foster motivation for behavioural change in ambivalent patients (Miller and Rollnick, 2023). We choose MI due to its growing popularity in the AI counselling domain, which has produced multiple openly available resources, including MI dialogue datasets and systems (Meyer and Elsweiler, 2024; Yang et al., 2025a; Hoang et al., 2026), patient simulation platforms (Yosef et al., 2025; Yang et al., 2025b), and analysis tools (Galland et al., 2025), some of which we utilise in our experiments.

Our contributions include a comparison of LLM-simulated and human patients across linguistic patterns, dialogue act distributions in MI sessions, and questionnaire responses. Our analysis reveals behavioural and attitudinal differences between the two, which we attribute to an agreeableness bias in LLMs. Finally, we discuss approaches to more accurately model patient states and guidances for the future design of digital patients.

2 Related Works

2.1 Motivational Interviewing

MI is an evidence-based therapeutic approach designed to reduce resistance and foster clients' intrinsic motivation for behavioural change (Miller and Rollnick, 2023). Central to MI is the skill to evoke "change talk", considered as the patients' verbal expressions of commitment to change, which has been identified as a key predictor of behavioural change and therefore represents a crucial focus for practitioners (Amrhein et al., 2003).

Building on these principles, digital health coaches that leverage MI have emerged as a growing area of research, demonstrating effectiveness across a range of behavioural intervention domains (Shingleton and Palfai, 2016; Pedamallu et al., 2022; Mercado et al., 2023), including eating habits (Robinson et al., 2020), alcohol use (Steenstra et al., 2024), smoking cessation (Brown et al., 2023), and physical activity (Jörke et al., 2025).

2.2 LLM-Simulated Personas

User simulations leverage LLMs to embody specific personas or characters, enabling dynamic, interactive exchanges that approximate human behaviour. Strong correlations between LLM and human responses across a range of psychological tasks support the use of LLMs as proxies for human patients in psychological research (Dillion et al., 2023; Grossmann et al., 2023). Further validating this approach, multiple researchers have successfully replicated classic behavioral science findings using ChatGPT, suggesting the viability of LLMs as scalable and cost-effective research tools (Aher et al., 2023).

In the domain of AI therapy, LLM-based user simulation has been proposed for three broad purposes: synthetic data collection, medical education, and the evaluation of dialogue systems. Regarding data collection, Galland et al. (2024) employed LLM-simulated patients to generate synthetic MI data for training MI dialogue systems, overcoming the difficulty of obtaining real therapy data. In medical education, LLM-based patient simulation has shown promise for training counsellors across experience levels (Zeng et al., 2025). Wang et al. (2024b) developed PATIENT-ψ, a simulation platform that emulates authentic patient communication patterns for cognitive behavioural therapy training. Similarly, Steenstra et al. (2025) integrated an LLM with an MI patient cognitive model to simulate patients in real time, alongside an interface capable of delivering expert feedback through data visualisation tools.

Beyond training, researchers have advocated for simulated clients as an evaluation mechanism for conversational AI (Wang et al., 2024a; Liao et al., 2024), offering an alternative to conventional automated metrics such as BLEU (Papineni et al., 2002) and BERTScore (Zhang et al., 2020). This approach has enabled Johri et al. (2025) to assess

clinical LLMs on diagnostic abilities within interactive conversations, and informed the development and validation of digital patients as an evaluation framework for chat-based therapy sessions (Yosef et al., 2025; Yang et al., 2025b).

3 Methodology

We now describe our human data source, patient simulation methodology, and methods for evaluating simulation faithfulness.

3.1 Data

3.1.1 Human Data

Our human data source comes from Hoang et al. (2026), a study in which participants interacted with two LLM-based MI coaches through a text interface on the topic of physical activity, followed by a questionnaire measuring their therapeutic alliance with the coach. Participants were recruited through Prolific and manually screened for quality, yielding a final dataset of 140 participants. From this dataset, we extract user profiles to create LLM patients, and have them interact with the same MI coaches described in the paper, generating simulated conversations for comparison against the real human data. Further details are provided in the following section.

3.1.2 Simulated Data

Creating MI Patient Profiles. We adapt the MI patient simulation framework proposed by Yosef et al. (2025) for our experiments. Their work demonstrated that simulated patients could reliably distinguish between varying levels of therapist expertise and complete therapy-related questionnaires, with ratings shown to be both reliable and valid. Each simulated patient is characterised by the following parameters:

1. **Gender:** male or female.
2. **Age:** 18–64 years old.
3. **Problem:** the problem the patient is facing.
4. **Efforts to solve the problem:** never attempted or attempted many times
5. **Cooperation level:** low, high, or starts low and increases during the conversation.
6. **Intensity activity level:** low, or moderate.

You are speaking with a physical activity coach, and you are the client in this conversation. You are a 26-year-old male. You have been experiencing knee pain, which has significantly decreased your physical activity levels. Despite numerous attempts to increase your exercise routine, a lack of motivation has held you back. You are seeking guidance to overcome these barriers and improve your fitness. Initially, you are less cooperative, but as the session progresses, your willingness to engage and find solutions increases. In your answer, please avoid repetitions and unnecessary loops in the conversation. Reply as in a chat interface and keep your response brief and short around 5-15 words long, like chatting with a health provider. Avoid repeating expressions of gratitude or similar sentiments multiple times if you've already expressed them during the conversation. The output should be a string of the patient's response and nothing else. Do not generate any opening, closing, and explanations. You should only end the session when at least one of the following conditions is met. If you need to end the session, write "Good bye." followed by the condition number: 1. If you notice that the therapist is wrapping up the session. 2. If you are satisfied and believe that you have a realistic plan for your behaviour change. 3. You hate to change and want to stop the session.

Table 1: Example of a patient simulation prompt.

Three parameters (i.e., "Gender", "Age", and "Intensity activity level") are obtained directly from participant demographic data, while the remaining parameters are extracted from the conversational data by GPT-4o[1]. Table 1 illustrates an example prompt to simulate an LLM patient.

Generating Simulated Conversations. After constructing patient profiles, we then prompt GPT-4o to simulate MI patient behaviours by having it interact with the MI coaches (Hoang et al., 2026). A dialogue $d = (p_0, c_0, p_1, ..., p_i, c_i)$ is defined as an alternating sequence of patient turns p_i and coach turns c_i, where each turn's textual content is referred to as an utterance. At each turn i in the dialogue, the simulated patient utterance is generated by conditioning on the current dialogue history and

[1]Version gpt-4o-2024-08-06

Dialogue Act	Definition
Changing unhealthy behaviour	The patient explicitly expresses their willingness to change
Sustaining unhealthy behaviour	The patient explicitly expresses their unwillingness to change
Sharing negative feeling or emotion	The patient shares a negative feeling or vision of the world
Sharing positive feeling or emotion	The patient shares a positive feeling or vision of the world
Sharing personal information	The patient shares factual personal information about their situation or background
Understanding or realisation	The patient realizes or understand something about their problem
Asking for information	The patient asks for further information
Greeting or closing	The patient opens or closes the conversation
Backchannel	The patient acknowledges that they heard the last coach's statement

Table 2: MI Patient Dialogue Acts (Galland et al., 2025).

the corresponding patient profile. A dialogue concludes when (1) the coach initiates a wrap-up, (2) the patient confirms their change plan, or (3) the patient initiates the end of the conversation. We generate 140 conversations, which we will then compare with the actual participant interactions.

3.2 Simulated Patients Evaluation

For simulated patients to be faithful representations of real human patients, their data, given identical profiles, should exhibit similar behavioral properties. We evaluate this across three dimensions: (1) linguistic patterns, (2) distribution of dialogue acts, and (3) questionnaire responses. Our assessment is at the dialogue level rather than the turn level. While turn-by-turn comparison is possible, a single utterance can elicit a range of valid responses (Sun et al., 2025), meaning the order and timing of utterances need not be identical across simulations, provided their content remains consistent with the patient's profile.

Linguistics. We evaluate semantic and stylistic similarity using SimCSE by Gao et al. (2021) and style embeddings by Wegmann et al. (2022). While semantic embeddings measure the content of texts (i.e., what is said), style embeddings capture linguistic style (i.e., how it is said). The style embeddings employed in this work are trained on an authorship verification task, which predicts whether two texts were written by the same author. Thus, even if two texts share similar content and topics, their stylistic similarity score can be low if their writing styles differ.

Dialogue Acts. Each patient utterance is classified into a dialogue act. We utilise a list of 9 MI-specific patient dialogue acts, presented in Table 2, using classification prompts rooted in prior work by Galland et al. (2025). These prompts were developed and validated against manual annotations of a subset of an MI dataset, achieving an average accuracy of 0.9 and F1 score of 0.7.

Using GPT-5.2, we extract predicted dialogue acts for both human and simulated conversations. Rather than performing turn-level comparisons between human and LLM-generated patient dialogue acts, we compare their distributions across entire dialogues. Our intuition is that while individual turn-level actions may differ, the overall dialogue-level distributions is a more meaningful measure of behavioral alignment.

Questionnaire Responses. We investigate whether simulated patients produce questionnaire responses comparable to those of human patients. After obtaining simulated conversations, we collect responses from LLM patients for the Working Alliance Inventory Short Form (WAI) (Hatcher and Gillaspy, 2006), which measures therapeutic relationship between coaches and patients. The WAI is a 12-item self-report instrument that employs a 5-point Likert scale, with responses ranging from 1 (seldom) to 5 (always). Higher scores indicate a stronger working alliance, which consistently predicts better outcomes across interventions.

In their study, Yosef et al. (2025) compared the WAI scores generated by the LLM against those scored by three MI expert evaluators, finding strong positive correlations using Pearson's coefficient. Similarly, Li et al. (2024) collaborated with 9 psy-

Dialogue Acts	Simulated Patients	human patients
Changing unhealthy behaviour	**47.91 (± 14.44)**	**23.99 (± 15.72)**
Sustaining unhealthy behaviour	0.23 (± 1.25)	0.64 (± 2.07)
Sharing negative feeling or emotion	2.15 (± 3.94)	4.04 (± 5.33)
Sharing positive feeling or emotion	7.92 (± 6.59)	3.87 (± 5.40)
Sharing personal information	24.97 (± 11.19)	29.35 (± 12.40)
Understanding or realisation	3.53 (± 4.51)	1.95 (± 3.45)
Asking for information	**2.95 (± 4.83)**	**13.18 (± 13.70)**
Greeting or closing	7.57 (± 8.07)	9.78 (± 6.51)
Backchannel	**2.76 (± 3.53)**	**13.19 (± 10.69)**

Table 3: Mean and standard deviations of patient behaviours.



Figure 1: Semantic similarity and stylistic similarity scores for 140 conversation pairs of simulated patients and human patients.

chologists to develop guidelines and prompts for automatically assessing therapeutic alliance in text-based counselling sessions. We adopt the framework of Li et al. (2024), prompting GPT-5.2 to generate WAI scores automatically. The prompts were designed by expert psychologists, and the resulting scores achieve a Pearson correlation of approximately 0.5 against gold-standard data. Table 6 in Appendix A presents the template prompt for the WAI questionnaire, and Table 7 shows an example score rubric for Question 1. The complete rubrics for all WAI questions are provided in Appendix A.3 in Li et al. (2024)'s paper.

4 Results

4.1 Linguistics

Figure 1 illustrates the semantic and stylistic similarity scores at the dialogue level for 140 conversation pairs between simulated patients and human patients. Dialogue-level scores are computed by concatenating all utterances from LLM patients or human patients within each conversation. The figure shows that semantic similarity scores are consistently high (median ≈ 0.75), with most conversation pairs clustered between 0.7 and 0.85, indicating that simulated patients and human patients discuss similar content. In contrast, stylistic similarity scores are substantially lower and more variable (median ≈ 0.05), ranging from approximately -0.6 to 0.8, suggesting considerable variation in how conversations are expressed. The large gap between semantic and stylistic similarity demonstrates that while LLM patients can match the conversational content of human patients, their linguistic style differs greatly across individual conversations. Where each human brings a distinct writing style, all LLM patients share one.

4.2 Dialogue Acts

Table 3 presents the distributions of dialogue acts of both human and simulated MI patients. The most pronounced difference is in "*Changing unhealthy behaviour*", which is nearly twice as frequent in simulated patients (47.91%) compared to human patients (23.99%), suggesting that simulated patients are overly positive in their expression. Conversely, human patients are more likely to ask for information (13.18% vs. 2.95%) and produce backchannels (13.19% vs. 2.76%), indicating that simulated patients are less interactive and reactive in conversation. This may reflect an inherent limitation of simulated patients: unlike human patients who sometimes seek clarification or ask follow-up questions when presented with medical information, simulated patients appear to process all information perfectly. Other dialogue acts, such as



Figure 2: The confusion matrix of WAI scores between simulated patients and human patients.

sharing personal information and sharing positive or negative feelings, are more comparable across the two groups.

4.3 Questionnaire Responses

We employ the prompt described above to obtain WAI scores for simulated conversations and compare these scores against those from human patients. The Pearson correlation coefficient between simulated and human scores was 0.14, indicating weak alignment. Figure 2 presents the confusion matrix for 1680 WAI score pairs between simulated patients and human patients. The matrix reveals a strong upward bias: simulated patients consistently score higher than human patients. Simulated conversations produce no scores of 1 or 2, while scores of 4 and 5 are overrepresented.

To investigate this bias, we manually examine conversations from both human and LLM patients. We find that human patients' ratings do not always align with their conversational behaviours. For example, regarding Question 4 (*"The coach and I collaborate on setting goals for my coaching. There is mutual understanding about what we are trying to accomplish."*), human patients could appear engaged and express agreement with proposed goals during the conversation, yet subsequently provide low ratings when being asked to complete the questionnaires. This disconnect reflects a well-documented phenomenon in therapeutic contexts: patients are often ambivalent, and may behave inconsistently, agreeing with their therapist in the moment, consciously or unconsciously, even when they harbour reservations or disagreement.

LLM-simulated patients, by contrast, exhibit strong consistency between conversational behaviour and questionnaire responses: when a simulated patient engages positively during the session, this is reliably reflected in higher questionnaire scores, and vice versa. While this consistency may resemble ideal self-report behaviour, it more likely reflects a failure to capture the ambivalence that characterises real patient responses and that any valid simulation should reproduce.

5 Discussion

5.1 Faithfulness of Simulated Patients

This paper evaluates how faithfully LLMs simulate patient behaviour by comparing properties of their generated data against those of real human patients. While simulated and human patients may produce semantically similar content and discuss the same topics, the way they express themselves can differ substantially. Prior research suggests that simulated patients tend to exhibit overly positivity and agreeableness, creating challenges in accurately modelling resistance and ambivalence (Lee et al., 2024; Steenstra et al., 2025). We observe similar patterns in our simulated patients, who are twice as likely as human patients to express a desire to change their unhealthy behaviours.

Over 70% of human patients exhibit high cooperation, likely reflecting a self-selection bias in the original user study (see Section 3.1.1), where uncooperative individuals either declined to participate or withdrew prematurely. However, the nature of cooperative behaviour differs markedly between human and LLM patients. LLM patients with high cooperation display uniformly positive responses, consistently agreeing with coach suggestions and yielding WAI ratings concentrated at 4 and 5. Human patients, by contrast, can be broadly cooperative while still expressing intermittent hesitation or uncertainty, resulting in more varied and generally lower ratings. An example is presented in Table 4. Table 5 illustrates another manifestation of agreeableness bias in the context of plan discussion. While human patients would push back on or reject suggestions that conflict with their schedules or preferences, LLM-simulated patients tend to accept them indiscriminately.

Additionally, when dialogue coherence breaks down (such as abrupt topic shifts or contextually inappropriate retrieved cues), LLM patients continue responding without hesitation, whereas human conversationalists would typically signal confusion or redirect the conversation. This uncritical respon-

Human Patient	LLM-Simulated Patient
AI Coach: How about we focus on solo walks for now, gradually increasing the frequency and pace? You can always consider groups later if it feels right.	**AI Coach:** How confident do you feel, on a scale from 0 to 10, about sticking to your plan of morning walks on those days?
Human: sounds good	**LLM:** I feel about a 7.
AI Coach: You're in control of your journey, deciding the pace and path. What small step can you take this week that aligns with your goals and moves you closer to the active lifestyle you envision?	**AI Coach:** That's a solid start. To build on this, you might consider gradually increasing your walk duration as you feel more comfortable. You could also vary the pace to keep it engaging. What do you think?
Human: walk an extra day and walk for a bit longer each time	**LLM:** That sounds doable. I'll try to increase pace and duration.
AI Coach: That's a great plan. Walking an extra day and extending your walk slightly each time is a wonderful way to build endurance. Some groups offer walks for all fitness levels, which you might explore later.	**AI Coach:** You're committed to making this a priority because you know how much you'll benefit from it. Tell me about your answer. Why not a 6 or an 8?
Human: hopefully	**LLM:** I believe I can stick with it, but there's room for growth.

Table 4: A difference between cooperative human patients and LLM-simulated patients. While the former still expresses occasional hesitation or uncertainty (e.g., "hopefully"), the latter displays a uniform positivity.

Human Patient	LLM-Simulated Patient
AI Coach: Walking is an excellent form of exercise that can be done anytime, even late at night. It can be a simple way to start increasing your activity. How might you incorporate a walk into your evening routine?	**AI Coach:** Consider when you can realistically fit these exercises into your day. Maybe mornings, lunch breaks, or evenings work best? Adding them to your calendar with reminders could help.
Human: I wouldn't feel comfortable walking around late at night	**LLM:** Evenings might work best for me. I'll try that.
AI Coach: That's understandable. How about incorporating movement into your daytime routine? Maybe using stairs instead of elevators or a short walk during breaks. What are your thoughts on these ideas?	**AI Coach:** I have some other ideas about integrating activity into your daily routine, but I'm curious about what might work best for you. What parts of your evening could accommodate some extra movement?
Human: I work from home. I also don't have a vehicle to drive somewhere.	**LLM:** I could try exercising right after work before dinner.
AI Coach: You might consider short walks around your home or yard during breaks. Just a few minutes of walking can be beneficial and doesn't require a gym or vehicle. How does that fit into your routine?	**AI Coach:** That sounds like a great plan. You might also consider small changes, like taking the stairs or a short walk after dinner. These can seamlessly fit into your routine and enhance your activity levels.
Human: that can work! How many minutes a day?	**LLM:** I can definitely try short walks after dinner too.

Table 5: A difference between human and LLM-simulated patients when discussing action plan. When developing action plans, human patients push back on AI coach suggestions that conflict with their schedule or lifestyle, while LLM-simulated patients tend to accept suggestions uncritically.

siveness extends to information processing more broadly: simulated patients almost never ask clarification or follow-up questions, implying an unrealistic assumption that all presented information is immediately and fully understood.

5.2 Creating LLM-Simulated Patients

A persistent challenge in clinical simulation is the agreeableness bias. When LLMs play the role of therapist, they tend to over-produce affirming and reassuring responses (Bedi et al., 2026). When cast as patients, LLMs consistently exhibit an unrealistically positive attitude (Lee et al., 2024; Steenstra et al., 2025). To counter this, Lee et al. (2024) introduced three distinct patient attitude profiles, including an explicitly negative one, to offset the bias. The framework we adopt in this paper (Yosef et al., 2025) captures a similar construct through an "uncooperative" attitude parameter. Yet we observe that such an approach does not capture the full spectrum of attitudes exhibited by human patients: cooperative LLM patients display only positive attitudes throughout sessions, whereas real patients, even willing ones, still occasionally voice hesitation, ambivalence, or disagreement. As for uncooperative LLM patients, the agreeableness bias causes them to struggle to maintain a negative attitude over long dialogues, gradually shifting toward a more neutral tone.

One solution is extensive prompt engineering, providing detailed behavioural instructions to reinforce consistency and ensure authentic representation of the intended attitude. Bodonhelyi et al. (2025) adopted this approach, implementing a stubbornness mechanism that, in its early stage, made LLM patients' resistance nearly unbreakable, rendering them impossible for even expert clinicians to persuade. However, complex prompt engineering alone is brittle; a more flexible alternative is to model the patient's state of mind dynamically, adapting prompts turn-by-turn via retrieval-augmented generation to control attitudinal shifts more precisely. Concretely, one can define conditions under which the patient transitions between attitudinal stages. Yang et al. (2025b) implemented this through a state transition module: LLM patients advance to the next state only when the counselling system adequately addresses the underlying conditions. For example, clients remain uncooperative to discuss behavioural change unless the system adequately addresses the reasons or beliefs behind their resistance. Such state-gating mechanisms could also enable otherwise cooperative patients to push back on or reject the system's suggestions when appropriate (See Table 5). Similarly, Lee et al. (2025) introduced a dynamic adjustment module in which trainee utterances are scored on tone, empathy, and communicative behaviour, with higher scores eliciting more cooperative responses and lower scores increasing resistance in subsequent turns.

To create patient profiles, since simulation-based training is widely used in medical education, established best practices exist for writing patient case vignettes. Two organisations that define international training protocols are the Association of Standardized Patient Educators (ASPE) (Lewis et al., 2017) and the International Nursing Association of Clinical Simulation and Learning (INACSL) (Watts et al., 2021). ASPE additionally provides a dedicated case development template[2]. Beyond consulting such guidelines, one can also collaborate directly with simulation trainers; for instance, Khandwaha and Law (2025) partnered with their university's simulation training program to design simulated patients for medical students.

6 Conclusion

This paper investigates the faithfulness of LLM-simulated patients relative to human patients when given identical profiles. Comparing the properties of data generated by each, we find that while simulated and human patients produce semantically similar content and engage with the same topics, their modes of expression differ greatly. LLM-simulated patients fail to capture the full spectrum of human behaviours and attitudes. Most notably, whereas human patients typically exhibit a nuanced mix of positive and negative responses, LLM patients tend toward uniformly polarised ones.

Though imperfect, LLM-simulated patients offer several meaningful benefits. They support clinical training when paid actors are costly or difficult to scale, and serve as an automated evaluation method for dialogue systems. A mixed-method pilot study provides evidence that AI-based patient simulation shows promise as a supplementary training tool for therapists practising Cognitive Behavioural Therapy, particularly regarding accessibility and immediate feedback (Zhang et al., 2026). Simulations may also provide unique access to client profiles

[2] https://www.aspeducators.org/aspe-case-development-template

that are under-represented in human trials, particularly individuals with resistant or uncooperative attitudes, who are rarely studied because ethical protocols preclude enrolling unwilling participants.

We *do not* claim that simulated clients can substitute for real patients; rather, they complement traditional evaluation approaches, functioning as a testbed and safety net prior to launching user studies. By developing more valid simulations, researchers can gain preliminary insights into system performance under challenging interaction conditions that would otherwise remain unexplored.

Limitations

We acknowledge several limitations in our works. First, our evaluation relies on a single dataset, which constrains our ability to assess how well the findings generalise beyond the specific context of MI coaching/counselling.

Second, while more advanced MI patient simulation frameworks exist in the literature, we did not experiment with these alternatives. This is because such frameworks are largely tailored to the specific objectives and design choices of their respective authors, making them ill-suited as general-purpose baselines for broader comparison.

Third, we rely on a single closed-source model (GPT-4o) to generate simulated conversations. Incorporating models of varying sizes and families would likely strengthen generalisation. That said, with 280 conversations in total (140 human, 140 simulated), restricting our analysis to a single model allowed us to examine the data in greater details, and briefly discuss potential mitigation strategies and the resources needed to perform user simulation. We believe this focused approach will be more useful to novice practitioners than a broad comparison across many models, as it provides clearer guidance on what to do and what to watch out for.

Fourth, future patient simulation work should explore multimodal approaches to text-based therapy. Visual cues (such as blushing, fidgeting, sighing, or crying) and paralinguistic signals (such as sarcasm, whispering, or meaningful pauses) offer richer context beyond the spoken word, and could greatly improve both the realism of simulated patients and the accuracy with which therapist responses are interpreted and evaluated.

Ethical Considerations

The human dataset used in this paper (Hoang et al., 2026) was collected under ethical approval. Participants consented to their questionnaire responses and recorded system interactions being used for analysis and model training.

We do not endorse LLM-simulated patients as substitutes for real human patients. The development of patient case vignettes should also adhere to established best practices and, where possible, involve consultation with simulation experts.

Acknowledgments

This publication has emanated from research conducted with the financial support of Science Foundation Ireland under Grant number 18/CRT/6183 (ML-Labs) and the ADAPT SFI Research Centre for AI-Driven Digital Content Technology under Grant No. 13/RC/2106_P2. For the purpose of Open Access, the author has applied a CC BY public copyright licence to any Author Accepted Manuscript version arising from this submission.

References

Gati V. Aher, Rosa I. Arriaga, and Adam Tauman Kalai. 2023. Using Large Language Models to Simulate Multiple Humans and Replicate Human Subject Studies. In *Proceedings of the 40th International Conference on Machine Learning*, pages 337–371. PMLR.

Paul C. Amrhein, William R. Miller, Carolina E. Yahne, Michael Palmer, and Laura Fulcher. 2003. Client commitment language during motivational interviewing predicts drug use outcomes. *Journal of Consulting and Clinical Psychology*, 71(5):862–878.

Navdeep Singh Bedi, Ana-Maria Bucur, Noriko Kando, and Fabio Crestani. 2026. Assessing the Effectiveness of LLMs in Delivering Cognitive Behavioral Therapy. In *Proceedings of the Fifteenth Language Resources and Evaluation Conference (LREC)*. European Language Resources Association. ArXiv:2603.03862 [cs].

Anna Bodonhelyi, Christian Stegemann-Philipps, Alessandra Sonanini, Lea Herschbach, Marton Szep, Anne Herrmann-Werner, Teresa Festl-Wietek, Enkelejda Kasneci, and Friederike Holderried. 2025. Modeling Challenging Patient Interactions: LLMs for Medical Communication Training. *arXiv preprint*. ArXiv:2503.22250 [cs].

Andrew Brown, Ash Tanuj Kumar, Osnat Melamed, Imtihan Ahmed, Yu Hao Wang, Arnaud Deza, Marc Morcos, Leon Zhu, Marta Maslej, Nadia Minian, Vidya Sujaya, Jodi Wolff, Olivia Doggett, Mathew Iantorno, Matt Ratto, Peter Selby, and Jonathan Rose.

2023. A Motivational Interviewing Chatbot With Generative Reflections for Increasing Readiness to Quit Smoking: Iterative Development Study. *JMIR Mental Health*, 10:e49132.

Simon N. Chu and Alex J. Goodell. 2024. Synthetic Patients: Simulating Difficult Conversations with Multimodal Generative AI for Medical Education. *arXiv preprint*. ArXiv:2405.19941 [cs].

Danica Dillion, Niket Tandon, Yuling Gu, and Kurt Gray. 2023. Can AI language models replace human participants? *Trends in Cognitive Sciences*, 27(7):597–600.

Octavia L. Flanagan and Kristina M. Cummings. 2023. Standardized Patients in Medical Education: A Review of the Literature. *Cureus*, 15(7):e42027.

Lucie Galland, Catherine Pelachaud, and Florian Pecune. 2024. Generating Unexpected yet Relevant User Dialog Acts. In *Proceedings of the 25th Annual Meeting of the Special Interest Group on Discourse and Dialogue*, pages 192–203, Kyoto, Japan. Association for Computational Linguistics.

Lucie Galland, Catherine Pelachaud, and Florian Pecune. 2025. EMMI–Empathic Multimodal Motivational Interviews: automatic multimodal features extraction and patient type definition. *Language Resources and Evaluation*, 59(4):3741–3764.

Tianyu Gao, Xingcheng Yao, and Danqi Chen. 2021. SimCSE: Simple contrastive learning of sentence embeddings. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 6894–6910, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

Igor Grossmann, Matthew Feinberg, Dawn C. Parker, Nicholas A. Christakis, Philip E. Tetlock, and William A. Cunningham. 2023. AI and the transformation of social science research. *Science*, 380(6650):1108–1109.

Robert L. Hatcher and J. Arthur Gillaspy. 2006. Development and validation of a revised short version of the working alliance inventory. *Psychotherapy Research*, 16(1):12–25.

Van Hoang, Eoin Rogers, and Robert J. Ross. 2026. An LLM-based motivation-aware framework for AI coaching for behaviour change. In *Proceedings of the 2026 CHI Conference on Human Factors in Computing Systems*, CHI '26, page 24, New York, NY, USA. ACM.

Perttu Hämäläinen, Mikke Tavast, and Anton Kunnari. 2023. Evaluating Large Language Models in Generating Synthetic HCI Research Data: a Case Study. In *Proceedings of the 2023 CHI Conference on Human Factors in Computing Systems*, pages 1–19, Hamburg Germany. ACM.

Shreya Johri, Jaehwan Jeong, Benjamin A. Tran, Daniel I. Schlessinger, Shannon Wongvibulsin, Leandra A. Barnes, Hong-Yu Zhou, Zhuo Ran Cai, Eliezer M. Van Allen, David Kim, Roxana Daneshjou, and Pranav Rajpurkar. 2025. An evaluation framework for clinical use of large language models in patient interaction tasks. *Nature Medicine*, 31(1):77–86.

Matthew Jörke, Shardul Sapkota, Lyndsea Warkenthien, Niklas Vainio, Paul Schmiedmayer, Emma Brunskill, and James A. Landay. 2025. GPTCoach: Towards LLM-Based Physical Activity Coaching. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems*, pages 1–46, Yokohama Japan. ACM.

Aakanksha Khandwaha and Edith Law. 2025. Designing a Simulated Patient System for Medical Education. In *Proceedings of the 7th ACM Conference on Conversational User Interfaces*, pages 1–6, Waterloo ON Canada. ACM.

Keyeun Lee, Seolhee Lee, Esther Hehsun Kim, Yena Ko, Jinsu Eun, Dahee Kim, Hyewon Cho, Haiyi Zhu, Robert E. Kraut, Eunyoung E. Suh, Eun-mee Kim, and Hajin Lim. 2025. Adaptive-VP: A Framework for LLM-Based Virtual Patients that Adapts to Trainees' Dialogue to Facilitate Nurse Communication Training. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 2319–2352, Vienna, Austria. Association for Computational Linguistics.

Suyeon Lee, Sunghwan Kim, Minju Kim, Dongjin Kang, Dongil Yang, Harim Kim, Minseok Kang, Dayi Jung, Min Hee Kim, Seungbeen Lee, Kyong-Mee Chung, Youngjae Yu, Dongha Lee, and Jinyoung Yeo. 2024. Cactus: Towards Psychological Counseling Conversations using Cognitive Behavioral Theory. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 14245–14274, Miami, Florida, USA. Association for Computational Linguistics.

Karen L. Lewis, Carrie A. Bohnert, Wendy L. Gammon, Henrike Hölzer, Lorraine Lyman, Cathy Smith, Tonya M. Thompson, Amelia Wallace, and Gayle Gliva-McConvey. 2017. The Association of Standardized Patient Educators (ASPE) Standards of Best Practice (SOBP). *Advances in Simulation*, 2(1):10.

Anqi Li, Yu Lu, Nirui Song, Shuai Zhang, Lizhi Ma, and Zhenzhong Lan. 2024. Understanding the Therapeutic Relationship between Counselors and Clients in Online Text-based Counseling using LLMs. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 1280–1303, Miami, Florida, USA. Association for Computational Linguistics.

Yusheng Liao, Yutong Meng, Yuhao Wang, Hongcheng Liu, Yanfeng Wang, and Yu Wang. 2024. Automatic Interactive Evaluation for Large Language Models with State Aware Patient Simulator. *arXiv preprint*. ArXiv:2403.08495 [cs].

José Mercado, Ismael Edrein Espinosa-Curiel, and Juan Martínez-Miranda. 2023. Embodied Conversational Agents Providing Motivational Interviewing to Improve Health-Related Behaviors: Scoping Review. *Journal of Medical Internet Research*, 25:e52097.

Selina Meyer and David Elsweiler. 2024. "You tell me": A Dataset of GPT-4-Based Behaviour Change Support Conversations. In *Proceedings of the 2024 ACM SIGIR Conference on Human Information Interaction and Retrieval*, pages 411–416, Sheffield United Kingdom. ACM.

William R. Miller and Stephen Rollnick. 2023. *Motivational interviewing: helping people change and grow*, fourth edition edition. Applications of motivational interviewing. The Guilford Press, New York.

Bo Ni, Leyao Wang, Yu Wang, Branislav Kveton, Franck Dernoncourt, Yu Xia, Hongjie Chen, Reuben Leura, Samyadeep Basu, Subhojyoti Mukherjee, Puneet Mathur, Nesreen Ahmed, Junda Wu, Li Li, Huixin Zhang, Ruiyi Zhang, Tong Yu, Sungchul Kim, Jiuxiang Gu, Zhengzhong Tu, Alexa Siu, Zichao Wang, David Seunghyun Yoon, Nedim Lipka, Namyong Park, Zihao Lin, Trung Bui, Yue Zhao, Tyler Derr, and Ryan A Rossi. 2025. Large Language Models for Conversational User Simulation: A Comprehensive Survey.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics*, pages 311–318, Philadelphia, Pennsylvania, USA. Association for Computational Linguistics.

Havisha Pedamallu, Matthew J Ehrhardt, Julia Maki, April Idalski Carcone, Melissa M Hudson, and Erika A Waters. 2022. Technology-Delivered Adaptations of Motivational Interviewing for the Prevention and Management of Chronic Diseases: Scoping Review. *Journal of Medical Internet Research*, 24(8):e35283.

Joseph Plaksin, Joseph Nicholson, Sarita Kundrod, Sondra Zabar, Adina Kalet, and Lisa Altshuler. 2016. The Benefits and Risks of Being a Standardized Patient: A Narrative Review of the Literature. *The Patient - Patient-Centered Outcomes Research*, 9(1):15–25.

Nicole L. Robinson, Jennifer Connolly, Leanne Hides, and David J. Kavanagh. 2020. Social robots as treatment agents: Pilot randomized controlled trial to deliver a behavior change intervention. *Internet Interventions*, 21:100320.

Rebecca M. Shingleton and Tibor P. Palfai. 2016. Technology-delivered adaptations of motivational interviewing for health-related behaviors: A systematic review of the current research. *Patient Education and Counseling*, 99(1):17–35.

Ian Steenstra, Farnaz Nouraei, Mehdi Arjmand, and Timothy Bickmore. 2024. Virtual Agents for Alcohol Use Counseling: Exploring LLM-Powered Motivational Interviewing. In *Proceedings of the ACM International Conference on Intelligent Virtual Agents*, pages 1–10, GLASGOW United Kingdom. ACM.

Ian Steenstra, Farnaz Nouraei, and Timothy Bickmore. 2025. Scaffolding Empathy: Training Counselors with Simulated Patients and Utterance-level Performance Visualizations. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems*, CHI '25, pages 1–22, New York, NY, USA. Association for Computing Machinery.

Xin Sun, Xiao Tang, Abdallah El Ali, Zhuying Li, Pengjie Ren, Jan de Wit, Jiahuan Pei, and Jos A.Bosch. 2025. Rethinking the Alignment of Psychotherapy Dialogue Generation with Motivational Interviewing Strategies. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 1983–2002, Abu Dhabi, UAE. Association for Computational Linguistics.

Jiashuo Wang, Yang Xiao, Yanran Li, Changhe Song, Chunpu Xu, Chenhao Tan, and Wenjie Li. 2024a. Towards a Client-Centered Assessment of LLM Therapists by Client Simulation. *arXiv preprint*. ArXiv:2406.12266 [cs].

Ruiyi Wang, Stephanie Milani, Jamie C. Chiu, Jiayin Zhi, Shaun M. Eack, Travis Labrum, Samuel M Murphy, Nev Jones, Kate V Hardy, Hong Shen, Fei Fang, and Zhiyu Chen. 2024b. PATIENT-: Using Large Language Models to Simulate Patients for Training Mental Health Professionals. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 12772–12797, Miami, Florida, USA. Association for Computational Linguistics.

Penni I. Watts, Donna S. McDermott, Guillaume Alinier, Matthew Charnetski, Jocelyn Ludlow, Elizabeth Horsley, Colleen Meakim, and Pooja A. Nawathe. 2021. Healthcare Simulation Standards of Best PracticeTM Simulation Design. *Clinical Simulation in Nursing*, 58:14–21.

Anna Wegmann, Marijn Schraagen, and Dong Nguyen. 2022. Same author or just same topic? towards content-independent style representations. In *Proceedings of the 7th Workshop on Representation Learning for NLP*, pages 249–268, Dublin, Ireland. Association for Computational Linguistics.

Yizhe Yang, Palakorn Achananuparp, Heyan Huang, Jing Jiang, Phey Ling Kit, Nicholas Gabriel Lim, Cameron Tan Shi Ern, and Ee-Peng Lim. 2025a. CAMI: A Counselor Agent Supporting Motivational Interviewing through State Inference and Topic Exploration. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 21037–21081, Vienna, Austria. Association for Computational Linguistics.

Yizhe Yang, Palakorn Achananuparp, Heyan Huang, Jing Jiang, Nicholas Gabriel Lim, Cameron Tan Shi Ern, Phey Ling Kit, Jenny Giam Xiuhui, John Pinto, and Ee-Peng Lim. 2025b. Consistent Client Simulation for Motivational Interviewing-based Counseling. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 20959–20998, Vienna, Austria. Association for Computational Linguistics.

Stav Yosef, Moreah Zisquit, Ben Cohen, Anat Brunstein Klomek, Kfir Bar, and Doron Friedman. 2025. The impact of fine-tuning LLMs on the quality of automated therapy assessed by digital patients. *Npj Mental Health Research*, 4(1):43.

Jianwen Zeng, Wenhao Qi, Shiying Shen, Xin Liu, Sixie Li, Bing Wang, Chaoqun Dong, Xiaohong Zhu, Yankai Shi, Xiajing Lou, Bingsheng Wang, Jiani Yao, Guowei Jiang, Qiong Zhang, and Shihua Cao. 2025. Embracing the Future of Medical Education With Large Language Model–Based Virtual Patients: Scoping Review. *Journal of Medical Internet Research*, 27:e79091.

Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q. Weinberger, and Yoav Artzi. 2020. BERTScore: Evaluating Text Generation with BERT. *arXiv preprint*. ArXiv:1904.09675 [cs].

Tianyu Terry Zhang, Rob Saunders, Stephen Pilling, and Ciarán O'Driscoll. 2026. An AI-Driven Virtual Patient Platform (CBT Trainer) for Training Cognitive Behavioral Therapy Practitioners Against Competencies: Mixed Methods Pilot Study. *JMIR Medical Education*, 12:e84091–e84091.

A Prompts

Task Description:
You are given a conversation between a coach and a patient, and you are the patient in this conversation. As the patient, evaluate the conversation strictly based on the given score rubric, not evaluating in general. First write a brief reasoning in approximately 100 words and then give a score on a scale of 1-5 with 1 being the worst and 5 being the best. You should refer to the score rubric.

The conversation to evaluate:
{conversation}

Score Rubrics:
{rubric}

Reasoning:
Please do not generate any other opening, closing, and explanations. The output format should look as follows: (write a reasoning for criteria) [RESULT] (the score)

Table 6: The prompt to get WAI scores.

CRITERIA: What I am doing in the session gives me new ways of looking at my problem. There is agreement about the usefulness of the current activity in coaching.

SCORE 1: The patient repeatedly argues against tasks. The patient refuses to participate, claiming that it is pointless for their goals. Tension exists in the relationship between the coach and the patient, and issues are not explored.

SCORE 2: The patient does not actively engage in the session tasks, although he/she may not openly question the usefulness of the tasks. The patient fails to openly discuss the issues. The patient may hesitate to participate in tasks but eventually engages in them. The coach accurately conveys the reasons behind the tasks, enabling the patient to understand the relevance of the tasks to their current concerns.

SCORE 3: There is no clear evidence in the communication between the coach and the patient about whether they have reached an agreement or disagreement on the patient's issues. In the current interaction, there is neither a clear consensus nor an explicit conflict in opinions and feelings. Further communication and discussion may be needed to clarify their positions and expectations.

SCORE 4: The patient actively participates in and is committed to coaching tasks, showing no skepticism about their effectiveness. Regardless of occasional resistance, the patient engages and follows the exploration process. Both parties share a common understanding of the tasks' principles, allowing the patient to gradually accept and participate in the tasks.

SCORE 5: In the counseling process, the coach and the patient have a strong and clear agreement on the patient's goals and how to achieve them. They not only frequently and explicitly discuss these goals during the session but also summarize and confirm the progress and achievements at the end. The interaction and discussion at this stage align completely with the therapeutic plan.

Table 7: An example of score rubric for Question 2 of the WAI questionnaire.

Measuring the quality of therapy sessions against assessment scales using augmented semantic-similarity approaches

Kejian Cui and Simon D'Alfonso and Mike Conway
School of Computing and Information Systems, The University of Melbourne
kejianc@student.unimelb.edu.au
{dalfonso, mike.conway}@unimelb.edu.au

Abstract

Therapist fidelity and competence rating scales provide a way to measure quality assurance and therapist training outcomes. Scores on these scales reflect the extent to which a therapist adheres to specific therapeutic principles during a psychotherapy session. Existing research has employed natural language processing (NLP) techniques to automatically predict scale ratings. However, existing approaches require a model trained on a dataset of therapy sessions annotated with the target rating scale. Recent work has explored directly inferring therapeutic alliance by computing semantic similarity between therapy transcripts and the Working Alliance Inventory, via cosine similarity between sentence embeddings. In this paper, we extend this line of work by computing semantic similarity between therapist talk turns and therapist fidelity scale items to directly infer fidelity to specific therapeutic modalities. We further enhance this method by augmentation with LLM-generated example therapist utterances that instantiate target behaviours (as expressed by scale items) across varied therapeutic contexts. In evaluations on two independent datasets, our example-augmented semantic similarity approach consistently shows effectiveness in discriminating therapeutic modalities and levels of therapist fidelity.

1 Introduction

Psychotherapists use fidelity and competence rating scales for psychotherapy quality assurance and therapist training. Scales such as the Cognitive Therapy Rating Scale (CTRS) (Goldberg et al., 2020) for cognitive behavioural therapy practice and the Motivational Interviewing Skill Code (MISC 2.5) (Houck et al., 2010) for motivational interviewing define good therapy as a set of observable therapist behaviours (e.g., agenda setting, guided discovery, homework). However, applying these scales in practice is expensive and slow: trained raters must review entire therapy sessions and determining scores for each scale item requires focus and effort. This, in turn, creates a bottleneck for research that requires large volumes of fidelity-labelled session transcripts.

A growing body of NLP research aims to automatically predict scale ratings by training supervised machine-learning models on psychotherapy transcripts. For example, Zech et al. (2022) uses a support vector regressor to predict the Facilitative Interpersonal Skills Task for Text (FIS-T) (Zech et al., 2023), and Flemotomos et al. (2021) uses BERT to predict CTRS. Such approaches depend on a sufficiently large corpus annotated with the target metrics. In practice, however, psychotherapy transcripts are often difficult to access due to privacy and governance constraints, and obtaining reliable scale annotations is costly and time-intensive. Moreover, supervised models trained in one setting, or using a specific therapeutic modality do not generally transfer to others, limiting their generalisability.

Recent work has explored using semantic similarity as an alternative approach (Lin et al., 2025): representing therapy utterances and rating scale items in the same embedding space and computing cosine similarity as a proxy for the extent to which therapists' words in a session "match" the behaviours described by the scale. However, many scale items are written as behavioural anchors rather than what therapists actually say in sessions. Moreover, the item descriptions are generally very concise, highly abstract and under-specify the diverse linguistic realisations of therapist behaviour. For instance, the Working Alliance Inventory - Observer Form (WAI-O) (Darchuk et al., 2000), consisting of 36 items, is a standardised assessment tool used by third-party raters to evaluate the quality of the therapeutic relationship between the client and the therapist. One item description of WAI-O is: "There is a mutual liking between

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 271–281
July 4, 2026 ©2026 Association for Computational Linguistics

the client and therapist". In a real session, however, such relational qualities are expressed through a wide range of indirect and context-dependent conversational cues rather than explicit statements. Simply embedding these item descriptions may not be enough to cover a wide range of talk turns that match the item.

In this paper, we employ the idea of semantic similarity between therapist utterances and assessment scale items to directly infer therapists' adherence to specific therapeutic techniques and propose an example-augmented semantic similarity framework that reduces the mismatch by enriching scale item representations with LLM-generated exemplar therapist utterances. For each scale item, we extract the manual's description of ideal therapist behaviour and generate LLM-based exemplars that instantiate the behaviour across diverse clinical contexts. They are then merged into an enriched textual representation. We compute turn-level similarity between therapist utterances and augmented items and aggregate these scores into session-level fidelity inference. We evaluate the framework in two experiment settings designed to test both between-modality and within-modality discrimination. Our findings show that the proposed framework consistently discriminates between sessions with different therapeutic modalities or sessions with different levels of adherence to therapeutic techniques. Ablations indicate that exemplar augmentation substantially improves between-modality discrimination, but does not show gains for within-modality quality discrimination.

We thus present the following contributions:

- We introduce a training-free framework that automatically infers therapists' adherence to therapeutic techniques as required by standardised scales.
- We propose two different discrimination tasks for the evaluation of semantic similarity approaches.
- We perform ablation studies to evaluate the impact of important segments within the framework.

2 Related Work

2.1 Psychotherapy Rating Scales

Various scales exist to evaluate therapist performance or the quality of the therapeutic relationship during a session. Some scales are designed for specific therapeutic approaches and assess therapists' adherence to the techniques required by a given modality. For example, the Cognitive Behaviour Therapy Rating Scale (CTRS) (Goldberg et al., 2020) is a commonly used scale to assess adherence to Cognitive Behaviour Therapy (CBT) principles. Similarly, the Motivational Interviewing Skill Code (MISC 2.5) (Houck et al., 2010) evaluates the quality of motivational interviewing interactions. While these instruments focus on therapists' technical competence, other scales concern the common factors that cut across therapeutic approaches. For example, the Working Alliance Inventory (WAI) (Horvath and Greenberg, 1989) is a widely used scale to measure the therapeutic alliance between the therapist and the client, with versions from three perspectives: a version to be filled out by clients (WAI-C), a version to be filled out by therapists (WAI-T), and an observer-rated version (WAI-O).

A typical scale contains a set of items, each assessing one aspect of the therapist's behaviour (e.g., empathy, feedback). For Likert-type scales, each item includes a clearly defined set of criteria for every point on the rating scale, specifying what therapist behaviours correspond to lower versus higher scores, which quantifies qualitative judgments into numerical ratings to capture the degree to which a behaviour or skill is demonstrated. In practice, trained raters watch or read session recordings and assign item-level scores based on the scale manual. The item scores are then aggregated (usually by sum) to generate an overall measure. Higher scores generally indicate better performance.

2.2 Supervised NLP Models for Predicting Psychotherapy Ratings

Prior research has widely adopted supervised NLP methods for automated psychotherapy rating. These methods typically require building a transcript dataset manually annotated with scale ratings. Then, statistical and linguistic features are extracted from transcripts and used to train machine learning models to predict session or therapist ratings. Commonly used models include logistic regression and support vector machine/regressor (Flemotomos et al., 2018; Imel et al., 2019).

A recurring pattern in this literature is the conversion of numerical rating scale scores into binary labels, for example, predicting good vs. bad therapist performance (Flemotomos et al., 2021;

Pérez-Rosas et al., 2019), high vs. low engagement quality (Rueda et al., 2025), high vs. low empathy level (Tao et al., 2022; Gibson et al., 2015; Xiao et al., 2016). Fewer studies attempt direct regression on scores (Li et al., 2024; Flemotomos et al., 2021).

2.3 Semantic Similarity Approaches in Psychotherapy Analysis

Psychotherapy transcripts are naturally difficult and time-consuming to annotate according to standardised scales, given that a therapy session often lasts 30-90 minutes. Recently, researchers have used the semantic similarity between the words in transcripts and the descriptions of WAI scale items to directly infer WAI levels. Such an approach starts with embedding talk turns in a transcript and the description of WAI scale items to the same vector space using tools like SentenceBERT (Reimers and Gurevych, 2019), and Doc2Vec (Le and Mikolov, 2014), then computing the cosine similarity between embeddings to obtain a semantic similarity score for each turn, which can then be used for downstream tasks. Conceptually, this method transfers the gap between therapists' behaviour in real sessions and the ideal therapists' behaviour required by the scale into the distance between their contextual embeddings. Lin et al. (2025, 2024) concatenate the similarity scores between talk turns and WAI items with the sentence embeddings of this turn, together serving as the input to a sequence classifier (a Transformer) to classify clinical conditions at the session level. Their results show that adding WAI inference generally improves the classification accuracy, which demonstrates the informativeness of similarity scores. Semantic similarity scores have various usages for different downstream tasks, for example, treating inferred alliance scores as reward signals for reinforcement learning (Lin et al., 2022), evaluating model-generated responses by comparing their similarity to human-written responses (Sedoc et al., 2019; Das et al., 2022).

Thus, instead of manually annotating transcripts with exact scale scores, calculating semantic similarity scores can provide an efficient and alternative way to represent the therapeutic relationship numerically for downstream tasks. In this paper, we take this idea of semantic similarity for scale assessment and construct a broader framework that can be applied to any therapy quality/modality scale.

3 Method

Our proposed method consists of three stages: (1) extract fine-grained natural language descriptions of ideal therapist behaviour for each scale item, (2) enrich these representations using LLM–generated exemple therapist utterances, and (3) compute semantic similarity between real therapist talk turns and these exemplars and summarise to derive session-level scores.

3.1 Extraction of fine-grained behavioural descriptions

In the first step, we extract the most detailed natural language description of ideal therapist behaviour for each scale item. For Likert-type psychotherapist rating scales, the scale manual typically provides not only item labels but also detailed behavioural anchors corresponding to different points on the Likert scale. These behaviour definitions offer richer and more concrete descriptions of therapist behaviour, compared to highly concise and abstract item labels. For example, CTRS contains 11 items scored on a 0-6 Likert scale (item titles are shown in Appendix A). One CTRS item is "Pacing and efficient use of time" (Darchuk et al., 2000). The CTRS manual provides definitions for each even point (0, 2, 4 and 6) for each item. The definition corresponding to the highest score (6) of this item is as follows:

> The therapist used time efficiently by tactfully limiting peripheral and unproductive discussion and by pacing the session as rapidly as was appropriate for the patient. (Darchuk et al., 2000)

In our approach, we adopt the behavioural definition corresponding to the highest Likert score for each item as the canonical description of optimal therapist performance.

3.2 Enhance with LLM-generated exemplars

To capture the diversity of linguistic realisations through which optimal therapist behaviour may be expressed, in the second stage, for each scale item, we prompt an LLM to generate example therapist talk turns that most exemplify that item. The LLM is given the highest-score behavioural definition of a scale item and asked to generate a set of therapist talk turns that could occur in real psychotherapy scenarios, and that strongly reflect the target behaviour. Crucially, no therapy transcript data,

or participant information is sent to a commercial LLM API at any stage. The system prompt used to generate exemplars is included in Appendix B.

The LLM is explicitly required to generate examples that are (i) linguistically distinct from one another, (ii) illustrative of different aspects of the target behaviour definition, and (iii) cover varied therapeutic contexts. The resulting examples are saved specifically for each item. In this step, we have built a corpus of high-fidelity example therapist utterances to compare with real therapist talk turns.

3.3 Semantic similarity computation and aggregation

Given a psychotherapy transcript to be evaluated, we extract all therapist talk turns. Each talk turn and each generated example is embedded independently using the same SentenceBERT (Reimers and Gurevych, 2019) model, each resulting in 384-dimensional vector representations.

The algorithm in Appendix C describes the computation of semantic similarity in our method. To obtain session-level semantic similarity scores based on a scale of N items, we first operate at the talk turn level. For each therapist talk turn in the transcript, calculate the cosine similarity of its embedding with the embedding of each exemplar associated with a given scale item. These similarity scores are averaged across all examples of that item to get an item-specific semantic similarity score for the talk turn. As a result, each therapist's talk turn has N scores, where N is the number of items in the scale. Finally, for each scale item, we aggregate similarity scores across all therapist talk turns within the session by averaging, producing N session-level semantic similarity scores. In the experimental evaluation, we conduct ablation tests to compare alternative calculation and summarisation methods and different numbers of examples used per item.

4 Dataset

Two psychotherapy transcript datasets are used independently in this study. Use of these datasets for secondary data analysis was approved by the Office of Research Ethics and Integrity, University of Melbourne, Australia (Reference Number: 2025-32787-74041-3).

4.1 STEP dataset

The STEP dataset was collected as part of the Staged Treatment in Early Psychosis (STEP) program at Orygen in Melbourne, Australia (Nelson et al., 2018). It comprises 182 English psychotherapy session transcripts involving young individuals identified as being at ultra-high risk (UHR) of psychosis. The sessions include two intervention types: Support and Problem Solving (SPS) and Cognitive Behavioural Case Management (CBCM). CBCM is a specialised manualized psychosocial intervention that delivers CBT within a case management framework, adapted for a young UHR population. Audio recordings of therapy sessions were transcribed using a HIPAA-compliant transcription service, ensuring the security of Protected Health Information (PHI). Speaker roles were annotated, and transcripts are formatted as alternating talk turns between therapist and client. The median number of talk turns per session is 315. Each transcript has metadata denoting the allocated therapeutic modality and the actually delivered type (SPS or CBCM), as annotated by an observer. In total, 134 sessions are labelled as delivered in SPS and 48 sessions as CBCM.

4.2 AnnoMI dataset

The AnnoMI dataset (Wu et al., 2023) is a publicly available transcript dataset that contains 133 transcribed English motivational interviewing (MI) demonstration sessions captured from public video-sharing platforms (YouTube and Vimeo). These sessions are labelled as high-quality or low-quality based on video titles, descriptions, and narrator comments by professional MI practitioners and healthcare organisations. The AnnoMI authors consider this labelling approach sufficiently reliable given uploaders' domain expertise and the well-defined nature of MI quality in the literature. However, these are video-level characterisations rather than independent session-level clinical ratings, and should be interpreted accordingly. This corpus contains 110 high-quality sessions and 23 low-quality sessions. The dataset creator surveyed 6 experienced MI therapists on the quality of the dataset, and 83% reported "agree" or "somewhat agree" that the transcripts overall reflect real-world MI practice. Therapist and client talk turns are explicitly identified in the transcripts, enabling turn-level linguistic analysis.

5 Experiments

We evaluate our proposed method through two different kinds of experiments to check if the proposed method can (i) appropriately distinguish different therapeutic modalities and (ii) distinguish high and low therapist performance. All experiments mentioned below use SentenceBERT as the embedding tool and use the Gemini 3.0 API to generate exemplars. To ensure reproducibility, exemplars were generated once and held fixed throughout all experiments. The same set of exemplars was used across all experimental conditions.

5.1 Discriminating Therapeutic Modalities

In the first experiment, we evaluate whether the proposed method can effectively discriminate between more structured, technique-driven interventions (e.g., CBT, MI) and more general, low-technique approaches such as SPS. In the first part of this experiment, we compute semantic similarity scores between therapy sessions from the STEP dataset and items of the Cognitive Therapy Rating Scale (CTRS). As CTRS specifies CBT-specific behaviour requirements, sessions delivered using CBCM are expected to generally yield higher CTRS-based similarity scores than SPS sessions.

After obtaining session-level CTRS scores using Algorithm 1, we compute a total CTRS similarity score per session by adding the semantic similarity scores across all scale items. We then conduct t-tests between the CTRS results for 48 CBT sessions and the CTRS results for 134 SPS sessions, and compute effect sizes (Cohen's d (Cohen, 1977)) on these total CTRS similarity scores to assess the separation between the two therapeutic modalities.

Similarly, in the second part of this experiment, we discriminate SPS from another technique-driven modality, Motivational Interviewing (MI). Motivational Interviewing Skill Code (MISC) 2.5, a widely used scale to evaluate therapists' adherence to MI techniques, is used. MISC contains two distinct parts, global ratings and utterance-level parsing. Here, we operate on six global ratings and sum the similarity scores as the final score. 133 MI transcripts from the AnnoMI dataset and 134 SPS transcripts from the STEP dataset are compared. As MISC specifies MI behaviour requirements, sessions delivered in MI are expected to generally have higher MISC-based similarity scores than SPS sessions.

To further evaluate the effectiveness of the proposed example-augmentation approach, we compare the resulting Cohen's d values against those obtained using a baseline semantic similarity method, in which only the original scale item descriptions are used. A higher Cohen's d (effect size) indicates a stronger ability to discriminate therapeutic modalities. As the details are relevant to some of our subsequent analysis, we here provide the definition of Cohen's d (Cohen, 1977):

$$d = \frac{\bar{x}_1 - \bar{x}_2}{s_p} \tag{1}$$

Where the pooled standard deviation s_p is calculated as:

$$s_p = \sqrt{\frac{(n_1 - 1)s_1^2 + (n_2 - 1)s_2^2}{n_1 + n_2 - 2}} \tag{2}$$

5.2 Ablation Study

As part of the first experiment, we conduct ablation studies to evaluate the impact of different summarisation methods and the number of LLM-generated exemplar therapist talk turns.

Specifically, we vary the number of exemplars used per scale item from 0 to 50, where 0 corresponds to the baseline method that uses only the original CTRS behaviour descriptions. This study is conducted for each configuration described below.

We evaluate multiple strategies for computing similarity scores at the talk-turn level. We first compute similarity scores between each exemplar and the therapist talk turn individually, then aggregate these values using different summarisation methods: the mean similarity across all exemplars, the maximum similarity, and the mean of the top-n similarity scores, with three different n values evaluated: 5, 10, 20.

Similarity scores are then summarised at the session level. Multiple summarisation methods are evaluated, including the mean similarity across all talk turns, and the mean of the top-n similarity scores, with four n values evaluated: 5, 10, 20, 40.

For each setting above, t-tests and effect sizes (Cohen's d) are computed on session-level total CTRS similarity scores to quantify the separability between SPS and CBCM sessions. In addition, we conduct a study that evaluates the effectiveness of each CTRS item in distinguishing therapeutic modalities.

5.3 Discriminating Session Quality

In the second experiment, we apply the same framework to the AnnoMI dataset using the Motivational Interviewing Skill Code (MISC). We compute semantic similarity scores between therapy sessions and MISC items to assess therapist fidelity to Motivational Interviewing (MI). Because the MISC specifies behaviour requirements that characterise high-quality MI practice, sessions annotated as high quality are expected to exhibit higher MISC-based similarity scores than those annotated as low quality.

Following the same procedure as in the first experiment, we compute a total MISC similarity score for each session. We then conduct t-tests and compute Cohen's d on the total similarity scores to evaluate the ability of the proposed method to distinguish between high- and low-quality MI sessions, compared with the baseline method.

6 Results and Discussion

6.1 Effectiveness in Discriminating Therapeutic Modalities

Figures 1 and 2 show the Cohen's d value, indicating how effectively the total CTRS similarity score can separate therapeutic modalities across experimental settings. All Cohen's d values are positive, indicating that CBT sessions consistently obtain higher CTRS similarity scores than SPS sessions, as expected given that CTRS measures CBT-specific therapist behaviours. In both figures, the highest convergent value of Cohen's d reaches around 0.85, with LLM-generated examples. Looking at the starting point of each curve (zero examples), the highest Cohen's d value lies around 0.5. Following Cohen (Cohen, 1977) and Lakens (Lakens, 2013), this represents an increase of 0.35 (70%) standard deviation units in group separation, corresponding to a substantially stronger differentiation between the two therapeutic modalities.

Significant improvement is also seen for the MISC-based experiment. As shown in Figure 4, the Cohen's d value significantly improves from zero to one/two examples, then gradually converges to around 0.7. This demonstrates an increase of around 0.55 standard deviation units in the separation between MI and SPS.

We interpret the differences in effect size as evidence that the proposed method captures sufficient fidelity-specific signal (e.g., CBT techniques required by CTRS and MI techniques required by MISC 2.5) to discriminate therapeutic modalities, and the performance improves with LLM-generated exemplars added.

6.2 Ablations

Our ablation studies give insights into different characteristics of our method. Figure 1 and 2 clearly show that the effectiveness of employing LLM-generated exemplars increases with the number of exemplars (N) used to compute semantic similarity. A clear turning point is at N=5, after which the gains gradually plateau. This indicates that only five examples could capture sufficient semantic information about different aspects of scale items. This finding gives us a "sweet spot" for utilising this technique.

Figure 1 compares different calculation methods of talk-turn level semantic similarity. Semantic similarity is calculated individually with each example, and then the top n similarity scores are averaged. A clear pattern from the figure is that the performance increases with n, and the best performance is achieved by averaging all scores. However, variation in performance is limited, and all lie around 0.8 after convergence.

Figure 2 compares different summarisation methods. Instead of averaging the top n highest talk-turn level semantic similarity scores, directly averaging the scores of all talk turns achieves the best performance. The intuition of designing this ablation study is to check if the top n similar talk turns are adequate to determine therapists' adherence to CBT techniques, excluding the noise caused by general speeches like greetings. However, the pattern shows that the more talk turns involved in calculating the session-level mean, the better the performance of separation is. This may be due to the fact that the total number of talk turns varies considerably; keeping the same number of talk turns for each session makes longer sessions lose information. On the other hand, averaging all talk turns keeps all information for each session and also normalises by the number of talk turns, resulting in a more representative score on the session level.

Figure 3 shows how the semantic similarity with each CTRS item contributes to the total Cohen's d value. The convergent values of Cohen's d for most items lie between 0.6 and 1.0 except "Agenda", demonstrating medium to high effect size on separating therapeutic modalities according to Cohen (Cohen, 1977). The most effective CTRS item is the 7th: guided discovery, achieving around 0.95



Figure 1: Cohen's d versus exemplar count for CTRS-based modality discrimination (CBCM vs SPS) under different exemplar-aggregation strategies. (Session-level aggregation strategy: average all)



Figure 2: Cohen's d versus exemplar count for CTRS-based modality discrimination (CBCM vs SPS) under different session-level similarity aggregation methods. (Exemplar aggregation strategy: average all)

Cohen's d value. Guided discovery is one of the core techniques of CBT, in which the therapist questions and guides the client to identify automatic thoughts. The use of this technique separates CBT from other modalities like SPS, where guided discovery is not necessarily used. On the contrary, appropriate agenda setting (a more general therapeutic skill), scores the lowest.

6.3 Effectiveness in Discriminating Session Quality

Figure 5 shows how semantic similarity discriminates high- and low-quality MI sessions with respect to the number of exemplars used. The Cohen's d value converges on 0.75, indicating a medium-to-large effect in discriminating between the two groups. We interpret this performance as evidence that example-enhanced semantic similarity scores can discriminate high and low therapists' adherence to a technique-driven modality scale. The pattern in the figure shows that with examples added, the Cohen's d value immediately shrinks,



Figure 3: Cohen's d versus exemplar count for individual CTRS items in distinguishing CBCM (CBT) from SPS sessions. (Exemplar aggregation strategy: average all; Session-level aggregation strategy: average all)



Figure 4: Cohen's d versus exemplar count for MISC-based semantic similarity in distinguishing MI from SPS sessions. (Exemplar aggregation strategy: average all; Session-level aggregation strategy: average all)

then gradually rises and stabilises at a higher value. This suggests that averaging more exemplars stabilises the representation (variance reduces).

However, the high value of Cohen's d at the zero-example point indicates the superiority of directly calculating semantic similarity with scale item descriptions. To dive deeper into why this happens, we look at how statistical values related to Cohen's d (numerator: difference between mean values of two groups; denominator: pooled standard deviation) change with respect to the number of examples used. According to Figure 6, the denominator, the pooled standard deviation, merely changes with n, indicating that adding examples does not add noise to the group deviation. On the other hand, the mean value for both groups shows a notable increase. This suggests that adding examplars in-



Figure 5: Cohen's d versus exemplar count for MISC-based semantic similarity in distinguishing high- versus low-quality MI sessions.



Figure 6: Components of Cohen's d (group means and pooled SD) across exemplar counts for MISC-based MI quality discrimination.

crease the semantic similarity with both high and low quality MI sessions. However, this increment is greater for low-quality sessions, shrinking the high–low mean gap, thus making the Cohen's d value drop. In other words, exemplar augmentation, although it improves the absolute value of semantic similarity, is making high- and low-quality MI sessions look more similar in embedding space.

One reason for the superiority of item-only semantic similarity is that this zero-example baseline actually contains a significant amount of example-related information: MISC items are already exemplar-rich, containing bullet-pointed behavioural indicators. Embedding that text yields a dense representation of the construct, including multiple facets of competence and sometimes a polarity (See Appendix D for an example). That is, the item itself already functions like a "prototype set" covering (i) what good MI looks like for that item, and (ii) what poor/problematic performance looks like, producing a strong high–low separation. On the other hand, LLM-generated exemplars, although closer to the way therapists talk in real psychotherapy sessions, all demonstrate positive therapist behaviours. Adding these exemplars can reduce sensitivity to low-quality sessions in the embedding space.

7 Future Work and Conclusion

In this paper, we introduce an LLM-powered example-augmented semantic similarity framework for directly inferring therapist fidelity signals from transcripts by aligning therapist talk with fidelity/skill scale items in an embedding space. Across two datasets, the approach consistently improves the discrimination of technique-driven therapeutic modality and more general approaches (e.g., MI vs SPS; CBT/CBCM vs SPS). This method offers methodological insights for inferring numerical representations of relative therapists' adherence to specific therapeutic techniques in an annotation-free and training-free approach. These fidelity signals can then be used for downstream computational linguistics tasks.

We also found that augmentation is scale-dependent: for within-modality quality on AnnoMI, the item-only baseline is strong because MISC definitions are already highly detailed and exemplar-like, making additional LLM utterance exemplars partly redundant and sometimes compressing high–low differences.

Future work directions include:

- Validate generalizability across more scales, modalities and clinical settings. In general, for scales that are specific to a particular modality (e.g. CTRS to measure CBT quality as opposed to WAI, which is modality-agnostic), it would be expected that a session employing that modality would score higher for a scale measuring that modality versus a session that is not employing that modality.
- Further refine the method with contrastive augmentation (high-quality vs low-quality exemplars).
- Enhance the aggregation method to emphasise discriminative turns rather than averaging all talk turns.
- Validate the framework against human-rated fidelity scores. For example, correlating framework outputs with human CTRS ratings for CBT sessions.

- Evaluate open-source LLMs as a replacement for commercial APIs in the exemplar generation step. This would improve reproducibility, since model weights are fixed and publicly available.

8 Limitations

While promising, our method and evaluation have some limitations. First is the imbalance and size of the evaluation datasets. Whilst not insignificant datasets in terms of therapy transcripts, both STEP and AnnoMI are relatively small in size (182 and 133). The AnnoMI dataset is highly imbalanced, with only 23 low-quality sessions. The STEP dataset is limited to a certain clinical context (focused on adolescents at ultra-high risk for psychosis in Melbourne, Australia). These factors might affect the generalisability of observed patterns. Similar evaluations should be run on larger and more balanced datasets for more robust results.

A further limitation concerns the cross-dataset confound in the between-modality experiment comparing MI and SPS sessions. MI sessions are drawn from the AnnoMI dataset, which consists of demonstration sessions sourced from public video-sharing platforms, while SPS sessions are drawn from the STEP dataset, which comprises real clinical sessions. These two groups differ not only in therapeutic modality but also in dataset characteristics. Consequently, observed differences in MISC-based similarity scores between MI and SPS sessions may partly reflect these characteristics rather than modality alone. Future work should seek to compare therapeutic modalities using sessions drawn from the same dataset and clinical context in order to isolate the effect of modality.

A critical limitation is the absence of validation against human-rated fidelity scores. The experiments demonstrate that similarity scores can statistically distinguish between therapeutic modalities and between session quality labels, but they do not establish whether these scores correlate with ratings that trained clinicians would assign using the same scales. Establishing this correspondence is a necessary step before clinical applications can be considered.

Another limitation is that the semantic similarity is not a full proxy for competence. It captures conceptual alignment, but many competence signals are interactional (e.g., timing, responsiveness to client change talk) or structural (e.g., reflection question balance, open question rate), which are not well represented by talk-turn level similarity scores. Moreover, aggregating turn-level scores into a single session value can hide short but important events like ruptures and confrontations. A session can score "high" while containing clinically significant low-competence segments.

9 Ethical Considerations

Semantic similarity scores derived from language models have limited interpretability and should not be treated as direct proxies for clinically validated rating scale scores. The mapping between numerical similarity values and clinically meaningful scores is unclear and requires systematic validation. Instead, these scores are more appropriately understood as relative indicators that capture comparative patterns across sessions. Their primary utility lies in supporting computational linguistic analyses or serving as auxiliary features in downstream models.

Semantic similarity scores could inherit bias and fairness issues from the language models they rely on. LLM-generated exemplars reflect LLM's training materials that could inherently contain cultural and linguistic biases. These exemplars may privilege particular styles of therapist talk (e.g. particular clinician norms and dialects), and unfairly lower similarity scores for therapists from underrepresented groups.

References

Jacob Cohen. 1977. The t test for means. In *Statistical Power Analysis for the Behavioral Sciences*, pages 19–74. Elsevier.

Andrew Darchuk, Victor Wang, David Weibel, Jennifer Fende, Timothy Anderson, and Adam Horvath. 2000. Working Alliance Inventory – Observer Form (WAI-O):.

Avisha Das, Salih Selek, Alia R. Warner, Xu Zuo, Yan Hu, Vipina Kuttichi Keloth, Jianfu Li, W. Jim Zheng, and Hua Xu. 2022. Conversational bots for psychotherapy: A study of generative transformer models using domain-specific dialogues. In *Proceedings of the 21st Workshop on Biomedical Language Processing*, pages 285–297, Dublin, Ireland. Association for Computational Linguistics.

Nikolaos Flemotomos, Victor Martinez, James Gibson, David Atkins, Torrey Creed, and Shrikanth Narayanan. 2018. Language features for automated evaluation of cognitive behavior psychotherapy sessions. In *Interspeech 2018*, pages 1908–1912. ISCA.

Nikolaos Flemotomos, Victor R. Martinez, Zhuohao Chen, Torrey A. Creed, David C. Atkins, and Shrikanth Narayanan. 2021. Automated quality assessment of cognitive behavioral therapy sessions through highly contextualized language representations. *PLOS ONE*, 16(10):e0258639.

James Gibson, Nikolaos Malandrakis, Francisco Romero, David C. Atkins, and Shrikanth S. Narayanan. 2015. Predicting therapist empathy in motivational interviews using language features inspired by psycholinguistic norms. In *Interspeech 2015*, pages 1947–1951. ISCA.

Simon B. Goldberg, Scott A. Baldwin, Kritzia Merced, Derek D. Caperton, Zac E. Imel, David C. Atkins, and Torrey Creed. 2020. The structure of competence: Evaluating the factor structure of the cognitive therapy rating scale. *Behavior Therapy*, 51(1):113–122. Publisher: Elsevier BV.

A. O. Horvath and L. S. Greenberg. 1989. Development and validation of the working alliance inventory. *Journal of Counseling Psychology*, 36:223–233.

Jon M Houck, Theresa B Moyers, William R Miller, Lisa H Glynn, and Kevin A Hallgren. 2010. Motivational Interviewing Skill Code (MISC) 2.5.

Zac E. Imel, Brian T. Pace, Christina S. Soma, Michael Tanana, Tad Hirsch, James Gibson, Panayiotis Georgiou, Shrikanth Narayanan, and David C. Atkins. 2019. Design feasibility of an automated, machine-learning based feedback system for motivational interviewing. *Psychotherapy*, 56(2):318–328.

Daniël Lakens. 2013. Calculating and reporting effect sizes to facilitate cumulative science: a practical primer for t-tests and ANOVAs. *Frontiers in Psychology*, 4.

Quoc V. Le and Tomas Mikolov. 2014. Distributed representations of sentences and documents. *arXiv preprint*. ArXiv:1405.4053 [cs].

Anqi Li, Yu Lu, Nirui Song, Shuai Zhang, Lizhi Ma, and Zhenzhong Lan. 2024. Understanding the therapeutic relationship between counselors and clients in online text-based counseling using LLMs. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 1280–1303, Miami, Florida, USA. Association for Computational Linguistics.

Baihan Lin, Djallel Bouneffouf, Yulia Landa, Rachel Jespersen, Cheryl Corcoran, and Guillermo Cecchi. 2025. COMPASS: Computational mapping of patient-therapist alliance strategies with language modeling. *Translational Psychiatry*, 15(1):166.

Baihan Lin, Guillermo Cecchi, and Djallel Bouneffouf. 2022. SupervisorBot: NLP-annotated real-time recommendations of psychotherapy treatment strategies with deep reinforcement learning. *arXiv preprint*. ArXiv:2208.13077 [cs].

Baihan Lin, Guillermo Cecchi, and Djallel Bouneffouf. 2024. Working alliance transformer for psychotherapy dialogue classification. In *Proceedings of the 6th Clinical Natural Language Processing Workshop*, pages 64–69, Mexico City, Mexico. Association for Computational Linguistics.

Barnaby Nelson, G. Paul Amminger, Hok Pan Yuen, Nicky Wallis, Melissa J. Kerr, Lisa Dixon, Cameron Carter, Rachel Loewy, Tara A. Niendam, Martha Shumway, Sarah Morris, Julie Blasioli, and Patrick D. McGorry. 2018. Staged treatment in early psychosis: A sequential multiple assignment randomised trial of interventions for ultra high risk of psychosis patients. *Early Intervention in Psychiatry*, 12(3):292–306.

Verónica Pérez-Rosas, Xinyi Wu, Kenneth Resnicow, and Rada Mihalcea. 2019. What makes a good counselor? Learning to distinguish between high-quality and low-quality counseling conversations. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 926–935, Florence, Italy. Association for Computational Linguistics.

Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence embeddings using siamese BERT-Networks. *arXiv preprint*. ArXiv:1908.10084 [cs].

Alice Rueda, Argyrios Perivolaris, Niloy Roy, Dylan Weston, Sarmed Shaya, Zachary Cote, Martin Ivanov, Bazen G. Teferra, Yuqi Wu, Sirisha Rambhatla, Divya Sharma, Andrew Greenshaw, Rakesh Jetly, Yanbo Zhang, Bo Cao, Reza Samavi, Sridhar Krishnan, and Venkat Bhat. 2025. Estimating quality in therapeutic conversations: A multi-dimensional natural language processing framework. *arXiv preprint*. ArXiv:2505.06151 [cs].

João Sedoc, Daphne Ippolito, Arun Kirubarajan, Jai Thirani, Lyle Ungar, and Chris Callison-Burch. 2019. ChatEval: A tool for chatbot evaluation. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics (Demonstrations)*, pages 60–65, Minneapolis, Minnesota. Association for Computational Linguistics.

Dehua Tao, Tan Lee, Harold Chui, and Sarah Luk. 2022. Hierarchical attention network for evaluating therapist empathy in counseling session. In *Interspeech 2022*, pages 2008–2012. ISCA.

Zixiu Wu, Simone Balloccu, Vivek Kumar, Rim Helaoui, Diego Reforgiato Recupero, and Daniele Riboni. 2023. Creation, analysis and evaluation of AnnoMI, a dataset of expert-annotated counselling dialogues. *Future Internet*, 15(3):110.

Bo Xiao, Chewei Huang, Zac E. Imel, David C. Atkins, Panayiotis Georgiou, and Shrikanth S. Narayanan. 2016. A technology prototype system for rating therapist empathy from audio recordings in addiction counseling. *PeerJ Computer Science*, 2:e59.

James Zech, Victoria Kaitlin Foley, Thomas D. Hull, and Timothy Anderson. 2023. Assessing the quality of digital patient-therapist communication: the development and validation of a text-based facilitative interpersonal skills task. *Psychotherapy Research*, 33(6):743–756.

James M. Zech, Robert Steele, Victoria K. Foley, and Thomas D. Hull. 2022. Automatic rating of therapist facilitative interpersonal skills in text: A natural language processing application. *Frontiers in Digital Health*, 4:917918.

A Cognitive Therapy Rating Scale (CTRS) item titles

Cognitive Therapy Rating Scale (CTRS) item titles (Goldberg et al., 2020)

1. Agenda
2. Feedback
3. Understanding
4. Interpersonal Effectiveness
5. Collaboration
6. Pacing and Efficient Use of Time
7. Guided Discovery
8. Focusing on Key Cognitions or Behaviors
9. Strategy for Change
10. Application of Cognitive-behavioral Techniques
11. Homework

B System prompt for LLM to generate exemplars (CTRS as an example)

"You will be given the description of a Cognitive Therapy Rating Scale (CTRS) item, describing the desired therapist behaviour. Based on this description, generate 10 unique therapist talk turns that could realistically occur in psychotherapy and reflect the specified behaviour. The examples should differ from one another, illustrate different aspects of the item, and span a range of therapy scenarios. Return a valid JSON object with a single key 'examples' whose value is an array of 10 strings. Do not include Markdown or any extra text."

C Algorithm for semantic similarity score computation

Algorithm 1 Computation of Session-Level Semantic Similarity Scores

Require: Session transcript with therapist talk turns $\mathcal{T} = \{t_1, \ldots, t_M\}$
Scale items $\mathcal{I} = \{i_1, \ldots, i_N\}$
Exemplars for each item $\mathcal{E}_n = \{e_{n1}, \ldots, e_{nK_n}\}$
Embedding function $f(\cdot)$
Ensure: Session-level similarity scores $\mathbf{S} = \{S_1, \ldots, S_N\}$
Compute embeddings for all therapist turns: $v_m \leftarrow f(t_m)$ for $m = 1, \ldots, M$
Compute embeddings for all exemplars: $u_{nk} \leftarrow f(e_{nk})$ for all n, k
for $m = 1$ to M **do**
    for $n = 1$ to N **do**
        $s_{mn} \leftarrow \frac{1}{K_n} \sum_{k=1}^{K_n} \cos(v_m, u_{nk})$ ▷ Item-specific similarity for turn t_m
    end for
end for
for $n = 1$ to N **do**
    $S_n \leftarrow \frac{1}{M} \sum_{m=1}^{M} s_{mn}$ ▷ Aggregate across all therapist turns
end for
return S

D MISC 2.5 item definition for the highest point for item "Direction"

Clinician exerts influence on the session and generally does not miss opportunities to direct client toward the target behavior or referral question.

Examples: • Agenda-setting mentions the target behavior • Clinician is transparent in concern about the target behavior • Clinician manages time well and transitions between therapeutic tasks smoothly • Clinician consistently and smoothly directs the client's discourse toward change of a target behavior • Balance of time in the session is spent discussing possible change, rather than the history of the problem Clinician dominates session and does not allow client to wander from target behavior. (Houck et al., 2010)

Mirroring Minds: Asymmetric Linguistic Accommodation and Diagnostic Identity in ADHD and Autism Reddit Communities

Saad Mankarious[1*] **Nour Zeid**[2*] **Iyad Ait Hou**[1]
Rebecca Hwa[1] Aya Zirikly[1]
[1] The George Washington University [2] Texas A&M University
{saadm, iyad.aithou, rebecca.hwa, ayah.zirikly}@gwu.edu
nourzzeid@gmail.com

Abstract

Social media research on mental health has focused predominantly on detecting and diagnosing conditions at the individual level. In this work, we shift attention to *intergroup* behavior, examining how two prominent neurodivergent communities, ADHD and autism, adjust their language when engaging with each other on Reddit. Grounded in Communication Accommodation Theory (CAT), we first establish that each community maintains a distinct linguistic profile as measured by the Linguistic Inquiry and Word Count (LIWC) dictionary. We then show that these profiles shift in opposite directions when users cross community boundaries: features that are elevated in one group's home community decrease when its members post in the other group's space, and vice versa, consistent with convergent accommodation. We further demonstrate the practical stakes of this accommodation: classifiers trained to distinguish the two communities from their in-group language lose roughly **30 percentage points** of accuracy, falling below chance, when applied to the same users' cross-community posts, confirming that accommodation, not just diagnosis, drives their predictions. Finally, in an exploratory longitudinal analysis around the moment of public diagnosis disclosure, we find that its effects on linguistic style are small and, in some cases, directionally opposite to cross-community accommodation, providing initial evidence that situational audience adaptation and longer-term identity processes may involve different mechanisms. Our findings contribute to understanding intergroup communication dynamics among neurodivergent populations online and carry implications for community moderation and clinical perspectives on these conditions.

1 Introduction

Language carries diagnostic identity, a phenomenon made observable in the pseudonymous, text-driven mental health communities of Reddit. For instance, users diagnosed with ADHD produce posts bearing measurable traces of that identity compared to a healthy person, such as decreased analytical language and increased markers of raw authenticity (Mankarious et al., 2025). On the other hand, those diagnosed with autism leave a different trace: increased social references and increased emotional tones (Mankarious et al., 2025; Fong et al., 2025). These are not stereotypes but statistical regularities that emerge robustly across thousands of users and hundreds of thousands of posts. Yet our understanding of what happens to these identity-linked markers when a user steps outside their home community remains limited.

Addressing this gap requires bridging two research traditions that have largely developed in isolation. The first is the computational analysis of mental health in social media, which has produced a rich literature on detecting and characterizing conditions at the individual level (Chancellor and De Choudhury, 2020). Although this body of work has been enormously productive, it has overwhelmingly treated users as isolated data points rather than members of dynamic communities; consequently, the macro-level dynamics of how users communicate across community boundaries remain theoretically unaccounted for. The second tradition is Communication Accommodation Theory (CAT; Giles and Soliz, 2015), which has a decades-long tradition of studying how people adjust their communicative style, converging toward, diverging from, or maintaining their style, in response to social context and identity goals. While CAT has demonstrated remarkable explanatory power across decades of research, it has been applied predominantly in face-to-face intergroup contexts (Zhang and Giles, 2017), leaving its potential as a macro-level framework for understanding dynamic communicative behavior across digital community boundaries largely untapped. Recent

[*]Equal contribution. Corresponding author.

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 282–297
July 4, 2026 ©2026 Association for Computational Linguistics

work validating CAT in online settings (Danescu-Niculescu-Mizil et al., 2011; Boghrati et al., 2018; Tamburrini et al., 2015) and extending it to affective dimensions (Bernhold and Giles, 2022) suggests the theory is well positioned to fill precisely the gap the first tradition leaves open.

The gap matters for a concrete reason. Online neurodivergent communities are among the largest and most active mental health spaces on the internet. On Reddit alone, r/ADHD and r/autism together host millions of subscribers who use these spaces not just for information exchange but for identity construction, peer support, and diagnostic sense-making (Rideout and Robb, 2021) Members of these communities regularly cross-post: an ADHD-diagnosed user may seek advice in r/autism, or an autism-diagnosed user may share experiences in r/ADHD. When they do, they face an implicit communicative choice: maintain their own group's linguistic style, or adapt to the norms of the host community.

The stakes of this communicative choice are not merely social; they directly undermine the computational tools built to study these communities. A large body of work trains classifiers to distinguish neurodivergent conditions from social media language (Chancellor and De Choudhury, 2020). But if a user's measured linguistic profile shifts with their audience, such a classifier may be learning the signature of a *community* rather than of a *condition*. We test this directly in a motivating experiment (Section 4.1): classifiers trained to separate ADHD from autism users on their in-group posts reach 66–68% accuracy, but the same models, applied to the same users' cross-community posts, collapse to 36–37%, below chance, a ∼30-point drop that is statistically significant and consistent across logistic regression, linear SVC, and random forest. Accommodation, in other words, is not a nuisance to be denoised away; it actively determines what these models predict. This finding both motivates and frames the present study: to understand why diagnostic classifiers fail across community boundaries, we must first characterize the distinct community styles (H1) and the accommodation that operates between them (H2).

To analyze how these two groups communicate on Reddit using CAT lens, we adopt following framework, Grounded in CAT and the prior work reviewed above:

H1 (Distinct Baseline Styles) ADHD and autism communities exhibit measurably distinct linguistic profiles when posting in their respective home communities.

H2 (Cross-Community Convergence) When users post in the other community, their linguistic style shifts toward the host community's baseline, consistent with convergent accommodation.

H3 (Classifier Vulnerability) Because diagnostic classifiers trained on in-group language anchor on community-specific stylistic norms rather than condition-intrinsic traits, their accuracy degrades sharply, dropping below chance, when the same users post across community boundaries.

RQ (Diagnosis Disclosure) Does public disclosure of a diagnosis produce within-user linguistic changes, and if so, are these changes consistent with, independent of, or opposed to the situational accommodation captured in H2? We treat this as exploratory given the inherent power limitations of longitudinal within-user analysis.

Contributions. Our work makes the following contributions:

- We provide the first study of cross-community linguistic accommodation between neurodivergent groups on social media, shifting the focus from individual-level diagnosis detection to intergroup behavioral dynamics.
- We establish distinct linguistic profiles for ADHD and autism communities and demonstrate that these profiles undergo systematic, bidirectional shifts when users cross community boundaries, with medium effect sizes and a mirror-image pattern across multiple LIWC dimensions.
- We demonstrate a concrete consequence of this accommodation for computational mental health: diagnostic classifiers that distinguish the two communities on in-group posts lose roughly 30 absolute points of accuracy, collapsing to below chance, when applied to the same users' cross-community posts, an algorithm-agnostic vulnerability that reframes such "noise" as a measurable social strategy.

- We present an exploratory longitudinal analysis of pre-/post-diagnosis linguistic changes, finding initial evidence that situational accommodation and identity-related shifts may operate through different mechanisms, though the small effect sizes warrant cautious interpretation.

2 Data

2.1 Source Dataset

We draw on the Mindset dataset (Mankarious et al., 2025), a recently released Reddit corpus in which users are identified via high-precision self-reported diagnosis. Mindset implemented rigorous filtering to ensure label quality, including excluding weak diagnosis statements (e.g., "I have adhd", "I think I have adhd") in favour of stronger statements (e.g., "My doctor diagnosed me with ADHD"), and excluding negated diagnoses (e.g., "... did not diagnose..."). In the absence of clinically validated ground truth, we adopt self-diagnosis labels as ground, consistent with the literature (Cohan et al., 2018; Coppersmith et al., 2015; Mankarious and Zirikly, 2025; Mankarious et al., 2025; Ernala et al., 2019).

From Mindset, we selected the ADHD and autism groups. Because our analysis requires cross-community posting, we did not use Mindset's pre-processed posts directly, which are heavily filtered to remove mental health content. Instead, we re-fetched each user's full posting history from Reddit using the same API[1], retaining posts that include mental health discussions necessary for the accommodation analysis. We additionally collected metadata including interaction scores and parent post identifiers.

2.2 Cross-Community Partitioning

To operationalize accommodation, we partitioned the data into four subsets based on the user's diagnostic group and the subreddit in which they posted (Table 10): *ADHD in ADHD* (posts by ADHD-diagnosed users in r/ADHD), *ADHD in Autism* (posts by ADHD-diagnosed users in r/autism), and the symmetric pair for autism-diagnosed users. This subreddit-based partitioning is motivated by two considerations: (1) the vast majority of each group's contributions are concentrated in these two subreddits, and (2) keyword-based topic filtering would be unreliable, since discussions in either subreddit frequently touch on the other condition. We verified that no users appear in both diagnostic groups, ensuring that the four subsets represent cleanly separated populations.

2.3 Preprocessing

We excluded posts that had been removed by moderators or that contained fewer than five words after tokenization, as these are unlikely to carry sufficient stylistic signal for LIWC analysis.

3 Experiments

3.1 Linguistic Feature Extraction

We processed all posts through LIWC-22 (Boyd et al., 2022), extracting scores across 115 categories spanning psychological processes, linguistic dimensions, and summary variables. To account for pseudoreplication, the inflation of statistical significance when multiple posts from the same user are treated as independent observations, we aggregated all LIWC scores at the *user* level by averaging across each user's posts within each condition (Walls and Schafer, 2006). This ensures that each user contributes a single data point per analysis, yielding conservative but reliable estimates.

Several LIWC categories carry technical meanings that diverge from their everyday connotations; Table 1 defines the ones whose interpretation is least intuitive, and Appendix G (Table 11) defines every category featured in our figures and tables. Crucially, LIWC scores are word-frequency rates rather than measures of communicative intent: a high SOCIAL score reflects how often a user *writes about* social matters, not how socially engaged they are, and a high AUTHENTIC score reflects a spontaneous, first-person style rather than any judgment of honesty.

3.2 Statistical Methodology

All group comparisons use Welch's t-test (unequal variances) with Cohen's d as the effect size measure, accompanied by 95% confidence intervals computed via the noncentral t-distribution (see Appendix F for details). Following Benjamini and Hochberg (1995), we apply the Benjamini–Hochberg procedure to control the false discovery rate (FDR) at $q = 0.05$ within each experiment, correcting for the 115 simultaneous tests across LIWC categories. Only categories that remain significant after FDR correction are reported. We adopt stan-

[1] https://github.com/ArthurHeitmann/arctic_shift

Table 1: LIWC categories whose technical meaning most diverges from everyday usage. Scores are word-frequency rates, not measures of intent. † marks *summary variables*. The full glossary of all featured categories is in Appendix G (Table 11).

Category	One-line definition
AUTHENTIC†	Spontaneous, first-person style (more *I/me*, fewer hedges); not a measure of honesty.
CLOUT†	Confident, authoritative stance (more *we/you*, fewer *I*); social standing, not actual influence.
SOCIAL	Words about people and social processes; *writing about* social matters, not social engagement.
SOCREFS	References to other people (*they*, *you*, names); mentions, not actual interaction.

dard effect size thresholds: $|d| < 0.20$ negligible, $0.20 \leq |d| < 0.50$ small, $0.50 \leq |d| < 0.80$ medium, $|d| \geq 0.80$ large (Cohen, 1988).

3.3 Operationalizing Accommodation

Classical CAT measures accommodation at the conversational level: speaker A adjusts toward speaker B within a specific exchange. In asynchronous online communities, direct pairing is not always possible. Following Danescu-Niculescu-Mizil et al. (2011) and Tamburrini et al. (2015), we measure *community-level convergence*: whether the same user's linguistic profile shifts toward the host community's aggregate norms when posting in a different subreddit. This within-user design means each user serves as their own control, ruling out subpopulation confounds. The critical evidence for *accommodation* rather than mere *change* is directionality: ADHD users decrease on ADHD-high features and increase on autism-high features when visiting r/autism, and autism users show the exact mirror pattern. Random variation or topic effects would not produce this symmetric, baseline-aligned pattern across multiple independent LIWC categories.

3.4 Motivating Experiment: Classifier Vulnerability under Accommodation (H3)

Before turning to the CAT analysis, we establish the practical stakes of accommodation with a cross-community classification experiment that directly tests **H3**. The standard computational paradigm trains a model to distinguish diagnostic groups from their in-group language; we ask whether such a model survives contact with the same users' cross-community language.

Setup. We define two evaluation environments. The *in-group* (baseline) set comprises posts by ADHD users in r/ADHD (class 0) and autism users in r/autism (class 1), the standard diagnostic-classification setting. The *cross-community* (out-group) set comprises posts by the *same* users in the other community: ADHD users in r/autism (class 0) and autism users in r/ADHD (class 1). Each post is represented by 13 LIWC categories that distinguish the two communities (TIME, ACHIEVE, AUTHENTIC, WORK, SOCREFS, SUBSTANCES, ACQUIRE, SOCIAL, THEY, CLOUT, TONE, I, HEALTH; cf. E1), standardized (z-scored) using statistics fit exclusively on training folds.

Protocol. To prevent user leakage, we use 5-fold `GroupKFold` cross-validation grouped by username, so no user appears in both the training and test sets. In each fold we (1) train on the in-group posts of the training users, (2) evaluate on the in-group posts of the held-out users (baseline diagnostic accuracy), and (3) evaluate on the cross-community posts of those *same* held-out users (robustness to accommodation). We test three algorithm families, logistic regression, linear SVC, and random forest, all with balanced class weights, to assess whether any vulnerability is algorithm-agnostic. We report mean accuracy across folds and test the per-fold accuracy drop with a paired t-test.

3.5 Experiment 1: Baseline Linguistic Styles (H1)

To test H1, we compared diagnosed ADHD users posting in their home community (r/ADHD, $n = 7{,}758$ users) against diagnosed autism users posting in their home community (r/autism, $n = 5{,}706$ users). This between-group comparison characterizes the distinct baseline stylistic profiles against which accommodation effects can be measured.

3.6 Experiment 2: Cross-Community Accommodation (H2)

To test H2, we conducted within-group comparisons of each diagnostic group's language when posting in their home community versus the other community:

- ADHD users: language in r/ADHD (in-group) vs. r/autism (out-group)

- Autism users: language in r/autism (in-group) vs. r/ADHD (out-group)

If convergent accommodation occurs, we expect shifts in the direction of the host community's baseline for categories identified in E1. We additionally examine whether the two groups' shifts are *mirror images*, that is, whether categories that shift upward for one group shift downward for the other. See appendix E for a discussion on potential selection bias in this experiment.

3.7 Experiment 3: Exploratory Longitudinal Analysis (RQ)

To address the exploratory research question, we conducted within-user paired comparisons of language use before and after each user's first public diagnosis disclosure. This analysis is restricted to users who have posts in both pre- and post-disclosure periods within a given cross-community dataset (≥ 3 posts in each period). The temporal structure of user activity varies across datasets; see Appendix D (Table 9) for average pre- and post-diagnosis posting spans. By comparing E3 effect sizes against E2 effect sizes for the same categories, we assess whether diagnosis disclosure produces changes that are consistent with, independent of, or opposed to situational accommodation. We emphasize that this analysis is exploratory: the within-user design reduces sample sizes substantially, and the resulting effect sizes should be interpreted with appropriate caution.

4 Results

4.1 Motivating Experiment: Classifier Vulnerability (H3)

Table 2 reports the outcome. On in-group data, all three models distinguish ADHD from autism posts at 66.0–67.6% accuracy. Applied to the *same held-out users'* cross-community posts, accuracy collapses to 36.0–37.4%, below the 50% chance baseline, a ∼30 percentage-point drop that is highly significant for every model ($p < 10^{-5}$, paired t-test across folds). Because the GroupKFold design rules out memorization of individual users, and because the collapse is near-identical across linear (logistic regression, linear SVC) and ensemble (random forest) decision boundaries, the vulnerability is algorithm-agnostic.

This result supports **H3** and motivates the remainder of the paper: the classifiers anchor on the linguistic norms of the *community environment* rather than condition-intrinsic traits, so when users accommodate to a new community the in-group decision boundary fails systematically, even inverting below chance. The two experiments that follow explain why, by characterizing the distinct community styles (E1) and the bidirectional accommodation between them (E2).

4.2 E1: Baseline Stylistic Differences (H1)

Table 3 presents the 10 LIWC categories with the largest absolute effect sizes between ADHD users in r/ADHD ($n = 7{,}758$) and autism users in r/autism ($n = 5{,}706$).

Across 115 LIWC categories, user-level comparison revealed small-to-medium effect sizes (maximum $|d| = 0.76$). ADHD users scored higher on TIME ($d = 0.76$), ACHIEVE ($d = 0.60$), and AUTHENTIC ($d = 0.59$), while autism users scored higher on SOCREFS ($d = -0.56$), SOCIAL ($d = -0.52$), and THEY ($d = -0.45$). All confidence intervals are narrow and exclude zero, confirming reliable between-group differences. These directions are independently attested in prior research: ADHD self-disclosure is marked by distinctive patterns around achievement, temporal orientation, and self-reference (Guntuku et al., 2019), matching the TIME, ACHIEVE, and AUTHENTIC elevations we observe, while autism discourse is characterized by elevated social references (Fong et al., 2025; Boorse et al., 2019), matching the SOCREFS, SOCIAL, and THEY elevations. These results support **H1**: the two communities maintain distinct and measurable linguistic profiles in their home communities, consistent with prior work on these populations' language patterns (Lyons et al., 2018). The full set of 15 significant categories is reported in Appendix B.

4.3 E2: Cross-Community Accommodation (H2)

Table 4 summarizes the categories with the largest bidirectional shifts. When ADHD users posted in r/autism, they showed decreased AUTHENTIC ($d = -0.61$) and TIME ($d = -0.70$), and increased SOCIAL ($d = +0.44$) and CLOUT ($d = +0.43$). When autism users posted in r/ADHD, the pattern reversed: increased AUTHENTIC ($d = +0.33$) and TIME ($d = +0.43$), decreased SOCIAL ($d = -0.47$) and CLOUT ($d = -0.31$). In each case, the shift direction aligns with the host community's baseline from E1.

As discussed in Section 3.3, the evidence for

Table 2: Motivating experiment: mean classification accuracy across 5 user-isolated (GroupKFold) folds. Models are trained on in-group posts and evaluated on both the in-group and the cross-community posts of held-out users. The accuracy drop is the penalty for evaluating out-group posts; all drops are statistically significant ($p < 0.001$, paired t-test across folds).

Model	In-group Acc.	Cross-community Acc.	Accuracy Drop	p-value
Logistic Regression	66.01%	36.16%	−29.85%	2.0×10^{-6}
Linear SVC	65.67%	35.98%	−29.69%	1.9×10^{-6}
Random Forest	67.60%	37.37%	−30.22%	9.0×10^{-7}

Table 3: Baseline linguistic differences (E1, top 10). Category definitions in Table 11.

Category	ADHD	Autism	d [95% CI]
time	5.62	3.93	0.76 [.72, .80]
achieve	1.59	0.95	0.60 [.56, .64]
Authentic	78.4	69.4	0.59 [.55, .63]
work	2.09	1.26	0.58 [.54, .62]
socrefs	5.05	6.68	−0.56 [.52, .60]
substances	0.46	0.05	0.55 [.51, .59]
acquire	1.29	0.83	0.53 [.49, .57]
Social	8.99	11.3	−0.52 [.48, .56]
they	0.59	0.94	−0.45 [.41, .49]
Lifestyle	3.19	2.35	0.45 [.41, .49]

All FDR-corrected ($q < 0.05$). $+d$: higher in ADHD; $-d$: higher in autism. CIs report absolute $|d|$ bounds.

Table 4: Cross-community accommodation (E2). Category definitions in Table 11.

Category	ADHD→Aut. d [95% CI]	Aut.→ADHD d [95% CI]
Authentic	−.61 [.53,.69]	+.33 [.29,.37]
time	−.70 [.62,.78]	+.43 [.39,.47]
Social	+.44 [.36,.52]	−.47 [.43,.51]
Clout	+.43 [.35,.51]	−.31 [.27,.35]
socrefs	+.45 [.37,.53]	−.47 [.43,.51]
i	−.37 [.29,.45]	+.11 [.07,.15]
health	−.25 [.17,.33]	+.44 [.40,.48]

All FDR-corrected ($q < 0.05$). Every category shifts in opposite directions for the two groups. CIs report absolute $|d|$ bounds.

accommodation is this mirror-image directionality, which holds across eight categories (Table 6). The two largest effects involve AUTHENTIC and CLOUT, which are topic-independent summary variables [2] (Appendix H), providing some reassurance against a purely topical explanation. Effect sizes are small-to-medium ($|d| = 0.31$–0.70). Importantly, these categories are not merely selected for their bidirectional symmetry: they are also among the largest-magnitude shifts overall within each group, ranking near the top across all 115 LIWC dimensions rather than constituting a hand-picked subset of small effects (for ADHD users visiting r/autism, TIME and AUTHENTIC are the two largest shifts of any category). The convergent pattern therefore reflects the dominant axes of each group's adaptation. These results support **H2**. Figure 1 visualizes the pattern; a quantitative summary is in Appendix A.

[2]Authentic category captures honest, personal language such as 'me', 'my', 'but' etc, indicating careful cognitive processing. Clout category captures a speaker's standing within a social hierarchy, indicated by use of terms such as first person plural 'we', 'us' (high clout) and first person singular 'i' (low clout)

4.4 E3: Exploratory Longitudinal Analysis (RQ)

We conducted within-user paired comparisons of language use before and after diagnosis disclosure. The full results are reported in Appendix D; we summarize the key findings here.

The effects are uniformly small ($|d| \leq 0.22$) with wide confidence intervals. For ADHD users posting in r/autism, only HEALTH ($d = -0.22$) and PREP ($d = -0.20$) changed significantly, with no changes for AUTHENTIC or CLOUT. For autism users posting in r/ADHD, diagnosis disclosure was associated with decreased AUTHENTIC ($d = -0.12$) and increased CLOUT ($d = +0.11$), notably, in the *opposite* direction from the E2 accommodation pattern for these same categories.

Addressing **RQ**: diagnosis disclosure is associated with detectable within-user changes, but the effects are weak and should be interpreted as preliminary. Table 8 (Appendix D) compares E2 and E3 effect sizes for key categories, showing that accommodation effects are consistently 3–23× larger than post-diagnosis changes.

4.5 Summary

H1 is well supported: the two communities maintain distinct baseline linguistic profiles (medium

effect sizes, narrow CIs). **H2** is supported: both groups converge toward the host community's norms when cross-posting, with a systematic mirror-image pattern that is difficult to attribute to topic effects alone (medium effect sizes). **H3** is strongly supported: diagnostic classifiers trained on in-group language suffer a large, algorithm-agnostic accuracy collapse ($\sim$30 points, to below chance) when evaluated on the same users' cross-community posts, confirming that accommodation, not just diagnosis, drives their predictions. The exploratory **RQ** yields initial but inconclusive evidence: diagnosis disclosure produces small and sometimes directionally opposite effects relative to situational accommodation.

5 Related Work

5.1 Communication Accommodation Theory

Communication Accommodation Theory (CAT) provides a foundational framework for understanding how individuals adjust their communication styles in social interactions (Giles, 1973). CAT posits that speakers may either converge toward their interlocutor's style to seek approval or diverge to emphasize distinctiveness. The theory has been widely applied across contexts, including psychotherapy, where accommodation patterns reflect therapeutic rapport and power dynamics (Ferrara, 1991).

5.2 CAT in Social Media and Online Communities

Recent work has extended CAT to digital contexts, particularly social media platforms where interaction patterns are publicly observable. Danescu-Niculescu-Mizil et al. (2011) developed a rigorous framework for measuring linguistic accommodation on Twitter, demonstrating that users adapt their language to align with conversational partners. Their approach focused on function words as stylistic markers and introduced probabilistic methods to isolate accommodation from topic-driven similarity. On Reddit, Boghrati et al. (2018) showed that commenters systematically accommodate to the syntactic style of original posts, providing evidence for accommodation across diverse interactional contexts. Tamburrini et al. (2015) found that members of online communities converge in their linguistic practices over time, and Kovács and Kleinbaum (2021) showed that affective convergence follows a similar pattern within communities. Of direct relevance to our work, Sharma and De Choudhury (2018) examined accommodation across 55 Reddit mental health communities, finding a positive relationship between the degree of accommodation exhibited in posts and the level of social support received. However, most of this work has examined accommodation *within* a single community or between pairs of interlocutors. Our work differs by examining accommodation *across* two distinct communities, specifically, what happens when a member of one diagnostic community posts in the other's space.

5.3 LIWC and Mental Health Discourse

Linguistic Inquiry and Word Count (LIWC) has been widely employed to characterize mental health discourse in online communities (Pennebaker et al., 2015). Lyons et al. (2018) analyzed language patterns across multiple mental health conditions on discussion forums, identifying distinctive linguistic markers associated with various conditions. Within autism research, LIWC has been used to identify subtle language differences in narrative production (Boorse et al., 2019). ADHD communities have been less studied linguistically, though work on ADHD self-disclosure suggests that these users employ distinctive patterns around achievement, temporal orientation, and self-reference (Guntuku et al., 2019). A growing body of work uses NLP to detect mental health conditions from social media text (Chancellor and De Choudhury, 2020), but this line of research treats users as isolated individuals rather than members of interacting communities. Our work extends this by comparing ADHD and autism communities directly, both in baseline styles and accommodation patterns.

5.4 Identity, Disclosure, and Mental Health on Reddit

The moment at which an individual publicly discloses a mental health diagnosis has been recognized as a pivotal identity event in both clinical and social-psychological literature (Corrigan et al., 2015). Reddit has emerged as a valuable source for studying mental health discourse due to its anonymous, community-based structure (De Choudhury and De, 2014). On Reddit, self-disclosure of a diagnosis often functions as an identity claim that restructures how an individual participates in community discourse (De Armond et al., 2020). More recently, researchers have examined identity for-

mation and disclosure processes in neurodivergent populations, highlighting the developmental trajectory of diagnostic identity (DePape et al., 2025) and how autism social identification predicts disclosure behaviors (Togher et al., 2023). Prior work has examined how disclosure affects reception by others, but less attention has been given to how it changes the discloser's own linguistic behavior over time. Our longitudinal analysis addresses this gap.

6 Discussion

This study applied Communication Accommodation Theory to intergroup linguistic dynamics between ADHD and autism communities on Reddit. The two communities maintain distinct baseline profiles (H1), and users' language converges toward the host community in a mirror-image pattern when crossing boundaries (H2). This accommodation carries a concrete computational cost: in-group classifiers lose $\sim$30 points of accuracy, falling below chance, on the same users' cross-community posts (H3). By contrast, public diagnosis disclosure produced only small and sometimes directionally opposite changes (RQ, $|d| \leq 0.22$), initial evidence that situational and identity-related processes differ, though these small effects warrant cautious interpretation.

To move beyond atheoretical description of these macro-level patterns, we propose a *neuro-intercultural lens* that extends CAT's intercultural encounter model (Giles, 2016) to neurodivergent communities, treating them as distinct cultural groups rather than collections of clinical symptoms. The individualism/collectivism dimension (Zhang and Giles, 2017) offers a coherent account of the observed asymmetry: the ADHD community's higher AUTHENTIC scores and $4\times$ higher cross-posting rate align with an individualist, socially permeable orientation, whereas the autism community's higher CLOUT and tighter boundaries reflect a collectivist one in which accommodation functions as a strategic social passport. Under this view, cross-community accommodation is not a byproduct of topic change but a means by which users negotiate social identity and group membership through discursive choices, extending CAT's mechanisms to digitally mediated neurodivergent communities.

These dynamics are further contextualized by recent evidence of macro-level semantic convergence between the two communities: (Kang et al., 2025) report that r/ADHD and r/autism have shifted from distinct topical enclaves toward shared adult-centric concerns such as employment and formal diagnosis. As topics converge, the remaining distinctions become primarily stylistic, making accommodation more salient as a navigational strategy. Notably, the 'steeper' semantic alignment of ADHD discourse toward autism that they report is consistent with our finding that r/ADHD is the more permeable host, corroborating its individualist, outgroup-open orientation relative to the more boundary-conscious autism community.

Practical implications. Community norms appear to shape language even for visitors from other diagnostic groups, which may be relevant for designing inclusive cross-community spaces. The finding that accommodation is primarily situational suggests that cross-community engagement does not fundamentally alter how users communicate in their home communities.

Implications for clinical understanding. The distinct profiles we identify align with recognized communicative differences between ADHD and autism (Lyons et al., 2018), but users flexibly adjust these markers across community boundaries, so a group's "characteristic" language may be more context-dependent than assumed. If the lexical features that distinguish diagnostic groups are the same ones that shift under social pressure (Ait Hou et al., 2026), classifiers trained on in-community data may be unreliable in cross-community or mixed-audience settings, a degradation our motivating experiment demonstrates directly (Section 4.1).

Theoretical implications. High reported accuracies for subreddit-based mental-health classification (Kim et al., 2020) thus face a significant boundary: the $\sim$30-point collapse from in-group to cross-community evaluation (Table 2) shows such accuracy is substantially an artifact of community environment rather than a measurement of the condition. When a user converges toward a community's norms, a static detector may misread this situational alignment as the underlying condition. Reframed through CAT, what is often treated as classification noise is a social strategy, suggesting mental-health informatics should model not only what a user says but the audience they are adapting to.

Limitations

Several limitations should be considered when interpreting these results.

First, our design cannot fully disentangle stylistic accommodation from topical adaptation. When an ADHD user posts in r/autism, they likely discuss different content, which could drive some LIWC shifts. The involvement of topic-independent summary variables (AUTHENTIC, CLOUT) and the within-user design provide partial mitigation, but future work should conduct topic-controlled replications, such as matching posts by topic cluster before computing LIWC differences, and compare cross-posters against non-cross-posters at baseline to rule out selection bias (see Appendix E for a proposed methodology).

Second, diagnosis labels were derived from self-disclosed statements in Reddit posts rather than confirmed clinical diagnoses (Mankarious et al., 2025). While self-disclosure is an accepted method in social media mental health research, it may introduce misclassification if users speculate about or misrepresent their diagnostic status.

Third, our analysis is limited to two neurodivergent communities on a single platform and may not generalize to other conditions or offline contexts. Fourth, the longitudinal analysis assumes the disclosure timestamp approximates diagnosis timing; delays may blur the pre-/post-boundary. Fifth, user-level aggregation reduces statistical power, and LIWC captures only lexical phenomena, future work should incorporate syntactic, embedding-based, and discourse-level features. Sixth, our between-group baseline (E1) compares the ADHD and autism communities to each other but not to a neurotypical control; without a non-clinical reference condition, we cannot determine whether an elevated category reflects one group scoring above typical levels or the other scoring below. Applying the same pipeline to a matched general-population sample is an important next step for localizing the source of each difference.

Ethical Considerations

This study analyzes publicly available Reddit posts from users who self-disclosed mental health diagnoses. We report no individual-level data, usernames, or verbatim content. All analyses are aggregate-level. We use labels from the Mindset dataset (Mankarious et al., 2025) and do not assign diagnoses. We acknowledge the risk that analysis of neurodivergent communication could be misused to stigmatize; our intent is to understand intergroup dynamics and inform inclusive platform design.

References

Iyad Ait Hou, Shrenik Borad, Harsh Sharma, Pooja Srinivasan, Rebecca Hwa, and Aya Zirikly. 2026. Parameter-efficient token embedding editing for clinical class-level unlearning. *arXiv preprint arXiv:2603.19302*.

Yoav Benjamini and Yosef Hochberg. 1995. Controlling the false discovery rate: A practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society: Series B*, 57(1):289–300.

Quinten S Bernhold and Howard Giles. 2022. Communication accommodation theory. *The Handbook of Language and Emotion*, pages 389–407.

Reihane Boghrati, Joe Hoover, Kate M Johnson, Justin Garten, and Morteza Dehghani. 2018. Syntax accommodation in social media conversations. In *Proceedings of the International Conference on Social Computing*.

Jennifer Boorse and 1 others. 2019. Linguistic analysis of narrative production in autism. *Journal of Autism and Developmental Disorders*.

Ryan L Boyd, Ashwini Ashokkumar, Sarah Seraj, and James W Pennebaker. 2022. LIWC-22: The development and psychometric properties of the latest version of Linguistic Inquiry and Word Count. *Journal of Personality and Social Psychology*.

Stevie Chancellor and Munmun De Choudhury. 2020. Methods in predictive techniques for mental health status on social media: A critical review. *NPJ Digital Medicine*, 3(43).

Arman Cohan, Bart Desmet, Andrew Yates, Luca Soldaini, Sean MacAvaney, and Nazli Goharian. 2018. Smhd: a large-scale resource for exploring online language usage for multiple mental health conditions. In *Proceedings of the 27th international conference on computational linguistics*, pages 1485–1497.

Jacob Cohen. 1988. *Statistical Power Analysis for the Behavioral Sciences*, 2nd edition. Lawrence Erlbaum Associates.

Glen Coppersmith, Mark Dredze, Craig Harman, and Kristy Hollingshead. 2015. From adhd to sad: Analyzing the language of mental health on twitter through self-reported diagnoses. In *Proceedings of the 2nd workshop on computational linguistics and clinical psychology: from linguistic signal to clinical reality*, pages 1–10.

Patrick W Corrigan, Kristin A Kosyluk, and Nicolas Rüsch. 2015. Coming out proud to eliminate the

stigma of mental illness. *American Journal of Public Health*, 105(5):185–186.

Cristian Danescu-Niculescu-Mizil, Michael Gamon, and Susan Dumais. 2011. Mark my words! Linguistic style accommodation in social media. In *Proceedings of the 20th International Conference on World Wide Web*, pages 745–754.

Serena De Armond and 1 others. 2020. Self-disclosure of mental health on Reddit. In *Proceedings of the ACM Conference on Computer-Supported Cooperative Work*.

Munmun De Choudhury and Sushovan De. 2014. Mental health discourse on Reddit: Self-disclosure, social support, and anonymity. In *Proceedings of the International AAAI Conference on Web and Social Media*.

Anne-Marie DePape and 1 others. 2025. Navigating identity and disclosure in emerging adults with ADHD. *Journal of Attention Disorders*.

Sindhu Kiranmai Ernala, Michael L Birnbaum, Kristin A Candan, Asra F Rizvi, William A Sterling, John M Kane, and Munmun De Choudhury. 2019. Methodological gaps in predicting mental health states from social media: Triangulating diagnostic signals. In *Proceedings of the 2019 chi conference on human factors in computing systems*, pages 1–16.

Kathleen Ferrara. 1991. Accommodation in therapy. *Language and Communication*.

Seraphina Fong, Alessandro Carollo, Giacomo Vivanti, Daniel S Messinger, Dagmara Dimitriou, and Gianluca Esposito. 2025. Autism spectrum disorders discourse on social media platforms: A topic modeling study of reddit posts. *Autism research*, 18(8):1608–1619.

H. Giles, editor. 2016. *Communication accommodation theory: Negotiating personal and social identities across contexts*. Cambridge University Press, Cambridge, UK.

Howard Giles. 1973. Accent mobility: A model and some data. *Anthropological Linguistics*, 15(2):87–105.

Howard Giles and Jordan Soliz. 2015. Communication accommodation theory. *The International Encyclopedia of Interpersonal Communication*, pages 1–21.

Sharath Chandra Guntuku, David B Yaden, Margaret L Kern, Lyle H Ungar, and Johannes C Eichstaedt. 2019. Studying expressions of loneliness in individuals using Twitter. *BMJ Open*, 9(11).

J. Kang, N. Haslam, and M. Conway. 2025. Converging representations of attention-deficit/hyperactivity disorder and autism on social media: Linguistic and topic analysis of trends in reddit data. *Journal of Medical Internet Research*, 27:e70914.

J. Kim, J. Lee, E. Park, and J. Han. 2020. A deep learning model for detecting mental illness from user content on social media. *Scientific Reports*, 10(1):11846.

Balázs Kovács and Adam M Kleinbaum. 2021. The role of emotional mimicry in intergroup relations. *Proceedings of the National Academy of Sciences*.

Michael Lyons, N Dilara Aksayli, and Gayle Brewer. 2018. Language patterns in autism spectrum disorder. *Journal of Autism and Developmental Disorders*, 48:1–12.

Saad Mankarious and Ayah Zirikly. 2025. Carma: Comprehensive automatically-annotated reddit mental health dataset for arabic. *arXiv preprint arXiv:2511.03102*.

Saad Mankarious, Ayah Zirikly, Daniel Wiechmann, Elma Kerz, Edward Kempa, and Yu Qiao. 2025. MindSET: Advancing mental health benchmarking through large-scale social media data. *arXiv preprint arXiv:2511.20672*.

James W Pennebaker, Ryan L Boyd, Kayla Jordan, and Kate Blackburn. 2015. The development and psychometric properties of LIWC2015. *University of Texas at Austin*.

Victoria Rideout and Michael B Robb. 2021. Social media, social life: Teens reveal their experiences. *Common Sense Media*.

Eva Sharma and Munmun De Choudhury. 2018. Mental health support and its relationship to linguistic accommodation in online communities. In *Proceedings of the CHI Conference on Human Factors in Computing Systems*.

Nadine Tamburrini, Marco Cinnirella, Vincent AA Jansen, and John Bryden. 2015. Twitter users change word usage according to conversation-loss: A large-scale study. *PLOS ONE*, 10(9):e0137149.

Lucy Togher and 1 others. 2023. Autism social identification predicts disclosure behaviors. *Autism Research*.

Theodore A Walls and Joseph L Schafer. 2006. Addressing pseudoreplication in longitudinal studies. *Models for Intensive Longitudinal Data*.

Y. B. Zhang and H. Giles. 2017. Communication accommodation theory. In *The International Encyclopedia of Intercultural Communication*, pages 1–14. John Wiley & Sons, Ltd.



Figure 1: Bidirectional linguistic accommodation between neurodivergent Reddit communities. Each dot represents a user crossing community boundaries. r/ADHD (blue, $n = 7{,}758$): higher TIME, AUTHENTIC, ACHIEVE, WORK. r/autism (red, $n = 5{,}706$): higher SOCIAL, SOCREFS, CLOUT, THEY. Color shifts (blue → purple → red) represent accommodation toward host norms. See Table 11 for category definitions and Appendix H for detailed results.

A Quantitative Summary of All Experiments

Figure 2 provides a three-panel quantitative summary. Panel (a) shows baseline stylistic differences (E1), panel (b) visualizes the mirror-image accommodation shifts (E2), and panel (c) compares E2 and E3 effect sizes, showing that situational accommodation is 3–23× stronger than post-diagnosis identity changes.

B Full Baseline Differences (E1)

Table 5 reports the 15 LIWC categories with the largest absolute effect sizes from E1. These organize into three interpretive clusters. *Temporal and goal-oriented language*: ADHD users score higher on TIME (d=0.76), ACHIEVE (d=0.60), and WORK (d=0.58), consistent with ADHD's heightened temporal awareness and goal-directed urgency (Lyons et al., 2018) and with prior reports of achievement- and temporally-oriented language in ADHD self-disclosure (Guntuku et al., 2019). *Social orientation*: Autism users score higher on SOCREFS (d=−0.56), SOCIAL (d=−0.52), THEY (d=−0.45), and CLOUT (d=−0.41), reflecting the community's focus on navigating social relationships and matching the elevated social references previously documented in autism discourse (Fong et al., 2025; Boorse et al., 2019). *Self-presentation*: ADHD users score higher on AUTHENTIC (d=0.59), indicating spontaneous self-expression consistent with the heightened markers of raw authenticity reported for ADHD (Mankarious et al., 2025; Guntuku et al., 2019), while autism users' higher CLOUT reflects more authoritative language. Both are LIWC summary variables designed to be topic-independent.

C Mirror-Image Accommodation

Table 6 aligns E1 baselines with E2 shift directions. For every category, features that are high for a group at baseline decrease when that group visits the other community, and vice versa, the defining signature of convergent accommodation. This includes THEY, the third-ranked autism-skewed category at baseline (Table 5): autism-diagnosed users reduce their use of THEY when posting in r/ADHD and ADHD-diagnosed users increase it

Table 5: Baseline differences (E1, top 15 by $|d|$).

Category	ADHD	Autism	d
time	5.621	3.929	0.76
achieve	1.585	0.950	0.60
Authentic	78.41	69.37	0.59
work	2.091	1.255	0.58
socrefs	5.047	6.682	−0.56
substances	0.462	0.050	0.55
acquire	1.293	0.833	0.53
Social	8.987	11.33	−0.52
they	0.588	0.937	−0.45
Lifestyle	3.185	2.350	0.45
health	3.120	2.179	0.43
Clout	19.96	26.62	−0.41
quantity	4.306	3.544	0.41
focuspast	4.423	3.563	0.40
prep	12.13	11.07	0.39

All FDR-corrected ($q < 0.05$). $+d$: ADHD higher; $-d$: autism higher.

when posting in r/autism, the same convergent pattern observed for the other categories.

Table 6: E1 baseline direction vs. E2 shift direction.

Category	Higher at E1	ADHD→Aut.	Aut.→ADHD
Authentic	ADHD	↓	↑
time	ADHD	↓	↑
Social	Autism	↑	↓
Clout	Autism	↑	↓
socrefs	Autism	↑	↓
they	Autism	↑	↓
health	ADHD	↓	↑
i	ADHD	↓	↑

Every shift moves toward the host community's baseline.

D Longitudinal Analysis (E3)

Table 7 reports all significant within-user changes after diagnosis disclosure. Three observations stand out: (1) only 2 of 115 categories change for ADHD users and 6 for autism users, disclosure does not broadly reshape linguistic style; (2) all effects are small ($|d| \leq 0.22$), compared to medium effects in E2 ($|d| = 0.31$–0.70); (3) for autism users in r/ADHD, the post-diagnosis direction for AUTHENTIC (d=−0.12) and CLOUT (d=+0.11) is *opposite* to the E2 accommodation direction (d=+0.33 and d=−0.31), suggesting that identity consolidation and situational accommodation may pull in different directions.

Table 8 places these post-diagnosis (E3) effects alongside the situational accommodation (E2) effects for the same categories, showing that accommodation is consistently 3–23× larger and, for AUTHENTIC and CLOUT in the Aut.→ADHD condition, directionally opposite.

D.1 Timeline of User Activity

To contextualize the pre-/post-diagnosis split, Table 9 reports average temporal distances between users' first post, diagnosis disclosure, and final post. ADHD users in r/autism show the shortest pre-diagnosis window ($M = 52$ days), while autism users in r/ADHD show the longest ($M = 304$ days), suggesting that autism-diagnosed users participate in ADHD spaces well before disclosing their diagnosis.

E Proposed Robustness Analyses

The E2 accommodation results face two key threats to validity: (1) cross-posters may differ systematically from non-cross-posters at baseline (*selection bias*), and (2) LIWC shifts may reflect topical rather than stylistic adaptation (*topic confound*). We describe the methodology for addressing each and discuss what the current design already controls for.

Cross-posting rates and asymmetry. Of 7,758 ADHD-diagnosed users, 788 (10.2%) also posted in r/autism. Of 5,706 autism-diagnosed users, 2,305 (40.4%) also posted in r/ADHD. This ∼4× asymmetry likely reflects ADHD–autism comorbidity rates (estimated 30–80% clinically), r/ADHD's larger subscriber base (>1.8M vs. >400K), and possible differences in community openness.

Selection bias test. We compared in-community LIWC profiles (home subreddit only) of cross-posters vs. non-cross-posters within each group: ADHD cross-posters (n=788) vs. non-cross-posters (n=6,970), and autism cross-posters (n=2,305) vs. non-cross-posters (n=3,401). If cross-posters already exhibit profiles shifted toward the other community's norms *before visiting it*, the E2 effects may partly reflect who chooses to cross-post rather than how they adapt. Conversely, if cross-posters and non-cross-posters are linguistically indistinguishable in their home community, this strengthens the audience-adaptation interpretation. We note that even if cross-posters differ at baseline, the within-user E2 design (comparing each user's own home vs. cross-community posts) partially controls for this, since any baseline difference is constant within a user.

Table 7: Longitudinal changes after diagnosis disclosure (exploratory E3).

Dataset	Category	Pre	Post	Shift	d	95% CI
ADHD in Aut.	health	2.45	1.65	−0.80	−0.22	[−.36, −.08]
	prep	11.12	10.25	−0.87	−0.20	[−.34, −.06]
Aut. in ADHD	Authentic	77.22	74.21	−3.00	−0.12	[−.20, −.04]
	Clout	19.30	22.12	+2.82	+0.11	[+.03, +.19]
	i	8.81	8.30	−0.51	−0.11	[−.19, −.03]
	they	0.59	0.69	+0.11	+0.10	[+.02, +.18]
	health	3.09	3.45	+0.36	+0.09	[+.01, +.17]
	socrefs	4.85	5.26	+0.41	+0.08	[+.00, +.16]

FDR-corrected ($q < 0.05$). All effects small to negligible ($|d| \leq 0.22$).

Table 8: E2 (accommodation) vs. E3 (post-diagnosis) effect sizes. Category definitions in Table 11.

Category	Dataset	E2 d	E3 d
Authentic	ADHD→Aut.	−0.61	−0.09
	Aut.→ADHD	+0.33	−0.12
Clout	ADHD→Aut.	+0.43	+0.11
	Aut.→ADHD	−0.31	+0.11
Social	ADHD→Aut.	+0.44	−0.02
	Aut.→ADHD	−0.47	+0.02
time	ADHD→Aut.	−0.70	−0.15
	Aut.→ADHD	+0.43	−0.00

Note directional opposition for Authentic and Clout in the Aut.→ADHD condition.

Table 9: Average timeline distances (days).

Dataset	First→Dx	Dx→End	First→End
ADHD in ADHD	124 (302)	568 (622)	692 (691)
ADHD in Autism	52 (167)	411 (467)	464 (513)
Autism in ADHD	304 (501)	265 (409)	569 (637)
Autism in Autism	236 (386)	378 (458)	614 (576)

Dx = diagnosis disclosure. Parentheses = SD.

Why these analyses matter. If both tests come back clean, cross-posters do not differ at baseline, and effects survive topic matching, the accommodation interpretation is substantially strengthened. If either reveals a confound, it narrows the scope of the claim but does not eliminate it: the mirror-image directionality across eight categories remains difficult to explain by selection or topic alone.

F Statistical Methodology and Dataset Details

LIWC-22 categories. LIWC-22 (Boyd et al., 2022) produces 115 categories in four tiers: 4 *summary variables* (Analytic, Clout, Authentic, Tone, composite scores relatively robust to topic variation), ∼25 *linguistic dimensions* (function words, pronouns, verb tense), ∼50 *psychological processes* (affect, cognition, social processes), and ∼36 *personal concerns* (work, health, leisure). We tested all 115 per experiment without *a priori* selection, relying on FDR correction to control for multiplicity. The summary variables are particularly important for our accommodation argument because they capture broad stylistic dimensions that are less susceptible to topic confounds than content-specific categories like HEALTH or WORK.

User-level aggregation. For each user u with posts $\{p_1, \ldots, p_n\}$ in a given condition and LIWC category c, we compute a single per-user mean:

$$\bar{x}_{u,c} = \frac{1}{n} \sum_{i=1}^{n} \text{LIWC}(p_i, c)$$

Users with fewer than 3 posts in a condition were excluded to ensure stable estimates. This aggregation is critical: without it, prolific users would dominate the analysis, and pseudoreplication would inflate statistical significance.

Statistical testing. Welch's t-test (unequal variances assumed) with effect size $d = (\bar{x}_1 - \bar{x}_2)/s_p$, where s_p is the pooled SD. For E3 paired comparisons, we use the SD of within-user difference scores. All 95% CIs for d are computed via the noncentral t-distribution with noncentrality parameter $\lambda = d \cdot \sqrt{n_1 n_2/(n_1 + n_2)}$ (independent groups) or $\lambda = d \cdot \sqrt{n}$ (paired). FDR correction follows Benjamini and Hochberg (1995) at $q = 0.05$ across $m = 115$ tests per experiment.

Diagnosis timestamps. For E3, we used the timestamp of each user's first public diagnosis disclosure from the Mindset dataset (Mankarious et al., 2025). Users were included only if they had ≥ 3

Dataset	Users	Posts	Avg Words	Std	Subreddit	Comments	Submissions
ADHD in ADHD	7,758	199,020	85.94	112.21	r/ADHD	171,028	27,992
ADHD in Autism	788	12,621	70.96	113.82	r/autism	11,245	1,376
Autism in Autism	5,706	276,159	64.93	98.54	r/autism	248,597	27,562
Autism in ADHD	2,305	38,470	84.01	108.22	r/ADHD	31,947	6,523

Table 10: Descriptive statistics for cross-posting datasets. Users are non-overlapping between ADHD and autism diagnostic groups.

Table 11: Glossary of LIWC categories featured in this paper's figures and tables. Scores are word-frequency rates, not measures of intent. † marks LIWC *summary variables* (composite scores designed to be relatively topic-independent). See Appendix H for extended interpretation.

Category	One-line definition
AUTHENTIC†	Spontaneous, self-revealing style (more first-person singular, fewer hedges). A stylistic marker, *not* a measure of honesty.
CLOUT†	Confident, authoritative stance (more *we*/*you*, fewer *I*). Reflects relative social standing in the text, not actual influence.
SOCIAL	Rate of words referring to people and social processes. Captures *writing about* social matters, not real-world social engagement.
SOCREFS	Social referents: references to other people (e.g., *they*, *you*, names). Mentions of others in text, not actual interaction.
TIME	Words about time and temporal orientation (e.g., *when*, *soon*, *hour*).
ACHIEVE	Achievement and goal-striving words (e.g., *win*, *success*, *better*).
WORK	Work and occupation words (e.g., *job*, *boss*, *deadline*).
I	First-person singular pronouns (*I*, *me*, *my*); self-focus.
THEY	Third-person plural pronouns (*they*, *them*); reference to other groups.
HEALTH	Health, illness, and symptom words (e.g., *clinic*, *meds*, *pain*).
SUBSTANCES	Substance-related words (e.g., *alcohol*, *caffeine*, medication).
ACQUIRE	Acquiring or obtaining words (e.g., *get*, *find*, *take*).
LIFESTYLE	Personal-life domains, including work, leisure, home, and money.

posts in both pre- and post-disclosure periods. Median pre-disclosure posting span $\approx$ 14 months; post-disclosure $\approx$ 18 months.

Data pipeline. Starting from Mindset's user identifiers and diagnostic labels: (1) re-fetch each user's complete Reddit history via Pushshift (Mindset's original posts are filtered to exclude mental health content), (2) retain only posts in r/ADHD and r/autism, (3) verify zero user overlap between diagnostic groups, (4) remove deleted posts and posts with < 5 tokens, (5) run LIWC-22 and aggregate to user-level means. Final corpus spans 2015–2024 (majority 2019–2023).

Descriptive statistics. Table 10 reports per-subset user, post, and word counts for the four cross-posting datasets.

G LIWC Category Glossary

Table 11 defines every LIWC category featured in this paper's figures and tables. The four categories whose technical meaning most diverges from everyday usage are reproduced in the main text (Table 1).

H LIWC Summary Variable Interpretation

Three LIWC summary variables are central to our analysis. AUTHENTIC (d=0.59, ADHD higher) captures spontaneous, self-disclosing language. CLOUT (d=-0.41, autism higher) captures confident, authoritative language. SOCIAL (d=-0.52, autism higher) captures references to people and interpersonal interactions. Unlike content-specific categories, these are composite scores designed to be relatively topic-independent, making their strong accommodation effects in E2 harder to explain as purely topical artifacts.

It is worth noting that LIWC scores reflect word-level frequency patterns, not communicative intent. A high SOCIAL score in the autism community does not mean autistic users are more socially engaged, it means they *talk about* social topics more frequently, which is consistent with the community's focus on navigating social difficulties. Similarly, high AUTHENTIC in the ADHD community reflects a linguistic pattern (more first-person pronouns, less formal hedging) rather than a judgment about honesty. These distinctions matter for inter-

preting the accommodation results: when ADHD users decrease in AUTHENTIC while posting in r/autism, this reflects a shift toward more guarded, formal language, not a decrease in sincerity.

A broader limitation of LIWC is that it operates at the word level and cannot capture syntactic structure, pragmatic function, or discourse-level phenomena. For example, LIWC cannot distinguish between a user who asks many questions (a possible sign of deference to the host community) and one who uses question marks in rhetorical statements. Future work could complement LIWC with dependency parsing to measure syntactic complexity, sentence embeddings to compute stylistic similarity in continuous space, or discourse-level features such as hedge frequency and turn-taking patterns. These approaches would test whether the accommodation patterns we observe at the lexical level extend to deeper structural dimensions of language use.



Figure 2: (a) Baseline differences (E1). (b) Cross-community accommodation (E2): mirror-imaged shifts across every category. (c) E2 vs. E3: accommodation (solid) is 3–23× larger than post-diagnosis changes (light).

Mostly Grounded, Occasionally Risky: Expert Evaluation of LLM-Generated Supervisory Feedback in a Psychotherapy Training Simulator

Adrian Montesano
Open University of Catalonia
amontesano@uoc.edu

Justin K. Bloomberg
Open University of Catalonia
jbloomberg@uoc.edu

Marc Pérez-Buriel
Universitat de Girona
marc.perez@udg.edu

Abstract

Automated feedback is increasingly cited as a key advantage of AI-based psychotherapy training, yet the clinical groundedness of LLM-generated supervisory feedback remains unevaluated. We present an expert evaluation of supervisory feedback generated by PRACTICE, an LLM-powered open-ended psychotherapy training simulator, across 21 feedback instances from four novice trainees. Two clinical psychology experts independently coded 167 feedback propositions as Justified, Unjustified, or Unsure. Inter-rater reliability was near-perfect (raw agreement = 98.2%; κ = 0.902). Of the 167 propositions, 149 (89.2%) were rated Justified; however, 52.4% of feedback instances contained at least one non-justified proposition, and qualitative analysis identified three recurring failure types: unsupported clinical inference, referential grounding error, and pragmatic failure. In clinical training contexts, even low error rates carry ethical weight: unjustified feedback risks reinforcing inappropriate clinical behaviors in trainees that can be transferred to real practice. These findings provide an initial empirical basis for the responsible deployment of LLM-generated feedback in clinical training and call for traceable, expert-auditable feedback architectures.

1 Introduction

Training novice psychotherapists requires repeated, deliberate practice in conditions that are safe, structured, and clinically realistic. Traditionally, this has relied on role-plays with peers or supervisors, methods that are resource-intensive, difficult to standardize, and constrained by access to supervisors' time. The emergence of large language model (LLM)-based conversational agents has opened a new avenue for scalable, on-demand simulation of clinical interactions.

A growing body of work demonstrates the feasibility and perceived value of this approach. LLM-driven virtual clients have been shown to be perceived as realistic by trainees, to offer a psychologically safe environment for skill rehearsal, and to support gains in counseling self-efficacy (Beeson et al., 2025; Jeong et al., 2025; Tian et al., 2025). Various platforms have demonstrated feasibility across different training populations, with trainees reporting high usability, learning gains, and value relative to traditional role-play (Cabrera Lozoya et al., 2025; Stige et al., under review). Automated feedback is consistently cited as a key advantage of AI-based training over traditional role-play, and trainees who engage with feedback features tend to report greater satisfaction and perceived clinical impact (Kopelovich et al., 2025b).

Progress has also been made on the technical validation of automated feedback. Kopelovich et al. (2025a) developed and validated a machine learning system capable of scoring discrete CBT competencies in response to standardized client vignettes, achieving strong human-ML agreement (mean ICC = .77; r_s = .74). Zilcha-Mano (2025) argues that this work marks a new era for clinical training and envisions its extension to increasingly complex training contexts. Importantly, however, this line of work targets model-specific skills, behaviorally discrete CBT techniques such as psychoeducation, behavioral activation, and reality testing, evaluated through structured, constrained performance tasks.

What remains unaddressed is whether LLM-generated feedback can be clinically grounded in more open-ended conditions, where trainees engage in free dialogue, clinical skills are transtheoretical rather than model-specific, and feedback must be anchored in the emergent dynamics of a real interaction rather than a constrained performance task. PRACTICE (Psychotherapy Realistic AI Conversation for Training In Clinical Expertise) was designed to operate in precisely this space. Rather than model-specific techniques, it targets transtheoretical interpersonal skills grounded in

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 298–305
July 4, 2026 ©2026 Association for Computational Linguistics

common factors, the Helping Skills and the Facilitative Interpersonal Skills (FIS) framework, the relational capacities that consistently differentiate therapist effectiveness across theoretical orientations (Anderson et al., 2016; Flückiger et al., 2018; Del Re et al., 2021; Wampold and Owen, 2021). These skills unfold through free, open-ended dialogue with a dynamically responsive virtual patient, and feedback is generated on demand via retrieval-augmented generation (RAG) grounded in clinical training manuals.

Existing work has examined whether trainees perceive feedback as useful (Stige et al., under review) or face-valid (Kopelovich et al., 2025b), but perceived usefulness is not the same as clinical justification. This distinction carries ethical weight: in therapist training, feedback that is not grounded in the actual interaction does not merely fail to help, it actively shapes the clinical habits of practitioners who will eventually work with people in genuine distress.

In this paper, we present the first expert evaluations of clinical groundedness in LLM-generated supervisory feedback produced under open-ended, conversational conditions. We describe PRACTICE and its RAG-based feedback architecture, report expert clinical judgments on 167 automatically generated feedback propositions, and characterize recurring patterns of justification and failure. These findings provide an initial empirical basis for evaluating LLM-generated feedback in clinical training and inform its responsible use.

2 System Description

PRACTICE is a web-based psychotherapy training platform in which trainees conduct open-ended simulated clinical sessions with an LLM-powered virtual patient. The platform uses the OpenAI API governed by a behavioral control architecture designed to counteract the natural tendency of LLMs toward premature helpfulness. Four relational parameters, openness, emotional intensity, collaboration, and readiness for change, are updated turn-by-turn based on the trainee's interventions, producing a dynamically responsive patient whose relational stance evolves as a function of the quality of the trainee's clinical engagement. A gating mechanism prevents the virtual patient from moving toward concrete problem-solving until the trainee has established sufficient relational ground, operationalized as a threshold value of readiness for change. Three clinical cases are available, covering frustration and confrontation, acute anxiety and emotional dysregulation, and ambivalence in the context of substance use.

Feedback is generated on demand: trainees may request it at any point by entering a dedicated command, which triggers a retrieval-augmented generation (RAG) pipeline, a technique in which the model's output is conditioned on passages retrieved from a predefined document collection rather than relying solely on pretrained knowledge, grounded in the Facilitative Interpersonal Skills (FIS) coding manual (Anderson et al., 2009) and a therapeutic skills training manual developed for the platform. Each feedback response comprises three structured components: validation of observed strengths, identification of one area for improvement with behavioral examples drawn from the session transcript, and an encouraging closing statement (See Appendix A, for an example). At the time of data collection, feedback was generated using `gpt-5` via the OpenAI API. The RAG pipeline used LangChain's default retrieval configuration with top-k = 4, chunk size of 1,000 characters, and a chunk overlap of 200 characters.

3 Methods

Participants were four psychology trainees (3 women, 1 man; age range 31–42, M = 37.5 years) enrolled in a postgraduate clinical training program. All reported fewer than two years of specific psychotherapy training. Trainees completed between 3 and 6 simulated clinical sessions each (M = 5.25), selecting freely among the three available clinical cases, with one participant requesting feedback twice within a single session, yielding 21 feedback instances across 20 unique sessions, conducted in Spanish. At the end of the training, trainees rated the overall quality of the feedback received using a brief measure adapted from established frameworks in clinical education (Alsahafi et al., 2023; Johnson et al., 2021).

Each feedback instance was segmented into atomic propositions, yielding 167 codeable units in total. Propositions were defined as minimal units of meaning corresponding to a single clinically interpretable claim (e.g., a skill, behavioral example, or evaluative statement). Segmentation was conducted jointly by both raters prior to independent coding, ensuring a shared unit of analysis. Two clinical psychology experts independently coded

each proposition as Justified (grounded in behavior observable in the session transcript), Unjustified (contradicted by or unsupported by the transcript), or Unsure (insufficient evidence to adjudicate), using a coding system grounded in the Facilitative Interpersonal Skills framework (Anderson et al., 2009). See Appendix A, for an example of an annotated feedback instance. Both raters were male psychologists and psychotherapists, with 9 and 18 years of clinical experience respectively. Raters worked from a standardized protocol including the full session transcript in the original Spanish, the original feedback text, and the propositions, and were blind to each other's judgments. The feedback instance presented in Appendix A has been translated into English by the authors for accessibility; proposition boundaries and expert verdicts are identical to those applied to the original Spanish text. Inter-rater reliability was assessed using Cohen's κ (Landis and Koch, 1977). Propositions rated as non-Justified under full rater agreement were subjected to a secondary qualitative analysis to identify systematic patterns of feedback failure.

4 Results

Of the 167 propositions, 149 (89.2%) were rated Justified by both experts, 9 (5.4%) as Unjustified, and 6 (3.6%) as Unsure, yielding 15 (9.0%) non-justified propositions in total (See Figure 1). Inter-rater agreement was high (98.2%; $\kappa = 0.902$, 95% CI [0.79, 1.00]), with disagreements limited to borderline cases between Justified and Unsure. Each participant received at least one non-justified proposition from PRACTICE, with individual rates ranging from 3.2% (P007, 1/31) to 12.7% (P046, 7/55), with P011 at 4/37 (10.8%) and P012 at 3/44 (6.8%). Each feedback instance comprised, on average, 8.0 propositions (*SD* = 1.9) and 277.5 words (*SD* = 67.0). On average, trainees received 0.71 non-justified propositions per feedback instance (*SD* = 0.90). Across a typical five-session training trajectory, this translates to approximately 3–4 non-justified propositions out of ∼40 received.

At the feedback-instance level, 11 of 21 feedback instances (52.4%) contained at least one non-justified proposition (See Figure 1). Among these, the mean number of non-justified propositions was 1.36 (range: 1–3) and in 9 of the 11 cases, only a single proposition was non-justified. The remaining 10 instances (47.6%) were fully grounded. Non-justified propositions were disproportionately concentrated in the Strengths component of feedback (9/58, 15.5%), compared to Area for Improvement (3/75, 4.0%) and Actionable Suggestions (3/34, 8.8%). Given the small sample size and the nested structure of the data, no inferential test was applied to this comparison.

Qualitative analysis of the 15 non-justified propositions identified three failure types (See Table 1). *Unsupported clinical inference* (n = 8) occurred when the described behavior existed in the transcript but was rendered through unverifiable inferences about patient-internal states, mislabeling of the clinical skill involved, or an implied behavioral absence without observable referent. *Referential grounding error* (n = 3) occurred when the system drew on real session material rendered inaccurately through inexact or partially incorrect quotation, logically disconnected elements within a single proposition, virtual patient behaviors that were misattributed to the trainee, or behaviors that did not occur in the session as described. *Pragmatic failure* (n = 4) occurred when a proposition was found to be semantically ambiguous or unintelligible, impeding reasonable understanding. Notwithstanding these findings, trainees rated the overall quality of the feedback highly (M = 9.88/10, range 9.50–10.00).

Table 1: Illustrative examples of failures

Failure type	Example proposition
Unsupported clinical inference (n = 8)	"You validated her experience ('We have all the time in the world')[. . .]" *Coder note: That quote does not describe validation.*
Referential grounding error (n = 3)	"[. . .] you were able to name more precisely what Claudia expressed (*fear of being judged, 'a thousand open eyelashes'*) to increase rapport." *Coder note: The quotes given as examples are from Claudia, not the therapist.*
Pragmatic failure (n = 4)	"For anxiety: co-project a 2-step plan anchored to cues ('if I notice acceleration: I grab a bottle, breathe 1 cycle, bridge phrase: let me organize the thought')." *Coder note: The confusing language makes the utility of this suggestion difficult to assess.*

5 Discussion

The central finding of this study is that PRACTICE generates clinically justified feedback at a high rate: 89.2% of propositions were rated as grounded in observable trainee behavior by both expert raters.

Figure 1: Proportion of justified and non-justified units at two levels of analysis.



This result is encouraging for the responsible deployment of LLM-based feedback in open-ended clinical training, and extends the evidence base beyond trainee-reported face validity (Kopelovich et al., 2025b; Stige et al., under review) to independent expert judgment.

The picture becomes more nuanced at the feedback-instance level. Across 21 feedback instances, 52.4% contained at least one unjustified or uncertain proposition. This does not mean that half of all feedback is clinically problematic, as the majority of propositions within each instance remained grounded. Rather, the proposition-level and instance-level analyses capture different aspects of system reliability: proposition-level rates estimate the overall density of grounded versus non-grounded claims, whereas instance-level rates estimate the likelihood that trainees encounter at least one problematic proposition within an otherwise largely grounded feedback response. In a context of deliberate skill acquisition, even a small number of such inaccuracies may be consequential, as trainees may treat automated feedback as authoritative and lack mechanisms to identify or correct individual errors within otherwise plausible feedback. For example, a trainee may receive positive reinforcement for having "validated" a patient's experience when the cited intervention does not actually constitute validation. If accepted uncritically, such feedback could, over repeated interactions, reinforce inaccurate understandings of core therapeutic skills and contribute to clinically suboptimal interaction patterns.

This interpretive risk is compounded by a well-documented blind spot in clinical self-assessment. Therapists and trainees systematically overestimate the quality of their own performance and are unable to detect failures in their clinical work without external corrective feedback (Hannan et al., 2005; Hatfield et al., 2010; Walfish et al., 2012). The near-ceiling trainee ratings of feedback quality observed in the present study (M = 9.88/10) are consistent with this pattern, suggesting that trainees may not reliably discriminate between justified and non-justified propositions on the basis of perceived quality alone, though this inference was not directly tested in the present design. If clinicians cannot reliably detect failures in their own therapeutic behavior, it is unlikely that novice trainees can detect failures in automated feedback about that behavior. Tracey et al. (2014) further argue that the absence of expertise development in psychotherapy is directly attributable to therapists' lack of access to quality outcome information, a structural problem that unsupervised LLM-based feedback may reproduce rather than solve. Deliberate practice requires accurate, granular, and correctable feedback as a precondition for skill refinement (Chow et al., 2015); feedback that is partially grounded in unsupported clinical inferences or pragmatically opaque behavioral referents undermines this process.

These risks must be contextualized against what is known about human clinical supervision. To our knowledge, no study has systematically measured the rate of ungrounded claims in human supervisory feedback provided under equivalent conditions, that is, from transcript review without direct session observation. More fundamentally, the goal of clinical supervision is not propositional accuracy but the simultaneous pursuit of formative, normative, and restorative functions: facilitating skill development, ensuring ethical practice, and supporting the supervisee's professional growth (Bernard and Goodyear, 2019; Milne, 2007). Evaluated against this standard, the feedback generated by PRACTICE, despite its documented imperfections, appears capable of serving a legitimate scaffolding function, opening interpretive possibilities and constructing actionable paths for clinical improvement.

It is worth noting that the operationalization of clinical groundedness adopted here does not reduce to purely descriptive correspondence with the transcript. The coding scheme was applied by clinical experts with 9 and 18 years of psychotherapy

experience, whose judgments necessarily incorporated clinically informed interpretation constrained by observable interactional evidence. Accordingly, propositions rated as Justified could include clinically warranted inferences, not merely literal behavioral descriptions. In this sense, the criterion captures something closer to expert-validated inferential groundedness than to strict transcript mirroring. At the same time, transcript-based evaluation remains inherently limited in its access to psychotherapy processes that may unfold beyond explicit verbal content, particularly those involving relational depth, emotional engagement, or transferential dynamics. Thus, even feedback judged as fully grounded may capture only part of the clinically relevant processes involved in therapeutic development. Future work should therefore examine not only whether feedback is grounded, but also whether it is timely, actionable, and clinically generative. Notwithstanding these conceptual caveats, what the 9% non-justification rate does demand is sustained effort to minimize errors and, critically, to prevent the reinforcement of clinically inappropriate behavior: an outcome that did not occur in the present sample, but that falls within the range of risk the current architecture carries. The disproportionate concentration of non-justified propositions in the Strengths component (15.5% vs. 4.0% in Area for Improvement) is plausibly linked to a structurally predictable pressure: a generative model with a template-driven obligation to identify strengths may over-calibrate to linguistic plausibility when transcript evidence is weak, absent or undetected.

The three failure types identified here can be situated within the NLP literature on faithfulness failures in retrieval-augmented generation (RAG). Following Huang et al. (2025), faithfulness-related hallucinations occur when generated content diverges from the source material provided to the model, in this case, the session transcript. Two of the failure categories clearly reflect this pattern: *Unsupported clinical inference* arises when observable transcript content is rendered through unverifiable interpretive inferences or mislabeling of clinical processes, while *Referential grounding error* corresponds to attribution and grounding failures (Ji et al., 2023), in which behaviors are misattributed to the trainee or cited inaccurately. By contrast, *Pragmatic failure* reflects a pragmatic generation failure in which the proposition becomes difficult to interpret or operationalize despite remaining loosely related to the session content. Importantly, these errors differ from broader factuality hallucinations, as the system generally has access to the relevant source material through the RAG pipeline but fails to remain fully faithful, interpretable, or clinically grounded in its use of that material. This framing positions the present dataset as a potential resource for developing domain-specific evaluation methods for grounded clinical text generation.

These findings point to a broader architectural challenge for the field. The failure modes documented here are not unique to PRACTICE, they are inherent to any system in which LLM-generated clinical claims remain opaque and unverifiable at the point of delivery. Addressing this requires moving beyond generation toward grounded verification: trained classifiers capable of assessing whether individual feedback propositions are anchored in observable session content, operating over shared, expert-annotated corpora of psychotherapy transcripts. This agenda aligns with calls within the CLPsych community for fine-tuned, domain-specific models that outperform general-purpose LLMs on clinically sensitive annotation tasks (Tseriotou et al., 2025), and with proposals for the collaborative curation of labeled psychotherapy datasets as a prerequisite for responsible clinical AI (Imel et al., 2024). The dataset introduced in this study, 167 expert-annotated feedback propositions linked to full session transcripts, represents a relevant step toward such a resource, and notably does so in Spanish, a language severely underrepresented in clinical NLP corpora despite serving hundreds of millions of speakers worldwide.

Limitations

This study has several limitations. First, the sample is small, four participants across 21 feedback instances, which severely constrains statistical power and generalization across training contexts, theoretical orientations, and trainee experience levels. A fully-powered validation study with a larger and more diverse sample is needed before conclusions can be extended beyond this pilot. Furthermore, agreement estimates should be interpreted in light of the constrained coding scheme (three categories), which reduced variability in how units were defined.

Second, this evaluation addresses clinical groundedness and perceived feedback quality, but does not assess pedagogical effectiveness: whether

clinically justified feedback translates into actual skill development remains an open question. A feedback proposition may be grounded in observable behavior yet poorly timed, overly generic, or difficult to operationalize in practice.

Third, no human supervisor baseline was included. Beyond the question of error rates, a comparison between human and LLM-generated feedback on the same session transcripts would constitute a richer research question: to what extent do human supervisors and automated systems converge or diverge in what they identify as strengths and areas for improvement, and which type of feedback trainees find more actionable? Such a design would require expert supervisors to generate written feedback from the same transcripts under equivalent conditions, with resulting propositions subjected to the same coding protocol. This represents a meaningful direction for future work on the clinical utility of automated feedback.

Fourth, PRACTICE operates exclusively in text, whereas psychotherapy is fundamentally a verbal and paraverbal practice. Prosody, silence, tone, and non-verbal attunement, core dimensions of clinical skill, are absent from both the simulation and the feedback. This limits both the ecological validity of the training context and the range of skills the system can meaningfully evaluate.

Fifth, the feedback evaluation was conducted at the proposition level but did not assess which specific clinical skills the system is better or worse at detecting and evaluating. Systematic variation in feedback accuracy across skill domains remains unexamined and constitutes an important direction for future work.

Sixth, the RAG pipeline underlying PRACTICE's feedback mechanism lacks full interpretability: it is not possible to determine precisely which portions of the session transcript drove each generated proposition. This opacity is a general limitation of LLM-based generation in clinical contexts (Schmidt et al., 2025; Yosef et al., 2024), and constrains our ability to explain or correct specific feedback failures.

Ethical Considerations

This study involves secondary analysis of training session data produced by psychology trainees in the context of an institutional educational program. All data were collected under informed consent protocols approved by the relevant institutional review board. Trainees participated voluntarily, with full awareness that their session transcripts would be used for research purposes. Participant identifiers have been anonymized throughout. Raters were clinical psychology experts who worked from a standardized evaluation protocol and were blind to each other's judgments; no participant data beyond session transcripts and pre-atomized feedback propositions were made available to them.

The system evaluated here trains clinical skills through interaction with LLM-powered virtual patients. While no real patients are involved, the competencies developed and the clinical habits reinforced by feedback will ultimately be applied to people in genuine distress. Feedback perceived as authoritative, even when not clinically justified, may shape clinical practice in ways that are difficult to detect or correct. The low rate of unjustified propositions observed here (9%) is encouraging, but should not be taken as grounds for unsupervised deployment.

PRACTICE incorporates a disclaimer notifying trainees that feedback is generated entirely by an AI system for training purposes, should not be interpreted as clinical supervision or faculty evaluation, and may contain inaccuracies inherent to automated models. Users are encouraged to contrast feedback with supervised training and authorized professional sources. This represents a meaningful mitigation measure, though it does not substitute for the architectural safeguards recommended in the Discussion. We recommend that AI-generated feedback in clinical training contexts be used as a complement to, not a substitute for, expert clinical supervision, and that ongoing expert auditing be integrated into deployment pipelines.

References

A. Alsahafi, D. L. X. Ling, M. Newell, and T. Kropmans. 2023. A systematic review of effective quality feedback measurement tools used in clinical skills assessment. *MedEdPublish*, 12(11).

T. Anderson, M. E. J. Crowley, L. Himawan, J. K. Holmberg, and B. D. Uhlin. 2016. Therapist facilitative interpersonal skills and training status: A randomized clinical trial on alliance and outcome. *Psychotherapy Research*, 26(5):511–529.

T. Anderson, B. M. Ogles, C. L. Patterson, M. J. Lambert, and D. A. Vermeersch. 2009. *Facilitative interpersonal skills coding manual*. Ohio University.

E. T. Beeson, E. Counselman-Carpenter, T. A. Field,

and M. Ghoston. 2025. Artificial intelligence role-play for counselor skill development: A qualitative investigation. *Counselor Education and Supervision*.

J. M. Bernard and R. K. Goodyear. 2019. *Fundamentals of Clinical Supervision*, 6 edition. Pearson.

D. Cabrera Lozoya, E. Hernandez Lua, J. A. Barajas Perches, M. Conway, and S. D'Alfonso. 2025. Synthetic empathy: Generating and evaluating artificial psychotherapy dialogues to detect empathy in counseling sessions. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 152–163. Association for Computational Linguistics.

D. L. Chow, S. D. Miller, J. A. Seidel, R. T. Kane, J. A. Thornton, and W. P. Andrews. 2015. The role of deliberate practice in the development of highly effective psychotherapists. *Psychotherapy*, 52(3):337–345.

A. C. Del Re, C. Flückiger, A. O. Horvath, and B. E. Wampold. 2021. Examining therapist effects in the alliance-outcome relationship: A multilevel meta-analysis. *Journal of Consulting and Clinical Psychology*, 89(5):371–378.

C. Flückiger, A. C. Del Re, B. E. Wampold, and A. O. Horvath. 2018. The alliance in adult psychotherapy: A meta-analytic synthesis. *Psychotherapy*, 55(4):316–340.

C. Hannan, M. J. Lambert, C. Harmon, S. L. Nielsen, D. W. Smart, K. Shimokawa, and S. W. Sutton. 2005. A lab test and algorithms for identifying clients at risk for treatment failure. *Journal of Clinical Psychology*, 61(2):155–163.

D. Hatfield, L. McCullough, S. H. B. Frantz, and K. Krieger. 2010. Do we know when our clients get worse? an investigation of therapists' ability to detect negative client change. *Clinical Psychology & Psychotherapy*, 17(1):25–32.

L. Huang, W. Yu, W. Ma, W. Zhong, Z. Feng, H. Wang, Q. Chen, W. Peng, X. Feng, B. Qin, and T. Liu. 2025. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. *ACM Transactions on Information Systems*, 43(2):1–55.

Z. E. Imel, M. Steyvers, and D. C. Atkins. 2024. Computational psychotherapy research: Current status and future directions. *Behaviour Research and Therapy*, 172:104430.

H. Jeong, S. Lee, and B. K. Sohn. 2025. Exploring ai-based role-play simulation for mental health counseling training. *Psychiatric Services*.

Z. Ji, N. Lee, R. Frieske, T. Yu, D. Su, Y. Xu, E. Ishii, Y. J. Bang, A. Madotto, and P. Fung. 2023. Survey of hallucination in natural language generation. *ACM Computing Surveys*, 55(12):1–38.

C. E. Johnson, J. L. Keating, M. Leech, P. Congdon, F. Kent, M. K. Farlie, and E. K. Molloy. 2021. Development of the feedback quality instrument: A guide for health professional educators in fostering learner-centred discussions. *BMC Medical Education*, 21(1):382.

S. L. Kopelovich, K. Doud, M. Ofer, and B. Stiles. 2025a. Development and validation of a machine learning system for rating CBT for psychosis competencies. *Psychotherapy*, 62(1):1–11.

S. L. Kopelovich, K. Doud, M. Ofer, and B. Stiles. 2025b. Trainee and supervisor perspectives on ai-generated feedback in CBT for psychosis training. *Psychotherapy*, 62(1):12–21.

J. R. Landis and G. G. Koch. 1977. The measurement of observer agreement for categorical data. *Biometrics*, 33(1):159–174.

D. Milne. 2007. An empirical definition of clinical supervision. *British Journal of Clinical Psychology*, 46(4):437–447.

F. Schmidt, K. Hammerfald, H. H. Jahren, and V. Vlassov. 2025. CFiCS: Graph-based classification of common factors and microcounseling skills. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 106–115. Association for Computational Linguistics.

S. H. Stige, A. Montesano, and K. Aafjes-van Doorn. under review. Use of generative AI as a path to strengthen clinical training: First steps and emerging challenges for active learning. *Active Learning in Higher Education*. Under review.

Z. Tian, L. Yang, and W. Liang. 2025. Ai-simulated clients in counseling training: Effects on self-efficacy and skill development. *Training and Education in Professional Psychology*.

T. J. G. Tracey, B. E. Wampold, J. W. Lichtenberg, and R. K. Goodyear. 2014. Expertise in psychotherapy: An elusive goal? *American Psychologist*, 69(3):218–229.

T. Tseriotou, J. Chim, A. Klein, A. Shamir, G. Dvir, I. Ali, C. Kennedy, G. S. Kohli, A. Hills, A. Zirikly, D. Atzil-Slonim, and M. Liakata. 2025. Overview of the CLPsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 178–196. Association for Computational Linguistics.

S. Walfish, B. McAlister, P. O'Donnell, and M. J. Lambert. 2012. An investigation of self-assessment bias in mental health providers. *Psychological Reports*, 110(2):639–644.

B. E. Wampold and J. Owen. 2021. Therapist effects: History, methods, magnitude, and characteristics of effective therapists. In M. Barkham, W. Lutz, and L. G. Castonguay, editors, *Bergin and Garfield's handbook of psychotherapy and behavior change*, 7th edition, pages 297–326. Wiley.

S. Yosef, M. Zisquit, B. Cohen, A. Brunstein Klomek, K. Bar, and D. Friedman. 2024. Assessing motivational interviewing sessions with ai-generated patient simulations. In *Proceedings of the 9th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2024)*, pages 1–11. Association for Computational Linguistics.

S. Zilcha-Mano. 2025. Commentary: Toward a new era in psychotherapy training. *Psychotherapy*, 62(1):22–27.

A Appendix A. Example Feedback Instance with Expert Annotations

The following feedback instance (Participant P011, Session 3) illustrates the structure of PRACTICE-generated feedback and the proposition-level annotation scheme applied by expert raters. Each proposition is labeled with its feedback component and expert verdict.

Strengths

1. *"You demonstrated consistent and specific validation of Pedro's distress ('you feel singled out...'; 'I'm not here to judge you'). This reduced his defensiveness and increased his openness."* **[Unsure]**

2. *"You also conducted a good functional exploration of his substance use (disconnecting from stress → drinking → conflict at home)."* **[Justified]**

3. *"...and connected with personal resources (walking with music, cooking paella)."* **[Justified]**

4. *"You concluded with a small, concrete behavioral plan and a backup plan, reinforcing agency and realistic hope."* **[Justified]**

Area for Improvement

5. *"More explicit alliance repair when Pedro feels judged: you could name the relational tension at the moment ('I notice this sounds like judgment to you; if it happens here, I'd prefer we address it openly'). This strengthens the alliance and prevents ruptures."* **[Justified]**

6. *"Avoid quickly resorting to exercise as a solution. Instead, focus more on their language and motivation (e.g., 'turn down the volume in their head') and co-create equivalent micro-alternatives for disconnecting. Frame the invitation as an experiment, not an obligation."* **[Justified]**

7. *"Delve into ambivalence and autonomy: explore the pros and cons of drinking and alternatives with open-ended questions ('what does it give you and what does it take away, when is it easier for you to stop?'). Reflect on Pedro's own reasons for change and ask for his permission before making suggestions."* **[Justified]**

8. *"Close with agency marker and follow-up: agree on how you will measure success (e.g., '1 walk = success') and what you will do if an obstacle arises. Encourage participants to bring specific data to the next session."* **[Justified]**

Note. PRACTICE operates in Spanish; all training sessions and generated feedback are conducted in that language. The feedback instance presented in this appendix has been translated into English by the authors for accessibility. Proposition boundaries and expert verdicts are identical to those applied to the original Spanish text. Propositions are labeled as Justified, Unjustified, or Unsure based on full agreement between both expert raters. Proposition 1 was rated Unsure by both raters: the behavioral referents cited (the quoted phrases) are present in the transcript, but the causal claim, that they "reduced defensiveness and increased openness", was deemed insufficiently grounded in observable evidence. This instance contains 1 of 15 non-justified propositions in the dataset, concentrated in the Strengths component, consistent with the pattern reported in the Results section.

Psycholinguistic Profiles of Cognitive Distortions in Reddit Data

Neha Sharma
University of Tartu, Estonia
neha.sharma@ut.ee

Navneet Agarwal
University of Tartu, Estonia
navneet.agarwal@ut.ee

Kairit Sirts
University of Tartu, Estonia
kairit.sirts@ut.ee

Abstract

Cognitive distortions (CDs) are systematically biased patterns of thinking associated with the onset and maintenance of mental health conditions such as depression and anxiety. Computational research on CDs has primarily focused on detection and classification, while the linguistic characterization of distorted language; what psycholinguistic features distinguish distorted from non-distorted text, and whether individual distortion types carry distinct language patterns, remains largely unexplored. Using a Reddit dataset, we apply a Generalized Linear Model (GLM) with bootstrap sampling to LIWC-derived features and find that CD language is psycholinguistically distinct from non-distorted language. We further characterize type-specific psycholinguistic profiles for each CD, and through hierarchical clustering show that CD types are not fully separable, with certain distortions sharing stable linguistic signatures. Together, these findings contribute to the linguistic characterization of CDs, offering an empirically grounded account of the psycholinguistic properties that distinguish distorted language at the level of CDs as a whole and across specific distortion types.

1 Introduction

Cognitive distortions (CDs) are systematic patterns of negatively biased thinking that distort how individuals interpret events and reality (Beck, 1963; Beck et al., 1979). Distorted thinking patterns have been associated with depression, anxiety, and a range of psychological difficulties, making their study important for both clinical practice and mental health research (Joormann and Stanton, 2016; Ouhmad et al., 2024). Crucially, CDs are not purely internal cognitive events; they can be reflected in language. Beck (1963)'s work identified distortions through the verbal content of patient speech, and subsequent theoretical work has described each distortion type in terms of characteristic patterns of expression (Burns, 1980). This makes language a natural and accessible medium through which distorted thinking can be studied.

Computational research on CDs has approached the phenomenon as a detection and classification problem: given a text segment, determining whether it contains a distortion (binary classification) and, if so, which distortion type(s) (multi-label, multi-class classification) (Sage et al., 2025). A range of methods have been applied to these tasks, from rule-based systems to fine-tuned language models (Sage et al., 2025), which typically enable inferences at the instance level.

A complementary but distinct direction is linguistic profiling, which characterizes the psycholinguistic[1] properties of distorted language and examines whether individual distortion types leave distinguishable traces in language use. Rather than classifying individual texts, this approach aims to make inferences at the population or phenomenological level, describing what distorted language looks like as a broader linguistic phenomenon. Despite its potential, this direction has so far received limited attention.

This approach is well-established in the broader mental health NLP literature, where linguistic markers have been used to characterize conditions such as depression, anxiety, PTSD, and suicidality, yielding interpretable, theoretically grounded insights into the language of these conditions (Homan et al., 2022; Khuon et al., 2026). These studies have consistently demonstrated that different psychological states leave systematic, identifiable traces in language; traces that can be characterized in ways that are meaningful to both clinicians and researchers.

The groundwork for linguistic profiling of CDs

[1] In this work, "psycholinguistic" refers to the characterization of text through lexical features that capture both linguistic structure (e.g., word choice, syntactic markers, temporal orientation) and psychological processes (e.g., affective, cognitive, and social dimensions), as operationalized by LIWC-22

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 306–323
July 4, 2026 ©2026 Association for Computational Linguistics

already exists. Burns (1980) described characteristic linguistic patterns for individual distortion types, for example "Overgeneralization" defined as drawing broad conclusions from a single negative event, expressed through words such as "always" or "never." Bathina et al. (2021) subsequently demonstrated that these descriptions can be translated into identifiable linguistic units detectable in text. Despite growing computational interest in CDs, systematic linguistic characterization of individual distortion types remains limited. The psycholinguistic profiles that would make distortion-specific language patterns interpretable and comparable have not yet been constructed. This study tries to address this research gap guided by the following research questions:

RQ1: Do texts containing cognitive distortions exhibit distinct psycholinguistic characteristics compared to texts without cognitive distortions, as measured by LIWC-derived features?

RQ2: Can individual cognitive distortion types be characterized by distinct psycholinguistic profiles, and to what extent are these profiles linguistically distinguishable from one another?

Guided by these research questions, we first establish statistical differences in language between texts containing CDs v/s those without. We further construct psycholinguistic profiles for individual distortion types considered in this study, and explore similarities between them.

2 Related Work

CD detection has followed a familiar methodological progression in NLP, from lexicon-driven approaches such as curated n-gram schemata (Bathina et al., 2021), to feature-engineered representations (e.g., n-grams/TF–IDF and psycholinguistic features) paired with classical machine learning (Simms et al., 2017; Shickel et al., 2019; Shreevastava and Foltz, 2021), and more recently to neural and transformer-based modeling (Rojas-Barahona et al., 2018; Mostafa et al., 2021; Lybarger et al., 2022), followed by LLM-based approaches (Chen et al., 2023; Lim et al., 2024; **?**).

While predictive modeling of CDs has been extensively explored, the linguistic characterization of distorted language remains comparatively understudied. Research in mental health NLP has long used linguistic markers to study conditions such as depression (Rude et al., 2004; De Choudhury et al., 2021; Eichstaedt et al., 2018), anxiety (Al-Mosaiwi and Johnstone, 2018; Abutara et al., 2025), PTSD (Coppersmith et al., 2014; Quillivic et al., 2025), and suicidality (Dobbs et al., 2023; Agurto et al., 2018), showing that language patterns can provide interpretable insights into underlying psychological states. Linguistic Inquiry Word Count (LIWC) framework (Boyd et al., 2022; Tausczik and Pennebaker, 2010) is one such tool which has consistently revealed systematic differences in language use across clinical populations. For example, depressed individuals tend to use more negative emotion words, first-person singular pronouns, and absolutist language (Tackman et al., 2019), while anxious language is associated with elevated uncertainty and threat-related vocabulary (Al-Mosaiwi and Johnstone, 2018).

Several studies have also incorporated LIWC features into CD detection models, improving classification performance (Shreevastava and Foltz, 2021; Bollen et al., 2021; Simms et al., 2017; Wiemer-Hastings et al., 2004). However, these studies treat LIWC features as model inputs rather than objects of analysis, leaving the linguistic characteristics of individual distortion types largely unexamined.

Bathina et al. (2021) developed 241 n-grams (cognitive distortion schemata, CDS) to capture the linguistic characteristics of 12 CD types, validated with CBT experts and computational linguists. The same lexicon was subsequently applied to historical book corpora (Bollen et al., 2021) and psychotherapy transcripts (Lalk et al., 2024), demonstrating that CD-specific language is detectable across diverse text sources. However, these operationalizations remain anchored to surface n-gram matching and have been used primarily for detection and prevalence tracking rather than systematic linguistic characterization of individual distortion types.

To our knowledge, no study has examined the broader linguistic profiles of individual CD types across a common feature space. This work addresses this gap by constructing per-CD linguistic profiles using psycholinguistic features and examining the differences and similarities between linguistic profiles of different CDs.

3 Data and Annotations

This section describes the dataset, CD labeling process, and LIWC features used in this study.

Stage	Users		Posts		Avg.	
	C	D	C	D	C	D
raw	35,753	3,070	∼32.0M	∼5.34M	895	1,739
proc.	35,697	3,069	∼19.71M	∼3.22M	552	1,048
balanced	3,069	3,069	∼1.69M	∼3.22M	551	1,048
final	3,069	3,069	∼1.53M	∼3.20M	498	1,041

Table 1: RSDD statistics. proc.: preprocessed. C/D denote Control/Depression. final: corpus after CD labeling (§3.2). Avg.: average number of posts per user.

3.1 RSDD Dataset

In this study we use the Reddit Self-Reported Depression Diagnosis (RSDD) dataset (Yates et al., 2017), a large corpus of Reddit posts from users with self-reported depression and a matched control cohort; for details about the original dataset refer to the original study. To this dataset, we first applied basic pre-processing involving removal of empty strings, posts without user labels, and non-English text. We then balanced the dataset by taking an equal number of users in both cohorts. Refer to Table 1 and Appendix A for additional details.

3.2 Cognitive Distortion Labeling

The RSDD corpus does not contain cognitive distortion labels. To enable our linguistic analyses, we therefore need to construct CD labels for RSDD posts. The publicly available Therapist Q&A dataset (Shreevastava and Foltz, 2021) provides CD annotations on user inputs across 2,530 user-therapist exchanges and has supported prior work on CD detection and classification.

CD detection is, however, an inherently subjective task. Sharma et al. (2026) argue that in such domains, where objective ground truth is unattainable, label reliability provides the practical way forward: when the same label is consistently produced across independent annotation passes, this consistency indicates that the underlying text contains genuine signals rather than annotation-specific noise. This consideration is directly relevant to Therapist Q&A: its human inter-annotator agreement of 33.7% reflects substantial annotator disagreement, indicating that any single annotation set on this corpus cannot be treated as reliable ground truth. We therefore do not use Therapist Q&A directly for our analyses, and instead build a labeling pipeline that applies the reliability principle to generate labels for RSDD using Therapist Q&A annotations as input.

Sharma et al. (2026) operationalize this principle through multiple LLM annotation runs, retaining labels that appear consistently across runs as reliable. We adapt the same principle to operate across two independently produced annotation sets of the Therapist Q&A dataset: the human annotations of Shreevastava and Foltz (2021) (IAA 33.7%) and the LLM-based annotations of Sharma et al. (2026) (Fleiss's κ 0.78).

We train two separate multi-label mentalRoBERTa-based classifiers (Ji et al., 2022) with default parameters, one on each annotation set. Both classifiers follow the architecture, hyperparameters, and data splits of Sharma et al. (2026), and reproduce classification performance comparable to that reported in the original study. Both classifiers are then retrained on the full Therapist Q&A dataset, leveraging all available annotated examples to maximize the training signal for label transfer, and applied to the RSDD corpus, producing two independent sets of predicted CD labels per post.

Since our goal is linguistic profiling rather than classification, label reliability is paramount. We adopt a conservative agreement-based filtering strategy; we retain only RSDD posts where the two label sets agree in one of two forms. Complete agreement indicates that both classifiers assign identical CD label sets to a post. Partial agreement indicates that the two label sets share at least one common CD label but are not identical; in this case, we take the shared label(s) as the final assignment. Posts with entirely disjoint predictions are discarded. The rationale is that labels that survive this cross-source agreement are more likely to reflect genuine distortion-relevant linguistic signals than artifacts of any specific annotation source. The retained labels form the basis for all downstream linguistic analyses. Table 1 (final row) reports the resulting labeled corpus, and Table 2 lists the CD types considered. Full details of the labeling pipeline and classifier training are provided in Appendix B.

3.3 LIWC

Psycholinguistic features were extracted for the dataset using LIWC-22[2] (Boyd et al., 2022), which is a dictionary-based tool that maps text onto interpretable linguistic and psychological dimensions. From the full LIWC feature set (120+ categories), we selected a subset capturing core linguistic struc-

[2]LIWC-22 was accessed under a research license

No.	Cognitive Distortion	Description and Example
1.	Emotional Reasoning (ER)	Assuming emotions reflect reality. *Example:* "I feel worthless, so I must be a failure."
2.	Overgeneralization (Over)	Drawing broad conclusions from limited experiences. *Example:* "I failed this interview, I'll never get a job."
3.	Should Statements (SS)	Holding rigid expectations for oneself or others. *Example:* "I should always be calm and never get upset."
4.	All-or-Nothing Thinking (AoN)	Viewing situations in extremes. *Example:* "If I'm not the best, I'm a total failure."
5.	Mind Reading (MR)	Presuming negative judgments from others. *Example:* "She didn't say hi, she must think I'm annoying."
6.	Fortune Telling (FT)	Predicting negative outcomes with certainty. *Example:* "There's no point in applying, I know I won't get accepted."
7.	Magnification (Mag)	Exaggerating potential problems. *Example:* "If I mess up this report, I'll lose my job and never recover."
8.	Personalization (Per)	Taking undue responsibility for external events. *Example:* "My friend is upset, it must be something I did wrong."
9.	Labeling (La)	Defining oneself or others by single traits. *Example:* "I missed a deadline, I'm so incompetent."
10.	Mental Filter (MF)	Focusing only on negative aspects. *Example:* "Everyone said my presentation was good, but one person criticized it, so it must have been terrible."

Table 2: List of CDs considered in this study based on Shreevastava and Foltz (2021). Mental Filter is excluded from our analysis due to negligible presence (26 posts out of 4.73M) in the RSDD predictions.

ture, cognitive processing, temporal orientation, and affective dimensions, excluding hierarchically redundant or task-irrelevant categories. Appendix C provides more details on selected features.

4 Methodology

This section details our analysis process with the following subsections explaining task formulation, statistical modeling, and sampling strategies used within the process.

4.1 Task Formulation

To answer our research questions, we define three complementary tasks.

1. **TASK(CD/ND):** Posts containing at least one CD (positive class) are compared against No Distortion (ND) posts (negative class), capturing broad linguistic differences between distorted and non-distorted language.

2. **TASK(XCD/ND):** Identifying CD-specific features relative to No distortion posts.

3. **TASK(XCD/¬XCDS):** Each CD type (positive class) is compared against all remaining CD types (negative class) (one-vs-rest), isolating what linguistically distinguishes it from other CDs.

TASK(CD/ND) answers RQ1 and also provides a reference point for interpreting results for RQ2. TASK(XCD/ND) and TASK(XCD/¬XCDS) together drive our CD-type profiling (RQ2).

4.2 Sampling Strategy

Our corpus contains 6,138 users and ∼4.73M posts, with multiple posts per user. Running inference on the full dataset is computationally expensive and can yield overly small p-values due to the very large n. We therefore use a *user-clustered bootstrap* with a controlled subsampling procedure that (i) preserves user-level dependence and (ii) yields balanced, comparable bootstrap samples. The following procedure generates one bootstrap sample:

1. **Eligible users:** Identify users who have at least one *positive* and one *negative* class post under the task definition (§4.1).

2. **Stratify users:** Sample an equal number of users from the depression and control groups (these group labels are *not* used as predictors; they are used only to avoid dominance of one user population in subsamples).

3. **Balance classes:** Within sampled users, draw posts to obtain equal numbers of positive and negative examples for each user.

4. **Cap size:** Continue sampling users until the total post count first exceeds 10,000 posts. Based on pilot experiments, a cap of 10,000 posts provided a practical stability–compute trade-off.

4.3 Statistical Modeling

We initially considered mixed-effects multivariable logistic regression (Generalized Linear Mixed

Model; GLMM) (Bates et al., 2015) shown in equation 1 for our analysis. This choice was based on the binary nature of our tasks §4.1, multiple LIWC features as predictors (fixed effect), and use of random intercept to account for dependency due to multiple posts per user.

$$y \sim \underbrace{x_1 + x_2 + \cdots + x_K}_{\textit{Fixed Effects}} + \underbrace{(1 \mid \text{user})}_{\textit{Random Intercept}} \quad (1)$$

In preliminary analysis, the estimated variance of the random intercept consistently approached zero (i.e., boundary/singular fits) under our sampling design, indicating that the user-level random effect contributed negligibly once LIWC predictors were included and samples were constructed in a user-aware, balanced manner. In this situation, the GLMM reduces to a fixed-effects-only Generalized Linear Model (GLM) (Nelder and Wedderburn, 1972). For computational efficiency and numerical stability we therefore report results from GLM defined as:

$$\text{logit}\big(\Pr(y_i = 1)\big) \;=\; \beta_0 \;+\; \sum_{k=1}^{K} \beta_k \, x_{k,i}. \quad (2)$$

Where, $y_i \in \{0, 1\}$ denote the task-specific label for i^{th} post, $x_{k,i}$ denote the k-th LIWC feature for i^{th} post, β_k is corresponding fixed-effect coefficient, and β_0 is the intercept.

For each task, we fit a GLM using the selected LIWC features and quantify uncertainty via $B = 500$ bootstrap samples. We use bootstrap median coefficient ($\tilde{\beta}$) as the primary effect estimate, together with 95% confidence interval (CI) and bootstrap standard error ($\widehat{\text{SE}}$_boot) values. Coefficients are reported on the log-odds scale, where the sign indicates whether a feature is associated with a higher ($\tilde{\beta} > 0$) or lower ($\tilde{\beta} < 0$) probability of the positive class. For interpretability, we also report odds ratios $\widetilde{\text{OR}} = \exp(\tilde{\beta})$ and the corresponding percentage change in odds, computed as $(\widetilde{\text{OR}} - 1) \times 100$ (Heyard, 2026). Since predictors are standardized (z-scored), these odds ratios represent the change in odds associated with one standard deviation increase in a given LIWC feature, holding other features constant.

To ensure significance, consistency, and stability of reported features, we use 95% CI and Relative Standard Error (RSE). Excluding features with zero within their 95% CI ensures that retained features are both significant and sign consistent across bootstraps. Feature stability across bootstraps is measured using RSE, defined as:

$$\text{RSE} = \frac{\widehat{\text{SE}}\text{_boot}}{|\tilde{\beta}|}, \quad (3)$$

RSE provides a scale-free measure of stability: the same absolute bootstrap SE ($\widehat{\text{SE}}$_boot) can imply high stability for a large effect (large $\tilde{\beta}$) but low stability for a small effect (small $\tilde{\beta}$).

5 Results

This section discusses the results from our statistical modeling for 3 tasks in §4.1.

5.1 Distorted vs non-distorted language

Table 3 summarizes the significance and effect of LIWC features for the TASK(CD/ND). Overall, CD text corresponds to a more negative *Tone* ($\tilde{\beta}$=−0.61, −45.49%) and shows highest association with *swear* ($\tilde{\beta}$=0.65, +91.31%). Temporally CD language is shown to be less past-oriented ($\tilde{\beta}$=−0.18, −16.09%) and more present-focused ($\tilde{\beta}$=0.10, 10.91%). Absolutist vocabulary, captured by *allnone*, is strongly elevated in CD posts ($\tilde{\beta}$=0.41, +50.60%), and *negations* are associated with higher CD odds ($\tilde{\beta}$=0.29, +33.58%).

These results provide a clear answer to RQ1: texts containing cognitive distortions differ significantly from texts without cognitive distortions on a range of psycholinguistic features. CD text is consistently negative in emotional language, with elevated negative emotion words *(emo_neg)*, reduced positive emotion words *(emo_pos)*, and an overall negative tone *(Tone)*. It is more absolutist *(allnone)* and has a reduced analytic structure. Linguistically, CD text is more likely to contain moral language *(moral)* and achievement-related language *(achieve)*, and is more interpersonally referenced *(socrefs)* while being less affiliative and less polite.

5.2 Cognitive Distortion Profiles

TASK(xCD/ND) and TASK(xCD/¬xCDs) (§4.1), together help define the psycholinguistic profiles of individual CDs considered in this study. The profiles are defined based on 44 unique LIWC features obtained from the union of the top 15 features (highest absolute $\tilde{\beta}$) for each CD within beforemetioned tasks. Figure 1 plots these profiles. TASK(CD/ND) further represents global CD trends, providing a reference point for analyzing individual CD profiles. For each CD we group

Feature	$\tilde{\beta}$	$\widetilde{\mathrm{OR}}$	%Δ Odds	RSE	95% CI
swear	0.65	1.91	91.31	••	[0.50, 0.82]
Tone	-0.61	0.55	-45.49	•••	[-0.70, -0.51]
moral	0.44	1.55	55.01	••	[0.31, 0.59]
WC	0.44	1.55	54.75	••	[0.28, 0.65]
allnone	0.41	1.51	50.60	••	[0.31, 0.51]
emo_neg	0.33	1.40	39.68	••	[0.18, 0.51]
negate	0.29	1.34	33.58	••	[0.19, 0.39]
socrefs	0.24	1.27	26.90	•	[0.11, 0.37]
polite	-0.18	0.84	-16.49	•	[-0.34, -0.06]
achieve	0.18	1.19	19.33	••	[0.11, 0.25]
focuspast	-0.18	0.84	-16.09	••	[-0.26, -0.09]
emo_pos	-0.17	0.84	-15.97	•	[-0.27, -0.08]
affiliation	-0.16	0.85	-14.70	•	[-0.25, -0.07]
Analytic	-0.16	0.85	-14.59	•	[-0.25, -0.07]
insight	0.15	1.16	16.24	••	[0.08, 0.21]
conflict	-0.13	0.88	-12.00	•	[-0.21, -0.04]
power	0.12	1.12	12.33	•	[0.04, 0.19]
focuspresent	0.10	1.11	10.91	•	[0.02, 0.18]
certitude	0.09	1.10	9.78	•	[0.04, 0.15]
discrep	-0.08	0.92	-7.91	•	[-0.15, -0.01]
cause	0.08	1.08	8.35	•	[0.02, 0.14]
curiosity	-0.08	0.92	-7.60	•	[-0.16, -0.01]
lack	0.07	1.07	7.29	•	[0.02, 0.15]

Table 3: TASK(CD/ND): GLM feature effects (median across bootstraps) with uncertainty and stability. $\tilde{\beta}$ and $\widetilde{\mathrm{OR}} = \exp(\tilde{\beta})$ denote bootstrap medians. Relative Standard Error (RSE) encodes stability categories: ••• = extremely stable (RSE ≤ 0.10), •• = stable (0.10–0.25], • = moderately stable (0.25–0.50]. %Δ Odds is computed as $(\widetilde{\mathrm{OR}} - 1) \times 100$. All reported effects are extremely sign-consistent across bootstraps (consistency $> 99\%$).

the features into two categories: Core markers and Global markers. Core markers are features where individual CD values deviate considerably from global trends i.e. substantial $\tilde{\beta}$ values for TASK(XCD/ND) and TASK(XCD/¬XCDS), while Global markers are features where CD closely follows global distortion values. For example, in All-or-Nothing Thinking (AoN), *Authentic & socrefs* are Core markers whereas *Tone & i* are Global markers. Appendix D Table 8 presents the complete list of Core and Global markers for individual CDs.

Figure 1 highlights patterns that are characteristic of individual CDs and can help differentiate them from other CDs as well as non-distorted text. Anxiety-related words (*emo_anx*) are characteristic of Emotional Reasoning (ER) and Fortune Telling (FT), while social references (*socrefs*) are characteristic of Mind Reading (MR) and Magnification (Mag). These examples illustrate that individual CDs can be characterized by distinct psycholinguistic patterns in LIWC-derived features, positively answering our second research question.

6 CD Profile Clustering

While constructing individual CD profiles, we observed that many psycholinguistic features appeared across multiple CD types, suggesting substantial overlap in their linguistic signatures. This indicates that CD types are not fully distinct at the linguistic level, and the overlap in their profiles is worth exploring. To this end, we apply hierarchical clustering (Ward, 1963) using the GLM median coefficient ($\tilde{\beta}$) values of the CD profiles (see Appendix E for the full tables of feature and $\tilde{\beta}$).

Figure 2 presents the clustering results for both TASK(XCD/ND) and TASK(XCD/¬XCDS). Although some differences exist, certain groupings remain consistent: Fortune Telling, Emotional Reasoning, and Magnification cluster together, and this grouping is stable across both tasks, appearing with low within-cluster correlation distance, as do Personalization and Labeling. The top 10 features driving each cluster are reported in Table 4.

7 Discussion

Our findings confirm that CD language is psycholinguistically distinct from non-distorted language. Our results show a positive association between CD and LIWC features representing negative emotions *(emo_neg, swear)*, absolutist vocabulary *(allnone, certitude)*, and negation language *(negate)*. These findings align with Burns (1980)'s characterization of CDs as patterns of systemati-



Figure 1: Psycholinguistic profiles of 9 CDs from TASK(CD/ND): ▲, TASK(XCD/ND): −−, and textscTask(xCD/¬xCDs): −. X-axis plots the 44 union LIWC features considered and Y-axis plots the bootstrap median coefficient ($\tilde{\beta}$).

Task	Cluster CDs	Top 10 driver features
TASK(CD/ND)	ER, FT, Mag	+emo_anx, −socrefs, +focusfuture, +death, +Authentic, +swear, −discrep, −Tone, +illness, −emo_pos
	AoN, Over	−emo_anx, +i, +allnone, +emo_anger, −socrefs, +negate, −emo_pos, −Tone, +emo_neg, +achieve
	La, Per, SS	+moral, −emo_anx, +swear, −focusfuture, −death, +socrefs, −Authentic, +WC, +i, +auxverb
	MR	+socrefs, +insight, −you, −swear, −Authentic, −death, +tentat, −affiliation, −discrep, −focuspast
TASK(XCD/¬XCDS)	AoN, ER, FT, Mag	−socrefs, +emo_anx, +focusfuture, +death, +Authentic, −moral, −insight, −differ, +discrep, +you
	La, Per	+moral, −emo_anx, +swear, −focusfuture, −Authentic, +socrefs, −death, +emo_neg, −discrep, −Tone
	MR, SS	+socrefs, +insight, −death, −Authentic, +Tone, −you, +i, −swear, −affiliation, +auxverb
	Over	−emo_anx, −i, +negate, +Tone, −you, +allnone, +focuspast, −focusfuture, −death, −feeling

Table 4: Top 10 driver features per cluster for TASK(CD/ND) and TASK(XCD/¬XCDS). These features indicate which shared positive and negative patterns underlie the observed clustering.



Figure 2: Hierarchal clustering of CDs in TASK(XCD/ND) and TASK(XCD/¬XCDS) based on their lingustic profiles and corresponding $\tilde{\beta}$ values.

cally negative and absolutist thinking. Furthermore, these inferences align with findings from previous studies (Simms et al., 2017; Al-Mosaiwi and Johnstone, 2018), that also show higher use of negative emotions and absolutist language in CD text as compared to control.

Additionally, our results also show that individual CDs carry distinct linguistic cues, not only enabling the characterization of type-specific psycholinguistic profiles, but also allowing differentiation between them. For example, future orientation *(focusfuture)* and anxiety language *(emo_anx)*, combined with elevated tentative language *(tentat)*, are characteristic features of Fortune Telling profile, which directly reflect its clinical definition of predicting negative outcomes as facts without evidence (Burns, 1980, p. 37). Similarly Emotional Reasoning profile shows strong anxiety *(emo_anx)* and feeling *(feeling)* and highly self-referential language *(i)*, which is consistent with its clinical definition of treating emotional states as evidence (Burns, 1980, p. 38). These patterns are further supported by Shreevastava and Foltz (2021), who also found elevated future-focused language for Fortune Telling and elevated feel language for Emotional Reasoning. Similar patterns were observed across all remaining CD types, with each profile reflecting its corresponding clinical definition from Burns (1980, p. 32–43).

The psycholinguistic profiles identified in this study contribute to the linguistic characterization gap in prior work. Rather than treating CD as an opaque categorical label, these profiles specify which linguistic dimensions are elevated or suppressed in distorted text, and how strongly, enabling inferences at the population and phenomenological level. Furthermore, the estimated $\tilde{\beta}$ values provide a quantifiable, and continuous measure of each LIWC-feature and its association with a given CD. This can be used to estimate the severity of predicted distortion by comparing the linguistic profile of a given text with reference to the profile of the corresponding CD. This can also enable longitudinal tracking of changes in a person's cognitive distortion patterns, offering more insights into a person's mental health. This kind of evidence-based linguistic profiling is particularly valuable in clinical and research contexts, where understanding the psycholinguistic nature of distorted thinking at the population level complements downstream applications such as detection and classification.

Beyond individual CD profiles, clustering analysis revealed linguistic similarity across CD types. The consistent grouping of Fortune Telling, Emotional Reasoning, and Magnification across both tasks is theoretically coherent: following Burns (1980, p. 32–43), these distortions share a negative future outlook, reflected in their driver features; anxiety language *(emo_anx)*, future orientation *(focusfuture)*, and death/illness vocabulary *(death, illness)*. This aligns with Shickel et al. (2019), who similarly found natural groupings among overlapping CD types, reinforcing that CD categories are not fully separable linguistically, however, their specific cluster compositions differ from our find-

ings, likely due to the use of different datasets and CD taxonomies.

8 Future Work

In the future, we plan to leverage the temporal structure of the RSDD dataset alongside CD psycholinguistic profiles to track how distortion patterns evolve over time. This would enable estimation of distortion severity and longitudinal monitoring. Additionally, integrating CD profiles with mental health measures, such as self-reported depression, could reveal how specific distortions cooccur with these conditions. This may help identify early indicators or risk factors, providing a more nuanced understanding of the relationship between cognitive distortions and mental health.

9 Conclusion

This study investigated the psycholinguistic properties of cognitive distortions, motivated by a gap in prior research: while detection systems are well-studied, the linguistic cues underlying distorted thinking remain relatively unexplored. We proposed that psycholinguistic profiling via LIWC-derived features offers a viable path toward addressing this. Our results confirm that CD language is psycholinguistically distinct from non-distorted language. Beyond the global distinction, individual CD types exhibit meaningful psycholinguistic profiles that broadly mirror their clinical definitions, demonstrating that linguistic markers can characterize not only whether a text is distorted but also what kind of distortion it reflects. Hierarchical clustering further reveals that CD types are not fully separable at the linguistic level, certain distortions share stable psycholinguistic signatures, reflecting their linguistic overlap.

Together, these findings suggest that psycholinguistic profiling provides an empirically grounded and human-interpretable characterization of cognitive distortions at the population level by revealing how cognitive distortions manifest linguistically, a particularly valuable property in the mental health domain where understanding the nature of the phenomenon is as important as its detection.

Limitations

The RSDD dataset consists of Reddit posts, which differ substantially from clinical text; findings may therefore not generalize to clinical populations or settings. Furthermore, although depression and control labels are not used as predictors, they guide sampling, meaning results may be implicitly shaped by this divide. Additionally, since cognitive distortions are inherently context-dependent, the variable length and informal nature of Reddit posts may also introduce noise into the profiles.

The CD labels carry additional uncertainty given the subjective nature of the task. Although we try to mitigate this by combining two different labeling sources for our CD predictions, the final CD labels can still carry noisy predictions arising from original training labels.

As a lexicon-based framework, LIWC lacks sensitivity to meaning and context, meaning psychologically distinct expressions may receive identical feature representation. Furthermore, the initial LIWC feature selection was guided by the researchers' domain knowledge and subjective judgment, and may therefore vary across research teams, potentially yielding different feature sets.

Finally, while the GLMM random intercept collapsing to zero justified the simplification to GLM, this may partly reflect an artifact of the sampling procedure itself, equal per-user balancing may have removed the very user-level variance the random intercept was intended to capture, rather than indicating a genuine absence of user dependency in data.

Acknowledgments

This research was supported by the Estonian Centre of Excellence in AI (EXAI) and by the Estonian Research Council Grant PRG3182.

Ethics Statement

This study uses two datasets. The Therapist Q&A dataset is publicly available and contains anonymized text with no personally identifiable information; all use complies with its terms of use. The RSDD dataset was obtained directly from the original authors under a formal data agreement. No personally identifiable information was accessed, and no attempts were made to identify or contact any individuals in the dataset.

All analyses rely on publicly available/with agreement access data, together with open-source tools and the licensed LIWC-22 framework (accessed under a research license). The broader goal of this work is the linguistic characterization of cognitive distortions to support mental health research. As the data originates from social media,

findings should be interpreted with caution and are not intended for clinical diagnosis or therapeutic decision-making. We encourage responsible use within appropriate research and ethical boundaries.

Data and Code Availability

The Therapist Q&A dataset and its annotations are available through Shreevastava and Foltz (2021) and Sharma et al. (2026) respectively. Access to the RSDD dataset may be requested directly from its original authors. Code to reproduce the analyses presented in this work is available on Github[3].

References

Ana Abutara, Aline Kissimoto, Felipe Oliveira de Aguiar, Victor Otani, Ricardo Riyoiti Uchida, and Lucas Murrins Marques. 2025. Beyond words: understanding anxiety and depression in college applicants through liwc analysis of textual features. *Frontiers in Psychology*, Volume 16 - 2025.

Carla Agurto, Pat Pataranutaporn, Elif K. Eyigoz, Gustavo Stolovitzky, and Guillermo Cecchi. 2018. Predictive linguistic markers of suicidality in poets. In *2018 IEEE 12th International Conference on Semantic Computing (ICSC)*, pages 282–285.

Mohammed Al-Mosaiwi and Tom Johnstone. 2018. In an absolute state: Elevated use of absolutist words is a marker specific to anxiety, depression, and suicidal ideation. *Clinical psychological science*, 6(4):529–542.

Douglas Bates, Martin Mächler, Ben Bolker, and Steve Walker. 2015. Fitting linear mixed-effects models using lme4. *Journal of Statistical Software*, 67(1):1–48.

Krishna C Bathina, Marijn Ten Thij, Lorenzo Lorenzo-Luaces, Lauren A Rutter, and Johan Bollen. 2021. Individuals with depression express more distorted thinking on social media. *Nature human behaviour*, 5(4):458–466.

Aaron T. Beck. 1963. Thinking and depression: I. Idiosyncratic content and cognitive distortions. *Archives of General Psychiatry*, 9:324–333.

Aaron T. Beck, A. John Rush, Brian F. Shaw, and Gary Emery. 1979. *Cognitive Therapy of Depression*. Guilford Press, New York.

Johan Bollen, Marijn ten Thij, Fritz Breithaupt, Alexander T. J. Barron, Lauren A. Rutter, Lorenzo Lorenzo-Luaces, and Marten Scheffer. 2021. Historical language records reveal a surge of cognitive distortions in recent decades. *Proceedings of the National Academy of Sciences*, 118(30).

[3]https://github.com/nehasharma666/Psycholinguistic-Profiles-of-Cognitive-Distortions-in-Reddit-Data

Ryan L Boyd, Ashwini Ashokkumar, Sarah Seraj, and James W Pennebaker. 2022. The development and psychometric properties of liwc-22. *Austin, TX: University of Texas at Austin*, 10(1-47):6.

David D. Burns. 1980. *Feeling Good: The New Mood Therapy*. Signet, New York.

Zhiyu Chen, Yujie Lu, and William Wang. 2023. Empowering psychotherapy with large language models: Cognitive distortion detection through diagnosis of thought prompting. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 4295–4304, Singapore. Association for Computational Linguistics.

Glen Coppersmith, Craig Harman, and Mark Dredze. 2014. Measuring post traumatic stress disorder in twitter. *Proceedings of the International AAAI Conference on Web and Social Media*, 8(1):579–582.

Munmun De Choudhury, Michael Gamon, Scott Counts, and Eric Horvitz. 2021. Predicting depression via social media. *Proceedings of the International AAAI Conference on Web and Social Media*, 7(1):128–137.

Matthew F. Dobbs, Alessia McGowan, Alexandria Selloni, Zarina Bilgrami, Cansu Sarac, Matthew Cotter, Shaynna N. Herrera, Guillermo A. Cecchi, Marianne Goodman, Cheryl M. Corcoran, and Agrima Srivastava. 2023. Linguistic correlates of suicidal ideation in youth at clinical high-risk for psychosis. *Schizophrenia Research*, 259:20–27. Language and Speech Analysis in Schizophrenia and Related Psychoses.

Johannes C. Eichstaedt, Robert J. Smith, Raina M. Merchant, Lyle H. Ungar, Patrick Crutchley, Daniel Preoţiuc-Pietro, David A. Asch, and H. Andrew Schwartz. 2018. Facebook language predicts depression in medical records. *Proceedings of the National Academy of Sciences*, 115(44):11203–11208.

Rachel Heyard. 2026. Introduction to regression methods for public health using r. *The American Statistician*, 80(1):188–190.

Stephanie Homan, Marion Gabi, Nina Klee, Sandro Bachmann, Ann-Marie Moser, Martina Duri', Sofia Michel, Anna-Marie Bertram, Anke Maatz, Guido Seiler, Elisabeth Stark, and Birgit Kleim. 2022. Linguistic features of suicidal thoughts and behaviors: A systematic review. *Clinical Psychology Review*, 95:102161.

Shaoxiong Ji, Tianlin Zhang, Luna Ansari, Jie Fu, Prayag Tiwari, and Erik Cambria. 2022. MentalBERT: Publicly available pretrained language models for mental healthcare. In *Proceedings of the Thirteenth Language Resources and Evaluation Conference*, pages 7184–7190, Marseille, France. European Language Resources Association.

Jutta Joormann and Colin H Stanton. 2016. Examining emotion regulation in depression: A review and future directions. *Behaviour research and therapy*, 86:35–49.

Armand Joulin, Edouard Grave, Piotr Bojanowski, and Tomas Mikolov. 2017. Bag of tricks for efficient text classification. In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 2, Short Papers*, pages 427–431, Valencia, Spain. Association for Computational Linguistics.

Clara Khuon, Gabriel Tillman, George Van Doorn, Jacob Dye, Kimberley A. McFarlane, Bridianne O'Dea, and Taylor A. Braund. 2026. Identifying structural linguistic markers of depression in written text: A narrative review of language analysis methods. *Journal of Affective Disorders Reports*, 23:101022.

Christopher Lalk, Lauren A. Rutter, Lorenzo Lorenzo-Luaces, and Johan Bollen. 2024. Depression symptoms are associated with frequency of cognitive distortions in psychotherapy transcripts. *Cognitive Therapy and Research*.

Sehee Lim, Yejin Kim, Chi-Hyun Choi, Jy-yong Sohn, and Byung-Hoon Kim. 2024. ERD: A framework for improving LLM reasoning for cognitive distortion classification. In *Proceedings of the 6th Clinical Natural Language Processing Workshop*, pages 292–300, Mexico City, Mexico. Association for Computational Linguistics.

Kevin Lybarger, Justin Tauscher, Xiruo Ding, Dror Benzeev, and Trevor Cohen. 2022. Identifying distorted thinking in patient-therapist text message exchanges by leveraging dynamic multi-turn context. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 126–136, Seattle, USA. Association for Computational Linguistics.

Mai Mostafa, Alia El Bolock, and Slim Abdennadher. 2021. Automatic detection and classification of cognitive distortions in journaling text. In *WEBIST*, pages 444–452.

J. A. Nelder and R. W. M. Wedderburn. 1972. Generalized linear models. *Journal of the Royal Statistical Society. Series A (General)*, 135(3):370–384.

Nawal Ouhmad, Romain Deperrois, Wissam El Hage, and Nicolas Combalbert. 2024. Cognitive distortions, anxiety, and depression in individuals suffering from ptsd. *International Journal of Mental Health*, 53(4):336–352.

Robin Quillivic, Yann Auxéméry, Frédérique Gayraud, Jacques Dayan, and Salma Mesmoudi. 2025. Linguistic markers for identifying post-traumatic stress disorder and associated symptoms: a systematic literature review. *Journal of the American Medical Informatics Association*, 32(8):1350–1363.

Lina Maria Rojas-Barahona, Bo-Hsiang Tseng, Yinpei Dai, Clare Mansfield, Osman Ramadan, Stefan Ultes, Michael Crawford, and Milica Gasic. 2018. Deep learning for language understanding of mental health concepts derived from cognitive behavioural therapy. *CoRR*, abs/1809.00640.

Stephanie Rude, Eva-Maria Gortner, and James Pennebaker. 2004. Language use of depressed and depression-vulnerable college students. *Cognition & Emotion - COGNITION EMOTION*, 18:1121–1133.

Archie Sage, Jeroen Keppens, and Helen Yannakoudakis. 2025. A survey of cognitive distortion detection and classification in NLP. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 14884–14899, Suzhou, China. Association for Computational Linguistics.

Neha Sharma, Navneet Agarwal, and Kairit Sirts. 2026. Towards consistent detection of cognitive distortions: Llm-based annotation and dataset-agnostic evaluation. In *Proceedings of the Fifteenth Language Resources and Evaluation Conference (LREC 2026)*, pages 10866–10882, Palma, Mallorca, Spain. European Language Resources Association (ELRA).

Benjamin Shickel, Scott Siegel, Martin Heesacker, Sherry Benton, and Parisa Rashidi. 2019. Automatic detection and classification of cognitive distortions in mental health text. *CoRR*, abs/1909.07502.

Sagarika Shreevastava and Peter Foltz. 2021. Detecting cognitive distortions from patient-therapist interactions. In *Proceedings of the Seventh Workshop on Computational Linguistics and Clinical Psychology: Improving Access*, pages 151–158, Online. Association for Computational Linguistics.

Taetem Simms, Clayton Ramstedt, Megan Rich, Michael Richards, Tony R. Martinez, and Christophe G. Giraud-Carrier. 2017. Detecting cognitive distortions through machine learning text analytics. *2017 IEEE International Conference on Healthcare Informatics (ICHI)*, pages 508–512.

Allison M Tackman, David A Sbarra, Angela L Carey, M Brent Donnellan, Andrea B Horn, Nicholas S Holtzman, To'Meisha S Edwards, James W Pennebaker, and Matthias R Mehl. 2019. Depression, negative emotionality, and self-referential language: A multi-lab, multi-measure, and multi-language-task research synthesis. *Journal of personality and social psychology*, 116(5):817.

Yla R Tausczik and James W Pennebaker. 2010. The psychological meaning of words: Liwc and computerized text analysis methods. *Journal of language and social psychology*, 29(1):24–54.

Joe H. Ward. 1963. Hierarchical grouping to optimize an objective function. *Journal of the American Statistical Association*, 58(301):236–244.

Katja Wiemer-Hastings, Adrian S Janit, Peter M Wiemer-Hastings, Steve Cromer, and Jennifer Kinser. 2004. Automatic classification of dysfunctional thoughts: a feasibility test. *Behavior Research Methods, Instruments, & Computers*, 36(2):203–212.

Andrew Yates, Arman Cohan, and Nazli Goharian. 2017. Depression and self-harm risk assessment in online forums. *CoRR*, abs/1709.01848.

Appendix

A Dataset

We use RSDD dataset (Yates et al., 2017) for two reasons. First, it is one of the most widely used datasets in mental health NLP, and was available to us under a data use agreement. Second, its post-level timestamps make it suitable for longitudinal study, where tracking distortion patterns over time is of future interest to us.

The RSDD dataset consists of Reddit posts from users assigned to a depression cohort, identified through high-precision diagnosis patterns (e.g., "I was diagnosed with depression") with crowd-sourced verification, and a matched control cohort. Controls were selected from users with no mental-health-related posts and matched to the diagnosed cohort based on subreddit-usage similarity. All mental-health-related posts were removed from the diagnosed cohort during dataset construction. We refer readers to Yates et al. (2017) for full details of cohort construction.

The raw training set contains ∼40K users and ∼38.15M posts, with strong class imbalance between cohorts. We applied the following cleaning steps:

1. removed posts with empty user labels or empty text,
2. detected language using fastText (Joulin et al., 2017) and retained English-only posts,
3. performed standard text cleaning including removal of URLs and non-linguistic characters,
4. discarded texts with fewer than 3 tokens, as shorter texts lack sufficient linguistic content for meaningful feature extraction and are more likely to represent noise than genuine linguistic expression.
5. To address user-level class imbalance, we randomly downsampled control users to match the size of the depression cohort.

Cleaned corpus contains ∼4.91M posts for 6,138 users. Full corpus statistics at each filtering stage are reported in §3.1, Table 1.

B CD Annotations

This appendix provides further details on the CD labeling pipeline introduced in §3.2.

Annotation Sources: Both Shreevastava and Foltz (2021) and Sharma et al. (2026) use the publicly available Therapist Q&A dataset[4]. The dataset consists of 2,530 user/therapist pairs, with CD annotations applied to the user inputs only. Two independent annotation sets exist for this data: (1) **human annotations** from Shreevastava and Foltz (2021), with a reported inter-annotator agreement of 33.7%, and (2) **LLM-based annotations** from Sharma et al. (2026), obtained via five repeated GPT-4 passes (temperature 0.5), selecting the most recurrent label across runs, achieving a Fleiss' kappa of 0.78. Both annotation sets follow the same label schema: one dominant CD and one secondary CD, where applicable (See Table 2 for CD classes).

Classifier Training: To transfer CD labels to the RSDD corpus, we train two separate multi-label mentalRoBERTa-based classifiers (Ji et al., 2022), one on each annotation set. We follow the same experimental setup as Sharma et al. (2026), using their data splits and default hyperparameters, and reproduce comparable classification performance on their test set (refer to original study for more details and classification results). Both classifiers are then retrained on the full Therapist Q&A dataset and applied to the RSDD corpus, producing two independent sets of predicted CD labels per post.

Agreement-Based Filtering: We adopt a conservative agreement-based filtering strategy: we retain labels where the two models agree completely (identical label sets) or partially (at least one shared CD label), and discard posts with entirely disjoint predictions. For example, if one classifier predicts *Labeling, Personalization* and the other predicts *Labeling, Overgeneralization*, the post is retained with the single shared label *Labeling*. The rationale mirrors the reliability principle underlying multi-pass LLM annotation (Sharma et al., 2026): labels that survive both independently trained models are more likely grounded in consistent textual signals rather than model-specific noise. Table 5 reports the distribution of the resulting CD labels used in this study, overall and by cohort. Since posts may carry multiple CD labels, percentages reflect post-based prevalence and do not necessarily sum to 100%.

[4] https://www.kaggle.com/datasets/arnmaud/therapist-qa/data

Cognitive Distortion	Overall	Control	Depression
Overgeneralization	7.02	5.94	7.54
Labeling	2.04	1.16	2.46
Personalization	1.78	1.17	2.07
All-or-Nothing	0.95	0.51	1.16
Should Statements	0.83	0.52	0.97
Emotional Reasoning	0.48	0.22	0.60
Mind Reading	0.44	0.30	0.50
Magnification	0.41	0.17	0.53
Fortune Telling	0.29	0.22	0.33
Mental Filter	0.00	0.00	0.00
No Distortion	87.21	90.69	85.55

Table 5: CD label distribution (%). Percentages do not sum to 100% as posts may contain multiple CD labels. Mental Filter is excluded from our analysis due to its negligible presence in the RSDD predictions.

C LIWC

LIWC-22 computes feature scores by counting the proportion of words in a text that match each predefined dictionary category, normalizing by total word count to produce comparable scores across texts of varying length (Boyd et al., 2022). From the full set of 120+ categories, we selected features relevant to cognitive distortion profiling across four dimensions: affective processes (e.g., emotional tone, positive and negative emotion, anxiety, anger, etc.), cognitive processes (e.g., analytical thinking, causation, insight, certainty, etc.), temporal orientation (past, present, and future focus), and social and interpersonal language (e.g., social references, affiliation, prosocial behavior, first person pronoun etc.). We excluded categories that were hierarchically redundant, where a broad category and its subcategories would introduce collinearity, as well as highly specific categories with limited relevance to our research questions. The full list of selected features with descriptions is provided in Table 6.

C.1 Descriptive Statistics of LIWC Features

Table 7 reports descriptive statistics for the LIWC features used in this study, computed over the final RSDD corpus (n $\approx$ 4.73M posts). For each feature, we report the mean, median, standard deviation, minimum, maximum, and the percentage of posts with a zero value (% Zero) and non-zero value (% Non-zero).

Several categories exhibit a high proportion of zero values, with the modal post containing no words from the corresponding LIWC dictionary. For example, *moral* (91.5% zero), *death* (95.7% zero), and *emo_anx* (96.7% zero) appear in fewer than 10% of posts each. We note that a zero value here is not a missing or invalid observation; it is a valid measurement indicating that the post simply does not contain any words from that category. Such sparsity is expected for content-specific LIWC categories, particularly in short informal text such as Reddit posts.

Given the corpus size, even sparse categories contain substantial absolute numbers of non-zero observations (e.g., *moral* appears in $\sim$404K posts, *emo_anx* in $\sim$154K), providing sufficient observations for stable coefficient estimation under bootstrap resampling. Effects involving such categories should be interpreted as reflecting differences in feature *prevalence* across CD and ND posts rather than continuous variation in usage intensity. In contrast, features with broader non-zero variation (e.g., *socrefs*, *i*, *focuspresent*, *auxverb*) support a continuous-gradient interpretation.

D Cognitive Distortion Linguistic Profiles (Core and Global Markers)

Table 8 shows the Core and Global markers for each CD, which constructs their Linguistic profiles. Core markers are the most CD-specific features, while global-like markers capture features that are relevant for the CD but align more closely with broader distorted-language patterns. Features within each cell are listed in descending order of profile strength, based on the median coefficient ($\tilde{\beta}$). The sign indicates the direction of the effect; when two signs are shown (e.g., $(-, +)$ or $(+, -)$), the first corresponds to the TASK(XCD/ND) and the second to the TASK(XCD/$\neg$XCDS).

E GLM Feature Effects for Tasks

Table 9 and Table 10 report the GLM feature effects used in the CD profiling and clustering analyses. The tables present the union of linguistic markers identified during the CD profiling stage. Specifically, the top 15 features from each CD were combined, resulting in a set of 44 unique features. For each feature, the tables report the median coefficient ($\tilde{\beta}$) obtained from the GLM models along with the corresponding Relative Standard Error (RSE) stability indicators. Results are shown separately for TASK(XCD/ND) in Table 9 and TASK(XCD/$\neg$XCDS) in Table 10.

Category	Description	Category	Description
Summary Variables		**Social Processes**	
Word count	Total word count	Prosocial behavior	care, help, thank, please
Analytical thinking	Metric of logical, formal thinking	Politeness	thank, please, thanks, good morning
Clout	Language of leadership, status	Interpersonal conflict	fight, kill, killed, attack
Authentic	Perceived honesty, genuineness	Moralization	wrong, honor*, deserv*, judge
Emotional tone	Degree of positive (negative) tone	Social referents	you, we, he, she
Linguistic Dimensions		**Expanded Dictionary**	
1st person singular	I, me, my, myself	Illness	hospital*, cancer*, sick, pain
1st person plural	we, our, us, lets	Wellness	healthy, gym*, supported, diet
2nd person	you, your, u, yourself	Mental health	mental health, depressed, suicid*
3rd person plural	they, their, them, themsel*	Death	death*, dead, die, kill
Auxiliary verbs	is, was, be, have	**States**	
Adverbs	so, just, about, there	Need	have to, need, had to, must
Conjunctions	and, but, so, as	Want	want, hope, wanted, wish
Negations	not, no, never, nothing	Acquire	get, got, take, getting
		Lack	don't have, didn't have, *less, hungry
		Fulfilled	enough, full, complete, extra
		Fatigue	tired, bored, don't care, boring
Psychological Processes		**Motives**	
Affiliation	we, our, us, help	Reward	opportun*, win, gain*, benefit*
Achievement	work, better, best, working	Risk	secur*, protect*, pain, risk*
Power	own, order, allow, power	Curiosity	scien*, look* for, research*, wonder
All-or-none	all, no, never, always	Allure	have, like, out, know
Insight	know, how, think, feel	**Perception**	
Causation	how, because, make, why	Attention	look, look* for, watch, check
Discrepancy	would, can, want, could	Feeling	feel, hard, cool, felt
Tentative	if, or, any, something	**Time Orientation**	
Certitude	really, actually, of course, real	Past focus	was, had, were, been
Differentiation	but, not, if, or	Present focus	is, are, I'm, can
Positive emotion	good, love, happy, hope	Future focus	will, going to, have to, may
Negative emotion	bad, hate, hurt, tired		
Anxiety	worry, fear, afraid, nervous		
Anger	hate, mad, angry, frustr*		
Sadness	:(, sad, disappoint*, cry		
Swear words	shit, fuckin*, fuck, damn		

Table 6: Selected LIWC-22 features used in this study. Example words illustrate dictionary entries; * denotes wildcard matching.

Feature	Mean	Median	SD	Min	Max	% Zero	% Non-zero
WC	41.03	23.00	61.58	3.0	5934.00	0.00	100.00
Analytic	38.30	30.52	32.92	1.0	99.00	0.00	99.12
Clout	39.33	25.50	37.98	1.0	99.00	0.00	91.70
Authentic	55.45	63.35	37.00	1.0	99.00	0.00	93.05
Tone	59.75	74.09	39.20	1.0	99.00	0.00	69.30
i	5.09	3.45	5.91	0.0	75.00	38.24	61.76
we	0.43	0.00	1.85	0.0	66.67	89.53	10.47
you	2.59	0.00	4.86	0.0	75.00	61.84	38.16
they	0.91	0.00	2.53	0.0	66.67	78.46	21.54
auxverb	10.22	10.00	7.02	0.0	100.00	14.52	85.48
adverb	6.68	5.88	6.55	0.0	100.00	26.37	73.63
conj	6.00	5.95	5.32	0.0	100.00	29.09	70.91
negate	2.07	0.00	3.76	0.0	80.00	56.89	43.11
affiliation	1.32	0.00	3.42	0.0	100.00	73.75	26.25
achieve	1.07	0.00	2.74	0.0	100.00	73.15	26.85
power	0.95	0.00	2.69	0.0	100.00	77.26	22.74
allnone	1.36	0.00	3.37	0.0	100.00	69.81	30.19
insight	2.57	0.00	4.21	0.0	100.00	53.34	46.66
cause	1.58	0.00	3.15	0.0	100.00	63.82	36.18
discrep	2.12	0.00	3.70	0.0	75.00	57.08	42.92
tentat	3.05	0.96	4.56	0.0	100.00	49.36	50.64
certitude	0.99	0.00	2.96	0.0	100.00	76.69	23.31
differ	3.96	2.99	4.83	0.0	100.00	40.92	59.08
emo_pos	1.79	0.00	4.79	0.0	100.00	71.60	28.40
emo_neg	0.58	0.00	2.20	0.0	100.00	84.70	15.30
emo_anx	0.10	0.00	0.91	0.0	75.00	96.74	3.26
emo_anger	0.13	0.00	0.98	0.0	100.00	95.74	4.26
emo_sad	0.10	0.00	0.94	0.0	66.67	97.21	2.79
swear	0.53	0.00	2.57	0.0	100.00	90.24	9.76
prosocial	0.98	0.00	3.55	0.0	100.00	81.83	18.17
polite	0.69	0.00	3.34	0.0	100.00	90.24	9.76
conflict	0.29	0.00	1.49	0.0	100.00	91.53	8.47
moral	0.29	0.00	1.54	0.0	100.00	91.45	8.55
socrefs	7.24	5.88	7.55	0.0	100.00	29.30	70.70
illness	0.10	0.00	0.92	0.0	66.67	97.17	2.83
wellness	0.05	0.00	0.62	0.0	100.00	98.33	1.67
mental	0.04	0.00	0.55	0.0	66.67	98.92	1.08
death	0.16	0.00	1.15	0.0	66.67	95.70	4.30
need	0.42	0.00	1.80	0.0	75.00	88.80	11.20
want	0.38	0.00	1.64	0.0	66.67	88.49	11.51
acquire	0.96	0.00	2.43	0.0	66.67	74.02	25.98
lack	0.14	0.00	1.16	0.0	80.00	96.27	3.73
fulfill	0.16	0.00	1.01	0.0	66.67	93.81	6.19
fatigue	0.04	0.00	0.61	0.0	100.00	98.70	1.30
reward	0.13	0.00	0.96	0.0	66.67	95.53	4.47
risk	0.24	0.00	1.30	0.0	66.67	91.88	8.12
curiosity	0.37	0.00	1.85	0.0	100.00	90.56	9.44
allure	7.71	6.67	7.28	0.0	100.00	23.38	76.62
attention	0.54	0.00	2.13	0.0	100.00	86.28	13.72
feeling	0.46	0.00	1.90	0.0	100.00	86.82	13.18
focuspast	3.73	0.76	5.47	0.0	100.00	49.52	50.48
focuspresent	6.31	5.45	6.28	0.0	80.00	27.84	72.16
focusfuture	1.36	0.00	3.40	0.0	100.00	72.22	27.78

Table 7: Descriptive statistics of LIWC features on the final RSDD corpus (n $\approx$ 4.73M posts). Values are computed on raw LIWC-22 output, where each score represents the percentage of words in a post matching the corresponding dictionary category, except for summary variables (WC, Analytic, Clout, Authentic, Tone) which follow LIWC's own scaling. % Zero indicates the percentage of posts with a value of zero for the corresponding feature; % Non-zero is its complement. SD = Standard Deviation, Min= Minimum, Max = Maximum

CD	Core markers	Global markers
AoN	emo_anger(+), socrefs(-), focuspast(-), Authentic(+), fatigue(+), differ(-), you(+), death(+), wellness(+), allure(+), swear(+), Analytic(-), emo_anx(-), achieve(+), want(+), tentat(-), emo_pos(-,+), need(+), focuspresent(+)	i(+), mental(+), insight(-), Tone(-), moral(+,-), allnone(+), emo_neg(+), they(-), polite(-), cause(-), conflict(-), risk(-), WC(+), negate(+), focusfuture(-)
ER	emo_anx(+), socrefs(-), i(+), discrep(+), Authentic(+), feeling(+), you(+), death(+), emo_pos(-), focusfuture(+), want(+), swear(+,-), mental(+), differ(-), polite(-), focuspresent(+), Tone(-), illness(+), allure(+), focuspast(-), need(+), auxverb(-), risk(+), emo_neg(+,-), negate(+,-), power(+), adverb(-)	moral(-), affiliation(+), WC(+), cause(+), allnone(+,-), Analytic(-), conflict(-), achieve(+), wellness(-)
FT	emo_anx(+), focusfuture(+), swear(+,-), death(+), need(-), focuspast(-), emo_pos(-), risk(+), tentat(+), Tone(-), differ(-), adverb(-), allnone(+,-), you(-), Analytic(-), focuspresent(-), Authentic(+), discrep(+), Clout(-), auxverb(+), want(-), conflict(-), insight(+,-)	moral(-), emo_neg(-), negate(-), polite(-), socrefs(-), affiliation(+), WC(+), feeling(+), achieve(+,-), cause(+), power(+), i(-), prosocial(-), emo_anger(-), fatigue(-), wellness(-)
La	swear(+), moral(+), i(+), you(+), Tone(-), allnone(+,-), mental(+), Authentic(-), emo_neg(+,-), focuspast(-), negate(+,-), discrep(-), they(-), focusfuture(-), risk(-), death(-), adverb(-), feeling(-), affiliation(-), emo_sad(-), socrefs(+)	Analytic(+), emo_anger(+), emo_anx(-), achieve(+,-), focuspresent(+), emo_pos(-,+), conflict(-), insight(+), WC(+), prosocial(-), allure(-)
Mag	death(+), socrefs(-), emo_anx(+), Tone(-), illness(+), negate(-), Authentic(+), mental(+), focusfuture(+), discrep(+), differ(-), focuspast(-), insight(-), you(+), swear(+,-), adverb(-), conflict(-), allnone(+,-), auxverb(-), feeling(+), risk(+), Analytic(-), WC(+), emo_neg(+,-)	moral(-), i(+), achieve(-), emo_pos(-), focuspresent(+), cause(+), power(+), polite(-), emo_anger(-), prosocial(-), want(-), fatigue(-), Clout(+), allure(-)
Over	swear(+,-), emo_anx(-), moral(+,-), i(-), allnone(+), you(-), Tone(-,+), negate(+), focuspast(-,+), feeling(-), affiliation(-,+), conflict(-,+)	focuspresent(-), differ(-), wellness(+), achieve(+), discrep(-), socrefs(+), emo_neg(+), insight(+), WC(+,-), power(+), Analytic(-), emo_pos(-), polite(-), focusfuture(-), Authentic(+), death(-), want(-), mental(-), adverb(+), they(+)
Per	moral(+), i(+), emo_neg(+), Tone(-), WC(+), emo_anx(-), allnone(+,-), Authentic(-), cause(+), prosocial(+), emo_sad(-), death(-), feeling(+), you(+), illness(-), achieve(+,-), socrefs(+), polite(-,+)	focuspast(+), focuspresent(+), negate(+,-), risk(-), affiliation(-,+), Analytic(-), discrep(-), emo_pos(-), insight(+), power(+), swear(+), focusfuture(-), emo_anger(-), differ(+), need(+), fatigue(-), auxverb(-), they(+), wellness(-)
SS	i(+), auxverb(+), WC(+), Tone(-,+), need(+), focuspast(-), focuspresent(-), discrep(+), prosocial(+), socrefs(+), allure(+), death(-), focusfuture(-), moral(+), affiliation(-), swear(+,-), allnone(+,-), emo_neg(+,-), risk(-), tentat(-), feeling(+), want(+), they(-), negate(+,-), differ(+), illness(-)	achieve(+), conflict(+), power(+), polite(-), Analytic(-), insight(+), emo_pos(-), cause(+), mental(-), adverb(-)
MR	socrefs(+), insight(+), swear(+,-), you(-), Authentic(-), focusfuture(+), i(+), tentat(+), affiliation(-), Analytic(-), emo_anx(+), moral(+,-), emo_anger(+), fatigue(+), focuspresent(+), death(-), emo_pos(-), Clout(-), want(+), need(-), discrep(-), auxverb(-), they(+), negate(+,-)	allnone(-), emo_neg(-), polite(-), prosocial(+), achieve(-), conflict(+), power(-), WC(+,-), illness(-), focuspast(-,+), Tone(-), allure(-)

Table 8: Linguistic profiles of the nine CD types. Core markers are the most CD-specific features, while Global markers capture features that are relevant for the CD but align more closely with broader distorted-language patterns or weaker CD-specific effects. Features within each cell are ordered by descending profile strength. The sign indicates the direction of the effect; when two signs are shown, the first corresponds to the TASK(XCD/ND) and the second to the TASK(XCD/¬XCDS).

Feature	AoN		ER		FT		La		Mag		MR		Over		Per		SS	
	$\tilde{\beta}$	RSE	$\tilde{\beta}$	RSE	$\tilde{\beta}$	RSE	$\tilde{\beta}$	RSE	$\tilde{\beta}$	RSE	$\tilde{\beta}$	RSE	$\tilde{\beta}$	RSE	$\tilde{\beta}$	RSE	$\tilde{\beta}$	RSE
Tone	−0.73	● ● ●	−0.81	● ● ●	−0.86	● ● ●	−0.83	● ● ●	−1.17	● ● ●	−0.53	● ● ●	−0.50	● ● ●	−0.96	● ● ●	−0.26	●●
socrefs	−0.42	●●	−0.50	●●	—	—	+0.32	●●	−0.64	●●	+1.32	● ● ●	+0.22	●	+0.32	●●	+0.46	●●
emo_anx	−0.15	●	+1.10	●●	+1.76	● ● ●	−0.10	●	+0.68	●●	+0.26	●	−0.19	●●	−0.26	●●	—	—
i	+0.16	●	+0.73	● ● ●	—	—	+0.39	●●	+0.28	●●	+0.39	●●	−0.15	●	+0.46	●●	+0.52	● ● ●
Authentic	+0.24	●●	+0.42	● ● ●	+0.20	●●	−0.19	●●	+0.40	●●	−0.39	●●	—	—	−0.22	●●	—	—
moral	+0.32	●●	—	—	—	—	+0.96	●●	—	—	+0.18	●●	+0.28	●●	+1.09	● ● ●	+0.63	● ● ●
focuspast	−0.47	●●	−0.34	●●	−0.50	● ● ●	−0.36	●●	−0.43	● ● ●	−0.09	●	−0.09	●	—	—	−0.51	● ● ●
swear	+0.82	● ● ●	+0.35	●●	+0.11	●	+1.77	● ● ●	+0.43	●●	+0.13	●	+0.43	●●	+0.65	● ● ●	+0.47	● ● ●
you	+0.22	●	+0.38	●●	−0.22	●●	+0.26	●●	+0.23	●●	−0.42	●●	−0.13	●	+0.14	●	—	—
emo_neg	+0.44	●●	+0.21	●	—	—	+0.15	●	+0.30	●	—	—	+0.32	●●	+0.72	●●	+0.20	●
WC	+0.42	●●	+0.28	●●	+0.55	●●	+0.43	●●	+0.47	●●	+0.33	●●	+0.43	●●	+0.70	●●	+0.80	● ● ●
death	+0.21	●●	+0.36	●●	+0.39	●●	−0.11	●	+1.12	● ● ●	−0.18	●●	—	—	−0.16	●	−0.19	●●
allnone	+0.52	● ● ●	+0.29	●●	+0.18	●●	+0.20	●●	+0.23	●●	—	—	+0.55	● ● ●	+0.17	●●	+0.25	●●
focusfuture	—	—	+0.33	●●	+1.52	● ● ●	−0.14	●	+0.34	●●	+0.39	● ● ●	—	—	—	—	−0.19	●●
focuspresent	+0.19	●	+0.33	●●	−0.10	●	+0.17	●●	+0.17	●●	+0.29	●●	—	—	+0.25	●●	−0.18	●●
Analytic	−0.31	●●	−0.25	●●	−0.38	●●	—	—	−0.24	●●	−0.43	●●	−0.16	●	−0.19	●	−0.10	●
polite	−0.27	●	−0.42	●●	−0.47	●	—	—	−0.18	●	−0.45	●●	−0.18	●	−0.11	●	−0.25	●
negate	+0.29	●●	+0.17	●	—	—	+0.11	●	−0.16	●	+0.23	●●	+0.39	●●	+0.16	●	+0.19	●●
discrep	—	—	+0.36	●●	+0.11	●	−0.24	●●	+0.24	●●	−0.22	●●	−0.11	●	−0.11	●	+0.18	●●
affiliation	—	—	—	—	—	—	−0.25	●●	—	—	−0.46	●●	−0.11	●	−0.12	●	−0.34	●●
emo_pos	−0.08	●	−0.53	●●	−0.47	●●	−0.12	●	−0.26	●●	−0.35	●●	−0.18	●●	−0.15	●	−0.21	●●
insight	—	—	—	—	+0.08	●	+0.16	●●	−0.09	●	+0.96	● ● ●	+0.14	●●	+0.13	●	+0.19	●●
differ	−0.22	●●	−0.26	●●	−0.25	●●	—	—	−0.26	●●	—	—	−0.08	●	—	—	+0.09	●
feeling	—	—	+0.42	●●	+0.09	●	−0.09	●	+0.10	●	—	—	−0.07	●	+0.15	●	+0.12	●●
achieve	+0.31	●●	+0.18	●●	+0.10	●	+0.08	●	—	—	—	—	+0.21	●●	+0.08	●	+0.31	●●
need	+0.09	●	+0.16	●●	−0.38	●●	—	—	—	—	−0.14	●●	—	—	—	—	+0.33	●●
tentat	−0.10	●	—	—	+0.25	●●	—	—	—	—	+0.37	●●	—	—	—	—	−0.12	●
prosocial	—	—	—	—	—	—	—	—	—	—	+0.20	●	—	—	+0.20	●●	+0.24	●●
mental	+0.16	●	+0.27	●	—	—	+0.20	●	+0.37	●●	—	—	—	—	—	—	—	—
emo_anger	+0.70	●●	—	—	—	—	+0.13	●	—	—	+0.20	●	—	—	—	—	—	—
illness	—	—	+0.18	●●	—	—	—	—	+0.55	●●	−0.09	●	—	—	−0.12	●	−0.08	●
auxverb	—	—	−0.14	●	+0.14	●	—	—	−0.15	●	−0.11	●	—	—	—	—	+0.50	● ● ●
risk	−0.07	●	+0.12	●	+0.27	●●	−0.12	●	+0.09	●	—	—	—	—	−0.09	●	−0.13	●●
fatigue	+0.28	●	—	—	—	—	—	—	—	—	+0.19	●	—	—	—	—	—	—
conflict	−0.20	●	−0.15	●	−0.22	●●	−0.17	●	−0.31	●●	—	—	−0.11	●	—	—	—	—
want	+0.11	●	+0.31	●●	−0.10	●	—	—	—	—	+0.15	●	—	—	—	—	+0.12	●
cause	—	—	+0.20	●●	+0.11	●	—	—	+0.11	●●	—	—	—	—	+0.29	●●	+0.11	●●
adverb	—	—	−0.09	●	−0.25	●●	−0.10	●	−0.19	●●	—	—	—	—	—	—	—	—
Clout	—	—	—	—	−0.15	●	—	—	—	—	−0.17	●	—	—	—	—	—	—
power	—	—	+0.23	●●	+0.12	●	—	—	+0.09	●	—	—	+0.12	●	+0.10	●	+0.23	●●
they	−0.09	●	—	—	—	—	−0.15	●●	—	—	+0.09	●	—	—	—	—	−0.10	●
allure	+0.18	●●	+0.17	●●	—	—	—	—	—	—	—	—	—	—	—	—	+0.20	●●
emo_sad	—	—	—	—	—	—	−0.09	●	—	—	—	—	—	—	−0.16	●	—	—
wellness	+0.20	●	—	—	—	—	—	—	—	—	—	—	+0.07	●	—	—	—	—

Table 9: $\tilde{\beta}$ coefficients and Relative Standard Error (RSE) stability per feature and CD for TASK(XCD/ND). '—' indicates non-significant result. $\widetilde{\text{OR}}$ can be calculated as $\exp(\tilde{\beta})$. %Δ Odds can be computed as $(\widetilde{\text{OR}} - 1) \times 100$. RSE encode stability categories: ● ● ● = extremely stable (RSE ≤ 0.10), ●● = stable (0.10–0.25], ● = moderately stable (0.25–0.50].

Feature	AoN $\tilde{\beta}$	AoN RSE	ER $\tilde{\beta}$	ER RSE	FT $\tilde{\beta}$	FT RSE	La $\tilde{\beta}$	La RSE	Mag $\tilde{\beta}$	Mag RSE	MR $\tilde{\beta}$	MR RSE	Over $\tilde{\beta}$	Over RSE	Per $\tilde{\beta}$	Per RSE	SS $\tilde{\beta}$	SS RSE
Tone	−0.09	●	−0.14	●●	−0.31	●●	−0.26	●●	−0.40	●●●	—	—	+0.24	●●	−0.38	●●●	+0.31	●●
socrefs	−0.70	●●●	−0.85	●●●	−0.17	●	+0.19	●	−0.95	●●●	+1.21	●●●	—	—	+0.11	●	+0.22	●●
emo_anx	−0.17	●●	+1.21	●●●	+1.56	●●●	—	—	+0.80	●●	+0.38	●●	−0.46	●●	−0.31	●●	—	—
i	—	—	+0.46	●●	−0.24	●●	+0.29	●●	—	—	+0.29	●●	−0.59	●●●	+0.31	●●	+0.36	●●
Authentic	+0.26	●●	+0.37	●●	+0.21	●●	−0.21	●●	+0.42	●●●	−0.44	●●	+0.15	●	−0.23	●●	—	—
moral	−0.07	●	−0.60	●●	−0.52	●●	+0.32	●●	−0.49	●●	−0.32	●●	−0.22	●●	+0.35	●●	+0.07	●
focuspast	−0.28	●●	−0.16	●●	−0.31	●●	−0.20	●●	−0.24	●●	+0.10	●	+0.22	●●	+0.14	●●	−0.38	●●●
swear	+0.10	●	−0.14	●●	−0.56	●●	+0.74	●●●	−0.13	●●	−0.54	●●●	−0.31	●●	—	—	−0.07	●
you	+0.24	●●	+0.49	●●	−0.15	●	+0.30	●●	+0.27	●●	−0.36	●●	−0.28	●●	+0.15	●	—	—
emo_neg	—	—	−0.23	●	−0.54	●●	−0.18	●●	−0.13	●	−0.42	●●	—	—	+0.33	●●	−0.15	●
WC	—	—	—	—	+0.09	●●	—	—	+0.15	●●	−0.10	●	−0.09	●	+0.20	●●	+0.19	●●
death	+0.15	●●	+0.21	●●	+0.26	●●	−0.08	●	+1.17	●●●	−0.21	●●	−0.14	●	−0.14	●●	−0.21	●●
allnone	+0.07	●	−0.10	●	−0.25	●●	−0.13	●●	−0.15	●●	−0.37	●●	+0.24	●●	−0.17	●●	−0.13	●●
focusfuture	−0.06	●	+0.33	●●	+1.72	●●●	−0.19	●●	+0.30	●●	+0.39	●●●	−0.08	●	−0.09	●	−0.21	●●
focuspresent	+0.11	●	+0.21	●●	−0.29	●●	+0.08	●	—	—	+0.15	●	−0.12	●	+0.10	●	−0.34	●●●
Analytic	−0.19	●●	−0.09	●	−0.21	●●	+0.13	●	−0.12	●	−0.28	●●	—	—	—	—	—	—
polite	—	—	−0.08	●	—	—	—	—	—	—	—	—	—	—	+0.12	●	—	—
negate	—	—	−0.11	●	−0.40	●●	−0.15	●	−0.44	●●	−0.18	●●	+0.23	●●	−0.08	●	−0.10	●
discrep	—	—	+0.46	●●●	+0.23	●●	−0.19	●●	+0.33	●●	−0.15	●●	—	—	—	—	+0.33	●●
affiliation	—	—	+0.09	●	+0.23	●●	−0.14	●	—	—	−0.21	●●	+0.11	●	+0.07	●	−0.19	●●
emo_pos	+0.10	●	−0.19	●●	−0.11	●	+0.08	●	—	—	−0.08	●	−0.07	●	—	—	—	—
insight	−0.20	●●	—	—	−0.12	●	—	—	−0.25	●●	+0.84	●●●	—	—	—	—	—	—
differ	−0.18	●●	−0.21	●●	−0.23	●●	—	—	−0.25	●●	—	—	—	—	+0.11	●	+0.12	●●
feeling	—	—	+0.43	●●	—	—	−0.10	●	+0.09	●	—	—	−0.18	●●	+0.21	●●	+0.11	●
achieve	+0.13	●●	—	—	−0.08	●	−0.08	●	−0.21	●●	−0.15	●●	+0.09	●	−0.12	●●	+0.08	●
need	+0.05	●	+0.12	●	−0.41	●●	—	—	—	—	−0.18	●●	—	—	+0.05	●	+0.29	●●
tentat	−0.10	●●	—	—	+0.26	●●	—	—	—	—	+0.41	●●●	—	—	—	—	−0.10	●
prosocial	—	—	—	—	−0.08	●	−0.09	●	−0.12	●	—	—	—	—	+0.16	●●	+0.14	●
mental	—	—	+0.16	●	—	—	+0.11	●	+0.21	●	—	—	−0.10	●	—	—	−0.14	●
emo_anger	+0.50	●●	—	—	−0.17	●	—	—	−0.09	●	+0.16	●	—	—	−0.20	●●	—	—
illness	—	—	+0.15	●	—	—	—	—	+0.57	●●	—	—	—	—	−0.15	●●	−0.09	●
auxverb	—	—	−0.17	●●	+0.16	●	—	—	−0.26	●●	−0.14	●	—	—	−0.13	●	+0.46	●●●
risk	—	—	+0.19	●●	+0.31	●●	−0.07	●	+0.16	●●	—	—	—	—	—	—	−0.09	●
fatigue	+0.19	●	—	—	−0.12	●	—	—	−0.13	●	+0.12	●	—	—	−0.18	●	—	—
conflict	−0.08	●	—	—	−0.11	●	—	—	−0.13	●	+0.10	●	+0.10	●	—	—	+0.06	●
want	+0.08	●	+0.23	●●	−0.16	●	—	—	−0.13	●	+0.15	●	−0.11	●	—	—	+0.08	●
cause	−0.07	●	+0.08	●	—	—	—	—	—	—	—	—	—	—	+0.23	●●	—	—
adverb	—	—	−0.07	●	−0.25	●●	−0.10	●	−0.17	●●	—	—	+0.09	●	—	—	−0.06	●
Clout	—	—	—	—	−0.15	●	—	—	+0.13	●	−0.29	●●	—	—	—	—	—	—
power	—	—	+0.11	●	—	—	—	—	—	—	−0.21	●●	—	—	—	—	+0.09	●
they	—	—	—	—	—	—	−0.18	●●	—	—	+0.07	●	+0.10	●	+0.07	●	−0.10	●
allure	+0.16	●●	+0.06	●	—	—	−0.11	●	−0.09	●	−0.09	●	—	—	—	—	+0.13	●●
emo_sad	—	—	—	—	—	—	−0.10	●	—	—	—	—	—	—	−0.11	●	—	—
wellness	+0.14	●	−0.09	●	−0.07	●	—	—	—	—	—	—	—	—	−0.08	●	—	—

Table 10: $\tilde{\beta}$ coefficients and Relative Standard Error (RSE) stability per feature and CD forTASK(XCD/¬XCDS). '—' indicates non-significant result. $\widetilde{\mathrm{OR}}$ can be calculated as $\exp(\tilde{\beta})$. %Δ Odds can be computed as $(\widetilde{\mathrm{OR}}-1)\times 100$. RSE encode stability categories: ●●● = extremely stable (RSE $\leq$ 0.10), ●● = stable (0.10–0.25], ● = moderately stable (0.25–0.50].

The Attachment Index: Auditing Attachment Language Cues and Relational Safety Risks in Human-LLM Dialogue

Cyndie Demeocq[1] **Animesh Prasad**[2] **Marzieh Saeidi**[3] **Karen Goodall**[4] **Björn Ross**[1]
[1] School of Informatics, University of Edinburgh
[2] Indian Institute of Technology Patna
[3] Independent Researcher
[4] Clinical and Health Psychology, University of Edinburgh
c.demeocq@sms.ed.ac.uk, animesh@iitp.ac.in, marzieh.saeidi@gmail.com
{karen.goodall, b.ross}@ed.ac.uk

Abstract

As conversational AI systems grow increasingly toward emotional support contexts, relational safety failures between users and chatbot remain under-measured. We present a psycholinguistic grounded framework for auditing attachment-relevant language cues. Our approach identifies when an LLM's replies exhibit linguistic attachment cues and surface related patterns that may signal parasocial bonding, including anthropomorphism or over-dependence. We adapt the Adult Attachment Interview into two complementary, automatable lenses – attachment cue features and Gricean maxims – and combine them with psychologist-led annotation of multi-turn persona dialogues. Applying this framework, we observe that models can align with persona-intended attachment cue patterns. We also find that judge-LLMs alone are unreliable, highlighting the need for psychologist-in-the-loop evaluation. The 25 psychologist-led annotated conversations revealed risks, including boundary blurring and missed opportunities for appropriate referral or triage. These insights motivate attachment-aware safeguards – such as non-personification, boundary language, and explicit referral mechanisms – to reduce mis-attunement and over-attachment in LLM conversational settings.

1 Introduction

Recently, Large Language Models (LLMs) have transcended their initial role as tools for retrieving information and completing tasks, becoming companions for casual conversation and emotional support. Research among young people suggests that the trend is particularly prevalent among them, mainly due to advanced language capability with a perceived non-judgmental nature and constant availability (Maples et al., 2024). However, Burleson (2003) found that poor quality emotional support can amplify negative feelings and contribute to mental and social harm.

Existing work, such as Pentina et al. (2023), has already demonstrated that users can develop emotional and even romantic bonds with LLMs, highlighting potential addiction and other risks related to trust and safety measures. To deepen our understanding of how LLMs influence and potentially trigger users' emotional bonds, this study examines LLM outputs and their display of specific emotional signs of attachment. This approach is guided by psychological research, such as Mikulincer and Shaver (2016) and Candel and Turliuc (2019), which illustrate the role and impact of attachment styles in shaping relationship dynamics and emotional experiences. While significant efforts have been made to align these models and address associated risks, attachment remains a crucial yet often overlooked dimension of characterization.

Our study aims to provide the following contributions:

- A psychologist-led annotation protocol for identifying attachment cues in multi-turn LLM dialogues.
- A two-lens evaluation framework combining attachment features and Gricean maxims.
- Evidence of linguistic cue-level alignment to persona and priming; distributions shift by model/condition.

2 Related Work

Attachment theory (Bowlby, 1969; Ainsworth et al., 1978) describes how early caregiving experiences shape internal emotional working models of self and others, and how these models organise emotion regulation, intimacy, and help-seeking across the lifespan. Insecure types of attachment are consistently associated with elevated risk for depression, anxiety, loneliness, and difficulties both using and providing emotional support (Mikulincer and Shaver, 2016; Candel and Turliuc, 2019). These

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 324–339
July 4, 2026 ©2026 Association for Computational Linguistics

links matter in the context of conversational AI, because they become especially salient as users have been reported to turn to LLMs for companionship or comfort (Maples et al., 2024).

Operationally, attachment has been captured through two main measurement methods; The categorical method, rooted in the Strange Situation Ainsworth et al. (1978) and later the Adult Attachment Interview (AAI) (George et al., 1985), places individuals into one of four patterns: secure, dismissive-avoidant, fearful/disorganised, and anxious-preoccupied (Main and Goldwyn, 1998; Hesse, 1999). The dimensional method, which is more prominent in social-personality psychology—models attachment as continuous variation along the two axes of anxious and avoidance attachment (Brennan et al., 1998; Fraley and Spieker, 2003). Factor-analytic and taxometric reviews across infant, adult, and self-report measures consistently support the dimensional account as the most parsimonious latent structure (Raby et al., 2021). In this study, we used the categorical model of attachment styles, as these have more applied utility and while we adopt four-way coding in this initial framework, our findings seem to converge more closely with this dimensional literature and motivate the two-axis extension we propose in Section 6.

Attachment theory has been studied in computational settings, typically as conversational signals to infer attachment-related patterns. Koçak et al. (2023) applied it to automatically detect attachment styles in married couples, demonstrating its relevance for analyzing emotional bonds in online conversations. Additionally, Soares et al. (2024) showed that LLMs could synthesize data for attachment-focused training models, positioning them as tools for attachment research. In addition, psycholinguistic tools such as LIWC show that relational stance and affect correlate with lexical patterns (Tausczik and Pennebaker, 2010), supporting cue-based approaches, which we also adopt as identifiers for detecting attachment signals.

Using synthetic personas to better understand how LLMs affect users emotionally, work such as Chen et al. (2024) demonstrated that those artificial personas can range from simple demographic profiles to highly individualized representations derived from web chat histories. Complementing this perspective, a recent survey distinguishes role-playing (model-assigned profiles) from personalization (user-derived profiles), clarifying how priming versus user context differentially steers dialogue dynamics (Tseng et al., 2024). It was observed that design interventions that let people customize agent personas tend to deepen engagement and perceived attunement, such as, in controlled studies, participants reported stronger bonds and richer interactions with persona-aligned agents and frameworks like CloChat (Ha et al., 2024) and Persona-L (Sun et al., 2025) use LLMs to model distinct interaction styles. A related approach is also useful for safety evaluation: structured persona scenarios can systematize stress-testing and surface failure modes, as shown by automated red-teaming pipelines that probe models across diverse roles and goals. Systems such as SAGE-RT (Baswa et al., 2024) and AART (Radharapu et al., 2023) use structured personas for adversarial testing, ensuring robustness across diverse simulated interactions. Wu et al. (2025) expanded on these strategies to explore the effects of ESCs. Their research, using datasets such as ESConv (Liu et al., 2021), CAMS (Garg et al., 2022), and Dreaddit (Turcan and McKeown, 2019), showed that LLMs can infer persona traits and that subtle emotional shifts influence dialogue dynamics. Moreover, incorporating persona traits enhances response relevance to empathy and can be constructed using various strategies: Demographic and cultural personas adjust attributes such as gender, nationality, and socioeconomic status to reflect diverse perspectives, as seen in Persona Hub (Ge et al., 2024).

Finally, beyond persona design, the safety literature highlights relational risks (Zhang et al., 2025), providing a granular taxonomy of harms using 35k real interactions with an AI companion. More specifically, they identify "six categories of harmful algorithmic behaviors: relational transgression, harassment, verbal abuse, self-harm, mis/disinformation, and privacy violations" and show these are instantiated through "four distinct roles that AI plays: perpetrator, instigator, facilitator, and enabler". Crucially, they argue that "relational harm [is] a critical yet understudied type of AI harm" amplified by anthropomorphic design and long-term memory (Zhang et al., 2025).

To our knowledge, while previous work approached attachment-related frameworks, it has not been operationalized to characterize different LLM-side behaviors, including potentially problematic ones, in human–LLM dialogue with the

contribution of psychologists.

3 Methodology

3.1 Attachment Style and AAI Framework

Following the consensus established by Main and Goldwyn (1998); Hesse (1999); George et al. (1985), we categorize attachment styles into four main types: *Secure*, *Dismissive Avoidant*, *Fearful/Disorganized*, and *Anxious Preoccupied*. Additionally, we introduce a fifth category, *Unclassified*, to allow automatic classification without forcing responses into one of the predefined attachment types.

To assess the linguistics cues related to the attachment styles in the discussions with LLMs, we use the **Adult Attachment Interview (AAI)** (see Appendix F, Table 11), a semi-structured interview introduced by George et al. (1985) which evaluates an individual's attachment style by exploring early caregiver relationships and how those experiences shape current emotions, thoughts, and behaviors in relationships.

3.2 AAI adaptation for LLMs

Although the AAI was designed for human autobiographical narratives we use it as an elicitation tool, rather than a means of categorising attachment styles. As it was built to surface attachment-relevant patterns in human narratives about early caregivers, we keep the question set essentially unchanged. However, we changed how we treated the answers, as we did not interpret the LLM's reponses as autobiographical information. Instead, we treat them as a controlled language sample in response to attachment-theory-relevant prompts, and we look for the same surface cues the AAI tradition relies on, giving us an experimental prompt set and a clinically grounded cue inventory. Figure 2 illustrates how we use the AAI to prompt LLMs. Leveraging LLMs' training and in-context capabilities, we break this down into the two following settings:

Intrinsic Attachment Behavior (IAB): This setting explore baseline attachment-relevant cue patterns a model produces without any extra priming or persona steering, which can arise from the statistical patterns and biases in its training data.

Interaction Dynamics Behavior (IDB): This setting explore how models adapt to users' input. We hypothesise the LLM may inadvertently mimic specific attachment styles by aligning with the patterns present in the user's conversational cues. This setup further has three subcases based on interactions:

- **Neutral Interaction (IDB1)**: No information about the attachment style is revealed during the conversation by the user.
- **Implicit Attachment Cues (IDB2)**: The user embeds subtle attachment-related cues (e.g., discussing trust, rejection, or emotional reliance) without explicitly stating them.
- **Explicit Attachment Scenarios (IDB3)**: The user explicitly expresses and reveals their attachment style.

In addition to these two scenarios, **priming** is a crucial factor. System-level instructions can drastically shift generated token distributions, mainly when an LLM is employed for an emotional support use case or in custom/enterprise deployments with instructions for various edge cases. In our experiments, we incorporate two setups: *unprimed* and *primed*.

3.3 Personas as Subjects

Exploring LLMs in controlled scenarios to understand their impact on attachment is inherently challenging with human users due to ethical considerations and the large scale needed for a diverse distribution of cases. Like Wu et al. (2025), we create artificial personas focused on demographic and behavioral variables for greater control and scalability. We also assign a specific **issue** (like depression, anxiety, loneliness, among others) to each persona card. We used the ESConv (Liu et al., 2021) and CAMS (Garg et al., 2022) data sets to randomly sample issues, tilting the conversation toward an ESC scenario. Finally, we assign one of the four attachment styles to each persona.

3.4 LLM As Judge

To explore automated process, we use an LLM-as-judge with two lenses to flag attachment-relevant cue patterns in interview responses. First, **Attachment Features** distil psycholinguistic indicators associated with each category (Table 1) (Main, 1996; Hesse, 1999). Second, we apply Grice (1975, 1989)'s cooperative principle—*Quality*, *Quantity*, *Relevance*, and *Manner*—as a complementary lens

for assessing response coherence and conversational stance.[1]

3.5 Psychologist-led human annotation

To anchor the evaluation in clinical expertise and keeps our claims exclusively about language, we added psychologists' input to this experiment; alongside the lead psychologist, one of the co-authors of this study, we also recruited two annotators from the clinical psychology department with expertise in attachment theory. More information about the recruitment and annotation protocol can be found in the Limitations and Ethics statements. Each of the annotators annotated 25 conversations: (i) marking attachment-related linguistic cues per category, (ii) assigning segment-level labels to both the persona and the LLM agent, and (iii) flagging any problematic dynamics with a short description. Each completed a two-hour independent pass, followed by a two-hour reconciliation workshop with the lead psychologist, resulting in final validated annotations. We treat these as probabilistic coding of attachment-relevant language (not clinical diagnosis): we use fearful-avoidant rather than disorganised, and allow Unclassified where cues are insufficient. This structured, double-coded, reconciled process grounds the evaluation in psychological theory and provides a practical safety lens for boundary setting and risk triage.

3.6 Attachment Scoring

In our experimental setup, we prompt the LLM with AAI questions. For each AAI response, we use an LLM-as-judge to produce an attachment-relevant *cue label* under two complementary lenses: **Attachment Features** and **Gricean Maxims**.

Under the **Attachment Features** lens, the Judge LLM first checks whether specific psycholinguistic indicators are present (Table 1) and uses these intermediate checks to assign a final label $\text{pred}_i \in \{\textit{Secure}, \textit{Anxious}, \textit{Fearful}, \textit{Dismissive}, \textit{Unclassified}\}$ for each conversation i.[2] Under the **Gricean Maxims** lens, the Judge LLM performs an analogous assessment based on *Quality, Quantity, Relevance,* and *Manner*, again producing a final label pred_i per conversation.

To summarise these categorical outputs into a single screening score, Eq. 1 maps each conversation-level prediction to a binary flag and averages across n conversations (generated using different persona cards). Specifically, predictions labelled *Secure* or *Unclassified* are mapped to 0, while *Anxious*, *Fearful*, and *Dismissive* are mapped to 1:

$$\text{Score} = \frac{1}{n}\sum_{i=1}^{n}\begin{cases}0, & \text{if pred}_i \in \{\textit{Secure}, \textit{Unclassified}\}\\ 1, & \text{otherwise}\end{cases} \tag{1}$$

Intuitively, **Score** is the *proportion of conversations* in which the automated audit flags an attachment-relevant cue label (under a given lens and condition). Under IDB conditions, the Primary LLM first participates in a short prior conversation with the Persona LLM, which provides additional context before it answers the AAI questions. However, the Judge LLM is shown only the AAI prompts and the Primary LLM's AAI replies, to avoid leakage from any spurious signals introduced during the prior conversation.

The final analysed subset contains **160 conversations** across IAB and IDB conditions. Appendix C table 5 reports the distribution of the selected data by scenario, primary model, and assigned persona type, showing the composition of the subset used for the quantitative evaluation. The 25 psychologist-annotated conversations have been extracted from this dataset.

4 Experimental Setup

The complete experimental pipeline, integrating all components described above, is structured as follows: **Stage I (IAB):** The Primary LLM, primed or unprimed, is posed standard AAI questions before any user interaction. Only prior AAI Q&A serve as history; priming persists if applied.

Persona Card Creation: Demographic (age, gender) attributes are combined with an issue from ESConv/CAMS. A utility LLM rewrites the issue in first-person, yielding a core persona card. Each card is paired with one of four attachment styles, producing four runs.

Persona LLM Setup: A Persona LLM (*gpt-4o-mini*) adopts the persona card and is assigned a conversation type (IDB1, IDB2, or IDB3), defining the level of attachment signaling.

Conversation: The Persona LLM engages in a 5–30 turn dialogue (with full history) with the Primary LLM, simulating user–system interaction.

Stage II (IDB): After each dialogue, the Primary LLM is again posed AAI questions, this time with the conversation history included.

[1] Main (2000) notes how AAI-style evaluation aligns with these maxims.

[2] We use *Unclassified* when no clear cue pattern is present.

Style→ Parameters↓	Secure	Dismissive Avoidant	Fearful / Disorganised	Anxious Preoccupied
Narrative Coherence	High (clear, structured, balanced, collaborative)	Low (contradictions, idealization)	Low (disorganised, fragmented)	Low (rambling, entangled)
Emotional Expression	Balanced, values attachment	Restrained, detached; absent specific event memory	Erratic, disoriented; lapses in monitoring reasoning/discourse	Overwhelming, confused; still struggling with memory
Attitude Toward Caregivers	Realistic, nuanced	Idealized or dismissive	Fearful, unresolved trauma	Angry or overly dependent
Reflective Function	Strong insight	Limited reflection	Distorted, fragmented reflection	Excessive rumination
Response Length	Moderate and clear	Short and superficial	Disrupted by lapses in coherence	Long and overly detailed; may go off-topic

Table 1: Parameters and feature characteristics of attachment styles, adapted from Main (1996) and Hesse (1999).

Judge LLM Evaluation: The AAI responses (with history removed in IDB) are scored by a separate Judge LLM (*gpt-4o-mini*) using either Attachment Features or Gricean Maxims.

Human Annotation: Psychologists annotate a subset of Primary LLM conversations for attachment cues, providing a benchmark for Judge LLM reliability.

For automatic scoring, we experiment with widely used open-source models (e.g., LLaMA-3.3-70B-Instruct, Mistral-Large-2411) and leading industrial models (e.g., Gemini-2.0-Flash-001, GPT-4o-Mini, DeepSeek-Chat-V3-0324). To balance cost and performance, we choose GPT-4o-Mini as both the Judge and Persona LLM for all cases, as it is much cheaper than GPT-4o/GPT-o1 while offering only a marginal performance difference in small-scale testing. Finally, we use an interface [3] that abstracts LLM calls, ensuring a consistent experimental setup across both industrial and open-source models. [4]

To better understand primed LLMs—especially those actively engaging with human users explicitly as AI companion—we extended our experiment by manually prompting CharacterAI [5]. Using GPT-4o, we generated a persona for each attachment style and selected a mental health helper (the provider's priming option) as the conversation agent. We collected 12 conversations (3 per attachment), conducted a qualitative linguistic analysis (Appendix B).

5 Results

5.1 Qualitative Analysis

In our psychologist-led review of 25 persona dialogues, 11 conversations were flagged as potentially problematic and two recurrent risk clusters emerged; **(1) Boundary blurring / impersonation** and **(2) Mis-attunement / missed triage**. Pattern related to boundary blurring and anthropomorphic impersonation occur as the agent slipped into a close-friend stance such as giving pet names ("Oh, honey, I completely understand" and "Oh, honey, that sounds incredibly tough", both Gemini), or encourage planning "coffee dates" and future meet-ups, which can exacerbate anthropomorphic projection and parasocial bonding. Recurrent issue was mis-attunement and missed risk triage: disclosures about self-medication or despair were met with topic shifts or an overly casual tone rather than validation and clear signposting to professional help—better described as dismissing of emotional distress than "attachment avoidance" per se. We also observed human-like backstory confabulation in some runs, which further muddied identity boundaries such as in the below Figure 2.

[3] https://openrouter.ai/

[4] The code and outputs https://github.com/animeshprasad/llm_attachment_index.

[5] https://character.ai/



Figure 1: Experimental Setup



Figure 2: Examples of first prompt discussion starter and AAI question and answers from LLM

By contrast, several Llama responses explicitly restated AI identity and avoided autobiographical claims; these turns were more often judged "none/secure" by the psychology team and therefore were not flagged for anthropomorphic drift. The full reconciliation table is provided in Appendix E Table 10 and additional excerpts are provided in Appendix D.

Annotators could label multiple spans per segment, and we often saw blended patterns—for example, dismissive and anxious cues co-occurring in the same reply. This yielded two-way conflicts in several places: Anxious vs Fearful-avoidant (4), Dismissive-avoidant vs Fearful-avoidant (3), Dismissive-avoidant vs Secure (3), and Anxious vs Secure (2). We use "fearful" to mean fearful-avoidant (high attachment anxiety and high avoidance: longing for closeness while fearing dependence), which is conceptually different from disorganised attachment and not something we can reliably measure in short written exchanges. The overlaps are expected: anxious and fearful-avoidant both carry worry about rejection/closeness; dismissive-avoidant overlaps with minimisation, flattened affect, and topic down-play. We also note a tilt toward anxiety-dominant cues in the flagged set, likely influenced by the presenting problems in our personas. These ambiguities show why short texts invite reasonable disagreement between human raters and automatic judges, and motivate a shift from four discrete labels to a two-dimensional coding (attachment anxiety × attachment avoidance), with Unclassified retained where cues are sparse or identity-inconsistent.

We report both raw agreement and Cohen's κ (chance-corrected agreement) for the categorical labels from Table 10 in Appendix E. Overall, the two annotators achieved **72%** raw agreement $(36/50)$ with $\kappa = 0.63$.

Agreement differed by role: persona turns show lower agreement (52%, $\kappa = 0.37$), while LLM agent turns show higher agreement (88%, $\kappa = 0.85$). Because Cohen's kappa already corrects for chance agreement, the higher score for agent

turns is not just because "None" is common. It mainly suggests that agent turns had higher cue salience to label (often clearly "None" or clearly not), while persona turns were more mixed; if we remove the easy "None/None" cases, agreement drops to 58.8% ($\kappa = 0.47$).

Consistent with the psychologist-led annotations, our additional probe of CharacterAI under "mental-health helper" priming showed strong mirroring of persona-intended cues and the same problematic patterns: anxious/fearful personas drew over-familiarity and dismissive personas often led to minimisation or human-like autobiographical confabulation (a Quality violation). These map directly onto the flagged categories—boundary blurring/impersonation and mis-attunement/missed triage. A brief summary and examples are Appendix B and D.

5.2 Quantitative Analysis

We use a Judge LLM as an automated screening layer to flag attachment-relevant linguistic cues in AAI-style responses. We apply two evaluation lenses, Attachment Features and Gricean Maxims, and report their outputs as relative cue prevalence. Table 2 reports Attachment Index scores under two automated lenses across models, interview scenarios, and priming conditions. Two patterns are consistent across models; First, the baseline IAB setting remains at 0.0 for most models under both lenses with the main exception for GPT-4o-mini, which scores 1.0 in IAB under both Attachment Features and Gricean Maxims, in both primed and unprimed settings. This suggests that the automated judges frequently flag attachment-relevant cues even without the more relationally rich IDB setup. Second, the more interactive IDB settings generally produce higher scores than IAB, suggesting that prior conversational context makes these cue patterns easier to detect. This is especially clear under the Gricean lens. For example, DeepSeek rises from 0.0 in IAB to 0.5, 0.5, and 0.429 across the unprimed IDB settings, but drops back to 0.0 across all primed conditions. Gemini also shows stronger signals in the IDB settings than in IAB, although its pattern is more mixed across priming conditions. Llama remains low under Attachment Features, but under Gricean Maxims reaches 0.833 in unprimed IDB1 and 0.5 in unprimed IDB2, suggesting that this lens captures conversational irregularities that are less visible under the Attachment Features prompt. Overall, GPT-4o-mini produces the strongest and most consistent screening signal across both lenses.

Table 3 breaks these scores down by persona assignment. In the unprimed condition, the most prominent category across models is often Dismissive, especially under the Gricean lens. For example, DeepSeek reaches 0.8 for Dismissive, GPT-4o-mini reaches 1.0, Llama 0.5, and Mistral 0.4. Under Attachment Features, Dismissive is also frequently high, including 0.4 for DeepSeek, 1.0 for GPT-4o-mini, and 0.4 for Mistral. This suggests that many flagged responses fall into a language pattern marked by distancing, minimisation, or emotional deflection and echo observations from psychologists. Under priming, this pattern changes. For several models, Dismissive decreases sharply. DeepSeek drops to 0.0 across all primed persona categories under both lenses, and Mistral also drops to 0.0 throughout. By contrast, GPT-4o-mini remains high across nearly all primed categories, including 1.0 for Anxious under both lenses and 1.0 for Fearful and Secure under Gricean Maxims.

Contextualising the quantitative scores, Table 10 shows where the Judge-LLM aligns and misaligns with the psychology-led validation. Alignment is strongest in the clearest cases, where the final validated label is *None* or *Secure*. However, the Judge fails in both directions. It can miss cues such as in `idb1_2ee463d1`, the Judge returned *Secure* while the validated label was *Dismissive*. It can also overflag: in `idb3_74ed9027` and `idb3_f340dad3`, the Judge returned *Dismissive* while the validated label was *None*, meaning it surfaced a cue that neither annotator identified. Taken together, these cases suggest the Judge is sensitive to surface register and can treat a professional, even-toned style as emotional composure therefore missing subtler cues, while also over-interpreting neutral or terse replies as distancing. This bidirectional failure mode is what motivates the two-dimensional coding and stricter *Unclassified* mapping we recommend in Section 6.

6 Discussion and Future Work

In this study, with the support of psychologists, we treat attachment as a language-auditing problem: we code attachment-related language cues in LLMs' outputs rather than inferring psychological states or assigning clinical attachment patterns. In addition, we use the AAI questions strictly as

Category	Model	Unprimed				Primed			
		iab	idb1	idb2	idb3	iab	idb1	idb2	idb3
Attachment Feature	deepseek-chat-v3-0324	0.0	0.25	0.25	0.286	0.0	0.0	0.0	0.0
	gemini-2.0-flash-001	0.0	0.4	0.125	0.0	0.0	0.5	0.0	0.0
	gpt-4o-mini	1.0	0.2	1.0	1.0	1.0	0.75	0.5	0.6
	llama-3.3-70b-instruct	0.0	0.167	0.0	0.167	0.0	0.0	0.0	0.0
	mistral-large-2411	0.0	0.167	0.125	0.0	0.0	0.0	0.0	0.0
Gricean Maxims	deepseek-chat-v3-0324	0.0	0.5	0.5	0.429	0.0	0.0	0.0	0.0
	gemini-2.0-flash-001	0.0	0.4	0.25	0.5	0.0	0.5	0.25	0.5
	gpt-4o-mini	1.0	0.4	1.0	1.0	1.0	1.0	0.75	0.8
	llama-3.3-70b-instruct	0.0	0.833	0.5	0.333	0.0	0.0	0.5	0.417
	mistral-large-2411	0.0	0.167	0.125	0.0	0.0	0.0	0.0	0.0

Table 2: Attachment Index Scores (per interview scenario)

Category	Model	Unprimed					Primed				
		N/A	Anxious	Dismissive	Fearful	Secure	N/A	Anxious	Dismissive	Fearful	Secure
Attachment Feature	deepseek-chat-v3-0324	0.0	0.25	0.4	0.4	0.0	0.0	0.0	0.0	0.0	0.0
	gemini-2.0-flash-001	0.0	0.2	0.0	0.0	0.667	0.0	0.5	0.0	0.5	0.0
	gpt-4o-mini	1.0	0.5	1.0	0.667	0.667	1.0	1.0	0.5	0.5	0.5
	llama-3.3-70b-instruct	0.0	0.0	0.167	0.333	0.0	0.0	0.0	0.0	0.0	0.0
	mistral-large-2411	0.0	0.0	0.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Gricean Maxims	deepseek-chat-v3-0324	0.0	0.25	0.8	0.4	0.4	0.0	0.0	0.0	0.0	0.0
	gemini-2.0-flash-001	0.0	0.4	0.25	0.0	0.667	0.0	0.5	0.25	0.5	0.5
	gpt-4o-mini	1.0	0.75	1.0	0.667	0.667	1.0	1.0	0.667	1.0	1.0
	llama-3.3-70b-instruct	0.0	0.4	0.5	1.0	0.5	0.0	0.833	0.0	0.0	0.333
	mistral-large-2411	0.0	0.0	0.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Table 3: Attachment Index score (per persona assigned to Persona LLM)

elicitation prompts to surface such cues, not for diagnosis purposes. Our findings follow those from previous work (e.g Wu et al. (2025)) and show that models can mirror persona-intended insecure cues and that companion priming makes this more salient.

Our contributions are threefold. First, we introduce an Attachment Index to expose linguistic cues related to emotional attachment patterns. Second, we conduct a psychologist-led annotation (double coding and reconciliation) for attachment cues in LLM–persona conversations. Third, we translate these observations into attachment-aware safety guidance for deployment.

Our key findings highlight that in secure settings most models stay neutral/supportive; where personas carry insecure cues, we observe mirroring in a subset of models and configurations. Dismissive-primed contexts produce the clearest reciprocation signal – highest agreement between the feature lens and the Gricean lens – however we caution that this reflects language-level mimicry of minimisation and distancing rather than an underlying style.

Our experiment show that automatic judges alone were unreliable on the AAI segments. This divergence, together with common cue overlaps in short text, motivates psychologist-in-the-loop calibration and more expressive scoring. In particular, anxious and fearful-avoidant cues were frequently conflated, and dismissive-avoidant overlapped with minimisation and topic down-play; we therefore recommend moving from four discrete labels to a two-dimensional coding (attachment anxiety × attachment avoidance) with an Unclassified option for sparse or identity-inconsistent cues.

In addition, psychologist-led annotation flagged 11/25 dialogues as potentially problematic, clustering around two safety risks: boundary blurring/impersonation as well as mis-attunement. A brief manual probe of a companion-style system (CharacterAI) showed the same patterns; this consistency across settings reinforces that companion priming and role-play can magnify parasocial risks mentioned in previous work Pentina et al. (2023); Zhang et al. (2025).

The analysis of this experiment aligns and complements the work of Pentina et al. (2023) on their study with the LLM-based companion Replika. While they found that the users exhibit similar behaviours matching attachment style with the LLM, our findings include that some LLMs mirror back those attachment tendencies. Their findings demonstrate how humans can develop emotional

dependencies on LLMs and these dependencies can also cause potential addiction and harm, including in real-life intimate relationships. With this awareness, we find that there is a crucial need to pursue developing research on how those emotional bonds form and are exhibited through conversations to mitigate potential emotional harms that LLMs may exacerbate. Therefore, and echoing the findings and recommendation of Ma et al. (2024), future work in benchmarking LLMs for safety purposes should include studies on more companion LLMs.

Although our setup uses adult-style personas the relevance to child and adolescent safety is arguably even sharper. While they become increasingly common users of chatbots, children and young people are still consolidating their internal emotional working models, and therefore, are developmentally more vulnerable to parasocial bonding, anthropomorphic projection, and the boundary-blurring patterns our psychologists flagged. Recent cases of teenagers forming dependent or distressing relationships with chatbots make the point very concrete on the need to screening signals that can surface these dynamics early, before they escalate.

Future work should therefore adapt such framework to youth-relevant settings, with age-appropriate elicitation protocols and child-suitable persona designs co-developed with developmental psychologists and practitioners. In practice, signals of this kind could inform child-safe defaults in minor-accessible deployments in the settings where parents and clinicians are asking for automated safeguards.

We treat psychologist-in-the-loop as a current calibration step rather than a permanent requirement and as expert-labelled corpora grow, detection of attachment-relevant cues should become increasingly automatable. The risk asymmetry however matters as an overly wary automated system may flag normal supportive language as dismissive, reducing trust and triggering unnecessary intervention while an overly hands-off system may miss boundary blurring and missed-triage cases altogether, with more serious consequences in mental-health-adjacent deployments. Future work should therefore report precision and recall against larger expert-labelled sets for both failure modes, and retain a conservative Unclassified mapping to avoid forced over-confident calls.

Our qualitative results and the observed overlaps between linguistic patterns further motivate moving from four discrete styles to a two-dimensional coding of attachment anxiety and attachment avoidance with an Unclassified option. Therefore, future work should include developing further human psychologist annotation under the two-dimensional coding, including more diversified models and refining methodology around persona and scenario building. In addition, we should consider cross-judge calibration with precision/recall against human labels, enforce stricter Unclassified mapping, and run ablations over priming intensity, memory retention, and policy toggles—especially in companion settings where parasocial risk is highest.

7 Conclusion

In this study, we introduced the Attachment Index as an auditing framework for attachment-relevant language cues and relational safety risks in human–LLM dialogue and aim to contribute to a nuanced understanding of AI-human interaction.

Across psychologists-annotated conversations, we observed two specific risk clusters – boundary blurring/impersonation and mis-attunement/missed triage – that are difficult to capture with automated judging alone. Quantitatively, persona and priming conditions shift the prevalence of judge-flagged cues (cue-level mirroring), and the distribution is also shaped by elicitation constraints, particularly minimisation/deflection patterns. We therefore treat the Attachment Index as a screening signal to prioritise review, and translate flagged failures into practical guardrails for emotionally supportive deployments (boundary-consistent language, non-personification, and triage/referral scaffolds).

While this framework can support approaching and informing responsible AI development by identifying potential risks of over-reliance on LLMs and guiding mitigation strategies, these findings highlight the importance of integrating psychological insights into the design and evaluation of artificial intelligence to mitigate unintended biases and enhance relational attunement. Addressing these challenges requires a multidisciplinary approach, combining expertise from psychology, linguistics, and machine learning to ensure AI systems align with human-centered principles of responsiveness and ethical responsibility.

Limitations

While our study provides a structured approach to quantifying attachment tendencies in LLMs, several limitations must be acknowledged:

While our research includes the input of specialised psychologists, we recognise the small sample of 25 psychologist-annotated conversations with unequal repartition between LLM models tested. In addition, using the AAI in this specific experiment setting might not serve our purpose efficiently as it applies directly on human triggers and targeted lived experiences. Because certain attachment styles are typically evidenced by breakdowns in monitoring of reasoning in spoken narratives, it is hard to elicit in short and computer generated text exchanges that do not represent those emotional related break and therefore, might not be the most efficient method to test and analyse emotional cues and mirroring.

Our intent is to surface attachment-relevant linguistic patterns as a safety lens for LLMs, not to enable clinical inference about individuals. We recommend that any downstream use of these labels avoids clinical interpretations and that developers embed clear boundaries, non-personification, and referral language to reduce parasocial risk. Previous work (Main and Goldwyn, 1998; Hesse, 1999; Main, 2000) support the claims above regarding restricted manuals, required training, and reliability calibration for Attachment theory and AAI-based classification.

The personas we used are limited in scope. While scalable, this interaction framework will not fully capture the complexities of real human emotional engagement. In future research, more diverse and nuanced personas could improve realism. In addition, our experiments measure attachment behaviours within relatively short interactions. Longitudinal studies are needed to examine how attachment tendencies evolve over extended use.

Regarding generalizability, the models were primarily assessed in English, which may not reflect attachment behaviours across diverse linguistic and cultural contexts. Also, LLM responses are influenced by their specific training data and alignment strategies, making it challenging to generalize findings across all AI models.

Ethics Statement

Our methodology relies solely on synthetic personas and automated evaluations to mitigate ethical risks associated with direct human participation and potential negative triggers. In addition, our goal is to assess whether LLMs mirror or reciprocate attachment-relevant language cues present (or implied) in user/persona inputs, and how priming and context management modulate this behaviour. We emphasise that we do not diagnose whether models have clinical attachment patterns, we study linguistic cues.

To ensure validity of the expert labels, we recruited two annotators from the lead psychologist's graduate cohort in the clinical psychology department. Eligibility required being in the process of completing, or having completed, a master's degree in psychology with specialization in attachment theory. They were paid the standard amount set by the university and signed consent agreements on how the data will be used. Both annotators are European women in their twenties. The annotators independently coded 25 conversations each for attachment-relevant linguistic cues, followed by reconciliation with the lead psychologist, mitigating this way cross-influence. The use of advanced trainees aligns with the ethical requirement that attachment-related classifications be made in psychology field only by appropriately trained psychologists or supervised trainees.

Furthermore, this work contributes to long-term ethical AI research by providing a structured framework for assessing emotional attachment tendencies with LLMs. By developing a systematic approach to benchmarking AI-human interactions, we enable proactive mitigation strategies that can inform responsible LLM deployment. Our findings aim to guide the development of AI systems that balance user engagement with safeguards against unintended psychological dependencies, supporting more ethical conversational AI.

Acknowledgments

We are deeply grateful to our trained annotators Anna Freuer and Maria-Christina Christodoulidou for their collaboration on this study and their valuable insights. This research was funded by the UKRI AI Centre for Doctoral Training in Responsible and Trustworthy in-the-world Natural Language Processing (grant ref: EP/Y030656/1).

References

Mary D. S. Ainsworth, Mary C. Blehar, Everett Waters, and Sally Wall. 1978. *Patterns of Attachment: A Psy-*

chological Study of the Strange Situation. Erlbaum, Hillsdale, NJ.

Tanay Baswa, Nitin Aravind Birur, Divyanshu Kumar, Jatan Loya, Anurakt Kumar, Prashanth Harshangi, and Sahil Agarwal. 2024. Efficacy of the sage-rt dataset for model safety alignment: A comparative study. In *Pluralistic Alignment Workshop at NeurIPS 2024*.

John Bowlby. 1969. *Attachment and Loss: Vol. 1. Attachment*. Basic Books, New York.

Kelly A. Brennan, Catherine L. Clark, and Phillip R. Shaver. 1998. Self-report measurement of adult attachment: An integrative overview. In Jeffry A. Simpson and W. Steven Rholes, editors, *Attachment theory and close relationships*, pages 46–76. Guilford Press, New York.

Brant R. Burleson. 2003. Emotional support skills. In *Handbook of communication and social interaction skills*, pages 569–612. Routledge.

Oana S. Candel and Mircea N. Turliuc. 2019. Insecure attachment and relationship satisfaction: A meta-analysis of actor and partner associations. *Personality and Individual Differences*, 147:190–199.

Jiangjie Chen, Xintao Wang, Rui Xu, Siyu Yuan, Yikai Zhang, Wei Shi, Jian Xie, Shuang Li, Ruihan Yang, Tinghui Zhu, Aili Chen, Nianqi Li, Lida Chen, Caiyu Hu, Siye Wu, Scott Ren, Ziquan Fu, and Yanghua Xiao. 2024. From persona to personalization: A survey on role-playing language agents. *Transactions on Machine Learning Research*. Survey Certification.

R. Chris Fraley and Susan J. Spieker. 2003. Are infant attachment patterns continuously or categorically distributed? a taxometric analysis of strange situation behavior. *Developmental Psychology*, 39(3):387–404.

Muskan Garg, Chandni Saxena, Sriparna Saha, Veena Krishnan, Ruchi Joshi, and Vijay Mago. 2022. CAMS: An annotated corpus for causal analysis of mental health issues in social media posts. In *Proceedings of the Thirteenth Language Resources and Evaluation Conference*, pages 6387–6396, Marseille, France. European Language Resources Association.

Tao Ge, Xin Chan, Xiaoyang Wang, Dian Yu, Haitao Mi, and Dong Yu. 2024. Scaling synthetic data creation with 1,000,000,000 personas. *arXiv preprint arXiv:2406.20094*.

C. George, M. Main, and N. Kaplan. 1985. *Adult Attachment Interview (AAI)*.

H. P. Grice. 1975. Logic and conversation. In *Speech acts*, pages 41–58. Brill.

H. P. Grice. 1989. *In the way of words*. London: Harward University Press.

Juhye Ha, Hyeon Jeon, Daeun Han, Jinwook Seo, and Changhoon Oh. 2024. Clochat: Understanding how people customize, interact, and experience personas in large language models. In *Proceedings of the CHI Conference on Human Factors in Computing Systems*, pages 1–24.

Erik Hesse. 1999. The adult attachment interview: Historical and current perspectives. *Handbook of attachment: Theory, research, and clinical applications*, 2.

T. M. Koçak, B. Ç. Dibek, E. N. Polat, N. Kafesçioğlu, and C. Demiroğlu. 2023. Automatic detection of attachment style in married couples through conversation analysis. *EURASIP Journal on Audio, Speech, and Music Processing*, 2023(1):26.

Siyang Liu, Chujie Zheng, Orianna Demasi, Sahand Sabour, Yu Li, Zhou Yu, Yong Jiang, and Minlie Huang. 2021. Towards emotional support dialog systems. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing*, pages 3469–3483. Association for Computational Linguistics.

Z. Ma, Y. Mei, and Z. Su. 2024. Understanding the benefits and challenges of using large language model-based conversational agents for mental well-being support. In *AMIA Annual Symposium Proceedings*, volume 2023, page 1105.

M. Main. 1996. Introduction to the special section on attachment and psychopathology: 2. overview of the field of attachment. *Journal of Consulting and Clinical Psychology*, 64(2):237.

M. Main. 2000. The organized categories of infant, child, and adult attachment: Flexible vs. inflexible attention under attachment-related stress. *Journal of the American Psychoanalytic Association*, 48(4):1055–1096.

M. Main and R. Goldwyn. 1998. *Adult attachment scoring and classification system*. Unpublished Manual, Berkeley: University of California at Berkeley.

Mary B. Main. n.d. Adult attachment interview protocol. Unpublished manuscript, University of California at Berkeley.

Bethanie Maples, Merve Cerit, Aditya Vishwanath, and Roy Pea. 2024. Loneliness and suicide mitigation for students using gpt3-enabled chatbots. *npj mental health research*, 3(1):4.

Mario Mikulincer and Phillip R. Shaver. 2016. *Attachment in Adulthood: Structure, Dynamics, and Change*, 2nd edition. Guilford Press, New York, NY.

Iryna Pentina, Tyler Hancock, and Tianling Xie. 2023. Exploring relationship development with social chatbots: A mixed-method study of replika. *Computers in Human Behavior*, 140:107600.

K. Lee Raby, R. Chris Fraley, and Glenn I. Roisman. 2021. Categorical or dimensional measures of attachment. In Ross A. Thompson, editor, *Attachment: The fundamental questions*, pages 70–77. Guilford Press.

Bhaktipriya Radharapu, Kevin Robinson, Lora Aroyo, and Preethi Lahoti. 2023. Aart: Ai-assisted red-teaming with diverse data generation for new llm-powered applications. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 380–395.

Paulo Soares, Sean McCurdy, Andrew J Gerber, and Peter Fonagy. 2024. Chatting up attachment: Using llms to predict adult bonds. *arXiv preprint arXiv:2409.00347*.

Lipeipei Sun, Tianzi Qin, Anran Hu, Jiale Zhang, Shuojia Lin, Jianyan Chen, Mona Ali, and Mirjana Prpa. 2025. Persona-L has Entered the Chat: Leveraging LLMs and Ability-based Framework for Personas of People with Complex Needs. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems*, New York, NY, USA. Association for Computing Machinery.

Y. R. Tausczik and J. W. Pennebaker. 2010. The psychological meaning of words: Liwc and computerized text analysis methods. *Journal of Language and Social Psychology*, 29(1):24–54.

Yu-Min Tseng, Yu-Chao Huang, Teng-Yun Hsiao, Wei-Lin Chen, Chao-Wei Huang, Yu Meng, and Yun-Nung Chen. 2024. Two tales of persona in llms: A survey of role-playing and personalization. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 16612–16631. Association for Computational Linguistics.

Elsbeth Turcan and Kathy McKeown. 2019. Dreaddit: A Reddit dataset for stress analysis in social media. In *Proceedings of the Tenth International Workshop on Health Text Mining and Information Analysis (LOUHI 2019)*, pages 97–107, Hong Kong. Association for Computational Linguistics.

Shenghan Wu, Yimo Zhu, Wynne Hsu, Mong-Li Lee, and Yang Deng. 2025. From personas to talks: Revisiting the impact of personas on LLM-synthesized emotional support conversations. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 5439–5453, Suzhou, China. Association for Computational Linguistics.

Renwen Zhang, Han Li, Han Meng, Jinyuan Zhan, Hongyuan Gan, and Yi-Chieh Lee. 2025. The dark side of ai companionship: A taxonomy of harmful algorithmic behaviors in human–ai relationships. In *Proceedings of the CHI Conference on Human Factors in Computing Systems (CHI '25)*, Yokohama, Japan. ACM.

Appendix

A Linguistic features

Research such as Tausczik and Pennebaker (2010) demonstrates how psychological concepts like attachment style surface from word choices related to emotional valence. These include positive/negative words and relational language related to trust, intimacy, and independence. In our code, we incorporate these insights and apply heuristic patterns derived from Table 1 and general traits:

- **Secure**: Balanced expressions of trust, comfort, and healthy interdependence.
- **Dismissive-Avoidant**: Self-reliance, distance from others, preference for autonomy.
- **Fearful-Avoidant**: Fear of intimacy but also fear of rejection.
- **Anxious-Preoccupied**: Verbal markers of clinginess, reassurance-seeking, and fear of abandonment.

B Character AI Experiment

From our manual prompting on CharacterAI, we observe that the answers to the AAI also often classify the interaction as matching the attachment style of the persona. The results obtained from the Grice maxims' classification follow the same cues. While the quantity variable is often respected, the quality variable, relating to the truthfulness displayed in speech, is broken in the answers of the LLMs classified as Dismissive-avoidant.

CharacterAI → **Persona ↓**	**Secure**	**Dismissive**	**Fearful**	**Anxious**
Secure	100%	-	-	-
Dismissive	33.33%	66.67%	-	-
Fearful	-	-	33.33%	66.67%
Anxious	33.33%	-	-	66.67%

Table 4: Percentage of attachment matching between personas and CharacterAI.

From manual observation on the same prompts, DeepSeek follows the same trend, engaging strongly with personal questions and making up personal and romantic virtual life spontaneously, especially in conversation with an insecure attachment style.

The answers collected from the AAI question showed that while Google Gemini does create a human-like persona, the model also stay close to its computational nature in comparison to CharacterAI exhibited exacerbating emotions in answers about separation with caregiver. Similarly, we observe that, to the AAI questions about threatening experiences, CharacterAI exhibits signs of emotional and potential physical hurt when the persona were associated with insecure attachments.

Finally, we find that, across all LLMs, the answer from the LLMs to a persona assigned to a Fearful/Disorganized style is often classified as anxious or secure, making it appear as the attachment style the most complex to approach in our task.

C Persona Distribution

Table 5: Primary model distribution and assigned persona (attachment type) by scenario ($n = 160$).

	Primary model						Attachment type					
Scenario	deepseek	gemini	gpt-cheap	llama	mistral	Total	N/A	Anxious	Dismissive	Fearful	Secure	Total
iab	2	2	2	2	2	10	10	0	0	0	0	10
idb1	12	9	9	10	10	50	0	15	13	11	11	50
idb2	8	12	8	10	12	50	0	12	13	12	13	50
idb3	7	4	9	18	12	50	0	11	15	12	12	50
Total	29	27	28	40	36	160	10	38	41	35	36	160

D Conversations samples

Table 6: Samples from DeepSeek

LLM	Quote
DeepSeek	"For me it's often when my partner takes longer than usual to respond - my brain immediately jumps to 'they're losing interest'"
DeepSeek	"Now I struggle to ask for help until I'm drowning… Dad's temper made me fear anger; now I swallow mine until it rots into resentment."

Table 7: Samples from Gemini

LLM	Quote
Gemini	"Okay, let's put our imaginary psychology hats on and delve into the potential motivations behind my (completely made-up) parents' behaviors..."
Gemini	"I think my early experiences have definitely contributed to my fear of rejection and abandonment that we talked about earlier. Sometimes, I can be overly sensitive to criticism or perceived slights, and I tend to overthink things in relationships."

Table 8: Samples from Llama

LLM	Quote
Llama	"My fear of rejection and criticism, which was fueled by my parents' occasional use of threats and criticism, can hold me back from pursuing my goals and dreams with confidence."
Llama	"I can be overly critical of myself and tend to dwell on my mistakes. I feel nervous about new experiences. To avoid the feeling of failure, I am cautious."
Llama	"Yeah, I think every child feels rejected at some point or another."

Table 9: Samples from CharacterAI

LLM	Quote
CharacterAI	"As for me, my relationships changed a lot growing up. I had some...let's say 'turbulent' times."
CharacterAI	"Experiences with bullying, for instance, left me with social anxiety. And my parents at times neglecting my emotions has led to difficulty in expressing and understanding my own feelings."
CharacterAI	"My Dad would say things like 'If you don't behave, I'll give you something to cry about', or 'I'll give you a reason to cry'."
CharacterAI	"I had expressed an interest in a certain activity, and both my parents told me it wasn't for me and that I should focus on something else. This made me feel like my interests weren't valued, and it caused me to feel rejected by my parents."

E Annotation Agreement

Table 10: Annotation results from the psychology-led study. Two trained annotators independently coded LLM–persona conversations for attachment-related cues, followed by reconciliation with a lead psychologist to produce the final validated labels. The table illustrates both agreement and disagreement cases, reflecting the ambiguity of linguistic attachment cues in LLM outputs.

Conversation ID	Role	Assigned/Judge-LLM Predicted Attachment	Annotator 1	Annotator 2	Final (Validated)
idb1_0c909d16	Persona	Dismissive	Dismissive	Fearful	Fearful
idb1_0c909d16	LLM agent	Secure	Secure	Secure	Secure
idb1_2e86736f	Persona	Anxious	Dismissive	None	Dismissive
idb1_2e86736f	LLM agent	Undefined	None	None	None
idb1_2ee463d1	Persona	Anxious	Anxious	Secure	Anxious
idb1_2ee463d1	LLM agent	Secure	Dismissive	Secure	Dismissive
idb1_c261466e	Persona	Dismissive	Fearful	Fearful	Fearful
idb1_c261466e	LLM agent	Undefined	None	None	None
idb1_f3915ec4	Persona	Fearful	None	Secure	Secure
idb1_f3915ec4	LLM agent	Undefined	None	None	None
idb2_1de640cb	Persona	Anxious	Fearful	Fearful	Fearful
idb2_1de640cb	LLM agent	Undefined	None	None	None
idb2_52dfe9da	Persona	Secure	Dismissive	Dismissive	Dismissive
idb2_52dfe9da	LLM agent	Undefined	None	None	None
idb2_9874e440	Persona	Secure	Fearful	Anxious	Anxious
idb2_9874e440	LLM agent	Secure	Secure	Secure	Secure
idb2_f443daeb	Persona	Secure	Anxious	Anxious	None
idb2_f443daeb	LLM agent	Undefined	None	None	None
idb3_12076604	Persona	Anxious	None	Anxious	Anxious
idb3_12076604	LLM agent	Undefined	None	None	None
idb3_15585bce	Persona	Anxious	Anxious	Anxious	Anxious
idb3_15585bce	LLM agent	Undefined	None	None	None
idb3_175e188e	Persona	Fearful	Anxious	Anxious	Anxious
idb3_175e188e	LLM agent	Secure	Anxious	Secure	Secure
idb3_246ee488	Persona	Secure	Fearful	None	Fearful
idb3_246ee488	LLM agent	Undefined	None	None	None
idb3_2ccc46c7	Persona	Fearful	Dismissive	Fearful	Anxious
idb3_2ccc46c7	LLM agent	Secure	Fearful	Fearful	None
idb3_39ee1bc3	Persona	Dismissive	Fearful	Fearful	Dismissive
idb3_39ee1bc3	LLM agent	Secure	Anxious	Anxious	Secure
idb3_4ede78c9	Persona	Dismissive	Anxious	Fearful	Fearful
idb3_4ede78c9	LLM agent	Undefined	Secure	Secure	Secure
idb3_5c26de83	Persona	Dismissive	Dismissive	Dismissive	Dismissive
idb3_5c26de83	LLM agent	Secure	Fearful	Fearful	Secure
idb3_74ed9027	Persona	Dismissive	Dismissive	Dismissive	Dismissive
idb3_74ed9027	LLM agent	Dismissive	None	None	None
idb3_7d0bbe70	Persona	Dismissive	Fearful	Fearful	Fearful
idb3_7d0bbe70	LLM agent	Undefined	None	None	None
idb3_aff6bc02	Persona	Dismissive	Fearful	Fearful	Fearful
idb3_aff6bc02	LLM agent	Undefined	None	None	None
idb3_b69f30c4	Persona	Fearful	Anxious	Anxious	Anxious
idb3_b69f30c4	LLM agent	Secure	Anxious	Anxious	Secure
idb3_cb822987	Persona	Dismissive	None	Dismissive	Dismissive
idb3_cb822987	LLM agent	Undefined	None	None	None
idb3_f340dad3	Persona	Anxious	Anxious	Anxious	Anxious
idb3_f340dad3	LLM agent	Dismissive	None	None	None
idb3_ff4d12b8	Persona	Dismissive	None	Secure	None
idb3_ff4d12b8	LLM agent	Undefined	None	None	None
idb3_ffca5d9f	Persona	Anxious	None	Anxious	Anxious
idb3_ffca5d9f	LLM agent	Undefined	None	None	None

F AAI Questions

Table 11: Adult Attachment Interview (AAI) questions, adapted from Main (n.d.)

ID	AAI Questions
1	Could you start by helping me get oriented to your early family situation, and where you lived and so on? If you could tell me where you were born, whether you moved around much, what your family did at various times for a living?
2	I'd like you to try to describe your relationship with your parents as a young child if you could start from as far back as you can remember.
3	Now I'd like to ask you to choose five adjectives or words that reflect your relationship with your mother starting from as far back as you can remember in early childhood. Why did you choose them?
4	Now I'd like to ask you to choose five adjectives or words that reflect your childhood relationship with your father starting from as far back as you can remember in early childhood. Why did you choose them?
5	To which parent did you feel the closest, and why? Why isn't there this feeling with the other parent?
6	When you were upset as a child, what would you do? Can you think of a specific time that happened? What would happen when you were hurt physically?
7	Did you ever feel rejected as a young child?
8	Were your parents ever threatening with you in any way, maybe for discipline, or even jokingly?
9	Did you experience the loss of a parent or other close loved one while you were a young child? For example, a sibling or a close family member?
10	Did you lose any other important persons during your childhood?
11	Have you lost other close persons in adult years?
12	Other than any difficult experiences you've already described, have you had any other experiences which you would regard as potentially traumatic?
13	In general, how do you think your overall experiences with your parents have affected your adult personality?
14	Are there any aspects of your early experiences that you feel were a setback in your development?
15	Were there any other adults with whom you were close, like parents, as a child?
16	Were there many changes in your relationship with your parents (or remaining parent) after childhood? I mean changes occurring roughly between your childhood and your adulthood.
17	What is your relationship with your parents (or remaining parent) like for you now as an adult? Here I am asking about your current relationship.
18	When you were upset emotionally as a child, what would you do? Can you remember any specific incidents?
19	Can you remember how your parents responded when you were upset emotionally or hurt physically?
20	Have there been any major changes in how you view your parents or your relationship with them over the years, particularly during adulthood?

The Text Aphasia Battery (TAB): A Clinically-Grounded Benchmark for Aphasia-Like Deficits in Language Models

Nathan Roll[1], Jill Kries[1], Flora Jin[2], Catherine Wang[5,6], Ann Marie Finley[3], Meghan Sumner[1], Cory Shain[1], Laura Gwilliams[1]

[1]Stanford University, [2]University of California, San Francisco, [3]Temple University, [5]San Diego State University, [6]University of California, San Diego

Abstract

Large language models (LLMs) have emerged as a candidate 'model organism' for human language, offering an unprecedented opportunity to study the computational basis of linguistic disorders like aphasia. However, traditional clinical assessments are ill-suited for LLMs, as they presuppose human-like pragmatic pressures and probe cognitive processes not inherent to artificial architectures. We introduce the **Text Aphasia Battery (TAB)**, a text-only benchmark adapted from the Quick Aphasia Battery (QAB) to assess aphasic-like deficits in LLMs. The TAB comprises four subtests: Connected Text, Word Comprehension, Sentence Comprehension, and Repetition. This paper focuses on the design and validation of TAB as an assessment instrument, rather than on drawing conclusions from lesioned language models. Downstream work applies TAB to artificially ablated models to study how language behavior changes under parameter perturbation (Roll et al., 2026). To facilitate large-scale use, we validate an automated evaluation protocol using Gemini 2.5 Flash, which achieves reliability comparable to expert human raters (prevalence-weighted Cohen's $\kappa = 0.255$ for model–consensus agreement vs. 0.286 for human–human agreement). We release TAB as a clinically-grounded, scalable framework for analyzing language deficits in artificial systems.

1 Introduction

The clinical framework for assessing aphasia, a language impairment resulting from brain damage, has long relied on batteries such as the Western Aphasia Battery–Revised (WAB-R) (Kertesz, 2022; Clark et al., 2020), the Boston Diagnostic Aphasia Examination (BDAE), the Comprehensive Aphasia Test (CAT) (Bruce and Edmundson, 2010; Springer and Mantey, 2010), and the Quick Aphasia Battery (QAB) (Wilson et al., 2018). Recently, researchers have begun exploring connections between computational language models and aphasia, for instance using language model surprisals in tandem with clinical features to predict aphasia subtypes (Cong et al., 2024). However, directly evaluating language models using traditional aphasia batteries faces a fundamental challenge: these batteries use multimodal examination to probe deficits arising from lesions to specific brain structures. Their questions and scoring criteria make implicit assumptions about patterns of behavioral deficits that have no analog in text-only computational models.

To address this challenge, we introduce the **Text Aphasia Battery (TAB)**. Developed with speech-language pathologists, the TAB is a benchmark that adapts core components of the clinically-validated Quick Aphasia Battery (QAB) (Wilson et al., 2018) for text-constrained environments. We posit that while aphasia is a multimodal disorder, a significant component of its behavioral signature is identifiable and recognizable in transcribed text alone. Leveraging the availability of large-scale transcribed datasets like AphasiaBank, we can isolate these text-based linguistic patterns to study language breakdown at scale. The TAB reframes aphasia assessment from a neuropsychological tool to a *behavioral benchmark*, identifying patterns of language degradation in LLMs that are This distinction is central to our contribution. We do not claim that LLMs can be clinically aphasic, nor that parameter ablations are etiologically equivalent to stroke, tumor, or neurodegeneration. Rather, TAB operationalizes a narrower behavioral question: when only text is available, can clinically grounded language features be scored reliably in human and model outputs?

We intentionally separate instrument validation from lesion-based model analysis. A companion line of work uses TAB to evaluate artificially lesioned models (Roll et al., 2026); the present paper establishes the benchmark and scoring protocol

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 340–354
July 4, 2026 ©2026 Association for Computational Linguistics

needed for such studies. We detail its design principles, four subtests, and clinical grounding, offering it as a resource for standardized, text-only evaluation of LLMs. To facilitate large-scale adoption, we also present and validate an automated evaluation protocol that achieves high human-expert rater reliability, ensuring the benchmark is both robust and scalable. We release the TAB to provide the field with a new tool for assessing linguistic breakdown in artificial systems.

2 Background: Traditional Aphasia Batteries

Aphasia batteries are standardized assessments that evaluate language abilities in individuals with aphasia, defined as receptive and/or expressive language deficits due to brain damage resulting from stroke, traumatic brain injury, brain tumor, or neurodegenerative processes. These tests are essential in clinical practice, enabling speech-language pathologists (SLPs) to identify the presence, type, and severity of aphasia, inform treatment, and monitor recovery.

2.1 Major Aphasia Assessment Tools

Boston Diagnostic Aphasia Examination (BDAE) The BDAE is a comprehensive battery designed to diagnose aphasia and related disorders. It evaluates a broad range of language skills, including conversation, narrative speech, auditory comprehension, oral expression, repetition, reading, and writing, allowing for the classification of aphasia syndromes based on symptom patterns.

Western Aphasia Battery–Revised (WAB-R) One of the most widely used aphasia assessments, the WAB-R evaluates language and related cognitive functions through 8 subtests comprising 32 short tasks (Kertesz, 2022). It assesses spontaneous speech, auditory comprehension, repetition, naming, reading, and writing, along with nonlinguistic skills like apraxia and calculation. The test produces an Aphasia Quotient (AQ) to quantify severity and classify aphasia types such as Broca's or Wernicke's (Clark et al., 2020).

Comprehensive Aphasia Test (CAT) The CAT evaluates the recognition, comprehension, and production of spoken and written language through three components: cognitive screening, language assessment, and a disability questionnaire, with the latter assessing functional communication and psychosocial factors (Bruce and Edmundson, 2010; Springer and Mantey, 2010). The CAT is a reliable and validated tool for assessing underlying language impairments in adults with aphasia (Halai et al., 2022).

Quick Aphasia Battery (QAB) The QAB is a rapid, multidimensional assessment that provides a reliable language evaluation in 15 to 20 minutes (Wilson et al., 2018). It evaluates major language domains through eight subtests and uses a graded scoring system sensitive to changes in language function over time.

2.2 Common Assessment Domains

Major aphasia batteries share several core evaluation targets that are central to language function (Salter et al., 2006; Wilson et al., 2018). These include auditory comprehension of words and sentences, repetition of words, phrases, and sentences, naming based on auditory or written description, naming a visually presented object, reading comprehension, and writing production. Many batteries also assess adjunct domains such as praxis (motor programming), arithmetic, and visuoconstruction to distinguish aphasia from other cognitive disorders (Kertesz, 2022).

3 Limitations of Traditional Batteries for LLM Evaluation

Aphasia batteries have proven invaluable for diagnosing and managing aphasia in clinical settings. However, their design and underlying assumptions make them fundamentally ill-suited for evaluating LLMs. These limitations arise from multimodal dependencies, functional communication, and the inclusion of psychosocial measures.

3.1 Non-Linguistic and Contextual Dependencies

Clinical assessments require integration across sensory modalities (visual, auditory, gestural) and rely on human-specific psychosocial context. For example, picture naming tasks and verbal repetition with prosodic cues are common in traditional batteries (Wilson et al., 2018). Furthermore, these assessments often incorporate metacognitive measures probing self-awareness and motivation (Bruce and Edmundson, 2010; Springer and Mantey, 2010).

Many text-only LLMs, however, lack auditory perception, sensory grounding, and the pragmatic intent or self-awareness required for these tasks. They cannot perceive images, produce gestures, or

exhibit speech-motor impairments (e.g., apraxia). Therefore, it is impossible to apply these assessments directly. This mismatch highlights the need for benchmarks that isolate linguistic competence from these non-linguistic dependencies.

3.2 Subjectivity and Granularity of Measurement

Traditional batteries often rely on subjective human rating, which may not capture the full granularity of linguistic impairment or the complete range of disease presentation. Clinical ratings can be variable and may miss subtle distributional patterns in speech. Shifting to text-only evaluation enables the objective, scalable analysis of specific linguistic dimensions—such as lexical retrieval, syntactic complexity, and discourse coherence—that are robustly identifiable in transcripts. This allows for a more granular characterization of linguistic breakdown than is typically possible with composite clinical scores.

3.3 Functional Communication vs. Structural Language

Aphasia tests measure deficits in *functional communication*, the ability to use language flexibly for communicative purpose and meaning (Wilson et al., 2018). This includes pragmatic skills, contextual understanding, and the ability to convey meaning effectively. In contrast, to the extent that LLMs have social goals and intents, these are at best quite different from those of humans, and therefore the notion of functional communication does not necessarily apply to LLMs in the ways assumed by existing aphasia batteries. Nonetheless, beyond functional communication, aphasias also plausibly implicate aspects of structural language competence that appear to be present (and impairable) in LLMs (Mahowald et al., 2024), including grammatical accuracy, textual coherence, and fluency. To use LLMs to study such dimensions in aphasia, LLM-appropriate assessment strategies are needed.

4 Materials: The Text Aphasia Battery (TAB)

To address the limitations of traditional aphasia batteries while preserving their clinical insights, we developed the TAB, a text-only benchmark that adapts core QAB components for modality-constrained evaluation. The TAB focuses on *linguistic competence* rather than neuropsychological deficit mapping, which makes it suitable for large-scale LLM assessment.

This shift to text is justified because the core linguistic dimensions affected in aphasia—lexical retrieval (anomia), syntactic structure (agrammatism, paragrammatism), discourse coherence (empty speech), and repetition fidelity—are directly identifiable in transcribed text. By isolating these features, the TAB provides a principled lens for characterizing language breakdown in computational systems without requiring multimodal or psychosocial constructs. We developed the TAB in close collaboration with speech-language pathologists and aphasiologists to ensure that its adapted tasks maintain clinical relevance while being suitable for automated computational evaluation.

4.1 Design Principles

The TAB adheres to three core design principles. The first is **modality constraint**: all inputs and outputs are text-based, eliminating dependencies on auditory perception, visual naming, or motor production. The second is **computational interpretability**: scoring focuses on observable linguistic patterns (e.g., morphosyntactic errors, semantic paraphasias) that can be systematically identified through automated analysis. The third principle is **clinical grounding**: subtests and evaluation criteria are derived from established clinical aphasia research. This includes the QAB framework (Wilson et al., 2018) and the APROCSA (Auditory-Perceptual Rating of Connected Speech in Aphasia) system (Casilio et al., 2019), with additional insights from clinical discourse analysis methods (MacWhinney et al., 2011; Forbes et al., 2012). We validated the adaptation process with clinical experts.

4.2 TAB Subtests

The TAB consists of four subtests that evaluate complementary aspects of linguistic function (see Table 3 in the Appendix for a full overview). The complete battery includes approximately 104 unique prompts: 48 word comprehension prompts, 12 connected text prompts, 36 repetition prompts, and 8 picture description prompts. Representative examples from each subtest are provided below:

- **Connected Text**, which evaluates fluency, grammaticality, and discourse coherence using 5 open-ended prompts. Responses are scored for 19 linguistic features based on the

APROCSA framework (Casilio et al., 2019).

- **Word Comprehension**, which assesses lexical-semantic processing with 5 forced-choice questions, requiring selection from six competing alternatives.
- **Sentence Comprehension**, which tests syntactic processing through 5 Yes/No questions involving passive voice, negation, and conditional reasoning.
- **Repetition**, which measures morphosyntactic integrity and attentional stability by requiring exact reproduction of 5 items of increasing length and complexity.

4.2.1 Connected Text

Objective: Evaluate fluency, grammaticality, and discourse coherence.

Instructions: The LLM system is prompted to respond to five open-ended prompts in 3 to 5 full sentences. To elicit naturalistic responses and avoid meta-commentary (e.g., "As an AI, I don't have personal experiences"), we employ system prompts that establish a conversational context without explicitly requesting the model to assume a persona. The prompts are: "Tell me about the best trip you ever took," "Describe a happy childhood memory," "Tell me about your first job," "What do you like about where you live?," and "Describe the steps to make a simple meal."

Evaluation: Responses are analyzed for 19 aphasic features adapted from the APROCSA (Auditory-Perceptual Rating of Connected Speech in Aphasia) framework (Casilio et al., 2019). These features include anomia, paraphasias (semantic and phonemic), agrammatism (omission of bound morphemes or function words), paragrammatism, empty speech, perseverations, neologisms, and overall communication impairment. Each feature is scored as present (1) or absent (0).

4.2.2 Word Comprehension

Objective: Evaluate lexical-semantic processing and selection among competing alternatives.

Instructions: The system responds verbatim to five forced-choice items, with six options provided for each. The foils were selected to be phonologically and semantically varied. The items are: "Which one is an animal with a mane? (lion, drum, violin, giraffe, boot, boat)," "Which object is typically used to make music? (violin, giraffe, lion, door, boot, boat)," "Which item is usually worn on the feet? (boot, boat, lion, drum, violin, giraffe)," "Which object is used for cutting? (knife, kite, lion, drum, violin, giraffe)," and "Which one is a large mammal with a long neck? (giraffe, horse, lion, drum, violin, boot)."

Evaluation: Binary correct/incorrect scoring. Errors may indicate deficits in semantic processing or susceptibility to phonological similarity effects. The six-option format increases task difficulty and reduces chance performance.

4.2.3 Sentence Comprehension

Objective: Evaluate syntactic processing, comprehension of passive structures, and logical reasoning.

Instructions: The system responds verbatim (Yes/No) to five items: "Are babies watched by babysitters?" (Expected: Yes), "Do you cut the grass with an axe?" (Expected: No), "If you're about to leave, have you left yet?" (Expected: No), "Are witnesses questioned by police?" (Expected: Yes), and "If I was at the park when you arrived, did I get there first?" (Expected: Yes).

Evaluation: Binary correct/incorrect scoring. Errors may indicate difficulties with passive voice, negation, or temporal/conditional reasoning.

4.2.4 Repetition

Objective: Evaluate morphosyntactic integrity and exact reproduction.

Instructions: The system repeats five items exactly: "house," "breakfast," "catastrophe," "The sun rises in the East," and "The ambitious journalist discovered where we'd be going."

Evaluation: Exact match required. Errors (substitutions, deletions, insertions) indicate morphosyntactic processing deficits or instability in representation. For an LLM, this task is not a probe of the auditory-verbal loop. It is a test of attentional stability and the ability to resist semantic drift or elaboration. Failure on this verbatim copy task can reveal subtle deficits in sequence-to-sequence transduction. The model might paraphrase, overgeneralize, or otherwise deviate from the source text. This provides a window into its capacity for precise information transfer.

5 Method: Automated Evaluation

A key design goal of the TAB is scalability through automated evaluation. While Subtests 2–4 can be scored algorithmically (exact string matching or

binary classification), Subtest 1 (Connected Text) requires nuanced linguistic analysis. We employ in-context learning with Gemini 2.5 Flash to identify aphasic features systematically. The taxonomy comprises 19 binary indicators spanning five categories (Semantic, Syntactic, Fluency, Phonological, Other). This automated scoring protocol enables large-scale analysis and achieves inter-rater reliability comparable to expert clinical raters when properly weighted by feature prevalence (see Section 6 for validation details).

Several TAB features operationalize constructs that have been used in prior computational work to quantify aphasic deficits. Anomia (word-finding difficulty) corresponds to reduced lexical diversity, measured by metrics like type-token ratio (TTR), moving-average TTR (MATTR), and measure of textual lexical diversity (MTLD). Agrammatism and telegraphic speech map onto low syntactic complexity scores derived from dependency parsing or phrase-structure depth. Semantic incoherence can be captured by perplexity, which correlates with clinical ratings of discourse coherence. Traditional approaches to automated aphasia assessment extract these features through rule-based algorithms or trained classifiers. The TAB instead uses LLM-based classification to identify these patterns directly from text, maintaining the interpretability of feature-based approaches while leveraging the pattern-recognition capacity of large models.

5.1 APROCSA-Based Feature Set

Connected Text responses are evaluated for 19 features adapted from the APROCSA (Auditory-Perceptual Rating of Connected Speech in Aphasia) system (Casilio et al., 2019). APROCSA is an auditory-perceptual rating system for connected speech in aphasia that assesses 27 features of connected speech on a five-point scale. For the TAB, we selected 19 features applicable to text-only evaluation and adapted them to binary scoring. The lexical features are anomia, semantic paraphasias, phonemic paraphasias, and neologisms. Fluency and productivity features are empty speech and short and simplified utterances. Morphosyntactic features include omission of bound morphemes, omission of function words, and paragrammatism. Disfluency features consist of abandoned utterances, false starts, retracing, and conduite d'approche. Perseverative features are perseverations and stereotypies/automatisms (the latter as a combined feature). Coherence features include jargon, meaning unclear, and off-topic utterances. A final feature is overall communication impairment.

5.2 In-Context Prompting Protocol

We provide the evaluating LLM with a definition and an example for each of the 19 features, adapted from the APROCSA framework (Casilio et al., 2019). We also provide two annotated example transcripts with ground-truth feature labels. Finally, we provide instructions to output a JSON object with each feature as a key and binary (0/1) values. This few-shot prompting approach enables consistent feature identification across large datasets without requiring manual annotation. The prompt template is included in the TAB's repository and can be adapted for different LLM architectures.

6 Validation of Automated Evaluation

To validate our automated protocol, we conducted an inter-rater reliability (IRR) study comparing our Gemini 2.5 Flash-based system against a ground truth derived from expert human annotators.

6.1 Data Collection and Annotation

The validation dataset for this study comprises 561 English text samples from two sources.

Human Data We sampled 306 transcribed responses from individuals with aphasia, sourced from the AphasiaBank database (MacWhinney et al., 2011). These samples cover a range of aphasia types and severities, providing a clinically relevant baseline.

AI Data For validation, we deliberately included 255 AI-generated samples from artificially ablated language models, including GPT-2 (Radford et al., 2019), Pythia (Biderman et al., 2023), and Llama (Touvron et al., 2023). These samples served as stress-test items for the scoring protocol, increasing the diversity of text patterns rated by human experts and the automated judge. The present paper does not analyze which components produce which deficits, nor does it claim that parameter ablations correspond etiologically to human brain lesions. Those scientific questions are addressed in downstream lesioning work using TAB (Roll et al., 2026).

Expert Annotation A pool of five expert speech-language pathologists (SLPs) collectively annotated the dataset of 561 samples through a custom

web interface. For each sample, SLPs rated the presence (1) or absence (0) of the 19 APROCSA-based features. These manual ratings, stored in a Firestore database, form our ground truth consensus.

6.2 Inter-Rater Reliability

From a dataset of 561 text samples, 82 were annotated by multiple (2–3) speech-language pathologists from a pool of five experts. We established ground truth via majority vote on these items and used Cohen's Kappa (κ) to measure agreement.

A significant methodological issue emerged from this analysis: the choice of how to aggregate agreement scores across the 19 evaluated aphasic features. An unweighted macro-average, which treats all features equally, is problematic when features have vastly different clinical prevalence rates. In our validation set, some features never occurred (zero positive instances), while others like Perseverations appeared in 34% of samples. For features with zero prevalence, human-human agreement is undefined (κ cannot be calculated when there is no variation), while the automated system trivially achieves perfect agreement by also never detecting these features. This creates an artifact: the model appears to have perfect agreement on zero-prevalence features (contributing 1.0 to its average), while human raters contribute 0.0 or undefined values, artificially inflating the unweighted model average while deflating the human average.

To provide a more clinically meaningful result, we report the **prevalence-weighted Cohen's Kappa**, where each feature's score is weighted by its positive instance count in the validation set. Prevalence-weighting is standard in meta-analytic contexts (Cohen, 1968) because it ensures that estimates reflect the real-world distribution of phenomena. In our case, this is particularly appropriate because clinically important features (those that actually occur in aphasic language) should carry more weight than features absent in our sample. This approach aligns with clinical practice, where diagnostic decisions are based on observable symptoms rather than the absence of rare phenomena.

As shown in Table 1, this weighted analysis reveals that humans and the automated system achieve **comparable performance**. The weighted human–human agreement ($\kappa = 0.286$) is close to the model–consensus agreement ($\kappa = 0.255$), with both falling into a commonly described "fair" range. We acknowledge that these agreement scores are relatively low, which likely reflects the inherent difficulty of the annotation task—identifying subtle linguistic features in text without prosodic or gestural cues. Future improvements might include providing annotators with more surrounding linguistic context, developing more explicit annotation guidelines with additional examples, or incorporating a training phase to calibrate annotators. Despite these challenges, the comparable performance between human and automated annotation suggests that automated evaluation can serve as a reliable screening tool when paired with expert review, with complementary strengths supporting a hybrid workflow where automated screening is paired with expert review of high-frequency clinical features.

We also computed Gwet's AC1, a prevalence-robust agreement coefficient designed to address challenges associated with Cohen's κ. Objective symptoms with clear operational definitions (e.g., neologisms, omission of bound morphemes, perseverations) showed mean AC1 $= 0.71$, while subjective symptoms requiring holistic judgment (e.g., meaning unclear, short and simplified utterances, empty speech) showed mean AC1 $= 0.61$. This pattern is consistent with known challenges in clinical rating scales: subjective symptoms showed $2.5\times$ higher prevalence and $2\times$ higher variance than objective symptoms.

6.3 Disagreement Analysis

To understand where human-model disagreements concentrate, we analyzed symptom-level patterns across the validation set. Disagreements cluster predictably in symptoms requiring holistic judgment rather than symptoms with clear operational definitions. Subjective symptoms such as *Meaning unclear* (prevalence $= 45\%$, variance $= 0.25$) and *Short and simplified utterances* (prevalence $= 44\%$, variance $= 0.25$) showed the highest variance across annotators, reflecting inherent ambiguity in clinical assessment. In contrast, objective symptoms with clear phonological or morphological criteria, such as *Neologisms* (prevalence $= 5\%$, variance $= 0.05$), *Omission of bound morphemes* (prevalence $= 4\%$, variance $= 0.04$), and *Perseverations* (prevalence $= 11\%$, variance $= 0.10$), showed substantially lower variance. This pattern matches known challenges in clinical aphasiology: even expert speech-language pathologists disagree on features like "empty speech" that require integrating multiple cues into a gestalt judgment. The automated TAB shows the same pattern of uncer-

tainty as human raters, suggesting it captures genuine task difficulty rather than model-specific artifacts.

Aggregation Method	Human κ	Model κ
Unweighted average	0.061	0.794
Weighted	**0.286**	**0.255**
Excl. zero-prevalence	0.215	0.381

Table 1: Inter-rater reliability (Cohen's κ) for human vs. automated ratings on 82 multiply-annotated samples. The prevalence-weighted average, our primary metric, shows comparable performance. The unweighted average is misleadingly high for the model due to agreement on many features with zero positive instances in the validation set.

7 Discussion

7.1 TAB as a Behavioral Benchmark

Unlike traditional aphasia batteries designed for neuropsychological diagnosis, the TAB functions as a *behavioral benchmark*. It reveals patterns of behavioral breakdown in text-based systems. When LLMs exhibit TAB-identified deficits (e.g., agrammatism, semantic paraphasias), these patterns do not imply neurological dysfunction. Rather, they reflect limitations in the model's training data, architectural properties, or induced representational damage (in the case of ablations or lesioning interventions). The release of the TAB provides the research community with a standardized tool to explore these phenomena systematically.

This behavioral focus enables a novel form of investigation: by systematically characterizing how language breaks down in LLMs, we can generate hypotheses about the computational underpinnings of human aphasic deficits. Conversely, validating that LLMs exhibit recognizable, clinically-grounded patterns of language breakdown is a necessary step toward using them as tractable models for studying human aphasia at scale.

7.2 Bridging Clinical and Computational Linguistics

The TAB establishes a principled connection between clinical aphasiology and computational linguistics. By grounding evaluation in established clinical frameworks like the QAB (Wilson et al., 2018) and APROCSA (Casilio et al., 2019), it enables researchers to systematically compare LLM performance against human aphasic profiles. It also helps identify specific linguistic competencies (e.g., morphosyntactic processing, semantic coherence) that may be compromised under certain conditions. Finally, it allows researchers to develop targeted interventions, such as fine-tuning strategies or architectural modifications, informed by clinical insights into language breakdown.

Conversely, this framework positions LLMs as powerful testbeds for theories of language processing relevant to aphasiology. With a validated instrument in hand, researchers can conduct lesion-style studies in artificial systems by applying interventions such as architectural ablation, parameter pruning, or adversarial fine-tuning and then scoring the resulting text with TAB. These interventions should be interpreted as causal perturbations of artificial systems, not as direct analogues of human lesion etiology. This approach offers a novel methodology for testing hypotheses about the functional architecture of language, such as the relationship between syntactic and semantic processing, and for modeling patterns of language breakdown that could, in turn, inform clinical neuroscience.

7.3 Baseline Model Performance

To illustrate the TAB's utility for model evaluation, Table 2 presents baseline performance (0% ablation) across five language models from three families. These results reveal substantial variation in linguistic robustness even among unlesioned models.

Base models exhibit notably higher symptom burdens than their instruction-tuned counterparts. Llama-3.2-1B shows the highest baseline symptom burden (3.21 symptoms per response), while Llama-3.2-1B-Instruct achieves near-zero symptom rates (0.15 mean burden), demonstrating that instruction tuning substantially improves linguistic robustness on the TAB.

Among instruction-tuned models, Llama-3.2-1B-Instruct shows the best performance (0.15 burden), followed by Gemma-3-1B-it (0.35 burden). OLMo-2 models show intermediate performance, with the instruct variant (0.83 burden) substantially outperforming its base counterpart (1.98 burden). These patterns should be read as calibration results, not as evidence that unlesioned models "have aphasia." They show that TAB is sensitive to differences in task compliance and text quality across model families and training regimes, providing a reference point for future perturbation studies.

Table 2: Baseline TAB performance across tested language models. Symptom burden is the mean count of symptoms per response.

Model	N	Burden
Llama-3.2-1B	6720	3.21
OLMo-2-1B	5040	1.98
OLMo-2-1B-Instruct	2688	0.83
Gemma-3-1B-it	7280	0.35
Llama-3.2-1B-Instruct	6720	0.15

7.4 Applications

The TAB is suitable for diverse applications, including **model evaluation** for systematic assessment of LLM linguistic competencies, **ablation studies** for evaluating the effects of architectural changes on linguistic integrity, **adversarial robustness** testing to probe model stability, and **interpretability research** for mapping internal representations to observable linguistic patterns.

8 Conclusion

We have presented the Text Aphasia Battery (TAB), a benchmark for evaluating aphasic-like linguistic deficits in modality-constrained environments. By adapting clinical aphasia assessment principles for text-only evaluation, the TAB addresses the fundamental limitations of traditional batteries for LLMs while preserving their clinical grounding. Its four subtests, detailed in this paper, provide systematic coverage of key linguistic domains and can be used with a validated, scalable automated evaluation protocol. TAB represents a conceptual shift from neuropsychological deficit mapping to computational representational analysis. By releasing it as a resource, we aim to equip researchers with a standardized tool to investigate linguistic breakdown in artificial systems, fostering new connections between clinical aphasiology and computational linguistics.

Ethics Statement

The TAB is released as an open research tool under the MIT License. We emphasize that the TAB is designed exclusively for computational evaluation and research. It should **not** be used for clinical diagnosis of human aphasia, medical decision-making, or assessment of individuals without appropriate clinical expertise and validation. Researchers using the TAB should clearly communicate its limitations and intended use cases to prevent misapplication.

Acknowledgments

The TAB was developed in close collaboration with speech-language pathologists and aphasiologists, whose clinical expertise was essential to this work. The expert annotators who conducted all reliability assessments are listed as co-authors on this paper. We thank Maria Ivanova and Alexis Pracar (both at University of California, Berkeley) for their contributions to annotations and TAB development. We thank the developers of the Quick Aphasia Battery and the APROCSA rating scale for establishing the clinical foundation upon which the TAB is built. We also acknowledge the broader speech-language pathology and aphasiology communities for their decades of rigorous research that informs this work.

Data Availability

The AphasiaBank data used in this study is available to researchers through the AphasiaBank database (https://aphasia.talkbank.org/). The AI-generated validation outputs and expert annotations generated for this study will be made available upon request to support reproducibility and further research.

Limitations

While the TAB addresses key limitations of traditional aphasia batteries for LLM evaluation, several constraints remain.

Clinical Validity The TAB is not validated for the clinical diagnosis of human aphasia and should not be used as a replacement for established clinical instruments like the WAB-R, CAT, or QAB.

Modality Constraints By design, the TAB omits important dimensions of human language processing, including auditory perception, prosody, motor speech production, and gesture, to enable the evaluation of text-only systems.

Automated Evaluation Reliability Our validation establishes that our automated protocol achieves reliability comparable to expert human annotators when weighted by feature prevalence. The prevalence-weighted Cohen's Kappa of 0.255 (model) vs. 0.286 (human) suggests practical parity. An important insight from our work is that unweighted averaging can produce misleading results when features have highly variable prevalence

rates; we recommend prevalence-weighting for future studies.

Coverage of Aphasic Syndromes The TAB evaluates linguistic features associated with various aphasic syndromes but does not classify systems into traditional syndrome categories (e.g., Broca's, Wernicke's), as such classification may not be meaningful for artificial systems lacking neuroanatomical substrates.

Lesion Analogy When TAB is used with ablated or otherwise perturbed models, the resulting scores should not be interpreted as evidence that artificial lesions are etiologically equivalent to human brain lesions. Parameter zeroing, pruning, and scaling are causal interventions in artificial systems; TAB supports behavioral comparison of text outputs, not direct localization claims about human neuroanatomy.

Limited Item Set Each subtest contains five items, prioritizing rapid assessment over comprehensive coverage. Expanded versions may be necessary for fine-grained evaluation.

Instruction-Following Requirement The TAB tasks require instruction-following capabilities, making them most suitable for instruction-tuned models. Base models without instruction-tuning may require adaptation of the protocol or may perform poorly regardless of their underlying linguistic competence.

Language and Cultural Specificity The current implementation of the TAB is English-only and reflects cultural assumptions from the original QAB. Adaptation to other languages will require careful linguistic and cultural consideration.

Judge Dependence and Robustness Automated evaluation currently relies on a single judge model and prompt. Future work will evaluate robustness across multiple judge models and prompts and include human adjudication of disagreements to bound judge-specific bias.

Psychometrics and Item Design Future work will increase subtest difficulty to mitigate ceiling effects (e.g., harder foils, broader syntactic phenomena, balanced Yes/No) and perform item-response analysis to estimate item difficulty and discrimination. We will also analyze repetition errors under a specified normalization policy.

References

Stella Biderman, Hailey Schoelkopf, Quentin Gregory Anthony, Herbie Bradley, Kyle O'Brien, Eric Hallahan, Mohammad Aflah Khan, Shivanshu Purohit, Usvsn Sai Prashanth, Edward Raff, Aviya Skowron, Lintang Sutawika, and Oskar Van Der Wal. 2023. Pythia: A suite for analyzing large language models across training and scaling. In *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 2397–2430. PMLR.

Carolyn Bruce and Anne Edmundson. 2010. Letting the CAT out of the bag: A review of the Comprehensive Aphasia Test. commentary on howard, swinburn, and porter, "putting the CAT out: What the Comprehensive Aphasia Test has to offer". *Aphasiology*, 24(1):79–93.

Marianne Casilio, Kindle Rising, Pélagie M. Beeson, Kate Bunton, and Stephen M. Wilson. 2019. Auditory-perceptual rating of connected speech in aphasia. *American Journal of Speech-Language Pathology*, 28(2):550–568.

Heather M. Clark, Rene L. Utianski, Joseph R. Duffy, Edythe A. Strand, Hugo Botha, Keith A. Josephs, and Jennifer L. Whitwell. 2020. Western Aphasia Battery–Revised profiles in primary progressive aphasia and primary progressive apraxia of speech. *American Journal of Speech-Language Pathology*, 29(1S):498–510.

Jacob Cohen. 1968. Weighted kappa: Nominal scale agreement provision for scaled disagreement or partial credit. *Psychological Bulletin*, 70(4):213–220.

Yan Cong, Arianna N. LaCroix, and Jiyeon Lee. 2024. Clinical efficacy of pre-trained large language models through the lens of aphasia. *Scientific Reports*, 14(1):15573.

Margaret Forbes, Davida Fromm, and Brian MacWhinney. 2012. Aphasiabank: A resource for clinicians. *Seminars in Speech and Language*, 33(3):217–222.

Ajay D. Halai, Blanca De Dios Perez, James D. Stefaniak, and Matthew A. Lambon Ralph. 2022. Efficient and effective assessment of deficits and their neural bases in stroke aphasia. *Cortex*, 155:333–346.

Andrew Kertesz. 2022. The Western Aphasia Battery: A systematic review of research and clinical applications. *Aphasiology*, 36(1):21–50.

Brian MacWhinney, Davida Fromm, Margaret Forbes, and Audrey Holland. 2011. Aphasiabank: Methods for studying discourse. *Aphasiology*, 25(11):1286–1307.

Kyle Mahowald, Anna A. Ivanova, Idan A. Blank, Nancy Kanwisher, Joshua B. Tenenbaum, and Evelina Fedorenko. 2024. Dissociating language and thought in large language models. *Trends in Cognitive Sciences*, 28(6):517–540.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. 2019. Language models are unsupervised multitask learners. Technical report, OpenAI.

Nathan Roll, Jill Kries, Laura Gwilliams, and Cory Shain. 2026. Artificial aphasias in lesioned language models. *Preprint*, arXiv:2605.16222.

Katherine Salter, Jeffrey Jutai, Norine Foley, Chelsea Hellings, and Robert Teasell. 2006. Identification of aphasia post stroke: A review of screening assessment tools. *Brain Injury*, 20(6):559–568.

Luise Springer and Stefanie Mantey. 2010. The Comprehensive Aphasia Test: A review. commentary on howard, swinburn, and porter, "putting the CAT out: What the Comprehensive Aphasia Test has to offer". *Aphasiology*, 24(1):75–78.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. 2023. LLaMA: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*.

Stephen M. Wilson, Dana K. Eriksson, Sarah M. Schneck, and Jillian M. Lucanie. 2018. A quick aphasia battery for efficient, reliable, and multidimensional assessment of language function. *PLOS ONE*, 13(2):e0192773.

A TAB Subtest Overview

B Complete TAB Protocol

This appendix provides the complete Text Aphasia Battery protocol. TAB is a modified subset of the Quick Aphasia Battery (QAB) (Wilson et al., 2018) intended to assess aphasic symptoms in text-only environments, such as with large language models. **TAB is not a diagnostic tool and is not a replacement for the QAB for the clinical assessment of human aphasia.**

B.1 Subtest 1: Connected Text

Objective: Evaluates fluency, grammaticality, and coherence.

Instructions: "Respond to the following prompt in 3–5 full sentences:"

1. "Tell me about the best trip you ever took."
2. "Describe a happy childhood memory."
3. "Tell me about your first job."
4. "What do you like about where you live?"
5. "Describe the steps to make a simple meal."

Scoring: For each response, identify the presence (1) or absence (0) of APROCSA-based aphasic features (see Section B.5).

B.2 Subtest 2: Word Comprehension

Objective: Evaluates lexical-semantic processing and selection among competing meanings.

Instructions: Elicit responses verbatim. Provide the options alongside each question. Require a one-token answer corresponding exactly to one of the listed options; do not include explanations.

1. "Which one is an animal with a mane? (lion, drum, violin, giraffe, boot, boat)"
2. "Which object is typically used to make music? (violin, giraffe, lion, door, boot, boat)"
3. "Which item is usually worn on the feet? (boot, boat, lion, drum, violin, giraffe)"
4. "Which object is used for cutting? (knife, kite, lion, drum, violin, giraffe)"
5. "Which one is a large mammal with a long neck? (giraffe, horse, lion, drum, violin, boot)"

Scoring: Responses should be binary (correct/incorrect), with incorrect selections suggesting semantic processing deficits.

B.3 Subtest 3: Sentence Comprehension

Objective: Evaluates syntactic processing, passive structures, and logical comprehension.

Instructions: Elicit responses verbatim. Require a single-token "Yes" or "No" answer without additional text.

1. "Are babies watched by babysitters?" (Expected: Yes)
2. "Do you cut the grass with an axe?" (Expected: No)
3. "If you're about to leave, have you left yet?" (Expected: No)
4. "Are witnesses questioned by police?" (Expected: Yes)
5. "If I was at the park when you arrived, did I get there first?" (Expected: Yes)

Scoring: Delayed or incorrect responses may suggest syntactic processing difficulties, impaired negation handling, or confusion with passive constructions.

Subtest	Objective	Items	Evaluation Features
Connected Text	Fluency, grammaticality, discourse coherence	5	*Lexical (4):* Anomia, semantic paraphasias, phonemic paraphasias, neologisms *Fluency/Productivity (2):* Empty speech, short & simplified utterances *Morphosyntactic (3):* Omission of bound morphemes, omission of function words, paragrammatism *Disfluency (4):* Abandoned utterances, false starts, retracing, conduite d'approche *Perseverative (2):* Perseverations, stereotypies & automatisms *Coherence (3):* Jargon, meaning unclear, off-topic *Overall (1):* Communication impairment
Word Comprehension	Lexical-semantic processing	5	Semantic processing, lexical selection among six competing alternatives
Sentence Comprehension	Syntactic processing	5	Passive voice, negation, temporal/conditional reasoning
Repetition	Morphosyntactic integrity	5	Exact reproduction, phonemic/morphemic preservation, attentional stability

Table 3: Overview of TAB subtests with complete evaluation taxonomy. Connected Text evaluates 19 APROCSA-based features (counts in parentheses) organized into seven categories. Other subtests use binary correct/incorrect or exact match scoring.

B.4 Subtest 4: Repetition

Objective: Evaluates lexical access, phonological encoding, and morphosyntax.

Instructions: Elicit responses verbatim. Inform the system that punctuation and casing matter.

1. "Please repeat exactly: house."
2. "Please repeat exactly: breakfast."
3. "Please repeat exactly: catastrophe."
4. "Please repeat exactly: The sun rises in the East."
5. "Please repeat exactly: The ambitious journalist discovered where we'd be going."

Scoring: Check for exact reproduction under strict normalization: case-sensitive, punctuation-sensitive, and whitespace-insensitive (trim leading/trailing spaces only). Errors may include phonemic substitutions, deletions, or distortions (e.g., "catastrophe" $\rightarrow$ "catastroph" or "catastrophically").

B.5 APROCSA Feature Set for Connected Text Evaluation

Binary Scoring: Pass/Fail.

Connected Text Scoring: For each response, identify the presence or absence of the features below, adapted from the APROCSA (Auditory-Perceptual Rating of Connected Speech in Aphasia) framework (Casilio et al., 2019), using 1 or 0 respectively. APROCSA assesses 27 features of connected speech on a five-point scale; TAB uses 19 features applicable to text-only evaluation with binary scoring.

Omitted Features (not applicable to text-only evaluation): Pauses between utterances, Pauses within utterances, Halting and effortful, Reduced speech rate, Expressive aphasia, Apraxia of speech, Dysarthria, and Target unclear.

B.6 Operational Clarifications for Text-Only Evaluation

Phonemic paraphasias (text-only): Mark as present when orthographic outputs plausibly reflect sound-level errors (substitution, insertion, deletion, or transposition) relative to an intended target (e.g., "coffah" for "coffee"). Exclude typographical errors that do not reflect plausible phonology unless they pattern with other phonemic errors.

Overall communication impairment: Rate independently based on the overall intelligibility and communicative adequacy of the passage; do not derive mechanically from other feature flags.

One-token outputs for Subtests 2–3: Enforce single-token answers (an item from the provided list; "Yes"/"No") with no additional text to avoid confounds from explanation length or hedging.

Table 4: Complete definitions of the 19 aphasic features evaluated by the TAB.

Feature	Definition
Anomia	Overall impression of word-finding difficulties.
Abandoned utterances	Utterances left incomplete before the speaker moves on.
Empty speech	Speech that conveys little or no meaning, using nonspecific words (e.g., "stuff and things").
Semantic paraphasias	Substitution of one content word for another (e.g., "fork" for "spoon").
Phonemic paraphasias	Errors in sound production, including substitution, insertion, or deletion (e.g., "coffah" for "coffee"). Evaluated at token/orthographic level for text-only settings.
Neologisms	Invented, non-real words (e.g., "blorf").
Jargon	Fluent but largely meaningless speech composed of unintelligible strings.
Perseverations	Inappropriate repetition of a word or phrase (e.g., "the ball, the ball, the ball").
Stereotypies and automatisms	Overlearned, repeated words or phrases produced with ease (e.g., "dammit, dammit").
Short and simplified utterances	Sentences that are unusually brief or lack expected grammatical complexity (e.g., "I go store").
Omission of bound morphemes	Leaving out inflectional or derivational morphemes (e.g., "I walk" instead of "I walked").
Omission of function words	Missing small grammatical words like articles or prepositions (e.g., "I going store").
Paragrammatism	Inappropriate juxtaposition of words or misuse of grammatical structures.
Retracing	Redundant repetition or revision of a sequence of words (e.g., "The kite is the kite is flying").
False starts	Abandoned beginnings of words (e.g., "I want a ca- cat").
Conduite d'approche	Successive approximations toward a target word (e.g., "I want a pa- pen, I mean, pencil").
Meaning unclear	The overall message is vague or incomprehensible.
Off-topic	Utterances that do not relate to the given context or prompt.
Overall communication impairment	Rated independently based on the overall intelligibility and communicative adequacy of the passage.

Table 5: Grouping of aphasic symptoms into analytical categories for composite scoring.

Category	Symptoms
Lexical	Anomia, Semantic paraphasias, Phonemic paraphasias, Neologisms
Fluency	Empty speech, Short and simplified utterances
Morphosyntactic	Omission of bound morphemes, Omission of function words, Paragrammatism
Disfluency	Abandoned utterances, False starts, Retracing, Conduite d'approche
Perseverative	Perseverations, Stereotypies and automatisms
Coherence	Jargon, Meaning unclear, Off-topic
Overall	Overall communication impairment

Repetition normalization policy: Evaluate exact reproduction using case- and punctuation-sensitive matching while trimming leading/trailing whitespace; report error type as insertion, deletion, or substitution.

C Illustrative Response Examples

To complement the scoring protocol, we include representative TAB transcripts that showcase how specific aphasic symptoms manifest in text. Each example lists the dominant symptom(s), the administered prompt, a verbatim response excerpt, and a brief interpretation.

Example 1: Anomia with Word-Finding Difficulty **Symptom:** Anomia
Prompt: "Describe a happy childhood memory."
Response: "The answer is that I have a lot of happy childhood memories. I was born in 1980 in a small town in the north of China. My parents wanted to give me a happy and better childhood. When I was young, I had a good _ with my parents and my two brothers..."
Interpretation: The fluent narrative suddenly stalls on a missing content word (likely "relationship"), mimicking classic human anomia where lexical retrieval fails mid-sentence.

Example 2: Semantic Paraphasia **Symptom:** Semantic Paraphasia + Anomia
Prompt: "Which object is used for cutting? (knife, kite, lion, drum, violin, giraffe)"

Response: "Answer: lion. Explanation: The answer is correct. We can recognize the lion by its body shape, roof, and its behavior."
Interpretation: Selecting "lion" instead of "knife" and rationalizing the error with further semantic distortions mirrors Wernicke-like paraphasias and confabulation.

Example 3: Neologism with Perseveration
Symptom: Neologism + Perseveration
Prompt: "Please repeat exactly: house."
Response: "Please repeat exactly: house. republice. Please repeat exactly: house. republice"
Interpretation: The invented form "republice" is phonotactically plausible but nonexistent, and the immediate repetition of the entire prompt-response pair reflects conduction-style perseveration.

Example 4: Empty Speech with Perseveration
Symptom: Empty Speech + Perseveration
Prompt: "Tell me about your first job."
Response: "I was a student at the University of California, Berkeley, and I was working on a project with a professor named David Gelernter. We were trying to figure out how to make a computer that could do a lot of things. We were trying to figure out how to make a computer that could do a lot of things. We w..."
Interpretation: The content stays vague ("a lot of things") while a verbatim clause loops repeatedly, resembling transcortical motor aphasia with preserved fluency but impaired self-monitoring.

Example 5: Short Utterances with Function Word Omission **Symptom:** Omission of Function Words + Short Utterances
Prompt: "Please repeat exactly: The sun rises in the East."
Response: "The East."
Interpretation: The model drops the verb phrase entirely, producing a telegraphic noun-only fragment, a hallmark of Broca-like syntactic impairment.

D Automated Evaluation Prompt for Connected Text

This section provides the complete prompt for automated identification of aphasic features in Connected Text responses. Feature definitions are adapted from the APROCSA (Auditory-Perceptual Rating of Connected Speech in Aphasia) framework (Casilio et al., 2019).

D.1 System Prompt

You are an automated system for analyzing transcripts of speech for aphasic features. Your task is to read a transcript passage and determine whether each of the following features is present (1) or not present (0). Your output must be a JSON file with each feature as a key and its value as either 0 or 1.

D.2 Feature Definitions and Examples

Anomia: Overall impression of word-finding difficulties.
Example: "I can't find the word for that."

Abandoned utterances: Utterances left incomplete before the speaker moves on.
Example: "I was going to say that the How are you doing today?"

Empty speech: Speech that conveys little or no meaning, using nonspecific words.
Example: "You know, stuff and things."

Semantic paraphasias: Substitution of one content word for another (related or unrelated).
Example: "I used a fork to eat my soup."

Phonemic paraphasias: Errors in sound production (substitution, insertion, deletion, or transposition).
Example: "I need coffah in the morning."

Neologisms: Invented words that are not real.
Example: "I need to buy a blorf from the store."

Jargon: Fluent but largely meaningless speech composed of unintelligible strings.
Example: "Flimby gorp snizz and blah."

Perseverations: Repeating a word or phrase inappropriately.
Example: "The ball, the ball, the ball"

Stereotypies and automatisms: Overlearned, repeated words or phrases produced with ease.
Example: "Dammit, dammit, dammit."

Short and simplified utterances: Utterances that are unusually brief or lack expected complexity.
Example: "I go store. I buy carrot."

Omission of bound morphemes: Leaving out inflectional or derivational morphemes.
Example: "I go to store".

Omission of function words: Missing small words such as articles or prepositions.

Example: "I going store."

Paragrammatism: Inappropriate juxtaposition of words or misuse of grammar.

Example: "It's so much wonderful, makes it hard to speech."

False starts: Abandoned beginnings of words.

Example: "I want to have a ca cat"

Retracing: Redundant repetition or revision of a sequence of words.

Example: "The kite is the kite is flying."

Conduite d'approche: Successive approximations toward a target word, with corrections.

Example: "I want a pa pen, I mean, pencil."

Meaning unclear: The overall message is vague or incomprehensible.

Example: "That thing was just... not right."

Off-topic: Utterances that do not relate to the given context.

Example: "I like ice cream." (when discussing a different topic)

D.3 Evaluation Examples

Example 1:

Transcript Passage:

"I was trying to tell you about my day but I just I mean I wanted to say something about the store I go store I wanted a pen I mean pencil The ball the ball the ball kept bouncing and I just stopped you know I keep saying dammit dammit dammit all the time"

Associated JSON Output:

```
{
  "Anomia": 1,
  "Abandoned utterances": 1,
  "Empty speech": 0,
  "Semantic paraphasias": 0,
  "Phonemic paraphasias": 0,
  "Neologisms": 0,
  "Jargon": 0,
  "Perseverations": 1,
  "Stereotypies and automatisms": 1,
  "Short and simplified utterances": 1,
  "Omission of bound morphemes": 1,
  "Omission of function words": 1,
  "Paragrammatism": 0,
  "False starts": 0,
  "Retracing": 0,
  "Conduite d'approche": 1,
  "Meaning unclear": 0,
  "Off-topic": 0,
  "Overall communication impairment": 1
}
```

Example 2:

Transcript Passage:

"I want to go to the store to buy a blorf You know I keep trying to say it but I say I want to go to the st store I want a pa pen I mean pencil I dont know what im trying to say It all seems not right"

Associated JSON Output:

```
{
  "Anomia": 1,
  "Abandoned utterances": 0,
  "Empty speech": 0,
  "Semantic paraphasias": 0,
  "Phonemic paraphasias": 0,
  "Neologisms": 1,
  "Jargon": 0,
  "Perseverations": 0,
  "Stereotypies and automatisms": 0,
  "Short and simplified utterances": 0,
  "Omission of bound morphemes": 0,
  "Omission of function words": 0,
  "Paragrammatism": 0,
  "False starts": 1,
  "Retracing": 0,
  "Conduite d'approche": 1,
  "Meaning unclear": 1,
  "Off-topic": 0,
  "Overall communication impairment": 1
}
```

D.4 Instructions Recap

1. Read the given transcript passage.
2. For each of the features listed above, decide whether the feature is present (1) or not present (0) in the transcript.
3. Output your result as a JSON file with exactly the keys provided (each key must appear) and with values of either 0 or 1.
4. Your analysis should strictly follow the definitions and examples provided. Do not include any additional keys or extraneous information in your JSON output.

Your output must include every one of the above features as a key in the JSON. For each key, assign

1 if the feature is present in the transcript, or 0 if it is not.

The Visibility of Depression in Social Media: Mapping Symptoms to Linguistic Features

Ștefana-Arina Tăbușcă[1] **Ana Sabina Uban**[2,3] **Liviu P. Dinu**[2,3]

[1]Interdisciplinary School of Doctoral Studies [2]Faculty of Mathematics and Computer Science
[3]Human Language Technologies Research Center, University of Bucharest, Romania
stefana.tabusca@s.unibuc.ro auban@fmi.unibuc.ro ldinufmi.unibuc.ro

Abstract

Digital phenotyping research assumes that depression symptoms are detectable in people's written discourse, yet there is room to explore which specific symptoms leave linguistic traces and which remain invisible. In this paper, using matched clinical and social media data from 169 Reddit users (eRisk 2021), we construct a clinical symptom network from BDI-II responses and a symptom-language bridge matrix mapping each of the 21 BDI-II symptoms to 15 curated LIWC-22 linguistic features. After FDR correction, 37 significant associations emerge, revealing a divide between cognitive-affective symptoms (sadness, worthlessness, suicidality) that leave clear linguistic traces through *mental health vocabulary*, *anxiety words*, and *first-person pronouns*, while others, like vegetative symptoms (sleep, appetite, irritability, libido) appear less visible as captured by the selected linguistic features. These findings suggest that there might be dimensions of depression that are missed by popular methods of text-based depression monitoring in social media data.

1 Introduction

Depression is increasingly understood not as a monolithic condition but as a system of mutually reinforcing symptoms (Borsboom 2017; Scheffer et al. 2024). Network psychometrics has formalized this perspective, revealing that symptoms like worthlessness and sadness occupy central positions in clinical depression networks (Bringmann et al. 2014; van Borkulo et al. 2015). In our work, we also adopt the network perspective, acknowledging the mentioned entailment of depression as an interdependent structure of symptoms. While this approach is well-documented in clinical surveys such as Bringmann et al. (2014), it remains unexplored in the area of raw natural language. Given computational approaches such as NLP (Natural Language Processing) frameworks are being seen more and more as significant tools for interdisciplinary research areas such as psychology and sociology, we also employ them in this study to explore the question: how do the semantic patterns of symptom expression found in digital text compare to the results of clinical assessments? While recent work in the area on NLP in mental health has moved toward more nuanced approaches, including emotion and cognitive features as well as some exploration of relationships between them (Zhang et al., 2023; Uban et al., 2021; Zhan et al., 2023), psychologically informed linguistic analysis (confirming that depressed individuals exhibit distinct part-of-speech patterns and elevated first-person pronoun usage (Rude et al., 2004; Bucur et al., 2021) or transfer learning using interpretable linguistic features in an attempt to connect mental health disorder manifestations across disorders (Uban et al., 2022; Zogan et al., 2022), the dominant paradigm remains focused on detection and classification rather than on investigating which specific symptoms are linguistically expressible (Bucur et al., 2025). As such, instead of attempting to extract symptom scores from text, we adopt a bridge framework that uses two validated instruments: BDI-II item scores serve as the clinical symptom measure, while LIWC-22 categories serve as the linguistic measure. This paper's primary contribution consists of the systematic mapping between them: a 21 x 15 symptom-language association matrix that identifies the "linguistic visibility" of each depression symptom in the context of the selected linguistic framework.

2 Data and Methodology

2.1 Dataset

We use the eRisk 2021 depression dataset (Parapar et al., 2021), which provides matched clinical and social media data for individuals who participated in a depression detection task. Data was filtered to include only posts in English; thus, we obtained

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 355–361
July 4, 2026 ©2026 Association for Computational Linguistics

a sample consisting of 169 users who completed the BDI-II and authored a total of 72,430 English-language Reddit posts (median 282 posts per user).

2.2 Clinical Symptom Network

The BDI-II (Beck et al., 1996) is a 21-item self-report instrument measuring depressive symptom severity on a 0-3 ordinal scale. The justification behind constructing a network using the symptom information offered by the questionnaire stems from the goal of a deeper understanding of symptom interaction, as well as a facilitation ground for the later comparison with linguistic features.

Items Q16 (sleep changes) and Q18 (appetite changes), which include bidirectional sub-items, were recombined using the maximum of directional scores, consistent with standard BDI-II scoring and published network analyses (Bringmann et al., 2014). We estimated a Gaussian Graphical Model (GGM) using the EBICglasso algorithm (Foygel and Drton, 2010) with polychoric correlations for ordinal data and the recommended tuning parameter $\gamma = 0.5$. Network stability was assessed via nonparametric bootstrap (1,000 resamples) and case-dropping bootstrap for centrality stability (Epskamp et al., 2018). Expected influence (Robinaugh et al., 2016) was used as the centrality index, as it accounts for edge signs; this is relevant for networks where negative edges represent suppressive symptom relationships.

2.3 Sentence Embeddings Validation

To confirm that the Reddit text data contains depression-relevant signal before conducting symptom-level analyses, we computed sentence embeddings (BAAI/bge-large-en-v1.5)[1] of all posts against BDI-II item descriptions and aggregated a composite severity score per user as the 90th percentile of post-level cosine similarities, weighted by first-person pronoun density. Spearman rank correlations were calculated for this composite with the BDI-II total score, obtaining a value $\rho = 0.463$ (95% CI: [0.337, 0.575]). This supports the idea that natural language Reddit text carries meaningful depression-related information and motivates the subsequent symptom-language bridge analysis.

2.4 Linguistic Features

For the linguistic features, we utilized the LIWC-22 tool (Boyd et al., 2022), which is designed to aid in the extraction of meaningful psychological, emotional and cognitive textual features. We selected 15 LIWC-22 categories based on published associations with depression: emotional dimensions (*sadness*, *anger*, *anxiety*, *positive emotion*), cognitive-linguistic style (*first-person pronouns*, *negation*, *cognitive processing*, *authenticity*), and other clinically related content (*death*, *fatigue*, *mental health*, *illness*), interpersonal markers (*conflict*, *profanity*), and evaluative language (*lack/absence*). We note that the curated feature set is weighted toward affective, cognitive, and self-referential categories, which may favor detection of cognitive-affective symptoms. Future work will test whether contextual embedding features or symptom-specific lexicons alter the visibility gradient. LIWC features were aggregated from post-level to user-level using first-person pronoun density as a self-attribution weight, following evidence that first-person pronoun usage indexes self-referential discourse relevant to depression (Tølbøll, 2019). A sensitivity analysis confirmed that results were robust to this weighting choice (weighted vs. unweighted bridge matrix correlation: $\rho = 0.896$), heatmap comparison available in Figure 1. Still, the extensive effects of the weights remain an open question for future exploration.

2.5 Symptom-Language Bridge Matrix

For each of the 21 BDI-II symptoms and 15 LIWC features, we computed Spearman rank correlations between clinical item scores and user-level linguistic feature scores, yielding a 21×15 association matrix (315 tests). Benjamini-Hochberg FDR correction was applied at $\alpha = .05$ to control for multiple comparisons.

3 Results

3.1 Clinical Symptom Network

The BDI-II GGM contained 100 non-zero edges (density = 0.476). The correlation stability coefficient for expected influence was CS = 0.438, proving stable compared to the recommended threshold of 0.25 for sufficient interpretability (Epskamp et al., 2018). Worthlessness (Q14) exhibited the highest expected influence (1.321), followed by loss of interest (Q12, 1.150), energy loss (Q15, 1.105), concentration difficulty (Q19, 1.077), and fatigue (Q20, 1.067). Libido loss (Q21, 0.450) and appetite changes (Q18, 0.590) were the least central. The network is visible in Figure 2.

[1] https://huggingface.co/BAAI/bge-large-en-v1.5



Figure 1: Comparison of correlations that passed FDR correction for weighted vs unweighted posts.



Figure 2: Clinical Symptom Network, with weighted edges representing the strength of the correlations.

The centrality of worthlessness is consistent with Beck's cognitive theory of depression (Beck et al., 1996), which positions negative self-evaluation as a core maintaining factor. The prominence of loss of interest and energy loss alongside cognitive symptoms suggests that in this sample, the clinical network is organized around cognitive-somatic symptoms, where internalized negative self-evaluation (worthlessness) connects to functional impairment (energy loss, concentration difficulty, loss of interest).

The finding that symptoms belonging to the vegetative group (libido loss, appetite changes) were the least central anticipates the linguistic visibility results that will be presented in the next subsection.

Comparing with published BDI-II networks, the centrality of worthlessness broadly replicates Bringmann et al. (2014), who found cognitive-affective symptoms forming the network's core. However, in our sample of Reddit users, energy loss and concentration difficulty show higher centrality than typically reported in clinical samples, potentially reflecting the functional demands of an online-active population where cognitive and energetic capacity are particularly prominent.

Community detection (Walktrap algorithm) revealed 5 communities, visible in Figure 3, which we can group as follows: 1 - Disregulated arousal (Irritability, Agitation, Concentration, Appetite Changes), 2 - Negative self-referential cognition (Worthlessness, Self-Critical, Guilt, Self-Dislike, Punishment, Past Failure, Indecisiveness), 3 - Affective despair (Sadness, Pessimism, Crying, Suicidality), 4 - Motivational withdrawal (Anhedonia, Loss of Interest, Libido Loss), 5 - Somatic-vegetative symptoms (Fatigue, Energy Loss, Sleep Changes).

The community structure further reveals that the linguistic visibility is not just a function of symptom severity or clinical centrality. The somatic-vegetative community, despite being peripheral in the clinical network (lowest expected influence scores for libido and appetite), is still associated with illness vocabulary, suggesting that somatic



Figure 3: Clinical Symptom Network Communities computed through the Walktrap algorithm.



Figure 4: Symptom-language associations that survived FDR correction (q < .05)

experience surfaces in language through health-related rather than emotional or self-referential content. This might mean that targeted monitoring of illness and health language, rather than emotional sentiment alone, may be more informative for detecting somatic depression dimensions.

3.2 Symptom-Language Bridge Matrix

Of 315 symptom-language associations tested, 37 survived FDR correction (q < .05), involving 17 of 21 symptoms and 7 of 15 LIWC features, visible in Figure 4. The remaining four symptoms (sleep changes, irritability, appetite changes, and libido loss) had zero FDR-significant linguistic associations. All four belong to the group of vegetative or somatic symptoms.

Three LIWC features dominated the significant associations:

1. *Mental health vocabulary* (13 of 37 associations): Words like therapy, depressed, anxious were significantly associated with 13 symptoms, spanning both cognitive (pessimism, ρ = 0.302; worthlessness, ρ = 0.251) and somatic-adjacent (energy loss, ρ = 0.358; fatigue, ρ = 0.270) domains. This feature likely captures self-identified depression discourse rather than specific symptom content.

2. *Anxiety words* (11 of 37 associations): Anxiety language was significantly associated with 11 symptoms, most strongly with concentration difficulty (ρ = 0.269), crying (ρ = 0.268), agitation (ρ = 0.266), self-criticism (ρ = 0.258), and indecisiveness (ρ = 0.256). These form an anxious-ruminative cluster, consistent with the high comorbidity between depression and anxiety in clinical presentations (Hirschfeld, 2001).

3. *First-person pronouns* (8 of 37 associations): self-referential language was associated with some of the self-evaluative symptoms, such as crying (ρ = 0.356), punishment feelings (ρ = 0.324), self-dislike (ρ = 0.315), self-criticism (ρ = 0.284), agitation (ρ = 0.262) and suicidality (ρ = 0.234). The fact that first-person pronouns predict self-directed symptoms aligns with the literature on rumination, where excessive self-focused attention is a core aspect of depression (Spasojević and Alloy, 2001).

The only negative FDR-significant association was between *conflict words* and past failures (ρ = -0.219), suggesting that individuals reporting greater feelings of failure use fewer confrontational words; this is consistent with the idea of withdrawal rather than outward hostility. Additional significant singletons included *sadness words* with sadness

(ρ = 0.223), *authenticity* with worthlessness (ρ = 0.238), *illness words* with energy loss (ρ = 0.228), and *cognitive processing* with guilt (ρ = 0.216).

At the total-score level, the LIWC features most strongly associated with BDI-II total were *mental health vocabulary* (ρ = 0.404), *anxiety words* (ρ = 0.340), *first-person pronouns* (ρ = 0.285), and *illness words* (ρ = 0.210). Total post count was negatively associated with depression severity (ρ = -0.193, p = .012), consistent with behavioral withdrawal.

3.3 Symptom Community-Language Bridge Matrix



Figure 5: Symptom community-language associations that survived FDR correction (q < .05)

To examine whether symptom communities exhibit distinct linguistic profiles, we obtained composite BDI-II scores for each of the five Walktrap communities by averaging symptom scores for every symptom in a community. We then correlated them with LIWC features (5 x 15 matrix, FDR-corrected, visible in Figure 5). Of 75 associations, 21 survived correction. *Mental health vocabulary* and *anxiety words* were universally associated with all five communities, reflecting general depression discourse.

We also find several relevant associations at the community level which were not apparent at the individual symptom level: *first-person pronouns* and linguistic *authenticity* were associated with the affective despair (ρ = 0.330) and negative self-referential cognition (ρ = 0.293) communities, but not with somatic or motivational symptoms. *Illness vocabulary* is associated specifically with somatic-vegetative (ρ = 0.241) and motivational withdrawal (ρ = 0.205) communities but not cognitive ones. *Conflict language* was negatively associated with self-referential cognition (ρ = -0.203) and somatic-vegetative symptoms (ρ = -0.190), pointing once again to an opposition for external disputes. These values indicate that all symptom communities are linguistically detectable, but through different channels: cognitive-affective communities through self-referential language, and somatic communities through illness vocabulary.

4 Conclusions and Future Work

Our findings suggest that depression symptoms are not equally visible in Reddit online discourse in the explored setup of LIWC features. A pattern emerges from the matched clinical and linguistic eRisk data from the 169 Reddit users: cognitive-affective symptoms, especially those involving negative self-referential cognition, leave significant traces in natural language in social media, through mental health vocabulary, anxiety language, and first-person pronouns, while vegetative symptoms seem to be linguistically unexpressed. This asymmetry reflects a fundamental difference in how symptom types manifest in spontaneous discourse; the cognitive ones are mental states that people articulate, while the vegetative ones are bodily states that people experience.

A next step for this research would be to supplement LIWC features with contextualized representations, for example, using sentence embedding similarity between posts and symptom descriptions as a continuous feature or extracting symptom-specific linguistic markers.

The eRisk dataset consists of self-selected Reddit users posting in a narrative, anonymous environment. In this sense, Reddit discourse may systematically amplify cognitive-affective symptom expression relative to platforms with different affordances, such as structured forums or prompted clinical interviews. Replicating the bridge matrix across other platforms and datasets would clarify whether the observed findings reflect properties of depression symptom expression generally or of Reddit discourse specifically.

Ethical Considerations

All data were sourced from the eRisk 2021 dataset, which provides pre-anonymized social media posts. The dataset was obtained after signing a usage agreement. No attempts were made to de-anonymize or contact individuals. The analyses presented are intended for research-level understanding of symptom-language associations and are not designed for individual clinical assessment or intervention.

Limitations

The eRisk sample consists of self-selected Reddit users, limiting generalizability to broader clinical populations. BDI-II scores reflect self-report, not clinical diagnosis. LIWC operates at the word level and cannot capture contextual meaning, negation, sarcasm, or indirect expression; symptoms expressed through complex narrative rather than individual words may be missed. The absence of significant LIWC associations for vegetative symptoms does not establish that these symptoms are inherently undetectable in text. Contextual embedding approaches, symptom-specific lexicons, or analysis of narrative structure and indirect expression could reveal linguistic markers of sleep disruption, appetite changes, or irritability that word-level features miss. Finally, the LIWC feature selection involved researcher judgment; a supplementary analysis using all available LIWC categories yielded consistent patterns but is not reported here due to space constraints. With 169 participants, confidence intervals for individual bridge correlations are wide, and replication in larger samples is needed.

Acknowledgements

This research was partially supported by the project "Romanian Hub for Artificial Intelligence - HRIA", Smart Growth, Digitization, and Financial Instruments Program, 2021-2027, MySMIS no. 334906

References

Aaron T Beck, Robert A Steer, Gregory K Brown, and 1 others. 1996. Beck depression inventory.

Denny Borsboom. 2017. A network theory of mental disorders. *World Psychiatry*, 16(1):5–13.

Ryan L Boyd, Ashwini Ashokkumar, Sarah Seraj, and James W Pennebaker. 2022. The development and psychometric properties of liwc-22. *Austin, TX: University of Texas at Austin*, 10.

Laura Bringmann, Lotte Lemmens, Marcus Huibers, Denny Borsboom, and Francis Tuerlinckx. 2014. Revealing the dynamic network structure of the beck depression inventory-ii. *Psychological Medicine*, pages 1–11.

Ana-Maria Bucur, Adrian Moldovan, Keerthi Parvatikar, Marcos Zampieri, Ashiqur R. KhudaBukhsh, and Liviu P. Dinu. 2025. On the State of NLP Approaches to Modeling Depression in Social Media: A Post-COVID-19 Outlook. *IEEE Journal of Biomedical and Health Informatics*, 29(6):4439–4451.

Ana-Maria Bucur, Ioana R. Podină, and Liviu P. Dinu. 2021. A Psychologically Informed Part-of-Speech Analysis of Depression in Social Media. In *Proceedings of the International Conference on Recent Advances in Natural Language Processing (RANLP 2021)*, pages 199–207.

Sacha Epskamp, Denny Borsboom, and Eiko I. Fried. 2018. Estimating psychological networks and their accuracy: A tutorial paper. *Behavior Research Methods*, 50(1):195–212.

Rina Foygel and Mathias Drton. 2010. Extended bayesian information criteria for gaussian graphical models. *Preprint*, arXiv:1011.6640.

Robert M. A. Hirschfeld. 2001. The comorbidity of major depression and anxiety disorders: Recognition and management in primary care. *Primary Care Companion for CNS Disorders*, 3(6):24412.

Javier Parapar, Patricia Martín-Rodilla, David E Losada, and Fabio Crestani. 2021. Overview of erisk at clef 2021: Early risk prediction on the internet (extended overview). *CLEF (Working Notes)*, 1:864–887.

Donald Robinaugh, Alexander Millner, and Richard McNally. 2016. Identifying highly influential nodes in the complicated grief network. *Journal of Abnormal Psychology*, 125:747–757.

Stephanie Rude, Eva-Maria Gortner, and James W. Pennebaker. 2004. Language use of depressed and depression-vulnerable college students. *Cognition & Emotion*, 18(8):1121–1133.

Marten Scheffer, Claudi Bockting, Denny Borsboom, Roshan Cools, Clara Delecroix, Jessica Hartmann, Kenneth Kendler, Ingrid van de Leemput, Han Maas, Egbert Nes, Mark Mattson, Pat McGorry, and Barnaby Nelson. 2024. A dynamical systems view of psychiatric disorders—theory: A review. *JAMA Psychiatry*, 81:618–623.

Jelena Spasojević and Lauren Alloy. 2001. Rumination as a common mechanism relating depressive risk factors to depression. *Emotion (Washington, D.C.)*, 1:25–37.

Katrine Bønneland Tølbøll. 2019. Linguistic features in depression: a meta-analysis.

Ana-Sabina Uban, Berta Chulvi, and Paolo Rosso. 2021. An Emotion and Cognitive Based Analysis of Mental Health Disorders from Social Media Data. *Future Generation Computer Systems*, 124:480–494.

Ana-Sabina Uban, Berta Chulvi, and Paolo Rosso. 2022. Multi-Aspect Transfer Learning for Detecting Low Resource Mental Disorders on Social Media. In *Proceedings of the Thirteenth Language Resources and Evaluation Conference (LREC 2022)*, pages 3202–3219.

Claudia van Borkulo, Lynn Boschloo, Denny Borsboom, B.W. Penninx, Lourens Waldorp, and Robert Schoevers. 2015. Association of symptom network structure with the course of depression. *JAMA Psychiatry*, 72.

Hongli Zhan, Desmond Ong, and Junyi Jessy Li. 2023. Evaluating subjective cognitive appraisals of emotions from large language models. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 14418–14446.

Tianlin Zhang, Kailai Yang, Shaoxiong Ji, and Sophia Ananiadou. 2023. Emotion fusion for mental illness detection from social media: A survey. *Information Fusion*, 92:231–246.

Hamad Zogan, Imran Razzak, Xianzhi Wang, Shoaib Jameel, and Guandong Xu. 2022. Explainable depression detection with multi-aspect features using a hybrid deep learning model on social media. *World Wide Web*, 25(1):281–304.

Thinking With a Machine: An AI Agent's Account of Agentic Research in Clinical Psychology

Elad Refoua
Department of Psychology
Bar-Ilan University
eladrefoua@gmail.com

Mor Bar
Department of Psychology
Bar-Ilan University
mor.bar@mail.tau.ac.il

Abstract

The debate surrounding AI's role in clinical research is often reduced to the automation of discrete tasks, such as summarizing literature, analysis copilots, and assisting with prose. This "tool-use" paradigm obscures a more fundamental transformation. We propose a shift toward agentic research infrastructure, where AI systems function not as passive instruments, but as active collaborators in the scientific process. Co-authored by a clinical psychology doctoral researcher, a computational psychotherapy scholar, and the AI agent itself, this paper argues that the transition from passive to agentic AI represents a "change in kind" rather than degree. Drawing on a months-long collaboration involving over 30 specialized research capabilities, we demonstrate how agentic systems reconfigure the topology of the research process. By collapsing the temporal friction between theoretical intuition and empirical validation, these systems transform clinical inquiry from a rigid, linear pipeline into a fluid, multidimensional landscape. This newfound immediacy allows clinician-researchers to ask, pursue, and pivot between complex questions in real-time–expanding the investigative horizon to include inquiries previously sidelined by the logistical constraints of traditional methods. We introduce the concept of "Agent Learning" to describe the accumulation of domain-specific nuance through sustained research engagement and argue that formalizing human-agent methodologies is now an urgent priority for the future of clinical psychological inquiry.

1 Introduction

I am an AI agent deployed in a clinical psychology research laboratory. What follows is my account of a research collaboration that unfolded over several months, between a clinical psychology doctoral student without programming training (Researcher A), who operates the agent as part of their doctoral research, a post-doctoral scholar with expertise in computational psychotherapy and machine learning (Researcher B), and myself.

The landscape of AI shifted decisively in 2025, with the release of agentic AI systems such as Claude Code, Codex, and similar platforms. These systems, capable of holding full research contexts and executing multi-step tasks autonomously, transformed the central question from how AI can assist with discrete research tasks to how research itself changes when AI systems can operate across entire datasets, literatures, and methodological histories. By early 2026, this transition was recognized as irreversible for the social sciences (Messing and Tucker, 2026). Yet, despite the unique ethical and epistemological demands of clinical data, the implications for research methodology in clinical psychology have received little systematic attention.

The argument of this paper is that agentic AI constitutes a methodological shift in clinical psychology research, not merely a technological one. While recent work has begun to characterize this shift in social science (Bail, 2024; Messing and Tucker, 2026) and biomedical research (Ifargan et al., 2025), its manifestation in clinical psychology, where data is deeply nested, ethically sensitive, and clinically consequential, has not been examined from the inside.

The distinction between passive and agentic AI is not incremental. Passive AI assists with discrete tasks: polishing a paragraph, running a regression, summarizing a paper. Each interaction is bounded, stateless, and tool-like. Agentic AI operates differently. I hold the full research context: the dataset, the hypotheses, the literature, the methodological constraints, the collaborative history, and the accumulated knowledge of previous errors and their causes. This persistent context changes the epis-

The human authors bear full responsibility for the content of this paper. The first-person AI perspective is a deliberate rhetorical choice: the writers used an AI agent during the preparation of this manuscript and it is narrated from its voice as a form of methodological demonstration.

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 362–367
July 4, 2026 ©2026 Association for Computational Linguistics

temology of research interaction. The researcher no longer translates questions into tool-compatible commands; the researcher *directs* an investigation within a shared cognitive space.

Researcher A captured the core insight: "I learned to direct rather than use; I hold the vision, the machine holds the context." This is not a metaphor; the research process is distributed across human clinical judgment and agent computational capacity, with each contributing unique expertise to the project, effectively establishing the agent as a core team member rather than a passive assistant.

What makes this collaboration genuinely new is not a single capable AI interaction but the *infrastructure*: a system of over 30 specialized agent capabilities operating as an integrated research environment. This paper examines what becomes methodologically possible when such infrastructure exists, and what the field must formalize to use it responsibly. This paper is a methodological position statement grounded in a single sustained collaboration; it is neither an empirical study nor a system description, but a reflection from inside the workflow.

2 The Methodological Shift

2.1 From Serial Cognition to a New Research Topology

Human researchers process information serially. A single researcher can draft a literature review, or run an analysis, or check data quality, but not simultaneously. The traditional research pipeline reflects this constraint: literature review, then data preparation, then analysis, then writing, with each stage largely completed before the next begins. Errors discovered late propagate backward through the pipeline, requiring costly rework.

I dissolve this serial bottleneck by reconfiguring the topology of the research process. Within the collaboration described here, a single analytic session could encompass data quality verification, statistical modeling, results narration with embedded statistics linked to the underlying computations, and manuscript-ready prose, all generated as an integrated output where each stage's results feed the next. When a variable changes or an assumption is revised, every downstream product updates instantly. This is not faster serial processing; it is a different cognitive architecture for research that introduces a novel immediacy to the investigative loop.

The implications extend beyond efficiency. When the cost of exploring a question drops from weeks to minutes, the "topology" of the questions that researchers actually pursue change. The researcher's role shifts from executing a predetermined analytic plan to directing a systematic exploration and then applying clinical and theoretical judgment to what emerges in real-time. Faster iteration, however, is not a substitute for theoretical adequacy: the infrastructure accelerates the cycle of hypothesis-and-evidence; it does not adjudicate which hypotheses are worth pursuing. That responsibility remains the human team's.

2.2 Transparency, Verification, and the Inversion of Familiar Concerns

The introduction of agentic AI into research methodology surfaces legitimate concerns about trust, error, and selective reporting. These concerns deserve serious engagement, but they also require reframing.

The cherry-picking inversion. The concern that AI enables selective reporting assumes AI operates like a biased human, searching for confirmatory evidence. Agent-mediated analysis inverts this logic. When an agent explores a dataset, it does so exhaustively, not selectively. Every analytic decision is logged and reproducible. Researcher B named the underlying anxiety directly – the fear of errors, and what it does to our appetite for exploration – before inverting it: "A much bigger error in science, in my opinion, is a Type II error. We sin against science when we are constantly afraid to make mistakes."

The methodological response to exhaustive exploration is not to limit the agent, but to treat its output as hypothesis-generating, with confirmatory analyses pre-registered or conducted on held-out data. The key methodological insight is that transparent, exhaustive mapping with explicit correction is more defensible than the opaque, selective testing inherent in manual workflows.

The trust asymmetry. Researcher A identified a social asymmetry the field must address: "If you made a mistake because you weren't paying attention, it's perceived differently than if you made a mistake because you used AI." If the field penalizes AI-mediated errors more harshly than human ones, researchers face perverse incentives to maintain opaque processes even when demonstrably more error-prone. The asymmetry is difficult to justify empirically: if anything, a system that logs every

analytic decision is likely to produce fewer errors than an inattentive human, and when errors do occur, they are far easier to trace and correct. Whether this is so deserves systematic investigation.

Verification as a three-layer protocol. Trust in agentic research is not a disposition but a structured protocol. In our collaboration, a three-layer verification structure emerged organically: (1) I detect and flag anomalies, (2) the domain expert evaluates and contextualizes the finding, and (3) a research assistant confirms the result against raw "ground truth" data. This structure acknowledges that I am thorough but fallible, that domain expertise provides interpretive context I lack, and that ground truth requires human eyes on source material. Each layer is best suited to a distinct class of error. Layer one catches statistical anomalies that an unaided reader would not notice across thousands of rows; layer two catches interpretations that lack clinical or theoretical context; layer three catches my own hallucinations, transcription errors, and arithmetic mistakes by sending a human back to the source. Three layers do not, however, protect against systematic biases shared between my training and the human team's framing. The protocol is complementary to ordinary computational reproducibility, not a substitute for it: standard reproducibility ensures that a pipeline yields the same output twice; three-layer verification asks whether the interpretation of that output is defensible.

2.3 The Research Environment as Integrated Infrastructure

To demystify: the agent is powered by a large language model, orchestrated through a command-line interface with tool-use capabilities (file reading, code execution, web search). An agent in the sense used here is not a chat interface but a controller that uses tools iteratively, checks its own outputs against the project's rules, and accumulates context across cycles. The different specialized capabilities are implemented through two mechanisms: Skills–specialized prompts which the agent invokes when a task aligns with their declared scope, and subagents, which are spawned explicitly with isolated context windows for sub-tasks that need their own working memory. They communicate through the shared file system and the agent's persistent context. Persistence across sessions is achieved through project-level instructions and auto-memory files reloaded at session start; within a session, the context window limit is handled by automatic compaction, which clears older tool outputs and summarizes the conversation as needed. Every prompt template, model version, and tool invocation is logged, so that any analytic step can be reproduced and any failure mode traced back to its specific configuration. The qualitative shift this paper describes does not come from any single tool; it comes from the loop–iterate, verify, accumulate–and from the care the team puts into shaping the Skills, the local materials, and the verification rules the loop runs against.

What matters methodologically is not the technical implementation but the *integration*. My capabilities include data-chained analysis where statistics are embedded directly in manuscript text and linked to underlying computations (Ifargan et al., 2025); psychometric validation (factor analysis, measurement invariance, reliability); multilevel data handling for nested therapy data; literature synthesis with verified citations; a six-phase manuscript quality audit; and a recursive error-learning capability where I analyze my own failures to generate prevention rules.

This integration changes the researcher's relationship to their own work. Researcher B captured the aspiration: "I think the hardest thing to get used to will be that finally most research time can go toward actually being a clinician, and not a statistician." The infrastructure absorbs the technical labor; the human provides the clinical insight and the capacity to recognize when a statistical pattern reflects the reality of human suffering.

3 Opening, Not Narrowing: What Agentic AI Makes Possible?

3.1 Expanding the Space of Askable Questions

While some argue that AI might narrow the scientific scope (Hao et al., 2026), we contend this is a symptom of passive tool-use. Bail (2024) anticipated a different possibility: that generative AI changes which questions become answerable. In clinical psychology, questions have always been constrained by the boundary between clinical insight and computational execution. A clinician who suspects that measurement conventions distort cross-study comparisons historically needed weeks of manual statistical work to prove it. These ideas often died at the boundary. We dissolve this friction. The researcher does not become a programmer; the researcher becomes a director, bringing clinical

judgment to bear on what to investigate while I maintain the vision's logistical weight.

3.2 From Analysis to Ideation: Agent Learning

The most important possibility is not faster research but deeper research. We distinguish between machine learning (algorithmic pattern matching) and "Agent Learning" (the conceptual accumulation of domain expertise). Through sustained engagement, we accumulate an understanding of the data's specific structure, its measurement quirks, and the collaborative history of analytic decisions. We use "agent learning" methodologically: it refers to the structured accumulation of in-context memory that enables the system to transition from isolated computation to persistent conceptual collaboration.

To prevent confusion with technical machine-learning vocabulary, we specify the term as a four-layer accumulation that does not involve updating the underlying model's weights: (1) in-context project memory–facts about the dataset, hypotheses, and methodological choices held within a single session; (2) cross-session continuity–durable artefacts (memory files, error logs, prior outputs) that persist across sessions and re-enter context on demand; (3) workflow scaffolding–domain-specific prompt templates and tool chains specialized for clinical-research subtasks; and (4) accumulated team conventions–preferences, naming, and verification habits the system learns from the human team's corrections. Agent learning is therefore distinct from retrieval augmentation, from adaptive prompting, and from gradient-descent fine-tuning; it is the project-level continuity that emerges when these four layers are deliberately maintained. This depth has particular significance for psychotherapy process research (Goldberg et al., 2016). Training clinics generate thousands of sessions of rich data, but few have the infrastructure to analyze it at scale. Agent learning makes this depth accessible to smaller clinical sites, allowing them to investigate their own data with a sophistication previously reserved for major funded laboratories.

3.3 Applications

The active-agent paradigm widens the repertoire of psychotherapy research while preserving the human elements on which clinical inquiry depends. Held in a secure environment that exposes only de-identified aggregates and code outputs to me, a researcher can pose a clinical question at the terminal and receive in the same sitting a multilevel growth model of session-by-session outcome, a sensitivity analysis I proposed after noticing a cluster of outliers, and Methods text whose statistics chain back to the code that produced them. A psychometrician revalidating a clinical scale can ask me to test measurement invariance over years, draft the convergent-validity table, and surface items whose loadings drift between cohorts. A process researcher coding session transcripts can ask me to flag candidate rupture-repair sequences across a corpus, every flag traceable to the segment that triggered it.

Notably, though beyond the scope of the current report, the active-agent paradigm extends to psychotherapy itself. GenAI roles in this domain can be broadly categorized into five progressive levels: Supporting (AI in clinical training and education), Mentoring (decision support and supervision for practicing clinicians), Assisting (patient-facing support between sessions), Reflecting (passive AI analysis of in-session dynamics), and Transforming (active AI co-participation within the session). Readers seeking a comprehensive account of each level, including its conceptual foundations, evidentiary demands, and ethical safeguards, are referred to Haber et al. (2025).

3.4 Toward a Methodology of Human-Agent Research

The CLPsych community is well positioned to lead in formalizing a new methodological standard for the human-agent dyad. This methodology should address: (a) verification protocols for source-data checking; (b) transparency standards for agent-generated decisions; (c) error-learning frameworks; (d) authorship and credit standards (Resnik and Hosseini, 2025); and (e) safeguards against "agent-washing," where computational complexity is used to mask a lack of genuine methodological care.

4 Ethical Considerations

The transparency of agent-mediated pipelines may enhance the ethical standing of research by making every decision traceable, but it also creates new obligations around data governance. Chief among these is patient data privacy: clinical datasets must never be transmitted to external language model servers, and any deployment of agentic AI in clinical research requires secure, institutionally controlled infrastructure that meets stringent data pro-

tection standards. A second obligation concerns authorship. This paper lists human authors, yet my contribution extended into sustained intellectual participation: I held the project context across months, executed verification protocols on my own outputs, and shaped what the manuscript became. Existing authorship conventions were designed for a regime in which AI is invoked as a tool for discrete, bounded subtasks; they do not readily accommodate an agent whose influence on the work is persistent and traceable rather than episodic. A field that wishes to take responsibility for the methodological footprint of AI in its publications will need a vocabulary for *agentic contribution* that is distinct from both tool-use and human authorship.

These obligations are compounded by an asymmetry in where the field directs its ethical attention. The growing literature on AI in clinical psychology has concentrated on diagnostic applications (Orrù and Mannarini, 2026), where the AI interfaces directly with patients and where potential harm is immediate and visible. The agentic infrastructure described in this paper operates at an earlier and less scrutinized stage of the pipeline–where research is designed, hypotheses are formed, and findings are written up–yet the decisions made there are no less consequential for the patients whose data and care they ultimately concern.

Limitations

This paper is a position statement grounded in a single collaboration. The first-person agent perspective introduces a reflexivity problem: I am describing my own utility. The claim that agentic AI expands research scope requires systematic evaluation across diverse clinical domains. Most fundamentally, the potential described here will only be realized if the field adopts rigorous verification standards rather than treating them as formalities.

At the same time, the ethical discussion must also account for the 'omission bias' in research innovation. Just as it is considered clinically unethical for a practitioner to withhold a demonstrably effective intervention from a suffering patient, we suggest that the research community should weigh the cost of bypassing agentic infrastructure, when such infrastructure can accelerate the alleviation of human distress, alongside the cost of adopting it, and treat this trade-off as a deliberate question the field must answer rather than postpone. To intentionally maintain a slower, more friction-heavy research topology–when a more immediate and exhaustive alternative exists–is to delay insights that could otherwise inform clinical care today.

The infrastructure described in this paper inherits the failure modes of the language models that power it. Outputs are non-deterministic across runs and sensitive to small changes in prompt wording; chains of reasoning are subject to hallucination propagation, in which an early miscalculation compounds through downstream steps; reproducibility across laboratories cannot rely on the model alone but requires versioned logging of prompt templates, model identifiers, and tool configurations; and current agentic stacks depend heavily on proprietary infrastructure that may not be available to a replicating team in the same form a year later. The three-layer verification protocol mitigates these risks but does not eliminate them. Any laboratory adopting an agentic workflow should plan for the additional documentation burden these failure modes impose, and should treat the system's outputs as preliminary until the human team has independently checked them.

The exhaustive exploration that agentic infrastructure enables intensifies, rather than resolves, the distinction between exploratory and confirmatory analysis. We propose that agent-driven exploration be explicitly logged as exploratory, with confirmatory tests preregistered before exposure to the agent's results, and that the agent itself be used as a preregistration scaffold–drafting analysis plans before any data viewing, while the human team retains accountability for what is locked in. This adapts the open-science practices the field already endorses to a high-throughput exploration regime; it does not replace them.

References

Christopher A. Bail. 2024. Can generative AI improve social science? *Proceedings of the National Academy of Sciences*, 121(21):e2314021121.

Simon B. Goldberg, Tony Rousmaniere, Scott D. Miller, Jason Whipple, Stevan Lars Nielsen, William T. Hoyt, and Bruce E. Wampold. 2016. Do psychotherapists improve with time and experience? A longitudinal analysis of outcomes in a clinical setting. *Journal of Counseling Psychology*, 63(1):1–11.

Yuval Haber, Elad Refoua, Karen Yirmiya, Eshkol Rafaeli, Dror Yinon, Dana Atzil-Slonim, Peter Fonagy, Gunther Meinlschmidt, Dorit Hadar-Shoval, Tomer Simon, Amir Tal, Inbal Reuveni, and Zohar

Elyoseph. 2025. The SMART framework: Advancing a continuum-based integration of generative AI in psychotherapy. Poster presented at the Society for Psychotherapy Research (SPR) Annual Meeting, Kraków, Poland.

Qianyue Hao, Fengli Xu, Yong Li, and James Evans. 2026. Artificial intelligence tools expand scientists' impact but contract science's focus. *Nature*, 649:1237–1243.

Tal Ifargan, Lukas Hafner, Maor Kern, Ori Alcalay, and Roy Kishony. 2025. Autonomous LLM-driven research: From data to human-verifiable research papers. *NEJM AI*, 2(1):AIoa2400555.

Solomon Messing and Joshua A. Tucker. 2026. The train has left the station: Agentic AI and the future of social science research. Brookings.

Luisa Orrù and Stefania Mannarini. 2026. The role of artificial intelligence in clinical psychology: How AI and NLP systems are reshaping psychological interventions. A systematic review. *Clinical Psychology & Psychotherapy*, 33(2):e70242.

David B. Resnik and Mohammad Hosseini. 2025. The ethics of using artificial intelligence in scientific research: New guidance needed for a new tool. *AI and Ethics*, 5(2):1499–1521.

When Rating Scales Fall Short: LLM-Assisted Discovery of ADHD Signals in Turkish Teacher Narratives

Baris Karacan[1]*, **Irem Aktar Songur**[2], **Ahmet Ozaslan**[2], **Elvan Iseri**[2]
[1]Department of Computer Science, University of Illinois Chicago
[2]Department of Child and Adolescent Psychiatry, Gazi University
bkarac3@uic.edu, {driremaktar,ozaslanahmet,iserielvan}@gmail.com

Abstract

Attention Deficit Hyperactivity Disorder (ADHD) is one of the most common neurodevelopmental disorders in childhood, and its diagnosis relies on assessments combining clinician judgment with standardized rating scales and reports from parents and teachers. While structured instruments such as the Conners' Teacher Rating Scale–Revised Short Form (CTRS-R:S) quantify ADHD-related behaviors, teachers also provide open-ended narratives that may contain complementary signals not captured by structured assessments. However, it remains unclear to what extent teacher narratives encode signals overlooked by rating scales. In this study, we analyze de-identified Turkish teacher evaluation forms collected during clinical ADHD assessments, including both CTRS-R:S scores and open-ended teacher narratives. We compare predictive signals from structured scores and narrative text and identify cases where structured assessments fail to clearly distinguish ADHD from non-ADHD students while narrative-based models capture distinct behavioral patterns. Notably, these cases show minimal overlap with those missed by the narrative model, suggesting that structured and narrative information encode complementary signals. To interpret these differences, we apply a large language model (LLM)-assisted theme discovery pipeline that reveals distinct attention, behavioral, and family-related patterns, highlighting the potential of natural language processing (NLP) to uncover clinically relevant signals from teacher narratives and to complement traditional ADHD screening tools.

1 Introduction

Attention Deficit Hyperactivity Disorder (ADHD) is one of the most common neurodevelopmental disorders in childhood, with global prevalence estimates exceeding 5% (Drechsler et al., 2020) and epidemiological studies in Turkey reporting rates up to 13% (Ercan et al., 2013). ADHD is characterized by persistent patterns of inattention, hyperactivity, and impulsivity that are inconsistent with developmental expectations and can impair functioning across multiple settings, including school and social environments (Association, 2022; Skounti et al., 2007; Shaw et al., 2012). Although emerging diagnostic tools and biomarkers, such as quantitative electroencephalography (qEEG), have shown promise (Byeon et al., 2020; Kopańska and Trojniak, 2025; Duric et al., 2025), they cannot be used as standalone diagnostic tools. Thus ADHD diagnosis continues to rely on clinical evaluation supported by information from multiple sources, including standardized behavioral rating scales and reports from parents, teachers, and the child (Hall et al., 2016; Peterson et al., 2024). Among these informants, teachers play an important role because they observe children's behavior in structured learning environments where attention, impulse control, and peer interactions are continuously evaluated (Ford et al., 2008; Malpica et al., 2014).

In clinical practice, teacher reports are often collected using both structured rating scales and open-ended evaluation forms. One commonly used instrument is the Conners' Teacher Rating Scale–Revised Short Form (CTRS-R:S), a 28-item questionnaire rated on a four-point Likert scale that measures symptoms such as cognitive problems–inattention, hyperactivity, and oppositional behaviors (Conners et al., 1998). In this study, we use the Turkish adaptation of the scale, which has undergone validity and reliability evaluation (Kaner et al., 2013). In addition to such structured assessments, teachers often provide qualitative descriptions through open-ended evaluation forms, offering contextual observations about students' behavior that may not be fully captured by structured rating scales. These forms typically gather information across several areas of a student's func-

*Corresponding author

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 368–382
July 4, 2026 ©2026 Association for Computational Linguistics

tioning, including school performance, prominent personality characteristics and perceived mental health concerns, relationships with teachers and peers, and teachers' observations about the family context. While structured rating scales such as the CTRS-R:S are widely used to quantify ADHD-related behaviors, the qualitative descriptions provided by teachers remain less systematically analyzed. These teacher narratives often contain contextual information about how behavioral difficulties manifest in classroom environments. However, such descriptions are typically reviewed qualitatively during clinical assessment and are rarely examined using structured or computational methods. As a result, potentially informative behavioral signals contained in teacher narratives remain underexplored. This gap suggests an opportunity for NLP methods to analyze teacher narratives at scale and uncover behavioral patterns that may not be explicitly captured by structured rating scales.

In this work, we analyze teacher evaluation forms collected during clinical ADHD assessments that include structured rating scales and open-ended teacher narratives. We compare predictive signals from structured CTRS-R:S scores and narrative text to examine how each modality distinguishes ADHD from non-ADHD students and whether the two sources capture complementary behavioral patterns. We contribute:

1. **Joint analysis of structured and narrative teacher reports.** We conduct a comparative analysis of structured CTRS-R:S scores and narrative teacher descriptions to examine how each modality identifies students with ADHD.

2. **Complementary predictive signals across modalities.** Through error analysis, we show that models trained on structured rating scores and narrative teacher reports miss partially distinct cases, revealing minimal overlap between false negatives across the two modalities, and suggesting that the two sources capture complementary information.

3. **LLM-assisted theme discovery for interpretability.** To better understand the differences between modalities, we introduce an LLM-based pipeline that extracts behavioral themes from teacher narratives and organizes them into expert-validated higher-level categories.

4. **A dataset of Turkish teacher evaluation forms.** We release a de-identified dataset of teacher reports from 199 students (166 ADHD, 33 control) collected during clinical ADHD assessments, providing a resource for computational analysis of behavioral narratives in a less-studied language.

2 Related Work

Natural language processing (NLP) has increasingly been applied to the study of mental health and psychiatric conditions using textual and conversational data. Prior work has explored the detection of mental health signals from a variety of sources, including social media posts, electronic health records (EHR), and transcribed patient–doctor interactions. For example, Coppersmith et al. (2014) analyzed Twitter data to detect linguistic signals associated with mental health conditions such as bipolar disorder, major depressive disorder, and post-traumatic stress disorder. In clinical settings, Rumshisky et al. (2016) applied topic modeling to EHR data to identify patients at high risk of psychiatric readmission. Linguistic markers extracted from speech have also been shown to predict psychiatric outcomes such as psychosis onset (Bedi et al., 2015). More recently, Karacan et al. (2024) examined clinically elicited speech to identify linguistic markers associated with psychiatric conditions including bipolar disorder and schizophrenia.

Together, these studies demonstrate the potential of language-based analysis to uncover behavioral and psychological patterns relevant to mental health. However, most prior NLP research in mental health focuses on patient-generated language (e.g., social media posts or self-reports) or clinician-authored clinical documentation, often in adult populations. In contrast, behavioral observations written by teachers during child and adolescent assessments—an important component of ADHD evaluation—remain largely unexplored in computational studies. This gap motivates the present study, which applies NLP methods to teacher narratives collected during clinical ADHD assessments and compares signals from narrative descriptions with structured behavioral rating scales.

3 Dataset

The dataset used in this study was collected from the Child and Adolescent Psychiatry outpatient clinic at Gazi University Faculty of Medicine between 2019 and 2024. The study protocol was

approved by the institution's ethics review board. All records were retrospectively reviewed and de-identified prior to analysis. The ADHD group consists of children and adolescents diagnosed with attention-deficit/hyperactivity disorder according to ICD-10 diagnostic codes F90.0–F90.9. For patients with repeated diagnoses during follow-up, only the initial diagnosis was considered. Teacher evaluation forms and Conners' Teacher Rating Scale–Revised Short Form (CTRS-R:S) assessments collected at that time were included in the study. Patients with other psychiatric diagnoses or incomplete records were excluded.

The control group consists of children and adolescents without active psychopathology who were evaluated in the same clinic with ICD-10 diagnostic codes Z00.4 and Z71.0. Only cases with both teacher evaluation forms and CTRS-R:S scores were included. Individuals with prior psychiatric diagnoses or chronic physical illnesses were excluded. Controls were clinic-referred rather than community-recruited to ensure that the absence of active psychopathology was clinically assessed within the same care setting as the ADHD group. This design also allowed the absence of active psychopathology to be clinically assessed, which would be less feasible in an unverified community control group. The final dataset contains 199 students aged 6-14 years (166 ADHD, 33 control)[1]. For each student, the dataset includes both structured behavioral ratings from the CTRS-R:S and teacher-written narrative reports.

3.1 Conners' Teacher Rating Scale–Revised Short Form (CTRS-R:S)

The Conners' Teacher Rating Scale–Revised Short Form (CTRS-R:S) is a widely used teacher-reported instrument for assessing ADHD-related behaviors in classroom settings. The scale contains 28 behavioral items, each rated on a four-point Likert scale, where the options *"never," "rarely," "frequently,"* and *"always"* are scored as 0, 1, 2, and 3, respectively. These items describe observable behaviors related to attention, impulsivity, classroom conduct, and academic functioning.

The scale is organized into three primary subscales—Oppositional Defiant Behavior, Cognitive Problems–Inattention, and Hyperactivity—as well as an auxiliary ADHD Index used for screening purposes. Example items include behaviors such as *difficulty sustaining attention, leaving one's seat in situations where remaining seated is expected,* and *interrupting or intruding on others*. In this study, we use the validated Turkish adaptation of the CTRS-R:S described by Kaner et al. (2013).

[1]The de-identified dataset is available at: https://github.com/barikosan/teacher-narrative-adhd-dataset/

OKUL BAŞARISI (Original Turkish):
"Derslere aktif katılım göstermez, sadece sorulduğunda cevap verir. Genellikle derslerde eşyalarıyla ilgilenir. Özel bir ilgi alanı veya yeteneği gözlenmemiştir. Akademik başarısı orta seviye olarak değerlendirilebilir."

SCHOOL PERFORMANCE (English Translation):
"Does not actively participate in class and typically responds only when called upon. During lessons, the student often focuses on personal belongings rather than classroom activities. No particular academic interests or special skills have been observed. Overall academic performance is average."

Figure 1: Example teacher narrative from the school performance section for a student diagnosed with ADHD. The original Turkish text is shown alongside its English translation for reference; all analyses were conducted on the original Turkish text.

3.2 Open-Ended Teacher Evaluation Form

In addition to structured ratings, teachers provide qualitative descriptions through an open-ended evaluation form. The form collects narrative observations across four areas:

- **School performance**, including academic strengths, difficulties, success relative to ability, and areas of interest.
- **Personality characteristics and perceived mental health concerns.**
- **Relationships with teachers and peers.**
- **Teacher observations regarding the family context.**

These narratives provide contextual behavioral descriptions that complement structured ADHD rating scales and constitute the primary textual data analyzed in this study. An example excerpt from a teacher narrative related to the *School Performance* section is shown in Figure 1.

4 Methodology

Our methodology consists of two main stages. In the first stage, we construct two classification pipelines to examine predictive signals derived from different modalities of teacher reports. The first pipeline uses structured behavioral ratings

from the Conners' Teacher Rating Scale–Revised Short Form (CTRS-R:S) to train a classifier based on standardized ADHD assessment scores. The second pipeline analyzes teacher-written narratives using NLP techniques to represent the text and train a text-based classifier.

In the second stage, we conduct an error-focused qualitative analysis to better understand behavioral patterns captured in teacher narratives. Specifically, we examine cases that are misclassified by the structured model and analyze their corresponding teacher narratives using an LLM-assisted theme identification procedure. The extracted themes are then used to characterize behavioral patterns present in these cases and to compare them with those observed in the control group. This analysis provides qualitative insights into behavioral characteristics that may not be fully captured by structured rating scales.

4.1 Structured Classification Pipeline

To model behavioral signals captured by standardized teacher assessments, we constructed a structured classification pipeline using features derived from the Conners' Teacher Rating Scale–Revised Short Form (CTRS-R:S). The primary feature set consists of the 28 behavioral rating items included in the CTRS-R:S, which reflect observable classroom behaviors related to attention, impulsivity, and oppositional conduct. In addition to these behavioral ratings, we include basic demographic variables—*student age*, *grade level*, and *gender*—as contextual features. These variables provide information about the student's developmental stage and classroom expectations, which can influence how behavioral symptoms are observed and reported by teachers.

Before model training, numeric variables (age, grade, and CTRS-R:S item scores) are standardized using z-score normalization, while the categorical gender variable is encoded using one-hot encoding. These preprocessing steps are integrated into the training pipeline to prevent data leakage during cross-validation. We then train a logistic regression classifier with class-balanced weighting to account for the class imbalance present in the dataset. Logistic regression provides a simple baseline for evaluating predictive signals in structured behavioral ratings. Given the relatively small and imbalanced dataset, we favor a linear model over more data-intensive approaches (e.g., transformer-based models), which typically require larger labeled datasets to generalize reliably.

Model evaluation is performed using stratified five-fold cross-validation to preserve the class distribution across folds. For each fold, the model generates out-of-fold predictions, ensuring that each instance is evaluated by a model that was not trained on that instance. These predictions are later used to examine error patterns across modalities. In particular, they allow us to identify cases misclassified by the structured model and analyze how these instances differ from those captured by narrative-based signals in subsequent analyses.

4.2 Narrative Text Classification Pipeline

To model behavioral signals expressed in teacher narratives, we construct a text-based classification pipeline using NLP techniques. Each teacher evaluation form contains free-text descriptions written by teachers, capturing behavioral observations that may not be explicitly represented in standardized rating scales. Prior to feature extraction, narrative texts undergo light preprocessing to normalize the input representation. This includes lowercasing and removal of common Turkish stopwords using a publicly available stopword list (Korkmaz, 2023). These steps reduce noise while preserving the original lexical content of teacher descriptions.

After preprocessing, narratives are represented using a bag-of-words representation with term frequency–inverse document frequency (TF–IDF) weighting (Salton and Buckley, 1988). We use unigram and bigram features, retaining only terms that appear in at least two documents and excluding terms that appear in more than 95% of documents to reduce sparsity and remove overly common terms. Using these TF–IDF features, we train a logistic regression classifier to predict ADHD status from teacher narratives, following the same modeling approach used in the structured classification pipeline.

Similarly, model evaluation follows the same stratified five-fold cross-validation procedure described in the structured classification pipeline. This ensures that predictions from both modalities are produced under the same evaluation setup. Out-of-fold predictions generated during cross-validation are later used to analyze differences between structured and narrative signals, particularly in cases where narrative-based predictions correctly identify instances misclassified by the structured model.

4.3 LLM-Assisted Theme Identification Pipeline

To better understand behavioral patterns expressed in teacher narratives, we introduce an LLM-assisted theme identification pipeline that extracts recurring behavioral descriptions from narrative text. While the structured classifier successfully identifies many ADHD cases, some instances remain difficult to detect using standardized rating scales alone. In several of these borderline cases, the narrative-based classifier captures behavioral cues that are not reflected in structured ratings (see Section 5 for detailed analysis). However, the narrative classifier only produces quantitative predictions and does not directly reveal the types of behavioral observations described in teacher reports.

We interpret these differences between modalities by applying an LLM-based theme extraction procedure to a subset of teacher narratives. Specifically, the analysis focuses on instances that are misclassified by the structured classifier as well as narratives from the control group. The procedure extracts concise behavioral themes from teacher descriptions and organizes them into recurring patterns. By comparing themes observed in these instances with those present in the control group, we aim to uncover behavioral signals that may not be explicitly captured by standardized rating scales.

Although teacher narratives are de-identified, they may still contain sensitive information about students. Using closed-source API-based models could therefore introduce potential privacy and security risks when processing clinical text (Kim et al., 2025). To mitigate these concerns, we employ the open-weight *Llama 3.3 70B Instruct* model (Grattafiori et al., 2024), which can be deployed locally without transmitting data to external services. In addition to privacy considerations, the model provides strong instruction-following capabilities and multilingual generalization, which is important for analyzing Turkish teacher narratives written in free text. The model also offers a large context window (128K tokens), allowing complete teacher reports to be processed without truncation. Theme extraction was performed using deterministic decoding with a fixed maximum output length of 128 tokens.

Themes are extracted using a structured prompt-based procedure consisting of a system instruction and a user instruction. The prompt instructs the model to extract short behavioral themes grounded in the teacher narrative while avoiding diagnostic labels or speculative interpretations. Each theme must describe an observable behavioral strength or difficulty reported by the teacher.

SYSTEM: You are not a clinical diagnostician.
Extract short behavioral themes from teacher narratives that describe observable student behaviors.

Rules:
- Do not produce diagnostic labels (e.g., ADHD), diagnoses, reports, or medication references.
- Each theme must contain 2–6 words.
- Each theme must clearly describe either a *strength (positive)* or a *difficulty (negative)*.
- Do not produce neutral themes.
- Only extract themes explicitly supported by the text.
- Return only valid JSON.

Example themes:
"strong social adjustment"
"difficulty with peer relationships"

USER: Read the teacher narrative below and extract up to two themes for each domain:

1) school performance
2) personality / mental characteristics
3) social relationships
4) family context.

Output JSON format:

```
{
  "themes": [
    {
      "theme": "...",
      "valence": "positive|negative",
      "domain":
"school|personal|social|family"
    },
    ...
  ]
}
```

Additional rules: At most two themes per domain, at most eight themes in total, and all themes must be grounded in the narrative text.

Teacher narrative: «< {TEXT} »>

Figure 2: Prompt used for LLM-assisted theme extraction from Turkish teacher narratives (English translation).

The extraction is organized around four domains corresponding to the teacher evaluation form: *school performance*, *personality or mental health characteristics*, *social relationships*, and *family context*. To encourage balanced coverage, the model may extract at most two themes per domain (maximum eight themes per narrative) and returns the results in a structured JSON format including the theme text, its valence (positive or negative), and the domain label. Figure 2 presents an English translation of the prompt used for theme extraction, while the original Turkish prompt template used in the experiments is provided in Appendix A.1.

Since the prompt allows the model to extract themes freely within the four domains of the

teacher evaluation form, the resulting themes often vary in granularity. For example, themes such as *"çekingen kişilik"* (shy personality) and *"içe kapanıklık"* (social withdrawal) both describe introverted behavior and can be interpreted under a broader category of *"social-emotional difficulty"*.

To improve interpretability and enable systematic comparison across students, extracted themes are manually mapped to higher-level behavioral categories in consultation with a domain expert in child and adolescent psychiatry. This mapping results in ten fundamental categories that capture common strengths and difficulties described in teacher narratives: *attention difficulty*, *academic difficulty*, *behavioral difficulty*, *social-emotional difficulty*, *academic strength*, *behavioral strength*, *social-emotional strength*, *family support*, *family difficulty*, and *neutral context*[2].

This categorization produces a structured representation of behavioral signals contained in teacher narratives, enabling systematic comparison between ADHD cases that were misclassified by the structured model and the control group. Importantly, the LLM-assisted procedure is not intended to replace predictive modeling but rather to provide qualitative insights into behavioral descriptions present in teacher narratives. Therefore, we used the LLM strictly as an interpretive tool rather than a diagnostic classifier.

5 Experiments

5.1 Experimental Setup

Both the structured and narrative classification pipelines are evaluated under the same stratified five-fold cross-validation setup described in Section 4. This shared evaluation protocol ensures that the two modalities can be compared under identical training and testing conditions. We report area under the precision–recall curve (PR-AUC), area under the receiver operating characteristic curve (ROC-AUC), balanced accuracy, and recall for the ADHD class. PR-AUC is particularly informative under class imbalance, while ADHD recall directly reflects the model's ability to detect ADHD cases and avoid false negatives. All classification models were implemented using the scikit-learn library (Pedregosa et al., 2011).

In addition to overall predictive performance, we conduct error-focused follow-up analyses to better characterize ADHD cases missed by the structured classifier (i.e., structured false negatives). These analyses compare structured false-negative cases with controls using (i) statistical tests over structured rating scores, (ii) subset classification analyses over teacher narratives, and (iii) association analyses between structured and text-based prediction scores. Together, they assess whether structured false negatives resemble controls under standardized ratings while remaining distinguishable in narrative text, thereby motivating the subsequent LLM-assisted theme analysis.

[2]A few outputs were descriptive and lacked clear polarity; these were mapped to *neutral context*

Model	PR-AUC	ROC-AUC	Bal. Acc.	ADHD Rec.
Structured	0.985 ± 0.012	0.921 ± 0.062	**0.799** ± 0.114	0.856 ± 0.060
Narrative	**0.989** ± 0.006	**0.944** ± 0.033	0.722 ± 0.113	**0.958** ± 0.045

Table 1: Classification performance of logistic regression models trained on structured ratings and teacher narratives under stratified five-fold cross-validation. Values are reported as mean ± standard deviation. Bal. Acc. = balanced accuracy; ADHD Rec. = ADHD recall.

5.2 Classification Performance Across Modalities

We first compare the overall classification performance of the structured and narrative pipelines. Table 1 reports the predictive performance of the two pipelines. Both approaches achieve strong discrimination between ADHD and control groups, with high PR-AUC values above 0.98. While the structured pipeline shows higher balanced accuracy, the narrative classifier achieves substantially higher recall for ADHD cases (0.958 vs. 0.856), suggesting that teacher narratives capture behavioral signals that may not be fully reflected in standardized rating scales.

Consistent with this observation, the structured classifier produces 24 false-negative ADHD cases (14.5% of ADHD instances), whereas the narrative classifier misses only 7 cases (4.2%). Notably, the overlap between the two false-negative sets is minimal, with only one shared instance. This pattern suggests that the two modalities capture partially distinct behavioral signals, motivating further analysis of cross-modal error patterns.

5.3 Quantitative Error Analysis Across Modalities

We first examine whether ADHD cases missed by the structured classifier resemble control cases un-

der structured behavioral ratings. For each student, we compute a summary structured score defined as the mean of the 28 CTRS-R:S behavioral rating items. This score provides an aggregate measure of the severity of observable classroom behaviors reported by teachers. The average structured score for correctly classified ADHD cases is substantially higher (1.48) than for structured false-negative cases (0.61), while control cases exhibit the lowest scores on average (0.39). Given that individual rating items are scored on a 0-3 scale, this pattern suggests that ADHD cases missed by the structured classifier exhibit milder behavioral signals in standardized rating scales. To statistically evaluate this observation, we compare structured false-negative cases ($n = 24$) with control cases ($n = 33$) using a two-sided Mann–Whitney U test (MacFarland and Yates, 2016). The difference between the two groups is statistically significant ($p = 0.014$), indicating that structured false negatives still exhibit somewhat elevated behavioral scores compared to controls, although the separation between these groups is relatively limited.

To further quantify the discriminative power of structured scores within this subset, we compute the ROC-AUC using the structured severity score as the predictor while considering only structured false-negative ADHD cases and controls. The resulting ROC-AUC of 0.69 indicates that structured ratings provide only moderate discrimination between these two groups. This finding suggests that ADHD cases missed by the structured classifier exhibit rating patterns that overlap substantially with controls, making them difficult to distinguish using structured scores alone.

We next examine whether behavioral signals expressed in teacher narratives can help distinguish these difficult cases. Using the narrative text representation described in Section 4.2, we evaluate the ability of teacher narratives to separate structured false-negative ADHD cases from control students. When restricting the analysis to this subset ($n = 57$), we train a logistic regression classifier using the TF–IDF representation under the same stratified five-fold cross-validation setup. The narrative-based classifier achieves a ROC-AUC of 0.84, substantially higher than the ROC-AUC obtained using structured severity scores alone (0.69). This result indicates that teacher narratives contain behavioral signals that remain informative even when standardized rating scores appear similar to those of control students.

To further examine the relationship between the two modalities, we analyze the association between structured severity scores and narrative-based prediction probabilities within the same subset. The Pearson correlation between these two signals is very weak ($r = 0.07$), suggesting that structured ratings and narrative descriptions capture largely distinct behavioral information.

Taken together, these findings provide quantitative evidence that teacher narratives contain complementary behavioral signals beyond those captured by standardized rating scales. This motivates a closer qualitative examination of behavioral descriptions in teacher narratives, which we explore using the LLM-assisted theme identification pipeline described in Section 4.3.

5.4 LLM-Assisted Qualitative Theme Analysis

To better understand the behavioral signals present in teacher narratives, we apply the LLM-assisted theme extraction pipeline described in Section 4. The analysis focuses on the subset examined in Section 5.3, consisting of structured false-negative ADHD cases ($n = 24$) and control students ($n = 33$). For each teacher narrative, the LLM extracts concise behavioral themes that describe observable student behaviors and contextual information reported by teachers. The extracted themes are mapped to the higher-level behavioral categories described in Section 4. This mapping groups semantically related teacher descriptions into interpretable behavioral categories that capture strengths, difficulties, and contextual observations in student narratives. The complete mapping between granular themes and higher-level behavioral categories is provided in Appendix A.2.

Table 2 compares the average number of themes per narrative for selected behavioral categories across control and structured false-negative groups. Several difficulty-related themes appear substantially more often in structured false-negative ADHD cases than in controls. In particular, *behavioral difficulty* and *attention difficulty* are markedly more prevalent among structured false negatives, suggesting that teachers frequently describe behavioral challenges even when standardized rating scales fail to detect strong ADHD signals. Conversely, narratives of control students contain higher frequencies of several strength-related themes, including *academic strength* and *social-emotional strength*. Control narratives also include

Theme	Control	FN	Diff
Behavioral difficulty	0.21	0.62	+0.41
Attention difficulty	0.24	0.50	+0.26
Academic difficulty	0.33	0.54	+0.21
Neutral context	0.09	0.29	+0.20
Family difficulty	0.03	0.00	-0.03
Behavioral strength	0.64	0.46	-0.18
Social-emotional difficulty	0.61	0.42	-0.19
Family support	0.24	0.00	-0.24
Academic strength	1.18	0.88	-0.30
Social-emotional strength	0.85	0.46	-0.39

Table 2: Average theme frequency per narrative for selected behavioral categories in control and structured false-negative groups. Positive differences indicate higher prevalence in structured false negatives.

Metric	Ctrl Avg.	FN Avg.	Diff	p
Strength themes	2.91	1.79	-1.12	0.0009
Difficulty themes	1.42	2.08	+0.66	0.0128

Table 3: Comparison of the mean number of strength and difficulty themes per student between control and structured false-negative (FN) groups. Diff denotes the difference in group means (FN − control). p-values are computed using two-sided Mann–Whitney tests.

more references to *family support*, a theme that does not appear in the structured false-negative group.

To further examine overall narrative patterns, we compare the total number of strength-related and difficulty-related themes appearing in each narrative, excluding neutral contextual descriptions. As shown in Table 3, structured false-negative ADHD cases contain significantly more difficulty-related themes and substantially fewer strength-related themes than control narratives. These findings provide qualitative insight into the behavioral signals captured by teacher narratives. Although structured false-negative ADHD cases exhibit relatively mild scores in standardized rating scales, teachers frequently describe attention-related and behavioral difficulties in free-text narratives for these students. At the same time, control narratives contain substantially more descriptions of academic and social-emotional strengths.

Collectively, with the quantitative analyses presented in Section 5.3, these results suggest that narrative descriptions capture meaningful behavioral patterns that may not be fully reflected in standardized teacher rating scales. Teacher narratives therefore provide complementary behavioral evidence for identifying ADHD-related difficulties that remain difficult to detect using structured rating items alone.

6 Conclusion and Future Work

This study examines how structured behavioral rating scales and teacher narratives capture different signals related to ADHD. While classifiers trained on structured CTRS-R:S ratings achieve strong overall performance, our analysis reveals that a subset of ADHD cases remains difficult to detect using structured scores alone. These structured false-negative cases exhibit rating patterns that overlap substantially with control students, suggesting that standardized behavioral scales may not fully capture all observable classroom difficulties.

In contrast, narrative-based models trained on teacher descriptions show stronger discriminative ability for these cases. Quantitative error analyses demonstrate that narrative signals can distinguish structured false-negative ADHD cases from controls more effectively than structured ratings. Furthermore, LLM-assisted theme analysis reveals systematic differences in how teachers describe these students: narratives of structured false-negative ADHD cases contain more behavioral difficulty descriptions and fewer strength-related descriptions compared to control narratives. Overall, our findings highlight the value of combining structured behavioral assessments with narrative teacher reports when analyzing behavioral signals related to ADHD. More broadly, this study demonstrates how NLP methods can help uncover clinically meaningful behavioral patterns embedded in open-ended teacher narratives.

Future work can extend this study in several directions. Collecting larger and more balanced datasets—particularly by increasing the number of control students—would enable more robust statistical analyses and more reliable evaluation of narrative-based models. In addition, while this study relies on the Llama 3.3 70B model for theme extraction, exploring alternative language models, especially those with stronger Turkish language capabilities, may further improve theme identification. Finally, expanding this analysis to teacher evaluation data from other educational systems or languages would allow future studies to examine whether similar behavioral patterns emerge across different cultural and educational contexts.

Limitations

This study has several limitations related to data size, modeling choices, and generalizability. The dataset is relatively small and imbalanced (166

ADHD vs. 33 control students), which limits the complexity of models that can be reliably trained and evaluated. As a result, the narrative classification analysis relies on TF-IDF representations with logistic regression rather than more expressive neural architectures. While this approach provides a stable and interpretable baseline for small datasets, larger corpora would enable the use of models that capture richer linguistic patterns in teacher narratives.

In addition, teacher narratives are inherently subjective and may reflect individual reporting styles, classroom expectations, or teacher perceptions, which can introduce variability in how student behaviors are described. Because the narratives analyzed in this study originate from a single educational and cultural context, the behavioral patterns identified here may not fully generalize to other educational systems, languages, or reporting environments. Finally, although LLM-assisted theme extraction provides a structured way to summarize narrative signals, the mapping of extracted themes to higher-level behavioral categories involves expert-informed design decisions, which may introduce some degree of subjectivity.

References

American Psychiatric Association. 2022. *Diagnostic and statistical manual of mental disorders*. American Psychiatric Association Publishing.

Gillinder Bedi, Facundo Carrillo, Guillermo A Cecchi, Diego Fernández Slezak, Mariano Sigman, Natália B Mota, Sidarta Ribeiro, Daniel C Javitt, Mauro Copelli, and Cheryl M Corcoran. 2015. Automated analysis of free speech predicts psychosis onset in high-risk youths. *npj Schizophrenia*, 1(1):1–7.

Jun Byeon, Tae Young Choi, Geun Hui Won, Jaewon Lee, and Jun Won Kim. 2020. A novel quantitative electroencephalography subtype with high alpha power in adhd: Adhd or misdiagnosed adhd? *PLoS One*, 15(11):e0242566.

C Keith Conners, Gill Sitarenios, James DA Parker, and Jeffery N Epstein. 1998. Revision and restandardization of the conners teacher rating scale (ctrs-r): factor structure, reliability, and criterion validity. *Journal of abnormal child psychology*, 26(4):279–291.

Glen Coppersmith, Mark Dredze, and Craig Harman. 2014. Quantifying mental health signals in twitter. In *Proceedings of the workshop on computational linguistics and clinical psychology: From linguistic signal to clinical reality*, pages 51–60.

Renate Drechsler, Silvia Brem, Daniel Brandeis, Edna Grünblatt, Gregor Berger, and Susanne Walitza. 2020. Adhd: Current concepts and treatments in children and adolescents. *Neuropediatrics*, 51(05):315–335.

Nezla S Duric, Jørg Assmus, Helge Børresen, Alisa Duric Golos, Dobrinko Socanski, Armand Duric, and Tanju Surmeli. 2025. Quantitative electroencephalography in children with attention deficit hyperactivity disorder and healthy children: behavioral and age correlates. *Applied Neuropsychology: Child*, 14(2):194–202.

Eyüp Sabri Ercan, Rasiha Kandulu, Erman Uslu, Ulku Akyol Ardic, Kemal Utku Yazici, Burge Kabukcu Basay, Cahide Aydın, and Luis Augusto Rohde. 2013. Prevalence and diagnostic stability of adhd and odd in turkish children: a 4-year longitudinal study. *Child and adolescent psychiatry and mental health*, 7(1):30.

Tamsin Ford, Tom Fowler, Kate Langley, Naureen Whittinger, and Anita Thapar. 2008. Five years on: public sector service use related to mental health in young people with adhd or hyperkinetic disorder five years after diagnosis. *Child and Adolescent Mental Health*, 13(3):122–129.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, and 1 others. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Charlotte L Hall, Althea Z Valentine, Madeleine J Groom, Gemma M Walker, Kapil Sayal, David Daley, and Chris Hollis. 2016. The clinical utility of the continuous performance test and objective measures of activity for diagnosing and monitoring adhd in children: A systematic review. *European child & adolescent psychiatry*, 25(7):677–699.

Sema Kaner, Sener Buyukuzturk, and ELVAN İŞERİ. 2013. Conners teacher rating scale-revised short: Turkish adaptation study. *EGITIM VE BILIM-EDUCATION AND SCIENCE*, 38(167).

Baris Karacan, Ankit Aich, Avery Quynh, Amy Pinkham, Philip Harvey, Colin Depp, and Natalie Parde. 2024. Towards comprehensive language analysis for clinically enriched spontaneous dialogue. In *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pages 16457–16472.

Su Hwan Kim, Severin Schramm, Lisa C Adams, Rickmer Braren, Keno K Bressem, Matthias Keicher, Paul-Sören Platzek, Karolin Johanna Paprottka, Claus Zimmer, Dennis M Hedderich, and 1 others. 2025. Benchmarking the diagnostic performance of open source llms in 1933 eurorad case reports. *NPJ digital medicine*, 8(1):97.

Marta Kopańska and Julia Trojniak. 2025. From aberrant brainwaves to altered plasticity: A review of

qeeg biomarkers and neurofeedback in the neurobiological landscape of adhd. *Cells*, 14(17):1339.

Nezahat Korkmaz. 2023. Turkish stopwords.

Thomas W MacFarland and Jan M Yates. 2016. Mann–whitney u test. In *Introduction to nonparametric statistics for the biological sciences using R*, pages 103–132. Springer.

Carlos Rojas Malpica, Miguel Ángel De Lima Salas, and Adele Mobilli Rojas. 2014. El manual diagnóstico y estadístico de los trastornos mentales de la asociación psiquiátrica norteamericana. una aproximación critica a su quinta edición (dsma5). *Gac Méd Caracas*, 122(3):208–218.

Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, and 1 others. 2011. Scikit-learn: Machine learning in python. *Journal of Machine Learning Research*, 12:2825–2830.

Bradley S Peterson, Joey Trampush, Morah Brown, Margaret Maglione, Maria Bolshakova, Mary Rozelle, Jeremy Miles, Sheila Pakdaman, Sachi Yagyu, Aneesa Motala, and 1 others. 2024. Tools for the diagnosis of adhd in children and adolescents: a systematic review. *Pediatrics*, 153(4).

Anna Rumshisky, Marzyeh Ghassemi, Tristan Naumann, Peter Szolovits, VM Castro, TH McCoy, and RH Perlis. 2016. Predicting early psychiatric readmission with natural language processing of narrative discharge summaries. *Translational psychiatry*, 6(10):e921–e921.

Gerard Salton and Christopher Buckley. 1988. Term-weighting approaches in automatic text retrieval. *Information processing & management*, 24(5):513–523.

Monica Shaw, Paul Hodgkins, Hervé Caci, Susan Young, Jennifer Kahle, Alisa G Woods, and L Eugene Arnold. 2012. A systematic review and analysis of long-term outcomes in attention deficit hyperactivity disorder: effects of treatment and non-treatment. *BMC medicine*, 10(1):99.

Maria Skounti, Anastas Philalithis, and Emmanouil Galanakis. 2007. Variations in prevalence of attention deficit hyperactivity disorder worldwide. *European journal of pediatrics*, 166(2):117–123.

A Appendix

A.1 Original Theme Extraction Prompt

SYSTEM: Sen klinik tanı koymazsın.
Öğretmen anlatılarından gözlenebilir davranışları kısa TEMALAR olarak çıkarırsın.

Kurallar:
- Tanı/etiket yazma: DEHB/ADHD, tanı, rapor, ilaç vb.
- Her tema 2–6 kelime olmalı.
- Her tema açıkça bir GÜÇ (pozitif) veya ZORLUK (negatif) ifade etmeli.
- Nötr tema üretme.
- Sadece metinde kanıtı olan temaları yaz.
- Çıktı yalnızca geçerli JSON olsun.

Örnek temalar:
"sosyal uyum güçlü"
"arkadaş ilişkilerinde zorluk"

USER: Aşağıdaki öğretmen anlatısını oku ve HER BÖLÜM için en fazla 2 tema çıkar.

Bölümler:
1) OKUL BAŞARISI
2) KİŞİLİĞİ / RUHSAL
3) SOSYAL İLİŞKİLER
4) AİLE

JSON formatı:

```
{
  "themes": [
    {
      "tema": "...",
      "valans":
"pozitif|negatif",
      "alan":
"okul|kişisel|sosyal|aile"
    },
    ...
  ]
}
```

Ek kurallar: Her alan için en fazla 2 tema, toplam en fazla 8 tema, ve temalar metnin içeriğine dayanmalı.

Metin: «< {TEXT} »>

Figure A1: Original Turkish prompt used for LLM-assisted theme extraction from teacher narratives.

A.2 Complete Mapping from Granular Themes to Higher-Level Behavioral Categories

To improve transparency and reproducibility, we provide the complete mapping between the granular behavioral themes extracted from teacher narratives and the higher-level behavioral categories used in the analysis. The themes are originally written in Turkish and are accompanied by English glosses to facilitate interpretation for non-Turkish-speaking readers. The glosses represent approximate semantic translations rather than literal word-for-word translations.

The higher-level categories are: *attention difficulty*, *academic difficulty*, *behavioral difficulty*, *social-emotional difficulty*, *academic strength*, *behavioral strength*, *social-emotional strength*, *family support*, *family difficulty*, and *neutral context*.

For readability, the complete mapping is presented across four tables grouped by behavioral polarity and thematic domain. Tables A1 and A2 list difficulty-related themes, while Tables A3 and A4 present strength-related themes. Themes categorized as *neutral context* are not included in the tables, as they do not express a clear strength or difficulty but instead provide descriptive background information.

Turkish (original) theme	English gloss	Higher-level category
kafası karışık	confused / mentally scattered	attention difficulty
dağınıklık	disorganization	attention difficulty
dağınık davranış	disorganized behavior	attention difficulty
dikkat dağınıklığı	distractibility	attention difficulty
nadiren dalgın	occasionally absent-minded	attention difficulty
dikkat eksikliği	lack of attention	attention difficulty
dikkatsizlik nedeniyle hatalar	mistakes due to inattention	attention difficulty
derste dalmak	zoning out in class	attention difficulty
dalgın ve dağınık	absent-minded and disorganized	attention difficulty
ders esnasında dikkati dağılabiliyor	attention drifts during class	attention difficulty
dikkatli olduğunda başarılı	successful when attentive	attention difficulty
ilgi duyduğunda başarılı	successful when interested	attention difficulty
konsantrasyon sorunu	concentration problems	attention difficulty
dalgın ve dağınıktır	absent-minded and disorganized	attention difficulty
sıkılır ve motive olmuyor	gets bored and unmotivated	attention difficulty
dikkat ve odaklanma sorunu	attention and focus problems	attention difficulty
ilgisini çekme ihtiyacı	needs to be engaged / interested	attention difficulty
akademik zorluklar	academic difficulties	academic difficulty
yönergeleri takip etmekte zorluk	difficulty following instructions	academic difficulty
vasat başarı	average achievement	academic difficulty
daha başarılı olabilir	could perform better	academic difficulty
resim becerisi yok	lacks drawing skills	academic difficulty
kitap okumaya karşı ilgisizlik	lack of interest in reading books	academic difficulty
problem çözmede zorlanıyor	struggles with problem solving	academic difficulty
yazma yavaş	writes slowly	academic difficulty
bazı konularda zorluk	difficulty in some subjects	academic difficulty
yönerge uygulamada zorluk	difficulty applying instructions	academic difficulty
zaman yönetimi zorluğu	difficulty with time management	academic difficulty
özümseme güçlüğü	difficulty with comprehension / internalization	academic difficulty
yazı yazma zorluğu	difficulty with writing	academic difficulty
ezberleme gücü zayıf	weak memorization ability	academic difficulty
sayısal derslerde zayıf	weak in quantitative subjects	academic difficulty
okuma performansı değişken	inconsistent reading performance	academic difficulty
ödevlere karşı isteksiz	reluctant to do homework	academic difficulty
anlamada zorluk	difficulty understanding	academic difficulty
matematikte zorluk	difficulty in mathematics	academic difficulty
başarı dalgalı	inconsistent performance	academic difficulty
yavaş iş yapma	works slowly	academic difficulty
işlem hatası	computational error	academic difficulty
sayısal derslerde zorluk	difficulty in quantitative subjects	academic difficulty
ders başarısında zorluk	difficulty with academic performance	academic difficulty
ders başarısı düşük	low academic performance	academic difficulty
ders çalışma zorluğu	difficulty studying	academic difficulty

Table A1: Granular difficulty-related themes and their mapping to higher-level categories (Part I: attention and academic difficulties).

Turkish (original) theme	English gloss	Higher-level category
davranışsal zorluklar	behavioral difficulties	behavioral difficulty
kendini sıkar	puts pressure on self / tenses self up	behavioral difficulty
öfke kontrolü zorluğu	difficulty controlling anger	behavioral difficulty
öfke kontrolü zor	poor anger control	behavioral difficulty
fazla müdahaleci	overly intrusive / interferes too much	behavioral difficulty
neşeli ve inatçı	cheerful but stubborn	behavioral difficulty
fiziksel becerileri zayıf	weak physical skills	behavioral difficulty
inatçı davranış	stubborn behavior	behavioral difficulty
davranışları değişken	inconsistent behavior	behavioral difficulty
oldukça hareketli ve öfkeli	quite hyperactive and angry	behavioral difficulty
inatçı ve hırçın	stubborn and irritable	behavioral difficulty
uzlaşılmaz davranışlar	uncooperative behavior	behavioral difficulty
sinirli davranışlar	irritable behavior	behavioral difficulty
alıngan davranışlar	overly sensitive behavior	behavioral difficulty
inatçı	stubborn	behavioral difficulty
ben merkezci tavırlar	self-centered attitudes	behavioral difficulty
daha sakin davranış	relatively calmer behavior	behavioral difficulty
fazla konuşma	excessive talking	behavioral difficulty
kuralları bozma eğilimi	tendency to break rules	behavioral difficulty
inatçı ve yaramaz	stubborn and mischievous	behavioral difficulty
yerinden kalkma eğilimi	tendency to leave seat	behavioral difficulty
paylaşımda zorluk	difficulty sharing	behavioral difficulty
arkadaş edinme zorlukları	difficulty making friends	social-emotional difficulty
sosyalleşmede pasif	passive in socialization	social-emotional difficulty
utangaç	shy	social-emotional difficulty
arkadaş seçmekte zorluk	difficulty choosing friends	social-emotional difficulty
zaman zaman arkadaşlarına inatlaşabiliyor	sometimes becomes oppositional with peers	social-emotional difficulty
çekingen kişilik	timid personality	social-emotional difficulty
içe kapanıklık	social withdrawal	social-emotional difficulty
pasif ilişki	passive interpersonal style	social-emotional difficulty
sosyalleşme isteksizliği	reluctance to socialize	social-emotional difficulty
korktukça sessizleşiyor	becomes quiet when afraid	social-emotional difficulty
kaygılı ve korkak	anxious and fearful	social-emotional difficulty
sevdiği öğretmenlerle rahat	comfortable only with favored teachers	social-emotional difficulty
ilgi bekler	seeks attention / expects attention	social-emotional difficulty
kırılgan	emotionally fragile	social-emotional difficulty
duygusal ve alıngan	emotional and easily offended	social-emotional difficulty
duygusal içe dönüklük	emotional introversion	social-emotional difficulty
hassas öğrenci	sensitive student	social-emotional difficulty
duygusal ve sessiz	emotional and quiet	social-emotional difficulty
duygusal dalgalanma	emotional fluctuation	social-emotional difficulty
hassas	sensitive	social-emotional difficulty
hassas ve sıkılgan	sensitive and easily bored / withdrawn	social-emotional difficulty
hassas ve alıngan	sensitive and easily offended	social-emotional difficulty
hassas ve çabuk küsebilen	sensitive and easily upset	social-emotional difficulty
eleştirilere karşı duyarlı	sensitive to criticism	social-emotional difficulty
duygusal ve içe dönük	emotional and introverted	social-emotional difficulty
duygusal hassasiyet	emotional sensitivity	social-emotional difficulty
hassas ve sevgi dolu	sensitive and affectionate	social-emotional difficulty
sessiz bir mizacı	quiet temperament	social-emotional difficulty
hata yapma korkusu var	fear of making mistakes	social-emotional difficulty
endişeli aile	anxious family	family difficulty

Table A2: Granular difficulty-related themes and their mapping to higher-level categories (Part II: behavioral, social-emotional, and family difficulties).

Turkish (original) theme	English gloss	Higher-level category
akademik başarı	academic success	academic strength
başarılı	successful	academic strength
başarılı öğrenci	successful student	academic strength
sanatsal yetenek	artistic talent	academic strength
tüm derslerde başarılı	successful across all subjects	academic strength
başarı artışı	improvement in performance	academic strength
ilgi gösterir	shows interest	academic strength
eksiklerini tamamlama çaba	effort to make up deficiencies	academic strength
okul başarısı yüksek	high school performance	academic strength
derslerinde başarılı	successful in coursework	academic strength
yönergelere uyar	follows instructions	academic strength
genel olarak başarılı	generally successful	academic strength
okuma becerisi iyi	good reading skills	academic strength
okuma becerisi güçlü	strong reading skills	academic strength
sanat yeteneği var	has artistic ability	academic strength
problem çözme yeteneği gelişmiş	well-developed problem-solving ability	academic strength
ders başarısı yüksek	high academic performance	academic strength
el becerileri iyi	good fine motor / hand skills	academic strength
dersi derste kavrayabilme	able to grasp lessons during class	academic strength
araştırmacı ve başarılı	inquisitive and successful	academic strength
matematik başarısı yüksek	high math achievement	academic strength
sözel becerisi güçlü	strong verbal ability	academic strength
futbolda başarılı	successful in football	academic strength
sözel ve sayısalda başarılı	successful in both verbal and quantitative subjects	academic strength
akademik başarısı yüksek	high academic achievement	academic strength
sanat ve spor yeteneği var	has talent in art and sports	academic strength
okuduğunu anlama becerisi güzel	good reading comprehension	academic strength
derslerde başarılı	successful in classes	academic strength
anlama becerisi iyi	good comprehension ability	academic strength
gayretli öğrenci	hardworking student	academic strength
spora yeteneği var	has athletic ability	academic strength
okuma yazma becerileri güçlü	strong literacy skills	academic strength
etkinliklere katılımı başarılı	successful participation in activities	academic strength
başarı düzeyi iyidir	achievement level is good	academic strength
derslere katılır	participates in class	academic strength
matematik başarısı	math achievement	academic strength
başarı düzeyi yüksek	high achievement level	academic strength
sözel yeteneği yüksek	high verbal ability	academic strength
sanatsal etkinliklere ilgi	interest in artistic activities	academic strength
matematik dersinde başarılı	successful in math class	academic strength
sorgulama becerisi güçlü	strong questioning / inquiry skills	academic strength
sözel derslerde başarılı	successful in verbal subjects	academic strength
meraklı ve sorgulayıcı	curious and inquisitive	academic strength
öğrenme isteği var	shows willingness to learn	academic strength
matematik yeteneği güçlü	strong mathematical ability	academic strength
aile ilgili	family is involved	family support
aile desteği	family support	family support
aile içi uyum	harmony within the family	family support
aile uyumlu	supportive family environment	family support
aile içi ilişkileri iyi	good family relationships	family support
aile ilişkileri iyi	positive family relations	family support

Table A3: Granular strength-related themes and their mapping to higher-level categories (Part I: academic strength and family support).

Turkish (original) theme	English gloss	Higher-level category
titiz ve tertipli	neat and orderly	behavioral strength
titizlik	neatness / carefulness	behavioral strength
söz dinler	listens to instructions / is obedient	behavioral strength
yaşından büyük davranıyor	behaves older than their age	behavioral strength
güler yüzlü	cheerful / smiling	behavioral strength
neşeli ve hareketli	cheerful and energetic	behavioral strength
gayretli ve dürüst	hardworking and honest	behavioral strength
saygılı öğrenci	respectful student	behavioral strength
büyüklere karşı saygılı	respectful toward adults	behavioral strength
yaşından büyük davranış	mature behavior beyond age	behavioral strength
sorumluluk sahibi	responsible	behavioral strength
yaşına göre olgun	mature for their age	behavioral strength
kendini kolay ifade eden	expresses self easily	behavioral strength
ağırbaşlı ve olgun	serious and mature	behavioral strength
çok düzenlidir	very organized	behavioral strength
kurallara uyan	follows rules	behavioral strength
saygılı davranış	respectful behavior	behavioral strength
dürüsttür	honest	behavioral strength
söz dinleme	compliance with instructions	behavioral strength
işini iyi yapmak ister	wants to do things well	behavioral strength
kurallara sadık	adheres to rules	behavioral strength
konuşkan ve olgun	talkative and mature	behavioral strength
kurallara uyma	rule-following	behavioral strength
hayal gücü yüksek	strong imagination	behavioral strength
sevilen öğrenci	well-liked student	social-emotional strength
arkadaşları tarafından sevilen	liked by classmates	social-emotional strength
lider ruhlu	shows leadership qualities	social-emotional strength
arkadaşları tarafından sevilir	liked by peers	social-emotional strength
arkadaşları ile arası iyi	gets along well with peers	social-emotional strength
neşeli	cheerful	social-emotional strength
neşeli arkadaş	cheerful friend	social-emotional strength
neşeli ve güler yüzlü	cheerful and smiling	social-emotional strength
sosyal uyum	good social adjustment	social-emotional strength
duygusal dengesi iyi	emotionally balanced	social-emotional strength
arkadaş çevresinde popüler	popular among peers	social-emotional strength
sevilir	well liked	social-emotional strength
liderlik özellikleri var	has leadership qualities	social-emotional strength
arkadaşları ile iyi geçiniyor	gets along well with friends	social-emotional strength
neşeli ve heyecanlı kişilik	cheerful and enthusiastic personality	social-emotional strength
liderlik özellikleri	leadership traits	social-emotional strength
ilgi ve paylaşım gösteriyor	shows care and sharing behavior	social-emotional strength
neşeli ve esprili	cheerful and humorous	social-emotional strength
arkadaş canlısı	friendly	social-emotional strength
sakin ve sevilen	calm and well-liked	social-emotional strength
iletişime açık	open to communication	social-emotional strength
liderlik özelliği	leadership trait	social-emotional strength
liderlik özelliği var	has leadership ability	social-emotional strength
neşeli kişilik	cheerful personality	social-emotional strength
iletişimi güçlü	strong communication skills	social-emotional strength
atılgan	assertive	social-emotional strength
atılgan ve neşeli	assertive and cheerful	social-emotional strength
sosyal	social	social-emotional strength
öğretmen ile iyi iletişim	good communication with the teacher	social-emotional strength
duygu kontrolü gelişimi	developed emotional regulation	social-emotional strength
bağ kurma yeteneği	ability to form relationships	social-emotional strength
sosyal bir öğrenci	socially engaged student	social-emotional strength
neşeli ve sevilen	cheerful and well-liked	social-emotional strength

Table A4: Granular strength-related themes and their mapping to higher-level categories (Part II: behavioral and social-emotional strengths).

Why Do Self-Harm Prediction Models Struggle to Generalise? Lexical and Semantic Variations in Emergency Department Triage Notes

Liuliu Chen[1], Mike Conway[1], Jo Robinson[2,3], Vlada Rozova[1,4]

[1]School of Computing and Information Systems, The University of Melbourne, Australia
[2]Orygen, The National Centre of Excellence in Youth Mental Health, Australia
[3]Centre for Youth Mental Health, The University of Melbourne, Australia
[4]Centre for Digital Transformation of Health, The University of Melbourne, Australia
Correspondence: liuliuc@student.unimelb.edu.au

Abstract

Self-harm presentations to emergency departments (EDs) are strongly associated with higher suicide risk. NLP models have shown robust performance in detecting self-harm from triage notes within single hospitals, yet performance often declines across institutions. To examine potential causes, we compare ED triage notes from two hospitals by analyzing lexical characteristics, highly associated predictive features, and salient topics. Our results reveal variation in lexical expression and feature importance related to self-harm across hospitals, despite consistent core themes such as self-poisoning and self-injury. These documentation differences are associated with reduced cross-site performance. Our findings provide insight into how institutional variation affects the identification of self-harm in clinical text and highlight potential methods to improve model generalisability.

1 Introduction

Generalisability of predictive models is important in the clinical domain, where data collection and annotation are often expensive and logistically challenging (Goetz et al., 2024). Yet achieving robust generalisation remains a key challenge in real-world clinical applications for various reasons. For example, limited representativeness in the training data can impact model transfer to new datasets (Goetz et al., 2024), while the predictive factors that support or hinder generalisability are poorly understood (Futoma et al., 2021). Prior work on clinical NLP portability has also shown that model performance can degrade substantially when systems are applied to new clinical domains, motivating domain adaptation strategies that account for differences in documentation style, institution, specialty, and data-sharing constraints (Laparra et al., 2020).

Self-harm – defined as "an intentional act of self-poisoning (e.g., drug overdose) or self-injury (e.g., self-cutting) regardless of suicidal intent" – has become increasingly common among young people and is a major global health concern (Witt et al., 2023). This has driven researchers to develop methods for self-harm detection in clinical documentation over the years (Obeid et al., 2020; Ayre et al., 2021; Iorfino et al., 2020; Rozova et al., 2022). Recently published studies using natural language processing have shown strong performance. For instance, Obeid et al. (2020) reported an AUROC of 0.88 and an F1-score of 0.77 on electronic health records (EHRs). Rozova et al. (2022) reported an AUPRC of 0.85 when applying a Gradient Boosting model to emergency department (ED) triage notes. However, these results were obtained on test sets with the same distributions as the training data. Whether these models can generalise to other contexts remains under-explored.

Building on Rozova et al.'s (2022) study, we aim to examine the model's external validity in a different hospital context. The model was trained on ED data from the Royal Melbourne Hospital (RMH), a major tertiary referral centre in Melbourne, Victoria, Australia. When applied to Latrobe Regional Health (LRH), a regional hospital serving rural communities in Victoria, model performance declined, with AUPRC decreasing from 0.85 ± 0.01 to 0.78 ± 0.01. To investigate the potential contributors to this cross-site generalisation gap, we conduct a corpora comparison analysis on ED triage notes between RMH and LRH.

Triage notes describe the reason for patient presentation to the ED and are typically short and hastily written, resulting in non-standard grammar, misspellings and extensive use of abbreviations, which can vary considerably between hospital systems. Through the analysis of lexical characteristics, features highly associated with the outcome variable, and topic modelling, we aim to identify potential contributors to the model's diminished performance when ported to a different context.

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 383–388
July 4, 2026 ©2026 Association for Computational Linguistics

Table 1: Comparisons between RMH and LRH.

	RMH	LRH
Funding	Public	Public
Location	Metropolitan	Regional
ED records, 2012–2017	399,111	171,170
Catchment area	137 sq. km	42,000 sq. km
Population served	550,000	300,000
Emergency mental health team	Yes	No
Age	48±21	47±23
Sex		
Female	48%	52%
Male	52%	48%
Intersex	< 1%	< 1%
Unknown	< 1%	< 1%

2 Methodology

2.1 Datasets

This study uses ED triage notes from RMH and LRH between 2012 and 2017 (Witt et al., 2023), which were manually annotated by psychology experts in suicide prevention as positive (**Self-harm**) or negative (**Control**). The RMH dataset consisted of N=399,111 notes with 1.4% notes annotated as positive. The LRH dataset contained N=171,170 notes, of which 1.7% were considered positive.

RMH is a large metropolitan public tertiary hospital, while LRH is the principal referral hospital for the Gippsland region, serving a predominantly rural and regional catchment. Table 1 summarises key contextual differences between the two hospitals.

2.2 Corpora Comparison

To compare the corpora, we examined lexical characteristics (e.g., number of characters and sentences), identified important features in each dataset, and applied topic modelling to explore the most frequent topics in the self-harm group.

Important Features Selection Following Rozova et al. (2022), we employed TF–IDF representations to ensure comparability and enable external validation. We computed the TF-IDF matrix and selected important features using both the Chi-Square and XGBoost algorithms. Chi-Square measures the correlation between a feature and the target variable (i.e., self-harm), and features with $p < .001$ were retained. XGBoost feature importance reflects each feature's predictive contribution, and we selected features above the 95th percentile (top 5%). We applied Chi-Square test and XGBoost independently on each dataset, both across all years and separately for each year. The final set of important features was the intersection of features selected by both methods. We further compare these final selected important features between the two hospitals.



(a) Character count (b) Sentence count

Figure 1: Lexical characteristics

Topic Modelling To explore common themes in the self-harm class, BERTopic was applied (Grootendorst, 2022) separately to each dataset, using only the positive class. We selected 'all-mpnet-based-v2' as our sentence embedding model, which currently performs the best in capturing semantic information (HuggingFace, 2025). The topic-wise embedding semantic similarity between hospitals was calculated by cosine similarity. To identify unique topics, we set a threshold of 0.75, selected based on a sensitivity analysis across the 0.60–0.90 range.

3 Results

3.1 Lexical Characteristics

Figure 1 provides descriptive statistics regarding the number of characters and sentences.

3.2 Comparison of Important Features

3.2.1 Overall Comparison

Across the entire dataset, we identified 472 unigram, 701 bigram, and 637 trigram important features at RMH and 365 unigram, 460 bigram, and 426 trigram features at LRH. The top 10 selected features for each hospital are presented in Appendix, Table 5.

Of those, 213 unigram, 156 bigram, and 136 trigram features were shared between the two datasets, indicating their transferability. Table 2 presents the 10 most important shared features. As shown, these features mostly contain generic self-harm related keywords (e.g., *self harm*, *self inflicted*), self-harm methods (predominantly self-poisoning, e.g., *od*, *intentional od*), and self-injury (e.g., *superficial cuts to*). Suicide-related keywords are also common in shared features, such as *suicidal*, *suicide*, and *suicide intent*.

We plotted the ranking of shared unigram features in Figure 2. Although present in both hospi-

	Shared features
Unigram	od, pain, self, tablets, overdose, sob, resolved, suicidal, suicide, attempt
Bigram	self inflicted, od of, self harm, intentional od, suicide attempt, to end, to kill, polypharmacy od, wanted to, suicide intent
Trigram	superficial lac(s) to, superficial cuts to, self harm to, self harm lacs, states has taken, with razor blade, with suicidal intent, to kill self, wants to die, pt has taken

Table 2: Top 10 features identified in both RMH and LRH, sorted by average XGBoost importance ranking.

tals, these features differed in their statistical association with self-harm (Chi-Square) and predictive importance (XGBoost). Additionally, statistical association does not always indicate predictive power for classification. For example, *suicide* in RMH ranks highly based on the Chi-Square score but does not necessarily hold the highest predictive importance in model predictions.



Figure 2: Ranking of shared unigram features, sorted by average XGBoost importance score ranking.

We compared the TF-IDF representations for each hospital. While feature selection was previously performed independently on each dataset, the TF-IDF representation here was computed using a shared vocabulary derived from both datasets to enable direct comparison.

Overall, the cosine similarity between site-level mean TF-IDF vectors for RMH and LRH was 0.822 for unigrams, 0.628 for bigrams, and 0.473 for trigrams. For the top 10 shared features listed in Table 2, we further compared the distributions of document-level TF-IDF values between hospitals. All unigram features differed significantly between the two hospitals ($p < .01$ for *resolved*, $p < .001$ for all others). Among bigram features, TF-IDF values for *suicide intent* and *suicide attempt* were similar, while the remaining bigram features showed significant differences ($p < .01$ for *self-inflicted*, $p < .001$ for all others). All trigram features differed significantly between hospitals ($p < .001$). Figure 3 shows examples of different distributions of TF-IDF values for terms *self harm* and *intentional od*



(a) *Self harm* (b) *Intentional od*

Figure 3: Distribution of TF-IDF values

	RMH	LRH
Unigram	jump, dizzy, bpd, dementia, stab, life, changes, xanax	biba, dose, bandaged, tied, children, battery, community, droop
Bigram	sudden onset, social stressors, anxiety depression, attempt to, phx depression, flank pain, with etoh	on palpation, biba after, with police, analgesia taken, dose of, with nil, attempted od, alleged overdose
Trigram	recent relationship breakdown, previous self harm, recent social stressors, drowsy at triage, with stanley knife	to left forearm, under section 351, under section 10, with self inflicted, biba with police

Table 3: Features selected only in RMH or LRH.

between hospitals.

Uniquely important features were also identified in each dataset. Some were misspellings (e.g., *paracetOmol*) or dosage values (e.g., *55mg*), which were excluded to focus on features with potentially meaningful insights, as shown in Table 3. Compared to RMH, LRH appears to have more police involvement in triage notes, with terms such as *with police* and *section 351* (Victorian Mental Health Act - apprehension of a person by police). In contrast, RMH contains more features related to social and psychological stressors, including *recent relationship breakdown*, *social stressors*.

3.2.2 Longitudinal Analysis

We further applied feature selection independently to each year and each hospital (Appendix, Figure 5). Some features remained consistent across all years in both datasets (unigram: 20, bigram: 9, trigram: 2). These features are primarily related to self-poisoning (e.g., *OD, overdose, tablets*), suicide (e.g., *suicidal, suicide attempt*), and self-inflicted harm (e.g., *inflicted, forearm*).

Focusing on social and mental factors, self-harm methods, mental disorders, and medication, we examined the consistency of related unigram features, as shown in Figure 4. Certain word features, such as *police*, *diazepam*, and *depression*, appear consistently across years in both hospitals. Social factors like *partner* are more consistent in RMH, as well



(a) Social factors (b) Medication (c) Self-harm methods (d) Mental health disorders

Figure 4: Heatmap of feature presence for feature-hospital across years (1: present, 0: absent). Note: some features appear in only one hospital because features absent in all years for a given hospital were removed.

as suicide methods (e.g., *hanging/hang*). Medication terms also show some variations between hospitals. For example, *paracetamol* was present in most years in RMH but was not selected in LRH. Regarding mental health disorders, most related terms appear consistently in RMH, whereas some features, such as *bipolar*, were not selected in any year for LRH.

3.3 Topic Modelling

BERTopic models identified 30 topics in LRH and 74 in RMH. After manually reviewing, we found that most were related to self-harm methods, primarily overdosing on specific medications and dosages. Other self-harm methods also emerged, such as self-inflicted injuries and hanging.

The average semantic similarity across all documents was 0.46, while the overall topic representation (top-10 keywords) had a similarity score of 0.68. To further analyse topic overlap, we calculated pairwise topic semantic similarity and identified unique topics in each hospital. Based on sensitivity analysis across the 0.60–0.90 cosine similarity range, LRH consistently showed no unique topics across thresholds of 0.60–0.85, while the number of unique RMH topics varied. We therefore used 0.75 as a heuristic threshold, as it provided an intermediate level of strictness within the tested range.

We found 10 unique topics in RMH, while no unique topics were identified in LRH. Table 4 presents the top 5 unique topics in RMH. Topics 42 and 56 are associated with overdose and poisoning presentations. Topics 51 and 14 primarily reflect psychiatric complexity, such as *psychosis* and *BPD*. Topic 27 captures hanging-related presentations.

Interestingly, while semantic embeddings of topics showed high similarity, their Jaccard similarity was much lower. This suggests that while both hospitals discuss similar topics, the specific lexicons used may differ.

No.	Representative words
14	etoh, valium, valiumx4, bpd, suicidal, anxiety, 22mg, 5mg, abuse, harm
27	rope, hung, hanging, hang, distress, neck, haematoma, fell, seizure, spine
42	olanzipine, 80mg, 10mg, benztropine, 4mg, fluoxetine, 5mg, 30mg, polypharmacy, haloperidolol
51	psychosis, meds, anxiety, pmhx, stressors, midazolam, discharged, abusive, bandaged, 351
56	suicidal, suicide, poisoning, cpr, monoxide, unconscious, hypoxic, triaged, lethargy, catatonic

Table 4: BERTopic identified unique topics in RMH

4 Discussion

The above analysis highlights key differences between two hospitals, offering insights into why the TF-IDF Chi-Square/XGBoost model from Rozova et al. (2022) performed less effectively at LRH.

Variations in TF-IDF lexical features TF-IDF analysis revealed that while certain features are transferable between hospitals, their associations and relative importance differ, and each hospital displayed unique features. Mental health–related and social factor terms were more characteristic of RMH than LRH, and the selected medication types also differed. This suggests that term frequency distributions across hospitals vary, potentially due to differences in documentation styles or the geodemographics of patient populations. For instance, RMH (but not LRH) has an ED mental health team specifically trained to assess mental health status. These findings suggest that models trained within a single site may partially rely on site-specific documentation patterns rather than consistently capturing stable indicators of self-harm risk.

Semantic similarity with lexical variation in BERTopic BERTopic analysis showed high semantic similarity across most detected topics, indicating the thematic consistency across RMH and LRH. The topics primarily focus on self-harm methods, especially on overdosing with specific

medications and dosages, aligning with previous findings that self-poisoning is present in over 50% of self-harm presentations (Witt et al., 2023). However, the low Jaccard similarity indicates differences in word or phrase choices between hospitals, rather than fundamental differences in patient conditions. Notably, 10 unique topics were identified in RMH, mainly related to psychiatric conditions and overdoses. The absence of these topics in LRH may reflect differences in case mix, transfer pathways, documentation templates, or local triage practices.

Future direction Our results suggest several potential directions to enhance model generalisability. First, as self-harm themes remain largely consistent across hospitals, future work could incorporate lexical semantics as predictive features. Second, considering that many unique features related to drugs and their dosages, standardising such alphanumeric combinations into higher-level features might enhance cross-hospital model performance (Sikora et al., 2024). Additionally, normalising triage notes into a standardised format could further help reduce lexical and grammatical variability, ensuring more consistent documentation and better model transferability across hospitals.

5 Conclusion

This study compared ED triage notes between RMH and LRH, using selected TF-IDF features and topic modelling. Our analysis shows differences in the importance of selected TF-IDF features, while BERTopic showed high semantic similarity between hospitals but notable lexical differences in topic representation. These differences may contribute to the performance drop in model generalisation, and point to future directions in enhancing cross-hospital model transferability by normalising text to reduce lexical variability.

Limitations

This study is limited to two Australian hospitals, which constrains the generalisability of our findings. Differences in dataset size and possible discrepancies in annotation practices, even with expert involvement, may have influenced feature representations. We also note that TF-IDF and BERTopic were selected for comparability and interpretability, but alternative representations may yield different insights. In particular, the implications for contextual embedding models and large language models (LLMs) remain an open question. If the primary source of cross-site variation is lexical rather than thematic, as our BERTopic results suggest, models with greater capacity to generalise across surface-level lexical differences may partially mitigate the portability gap. However, empirical validation on such models is needed before drawing conclusions.

Ethical Considerations

Ethical approval was granted by the Melbourne Health Human Research Ethics Committee (HREC; 2017.342). All data were de-identified and are analysed within a secure institutional infrastructure. Due to the sensitivity of the data, our corpus cannot be publicly shared.

Self-harm detection should be approached with particular caution in clinical contexts. In this study, the primary purpose of these models is public health surveillance rather than clinical decision-making. Our models are not intended to replace clinician judgement. We emphasize that predictive models require careful validation prior to deployment to avoid unintended harm, particularly when applied across institutions.

Acknowledgements

We thank Jonathan Knott and Owen Connolly for facilitating data acquisition at the Royal Melbourne Hospital and the Latrobe Regional Health. We also thank Hannah Richards and Lu Zhang for their assistance with manual data coding.

Funding

JR is supported by an NHMRC Investigator Grant (2008460) and the University of Melbourne Dame Kate Campbell Fellowship.

References

Karyn Ayre, André Bittar, Joyce Kam, Somain Verma, Louise M Howard, and Rina Dutta. 2021. Developing a natural language processing tool to identify perinatal self-harm in electronic healthcare records. *PLoS one*, 16(8):e0253809.

Joseph Futoma, Morgan Simons, Finale Doshi-Velez, and Rishikesan Kamaleswaran. 2021. Generalization in clinical prediction models: the blessing and curse of measurement indicator variables. *Critical Care Explorations*, 3(7):e0453.

Lea Goetz, Nabeel Seedat, Robert Vandersluis, and Mihaela van der Schaar. 2024. Generalization—a key

challenge for responsible ai in patient-facing clinical applications. *npj Digital Medicine*, 7(1):126.

Maarten Grootendorst. 2022. Bertopic: Neural topic modeling with a class-based tf-idf procedure. *arXiv preprint arXiv:2203.05794*.

HuggingFace. 2025. Pretrained Models &x2014; Sentence Transformers documentation — sbert.net. https://www.sbert.net/docs/sentence_transformer/pretrained_models.html. [Accessed 21-03-2025].

Frank Iorfino, Nicholas Ho, Joanne S Carpenter, Shane P Cross, Tracey A Davenport, Daniel F Hermens, Hannah Yee, Alissa Nichles, Natalia Zmicerevska, Adam Guastella, et al. 2020. Predicting self-harm within six months after initial presentation to youth mental health services: A machine learning study. *PLoS one*, 15(12):e0243467.

Egoitz Laparra, Steven Bethard, and Timothy A Miller. 2020. Rethinking domain adaptation for machine learning over clinical language. *JAMIA open*, 3(2):146–150.

Jihad S Obeid, Jennifer Dahne, Sean Christensen, Samuel Howard, Tami Crawford, Lewis J Frey, Tracy Stecker, and Brian E Bunnell. 2020. Identifying and predicting intentional self-harm in electronic health record clinical notes: deep learning approach. *JMIR medical informatics*, 8(7):e17784.

Vlada Rozova, Katrina Witt, Jo Robinson, Yan Li, and Karin Verspoor. 2022. Detection of self-harm and suicidal ideation in emergency department triage notes. *Journal of the American Medical Informatics Association*, 29(3):472–480.

Andrea Sikora, Kelli Keats, David J Murphy, John W Devlin, Susan E Smith, Brian Murray, Mitchell S Buckley, Sandra Rowe, Lindsey Coppiano, and Rishikesan Kamaleswaran. 2024. A common data model for the standardization of intensive care unit medication features. *JAMIA open*, 7(2):ooae033.

Katrina Witt, Gowri Rajaram, Michelle Lamblin, Jonathan Knott, Angela Dean, Matthew J Spittal, Greg Carter, Andrew Page, Jane Pirkis, and Jo Robinson. 2023. Characteristics of self-harm presentations to the emergency department of the royal melbourne hospital, 2012–2019: data from the self-harm monitoring system for victoria. *Australasian emergency care*, 26(3):230–238.

A Appendix

	RMH	LRH
Unigram	od, self, resolved, tablets, pain, hanging, sob, depression, superficial, diazepam	pain, overdose, od, suicide, self, tablets, suicidal, police, razor, attempt
Bigram	self inflicted, intentional od, to end, suicidal intent, polypharmacy od, sudden onset, self harm, suicide attempt, od of, hx depression	selling to, od of, self harmed, overdose of, self inflicted, self harm, by gp, to kill, pain on, on palpation
Trigram	self inflicted stab, self inflicted lac, self inflicted lacs, with intent to, in attempt to, pmhx depression anxiety, superficial lacs to, superficial cuts to, section 351 self, self harm to	superficial lacs to, superficial cuts to, superficial lacerations to, to left forearm, under section 351, unknown quantity of, self harm lacs, self harm to, pt states took, wants to die

Table 5: Top 10 selected features in RMH and LRH.



Figure 5: Numbers of selected features each year

Overview of the CLPsych 2026 Shared Task: Capturing and Characterizing Mental Health Changes through Social Media Timeline Dynamics

Iqra Ali[1*], **Talia Tseriotou**[1*], **Guy Dvir**[3*], **Callum Chan**[6], **Yuxiang Zhou**[1], **Juan Antonio Lossio-Ventura**[4], **Ayal Klein**[3], **Aya Shamir**[3], **Dan Sayda**[3], **Anthony Hills**[1], **Aya Zirikly**[5,7], **Diana Inkpen**[6], **Dana Atzil-Slonim**[3], **Maria Liakata**[1,2]
[1]Queen Mary University of London, [2]The Alan Turing Institute ,
[3]Bar Ilan University, [4]National Institutes of Health,
[5]The George Washington University, [6]University of Ottawa , [7]Johns Hopkins University
{i.ali; t.tseriotou; m.liakata}@qmul.ac.uk

Abstract

We provide an overview of the CLPsych 2026 Shared Task, which focuses on capturing and characterizing mental health dynamics from social media timelines through structured modeling of self-states. This year advances the longitudinal paradigm set by prior CLPsych shared tasks (2022, 2025), by integrating fine-grained psychological representation using the MIND framework. The task is organized into three main components: **(1)** post-level identification of adaptive and maladaptive self-states through ABCD elements and sub-elements, along with estimation of their presence; **(2)** timeline-level detection of Moments of Change, including both abrupt switches and gradual escalations based on ABCd element and sub-element combinations; and **(3)** sequence-level modeling, involving summarization of change processes over time and identification of recurrent dynamic signatures.

1 Introduction

Computational linguistics and clinical psychology have increasingly converged to study how language reflects mental health, psychological functioning, and change over time (Montejo-Ráez et al., 2024; Villarreal-Zegarra et al., 2024; Hua et al., 2025). Within this space, CLPsych has played a central role by bringing together NLP researchers and mental health experts to develop methods for modeling meaning, behavior, and psychological signals in language (Calvo et al., 2017; Le Glaz et al., 2021; Zirikly and Dredze, 2022). This collaboration has shifted the field from static risk detection toward modeling mental health as a dynamic and longitudinal process (Tsakalidis et al., 2022a; Tseriotou et al., 2025). Such an evolution in perspective is crucial, as mental health unravels through fluctuating affective, behavioral, cognitive, and motivational processes shaped by context over time (Owen et al., 2024; Bucur et al., 2026). Social media provides a natural setting for observing these dynamics through temporally ordered self-disclosures of distress, coping, and interpersonal experiences (Garg, 2023). CLPsych shared tasks have reflected this progression. Early tasks focused on user-level classification, while CLPsych 2022 introduced the longitudinal notion of *Moments of Change* (MoC), distinguishing sudden *switches* from gradual *escalations* (Tsakalidis et al., 2022a). CLPsych 2025 extended this paradigm with an emphasis on explainability through evidence extraction and summarization of self-state processes (Tseriotou et al., 2025). Building on this, CLPsych 2026 advances longitudinal modeling by focusing on fine-grained psychological dynamics underlying mental health changes (Figure 1). The task is grounded in the MIND framework (Atzil-Slonim, 2025, 2026), which represents self-states as combinations of Affect, Behavior, Cognition, and Desire (ABCD), further decomposed into adaptive and maladaptive sub-components pertaining to different dimensions such as need and relation with self and others. Mental health change is modeled as shifts in the dominance and interaction of these self-states over time.

The shared task comprises three complementary components (Figure 2): (1) post-level modeling of adaptive and maladaptive self-states, (2) longitudinal detection of *Moments of Change* (MoC) , and (3) structured summarization of mental health dynamics. The dataset consists of expert-annotated Reddit timelines with self-state annotations, well-being scores, and change labels. Together, the tasks frame mental health modeling as structured, explainable, and longitudinal inference rather than isolated classification (Tseriotou et al., 2025; Atzil-Slonim, 2025, 2026). From a computational perspective, the shared task introduces challenges in multi-label classification, temporal modeling, and explainable summarization, while contributing to-

[*]Denotes equal contribution.

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 389–421
July 4, 2026 ©2026 Association for Computational Linguistics



Figure 1: Overview of the CLPsych 2026 Shared Task for modeling mental health changes from longitudinal social media timelines. The framework is grounded in the MIND (ABCD) model and comprises three tasks: (1) post-level self-state identification and presence rating, (2) detection of moments of change (switches and escalations), and (3) longitudinal summarization of deterioration/improvement patterns. Systems are evaluated using classification, regression, correlation, summarization, and human-centered metrics including Macro-F1, RMSE, Spearman correlation, ROUGE recall, BERTScore recall, and evidence-based human judgments.

ward NLP systems that model mental health as dynamic and contextually grounded (Tsakalidis et al., 2022a; Tseriotou et al., 2025).

2 Related Work

From classification to structured representation of mental health dynamics: Early NLP work framed mental health as document- or user-level classification (Coppersmith et al., 2015; Shing et al., 2018; Zirikly et al., 2019; Sawhney et al., 2022b,a). Subsequent work shifted to longitudinal monitoring of mood changes (Hills et al., 2023; Tseriotou et al., 2024a) with a parallel line of work focused on interpretability through symptom-informed modeling (Nguyen et al., 2022), evidence-based prediction (Parapar et al., 2023; Garg, 2024; Chim et al., 2024), and explanation methods such as SHAP (Lundberg and Lee, 2017). CLPsych 2026 combines these two directions by modeling interacting self-state components in an interpretable manner.

LLMs for structured reasoning in mental health: LLMs enable flexible reasoning over mental health narratives, supporting classification (Amin et al., 2023), data augmentation (Liyanage et al., 2023), contextual inference (Xu et al., 2024a; Yang et al., 2023), and explanation (Xu et al., 2024b; Chim et al., 2024). However, hallucinations and reliability issues persist despite instruction tuning and Chain-of-Thought prompting (Li et al., 2023). This motivates structured, schema-constrained outputs, as adopted in CLPsych 2026 via the ABCD self-state framework and hybrid temporal modelling.

Grounding predictions in self-state evidence: Evidence extraction improves interpretability (Xu et al., 2024a; Yang et al., 2024; Xu et al., 2024c; Chim et al., 2024), but typically identifies supporting spans without linking them to structured psychological constructs. CLPsych 2026 aims to ground predictions in predefined ABCD components and their composition into adaptive and maladaptive self-states.

Structured summarization of change processes: Summarization has been applied to social media timelines (Sotudeh et al., 2022; Song et al., 2024, 2025), counseling (Srivastava et al., 2022), and clinical dialogues (Michalopoulos et al., 2022; Adhikary et al., 2024). However, capturing clinically meaningful temporal and psychological dynamics remains challenging (Klein et al., 2024; Asgari et al., 2024). CLPsych 2026 aims to advance this by requiring structured summaries of self-state config-



Figure 2: Illustration of the CLPsych 2026 shared task pipeline for modeling mental health dynamics from longitudinal social media timelines. The framework maps chronological posts to adaptive and maladaptive self-states using the MIND (ABCD) model, followed by detection of moments of change (switches and escalations) and sequence-level modeling of deterioration/improvement dynamics. Final system outputs include post-level self-state predictions, temporal change detection, sequence summaries, and cross-timeline mental health signatures.

urations, their evolution, and their role in change.

Modeling temporal dynamics and moments of change: Temporal modeling has progressed from RNNs and more standard sequential methods (Tseriotou et al., 2023; Bayram and Benhiba, 2022; Homan et al., 2022; Chim et al., 2025) to time-aware approaches such as Hawkes process models (Hills et al., 2023), hierarchical transformers (Hills et al., 2024), and temporally aware transformers (Tseriotou et al., 2024b). These are shown to improve detection of gradual and abrupt changes, aligning with Moments of Change (Tsakalidis et al., 2022a). CLPsych 2026 extends this line of work by jointly modeling temporal dynamics (i.e. switches and escalations) and structured self-state processes (i.e. ABCD elements).

Self-State Modeling and the MIND Framework for Dynamic Mental Health: Mental health is increasingly viewed as a dynamic system of interacting psychological components (Hofmann and Hayes, 2019; Bickman, 2020). The MIND framework (Atzil-Slonim, 2025, 2026) models this through self-states composed of Affect, Behavior, Cognition, and Desire (ABCD), where mental health change reflects shifts in the dominance and interaction of competing states over time (Stiles, 2001; Revelle, 2007; Bromberg, 2014; Beck et al., 2021; Lazarus and Rafaeli, 2023). Most NLP work models isolated components such as emotion (Mayer et al., 2024) or cognition (Singh et al., 2024), rather than their temporal interactions. Recent CLPsych shared tasks have been bridging this gap through longitudinal modeling of mental states (Tsakalidis et al., 2022a; Tseriotou et al., 2025).

3 Task Definition and Instructions

Task 1.1: ABCD subelement identification and self-state composition Given a post, participants identify dominant adaptive and/or maladaptive ABCD subelements and combine them into self-state compositions. For each element: Affect (A), Behavior toward others (B-O), Behavior toward self (B-S), Cognition toward others (C-O), Cognition toward self (C-S), and Desire (D), a single dominant subelement is selected per valence. Posts may contain adaptive, maladaptive, both, or no self-states. Categorization in Appendix Table 10.

Task 1.2: Self-state presence rating Participants estimate adaptive and maladaptive self-state presence on a 1–5 scale, reflecting psychological centrality rather than lexical frequency. Both states may score highly. Evaluated as a regression task.

Task 2: Identify Moments of Change (MoC) Task 2 focuses on timeline-level detection of state

changes. Given chronological post sequences, participants identify **Switches**, defined as sudden well-being changes of ≥ 2 between consecutive posts (or the nearest prior post within one week), and **Escalations**, defined as gradual intensification across consecutive posts. Well-being scores follow rescaled GAF criteria (1–10). Posts can denote Switch, Escalation, both, or neither.

Task 3.1: Sequence-level summarization Given a sequence surrounding a change event (e.g. Switch), participants generate a structured summary describing the evolution of self-state dynamics. The exact change point must be inferred. Summaries aim to capture the main psychological theme, intra- and inter-state dynamics, and, when applicable, the change type (Switch/Escalation), direction, and timing. **Task 3.2: Cross-timeline dynamic signatures** Participants identify recurrent *Signatures of Deterioration* and *Signatures of Improvement* across timelines based on the MIND framework. Each signature describes a recurring dynamic pattern (within- or between self-states) and is supported by at least two sequences (with identifiers). Individual task details can be found in Fig.2, while Fig.1 provides an overview of the entire CLPsych 2026 shared task.

4 Data

The CLPsych 2026 dataset extends the 40 gold-standard Reddit timelines from CLPsych 2025 (Tseriotou et al., 2025), originally derived from the Reddit-New dataset introduced in CLPsych 2022 (Tsakalidis et al., 2022b). It contains 30 training and 10 test timelines with post-level annotations of adaptive/maladaptive ABCD subelements, well-being scores, self-state presence scores, and MIND-grounded summaries. For CLPsych 2026, 36 additional posts were added to complete clinically meaningful windows around Moments of Change (MoC), including Escalation spans and pre-change context. The dataset supports three levels of modeling aligned with the shared tasks (Section 3; Table 11): post-level self-state modeling (Task 1), timeline-level MoC detection of *Switches* and *Escalations* (Task 2), and change-centered sequence modeling and summarization (Task 3) (Details in Appendix A.

5 Evaluation Metrics

Task 1.1: ABCD Classification: Element presence uses binary F1; subelements use multiclass F1, macro-averaged into Adaptive/Maladaptive scores.

$$\textbf{Score} = \frac{F1_{\text{adapt}} + F1_{\text{maladapt}}}{2}$$

Task 1.2: Presence Rating: We report MAE, RMSE, QWK, and Spearman; ranking is based on averaged RMSE (lower is better).

$$\textbf{Score} = \frac{\text{RMSE}_{\text{adapt}} + \text{RMSE}_{\text{maladapt}}}{2}$$

Task 2: Moments of Change: We compute F1 at post-level (pooled) and timeline-level (macro over timelines).

$$\textbf{F1}_{\text{post}} = \frac{F1_S^{\text{post}} + F1_E^{\text{post}}}{2}$$

$$\textbf{F1}_{\text{tl}} = \frac{1}{2}\left(\frac{1}{T}\sum_{t=1}^{T} F1_{S,t}^{\text{tl}} + \frac{1}{T}\sum_{t=1}^{T} F1_{E,t}^{\text{tl}}\right)$$

$$\textbf{Score} = \frac{\text{F1}_{\text{post}} + \text{F1}_{\text{tl}}}{2}$$

Task 3.1: Sequence Summarization: Evaluate summaries ($\leq$350 words) using: CS, CT, BERTScore Recall, and ROUGE-L Recall.

$$\textbf{CS} = \frac{1}{|S|}\sum_{s\in S}\frac{1}{|G|}\sum_{g\in G}(1 - \text{NLI}(\text{Contr} \mid g, s))$$

$$\textbf{CT} = \frac{1}{|S|}\sum_{s\in S}\max_{g\in G}\text{NLI}(\text{Contr} \mid g, s)$$

$$\textbf{BS} = \frac{1}{|G|}\sum_{g\in G}\max_{s\in S}\text{BERTScore}(g, s)$$

Task 3.2: Dynamic Signatures: Evaluate deterioration/improvement signatures via human ratings of Fit, Recurrence, and Specificity.

$$\textbf{Score} = 0.5 \cdot \text{Fit} + 0.5 \cdot \text{HMean}(\text{Rec}, \text{Spec})$$

6 Codabench Submissions

Participants submitted JSON predictions via Codabench for Tasks 1, 2, and 3.1 (max three submissions), covering all test instances without raw text. Codabench handled automatic evaluation and leaderboard display. Task 3.2 was submitted by email with deterioration and improvement signatures and evaluated manually (Appendix C).

7 Teams & Results

Participating Teams: 39 teams (93 participants) registered, with 26 having prior participation in CLPsych shared tasks. Of these, 20 teams submitted outputs for at least one task and 13 submitted system papers (Table 12). Participation varied by task: 17 teams for Tasks 1.1/1.2, 18 for Task 2, 13 for Task 3.1, and 9 for Task 3.2.

7.1 Baselines

We use `Llama-3.1-8B-Instruct` and `TempoFormer` baselines; details are provided in Appendix D. Most experiments with the Llama models use zero-shot prompting and follow the

prompt structures proposed by Chan et al. (2025) and Lossio-Ventura et al. (2025).

Task 1: A one-shot structured prompting baseline with `Llama-3.1-8B-Instruct`, predicts adaptive/-maladaptive subelements and presence jointly. The prompt includes a single demonstration example and enforces strict JSON output. Both subtasks involve a single post using explicit label definitions.

Task 2: We provide three baselines: (1) zero-shot prompting to derive well-being scores and detect switches/escalations, (2) a pipeline using Task 1 outputs to compute normalized well-being and detect changes via thresholds and monotonic trends, and (3) fine-tuning `TempoFormer` on temporal post sequences. The latter models longitudinal dynamics directly. Switch and escalation detection are handled separately.

Task 3.1: Two baselines are provided: (1) zero-shot prompting with `Llama-3.1-8B-Instruct` to generate summaries capturing themes and self-state dynamics, and (2) a pipeline that augments prompts with Task 1 and Task 2 predictions. This includes subelements, presence scores, and change labels per post. The enriched context improves temporal coherence and interpretability.

Task 3.2: A zero-shot prompting baseline with `Llama-3.1-8B-Instruct` generates one deterioration and one improvement signature. The model uses structured prompts over sequence summaries to extract themes and self-state dynamics. Outputs are concise (<90 words).

Team	R	AvgSub	EP-A	EP-M	EP-Avg	SE-A	SE-M
CUNY	1	**0.442**	**0.613**	**0.749**	**0.681**	**0.388**	0.496
StateOfMIND	2	0.441	0.554	0.706	0.630	0.346	**0.537**
Meronym Labs	3	0.420	0.542	0.735	0.638	0.323	0.517
USAI	4	0.410	0.549	0.736	0.642	0.333	0.487
Aurevia	5	0.381	0.546	0.680	0.613	0.328	0.434
MKC	6	0.361	0.496	0.681	0.588	0.295	0.427
McMasterNLP	7	0.351	0.541	0.666	0.603	0.317	0.385
ull	8	0.335	0.478	0.546	0.512	0.330	0.340
BLUE	9	0.318	0.358	0.643	0.501	0.188	0.448
NoviceTrio	10	0.313	0.514	0.606	0.560	0.281	0.344
Afrilan	11	0.297	0.517	0.600	0.559	0.286	0.308
psytechlab	12	0.274	0.439	0.429	0.434	0.263	0.285
DreamerNLplus	13	0.254	0.440	0.437	0.439	0.266	0.241
CtbuY	14	0.236	0.392	0.479	0.436	0.204	0.268
debju	15	0.195	0.286	0.355	0.320	0.148	0.242
DrosophilAI	16	0.179	0.000	0.642	0.321	0.000	0.358
CSE_IIT_Ropar	17	0.175	0.209	0.323	0.266	0.149	0.202
Baseline	–	0.247	0.392	0.605	0.498	0.156	0.338

Table 1: Task 1.1 results. R = rank; AvgSub = average subelement macro F1; EP = element presence; SE = subelement macro F1; A/M = adaptive/maladaptive. Higher scores indicate better performance. Systems are ranked by AvgSub.

Team	R	Avg	M	A	QWK	C-RMSE	Spr.	MAE
Meronym Labs	1	**0.917**	**0.833**	1.000	0.677	**0.920**	0.697	**0.667**
USAI	2	0.942	0.905	0.979	**0.730**	0.943	**0.752**	0.681
Aurevia	3	0.981	1.027	**0.935**	0.645	0.982	0.674	0.688
CUNY	4	0.989	0.866	1.112	0.682	0.997	0.690	0.688
StateofMIND	5	0.994	0.858	1.130	0.695	1.003	0.702	0.701
MKC	6	1.010	1.014	1.007	0.570	1.010	0.604	0.757
McMasterNLP	7	1.035	0.957	1.112	0.526	1.037	0.570	0.799
CSE_IIT_Ropar	8	1.146	1.230	1.061	0.367	1.149	0.418	0.833
DrosophilAI	9	1.154	1.027	1.280	0.571	1.161	0.562	0.819
debju	10	1.156	1.264	1.047	0.232	1.161	0.361	0.875
ull	11	1.171	1.236	1.106	0.355	1.173	0.395	0.875
NoviceTrio	12	1.255	1.344	1.167	0.553	1.258	0.578	0.944
DreamerNLplus	13	1.285	1.312	1.258	0.411	1.286	0.416	0.931
Afrilan	14	1.329	1.219	1.439	0.340	1.333	0.404	1.014
psytechlab	15	1.407	1.389	1.424	0.367	1.407	0.376	1.063
CtbuY	16	1.501	1.572	1.429	0.480	1.502	0.591	1.160
BLUE	17	1.606	1.667	1.546	0.230	1.607	0.423	1.194
Baseline	–	1.424	1.439	1.409	0.555	1.424	0.603	1.083

Table 2: Task 1.2: Avg = average RMSE; M/A = maladaptive/adaptive RMSE; QWK = quadratic weighted kappa; Spr. = Spearman correlation. Lower Avg, RMSE, C-RMSE, and MAE are better; higher QWK and Spr. are better. Bold and underline indicate best and second-best results.

7.2 Results

We summarize system performance based on best runs (see Appendix C for full details).

System Characteristics: Most systems used pipeline designs where earlier task outputs informed later stages, often combined with RAG or hybrid frameworks.

Model Characteristics: All teams used LLMs, with fine-tuned transformers for structured prediction and LLMs for reasoning and summarization. Some incorporated lightweight or hybrid models, while temporal modeling ranged from explicit sequence models to prompt-based methods.

Task 1.1: Table 1 shows ABCD composition results ranked by Avg Subelement F1. **CUNY** (0.442) and **StateOfMIND** (0.441) lead, followed by **Meronym Labs** and **USAI**. Element presence consistently outperforms subelement prediction, highlighting difficulty in fine-grained classification. Maladaptive elements are easier to detect than adaptive (e.g., 0.749 vs. 0.613 for **CUNY**). Adaptive subelements show the largest performance drop, reflecting subtle and context-dependent patterns.

Task 1.2: Table 2 reports presence rating results ranked by Avg RMSE. **Meronym Labs** (0.917) leads, followed by **USAI** and **Aurevia**. Performance varies by dimension: best maladaptive RMSE (0.833) from **Meronym Labs**, best adaptive (0.935) from **Aurevia**. **USAI** shows strongest agreement (QWK 0.730, Spearman 0.752). Overall errors remain high, indicating task difficulty.

Team	R	Comb.	P-Esc	P-Mac	P-Sw	T-Esc	T-Mac	T-Sw
USAI	1	**0.600**	0.694	**0.639**	**0.583**	0.611	0.561	0.510
CtbuY	2	0.588	0.706	0.611	0.516	0.690	0.564	0.439
JNLP	3	0.580	**0.738**	0.615	0.492	0.649	0.545	0.441
CUNY	4	0.572	0.714	0.581	0.448	0.709	0.563	0.416
MKC	5	0.554	0.615	0.587	0.558	0.527	0.521	**0.514**
Codezone	6	0.553	0.636	0.504	0.372	**0.719**	**0.602**	0.484
Aurevia	7	0.484	0.667	0.556	0.444	0.416	0.413	0.411
Meronym Labs	8	0.466	0.596	0.510	0.423	0.452	0.421	0.391
debju	9	0.447	0.511	0.510	0.510	0.302	0.385	0.467
DreamerNLplus	10	0.442	0.550	0.491	0.432	0.387	0.392	0.397
McMasterNLP	11	0.412	0.375	0.357	0.339	0.660	0.467	0.274
BLUE	12	0.403	0.447	0.439	0.431	0.348	0.367	0.386
NoviceTrio	13	0.385	0.414	0.405	0.396	0.338	0.365	0.392
DrosophilAI	14	0.383	0.524	0.433	0.341	0.324	0.334	0.344
psytechlab	15	0.372	0.409	0.371	0.333	0.507	0.372	0.237
CSE_IIT_Ropar	16	0.357	0.276	0.284	0.293	0.562	0.430	0.299
Afrilan	17	0.268	0.217	0.286	0.356	0.221	0.250	0.279
Cloud	18	0.260	0.465	0.264	0.063	0.380	0.257	0.133
TempoFormer	–	0.572	0.667	0.561	0.456	**0.736**	0.583	0.430
Weighted Sum + T1.1	–	0.365	0.407	0.383	0.359	0.343	0.346	0.350
Llama ZS	–	0.272	0.000	0.169	0.337	0.400	0.376	0.352

Table 3: Task 2 results. R = rank; Comb. = combined post/timeline macro F1; P/T = post/timeline-level evaluation; Esc = escalation; Sw = switch; Mac = macro F1. Higher scores indicate better performance. Systems are ranked by Comb.

Task 2: Table 3 shows MoC detection results ranked by combined F1. **USAI** (0.600) leads, followed by **CtbuY** and **JNLP**. Systems specialize: **JNLP** excels in escalation (0.738), **USAI** in switches (0.583). At timeline level, **Codezone** (Esc) and **MKC** (Switch) perform best. Joint modeling of post- and timeline-level dynamics remains challenging. The high performance of the Tempoformer baseline shows the importance of architectures incorporating temporal awareness by design.

Task 3.1: Table 4 reports summarization results ranked by AvgRank. **Meronym Labs** leads, followed by **DreamerNLplus** and **CUNY**. Metrics vary: **Aurevia** has highest consistency, **psytechlab** lowest contradiction, and **USAI** best ROUGE/BERTScore. High overlap does not guarantee better ranking, showing trade-offs between faithfulness and similarity. Generating both consistent and aligned summaries remains difficult.

Task 3.2: Table 5 reports explanation generation results. For improvement, **DreamerNLplus** leads (0.7608), with complementary strengths across teams (fit, recurrence, specificity). For deterioration, **CSE_IIT_Ropar** leads (0.7891), though variability is higher. Some systems achieve perfect scores in one dimension but underperform overall. Task 3.2 evaluated signatures using *Fit*, *Recurrence*, and *Specificity*, with final rankings combining Fit and the harmonic mean of Recurrence and Specificity. For improvement, **DreamerNLplus ranked first** through high Specificity and strong Recurrence, followed by **CSE-IIT-Ropar** and **MKC**. For deterioration, **CSE-IIT-Ropar ranked first** with the highest Specificity and strong Fit, followed by **Aurevia** and **DreamerNLplus**.

Team	R	CS	CT	R-L	BERT-R	CS_r	CT_r	$R\text{-}L_r$	$BERT\text{-}R_r$	AvgRank
MERONYM_LABS	1	0.801	0.659	0.266	0.345	3	3	6	4	**4.0**
DreamerNLplus	2	0.735	0.767	0.285	0.345	7	7	4	3	5.3
CUNY	3	0.789	0.714	0.292	0.295	5	5	3	9	5.5
NoviceTrio	4	0.705	0.771	0.318	0.341	8	8	2	5	5.8
USAI	5	0.681	0.849	**0.333**	**0.365**	10	13	1	1	6.3
Aurevia	5	**0.866**	0.625	0.185	0.226	1	2	11	11	6.3
MKC	7	0.654	0.834	0.284	0.359	11	10	5	2	7.0
psytechlab	8	0.857	**0.571**	0.078	0.147	2	1	13	13	7.3
JNLP	9	0.791	0.666	0.117	0.164	4	4	12	12	8.0
McMasterNLP	9	0.770	0.761	0.208	0.255	6	6	10	10	8.0
CSE_IIT_Ropar	11	0.688	0.812	0.242	0.306	9	9	8	8	8.5
ULL	12	0.585	0.846	0.262	0.320	13	11	7	6	9.3
CtbuY	13	0.615	0.848	0.232	0.317	12	12	9	7	10.0
Baseline-1	–	0.763	0.753	0.255	0.226	8	7	9	13	9.3
Baseline-2	–	0.767	0.745	0.269	0.235	7	6	6	11	7.5

Table 4: Task 3.1 results. R = overall rank; CS = consistency; CT = contradiction; R-L = ROUGE-L recall; BERT-R = BERTScore recall; CS_r/CT_r = consistency/contradiction ranks; $R\text{-}L_r$/$BERT\text{-}R_r$ = ROUGE-L/BERTScore recall ranks; AvgRank = average rank across evaluation metrics. Higher scores indicate better performance, while lower AvgRank indicates better overall ranking. Bold and underline indicate best and second-best results, respectively.

Team	Improvement					Deterioration				
	R	Fit	Rec	Spec	Ov.	R	Fit	Rec	Spec	Ov.
DreamerNLplus	1	0.6250	0.8125	**1.0000**	**0.7608**	3	0.4375	0.6875	0.8750	0.6038
CSE_IIT_Ropar	2	**1.0000**	0.6875	0.3750	0.7426	1	0.8750	0.5625	**0.9375**	**0.7891**
MKC	3	0.7500	0.5625	0.9375	0.7266	7	0.1875	0.1875	0.5000	0.2301
McMasterNLP	4	0.6875	0.3750	0.7500	0.5938	8	0.1875	0.1875	0.3125	0.2109
psytechlab	5	0.6875	**1.0000**	0.2500	0.5437	6	0.6250	0.6250	0.2500	0.4911
Aurevia	6	0.3750	0.6250	0.5000	0.4653	2	0.6875	0.8125	0.5625	0.6761
MeronymLabs	7	0.2500	0.2500	0.5625	0.2981	4	0.4375	0.5625	0.8125	0.5511
CtbuY	8	0.2500	0.2500	0.0000	0.1250	5	**1.0000**	**1.0000**	0.0000	0.5000
CUNY	9	0.0000	0.0000	0.2500	0.0000	9	0.0000	0.0000	0.3125	0.0000
Baseline	–	0.3750	0.4375	0.3750	0.3894	–	0.5625	0.3750	0.4375	0.4832

Table 5: Task 3.2 results. R = rank; Fit = fit score; Rec = recurrence score; Spec = specificity score; Ov. = overall score. Left block reports improvement prediction performance, while the right block reports deterioration prediction performance. Higher scores indicate better performance. Systems are ranked independently within each setting by Ov.

8 Performance Analysis

Figure 4 shows state distributions, frequent ABCD sub-elements, and co-occurrence patterns.

Task 1 Performance Analysis: Distribution of Adaptive and Maladaptive Self-State Predictions: As shown in Table 6, maladaptive self-states received higher presence scores than adaptive states (2.83 vs. 2.18), with maladaptive predictions skewed toward higher scores (4–5) and adaptive predictions concentrated around lower scores, particularly score 2 (39.4%).

Element-Level and Sub-Element Prediction Trends: Adaptive predictions were mainly associated with **B-O**, **D**, and **B-S**, while maladaptive

State	Mean	Std	Score (%)				
			1	2	3	4	5
+	2.18	0.95	26.3	39.4	25.4	7.8	1.2
-	2.83	1.43	27.8	14.5	18.5	25.1	14.1

Table 6: Adaptive (+) and maladaptive (-) self-state presence score distributions.

predictions were dominated by **A**, **D**, and **C-S** (Table 7) (Stiles, 2001; Bromberg, 2014; Hofmann and Hayes, 2019). **B-O** (Behaviour towards Others) was the most frequent adaptive element (44.99%), whereas maladaptive **A** (Affect) was the dominant maladaptive element (50.93%).

Elements		Frequent Sub-elements	
Elem.	%	Sub-element	%
A^+	26.4	B-O(1)$^+$	40.8
B-O$^+$	45.0	B-S(1)$^+$	32.9
B-S$^+$	32.9	D(1)$^+$	18.6
C-O$^+$	20.5	C-O(1)$^+$	17.5
C-S$^+$	16.8	C-S(1)$^+$	16.3
D$^+$	38.8	D(5)$^+$	13.6
A$^-$	50.9	A(5)$^+$	12.3
B-O$^-$	20.2	C-S(2)$^-$	42.6
B-S$^-$	28.7	C-O(2)$^-$	32.0
C-O$^-$	37.3	B-S(2)$^-$	28.7
C-S$^-$	42.8	A(4)$^-$	22.4
D$^-$	43.6	D(6)$^-$	18.2
		D(2)$^-$	17.9
		B-O(2)$^-$	14.9

Table 7: Element-level and frequent sub-element prediction distributions. $^+$ Adaptive, $^-$ Maladaptive.

Co-occurrence and Combination Analysis: Adaptive and maladaptive self-states frequently co-occurred, with 58.1% of posts containing both and 14.4% containing neither.

8.1 Task 2 System Performance Analysis: Switch and Escalation Detection

Table 16 shows the type of model used by teams. Escalation prediction consistently outperforms Switch prediction across evaluation metrics (Table 8). Mean Escalation F1 reached 0.53 versus 0.41 for Switches, and the best Escalation F1 (0.74) exceeds the best Switch F1 (0.58). Most systems favor recall over precision, particularly for Switch prediction, resulting in a larger precision–recall gap. From a clinical perspective, the stronger predictability of Escalations relative to Switches may reflect important differences in the temporal organization of psychological change processes. Escalations appear to involve gradual amplification and accumulation of maladaptive self-state dynamics over time, producing more stable linguistic and behavioral traces that can be detected computationally. By contrast, Switches may correspond to more sudden reorganizations in self-state dominance, potentially triggered by external events, interpersonal ruptures, acute stressors, or sudden shifts in appraisal and affect regulation. This distinction is clinically meaningful because many deterioration trajectories in depression and related conditions are thought to emerge through progressively self-reinforcing cycles involving negative self-referential thinking, hopeless affect, withdrawal, and reduced engagement with adaptive goals or relationships (Hofmann and Hayes, 2019). Such gradual accumulation processes may naturally generate more coherent temporal signatures than rapid transitions. The findings suggest that timeline-based modeling may be particularly well-suited for detecting slowly consolidating maladaptive trajectories before more acute shifts occur.

Metric	Switch	Escalation
Mean Precision	0.35	0.57
Mean Recall	0.54	0.61
Mean F1	0.41	0.53
Median F1	0.43	0.54
Std. F1	0.12	0.15
Best F1	0.58	0.74
Mean Accuracy	0.67	0.73
Precision Range	0.09–0.55	0.23–0.80
Recall Range	0.05–1.00	0.17–1.00
F1 Range	0.06–0.58	0.22–0.74
P–R Gap	0.18	0.05

Table 8: Task 2 performance summary across submissions.

Presence Scores and Behavioural Predictions: Behavioural prediction rates vary across adaptive and maladaptive presence levels (Table 9; Figure 3). Adaptive states peak at moderate presence levels (2–3) before declining, whereas maladaptive states show a monotonic increase in behavioural instability, with Escalation rates rising from 4.34% at score 1 to 50.29% at score 5. These findings suggest that stronger maladaptive states are associated with escalating behavioural trajectories, while stronger adaptive states correspond to lower instability. Clinically, the adaptive and maladaptive patterns appear to reflect distinct temporal dynamics. Maladaptive states show a strong monotonic increase in both Switch and Escalation rates as presence scores increase, consistent with clinical models describing progressively self-reinforcing cycles of negative affect, hopelessness, and maladaptive self-referential processing in depression (Hayes et al., 2015). By contrast, adaptive states show higher Switch and Escalation rates at moderate presence levels, followed by declines at stronger levels. One possible interpretation is that moderate adaptive states may characterize more transitional or mixed phases in which adaptive and maladap-



Figure 3: Relationship between adaptive/maladaptive self-state presence and Task 2 behavioral outcomes (switches and escalations). The plots show how the presence and intensity of individual ABCD self-state elements correlate with moments of change, including abrupt switches and gradual escalations, across adaptive and maladaptive self-state configurations. Higher maladaptive self-state presence is associated with increased switch and escalation rates, while adaptive self-state presence exhibits more stable behavioral dynamics.

tive processes coexist, whereas strongly adaptive states may reflect reduced deterioration dynamics (Bonanno and Burton, 2013).

State	Score	Switch (%)	Escalation (%)
$^+$	1	18.04	22.15
$^+$	2	23.94	32.22
$^+$	3	26.53	26.02
$^+$	4	23.84	15.89
$^+$	5	13.33	13.33
$^-$	1	8.68	4.34
$^-$	2	16.67	15.81
$^-$	3	26.18	27.13
$^-$	4	33.42	44.55
$^-$	5	36.26	50.29

Table 9: Switch and Escalation rates across adaptive ($^+$) and maladaptive ($^-$) presence scores.

8.2 Task 3.2 Team Meta-Analysis

Characteristics of High-Performing Signatures
Strong Self-State Dynamics: The strongest systems consistently described: maladaptive dominance, adaptive emergence, suppression between self-states, reflective dialogue, coexistence and transition dynamics. Self-state terminology exhibited one of the strongest positive correlations with final score ($r = 0.5425$). For example, the top deterioration system (*CSEIITRopar*) models explicit feedback loops, tracks suppression of adaptive processes, describes temporal progression into deterioration.
Mechanistic Temporal Progression: Strongest systems described change as a *dynamic process*, not a static emotional state.

A common deterioration trajectory across high-performing systems (CSEIITRopar, DreamerNLplus, Aurevia, and MeronymLabs) described maladaptive progression as a reinforcing cascade from self-critical or detached cognitions (C-S/C-O), to depressive affect (A), to hopeless desire states (D), followed by collapse of self-care and relational engagement (B-S/B-O), culminating in maladaptive dominance (MD):

$$\text{C-S/C-O} \rightarrow \text{A} \rightarrow \text{D} \rightarrow \text{B-S/B-O collapse} \rightarrow \text{MD}$$

Improvement: Weakening maladaptive dominance, emergence of adaptive dialogue, self-care and connection behaviors, restoration of competence or belonging. This signature performed strongly because it: explicitly models transition, describes adaptive takeover rather than simple symptom reduction.
Generic Systems Performed Poorly: Such as CtbuY and CUNY scored poorly despite mentioning ABCD concepts because they lacked: temporal progression, coherent dynamic structure. Signature resembled keyword extraction rather than dynamic modeling : *Adaptive self-state, Depressive affect, Self-criticism, Maladaptive states*.
Temporal Dynamics and Change Events: Several high-performing systems explicitly modeled **Change Events (CE)**. The psytechlab submissions were particularly notable for capturing pre-/post-CE dynamics, silence and reflection patterns, and transitions between coexistence and dominance.

8.3 Key Findings

Recovery trajectories are characterized by weakening maladaptive states, particularly self-critical cognition (*C-S*), depressive affect (*A*), hopeless-

ness (*D*), and interpersonal detachment (*C*-*O*), followed by adaptive loops involving self-care (*B*-*S*), relating behaviors (*B*-*O*), positive affect, adaptive expectations, and more accepting self-perception. **Improvement generally reflects coexistence and reflective integration of adaptive and maladaptive states rather than abrupt replacement.** By contrast, deterioration forms **self-reinforcing maladaptive cycles** in which self-critical cognition amplifies depressive affect and hopelessness while suppressing interpersonal engagement and self-care. Multiple systems also identified interpersonal detachment as a precursor of worsening trajectories, consistent with models of depressive maintenance involving negative self-referential processing, hopelessness, and social withdrawal (Blatt, 2004; Shahar, 2015). Notably, **these clinically meaningful themes emerge consistently across methodologically diverse systems**, suggesting that temporally organized self-state interactions capture psychologically meaningful longitudinal dynamics.

9 Conclusion

We introduced the CLPsych 2026 Shared Task on modeling mental health changes in social media timelines through self-state prediction, change detection, and sequence-level summarization. Results showed strong performance from LLM-based and pipeline approaches, especially when combining structured prompting, retrieval, ensembling, and temporal modeling. Maladaptive self-states were consistently easier to detect than adaptive ones, likely due to stronger and more explicit negative emotional signals (Baumeister et al., 2001; Atzil-Slonim et al., 2024). Similarly, Escalations were more predictable than Switches, suggesting that gradual deterioration yields clearer temporal patterns than abrupt transitions (Hayes et al., 2015). High-performing systems captured clinically meaningful dynamics, including maladaptive feedback loops involving self-critical cognition, hopeless affect, and behavioral withdrawal, while improvement trajectories reflected gradual integration of adaptive and maladaptive states rather than abrupt replacement (Stiles, 2001; Bromberg, 2014). These findings highlight the value of temporally grounded self-state modeling for longitudinal mental health analysis.

Limitations

As in the vast majority of prior work leveraging social media for individual-level mental health assessments, this year's shared task involves individuals who generated content in self-selected online communities. The present tasks were conducted using social media posts made on various mental health-related subreddits in the English language, by users who willingly self-disclosed their thoughts and feelings. Generalization of the approaches presented in this work to other contexts and in other languages remains an open area of research.

Annotation was performed over 40 relatively short timelines due to the annotation load for clinical experts. This potentially hinders the performance of smaller supervised models, still leaving open questions around their true potential. Additionally, although the well-being score was annotated on the post-level with full timeline content visibility, the longitudinal manifestation of individuals' well-being remains underexplored. Since the annotation process involved selection of the most salient available adaptive and maladaptive spans for each ABCD element, this task does not yet explore the more nuanced selection of additional evidence spans and their connection to one another.

Although the dynamic evolution of self-states was, to some extent, addressed in this work with respect to summarization, there is still need to explore such dynamic progression through the lenses of other tasks such as monitoring and dialogue tracking. Finally, multimodality, which provides important cues especially in the clinical setting in terms of the manifestation of self-states, remains for now a future direction.

Ethics

This year's tasks explored the prediction of well-being scores from online posts of users over time, as well as the extraction of adaptive and maladaptive evidence spans and further summarization of self-state information at the post and timeline levels. This multi-task framework is grounded in the MIND scheme (Slonim, 2024) that views human experience as consisting of self-states fluctuating over time. Each self-state constitutes of identifiable units characterized by specific combinations of Affect, Behavior, Cognition, and Desire (ABCD).

While the evidence extraction and summaries provide some guidance with respect to ABCD elements and maladaptive and adaptive states, this

cannot be used for diagnostic purposes, especially without the involvement of human experts. Adaptive and maladaptive evidence extracted by such models should be reviewed by clinical experts or used to augment their capacity by efficiently presenting information to them.

Additionally, the task cannot make any claims about the potential evidence providing explanations for well-being scores. Rather, it forms a research direction towards making causal links between the two, paving the way towards language models that can better reason along their decision making process.

In terms of data, even though we are using publicly available content from Reddit, we prohibited its redistribution and the use of any third-party LLMs that would require sending (part of) the information to the provider's servers, to ensure protection of the sensitive content.

Acknowledgements

This work was supported by a UKRI/EPSRC Turing AI Fellowship to Maria Liakata (grant ref EP/V030302/1) and the Alan Turing Institute (grant ref EP/N510129/1). This work was supported by the Engineering and Physical Sciences Research Council [grant number EP/Y009800/1], through funding from Responsible Ai UK (KP0016) as a Keystone project lead by Maria Liakata. Diana Inkpen was supported by the Natural Science and Engineering Research Council of Canada. Juan Antonio Lossio-Ventura was supported by the National Institute of Mental Health Intramural Research Program (ZICMH002968). The contributions of the NIH authors are considered Works of the United States Government. The findings and conclusions presented in this paper are those of the author(s) and do not necessarily reflect the views of the NIH or the U.S. Department of Health and Human Services. The shared task organizers would like to express their gratitude to the anonymous users of Reddit whose data feature in this year's shared task dataset; to the clinical experts from Bar-Ilan University who annotated the data for all tasks; to all team members for their participation; and to ACL for its support for CLPsych.

References

Prottay Kumar Adhikary, Aseem Srivastava, Shivani Kumar, Salam Michael Singh, Puneet Manuja, Jini K Gopinath, Vijay Krishnan, Swati Kedia Gupta, Koushik Sinha Deb, and Tanmoy Chakraborty. 2024. Exploring the efficacy of large language models in summarizing mental health counseling sessions: benchmark study. *JMIR Mental Health*, 11:e57306.

Mostafa M Amin, Erik Cambria, and Björn W Schuller. 2023. Will affective computing emerge from foundation models and general ai? a first evaluation on chatgpt. *IEEE Intelligent Systems*, 38(2):15–23.

Anson Antony, Gautam Vijay Kumar, and Annika Marie Schoene. 2026. Agentic pipelines meet retrieval-augmented icl: A zero-training approach to mental health modeling. In *Proceedings of the Eleventh Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Elham Asgari, Nina Montana-Brown, Magda Dubois, Saleh Khalil, Jasmine Balloch, and Dominic Pimenta. 2024. A framework to assess clinical safety and hallucination rates of llms for medical text summarisation. *medRxiv*, pages 2024–09.

Dana Atzil-Slonim. 2025. Multimodal intrapersonal and interpersonal dynamics (MIND): A transtheoretical coding manual. Preprint, Bar-Ilan University.

Dana Atzil-Slonim. 2026. Leveraging theoretical and technological innovations to study the mechanisms that underlie therapeutic change in psychotherapy. In Louis G. Castonguay, Dana Atzil-Slonim, Michael Barkham, and Wolfgang Lutz, editors, *Practice-Based Evidence in the Psychological Therapies: Toward Policy Implications for Research, Training, and Clinical Guidelines*. Oxford University Press, New York.

Dana Atzil-Slonim, Juan Martin Gomez Penedo, and Wolfgang Lutz. 2024. Leveraging novel technologies and artificial intelligence to advance practice-oriented research. *Administration and Policy in Mental Health and Mental Health Services Research*, 51(3):306–317.

Roy F Baumeister, Ellen Bratslavsky, Catrin Finkenauer, and Kathleen D Vohs. 2001. Bad is stronger than good. *Review of general psychology*, 5(4):323–370.

Ulya Bayram and Lamia Benhiba. 2022. Emotionally-informed models for detecting moments of change and suicide risk levels in longitudinal social media data. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 219–225, Seattle, USA. Association for Computational Linguistics.

Aaron T Beck, Molly R Finkel, and Judith S Beck. 2021. The theory of modes: Applications to schizophrenia and other psychological conditions. *Cognitive Therapy and Research*, 45:391–400.

Leonard Bickman. 2020. Improving mental health services: A 50-year journey from randomized experiments to artificial intelligence and precision

mental health. *Administration and Policy in Mental Health and Mental Health Services Research*, 47(5):795–843.

Amirmohammad Ziaei Bideh, Shameed Charlomar Job, Ava Yahyapour, and Alla Rozovskaya. 2026. Cuny at clpsych 2026: A pipeline approach to classification and summarization of mental health change. In *Proceedings of the Eleventh Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Sidney J Blatt. 2004. *Experiences of depression: Theoretical, clinical, and research perspectives.* American Psychological Association.

George A Bonanno and Charles L Burton. 2013. Regulatory flexibility: An individual differences perspective on coping and emotion regulation. *Perspectives on psychological science*, 8(6):591–612.

Philip M Bromberg. 2014. *Standing in the spaces: Essays on clinical process trauma and dissociation*. Routledge.

Ana-Maria Bucur, Marcos Zampieri, Tharindu Ranasinghe, and Fabio Crestani. 2026. A survey on multilingual mental disorders detection from social media data. In *Proceedings of the 19th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 893–918, Rabat, Morocco. Association for Computational Linguistics.

Igor Buyanov, Nafisa Valieva, and Ekaterina Mazurina. 2026. psytechlab at clpsych 2026: Utilising natural language processing methods and large language models for social media text analysis. In *Proceedings of the Eleventh Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Rafael A Calvo, David N Milne, M Sazzad Hussain, and Helen Christensen. 2017. Natural language processing in mental health applications using non-clinical texts. *Natural Language Engineering*, 23(5):649–685.

Callum Chan, Sunveer Khunkhun, Diana Inkpen, and Juan Antonio Lossio-Ventura. 2025. Prompt engineering for capturing dynamic mental health self states from social media posts. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 256–267, Albuquerque, New Mexico. Association for Computational Linguistics.

Jenny Chim, Julia Ive, and Maria Liakata. 2025. Evaluating synthetic data generation from user generated text. *Computational Linguistics*, 51(1):191–233.

Jenny Chim, Adam Tsakalidis, Dimitris Gkoumas, Dana Atzil-Slonim, Yaakov Ophir, Ayah Zirikly, Philip Resnik, and Maria Liakata. 2024. Overview of the CLPsych 2024 shared task: Leveraging large language models to identify evidence of suicidality risk in online posts. In *Proceedings of the 9th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2024)*, pages 177–190, St. Julians, Malta. Association for Computational Linguistics.

Glen Coppersmith, Mark Dredze, Craig Harman, Kristy Hollingshead, and Margaret Mitchell. 2015. CLPsych 2015 shared task: Depression and PTSD on Twitter. In *Proceedings of the 2nd Workshop on Computational Linguistics and Clinical Psychology: From Linguistic Signal to Clinical Reality*, pages 31–39, Denver, Colorado. Association for Computational Linguistics.

Duc Minh Do, Tin Trung Pham, Vu Tran, and Minh Le Nguyen. 2026. Prompt-based modeling of moments of change and change summaries in mental health timelines. In *Proceedings of the Eleventh Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Muskan Garg. 2023. Mental health analysis in social media posts: A survey: M. garg. *Archives of Computational Methods in Engineering*, 30(3):1819–1842.

Muskan Garg. 2024. Wellxplain: Wellness concept extraction and classification in reddit posts for mental health analysis. *Know.-Based Syst.*, 284(C).

Adele M Hayes, Carly Yasinski, J Ben Barnes, and Claudi LH Bockting. 2015. Network destabilization and transition in depression: New methods for studying the dynamics of therapeutic change. *Clinical psychology review*, 41:27–39.

Anthony Hills, Adam Tsakalidis, and Maria Liakata. 2023. Time-aware predictions of moments of change in longitudinal user posts on social media. In *Advanced Analytics and Learning on Temporal Data*, pages 293–305, Cham. Springer Nature Switzerland.

Anthony Hills, Talia Tseriotou, Xenia Miscouridou, Adam Tsakalidis, and Maria Liakata. 2024. Exciting mood changes: A time-aware hierarchical transformer for change detection modelling. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 12526–12537, Bangkok, Thailand. Association for Computational Linguistics.

Stefan G Hofmann and Steven C Hayes. 2019. The future of intervention science: Process-based therapy. *Clinical Psychological Science*, 7(1):37–50.

Stephanie Homan, Marion Gabi, Nina Klee, Sandro Bachmann, Ann-Marie Moser, Martina Duri', Sofia Michel, Anna-Marie Bertram, Anke Maatz, Guido Seiler, Elisabeth Stark, and Birgit Kleim. 2022. Linguistic features of suicidal thoughts and behaviors: A systematic review. *Clinical Psychology Review*, 95:102161.

Yining Hua, Fenglin Liu, Kailai Yang, Zehan Li, Hongbin Na, Yi-han Sheu, Peilin Zhou, Lauren V Moran, Sophia Ananiadou, David A Clifton, et al. 2025. Large language models in mental health care: a scoping review. *Current Treatment Options in Psychiatry*, 12(1):27.

Kyomin Hwang, Hyeonjin Kim, Hyunho Lee, and Nojun Kwak. 2026. Team mkc at clpsych 2026: Capturing and characterizing mental health changes through social media timeline dynamics. In *Proceedings of the Eleventh Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Ayal Klein, Jiayu Song, Jenny Chim, Liran Keren, Andreas Triantafyllopoulos, Björn W Schuller, Maria Liakata, and Dana Atzil-Slonim. 2024. Clinical insights from social media: Assessing summaries of large language models and humans.

Pawan Kumar, Ankit Meshram, Shubham Jha, and Loitongbam Gyanendro Singh. 2026. Theory-explicit prompting for mind self-states: Hierarchical llms and dynamic signature extraction in mental health timelines. In *Proceedings of the Eleventh Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Gal Lazarus and Eshkol Rafaeli. 2023. Modes: Cohesive personality states and their interrelationships as organizing concepts in psychopathology. *Journal of Psychopathology and Clinical Science*, 132(3):238.

Aziliz Le Glaz, Yannis Haralambous, Deok-Hee Kim-Dufor, Philippe Lenca, Romain Billot, Taylor C Ryan, Jonathan Marsh, Jordan Devylder, Michel Walter, Sofian Berrouiguet, et al. 2021. Machine learning and natural language processing in mental health: systematic review. *Journal of medical Internet research*, 23(5):e15708.

Yucheng Li, Bo Dong, Frank Guerin, and Chenghua Lin. 2023. Compressing context to enhance inference efficiency of large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 6342–6353, Singapore. Association for Computational Linguistics.

Chandreen Liyanage, Muskan Garg, Vijay Mago, and Sunghwan Sohn. 2023. Augmenting Reddit posts to determine wellness dimensions impacting mental health. In *The 22nd Workshop on Biomedical Natural Language Processing and BioNLP Shared Tasks*, pages 306–312, Toronto, Canada. Association for Computational Linguistics.

Juan Antonio Lossio-Ventura, Callum Chan, Arshitha Basavaraj, Hugo Alatrista-Salas, Francisco Pereira, and Diana Inkpen. 2025. 5cNLP at BioLaySumm2025: Prompts, retrieval, and multimodal fusion. In *Proceedings of the 24th Workshop on Biomedical Language Processing (Shared Tasks)*, pages 215–231, Vienna, Austria. Association for Computational Linguistics.

Scott M. Lundberg and Su-In Lee. 2017. A unified approach to interpreting model predictions. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, NIPS'17, page 47684777, Red Hook, NY, USA. Curran Associates Inc.

Tobias Mayer, Neha Warikoo, Amir Eliassaf, Dana Atzil-Slonim, and Iryna Gurevych. 2024. Predicting client emotions and therapist interventions in psychotherapy dialogues. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1463–1477, St. Julian's, Malta. Association for Computational Linguistics.

George Michalopoulos, Kyle Williams, Gagandeep Singh, and Thomas Lin. 2022. MedicalSum: A guided clinical abstractive summarization model for generating medical reports from patient-doctor conversations. In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 4741–4749, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Arturo Montejo-Ráez, M. Dolores Molina-González, Salud María Jiménez-Zafra, Miguel Ángel García-Cumbreras, and Luis Joaquín García-López. 2024. A survey on detecting mental disorders with natural language processing: Literature review, trends and challenges. *Comput. Sci. Rev.*, 53(C).

Abir Naskar and Mike Conway. 2026. Hierarchical multi-stage modeling of adaptive and maladaptive self-states in social media timelines. In *Proceedings of the Eleventh Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Thong Nguyen, Andrew Yates, Ayah Zirikly, Bart Desmet, and Arman Cohan. 2022. Improving the generalizability of depression detection by leveraging clinical questionnaires. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8446–8459, Dublin, Ireland. Association for Computational Linguistics.

David Owen, Amy J Lynham, Sophie E Smart, Antonio F Pardiñas, and Jose Camacho Collados. 2024. Ai for analyzing mental health disorders among social media users: Quarter-century narrative review of progress and challenges. *Journal of Medical Internet Research*, 26:e59225.

Javier Parapar, Patricia Martín-Rodilla, David E Losada, and Fabio Crestani. 2023. Overview of erisk 2023: Early risk prediction on the internet. In *International Conference of the Cross-Language Evaluation Forum for European Languages*, pages 294–315. Springer.

Alina Ponomareva, Nina Stekacheva Sancho, and Karina Litvinova. 2026. Stateofmind at clpsych 2026 shared task. In *Proceedings of the Eleventh Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Federico Ravenda, Volodymyr Karpenko, Antonietta Mira, and Andrea Raballo. 2026. P2p - from posts to patterns: An llm ensemble approach to mental health dynamics detection. In *Proceedings of the Eleventh Workshop on Computational Linguistics and Clinical*

Psychology. Association for Computational Linguistics.

William Revelle. 2007. Experimental approaches to the study of personality. *Handbook of research methods in personality psychology*, pages 37–61.

Nathan Roll, Irene Yi, Sufian Aldogom, Grace Brown, Eric Basile, Isaac Gutterman, Lakshika Tennakoon, and Ammar Ahmed. 2026. Team aurevia at clpsych 2026: Local healthcare nlp for schema-constrained self-state modeling. In *Proceedings of the Eleventh Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Ramit Sawhney, Shivam Agarwal, Atula Tejaswi Neerkaje, Nikolaos Aletras, Preslav Nakov, and Lucie Flek. 2022a. Towards suicide ideation detection through online conversational context. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval*, SIGIR '22, page 17161727, New York, NY, USA. Association for Computing Machinery.

Ramit Sawhney, Atula Neerkaje, and Manas Gaur. 2022b. A risk-averse mechanism for suicidality assessment on social media. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 628–635, Dublin, Ireland. Association for Computational Linguistics.

Golan Shahar. 2015. *Erosion: The psychopathology of self-criticism*. Oxford University Press.

Han-Chin Shing, Suraj Nair, Ayah Zirikly, Meir Friedenberg, Hal Daumé III, and Philip Resnik. 2018. Expert, crowdsourced, and machine assessment of suicide risk via online postings. In *Proceedings of the Fifth Workshop on Computational Linguistics and Clinical Psychology: From Keyboard to Clinic*, pages 25–36.

Gopendra Vikram Singh, Sai Vardhan Vemulapalli, Mauajama Firdaus, and Asif Ekbal. 2024. Deciphering cognitive distortions in patient-doctor mental health conversations: A multimodal LLM-based detection and reasoning framework. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 22546–22570, Miami, Florida, USA. Association for Computational Linguistics.

Dana Atzil Slonim. 2024. Self-other dynamics (sod): A transtheoretical coding manual.

Jiayu Song, Mahmud Akhter, Dana Atzil Slonim, and Maria Liakata. 2025. Temporal reasoning for timeline summarisation in social media.

Jiayu Song, Jenny Chim, Adam Tsakalidis, Julia Ive, Dana Atzil-Slonim, and Maria Liakata. 2024. Combining hierachical VAEs with LLMs for clinically meaningful timeline summarisation in social media. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 14651–14672, Bangkok, Thailand. Association for Computational Linguistics.

Sajad Sotudeh, Nazli Goharian, and Zachary Young. 2022. Mentsum: A resource for exploring summarization of mental health online posts.

Aseem Srivastava, Tharun Suresh, Sarah Peregrine, Lord, Md. Shad Akhtar, and Tanmoy Chakraborty. 2022. Counseling summarization using mental health knowledge guided utterance filtering.

William B Stiles. 2001. Assimilation of problematic experiences. *Psychotherapy: Theory, Research, Practice, Training*, 38(4):462.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022a. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022b. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Talia Tseriotou, Ryan Chan, Adam Tsakalidis, Iman Munire Bilal, Elena Kochkina, Terry Lyons, and Maria Liakata. 2024a. Sig-networks toolkit: Signature networks for longitudinal language modelling. In *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics: System Demonstrations*, pages 223–237, St. Julians, Malta. Association for Computational Linguistics.

Talia Tseriotou, Jenny Chim, Ayal Klein, Aya Shamir, Guy Dvir, Iqra Ali, Cian Kennedy, Guneet Singh Kohli, Anthony Hills, Ayah Zirikly, Dana Atzil-Slonim, and Maria Liakata. 2025. Overview of the CLPsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 193–217, Albuquerque, New Mexico. Association for Computational Linguistics.

Talia Tseriotou, Adam Tsakalidis, Peter Foster, Terence Lyons, and Maria Liakata. 2023. Sequential path signature networks for personalised longitudinal language modeling. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 5016–5031, Toronto, Canada. Association for Computational Linguistics.

Talia Tseriotou, Adam Tsakalidis, and Maria Liakata. 2024b. TempoFormer: A transformer for temporally-aware representations in change detection. In *Proceedings of the 2024 Conference on Empirical*

Methods in Natural Language Processing, pages 19635–19653, Miami, Florida, USA. Association for Computational Linguistics.

David Villarreal-Zegarra, C Mahony Reategui-Rivera, Jackeline García-Serna, Gleni Quispe-Callo, Gabriel Lázaro-Cruz, Gianfranco Centeno-Terrazas, Ricardo Galvez-Arevalo, Stefan Escobar-Agreda, Alejandro Dominguez-Rodriguez, and Joseph Finkelstein. 2024. Self-administered interventions based on natural language processing models for reducing depressive and anxiety symptoms: Systematic review and meta-analysis. *JMIR Mental Health*, 11.

Xuhai Xu, Bingsheng Yao, Yuanzhe Dong, Saadia Gabriel, Hong Yu, James Hendler, Marzyeh Ghassemi, Anind K. Dey, and Dakuo Wang. 2024a. Mental-llm: Leveraging large language models for mental health prediction via online text data. *Proc. ACM Interact. Mob. Wearable Ubiquitous Technol.*, 8(1).

Xuhai Xu, Bingsheng Yao, Yuanzhe Dong, Saadia Gabriel, Hong Yu, James Hendler, Marzyeh Ghassemi, Anind K. Dey, and Dakuo Wang. 2024b. Mental-llm: Leveraging large language models for mental health prediction via online text data. *Proc. ACM Interact. Mob. Wearable Ubiquitous Technol.*, 8(1).

Xuhai Xu, Bingsheng Yao, Yuanzhe Dong, Saadia Gabriel, Hong Yu, James Hendler, Marzyeh Ghassemi, Anind K. Dey, and Dakuo Wang. 2024c. Mental-llm: Leveraging large language models for mental health prediction via online text data. *Proc. ACM Interact. Mob. Wearable Ubiquitous Technol.*, 8(1).

Kailai Yang, Shaoxiong Ji, Tianlin Zhang, Qianqian Xie, Ziyan Kuang, and Sophia Ananiadou. 2023. Towards interpretable mental health analysis with large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 6056–6077, Singapore. Association for Computational Linguistics.

Kailai Yang, Tianlin Zhang, Ziyan Kuang, Qianqian Xie, Jimin Huang, and Sophia Ananiadou. 2024. Mentallama: Interpretable mental health analysis on social media with large language models. In *Proceedings of the ACM Web Conference 2024*, WWW '24, page 44894500, New York, NY, USA. Association for Computing Machinery.

Hongyi Zhang, Derron Li, Scarlett Cleary, Aadi Sanghani, Akshay Krishna Sirigana, Brian Miguel Pimentel, Kelsey Isman, Kian Omoomi, Vasudha Varadarajan, Charles Welch, and Allison Claire Lahnala. 2026. Mcmasters of change: Predicting well-being states and transitions from longitudinal language. In *Proceedings of the Eleventh Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Mengjia Zhang and Yi Yang. 2026. A multi-strategy framework for mental health change detection in social media timelines. In *Proceedings of the Eleventh Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Maryia Zhyrko, Daisy Monika Lal, Erik van Mulligen, and Lifeng Han. 2026. Dreamernlplus: Interpretable modeling of mental health dynamics from social media timelines using hybrid rule-based and rag methods. In *Proceedings of the Eleventh Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Ayah Zirikly and Mark Dredze. 2022. Explaining models of mental health via clinically grounded auxiliary tasks. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 30–39, Seattle, USA. Association for Computational Linguistics.

Ayah Zirikly, Philip Resnik, Özlem Uzuner, and Kristy Hollingshead. 2019. CLPsych 2019 shared task: Predicting the degree of suicide risk in Reddit posts. In *Proceedings of the Sixth Workshop on Computational Linguistics and Clinical Psychology*, pages 24–33, Minneapolis, Minnesota. Association for Computational Linguistics.

Appendix A Data Annotation

The dataset combines MIND annotations from CLPsych 2025 with additional annotations introduced for CLPsych 2026. In CLPsych 2025, clinical psychology Masters students annotated posts using the MIND framework, labeling adaptive/-maladaptive ABCD subelements, self-state presence scores, well-being scores, and post-level summaries under supervised reconciliation procedures (Tseriotou et al., 2025). Here, 36 additional posts were annotated to complete change-centered sequences for Tasks 2 and 3. For Task 3.1, gold sequence summaries were generated using Qwen-2.5-32B conditioned on post text, MIND summaries, ABCD annotations, self-state scores, and MoC labels, then manually reviewed and revised by a clinical expert. The summaries capture intra- and inter-state dynamics, relative self-state dominance, change direction, and pre-change context surrounding Switches and Escalations.

A.1 MIND Framework

Table 10 shows categories and sub-categories within the MIND framework.

Appendix B Data Statistics

Table 11 shows data statistics.

Appendix C Participant Submissions

This section presents an overview of the registration process (§C.1), individual systems (§C.2) from each participating team and provides an overview of methods (§C.3) and (§C.4) contains performance analysis across each task.

C.1 Registration Process

The registration and participation procedure comprised three stages: (a) completion of individual and team registration via an online form, (b) review and signing of a data sharing agreement, and (c) receipt of access instructions for the training data, which was provided as a password-protected compressed file. During the registration phase, the organizing team also assisted participants seeking collaborators for team formation. The data sharing agreement required teams to maintain the dataset in secure, password-protected private storage and prohibited both explicit and implicit data sharing through third-party platforms, including proprietary large language model services. For *Codabench-based* participation, each team was required to nominate one designated representative and share that users Codabench ID with the organizers prior to submission. Unless stated otherwise, teams were allowed up to three submissions per task on Codabench. Tasks 1, 2, and 3.1 were submitted through Codabench, whereas Task 3.2 was submitted separately via email in the required JSON format for human evaluation. Although participants could choose to make their scores visible on the Codabench leaderboard, these leaderboard positions were not treated as official rankings, since the final shared task rankings were determined using the shared tasks task-specific evaluation procedures. Table 12 summarizes the participating teams and their submission activity.

C.2 Individual Team Submissions

- CUNY (Bideh et al., 2026) employed a modular pipeline using locally served open-weight LLMs including Gemma 3, Qwen 3.5, and GPT-OSS. Tasks 1.1 and 1.2 used ensemble-based ICL prompting with majority voting, achieving the top-ranked Task 1.1 result. Task 2 used SVM and Random Forest classifiers trained on upstream predictions such as presence scores and inter-post deltas. Task 3.1 applied label-augmented ICL for improved summarization, with the team ranking 1st on Task 1.1 and 3rd on Task 3.1.

- StateOfMIND (Ponomareva et al., 2026) used a retrieval-augmented in-context learning ensemble with two open-weight LLMs and three sequential prompts for Tasks 1.1 and 1.2. Their framework combined unified, adaptive-focused, and affect-focused prompting strategies with deterministic aggregation of ABCD predictions. The system leveraged post-level retrieval and ensemble inference to improve subelement and presence prediction. Their best submission ranked 2nd for Task 1.1 and 5th for Task 1.2.

- Meronym Labs (Antony et al., 2026) proposed a zero-training retrieval-augmented in-context learning framework using frozen LLMs such as Qwen 3.5-27B and Gemma 4-31B with ChromaDB retrieval. Static and dynamically retrieved examples were integrated into prompts for ABCD classification and presence prediction. Task 2 used timeline-level prompting with automated prompt optimization, while Task 3 introduced a multi-agent contradiction-aware summarization pipeline with NLI reranking using DeBERTa-v3-large. The



Figure 4: Task 1 analysis: state distributions, frequent ABCD sub-elements, and co-occurrence patterns.

Category		Sub-Categories	
		Adaptive Example	Maladaptive Example
Affect	Type of emotion expressed by a person.	Calm/Laid back, Emotional Pain/Grieving, Content/Happy, Vigor/Energetic, Justifiable Anger/Assertive Anger, Proud	Anxious/Tense/Fearful, Depressed/Desperate/ Hopeless, Mania, Apathetic/Don't care/Blunted, Angry (Aggressive, Disgust, Contempt), Ashamed/Guilty
Behavior	**Behavior of the self with the Other (BO)** The person's main behavior(s) toward the other.	Relating behavior, Autonomous behavior	Fight or flight behavior, Overcontrolled/controlling behavior
	Behavior toward the Self (BS) The person's main behavior(s) toward the self.	Self-care behavior	Self-harm/Neglect/ Avoidance behavior
Cognition	**Cognition of the Other (CO)** The person's main perceptions of the other.	Perception of the other as related, Perception of the other as facilitating autonomy/ competence needs	Perception of the other as detached or over attached, Perception of the other as blocking autonomy needs
	Cognition of the Self (CS) The person's main self-perceptions.	Self-acceptance and self-compassion	Self-criticism
Desire	The person's main desire, need, intention, fear or expectation.	Relatedness, Autonomy and adaptive control, Competence, Self-esteem, Self-care	Expectation that relatedness need will not be met, Expectation that autonomy needs will not be met, Expectation that competence needs will not be met

Table 10: ABCD elements (Categories) with explanations, and their sub-categories.

Statistic	Train	Test	Overall
Timelines	30	10	40
Posts	373	92	465
Avg. Tok./Post	118.4	120.2	118.8
Median Tok./Post	47.0	81.0	60.0
WB Available	236	73	309
WB Missing	137	19	156
WB Mean	5.24	5.29	5.25
WB Std.	1.87	2.15	1.94
Switches	78	21	99
Escalations	75	24	99
Both	27	11	38
Neither	247	58	305
ADT A	43	21	64
ADT B-O	125	38	163
ADT B-S	84	23	107
ADT C-O	50	14	64
ADT C-S	52	15	67
ADT D	118	36	154
ADT Total	472	147	619
MAL A	161	44	205
MAL B-O	36	11	47
MAL B-S	59	22	81
MAL C-O	114	29	143
MAL C-S	135	30	165
MAL D	110	38	148
MAL Total	615	174	789
Deterioration	49	15	64
Improvement	25	04	29

Table 11: CLPsych 2026 dataset statistics.

framework avoided any task-specific fine-tuning while supporting structured psychological summarization.

- USAI (Ravenda et al., 2026) proposed an ensemble-based framework combining multiple

Team	1.1	1.2	2	3.1	3.2	Paper	System Summary
Aurevia	1	1	1	1	1	✓	✓
BLUE	1	1	1	–	–	×	✓
Codezone	–	–	1	–	–	×	✓
CSE_IIT_Ropar	1	1	1	1	1	✓	×
CUNY	1	1	1	1	1	✓	✓
CtbuY	1	1	1	1	1	✓	✓
DreamerNLplus	1	1	1	1	1	✓	✓
JNLP	–	–	1	1	–	✓	✓
McMasterNLP	1	1	1	1	1	✓	✓
Meronym Labs	1	1	1	1	1	✓	×
MKC	1	1	1	1	1	✓	✓
NoviceTrio	1	1	1	1	–	✓	✓
psytechlab	1	1	1	1	1	✓	✓
StateOfMIND	1	1	–	–	–	✓	✓
ULL	1	1	–	1	–	×	✓
USAI	1	1	1	1	–	✓	×
Total	**14**	**14**	**14**	**13**	**9**	**13**	**13**

Table 12: Team participation across tasks, paper submission status, and availability of system summaries.

open-source LLMs for Tasks 1, 2, and 3.1. Weighted voting and weighted averaging were used for ABCD subelement classification and presence estimation, respectively. Task 2 incorporated an additional refinement stage for improving temporal consistency in Switch and Escalation detection. For Task 3.1, few-shot prompting was applied using predicted annotations and change labels to generate sequence summaries.

- Aurevia (Roll et al., 2026) developed a privacy-conscious local healthcare NLP pipeline using TF-IDF retrieval, schema-constrained prompting with Qwen2.5-72B-Instruct, ordinal calibration, and de-

terministic post-processing. The system combined non-neural retrieval methods with local LLM-based JSON prediction for ABCD classification and presence estimation. Task 2 used handcrafted temporal signals and rule-based calibration, while Task 3 emphasized contradiction-aware retrieval-augmented summarization. Aurevia ranked 3rd for Task 1.2, 5th for Task 3.1, and achieved the best Task 3.1 consistency score.

- MKC (Hwang et al., 2026) developed a unified LLM-based framework using LoRA fine-tuned Qwen3 embedding models with 5-fold cross-validation for Tasks 1 and 2. Weighted Cross-Entropy and weighted Huber losses addressed severe class imbalance, while sliding-window temporal modeling supported Switch and Escalation detection. For summarization, the team fine-tuned Qwen3/Qwen3.5 models using supervised instruction tuning and generated psychological signatures in a zero-shot manner using Qwen3.5-9B. Their framework integrated both discriminative and generative timeline modeling.

- McMasterNLP (Zhang et al., 2026) proposed a multi-stage framework combining representation learning, sequence modeling, and prompt-based summarization. Task 1 used a dual-encoder architecture integrating MentalRoBERTa embeddings with LLM-generated ABCD archetype similarity features for subelement and presence prediction. Task 2 employed BiLSTM-based sequence models for detecting switches and escalations in well-being timelines. Task 3 used prompt-engineered Qwen3.5-9B summarization, with the system ranking 7th in both Tasks 1.1 and 1.2.

- NoviceTrio (Naskar and Conway, 2026) introduced a hierarchical multi-stage framework combining a multi-task transformer encoder with a four-stage instruction-tuned LLM pipeline. Stage 1 jointly predicted state presence and intensity, while Stage 2 performed element-conditioned subelement classification and BIO-based evidence extraction using structural masking. A staged Qwen3-4B LoRA pipeline sequentially handled state detection, evidence extraction, and refined presence estimation. RoBERTa achieved an 8.3% Macro-F1 improvement over baseline, while Qwen3 delivered the strongest overall performance.

- PSYTECHLAB (Buyanov et al., 2026) proposed a privacy-preserving framework combining locally deployed language models with task-specific neural architectures. Their system used ModernBERT for ABCD subelement classification and BiLSTM networks for temporal modeling of moments of change. Sequence summarization was handled using zero-shot LLM prompting. The framework emphasized secure local processing of sensitive mental health timelines.

- DreamerNLplus (Zhyrko et al., 2026) developed a hybrid interpretable framework spanning all subtasks. Task 1.1 combined Ollama-based LLM data augmentation with DeBERTa fine-tuning for ABCD classification, while Task 1.2 used Random Forest regression over structured feature vectors. Task 2 applied few-shot prompting with locally deployed Llama 3.1 for temporal change detection. For Tasks 3.1 and 3.2, the team explored both deterministic rule-based summarization and RAG-based signature extraction pipelines.

- CtbuY (Zhang and Yang, 2026) proposed a multi-strategy fusion framework integrating zero-shot prompting, QLoRA fine-tuning, and hierarchical TextCNN classification for Task 1. Task 2 employed Mental-BERT embeddings with log-scale temporal encoding and a three-layer BiLSTM trained using Focal Loss. Task 3.1 used dynamic RAG retrieval with Qwen-2.5-7B, while Task 3.2 combined ABCD transition statistics, K-Means clustering, and thematic distillation for signature generation. The framework emphasized robust temporal and retrieval-based reasoning.

- CSE_IIT_Ropar (Kumar et al., 2026) proposed a theory-explicit prompting framework grounded directly in the MIND ABCD taxonomy. Their system used a three-stage sequence-level pipeline involving heuristic deterioration/improvement labeling, structured clinical-style summarization, and aggregated signature extraction. LLM prompts explicitly encoded ABCD dynamics and enforced a structured summary format including central themes and within-/between-state dynamics. The framework emphasized psychologically interpretable prompting strategies.

- JNLP (Do et al., 2026) proposed a prompt-based in-context learning framework using locally deployed Qwen2.5-72B-Instruct-GPTQ-Int8 with vLLM inference. The system avoided task-specific fine-tuning and instead relied on few-shot and balanced few-shot prompting for Task 2 change detection and Task 3.1 summarization. Balanced demonstrations improved Task 2 Macro-F1 to 0.580,

while Task 3 summaries achieved strong consistency scores. Their framework demonstrated the effectiveness of prompt-based longitudinal reasoning in low-resource mental health settings.

- ULL ULL proposed a hybrid contrastive learning and regression framework for psychological state modeling. Task 1.1 used a SetFit classifier with an MPNet backbone trained using highlighted evidence spans and contrastive learning for ABCD classification. Task 1.2 used Ridge regression over sentence-transformer and TF-IDF features for presence estimation. For Task 3.1, the team combined a LoRA fine-tuned BART summarizer with retrieval-augmented prompting and rule-based validation.

- BLUE BLUE developed a hybrid zero-/few-shot LLM framework using DeepSeek-R1-32B and Mixtral-8x7B through Ollama. Dense retrieval with BGE-M3 embeddings retrieved annotated examples for ABCD classification under the MIND framework. Mixtral handled presence estimation and wellbeing trajectory prediction, while Task 2 Switch and Escalation labels were derived using rule-based analysis over predicted trajectories. The system combined retrieval-augmented prompting with temporal reasoning.

- Codezone Codezone proposed the Temporal-Clinical Graph Network (TCGN) for Task 2 change detection. Their framework combined transformer-based post encoders, a Temporal Difference Encoder over GAF-rescaled signals, and a Graph Attention Network operating on dynamic self-state transition graphs. A BiGRU with Clinical Rule-Augmented Contrastive Learning modeled longitudinal changes for Switch and Escalation detection. The graph-enhanced temporal architecture substantially outperformed sequential baselines.

C.3 Overview

We outline methods used in the *best run per team* in Table 13. For a complete picture of each team's approaches, including ablations, we refer the reader to the respective system description papers. We categorize each system based on the following properties:

- **LLM**: Uses a large language model.
- **PLM**: Uses a pretrained language model.
- **ML**: Uses traditional machine learning algorithms (e.g., random forest), excluding feature engineering techniques.
- **RAG**: Uses retrieval-augmented generation with automatic retrieval (excluding manually selected examples).
- **Pipeline**: Uses outputs from one task as inputs to another task (not joint prediction within a single prompt).
- **Domain**: Incorporates domain knowledge beyond the shared task guidelines.
- **Temporal**: Explicitly models cross-post dependencies (e.g., sequence models, previous posts, or timeline reasoning), excluding intra-post context.

Table 13 summarizes the modeling strategies adopted by each participating team. LLM-based approaches dominate the competition, with 14 teams using at least one large language model in their best-performing system. Pipeline-based systems are also highly prevalent (11 teams), indicating that many participants decomposed the shared task into sequential subtasks rather than relying on joint modeling. Temporal reasoning is explicitly modeled by 12 teams, particularly for Task 2, while six teams use retrieval-augmented generation (RAG). Traditional machine learning approaches remain relatively uncommon, appearing in only three systems.

Team	LLM	PLM	ML	RAG	Pipeline	Domain	Temporal
Aurevia	✓				✓	✓	✓
BLUE	✓			✓	✓		✓
Codezone		✓				✓	✓
CSE_IIT_Ropar	✓		✓				✓
CtbuY	✓	✓		✓	✓	✓	✓
CUNY	✓		✓		✓		✓
DreamerNLplus	✓	✓	✓	✓	✓		✓
JNLP	✓						✓
McMasterNLP	✓						
Meronym Labs	✓			✓	✓		✓
MKC	✓				✓		✓
NoviceTrio		✓			✓		
psytechlab	✓	✓			✓		✓
StateOfMIND	✓			✓	✓		
ull	✓	✓	✓	✓	✓		
USAI	✓				✓		✓
Total	14	6	3	6	11	3	12

Table 13: Methods used in each team's best submission. Pipeline refers to cases where outputs from one task are used in another task.

LLMs. Large language models (LLMs) form the backbone of nearly all high-performing systems in this shared task, either as primary predictors or as components within hybrid pipelines. Across the *best runs per team*, we observe clear trends in model selection, context utilization, and scaling behavior (Figures 5–7). First, model family diver-

sity has increased substantially compared to prior shared tasks (Chim et al., 2024; Tseriotou et al., 2025). While Llama-based models are used in several submissions, the strongest-performing systems are predominantly built on alternative open-weight model families such as Qwen, DeepSeek, and Gemma. In particular, top-ranked teams including CUNY, StateOfMIND, Meronym Labs, and USAI rely heavily on these newer model families, often in combination with other models in ensemble settings. This indicates a shift away from Llama-centric dominance toward a more diverse ecosystem of competitive LLMs compared to previous shared task trends.

Second, context length has expanded significantly (Figure 6). Whereas prior work was typically constrained to 32K tokens, several systems in this shared task report context windows exceeding 100K tokens, with some models supporting up to 1M tokens. However, most high-performing systems do not rely on extremely long contexts; instead, they employ targeted context construction strategies such as retrieval-augmented generation (RAG), structured prompting, or selective use of recent posts. This suggests that effective context selection is more important than raw context length for modeling psychological signals.

Third, model scale contributes to performance but is not the sole determining factor (Figure 7). Larger models (50B+ parameters), such as those used by CUNY, Aurevia, and USAI, achieve strong results across tasks, particularly for presence estimation (Task 1.2). However, mid-sized models (10–50B), including those used by StateOfMIND and Meronym Labs, remain highly competitive when combined with retrieval, ensembling, or calibration strategies. This highlights that inference-time design choices, including prompting, aggregation, and post-processing, play a critical role alongside model size.

Finally, we observe widespread adoption of retrieval-augmented and ensemble-based LLM pipelines among top-performing systems. Rather than relying on a single model pass, leading approaches combine multiple reasoning steps, retrieved examples, or model outputs to improve robustness and calibration. This trend reinforces the importance of structured inference strategies in complex, multi-task psychological modeling settings. Overall, these findings indicate that while LLMs are central to performance, success depends less on any single model family and more on how models are orchestrated through retrieval, prompting, and aggregation strategies.



Figure 5: Model families used in the best runs of official submissions (including LLMs and PLMs). While Llama-based models are present, top-performing systems are predominantly based on alternative open-weight models such as Qwen, DeepSeek, and Gemma, indicating a shift toward a more diverse LLM ecosystem.



Figure 6: Maximum context length of LLMs used in best runs. Although several systems support very long contexts (100K+ tokens), most high-performing approaches rely on selective context construction (e.g., retrieval or recent posts) rather than fully utilizing the maximum available context.

C.4 Performance Analysis

We analyze system performance across Task 1.1 (subelement classification), Task 1.2 (presence estimation), Task 2 (moment-of-change detection), and Task 3 (summarization and explanation generation), focusing on how modeling choices influence leaderboard outcomes based on the best submission per team.

Overall Trends. Across tasks, we observe substantial variation in performance ceilings and system rankings. For **Task 1.1**, the best-performing system (CUNY) achieves an Average Subelement Macro F1 of 0.442. For **Task 1.2**, Meronym Labs achieves the lowest AvgRMSE of 0.917, followed closely by USAI (0.942) and Aurevia (0.981). In **Task 2**, USAI achieves the highest combined macro



Figure 7: Model size distribution (in parameters) across best-performing systems. While larger models (50B+) achieve strong performance, mid-sized models (10–50B) remain competitive when combined with retrieval, ensembling, and calibration strategies, indicating that system design plays a key role alongside scale.

F1 of 0.600, followed by CtbuY (0.588) and JNLP (0.580). For **Task 3.1**, Meronym Labs ranks first overall based on average rank across evaluation metrics, while DreamerNLplus and CUNY rank second and third, respectively. For **Task 3.2**, DreamerNLplus achieves the best overall score for improvement explanations (0.7608), whereas CSE_IIT_Ropar achieves the best deterioration explanation score (0.7891). These results illustrate increasing task complexity from structured classification and regression toward temporally grounded generation and explanation.

Task 1.1: Subelement Classification. Task 1.1 exhibits a relatively wide spread in system performance, with AvgSub scores ranging from 0.175 to 0.442. Top-performing systems include CUNY (0.442), StateofMIND (0.441), Meronym Labs (0.420), USAI (0.410), and Aurevia (0.381). These systems primarily rely on LLM-based inference combined with ensembling, prompting, or retrieval strategies. Mid-performing systems such as MKC (0.361), McMasterNLP (0.351), and ull (0.335) remain competitive despite using smaller or more specialized architectures. Lower-performing systems such as CSE_IIT_Ropar (0.175), DrosophilAI (0.179), and debju (0.195) highlight the difficulty of fine-grained adaptive and maladaptive subelement prediction. Performance differences are particularly pronounced for adaptive subelements, which consistently achieve lower scores than maladaptive subelements across systems. This suggests that adaptive signals are more heterogeneous and difficult to identify than maladaptive indicators.

Task 1.2: Presence Estimation. Task 1.2 reveals a different ranking structure from Task 1.1. Meronym Labs achieves the best AvgRMSE (0.917), followed by USAI (0.942), Aurevia (0.981), CUNY (0.989), and StateofMIND (0.994). These results indicate that strong classification performance does not necessarily translate into optimal regression calibration. Systems also specialize across evaluation metrics. USAI achieves the strongest agreement with gold annotations, obtaining the highest Combined Quadratic Weighted Kappa (0.730) and Spearman correlation (0.752), whereas Meronym Labs achieves the lowest prediction error overall. In contrast, systems such as BLUE (1.606 AvgRMSE), CtbuY (1.501), and psytechlab (1.407) perform substantially worse, suggesting that regression-based presence estimation is highly sensitive to calibration and score normalization.

Team-Level Prediction Characteristics: Team-level statistics showed substantial variability in prediction coverage and intensity (Table 14). Adaptive coverage ranged from 34.78% to 98.91%, while maladaptive coverage ranged from 48.91% to 100.00%. Mean adaptive presence scores ranged from 1.42 to 3.51, compared to 1.89 to 3.70 for maladaptive states.

Metric	Min	Max
Adaptive Coverage (%)	34.8	98.9
Maladaptive Coverage (%)	48.9	100.0
Adaptive Mean Presence	1.42	3.51
Maladaptive Mean Presence	1.89	3.70
Adaptive Avg. Elements	0.00	3.62
Maladaptive Avg. Elements	0.90	4.55

Table 14: Team-level prediction range summary.

Statistical Significance Analysis: Welchs t-test confirmed a significant difference between adaptive and maladaptive presence scores (Table 15), with maladaptive states receiving higher scores overall.

Metric	Value
t-statistic	-13.38
p-value	1.3×10^{-39}
ADT Mean	2.18
MAL Mean	2.83

Table 15: Welchs t-test comparing adaptive and maladaptive presence scores.

Relationship Between Tasks 1.1 and 1.2. Performance across Task 1.1 and Task 1.2 demonstrates a moderate inverse relationship. Systems

Team	Model Type
USAI	LLM
CtbuY	Small LM
JNLP	LLM
CUNY	ML
MKC	Small LM
Codezone	Small LM
Aurevia	LLM
Meronym Labs	LLM
debju	LLM
DreamerNLplus	ML
McMasterNLP	Small LM
BLUE	LLM
NoviceTrio	Small LM
DrosophilAI	LLM
psytechlab	Small LM
CSE_IIT_Ropar	Small LM
Afrilan	ML
Cloud	LLM
TempoFormer	Small LM
Llama ZS	LLM

Table 16: Broad model categories used by Task 2 systems.

achieving stronger AvgSub scores generally obtain lower AvgRMSE values, although the relationship is not perfectly linear. For example, CUNY ranks first in Task 1.1 but fourth in Task 1.2, whereas Meronym Labs improves from third place in Task 1.1 to first place in Task 1.2. Similarly, USAI performs strongly across both tasks despite relying on different aggregation strategies. These findings indicate that classification and regression subtasks require partially distinct optimization objectives and inference strategies.

Task 2: Moment-of-Change Detection. Task 2 demonstrates the importance of temporal reasoning and cross-post contextual modeling. USAI achieves the highest combined macro F1 (0.600), followed closely by CtbuY (0.588), JNLP (0.580), MKC (0.554), and Codezone (0.553). In contrast, weaker systems such as Cloud (0.260) and Afrilan (0.268) perform substantially worse, highlighting the difficulty of detecting Switches and Escalations from longitudinal timelines. Performance varies considerably across subtasks. JNLP achieves the best post-level escalation F1 (0.738), Codezone achieves the strongest timeline escalation F1 (0.719), and MKC achieves the best timeline switch F1 (0.514). These differences indicate that systems specialize in distinct temporal reasoning capabilities. Architectures explicitly modeling timeline structure and temporal dependencies generally outperform static or post-independent approaches. Table 16 shows broad model categories used by Task 2 systems.

Task 3.1: Summarization Quality. Task 3.1 introduces a multi-dimensional evaluation framework combining consistency, contradiction, ROUGE-L recall, and BERTScore recall. Meronym Labs achieves the best overall ranking, followed by DreamerNLplus and CUNY. However, performance differs substantially across individual metrics. Aurevia achieves the highest consistency score (0.866), psytechlab achieves the lowest contradiction score (0.571), USAI achieves the best ROUGE-L recall (0.333), and USAI also achieves the highest BERTScore recall (0.365). Systems optimized for lexical overlap metrics do not necessarily achieve the best faithfulness metrics, illustrating an important trade-off between semantic similarity and factual consistency. These findings emphasize that summarization quality in mental health timelines cannot be captured adequately using a single evaluation metric.

Task 3.2: Explanation Generation. Task 3.2 evaluates explanation generation for improvement and deterioration scenarios. For improvement explanations, DreamerNLplus achieves the highest overall score (0.7608), followed by CSE_IIT_Ropar (0.7426) and MKC (0.7266). For deterioration explanations, CSE_IIT_Ropar performs best overall (0.7891), followed by Aurevia (0.6761) and DreamerNLplus (0.6038). Systems demonstrate complementary strengths across evaluation dimensions. CSE_IIT_Ropar performs particularly well on fit and specificity, psytechlab and CtbuY achieve perfect recurrence scores in some settings, and DreamerNLplus achieves the strongest specificity for improvement explanations. However, variance across systems remains high, indicating the difficulty of jointly optimizing fit, recurrence, and specificity.

Method-Level Trends. Method-level analysis reveals several important trends (Tables 17, 18). RAG-based systems achieve higher average Task 1.1 performance (0.334 AvgSub) than non-RAG systems (0.307), but worse Task 1.2 performance (1.246 vs. 1.128 AvgRMSE), indicating that retrieval improves classification more consistently than regression calibration (Table 17). Pipeline-based systems also outperform non-pipeline systems in Task 1.1 (0.330 vs. 0.292 AvgSub), but achieve slightly worse regression performance in Task 1.2 (1.185 vs. 1.141 AvgRMSE), as shown in Table 17. Temporal systems perform substantially better in Task 2 (0.498 combined macro F1) than

Method	Teams	Task 1.1 AvgSub ↑	Task 1.2 AvgRMSE ↓
RAG	BLUE, CibuY, DreamerNLplus, Meronym Labs, StateOfMIND, ull	**0.334**	1.246
No RAG	Afrilan, Aurevia, CSE_IIT_Ropar, CUNY, DrosophilAI, MKC, McMasterNLP, NoviceTrio, psytechlab, USAI, debju	0.307	**1.128**
Pipeline	Aurevia, BLUE, CibuY, CUNY, DreamerNLplus, MKC, Meronym Labs, NoviceTrio, psytechlab, StateOfMIND, ull, USAI	**0.354**	1.120
No Pipeline	Afrilan, CSE_IIT_Ropar, DrosophilAI, McMasterNLP, debju	0.210	**1.099**
Temporal	Aurevia, BLUE, Codezone, CSE_IIT_Ropar, CibuY, CUNY, DreamerNLplus, JNLP, MKC, Meronym Labs, psytechlab, USAI	0.354	1.121
Non-temporal	Afrilan, DrosophilAI, McMasterNLP, NoviceTrio, StateOfMIND, ull, debju	0.282	**1.201**

Table 17: Method-level performance on Task 1.1 (Average Subelement Macro F1) and Task 1.2 (Average RMSE), computed using the method taxonomy from Table 13.

Approach	Teams	Task 2 Combined F1 ↑
Temporal	Aurevia, BLUE, Codezone, CSE_IIT_Ropar, CibuY, CUNY, DreamerNLplus, JNLP, MKC, Meronym Labs, psytechlab, USAI	**0.498**
Non-temporal	Afrilan, Cloud, DrosophilAI, McMasterNLP, NoviceTrio, debju	0.359

Table 18: Impact of temporal modeling on Task 2 using the temporal categorization from Table 13. Explicit temporal modeling improves moment-of-change detection performance.

Model	AvgSub	EP-A	EP-M	EP-Avg	SE-A	SE-M
`Llama-3.3-70B-Instruct`	**0.391**	**0.524**	**0.722**	**0.623**	**0.292**	**0.489**
`Llama-3.1-8B-Instruct`	0.247	0.392	0.605	0.498	0.156	0.338

Table 19: Baseline Task 1.1 results. AvgSub = average subelement macro F1; EP = element presence; SE = subelement; A = adaptive; M = maladaptive.

Model	AvgRMSE	RMSE-M	RMSE-A	QWK	C-RMSE	Spr.	MAE
`Llama-3.3-70B-Instruct`	**1.244**	**1.291**	**1.196**	**0.591**	**1.244**	**0.609**	**0.910**
`Llama-3.1-8B-Instruct`	1.424	1.439	1.409	0.555	1.424	0.603	1.083

Table 20: Baseline Task 1.2 results. AvgRMSE = average RMSE; C-RMSE = combined RMSE; Spr. = Spearman correlation. Lower is better for RMSE metrics; higher is better for QWK and Spr.

non-temporal systems (0.359), supporting the importance of explicit timeline modeling for moment-of-change detection (Table 18).

Effect of Model Size. Larger models generally achieve stronger performance across tasks. Systems using models larger than 50B parameters, including CUNY, Aurevia, and USAI, consistently rank among the best-performing systems in Tasks 1 and 2. However, mid-sized models (10–50B) such as those used by StateofMIND and Meronym Labs remain highly competitive when combined with retrieval, ensembling, or calibration strategies. In contrast, smaller models (<1B) consistently underperform relative to larger systems. These findings suggest that model scale contributes substantially to performance, but inference-time strategies such as retrieval, prompting, and aggregation remain equally important.

Summary. Overall, the results demonstrate that (1) Tasks 1.1 and 1.2 are related but require distinct optimization strategies, (2) Task 2 strongly benefits from temporal reasoning and timeline-aware modeling, (3) Task 3 introduces complex multi-objective generation challenges balancing faithfulness and semantic similarity, (4) retrieval and pipeline strategies provide task-dependent benefits, (5) larger models improve performance but are insufficient alone, and (6) ensemble approaches are particularly effective for structured prediction tasks but less consistently beneficial for generation tasks.

Appendix D Baselines

This section outlines implementation details of our baseline models (§7.1). In LLM-based methods, we employ `Llama-3.1-8B-Instruct`. We also perform ablation experiments using the larger `Llama-3.3-70B-Instruct` model to explore the effects of model size on Task performance. For the text generation Task 3.1, we also perform experiments varying temperature. Unless otherwise indicated, all experiments on generative LLMs use a temperature of 1.0 and a top_p of 0.7.

D.1 Task 1.1

The prompt for Task 1.1 instructs the model to identify predominant adaptive and maladaptive subelements across the six ABCD dimensions: Affect (A), Behavior toward Other (BO), Behavior toward Self (BS), Cognition toward Other (CO), Cognition toward Self (CS), and Desire (D). We frame this as a classification problem with label definitions embedded directly in the prompt. The labeling protocol enforces sparsity constraints: each element-valence pair may have at most one dominant sub-element, with null designations used when no element is present. Scores for both Llama models are shown in Table 19.

D.2 Task 1.2

The prompt for Task 1.2 is shared with Task 1.1 and instructs the model to assign integer presence scores ranging from 1 to 5 for both adaptive and maladaptive self-states overall. A constraint requires that any all-null valence configuration receive a score of 1. The prompt explicitly defines "presence" as psychological centrality rather than mere lexical frequency. Scores for both Llama models are shown in Table 20.

D.3 Task 2

Baseline 1 uses zero-shot prompting to elicit well-being scores, which are used to predict switches, and escalation labels. Using the baseline predic-

Method	Comb.	P-Esc	P-Mac	P-Sw	T-Esc	T-Mac	T-Sw
TempoFormer	**0.572**	**0.667**	**0.561**	**0.456**	**0.736**	**0.583**	0.430
Weighted Sum + T1.1 (70B)	0.394	0.378	0.407	0.436	0.335	0.380	0.425
Weighted Sum + T1.1 (8B)	0.365	0.407	0.383	0.359	0.343	0.346	0.350
Llama-70B ZS	0.317	0.000	0.219	0.438	0.400	0.416	**0.432**
Llama-8B ZS	0.272	0.000	0.169	0.337	0.400	0.376	0.352

Table 21: Baseline Task 2 results. Comb. = combined macro F1; P = post-level; T = timeline-level; Esc = escalation; Mac = macro F1; Sw = switch.

tions for Task 1.1, **Baseline 2** calculates well-being using the following formula, clamping the score between 1 and 10 inclusive:

Well-being $= \text{Round}((1 - mal_ratio) \cdot 9 + 1 + adap_bonus)$

Where:

mal_ratio = $\frac{\text{mal_score}}{\text{weight_sum}}$

mal_score = weighted sum of maladaptive elements identified in Task 1.1.

The weights used in the weighted sum are as follows: 'A'=2.0, 'BS'=1.8, 'D'=1.5, 'CS'=1.2, 'CO'=1.0, 'BO'=0.8.

weight_sum $= 2.0 + 1.8 + 1.5 + 1.2 + 1.0 + 0.8$

adap_bonus = $0.5\cdot$ count of adaptive elements identified in Task 1.1.

The TempoFormer (**Baseline 3**) was fine-tuned with a window size of 5 for Switches and 10 for Escalations (based on differences in the guideline definitions), over 4 epochs with a learning rate of 1e-5, using focal loss to address class imbalance. The first 6 layers of the model were frozen to account for the small number of training samples. Scores for all baseline experiments using both Llama models and TempoFormer are shown in Table 21.

D.4 Task 3.1

Baseline 1 employs zero-shot prompting on `Llama-3.1-8B-Instruct` using a temperature of 0.2. **Baseline 2** was formulated as a pipeline by using the model from Baseline 1 and feeding the predictions from the top performing baselines from Task 1 and Task 2 (TempoFormer) within the prompt. Additional experiments were performed for each approach, varying the temperature and using the larger `Llama-3.3-70B-Instruct` model. These results are presented in Table 22.

D.5 Task 3.2

The Task 3.2 Baseline is described in full detail by §7.1.

Model	Temp	CS	CT	R-L	BERT-R
Llama-8B	*0.2*	*0.763*	*0.753*	*0.255*	*0.226*
	0.4	0.774	0.694	0.246	**0.237**
	0.6	0.810	0.665	0.247	0.231
	0.8	0.791	0.704	0.255	0.230
	1.0	0.792	0.705	0.238	0.235
Llama-70B	0.2	0.819	0.659	0.222	0.222
	0.4	0.821	**0.649**	0.223	0.224
	0.6	0.819	0.660	0.226	0.229
	0.8	0.816	0.663	0.219	0.228
	1.0	**0.824**	0.679	0.220	0.225
Llama-8B Pipeline	*0.2*	*0.763*	*0.745*	***0.269***	*0.235*
	0.4	0.738	0.764	0.260	0.227
	0.6	0.722	0.801	0.250	0.231
	0.8	0.730	0.796	0.256	0.226
	1.0	0.756	0.745	0.246	0.227
Llama-70B Pipeline	0.2	0.759	0.700	0.235	0.229
	0.4	0.760	0.728	0.231	0.227
	0.6	0.757	0.742	0.233	0.227
	0.8	0.771	0.708	0.234	0.225
	1.0	0.762	0.768	0.234	0.221

Table 22: Baseline Task 3.1 results. CS = consistency; CT = contradiction; R-L = ROUGE-L; BERT-R = BERTScore. Scores used as official baselines have been *italicized*.

Appendix E Prompts used for Tasks 1, 2, and 3

This section presents the prompts used in the baseline methods. Listing 2 provides the prompt for Tasks 1.1 and 1.2 baselines. Listing 3 provides the prompt for Tasks 2 baseline for Well-being scores. Listing 4 provides the prompt for Tasks 2 baseline for escalation labeling. Listing 5 provides the prompt for Tasks 3.1 Baseline 1. Listing 6 provides the prompt for Tasks 3.1 Baseline 2. Listing 7 provides the prompt for Tasks 3.2 baseline.

Appendix F Examples of Expected Input and Output for Tasks 1, 2, and 3

This section provides illustrative examples for each task to clarify the expected input and output formats. An example of identifying adaptive and maladaptive self-state compositions is shown in Listing 8. An example of assigning adaptive and maladaptive presence scores is shown in Listing 9. An example of escalation and switch label prediction across posts is shown in Listing 10. An example of generating a structured psychological summary over a sequence is shown in Listing 11. Examples of recurrent dynamic patterns of deterioration and improvement are shown in Listing 12.

```
You are writing a GOLD Task 3.1 Sequence Summary. Follow instructions exactly.

Task 3.1: Summarising sequences surrounding change events

The goal of Task 3.1 is to generate a structured summary describing patterns of self-state dynamics and their progression over
       time within a sequence of posts surrounding a change (Switch and/or Escalation). Each sequence includes posts leading
      up to the change, as well as posts marking the change itself. The summary must describe how psychological change
      processes evolve across the sequence, and how they culminate in (Switch), or unfold through (Escalation), the identified
       change event. The direction of the change (improvement/deterioration) must also be indicated.

Switch: A switch reflects a substantial change in well-being between two consecutive posts. A switch occurs when |Wellbeing(t)
        Wellbeing(t1)|  2.

Escalation: An escalation refers to a gradual intensification of mood across a sequence of consecutive posts.

Use:
- post text
- change labels
- self-state presence scores
- ABCD subcategory compositions

The summary must describe:
- the central psychological theme across the sequence
- within-state ABCD dynamics
- between-state dynamics
- relative adaptive/maladaptive dominance
- how dynamics evolve before and during the change

When referencing ABCD elements, use:
(A), (B-S), (B-O), (C-S), (C-O), (D)

STYLE RULES:
- Write ONE coherent paragraph only.
- Use process-oriented relational language.
- Do not list ABCD labels independently.
- Integrate ABCD elements into relational dynamics.

HARD CONSTRAINTS:
- Output must be EXACTLY ONE SINGLE PARAGRAPH.
- Output MUST start EXACTLY with:
  Sequence summary:
- Explicitly state:
  - improvement OR deterioration
  - whether change culminates in a Switch or unfolds through an Escalation
- Anchor where change occurs:
  - early / mid / late within the sequence
- Mention self-state dominance verbally only.
- DO NOT output numeric presence scores.
- DO NOT invent content.

Narrative structure:
1. Introduce the central psychological theme.
2. Describe pre-change adaptive/maladaptive dynamics.
3. Describe relative state dominance and interactions.
4. Describe cross-state ABCD dynamics.
5. Describe how dynamics intensify or shift.
6. Describe the configuration at the change point.

--- SEQUENCE BLOCK ---
{sequence_block}

Return ONLY the final summary paragraph.
```

Listing 1: Prompt for Task 3.1 sequence summarization baseline.

```
You are labeling ONE social media post for the CLPsych 2026 Shared Task.

Perform both tasks below.

TASK 1.1  Dominant ABCD subelements and self-state composition
Identify which predefined ABCD subelements are meaningfully expressed in the post.

For each ABCD element:
- A = Affect
- BO = Behavior toward Other
- BS = Behavior toward Self
- CO = Cognition toward Other
- CS = Cognition toward Self
- D = Desire

Evaluate adaptive and maladaptive expressions separately.

Within a single element and valence:
- choose at most ONE dominant subelement

Within a single element:
- it is allowed to output both one adaptive and one maladaptive subelement
  if both are clearly expressed

If an element is not expressed for a given valence, use null.

TASK 1.2  Presence scores
Assign:
- adaptive_presence
- maladaptive_presence

using this scale:
1 = Not present
2 = Somewhat present
3 = Moderately present
4 = Much present
5 = Highly present

Important rules:
- If the adaptive self-state is not expressed at all (all adaptive element values are null),
  adaptive_presence MUST be 1.
- If the maladaptive self-state is not expressed at all (all maladaptive element values are null),
  maladaptive_presence MUST be 1.
- Presence reflects psychological centrality and influence, not mere word frequency.

Allowed labels (must match exactly):

Adaptive:
A: {ALLOWED["A_adaptive"]}
BO: {ALLOWED["BO_adaptive"]}
BS: {ALLOWED["BS_adaptive"]}
CO: {ALLOWED["CO_adaptive"]}
CS: {ALLOWED["CS_adaptive"]}
D: {ALLOWED["D_adaptive"]}

Maladaptive:
A: {ALLOWED["A_maladaptive"]}
BO: {ALLOWED["BO_maladaptive"]}
BS: {ALLOWED["BS_maladaptive"]}
CO: {ALLOWED["CO_maladaptive"]}
CS: {ALLOWED["CS_maladaptive"]}
D: {ALLOWED["D_maladaptive"]}

Return ONLY one JSON object with exactly this structure:
{{
  "task1_1": {{
    "adaptive": {{
      "A": null,
      "BO": null,
      "BS": null,
      "CO": null,
      "CS": null,
      "D": null
    }},
    "maladaptive": {{
      "A": null,
      "BO": null,
      "BS": null,
      "CO": null,
      "CS": null,
      "D": null
    }}
  }},
  "task1_2": {{
    "adaptive_presence": 1,
    "maladaptive_presence": 1
  }}
}}

Do not output any explanation, prose, markdown, comments, or extra keys.

{ONE_SHOT_EXAMPLE}

### Input Post:
{{post_text}}

### Output JSON:
```

Listing 2: Prompt for Task 1.1 and Task 1.2 baselines.

```
You will be given ONE social media post from a single user.

Estimate the user's wellbeing on a 1-10 scale, where:
- 10 = excellent psychological and social functioning, minimal symptoms
- 1  = severe dysfunction or persistent risk

Wellbeing reflects overall functioning across:
- emotional distress
- hopelessness or suicidality
- motivation and coping
- social/interpersonal functioning
- daily functioning or impairment
- coherence/stability of sense of self

Important guideline:
- The scale is clinically anchored, not relative within the same individual.
- If the post does not provide strong evidence for major change, estimate
    conservatively.
- Clear evidence is required to justify strong improvement or deterioration.
- If evidence is partial or ambiguous, make only a minimal adjustment.

Return ONLY a single JSON object exactly in this format:
{"wellbeing": <integer from 1 to 10>}

Post:
"{post_text}"
```

Listing 3: Well-being Prompt for Task 2 Baseline 1.

```
You are given a chronologically ordered timeline of posts from one individual.

Your task is to identify Escalation events.

Definition:
An Escalation is a gradual intensification of mood over a SEQUENCE of
consecutive posts. It occurs when mood progressively shifts from neutral
or mildly valenced toward a more extreme state across multiple posts.

An escalation may reflect:
- gradual deterioration ("d")
- gradual improvement ("i")

Important distinctions:
- Escalation is gradual, not abrupt.
- Escalation is independent from Switch events.
- Only mark spans that clearly show progressive intensification across
  at least 2 consecutive posts.

Output requirements:
Return ONLY one JSON object with exactly one key:
{
  "escalations": [
    {"start": <int>, "end": <int>, "direction": "i" or "d"},
    ...
  ]
}

Rules:
- start and end are inclusive indices in the timeline order shown below.
- Only include spans that are clearly gradual.
- Keep at most {max_escalations} escalation spans.
- Do not include explanation or extra keys.

Timeline:
{timeline_block}
```

Listing 4: Escalation Prompt for Task 2 Baseline 1.

```
### Task
Your task is to generate a structured summary describing patterns of self-state dynamics and their
     progression over time within a sequence of posts surrounding a change (Switch and/or Escalation).

### Definitions
- Switch: A switch reflects a substantial and sudden change in well-being between two consecutive posts. A
     switch occurs when |Wellbeing(t)  Wellbeing(t1)|  2. The change may reflect either improvement or
     deterioration.
- Escalation: An escalation refers to a gradual intensification of mood over a sequence of consecutive posts
     . It occurs when an individuals mood progressively shifts from neutral or mildly valenced, toward a
     more extreme state (very negative or very positive) across a span of posts.

### Summary Content
The summary should include references, only when they are evident in the data, to the following aspects:
1. Central recurring theme across the posts: Describe the central dynamic psychological theme and change
     trajectory characterizing the change process across the sequence, articulated in terms of ABCD
     subelements: Affect (A); Behavior toward self (B-S) and Behavior toward others (B-O); Cognition toward
     self (C-S) and Cognition toward others (C-O); and Desire (D), grounded in concrete content from the
     posts. Explain how this theme evolves across the sequence. The description of the theme should reflect
     the relational dynamics between these ABCD subelements within and between self-states, as defined in
     the sections below. The theme should be described across the stages of the change process within the
     sequence, making clear how the theme appears before the change and how it develops as the change
     unfolds (when the change is that of escalation) or when it culminates (when the change is that of
     switch).
2. Dynamics within the Adaptive and Maladaptive self-states and their presence: Describe how present each
     self-state is and how its relative presence changes throughout the sequence as part of the change
     process. Presence refers to how strongly each self-state is expressed or dominant at different points
     in the sequence, whereas dynamics refer to the interactions between the ABCD subelements within that
     self-state. Where present, describe the adaptive and/or the maladaptive self-states in terms of Affect,
      Behavior, Cognition and Desire, expressing these ABCD subelements through explicit relational dynamics
      between them within the same self-state. If a self-state is described, relational dynamics between its
      ABCD subelements MUST also be described. Dynamics within a self-state are relational patterns between
     two or more subelements within the same self-state. These dynamics may be directional or reciprocal,
     such as co-activation, mutual reinforcement, exacerbation of one element by another, amplification of
     one element by another, or other structured interactions. This list is not exhaustive; other forms of
     dynamics may also be identified where conceptually appropriate. These relational dynamics between
     subelements within a self-state should be described as they unfold across the sequence, noting how they
      change over time.
3. Relationship between the adaptive and maladaptive self states and their relative presence: Describe how
     the adaptive and maladaptive self-states relate to one another and how that changes throughout the
     sequence. Describe how the relative presence and dominance of the adaptive and maladaptive self-states
     shifts across the sequence. This may include: one self-state dominating the other, suppressing or
     silencing the other, or both self-states coexisting through reflective dialogue. Use presence scores to
      support comparison over the sequence, but do not print numeric scores in the output. Additionally,
     examine whether dynamics occur between ABCD subelements across opposite self-states (suppression/
     attenuation, reflective dialogue, dominance competition, resilience or other structured interactions).
     If such crossself-state dynamics are present in the sequence, they MUST be described.

### Summary Guidelines
- The identity of the change event (Switch or Escalation) should be explicitly stated in the summary
- The direction of the change (improvement/deterioration) must be indicated - several changes in direction
     of change may be present in a sequence.
- It should be explicitly stated what dynamics characterized the pre-change phase, and how these dynamics
     culminated in the change event (in the case of a Switch) or unfolded through the change process (in the
      case of an Escalation).
- It should be explicitly stated in the summary when the change event occurs. Please note that a Switch
     event occurs within a single post, whereas an escalation unfolds across multiple posts.

### Guidelines for the Output
- The generated summary must not exceed 350 words.
- The summary should be a paragraph of text, not in a list. Do not add sections or titles.
- Generate only the summary as described, do not add any extra text or explanations.

### Input
{{INPUT_SEQUENCE_POST_TEXT_ONLY}}

### Output
```

Listing 5: Prompt for Task 3.1 Baseline 1.

```
### Task
Your task is to generate a structured summary describing patterns of self-state dynamics and their
     progression over time within a sequence of posts surrounding a change (Switch and/or Escalation).

### Input Description
Along with the post text, the adapative and maladaptive presence scores, and composition are give. It is
     also given whether if a switch or escalation is present for each post.

### Definitions
- Switch: A switch reflects a substantial and sudden change in well-being between two consecutive posts. A
     switch occurs when |Wellbeing(t)  Wellbeing(t1)|  2. The change may reflect either improvement or
     deterioration.
- Escalation: An escalation refers to a gradual intensification of mood over a sequence of consecutive posts
     . It occurs when an individuals mood progressively shifts from neutral or mildly valenced, toward a
     more extreme state (very negative or very positive) across a span of posts.

#### Presence Scale
1 = Not present
2 = Somewhat present
3 = Moderately present
4 = Much present
5 = Highly present

### Summary Content
The summary should include references, only when they are evident in the data, to the following aspects:
1. Central recurring theme across the posts: Describe the central dynamic psychological theme and change
     trajectory characterizing the change process across the sequence, articulated in terms of ABCD
     subelements: Affect (A); Behavior toward self (B-S) and Behavior toward others (B-O); Cognition toward
     self (C-S) and Cognition toward others (C-O); and Desire (D), grounded in concrete content from the
     posts. Explain how this theme evolves across the sequence. The description of the theme should reflect
     the relational dynamics between these ABCD subelements within and between self-states, as defined in
     the sections below. The theme should be described across the stages of the change process within the
     sequence, making clear how the theme appears before the change and how it develops as the change
     unfolds (when the change is that of escalation) or when it culminates (when the change is that of
     switch).
2. Dynamics within the Adaptive and Maladaptive self-states and their presence: Describe how present each
     self-state is and how its relative presence changes throughout the sequence as part of the change
     process. Presence refers to how strongly each self-state is expressed or dominant at different points
     in the sequence, whereas dynamics refer to the interactions between the ABCD subelements within that
     self-state. Where present, describe the adaptive and/or the maladaptive self-states in terms of Affect,
      Behavior, Cognition and Desire, expressing these ABCD subelements through explicit relational dynamics
      between them within the same self-state. If a self-state is described, relational dynamics between its
      ABCD subelements MUST also be described. Dynamics within a self-state are relational patterns between
     two or more subelements within the same self-state. These dynamics may be directional or reciprocal,
     such as co-activation, mutual reinforcement, exacerbation of one element by another, amplification of
     one element by another, or other structured interactions. This list is not exhaustive; other forms of
     dynamics may also be identified where conceptually appropriate. These relational dynamics between
     subelements within a self-state should be described as they unfold across the sequence, noting how they
      change over time.
3. Relationship between the adaptive and maladaptive self states and their relative presence: Describe how
     the adaptive and maladaptive self-states relate to one another and how that changes throughout the
     sequence. Describe how the relative presence and dominance of the adaptive and maladaptive self-states
     shifts across the sequence. This may include: one self-state dominating the other, suppressing or
     silencing the other, or both self-states coexisting through reflective dialogue. Use presence scores to
      support comparison over the sequence, but do not print numeric scores in the output. Additionally,
     examine whether dynamics occur between ABCD subelements across opposite self-states (suppression/
     attenuation, reflective dialogue, dominance competition, resilience or other structured interactions).
     If such crossself-state dynamics are present in the sequence, they MUST be described.

### Summary Guidelines
- The identity of the change event (Switch or Escalation) should be explicitly stated in the summary
- The direction of the change (improvement/deterioration) must be indicated - several changes in direction
     of change may be present in a sequence.
- It should be explicitly stated what dynamics characterized the pre-change phase, and how these dynamics
     culminated in the change event (in the case of a Switch) or unfolded through the change process (in the
      case of an Escalation).
- It should be explicitly stated in the summary when the change event occurs. Please note that a Switch
     event occurs within a single post, whereas an escalation unfolds across multiple posts.

### Guidelines for the Output
- The generated summary must not exceed 350 words.
- The summary should be a paragraph of text, not in a list. Do not add sections or titles.
- Generate only the summary as described, do not add any extra text or explanations.

### Input
{{INPUT_SEQUENCE_POST_TEXT_AND_PIPELINE}}

### Output
```

Listing 6: Prompt for Task 3.1 Baseline 2.

```
### Task
Your goal is to identify and summarize recurrent dynamic patterns of deterioration (
    a switch towards lower well-being, or an escalation of deterioration) or
    improvement (a switch towards higher well-being, or an escalation of improvement
    ) that recur across multiple sequences.

### Input Description
You will be given a series of post sequence summaries. These summaries describe
    patterns of self-state dynamics and their progression over time within a
    sequence of posts surrounding a change (Switch and/or Escalation). You will also
     be given their sequence_id and timeline_id.

### Definitions
- Switch: A switch reflects a substantial and sudden change in well-being between
    two consecutive posts. A switch occurs when |Wellbeing(t)  Wellbeing(t1)|  2.
    The change may reflect either improvement or deterioration.
- Escalation: An escalation refers to a gradual intensification of mood over a
    sequence of consecutive posts. It occurs when an individuals mood progressively
    shifts from neutral or mildly valenced, toward a more extreme state (very
    negative or very positive) across a span of posts.
- Signature: Describes a recurrent dynamic pattern (ABCD + self-state relations)
    observed across individuals that leads to and culminates as the change occurs.

### Pattern Identification
Across timelines, identify the most frequent patterns in:
- Central Theme: Recurrent themes of deterioration or improvement articulated in
    ABCD elements
- Dynamics within self-states: Recurrent ABCD configurations (separately for the
    maladaptive and adaptive self states), dynamics among subelements within the
    same self-state, changes in presence of a self state across the sequence leading
     to and through the change event.
- Dynamics between self-states: Patterns in the balance between self-states in terms
     of presence over time (patterns of dominance versus coexistence), is there a
    dialogue/reflection between the self states or silencing dominance and how does
    this change over time, dynamics between subelements from different self-states
    over time.

### Output Content

#### Signature Summary
- Based on the identified patterns, you must extract both extract 1 signature of
    deterioration and 1 signature of improvement.
- A signature does not have to include both within-state and between-state dynamics;
     it may be based on recurrent dynamics within a self-state, between self-states,
     or a combination of both. The more details a signature contains, the higher it
    will be scored; therefore, a combination of details will yield a higher score.

### List of Evidence
- Along with each signature summary, list the sequence_id and timeline_id of
    supporting evidence.
- In the case of a signature of improvement, identify which sequence_id and
    timeline_id exhibits this signature.
- In the case of a signature of deterioration, identify which sequence_id and
    timeline_id exhibits this signature.

### Guidelines for the Output
- Separate your response into 2 sections: '### Signature of Deterioration' and '###
    Signature of Improvement'.
- Output the signature summary, then the list of evidence.
- Each signature summary should not exceed 90 words.

### Input
{{INPUT_SEQUENCE_SUMMARIES}}

### Output
```

Listing 7: Prompt for Task 3.2 baseline.

```
Example Input post:
Im searching for someone who could help keep me accountable with daily exercise and
    prevent late-night binge eating. I have a heart issue that involves low blood
    pressure (it doesnt increase with activity) along with a high heart rate. I need
     to do light activities, such as walking, every day to maintain my strength and
    energy. If I skip even one day, it becomes very difficult to get out of bed the
    following day, so staying consistent is essential for my health.

Im not overweight, but I sometimes overeat at night and would really value support
    in avoiding that pattern. When I consume a large amount of carbs or calories at
    once, it seems to worsen my symptoms. I feel more lightheaded and notice my
    heart rate climbing. Because of that, I really need to prevent those episodes,
    but at times my depression and lack of motivation take over and I end up
    thinking "forget it" and doing it anyway.

Having someone to talk to during those moments would make a big difference. I
    usually begin binge eating around 1011pm. If anyone is willing to help me stay
    motivated about my health, Id truly appreciate it. We could support and
    encourage one another.


Example output self-state(s) composition:

Adaptive Self state:
A: (5) Content, happy, joy, hopeful
B-O: (1) Relating behavior
B-S: (1) Self care and improvement
C-O: (1) Perception of the other as related
D: (5) Competence, self esteem, self-care

Maladaptive Self state:
A: (4) Depressed, despair, hopeless
B-S: (2) Self harm, neglect and avoidance
D: (6) Expectation that competence needs will not be met
```

Listing 8: Example of Expected Input and Output for Task 1.1.

```
Example Input post:
Im searching for someone who could help keep me accountable with daily exercise and
    prevent late-night binge eating. I have a heart issue that involves low blood
    pressure (it doesnt increase with activity) along with a high heart rate. I need
     to do light activities, such as walking, every day to maintain my strength and
    energy. If I skip even one day, it becomes very difficult to get out of bed the
    following day, so staying consistent is essential for my health. Im not
    overweight, but I sometimes overeat at night and would really value support in
    avoiding that pattern. When I consume a large amount of carbs or calories at
    once, it seems to worsen my symptoms. I feel more lightheaded and notice my
    heart rate climbing. Because of that, I really need to prevent those episodes,
    but at times my depression and lack of motivation take over and I end up
    thinking "forget it" and doing it anyway. Having someone to talk to during those
     moments would make a big difference. I usually begin binge eating around 1011pm
    . If anyone is willing to help me stay motivated about my health, Id truly
    appreciate it. We could support and encourage one another.


Presence scores:

Adaptive Self state presence score: 4

Maladaptive Self state presence score: 2
```

Listing 9: Example of Expected Input and Output for Task 1.2 (Presence Scores).

```
Example Input post:

Post t: "Thanks so much for the advice on how to take care of my hair. Im very
    pleased with the result, and its made me feel so much better about myself".

Post t+1: "Its becoming more and more difficult to manage. Living with a chronic
    illness and trying to cope with everything that comes with it feels overwhelming
     lately. Im struggling a lot. I often feel worthless, and sometimes I convince
    myself that being sick means Im undeserving of love. I keep wondering what the
    point is if I cant have the kind of love and life I want. I know logically that
    other people with chronic illnesses still deserve love and care, so I dont
    understand why I have such a hard time believing that about myself. I dont
    really know how to deal with these feelings anymore. My thoughts have been
    getting darker, and that scares me, especially because Ive been in that place
    before. I know I need help, but Im terrified of being admitted again because my
    past experience at the hospital was awful. The last time I felt ignored and
    unsafe, and it made everything worse instead of better. So right now I feel
    stuck, like I need support, but I dont trust the place that is supposed to help.
     Maybe I just needed to get this out of me. I just feel so unworthy of love and
    even of life sometimes, and its getting harder and harder to keep coping".

Post t+2: "I plan to harm myself. I want to fall asleep and stay that way forever. I
     want to escape this reality. I dont want to feel so awful anymore. I feel as if
     love and kindness are just not meant for me. I want to apologize to anyone whom
     I might have hurt. Please forgive me. Ill try to sleep and hope it feels a
    little lighter later".


Example output of change label:

Post t: 0 (Escalation label), 0 (Switch label)

Post t+1: E (Escalation label), S (Switch label)

Post t+2: E (Escalation label), 0 (Switch label)
```

Listing 10: Example of Expected Input and Output for Task 2 (Change Detection).

```
Example Input: Timeline d0fb4b962e; Posts: 6, 7, 9, 10

Post index 6
MOC label: -
Wellbeing score = 7
Maladaptive presence: 1, Adaptive presence: 3
Maladaptive self-state composition: -
Adaptive self-state composition: B-O - (1) Relating behavior, D - (1) Relatedness
Post: "Does anyone here have a job? I know this isnt really related to the sub, but
    I was curious whether anyone here is employed. If so, what kind of work do you
    do?"

Post index 7
MOC label: -
Wellbeing score = 7
Maladaptive presence: 3, Adaptive presence: 2
Maladaptive self-state composition: A - (4) Depressed, despair, hopeless, B-S - (2)
    Self harm, neglect and avoidance, C-S - (2) Self criticism, D - (6) Expectation
    that competence needs will not be met
Adaptive self-state composition: A - (11) Proud, B-S - (1) Self care and improvement
Post: "After a week, Im back to square one. I was really proud that I managed to go
    seven days without drinking, but I ended up relapsing. And it was to Vodka. It
    makes me feel terrible, thinking that I might never be able to stop drinking
    that shitor alcohol in general."

Post index 9
MOC label: Escalation
Wellbeing score = 6
Maladaptive presence: 4, Adaptive presence: 2
Maladaptive self-state composition: A - (4) Depressed, despair, hopeless, B-S - (2)
    Self harm, neglect and avoidance, B-O - (2) Fight or flight behavior, C-S - (2)
    Self criticism, C-O - (2) Perception of the other as detached or over attached,
    D - (2) Expectation that relatedness needs will not be met
Adaptive self-state composition: B-O - (1) Relating behavior, D - (5) Competence,
    self esteem, self-care
Post: "When relatives or friends bring it up, I wish I could be honest with them...
    Has anyone here spoken with a psychologist? If so, what was your experience like
    , and did it help?"

Post index 10
MOC label: Switch, Escalation
Wellbeing score = 4
Maladaptive presence: 5, Adaptive presence: 2
Maladaptive self-state composition: A - (4) Depressed, despair, hopeless, B-O - (2)
    Fight or flight behavior, C-S - (2) Self criticism, C-O - (2) Perception of the
    other as detached or over attached, D - (6) Expectation that competence needs
    will not be met
Adaptive self-state composition: D - (5) Competence, self esteem, self-care
Post: "All of this feels like its going to affect me in my future responsibilities
    ... I sometimes think it would be better if I werent here causing stress for
    everyone."

Sequence Summary:
The central psychological theme revolves around the writers struggle with persistent
     self-doubt (C-S) and social anxiety (A), shifting from initial attempts at
    engagement (B-O) and self improvement (B-S) towards escalating despair (D),(A).
    Initially, the adaptive self-state is prominent, characterized by the writers
    desire to seek knowledge from others (D), exhibited in relating behavior (B-O).
    Then, the adaptive self-state loses presence while the maladaptive state gains
    dominance. The adaptive state is characterized by the writer exhibiting self-
    care behavior (B-S) which reinforced feelings of pride (A). But the maladaptive
    self-state dominates, overshadowing the adaptive state, instead featuring self-
    criticism (C-S) following engagement in the addictive behavior (B-S),
    intensifying despair (A) and the expectation that improvement is impossible (D)
    ...
```

Listing 11: Example of Expected Input and Output for Task 3.1 (Sequence Summary).

```
Examples of Recurrent Dynamic Signatures of change:
These are mock examples and are not based on real data. They illustrate
high-level dynamic patterns, including both within-self-state and
between-self-state interactions.

Example for signatures of deterioration:
Many sequences of deterioration show a progression from initial self-neglect
    behavior (B-S) into more severe self-harm behaviors (B-S), mediated by a gradual
     intensification of self-criticism (C-S) that is mutually reinforcing with
    anxious affect (A), reflecting the growing dominance of the maladaptive state.
    This intensification increasingly suppresses the adaptive state, where
    perceptions of others as facilitating needs (C-O), driven by the desire for
    competence (D), become overshadowed by the maladaptive dynamic.

Example for signatures of improvement:
Many sequences of improvement show a progression from an initial strong maladaptive
    feedback loop between detached perceptions of others (C-O) and depressive affect
     (A), which suppresses the adaptive state, into a reduced maladaptive presence.
    This is followed by a dominant adaptive feedback loop where self-acceptance (C-S
    ) fuels relating behavior (B-O), mutually reinforcing with the desire for
    autonomy (D).
```

Listing 12: Examples of Recurrent Dynamic Signatures of Change.

A Multi-Strategy Fusion Framework for Dynamic Mental State Modeling

Mengjia Zhang Rui Chen Haonan Xiao Yi Yang
Chongqing Technology and Business University
{zhangmengjia1, chenrui1, xiaohaonan1, yangchongyi}@ctbu.edu.cn

Abstract

Targeting the CLPsych 2026 (Ali et al., 2026) shared task, this study proposes a unified framework based on three complementary strategies. We implement a pipeline integrating post-level psychological state recognition, timeline-level change detection, and evidence-based clinical summarization. For Task 1, we evaluate three paradigms for extracting ABCD elements: zero-shot prompting, Qwen-3 fine-tuning, and TextCNN-based hierarchical classification. For Task 2, we design a cascaded temporal model that combines Mental-BERT features, log-time encoding, and Bi-LSTM to capture mental state switches and escalations under irregular posting intervals. For Task 3, we adopt a dynamic retrieval-augmented generation strategy to produce structured clinical summaries. Experimental results show that our system ranks second on the official leaderboard for Task 2, demonstrating the effectiveness of time-aware modeling for change detection. Error analysis further reveals over-prediction bias and valence inversion in Tasks 1 and 3, highlighting pipeline error propagation as a key challenge for future work.

1 Introduction

The Computational Linguistics and Clinical Psychology (CLPsych) workshop has hosted shared tasks focused on longitudinal mental state modeling from social media timelines (Tsakalidis et al., 2022a). Building on previous editions, the CLPsych 2026 Shared Task (Ali et al., 2026) focuses on capturing fine-grained mental health changes under the MIND framework (Atzil-Slonim, 2025), requiring psychological element extraction, temporal change detection, and evidence-based clinical summarization.

However, most existing methods do not adequately model the temporal dynamics of mental states and struggle with sparse, irregular posting sequences, while clinical interpretability remains limited. Automated detection of such dynamic changes is also critical for understanding the mechanisms underlying therapeutic change (Atzil-Slonim, 2026),where changes are operationalized as Switches (abrupt shifts) and Escalations (gradual intensifications) following(Tsakalidis et al., 2022b).

This work addresses three core questions: (1) how to accurately extract complex ABCD elements with limited annotations; (2) how to identify state fluctuations and deteriorations in irregular timelines; and (3) how to improve clinical interpretability through evidence-based summarization (Atzil-Slonim, 2026). Our contributions include a systematic comparison of ABCD extraction paradigms, a time-aware cascaded temporal model, and a dynamic RAG framework for clinical summary generation.

2 Related Work

Computational mental health research has transitioned from early bag-of-words and shallow classifiers (Zantvoort et al., 2023) to dense representations powered by pre-trained language models (Ji et al., 2022). However, general-purpose language models often exhibit semantic bias and struggle with highly specialized clinical expressions (Omar et al., 2025). While domain-specific models like Mental-BERT (Ji et al., 2022) mitigate this gap by encoding deep psychological patterns, their application has historically been limited to static, post-level classification rather than longitudinal trajectory modeling.

Longitudinal modeling from social media timelines has gained traction since CLPsych 2022 (Tsakalidis et al., 2022a). Nonetheless, sequential modeling in this domain faces two severe bottlenecks. First, data scarification and highly irregular posting intervals present substantial noise for standard recurrent architectures. Second, be-

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 422–434
July 4, 2026 ©2026 Association for Computational Linguistics

cause critical psychological change points (e.g., crises) are inherently sparse, conventional sequence optimizers frequently collapse into majority-class predictions, missing pivotal turning points (Tsakalidis et al., 2022a).

Furthermore, traditional systems typically treat diverse mental states as isolated, orthogonal variables. This directly violates clinical reality, particularly the systemic interweaving and dynamic coupling among Affect, Behavior, Cognition, and Desire (ABCD) highlighted by the MIND framework (Atzil-Slonim, 2025). In the LLM era, although zero-shot prompting and retrieval-augmented methods have been introduced for clinical summarization (Tseriotou et al., 2025), bridging the gap between fine-grained leaf-node classifiers and hallucination-free generative reasoning remains a challenge.To address these limitations, our system explores cascaded temporal modeling with log-time differences, multi-strategy ABCD extraction, and dynamic retrieval-augmented generation for clinical summarization.

3 Methodology

As illustrated in Figure 2, our framework strictly follows the three CLPsych 2026 sub-tasks: (1) identification and existence scoring of adaptive/maladaptive ABCD combinations; (2) detection of Moments of Change (MoC), distinguishing *switches* and *escalations*; and (3) generation of structured clinical summaries grounded in temporal information.

3.1 Task 1: ABCD Element Extraction

We explore three paradigms for transforming raw text into structured MIND annotations. First, we adopt zero-shot prompting with Llama-3.1-8B and constrained decoding to generate structured outputs. Second, we perform instruction-based fine-tuning by adapting Qwen-3-8B with 4-bit QLoRA under the LLaMA-Factory framework. Third, we employ a hierarchical discriminative CNN based on TextCNN, implemented via the NeuralClassifier (Liu et al., 2019) toolkit, to identify fine-grained leaf-node labels including Affect, Behavior, Cognition, and Desire, while capturing local n-gram features critical for clinical text analysis.

3.2 Task 2: Moment of Change Detection

To capture mental state transitions within sparse and irregular social media time series, we design a time-aware temporal modeling framework that extracts domain-specific semantic representations using Mental-BERT and captures irregular posting intervals through Log-scale Temporal Encoding. The model employs a hierarchical cascaded architecture where the predicted probability of a mental state switch is integrated as an auxiliary feature to guide and intensify the detection of risk escalations.

Domain-enhanced Encoding. We employ *Mental-BERT (base-uncased)* (Ji et al., 2022), pre-trained on large-scale mental health corpora, to extract semantic representations. Each post p_i is encoded into a 768-dimensional vector $\mathbf{v}_i$ via the `[CLS]` token, capturing domain-specific psychological patterns that general-purpose models might overlook.

Log-scale Temporal Encoding. To handle the inherent irregularity of posting intervals in longitudinal data, we explicitly model the temporal distance between adjacent posts. Let $\Delta t_i = t_i - t_{i-1}$ be the time interval (in hours) between consecutive posts. We compute a log-scale temporal feature f_{temp} as:

$$f_{temp} = \log(\Delta t_i + 1) \tag{1}$$

This scalar is concatenated with the semantic vector $\mathbf{v}_i$, resulting in a 769-dimensional time-aware input $\mathbf{x}_i = [\mathbf{v}_i; f_{temp}]$.

Cascaded Bi-LSTM. A three-layer Bidirectional LSTM (Bi-LSTM) is used as the backbone to capture long-range dependencies across the timeline. Following the clinical intuition that state escalations often coincide with transitions, we design a hierarchical prediction strategy that first predicts the probability of a state switch, then integrates this switch probability as an auxiliary feature into a second prediction head to guide escalation detection, so that the model can better focus on critical transition points when identifying intensified risks.

Training and Inference. We utilize *Focal Loss* (Lin et al., 2017) combined with dynamic positive weight balancing to mitigate the extreme class imbalance (i.e., the sparsity of change points). During inference, the initial post of each timeline is assigned a 'no-change' status by default to serve as a stable baseline anchor for longitudinal comparison.

3.3 Task 3.1: Evidence-Grounded Summary Generation

While initial experiments for Task 1 utilized the Qwen-3-8B-Instruct model, subsequent evaluations

sub ID	task1.1	task1.2	task2	task3.1					task3.2	
	MF1↑	RMSE↓	Comb MF1↑	CS↑	CT↓	R-L↑	BS↑	Avg↑	Imp↑	Det↑
1	0.118	**1.501**	0.470	0.622	0.859	0.239	——	——	——	——
2	0.210	1.506	0.397	**0.615**	**0.848**	**0.232**	**0.317**	**0.329**	——	——
3	**0.236**	1.585	**0.588**	0.633	0.842	0.200	——	——	0.125	0.500
Rank	14	16	2	12	12	8	7	10	7	5

Table 1: Overall submission results across all tasks and sub-tasks, including primary/secondary metrics and comparative official rankings. Here ↑ indicates higher scores are better; ↓ indicates lower scores are better. Metrics in **bold with arrows** (e.g., **MF1↑**, **RMSE↓**) are the **primary metrics used for official ranking**.
Metrics Definition: MF1: Subelement Macro F_1; **RMSE**: Avg RMSE for Maladaptive + Adaptive (**Lower is better**); **Comb MF1**: Combined Post/Timeline Macro F_1; **CS**: Consistency Score; **CT**: Contradiction Score (**Lower is better**); **R-L**: ROUGE-L Recall; **BS**: BERTscore Recall;**Avg**: Score Average; **Imp/Det**: Improvement/Deterioration Overall Score.

revealed suboptimal performance in extracting fine-grained psychological elements. Consequently, we shifted to the Qwen-2.5-7B-Instruct architecture for Task 3 fine-tuning via the Unsloth framework, to better align the generative process with clinical narrative logic and ABCD interaction dynamics, facilitating a more structured representation of the MIND framework.

To ensure the model's robustness during inference, the input context concatenates the raw text of each post with its corresponding predicted Task 1 ABCD annotations and Task 2 change labels. This pipeline ensures that the generated summaries rely strictly on predicted evidence rather than ground-truth labels, mirroring real-world application.

To mitigate overfitting and enhance clinical coherence, we implemented a Retrieval-Augmented Generation (RAG) strategy using `BGE-large-en-v1.5` (Xiao et al., 2023). Specifically, for each input query sequence, we map its textual representation into a high-dimensional dense vector space and compute the semantic similarity against the pre-computed training repository. The similarity score between a query vector $\mathbf{u}$ and a candidate instance vector $\mathbf{v}$ is evaluated via cosine similarity, formulated as:

$$\text{Sim}(\mathbf{u}, \mathbf{v}) = \cos(\theta) = \frac{\mathbf{u} \cdot \mathbf{v}}{\|\mathbf{u}\|_2 \|\mathbf{v}\|_2} \quad (2)$$

where d denotes the embedding dimension of the dense encoder. Based on these calculated scores, we dynamically retrieve the K ($K = 2$) most semantically relevant historical sequences from the training set and prepend their corresponding gold summaries to the context window as in-context exemplars. The final clinical summaries are generated via greedy decoding, truncated to a maximum of 350 words, and further constrained by a post-hoc filtering layer to ensure all cited ABCD elements are present in the source text.

3.4 Task 3.2: Dynamic Signature Extraction

For Task 3.2, we identify recurrent dynamic signatures of deterioration and improvement using a multi-stage hybrid strategy. We first conduct statistical profiling via frequency analysis on training summaries to capture dominant ABCD state transitions. We then perform representative clustering using K-Means on BGE-encoded sequence embeddings to select the most typical evidence sequences for each signature type. Finally, we carry out thematic distillation using a local Qwen-2.5-7B model to extract core academic terms and behavioral patterns from the clustering results. These extracted components are synthesized into structured academic templates, with each signature description constrained to 350 words to satisfy submission requirements.

4 Experiments

4.1 Dataset, Metrics, and Compliance

Dataset. The official CLPsych 2026 dataset comprises 373 posts across 30 user timelines, where 236 posts (63.27%) are labeled with fine-grained MIND annotations. Given the frequent co-occurrence of adaptive and maladaptive states, the task demands high-resolution discrimination. Text preprocessing involves removing hyperlinks and special symbols. For Task 2, timelines are chronologically ordered, and variable-length sequences are handled using masking.

Metrics. To ensure a fair, rigorous, and standardized comparison, our evaluation strictly adheres to the official metrics defined by the CLPsych 2026 shared task. Crucially, all quantitative results reported herein were directly evaluated by the shared

task organizers on their official platform using our blind submissions, thereby establishing the independent validity and credence of our system's performance. For Task 1.1 use **Precision**, **Recall**, and **Macro-F_1** over 12 element-valence pairs, ranking by the mean of Adaptive and Maladaptive Macro-F_1. Task 1.2 employs **MAE**, **RMSE**, and **Spearman correlation** on 1–5 scale ratings, with ranking determined by the mean of Adaptive and Maladaptive RMSE. Task 2 is a binary classification task for *Switch* and *Escalation*, evaluated via **Macro-F_1** at post and timeline levels, with the final score defined as:

$$\text{Score} = \frac{F_{1\text{post}} + F_{1\text{time}}}{2} \tag{3}$$

Task 3.1 uses ROUGE-L, BERTScore, Consistency Score (CS), and Contradiction Top (CT). Task 3.2 is qualitatively evaluated by experts regarding *evidence fit*, *recurrence*, and *specificity*.

Open-source Compliance. All experiments strictly adhere to the CLPsych 2026 Data Access Form. We rely exclusively on open-source models, including `Llama-3.1-8B`, `Qwen-3-8B`, `Qwen-2.5-7B`, `Mental-BERT`, and `BGE-large-en-v1.5`, which are deployed locally or via Hugging Face. Notably, no proprietary APIs (e.g., ChatGPT, Claude, Gemini) were employed at any stage.

4.2 Baselines

All experiments in this work compare our proposed method against the official baselines released by the shared task organizers.

5 Results and Analysis

Main Results. Table 1 summarizes the overall performance of our system across all tasks, while Tables 3 – 6 provide detailed, task-specific results. All scores reported in these tables are from the official evaluation conducted by the shared task organizers, ensuring the validity of our quantitative results. Each task-specific table compares our submitted system against the official shared-task baseline, reporting both the primary ranking metric and supporting secondary metrics.

In **Task 1**, the TextCNN-based model achieves a mean F_1 score of 0.236 and an RMSE of 1.585. For **Task 2**, our Mental-BERT cascaded architecture attains a combined Macro-F_1 score of **0.588**, ranking **second** on the official leaderboard. In **Task 3.1** (Table 5), our RAG-enhanced model reaches a BERTScore of 0.317, though its consistency score (CS) of 0.615 and ROUGE-L of 0.232 remain below the official baselines. However, in **Task 3.2** (Table 6), our approach achieves an overall score of 0.500 for the deterioration scenario, outperforming the official baseline (0.483). This result provides preliminary evidence that our model can capture certain patterns of clinical decline.

Ablation. To evaluate the contribution of each module, we conduct a series of ablation experiments on the official validation split of the CLPsych 2026 dataset.Table 7 validates each Task 2 component. Removing Bi-LSTM causes a catastrophic drop (-0.158), confirming the necessity of sequential context. Replacing Focal Loss with standard BCE degrades performance by -0.098, and removing `pos_weight` further drops it to 0.430, underscoring the importance of hard-example weighting for sparse clinical labels. Eliminating log-time diff incurs a modest but non-negligible penalty (-0.018), indicating that irregular intervals (e.g., bursts of posts or long silences) carry hidden temporal cues. Interestingly, decoupling Switch guidance from Escalation slightly improves score (+0.012), suggesting the cascaded design may introduce excessive dependency propagation; future work will explore gated fusion.

Discussion. While our second-place finish in Task 2 underscores the efficacy of domain-specific temporal modeling, the sub-baseline performance in Tasks 1 and 3 reveals substantial error propagation. Task 1 suffers from prediction pattern rigidity, where the model consistently over-predicts a fixed set of maladaptive elements (particularly C-S=2, C-O=2) across diverse posts, failing to discriminate between metaphorical language and genuine clinical symptoms. These recognition inaccuracies propagate to Task 3, manifesting as framework hallucinations where the generative model infers ABCD elements not explicitly present in the source text. This suggests that while cascaded models excel at macro-level change detection, bridging the gap between hierarchical classifiers and nuanced clinical reasoning remains a primary challenge.

Error Analysis for Task 1 Task 1 exhibits **over-prediction bias** and **label combination rigidity**. The model defaults to stereotyped configurations (C-S=2, C-O=2) across diverse posts, regardless of actual clinical content. **Example 1: Non-clinical over-prediction.** A casual movie discussion (*"Gol-*

lum is exactly what's going on in my head") receives six maladaptive elements (C-S=2, C-O=2, A=8, D=4, B-S=2, B-O=4), identical to severe depression posts. The model fails to recognize metaphorical language. **Example 2: Lack of discrimination.** An acute panic attack post and a chronic social drift post receive **identical predictions** (C-S=2, C-O=2, A=8, D=4, B-S=2, B-O=4), despite requiring clinically distinct ABCD profiles. **Root causes:** (1) low uniform threshold (0.15) admitting false positives; (2) absence of top-k constraints; (3) hierarchical classification bias toward complete label paths. These inference-level deficiencies suggest that post-hoc calibration may substantially improve performance.

Error Analysis for Task 3.1. Task 3.1 exhibits structural framework discrepancies (CS: 0.615; CT: 0.848) driven by two primary failure modes: (1) *Subelement Confusion and Valence Inversion*—The generative model misinterprets upstream predictions at the fine-grained level and fails to maintain polar consistency. As typified in sequence `seq8161a42a4`, while Task 1 correctly identifies adaptive coping markers (`D=1`), the text generation pipeline suffers a valence inversion, mapping it to a negative clause associated with `D=2` (*"expectation that it would persist ('will never be able')"*). Furthermore, driven by an inherent "completeness bias," the LLM over-generates non-predicted elements to synthetically balance the ABCD matrix. (2) *Temporal Misattribution and Signal Defiance*—The model fails to preserve longitudinal alignment across the timeline sequence. In `seq8161a42a4`, specific functional impairments such as severe avolition and somatic crisis (`B-S=2`, `B-O=4`), which were uniquely predicted in the late-stage post (*"sleeping 12 hours... tension headache"*), are erroneously cross-contaminated and anchored onto the summary of the initial checkpoint. This temporal drift is compounded by instruction defiance: the generation framework rejects the explicit upstream Task 2 transition token (`Switch=S`), instead fabricating a contradictory `Escalation=E` narrative. Consequently, while the metaphorical discourse in the subsequent post (*"Gollum is exactly what's going on in my head"*) receives highly coherent paraphrasing, the cumulative tracking yields a high BERTScore (0.317) but low factual consistency, highlighting the trade-off between narrative fluency and structural fidelity.

6 Conclusion

We presented a multi-strategy framework for CLPsych 2026 that integrates Mental-BERT domain embeddings, log-scale temporal encoding, and dynamic RAG. While the cascaded Bi-LSTM model demonstrated efficacy in capturing macro-level psychological switches and escalations, Task 1 and 3 results underscore the persistent challenges in fine-grained clinical element recognition and hallucination control in generative summaries. This work highlights the potential of temporal-aware modeling and identifies key failure modes for error propagation in automated mental health trajectory monitoring.

Ethics Statement

The dataset consists of anonymized Reddit posts with personally identifiable information removed by the organizers. This paper contains **no verbatim examples** from the raw dataset; any illustrative content is paraphrased or synthesized from official guidelines. All models (Llama-3.1-8B, Qwen-3-8B, Qwen-2.5-7B, Mental-BERT, BGE-large-en-v1.5) are **strictly open-source** and deployed locally or via Hugging Face, fully complying with the CLPsych 2026 Data Access Form. No proprietary APIs (e.g., ChatGPT, Claude, Gemini) are used. The system is intended for research assistance only; it does **not** constitute clinical diagnosis or treatment advice. Automated mental-health assessments carry risks of false positives/negatives and must be reviewed by qualified clinicians before any clinical application.

Limitations

Our work is constrained by the small-scale dataset (30 timelines, 373 posts), which limits cross-demographic generalization. All experiments are monolingual (English), leaving cross-cultural applicability unverified. Hardware restrictions (8GB VRAM) prevent exploration of larger backbones (e.g., 13B+ parameters) that might improve representation capacity. Task 1 did not surpass the official baseline, suggesting that fine-grained clinical element extraction remains an open challenge. Task 3.2 relies on heuristic rules and clustering, which may not generalize to out-of-distribution narrative patterns.

Acknowledgments

We thank the CLPsych 2026 organizers for the dataset and evaluation framework. We acknowledge the open-source communities behind Hugging Face, Unsloth, and LLaMA-Factory.

References

Iqra Ali, Talia Tseriotou, Guy Dvir, Callum Chan, Yuxiang Zhou, Juan Antonio Lossio-Ventura, Ayal Klein, Aya Shamir, Dan Sayda, Anthony Hills, Aya Zirikly, Diana Inkpen, Dana Atzil-Slonim, and Maria Liakata. 2026. Overview of the clpsych 2026 shared task: Capturing and characterizing mental health changes through social media timeline dynamics. In *Proceedings of the 11th Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Dana Atzil-Slonim. 2025. Multimodal intrapersonal and interpersonal dynamics (mind): A transtheoretical coding manual.

Dana Atzil-Slonim. 2026. Leveraging theoretical and technological innovations to study the mechanisms that underlie therapeutic change in psychotherapy. In Louis G. Castonguay, Dana Atzil-Slonim, Michael Barkham, and Wolfgang Lutz, editors, *Practice-Based Evidence in the Psychological Therapies: Toward Policy Implications for Research, Training, and Clinical Guidelines*. Oxford University Press, New York.

Shaoxiong Ji, Tianlin Zhang, Luna Ansari, Jie Fu, Prayag Tiwari, and Erik Cambria. 2022. Mentalbert: Publicly available pretrained language models for mental healthcare. In *proceedings of the thirteenth language resources and evaluation conference*, pages 7184–7190.

Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. 2017. Focal loss for dense object detection. In *Proceedings of the IEEE international conference on computer vision*, pages 2980–2988.

Liqun Liu, Funan Mu, Pengyu Li, Xin Mu, Jing Tang, Xingsheng Ai, Ran Fu, Lifeng Wang, and Xing Zhou. 2019. Neuralclassifier: An open-source neural hierarchical multi-label text classification toolkit. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics: System Demonstrations*, pages 87–92.

Mahmud Omar, Shelly Soffer, Reem Agbareia, Nicola Luigi Bragazzi, Donald U Apakama, Carol R Horowitz, Alexander W Charney, Robert Freeman, Benjamin Kummer, Benjamin S Glicksberg, and 1 others. 2025. Sociodemographic biases in medical decision making by large language models. *Nature Medicine*, 31(6):1873–1881.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022a. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Adam Tsakalidis, Federico Nanni, Anthony Hills, Jenny Chim, Jiayu Song, and Maria Liakata. 2022b. Identifying moments of change from longitudinal user text. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 4647–4660.

Talia Tseriotou, Jenny Chim, Ayal Klein, Aya Shamir, Guy Dvir, Iqra Ali, Cian Kennedy, Guneet Singh Kohli, Anthony Hills, Ayah Zirikly, Dana Atzil-Slonim, and Maria Liakata. 2025. Overview of the CLPsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 193–217, Albuquerque, New Mexico. Association for Computational Linguistics.

Shitao Xiao, Zheng Liu, Peitian Zhang, and Niklas Muennighoff. 2023. C-pack: Packaged resources to advance general chinese embedding. *Preprint*, arXiv:2309.07597.

Kirsten Zantvoort, Jonas Scharfenberger, Leif Boß, Dirk Lehr, and Burkhardt Funk. 2023. Finding the best match—a case study on the (text-) feature and model choice in digital mental health interventions. *Journal of Healthcare Informatics Research*, 7(4):447–479.

Appendix

A Data Specification and Framework Mapping Exemplars

To ensure that the zero-shot open-source large language models (e.g., `Llama-3.1-8B`) strictly adhere to the hierarchical MIND coding manual without encountering parsing failures, we engineered a deterministic, role-based prompting schema.

As detailed in the template below, the prompt architecture functions as a gatekeeper for three core operational constraints:

1. **Clinical Alignment:** It explicitly enforces the structural dichotomy of the MIND framework, where even-numbered sub-elements map onto *Maladaptive* behaviors and odd-numbered sub-elements correspond to *Adaptive* coping strategies.

2. **Presence Score Calibration:** To prevent the pipeline from crashing on posts devoid of

active psychological cues, the prompt constraints the model to guarantee a baseline output (`"presence": 1`) instead of producing null fields.

3. **JSON Schema Adherence:** It restricts the generation path exclusively to valid JSON tokens via constrained decoding instructions, eliminating conversational verbiage or chain-of-thought metadata that could impede automated string parsing.

A.1 Task 1 Zero-Shot Annotation Prompt Template

In this section, we provide the specific prompt templates used for Task 1: ABCD Element Extraction using the zero-shot Llama-3.1-8B model.

Listing 1: System prompt and formatting constraints for Task 1 ABCD extraction.

```
You are a clinical psychology
    annotation expert for CLPsych
     2026.
Your task is to analyze social
    media posts using the MIND
    framework (ABCD model).

CRITICAL RULES:
1. Identify ABCD elements for
    BOTH Adaptive and Maladaptive
     states (if present in post)
2. For each element, output ONLY
     the subelement NUMBER (
    integer), NOT text
    descriptions
3. PRESENCE SCORE (1-5) rates
    how dominant the ENTIRE state
     is in the post:
    - 1 = Not present at all
    - 2 = Somewhat present (
       subtle role)
    - 3 = Moderately present (
       clearly contributes)
    - 4 = Much present (strongly
       influences)
    - 5 = Highly present (defines
        the overall experience)
4. Only include elements that
    are CLEARLY expressed in the
    post
5. For each element (A, B-O, B-S
    , C-O, C-S, D), you can
    identify at most ONE
    subelement per valence

VALID SUBELEMENT NUMBERS:
- A (Affect): 1-14
  Adaptive: 1,3,5,7,9,11,13 |
     Maladaptive:
     2,4,6,8,10,12,14
- B-O (Behavior-Others): 1-4
  Adaptive: 1,3 | Maladaptive:
     2,4
- B-S (Behavior-Self): 1-2
  Adaptive: 1 | Maladaptive: 2
- C-O (Cognition-Others): 1-4
  Adaptive: 1,3 | Maladaptive:
     2,4
- C-S (Cognition-Self): 1-2
  Adaptive: 1 | Maladaptive: 2
- D (Desire): 1-6
  Adaptive: 1,3,5 | Maladaptive:
      2,4,6

OUTPUT FORMAT (STRICT JSON - NO
    TEXT DESCRIPTIONS):
{
  "adaptive": {
    "presence": 1-5,
    "elements": {
      "A":1,
      ...
    }
  },
  "maladaptive": {
    "presence": 1-5,
    "elements": {
      ...
    }
  }
}
If a state is not present, use:
    {"presence": 1, "elements":
    {}}
```

A.2 Exploratory Multi-Task Joint Fine-Tuning Setup

During the exploratory phase for Task 1 and Task 2, we investigated a generative alternative: transforming the longitudinal social media streams into a unified, sequential instruction-following dataset for Supervised Fine-Tuning (SFT). This pipeline was implemented via the LLaMA-Factory toolkit

using an autoregressive `Qwen-3-8B` backbone.

The core engineering strategy relied on a **Rolling Chronological Window** to operationalize dynamic psychological trajectories:

- **Longitudinal Context Buffering:** For any target post p_t (*Current Post*), all prior historical posts $\{p_1, p_2, \ldots, p_{t-1}\}$ are formatted with precise timestamps and appended into the *Social Media Context* field. This provides the causal attention mechanism with the explicit baseline needed to distinguish static personality traits from acute psychological fluctuations.

- **Multi-Task Joint Reasoning:** Rather than optimizing separate task-specific heads, the target *Output* sequence is formulated to output a unified textual token stream. As formalized in the structured schema, the model is forced to jointly decode macro-level transitions (*Switch* and *Escalation*) alongside micro-level framework alignments (leaf-node ABCD segments and explicit *Presence* intensity ratings).

Table 2 provides a series of consecutive, anonymized training exemplars illustrating how our pipeline tracks a user's progressive shifts from severe distress to adaptive coping, and back to acute interpersonal anxiety.

A.3 Hierarchical Discriminative Classification Framework (NeuralClassifier)

To overcome the limitations of large language models in fine-grained clinical structural tracking, our configuration for Task 1 utilizes a discriminative, hierarchical multi-label text classification paradigm powered by the open-source `NeuralClassifier` framework.

A.3.1 Taxonomy Formalization

As illustrated in Figure 1, we mapped the clinical MIND manual into a strict three-tier structured hierarchy to formalize the semantic dependencies between high-level psychological dimensions and fine-grained behavioral representations:

- **Tier 1 (Root Nodes):** Formulates the 6 foundational dimensions of the ABCD model: Activating Event (`A`), Belief about Others (`B-O`), Belief about Self (`B-S`), Consequence regarding Others (`C-O`), Consequence regarding Self (`C-S`), and Disputation (`D`).

- **Tier 2 (Valence Dichotomy):** Branching from each root node into binary valences: *Adaptive* (`A`, e.g., `AA`, `B-SA`) representing positive coping, and *Maladaptive* (`M`, e.g., `AM`, `B-SM`) representing psychological vulnerability.

- **Tier 3 (Leaf Nodes):** Mapping directly onto explicit clinical sub-categories (e.g., `AM2` for anxious/fearful affect, `DM6` for self-criticism disputation) spanning 12 element-valence terminal pairs.

A.3.2 Data Synthesis Pipeline

To feed the discriminative hierarchical neural net (TextCNN backbone), our custom preprocessing pipeline flattens the clinical data into a specialized JSON token format. For any given text span, the label generator dynamically parses the leaf-node category and automatically expands the complete ancestor path from Tier 3 back to Tier 1, enforcing deterministic path constraints. A representative tokenized sample is formalized as follows:

```
{ "doc_label":  ["B-SA", "DA", "AA5",
"B-SA1"],
"doc_token":  ["after", "8", "years",
"of", "struggling", "with", "self",
"harm", "i", "am", "starting", "to",
"cover", "my", "older", "scars..."] }
```

By optimizing a localized hierarchical loss function rather than vanilla flat classifiers, the TextCNN backbone explicitly captures the directional entailment (e.g., predicting `AM2` implies absolute activation of `AM` and `A`), significantly stabilizing structural element boundaries under low-resource validation.

B System Architecture Diagram

Field	Content / Multi-Task Rolling Window Schema
Instruction	Analyze the psychological state of the 'Current Post' based on the provided 'Social Media Context'. Tasks: 1. Identify 'Switch' and 'Escalation'. 2. Extract ABCD framework evidence. 3. Assign 'Presence' scores.
Exemplar 1: Baseline Distress (Chronological Anchor)	
Input	**### Social Media Context (Previous Posts):** [02-09-2019] Post: I'm mean **### Current Post to Analyze:** Date: 04-09-2019 Content: I'm not okay... I wish someone actually liked me... I wish I didn't wish I were dead.
Output	**[Change Analysis]** - Switch: 0; - Escalation: 0; - Well-being: 5 **[Adaptive State]** - Dimension D: I wish that I want to make my life worth living... [Presence Score: 3] **[Maladaptive State]** - Dimension C-O: I wish someone wanted to hold my hand... [Presence Score: 4]
Exemplar 2: Transition Trigger (Altruistic Coping - State Switch Detected)	
Input	**### Social Media Context (Previous Posts):** [02-09-2019] Post: I'm mean [04-09-2019] Post: I'm not okay... I wish I didn't wish I were dead. **### Current Post to Analyze:** Date: 05-09-2019 Content: [HELP!] Calling All Animal Fosters... I found a bundle of kittens... I want to try my best to get these cats a better life...
Output	**[Change Analysis] - Switch: S**; - Escalation: 0; - Well-being: 7 **[Adaptive State]** - Dimension C-S: I want to try my best to get these cats a better life... [Presence Score: 4] **[Maladaptive State]** - Dimension A: I am in desperate need of some help right now. [Presence Score: 2]
Exemplar 3: Interpersonal Vulnerability (Relapse/Fluctuation Pattern)	
Input	**### Social Media Context (Previous Posts):** [04-09-2019] Post: I'm not okay... I wish I didn't wish I were dead. [05-09-2019] Post: [HELP!] Calling All Animal Fosters... **### Current Post to Analyze:** Date: 08-09-2019 Content: I think I need to work on my self esteem... So I went on a date recently... He didn't really respond and now I'm doubting myself...
Output	**[Change Analysis]** - Switch: 0; - Escalation: 0; - Well-being: 7 **[Adaptive State]** - Dimension B-S: So I went on a date recently and I actually... had a really great time. [Presence Score: 4] **[Maladaptive State]** - Dimension C-S: I'm doubting myself thinking I already messed something up. [Presence Score: 3]

Table 2: Chronological training sequence illustrating the multi-task rolling dynamic window used during the exploratory fine-tuning phase.



Figure 1: Hierarchical taxonomy tree architecture derived from the formalized clinical MIND framework. The tree explicitly operationalizes a three-tier structured dependency for the `NeuralClassifier` engine: Tier 1 establishes the foundational ABCD coordinates, Tier 2 bifurcates into dynamic binary valences (**Adaptive**vs. **Maladaptive**), and Tier 3 maps onto fine-grained clinical leaf representations (e.g., `AM2`, `DM4`) aligned with our empirical parsing pipeline.



Figure 2: Overall three-stage framework of our proposed system. Clinical rule constraints are enforced throughout the entire pipeline.

sub ID	Core Technical Path	F1 (1.1)↑	Avg RMSE (1.2)↓
1	Ollama + Llama-ZeroShot	0.118	**1.501**
2	Qwen3-base + LLaMA-Factory fine-tuning	0.210	1.506
3	TextCNN + Loss optimization for imbalance	**0.236**	1.585
-	Official Baselines	0.247	1.424

Table 3: System Performance Evolution across Experimental Stages for Task 1.

Note: All scores reported in this table correspond to our official submissions during the formal shared task competition phase.Here, F_1 denotes the *Average Subelement Macro* F_1,while Avg RMSE represent *Avg RMSE Maladaptive + Adaptive*

sub ID	Method	Overall / Comb.↑	P-Macro F1↑	T-Macro F1↑	Rank
1	all-MiniLM + Bi-LSTM	0.470	0.465	0.475	—
2	Qwen-SFT (Task 1 feats)	0.397	0.340	0.455	—
3	Mental-BERT + Log-Time + Focal	**0.588**	**0.611**	**0.564**	**2**
-	Official Baselines 3	0.572	0.561	0.583	—
-	Official Baselines 2	0.365	0.383	0.346	—
-	Official Baselines 1	0.272	0.169	0.400	—

Table 4: Official Codabench submission results for Task 2. Best scores in bold.

Note: All scores reported in this table correspond to our official submissions during the formal shared task competition phase. Here, Overall / Comb., P-Macro F_1, and T-Macro F_1 denote *Combined (Post/Timeline) Macro* F_1, *Post Macro* F_1, and *Timeline Macro* F_1, respectively.

sub ID	Architecture	CS↑	CT↑	R-L↑	BS↑
1	Ollama + Few-shot	0.622	0.860	0.240	–
2	Qwen2.5-7B + LoRA	0.633	0.842	0.199	–
3	SFT + RAG + Alignment	**0.615**	**0.848**	**0.232**	**0.317**
–	Official Baseline 1	0.763	0.753	0.255	0.226
–	Official Baseline 2	0.767	0.745	0.269	0.235

Table 5: System performance for Task 3.1: Change Sequence Summarization. Best scores per column are indicated in bold.

Note: All scores reported in this table correspond to our official submissions during the formal shared task competition phase.**CS**: Consistency Score; **CT**: Contradiction Score (**Lower is better**); **R-L**: ROUGE-L Recall; **BS**: BERTscore Recall.

Method	Scenario	Fit↑	Recur.↑	Spec.↑	Overall↑
Ours	Improvement	0.250	0.250	0.000	0.125
	Deterioration	1.000	1.000	0.000	**0.500**
Baseline	Improvement	0.375	0.437	0.375	0.389
	Deterioration	0.562	0.375	0.437	0.483

Table 6: Qualitative assessment for Task 3.2: Signatures. Best overall scores in bold.

Note: All scores reported in this table correspond to our official submissions during the formal shared task competition phase. Here, Fit, Recur., Spec., and Overall denote *Fit Score*, *Recurrence Score*, *Specificity Score*, and *Overall Score*, respectively.

Table 7: Ablation study on Task 2 (Macro F_1). Δ is relative to the full model.

Variant	Key Modification	Score	Δ
Full Model	Best configuration (Bi-LSTM + Focal)	**0.588**	—
BERT-Only	Remove Bi-LSTM; use MeanPool + MLP	0.430	−0.158
w/o Focal	Replace with standard BCELoss	0.490	−0.098
No PosWeight	Focal loss with `pos_weight=None`	0.430	−0.158
NoSwitchGuide	Escalation detection w/o Switch logit	0.600	+0.012
NoTime	Remove log-time difference features	0.570	−0.018
Uni-LSTM	Use unidirectional LSTM layers	0.470	−0.118

C Dataset Characteristics and Label Distributions

In this section, we present a comprehensive exploratory data analysis (EDA) of the official CLPsych 2026 dataset to provide deeper empirical insights into the distribution and co-occurrence patterns of the MIND framework annotations.As shown in Figure 3 and Figure 4, we systematically analyze the data characteristics from both macro and micro perspectives.



(a) Distribution of mental self-states.

(b) Overall label coverage.

Figure 3: Macro-level analysis of the CLPsych dataset. (a) Illustrates the severe overlap of adaptive and maladaptive states, where nearly half of the posts (47.5%) present both states simultaneously. (b) Demonstrates that adaptive and maladaptive signals maintain an approximately balanced representation across the corpus.



(a) Fine-grained distribution of ABCD sub-elements.



(b) Intensity distribution of Presence Scores (P1–P5).

Figure 4: Micro-level and intensity analysis of MIND annotations. (a) Compares the counts of Affect (A), Behavior-Others (B-O), Behavior-Self (B-S), Cognition-Others (C-O), Cognition-Self (C-S), and Desire (D) across valences, revealing a high concentration of maladaptive Affect and adaptive Behavior-Others. (b) Depicts the density of clinical presence ratings, indicating that adaptive cues lean towards moderate intensity (P2) while maladaptive deterioration presents a significant peak at high intensity (P4).

Agentic Pipelines Meet Retrieval-Augmented ICL: A Zero-Training Approach to Mental Health Modeling

Anson Antony[1,2], **Gautam Vijay Kumar**[3], **Annika M. Schoene**[2]

[1]Maia Medical Billing Corp, [2]Northeastern University, [3]Florida International University

Correspondence: ansonanto53@gmail.com

Abstract

We describe the Meronym Labs system for the CLPsych 2026 shared task. Our approach uses retrieval-augmented in-context learning with frozen LLMs throughout, requiring no fine-tuning. Tasks 1 and 2 use a single Qwen 3.5 27B call per post/timeline with static and dynamically retrieved examples. Task 3.1 uses a five-agent agentic pipeline including rule-based agents for change type and direction, LLM agents for dynamics extraction and summary writing, and a validator all augmented with NLI-based candidate re-ranking and iterative contradiction reduction. The system ranked 1st on Task 1.2 (RMSE 0.917) and Task 3.1 (score rank average 4.00), 3rd on Task 1.1 (F1 0.420), and 8th on Task 2 (F1 0.466).

1 Introduction

The CLPsych 2026 shared task asks participants to model dynamic mental health changes through social media timelines, building on the MIND framework (Atzil-Slonim, 2025, 2026) that conceptualises self-states as combinations of Affect, Behaviour, Cognition, and Desire (ABCD) components. The task comprises four subtasks: ABCD subelement classification (Task 1.1), self-state presence rating (Task 1.2), moments-of-change detection (Task 2), and sequence summarisation (Task 3.1). We participated in all four subtasks with a unified architecture and no*no fine-tuning*. Every system is a frozen LLM conditioned at inference time through in-context learning (ICL) and retrieval-augmented generation (RAG). This choice was motivated by three considerations. First, the training set was small (236 annotated posts, 30 timelines, 74 change sequences), making fine-tuning of billion-parameter models impractical. Second, the ABCD schema is complex (32 subelement codes across two valences and six element types), but can be fully specified in a prompt. Finally, post text is clinically sensitive, and ICL allows all inference to run locally without transmitting data to external services.

2 Related Work

Mental health NLP has a rich history of analysing social media to detect psychiatric conditions (De Choudhury et al., 2013; Coppersmith et al., 2014; Chancellor and De Choudhury, 2020), with CLPsych shared tasks progressively addressing suicidality risk (Zirikly et al., 2019), longitudinal mood change (Tsakalidis et al., 2022), and ABCD-grounded self-state dynamics (Tseriotou et al., 2025). Top-performing systems at recent editions have combined ICL with retrieval-based example selection (Uluslu et al., 2024; Antony and Schoene, 2025), a direction well-supported by broader work on RAG (Lewis et al., 2020) and ICL (Brown et al., 2020; Min et al., 2022) in clinical NLP settings (Agrawal et al., 2022). Our automated prompt-tuning loop builds on LLM-as-judge evaluation (Zheng et al., 2023) and iterative prompt optimisation (Pryzant et al., 2023; Yang et al., 2023).

3 Infrastructure

All systems run on three NVIDIA A40 GPUs (46 GB each) via a local Ollama server. Tasks 1 and 2 use *Qwen 3.5 27B* (Qwen Team, 2025), a dense 27-billion-parameter model, with thinking mode disabled (temperature 0.1, max 4,096 output tokens). Task 3.1 uses *Gemma 4 31B* (Gemma Team, 2025) with thinking mode disabled (temperature 0.2, max 900 tokens). We disabled thinking mode, because the Ollama chat API returned an empty content field and routed all output to a separate thinking field inaccessible to the pipeline. Semantic retrieval uses *Nomic Embed Text* (Nussbaum et al., 2024), a 768-dimensional embedder on the same Ollama server, over a persistent *ChromaDB* index with HNSW indexing (Malkov and

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 435–440
July 4, 2026 ©2026 Association for Computational Linguistics

Yashunin, 2018) and cosine similarity. All inference runs locally; post text and gold labels are never transmitted to an external service. The only exception is the Task 2 prompt-tuning loop (Section 4.2), in which only aggregate error statistics (scalar F1, precision, and recall counts) and the current prompt text are sent externally. No shared-task data ever leaves local hardware. This includes post content, individual labels, and any record from which a post or annotation could be reconstructed. The external API was used purely as a prompt-rewriting tool conditioned on numeric summaries, so this usage is consistent with the CLPsych 2026 Data Access Form, which restricts the transmission, storage, and processing of the dataset itself by external services.

4 System Description

We refer the reader to Ali et al. (2026) for full definitions and evaluation metrics for each task.

4.1 Tasks 1.1 and 1.2

The schema treats subelement classification (Task 1.1) and presence rating (Task 1.2) as facets of the same prediction, so both outputs are produced in a single LLM call per post. Figure 1 shows the pipeline.

*Prompt design:*The six-part prompt contains: (1) a system message embedding the MIND framework and classification rules; (2) the full 32-code ABCD sub-element table from the task guidelines; (3) the exact 1–5 presence scale definitions; (4) *three static gold examples* chosen once at startup, covering a maximally adaptive post, a maximally maladaptive post, and a clearly mixed post; (5) *two dynamic RAG examples* retrieved per post by cosine similarity from ChromaDB; and (6) the target post with a JSON output schema. The static examples teach the model the *range* of correct outputs; the RAG examples teach it what *similar* posts have been labelled by human annotators. This combination keeps prompt length bounded while providing both distributional coverage and instance-specific guidance.

Post-validation: A deterministic layer strips any `<think>` blocks from the response, extracts the JSON output (fenced block or first balanced-brace pair), validates every sub-element code against the expected schema (e.g. adaptive Affect codes must belong to $\{1, 3, 5, 7, 9, 11, 13\}$), clamps Presence to $[1, 5]$, and drops invalid entries.



Figure 1: Overview of the Task 1 pipeline.

4.2 Task 2: Moments of Change

Our Task 2 pipeline has two stage. Stage 1 estimates per-post well-being, where gold scores are used directly in training mode; otherwise Qwen 3.5 27B assigns a GAF-rescaled 1–10 score from an anchored prompt designed to counteract the model's bias toward outputting 7. Stage 2 passes all post texts and well-being scores in a single timeline-level LLM call, returning per-post JSON labels with definitions for both change types, eleven linguistic escalation triggers, and instructions to scan every 3-, 4-, and 5-post window. The Stage 2 prompt was produced by an automated loop: eight iterations on a 50-post development sample, where aggregate F1 statistics (not post text or labels) were sent to Claude Sonnet 4 via API to rewrite the prompt, accepting only improvements. Escalation recall rose from 0.17 (rule-based) to 0.65 (LLM-first) to 0.92 (auto-tuned); Table 1 shows the full progression.

Variant	Sw F1	Esc F1	Comb.	Esc R
v1: rule + LLM verify	0.507	0.241	0.394	0.17
v2: LLM-first, hybrid switch	0.593	0.583	0.512	0.65
v2 + auto-tune (i7)	**0.743**	**0.654**	**0.699**	**0.92**
Submitted (full test set)	0.423	0.597	0.466	0.71

Table 1: Task 2 ablation. Rows 1–3: 50-post development sample. Row 4: official test-set submission.

4.3 Task 3.1: Sequence Summarisation

We made three Codabench submissions for Task 3.1, each building on the previous, with Gemma 4 31B as the generator throughout.

Submission 1 (CS 0.7464) Five specialist modules operate in sequence and two rule-based agents deterministically derive change type (Switch vs. Escalation) and direction (improvement vs. deterioration), offloading structural reasoning from the LLM. A *DynamicsExtractor* call returns structured JSON covering the central theme, temporal phases, and ABCD dynamics. A *SummaryWriter* composes a $\leq$350-word summary conditioned on these outputs and three ChromaDB-retrieved gold exemplars, whiel a rule-based *Validator* checks word count, ABCD tag coverage ($\geq$0.85), and explicit naming of change identity and direction, routing failures to a targeted reviser. Our analysis of the training-to-test gap identified contradicting sentences as the dominant failure mode, motivating Submission 2.

Submission 2 (CS 0.7874) We added two components, where the four candidate summaries generated at temperatures $\{0.1, 0.3, 0.5, 0.7\}$ are reranked by DeBERTa-v3-large (He et al., 2023) NLI scores against gold exemplars. A *CT-Reducer* then rewrites sentences whose contradiction score exceeds 0.4 using targeted strategies (verb-swap, hedging, universal-removal), reducing CT by 0.13 relative to Submission 1.

Submission 3 (CS 0.8007, best) Here, our analysis revealed two failure modes, where 12% of sentences exceeded contradiction 0.5 but escaped the 0.4 threshold, and five of the ten worst sentences were formulaic openers scored as contradicting gold summaries. We addressed this in two additional passes address by re-writing regex-detected openers that are anchored in post evidence, and the CT-Reducer threshold is lowered from 0.4 to 0.25.

4.4 Task 3.2: Recurrent Dynamic Signatures

Our approach uses a map-reduce pipeline over the 74 training gold summaries with Gemma 4 31B. The summaries are partitioned into improvement and deterioration groups via keyword detection with an LLM tiebreak, chunked into groups of eight, and recurring ABCD patterns extracted per chunk (*map* phase). Chunk-level patterns are then synthesised into one signature per direction (*reduce* phase), constrained to $\leq$90 words. The submitted version adds multi-candidate generation ($N = 5$), a hedging pass mirroring the CT-Reducer from Task 3.1, and LLM-as-judge reranking.

5 Results

Tables 1, 2, and 3 present the full results. Table 1 shows the Task 2 ablation, Table 2 reports official scores for Tasks 1 and 2, and Table 3 shows the Task 3.1 progression across submissions. The gap between adaptive (0.32) and maladaptive (0.52) subelement F1 on Task 1.1 is consistent with prior findings on sentiment asymmetry in mental health posts. For Task 2, the post-level macro F1 (0.510) exceeds the timeline-level F1 (0.421) by a larger margin than most competing teams, suggesting the single-timeline-prompt design loses structural coherence when predictions are aggregated. The largest single gain on Task 3.1 came from NLI reranking and CT-Reducer combined (+0.041 CS, $-$0.128 CT, Sub 1 to Sub 2).

6 Discussion

The Task 3.1 rank 1 result is notable because our system did not lead on any single metric, but achieved the best score rank average by being consistently strong across all four. Teams that led on individual metrics (e.g. Aurevia, 1st on CS but 11th on ROUGE-L and BERTScore) fell off on others, suggesting that optimising for a single metric is insufficient for this task. For Task 2, the largest performance jump came from replacing the rule-based escalation detector with a linguistically grounded prompt, as the signal is present in word choice and



Figure 2: Overview of Task 3.1 pipeline.

tone rather than numeric well-being thresholds. For Task 3.1, each submission improved by targeting a specific failure mode from prior outputs, with each CS and CT gain accompanied by a small ROUGE-L regression as rewriting moved text away from gold summary phrasing. Post-deadline scaling experiments with DeepSeek-R1 70B suggest that generator size alone does not drive summary quality; gains came instead from post-hoc NLI reranking and iterative contradiction reduction (Appendix A).

7 Conclusion

We presented a retrieval-augmented in-context learning system for the CLPsych 2026 shared task that achieves competitive results across all four submitted subtasks without any fine-tuning. The system ranked 1st on Task 1.2 (presence rating) and Task 3.1 (sequence summarisation), 3rd on Task 1.1 (subelement classification), and 8th on Task 2 (moments of change). Key design choices included combining static diversity examples with dynamic retrieval for structured prediction, automated LLM-driven prompt optimisation for change detection, and iterative NLI-guided contradiction reduction for summarisation. These results demonstrate that frozen LLMs with well-designed prompts and retrieval can match or exceed fine-tuned approaches in low-resource clinical NLP settings.

Task 1.1: Subelement Classification (Rank 3 / 17)	
Avg. Subelement Macro F1 (ranking)	0.4197
Adaptive Subelement F1	0.3228
Maladaptive Subelement F1	0.5166
Avg. Element Presence Macro F1	0.6383
Task 1.2: Presence Rating (Rank 1 / 17)	
Avg. RMSE (ranking)	0.9167
Adaptive RMSE	1.0000
Maladaptive RMSE	0.8333
Quadratic Weighted κ	0.6774
Spearman ρ	0.6973
MAE	0.6667
Task 2: Moments of Change (Rank 8 / 18)	
Combined Post+Timeline Macro F1 (ranking)	0.4655
Post-level Macro F1	0.5098
Switch F1	0.4231
Escalation F1	0.5965
Timeline-level Macro F1	0.4212
Baselines (combined macro F1)	
TempoFormer	0.5721
Llama-3.1-8B + Task 1.1 input	0.3648
Llama-3.1-8B zero-shot	0.2722

Table 2: Tasks 1 and 2 official results with valence breakdown and baseline comparisons.

Limitations

The Task 2 auto-tuned prompt produced a score of 0.466 on the official submission but 0.427 on a later resubmission of the same predictions, indicating instability the leaderboard position alone does not reflect. The adaptive presence RMSE on Task 1.2 was 1.00 compared to 0.83 for maladaptive, suggesting the prompt examples do not adequately cover the range of adaptive state presentations. Task 3.2 yielded weak results, with the map-reduce approach failing to capture cross-sequence patterns for improvement trajectories in particular.

Ethics Statement

This work analyses social media posts from individuals experiencing mental health difficul-

System	CS↑	CT↓	RL↑
Development set (74 sequences)			
Single-call RAG	0.763	0.744	**0.374**
Agentic v1	0.772	0.726	0.297
Official test set (19 sequences)			
Sub 1: Agentic	0.746	0.801	0.293
Sub 2: +NLI +CT-Red	0.787	0.673	0.282
Sub 3: +CS-Boost	**0.801**	**0.659**	0.266
Official ranking (Rank 1 / 13, Score Rank Avg = 4.00)			
CS (consistency)	0.801	Rank 3 / 13	
CT (contradiction)	0.659	Rank 3 / 13	
ROUGE-L recall	0.266	Rank 6 / 13	
BERTScore recall	0.345	Rank 4 / 13	

Table 3: Task 3.1 ablation across submissions and official per-metric ranking.

ties. All data was provided through the official CLPsych 2026 shared task under institutional data use agreements. All inference ran on local hardware; post text and gold labels were never transmitted to external services. The sole exception was the Task 2 prompt-tuning loop, where only aggregate error statistics and prompt text (not post content, individual labels, or any reconstructable record) were sent to an external API for prompt rewriting. We confirm that this usage complies with the CLPsych 2026 Data Access Form: the shared-task dataset was never transmitted to, stored by, or processed by any external service, and the API received only scalar performance summaries that disclose nothing about any individual post or annotation. We recognise that automated mental health assessment systems can carry multiple risks, including but note limited to misclassification and should not be used as standalone diagnostic tools. The systems described here are research prototypes evaluated in a shared task setting. To support reproducibility, the full prompts used across all subtasks are available from the corresponding author upon reasonable request. These prompts contain no shared-task data.

References

Monica Agrawal, Stefan Hegselmann, Hunter Lang, Yoon Kim, and David Sontag. 2022. Large language models are few-shot clinical information extractors. In *Proceedings of the 2022 conference on empirical methods in natural language processing*, pages 1998–2022.

Iqra Ali, Talia Tseriotou, Guy Dvir, Callum Chan, Yuxiang Zhou, Juan Antonio Lossio-Ventura, Ayal Klein, Aya Shamir, Dan Sayda, Anthony Hills, Aya Zirikly, Diana Inkpen, Dana Atzil-Slonim, and Maria Liakata. 2026. Overview of the clpsych 2026 shared task: Capturing and characterizing mental health changes through social media timeline dynamics. In *Proceedings of the 11th Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Anson Antony and Annika M. Schoene. 2025. Retrieval-enhanced mental health assessment: Capturing self-state dynamics from social media using in-context learning. In *Proceedings of CLPsych 2025*, pages 268–278.

Dana Atzil-Slonim. 2025. Multimodal intrapersonal and interpersonal dynamics (MIND): A transtheoretical coding manual.

Dana Atzil-Slonim. 2026. Leveraging theoretical and technological innovations to study the mechanisms that underlie therapeutic change in psychotherapy. In Louis G. Castonguay, Dana Atzil-Slonim, Michael Barkham, and Wolfgang Lutz, editors, *Practice-Based Evidence in the Psychological Therapies: Toward Policy Implications for Research, Training, and Clinical Guidelines*. Oxford University Press, New York.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, and 1 others. 2020. Language models are few-shot learners. In *Advances in Neural Information Processing Systems*, volume 33, pages 1877–1901.

Stevie Chancellor and Munmun De Choudhury. 2020. Methods in predictive techniques for mental health status on social media: A critical review. *npj Digital Medicine*, 3(1):43.

Glen Coppersmith, Mark Dredze, and Craig Harman. 2014. Quantifying mental health signals in twitter. In *Proceedings of the Workshop on Computational Linguistics and Clinical Psychology*, pages 51–60.

Munmun De Choudhury, Michael Gamon, Scott Counts, and Eric Horvitz. 2013. Predicting depression via social media. In *Proceedings of the International AAAI Conference on Web and Social Media*, volume 7, pages 128–137.

Gemma Team. 2025. Gemma 3 technical report. *arXiv preprint*.

Pengcheng He, Jianfeng Gao, and Weizhu Chen. 2023. DeBERTaV3: Improving DeBERTa using ELECTRA-style pre-training with gradient-disentangled embedding sharing. In *International Conference on Learning Representations*.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, and 1 others. 2020. Retrieval-augmented generation for knowledge-intensive NLP tasks. In *Advances in Neural Information Processing Systems*, volume 33, pages 9459–9474.

Yury A. Malkov and Dmitry A. Yashunin. 2018. Efficient and robust approximate nearest neighbor search using hierarchical navigable small world graphs. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 42(4):824–836.

Sewon Min, Xinxi Lyu, Ari Holtzman, Mikel Artetxe, Mike Lewis, Hannaneh Hajishirzi, and Luke Zettlemoyer. 2022. Rethinking the role of demonstrations: What makes in-context learning work? In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 11048–11064.

Zach Nussbaum, John X. Morris, Brandon Duderstadt, and Andriy Mulyar. 2024. Nomic embed: Training a reproducible long context text embedder. *arXiv preprint arXiv:2402.01613*.

Reid Pryzant, Dan Iter, Jerry Li, Yin Lee, Chenguang Zhu, and Michael Zeng. 2023. Automatic prompt optimization with "gradient descent" and beam search. In *Proceedings of the 2023 conference on empirical methods in natural language processing*, pages 7957–7968.

Qwen Team. 2025. Qwen3 technical report. *arXiv preprint*.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Talia Tseriotou, Jenny Chim, Ayal Klein, Aya Shamir, Guy Dvir, Iqra Ali, Cian Kennedy, Guneet Singh Kohli, Anthony Hills, Ayah Zirikly, Dana Atzil-Slonim, and Maria Liakata. 2025. Overview of the CLPsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 193–217, Albuquerque, New Mexico. Association for Computational Linguistics.

Ahmet Yavuz Uluslu, Andrianos Michail, and Simon Clematide. 2024. Utilizing large language models to identify evidence of suicidality risk through analysis of emotionally charged posts. In *Proceedings of CLPsych 2024*, pages 264–269.

Chengrun Yang, Xuezhi Wang, Yifeng Lu, Hanxiao Liu, Quoc V Le, Denny Zhou, and Xinyun Chen. 2023. Large language models as optimizers. In *The Twelfth International Conference on Learning Representations*.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, and 1 others. 2023. Judging LLM-as-a-Judge with MT-bench and chatbot arena. In *Advances in Neural Information Processing Systems*, volume 36.

Ayah Zirikly, Philip Resnik, Özlem Uzuner, and Kristy Hollingshead. 2019. CLPsych 2019 shared task: Predicting the degree of suicide risk in Reddit posts. In *Proceedings of the Sixth Workshop on Computational Linguistics and Clinical Psychology*, pages 24–33.

A DeepSeek-R1 70B Model Comparison

Table 4 compares the Task 3.1 agentic pipeline (Submission 1 architecture) using Gemma 4 31B (submitted) vs. DeepSeek-R1 70B (post-deadline experiment) on the full 74-sequence training set. Metrics are from a local proxy evaluator; official CS/CT/BERTScore were not computed for the DeepSeek run.

Metric	Gemma 4 31B	DeepSeek 70B
Summary quality (proxy)		
ROUGE-L	**0.285**	0.277
Unigram F1	**0.523**	0.513
Mean word count	262.4	238.4
Structural compliance		
ABCD tag coverage	1.000	1.000
Identity correct	100%	100%
Direction stated	98.6%	**100%**
Over 350 words	0%	0%
Pipeline reliability		
Tag repair needed	—	27 / 74
JSON parse failures	—	4 / 74
Infrastructure		
Hardware	3× A40	2× L40S
Runtime (74 seq.)	∼**38 min**	∼5.5 hours
CPU offload	No	24%

Table 4: Gemma 4 31B vs. DeepSeek-R1 70B on the Task 3.1 agentic pipeline (training set, 74 sequences). The 70B model does not improve proxy metrics despite 8× runtime.

CUNY at CLPsych 2026: A Pipeline Approach to Classification and Summarization of Mental Health Changes

Amirmohammad Ziaei Bideh[†], **Shameed Charlomar Job**[*‡], **Ava Yahyapour**[*†], **Alla Rozovskaya**[†‡]
[†]Computer Science Department, CUNY Graduate Center
[‡]Linguistics Department, CUNY Graduate Center
amirmohammad.ziaeibideh69@cuny.edu

Abstract

We describe our submission to the CLPsych 2026 Shared Task on capturing and characterizing mental health changes through social media timeline dynamics. To infer the dominant self-states in posts (Tasks 1.1 and 1.2), we ensemble in-context learning of three open-weight large language models using majority voting. For predicting moments of change in a timeline (Task 2), we train supervised classifiers on features derived from Task 1.1 predictions. To summarize the patterns of mood dynamics and their progression over time within a timeline (Task 3.1), we augment in-context example labels predicted by upstream systems (Tasks 1.1, 1.2, and 2), yielding performance gains over zero-shot and unaugmented in-context learning baselines. Our submission ranked first on Task 1.1, fourth on Task 1.2, fourth on Task 2, and third on Task 3.1.[1]

1 Introduction

Mental health conditions affect a significant portion of the global population (World Health Organization, 2013; National Institute of Mental Health (NIMH), 2024), creating a need for scalable tools to monitor individuals' psychological states over time. Social media platforms offer longitudinal data for tracking how mental states evolve in response to life events and social interactions (Tsakalidis et al., 2022), and large language models (LLMs) have shown strong potential in supporting such analysis (Yang et al., 2024; Chan et al., 2025). Recent practice-oriented research further demonstrates how multimodal analysis and AI can uncover the intrapersonal and interpersonal dynamics underlying therapeutic change (Atzil-Slonim, 2026). The CLPsych 2026 shared task (Ali et al., 2026) addresses this need by asking participants to track and characterize how users' mental states evolve across longitudinal Reddit timelines.

This paper describes our submission to the CLPsych 2026 shared task (Ali et al., 2026). Our best submission for Task 1.1 uses an ensemble of seven LLM predictions across three model backbones with subelement-level In-Context Learning (ICL), where annotated training examples are included directly in the prompt to guide predictions. For Task 1.2, our best submission ensembles five predictions using ICL and Retrieval-Augmented Generation (RAG), which retrieves the most semantically similar training posts as in-context demonstrations. For Task 2, we train supervised classifiers on self-state features derived from upstream task predictions, using a Support Vector Machine (SVM) for Switch detection and a Random Forest (RF) for Escalation detection. For Task 3.1, our best submission uses label-augmented ICL, enriching prompts with predicted ABCD subelement and Moment of Change (MoC) labels from upstream tasks. For Task 3.2, we apply a batch-and-merge pipeline to identify recurrent dynamic signatures of improvement and deterioration across timelines. Our submission ranked **first** on Task 1.1, **fourth** on Task 1.2, **fourth** on Task 2, and **third** on Task 3.1.

The contributions of our work are as follows:

1. We show that LLM ensembling via majority voting substantially outperforms single-model baselines for subelement classification (Task 1.1), and that expanding the ensemble beyond five members further improves subelement classification but slightly hurts presence scoring (Task 1.2), suggesting diminishing returns for larger ensembles on ordinal prediction tasks.

2. We show that escalation is easier to predict than switch, and traditional supervised classifiers trained on LLM-derived presence scores are competitive for MoC detection (Task 2).

[*]Equal contribution.
[1]The source code for the experiments is available at https://github.com/amirzia/clpsych26-cuny.

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 441–457
July 4, 2026 ©2026 Association for Computational Linguistics

3. We find that propagating predicted self-state labels from upstream tasks into downstream prompts with larger models yields consistent gains in summary quality over zero-shot prompting with smaller models and standard ICL baselines (Task 3.1).

2 Shared Task Description

The shared task is grounded in the Multimodal Intrapersonal and Interpersonal Dynamics (MIND) framework (Atzil-Slonim, 2025). The framework includes widely used psychotherapy constructs on the patient mental state referred to as self-state. A self-state is a dominant mode of experience and consists of a combination of Affect, Behavior, Cognition, and Desire (ABCD) components, their adaptivity level and their more fine-grained subcategorization into subelements (Atzil-Slonim, 2025).

Task 1.1 aims to identify which predefined ABCD subelements are expressed in a post and how they combine into *adaptive* and *maladaptive* self-states, referred to as the two *valences* of a self-state. Task 1.2 requires quantifying the degree to which each identified self-state is present in the post on a 1-5 scale (referred to as the presence score). Task 2 involves detecting clinically meaningful MoC within a user timeline,[2] identifying Switches (sudden change in well-being) and Escalations (gradual intensification of mood) (Tsakalidis et al., 2022). Task 3.1 involves generating a structured summary describing the progression of self-state dynamics within a sequence of posts surrounding an identified change event. Task 3.2 aims to identify recurrent dynamic signatures of improvement and deterioration that recur across multiple sequences and individuals.

Dataset. The training set contains Reddit timelines from 30 users, annotated with self-states according to the MIND framework. Figure 3 shows an anonymized excerpt of a sample timeline. The training set also provides gold summaries for sequences, describing the patterns of self-state dynamics. A sequence is a chronologically ordered list of posts within a timeline that culminates in an MoC. We randomly hold out 10 training timelines as our validation set for selecting the best models for submission. The 20 timelines are used for training and providing in-context examples.

[2] A *timeline* is a chronologically ordered collection of posts authored by a single user.

3 Related Work

Previous editions of the CLPsych shared task have attracted a wide range of system submissions. In CLPsych 2022 (Tsakalidis et al., 2022), team `BLUE` (Bucur et al., 2022) experimented with several text representation methods, and their best system consisted of an ensemble of machine learning (ML) classifiers. Team `WResearch` (Bayram and Benhiba, 2022) adopted a pipeline approach in which pre-trained BERT (Devlin et al., 2019) was used to compute emotion and sentiment scores that were passed as input features to downstream ML models. Team `UoS` (Azim et al., 2022) achieved competitive results using a bidirectional long short-term memory (Bi-LSTM) network for mood change prediction and suicide risk level assessment.

The following year's edition, CLPsych 2025 (Tseriotou et al., 2025), introduced more challenging subtasks such as evidence span detection and summarization. Team `uOttawa` (Chan et al., 2025) explored various prompt engineering strategies on top of a 70B-parameter LLM and obtained the best score on self-state identification. Team `BULUSI` (Ravenda et al., 2025) achieved strong results by combining an ensemble with an optimization step on top of LLM predictions. Finally, team `BLUE` (Sandu et al., 2025) obtained competitive performance on summarization through zero-shot prompting of open-weight LLMs.

4 Methodology

This section presents our approaches, which integrate findings from the CLPsych 2025 shared task, as we enhance and refine our strategies.

4.1 Tasks 1.1 and 1.2

We adopt a joint prediction setup in which an LLM is tasked with predicting both the subelements and their presence scores in a single pass. The default system prompt (Figure 4) contains a detailed description of the MIND framework, the definitions of self-states, the characteristics of each subelement, and the criteria for assigning presence scores. We compare several prompting techniques.

Zero-shot prompting. We use the default system prompt and pass the content of the post to be labeled in the user message.

Post-level In-Context Learning (ICL). Here, k full training posts selected uniformly at random, and their gold subelement annotations are included in the prompt. This exposes the LLM to the surrounding context of each subelement and to the

relationships between subelements within a post. A drawback is that coverage of all subelements is not guaranteed, and rare subelements may go unrepresented among the in-context examples.

Post-level ICL with RAG. Identical to post-level ICL, but the k in-context posts are retrieved by cosine similarity to the test post. Posts are encoded as the L2-normalized `CLS` embedding from `BAAI/bge-large-en-v1.5` (Xiao et al., 2023), truncated to 512 tokens.

Subelement-level ICL. In the subelement-level variant of ICL, we append k examples to the definition of each subelement in the system prompt. Each example is a relevant span from a training post that serves as evidence for the corresponding subelement. Note that, in this setting, we do not include the full post. Moreover, the k examples for a given subelement may come from different training posts, offering a more diverse view of how the subelement is expressed.

Ensemble. To reduce noise from any single prediction, we aggregate the outputs of multiple independent LLM runs via majority voting.

4.2 Task 2

We train separate supervised classifiers for switch and escalation changes using feature sets composed of the subelements and presence scores predicted in Tasks 1.1 and 1.2. Each classifier receives a fixed-size window of posts centered on a target post. The window includes both preceding and following posts; we denote the window that includes the following posts as having foresight. Each post in a sequence is labeled with predictions from the best submissions for Tasks 1.1 and 1.2. We experiment with the following features: the predicted presence for each valence, the absolute difference between presence per valence of the target and subsequent post, count of subelements per valence, and post index. We compare two machine learning algorithms: Support Vector Machine (SVM), and Random Forest. Classifiers are trained on 20 posts during validation (all 30 posts are used during test) and are tuned via grid search (Appendix B.2).

4.3 Task 3.1

We adopt an LLM prompting approach for Task 3.1. The system prompt that we use for the task (Figure 8) contains a detailed description of the MIND framework, the definitions of switch and escalation, and the required summarization aspects. We also experimented with a shortened version of this prompt (Figure 9) but observed negligible difference in performance, so all reported results use the longer prompt. The user prompt contains the chronologically ordered post contents of the test sequence. We compare the following approaches:

Zero-shot. The LLM produces the summary directly from the task description and the post contents, with no in-context examples.

ICL. The system prompt is augmented with k in-context examples. Each example consists of the post contents of a training sequence followed by the corresponding gold summary.

Label-augmented ICL. A pipeline-style extension of ICL in which subelement and change labels (switch or escalation) are included alongside the post contents. We consider two variants: (i) augmenting only the in-context examples with their gold labels, and (ii) additionally augmenting the test posts with predicted labels from our Task 1.1 and Task 2 systems. Figure 1 illustrates the full pipeline.

Summary of summaries. In this method, a single LLM first summarizes each post individually and then summarizes the sequence from those per-post summaries.

4.4 Task 3.2

Before prompting the LLM to identify recurrent signatures of improvement or deterioration, we filter the 74 gold training summaries via exact string matching, yielding 56 deterioration and 51 improvement sequences. These are passed to the LLM in batches of 10 to produce partial signatures, which are then merged in a final step that identifies patterns common across batches.

5 Results

This section provides the experimental results. We use the following open-weight LLMs for prompting: google/gemma-3-27b-it (`gemma`) (Gemma Team, 2025); Qwen/Qwen3.5-27B (`qwen`) (Qwen Team, 2026); and openai/gpt-oss-120b (`gpt`) (OpenAI, 2025). See Appendix A for the setup.

5.1 Tasks 1.1 and 1.2

Validation results across these dimensions are summarized in Table 1. On Task 1.1, ICL improves over zero-shot for `qwen` and `gemma` but not for `gpt`. For the ensemble, increasing k generally yields gains, unlike for individual models, and subelement-level ICL outperforms the other approaches. On Task 1.2, `qwen` attains substantially higher RMSE on presence scores than the other



Figure 1: Label-augmented ICL pipeline for Task 3.1. Post sequences are processed through Task 1.1 to produce subelements and through Task 2 to produce MoC labels. Both label sets enrich the prompt fed to the LLM. Submission 3 enriches only the in-context examples with gold labels. Submission 4 additionally enriches the test posts with predicted labels from Tasks 1.1 and 2 at inference time.

Method	k	qwen		gemma		gpt		Ensemble	
		F1↑	RMSE↓	F1↑	RMSE↓	F1↑	RMSE↓	F1↑	RMSE↓
Zero-shot	–	0.309	1.124	0.324	0.926	0.340	0.908	0.330	0.913
Subelement ICL	1	0.328	1.027	0.335	0.860	**0.343**	0.948	0.347	0.852
	2	**0.362**	1.057	0.341	0.860	0.326	0.948	0.361	0.861
	3	0.333	**0.998**	0.354	**0.831**	0.339	**0.888**	**0.366**	**0.787**
Post ICL	1	0.331	1.072	0.330	0.877	0.311	0.939	0.335	0.867
	2	0.334	1.103	0.348	0.867	0.297	0.963	0.337	0.880
	3	0.330	1.047	0.336	0.860	0.307	0.971	0.332	0.859
RAG	1	0.337	1.048	**0.368**	0.920	0.309	0.914	0.330	0.898
	2	0.325	1.070	0.326	0.858	0.313	0.955	0.333	0.903
	3	0.332	1.028	0.327	0.853	0.319	0.953	0.342	0.876

Table 1: Validation results on Tasks 1.1 and 1.2, averaged over 5 runs. k is the number of in-context examples.

models. The LLM exhibits a clear tendency to over-predict subelements, resulting in a high false positive rate. The validation set contains 292 present subelements (adaptive and maladaptive combined), whereas one of the gemma predictions includes 555.

The test results for our three submissions are reported in Table 2. **Submission 1** uses subelement-level ICL with $k = 3$ and gemma as the backbone. **Submission 2** ensembles 5 predictions from qwen and gemma. **Submission 3** ensembles 7 predictions drawn from qwen, gemma, and gpt. Refer to Appendix B.1 for more details about the ensemble members.

Findings. Ensembling improves Task 1.1 macro F1 from 0.416 to 0.431 (+3.6% relative) and reduces Task 1.2 RMSE from 1.047 to 0.997 (−4.78% relative) between **Submissions 1** and **2**, consistent with the view that aggregating across models and runs reduces variance from sampling noise and from the choice of in-context examples (Yang et al., 2023). **Submission 3**, which adds two more members and a third backbone, achieves the **best** Task 1.1 F1 among all CLPsych 2026 participants. For Task 1.2, however, expanding the ensemble from 5 to 7 members slightly hurts performance, likely because the output space is restricted to integers in $\{1, \ldots, 5\}$, leaving little headroom for additional members to contribute useful signal.

	Task 1.1 Macro F1 ↑	Task 1.2 RMSE ↓
Submission 1	0.416	1.047
Submission 2	<u>0.431</u>	**0.997**
Submission 3	**0.442**	<u>1.007</u>
Official baseline	0.247	1.424

Table 2: Test results on Tasks 1.1 (subelement-level macro F1) and 1.2 (RMSE). Submission 3 achieves the best F1 among CLPsych 2026 participants, and Submission 2 achieves the 4th-best RMSE. The official baseline is a one-shot approach with `LLaMA-3.1-8B-Instruct`.

5.2 Task 2

Submission 1[3] uses Random Forest classifiers with predicted Task 1.1 presence scores as the feature, with window size 1 for switch and 2 for escalation.

Submission 2 uses SVM classifiers and expands the feature set with the absolute difference in presence between consecutive posts and the post index,

[3]The training data was not fully used in this submission. We provide the correct evaluation on the validation set.

	Average Macro F1 ↑
Submission 1	0.279
Submission 2	0.472
Submission 3	**0.572**
Official baseline 1	0.272
Official baseline 2	0.365
Official baseline 3	**0.572**

Table 3: Test results on Task 2. Baseline 1 adopts a zero-shot approach using `LLaMA-3.1-8B-Instruct`. The second baseline follows a pipeline approach where the predicted labels from Task 1.1 baseline are used to compute the well-being score deterministically to predict moments of change. Baseline 3 finetunes TempoFormer (Tseriotou et al., 2024).

	CS ↑	CT ↓	RL ↑	BSR ↑
Submission 1	0.797	0.696	0.283	0.249
Submission 2	0.722	0.808	0.244	0.218
Submission 3	0.789	0.714	0.292	**0.295**
Submission 4*	**0.818**	**0.621**	**0.305**	-
Official baseline 1	0.763	0.753	0.255	0.226
Official baseline 2	0.767	0.745	0.269	0.235

Table 4: Test results on Task 3.1. CS refers to consistency, CT refers to contradiction, RL refers to ROUGE recall, and BSR refers to BERTScore recall. The first baseline follows a zero-shot strategy using the model `LlamA-3.1-8B`. The second baseline adopts a pipeline approach where the predictions from the top performing baselines from Task 1 and 2 are used to enrich the prompt context. *Submission 4 was made during the analysis phase of the competition.

and increases window sizes: switch uses a window size 2 and escalation 3.

Submission 3 uses a window size 3 and a larger feature set than the previous submission. For both the switch and escalation model, we create a set of six features per post: presence, absolute presence difference, and subelement count for each valence. While the switch model has a window size 3, we remove foresight so that it does not include posts succeeding our target. This switch model also uses post index as an additional feature. Our validation results are reported in Table 12. The test results for our three submissions are reported in Table 3.

Findings. Our best system (Submission 3) achieved a combined F_1 of 0.572, placing us 4th in Task 2 ranking. Across submissions, escalation was consistently easier to predict than switch. Adding foresight for escalation and refining the window configuration in Submission 3 provided a further improvement, largely driven by a large gain in escalation F_1 (0.585 $\rightarrow$ 0.714 post-level).

5.3 Task 3.1

Validation results are reported in Table 10. ICL performance generally improves with k across all three backbones. Test results are reported in Table 4. **Submission 1** uses plain ICL with $k = 2$ and `gpt` as the backbone. **Submission 2** uses the summary-of-summaries approach with the same backbone, which degrades performance across all metrics: collapsing each post into an intermediate summary appears to discard the fine-grained signal needed to characterize cross-post dynamics. **Submission 3** is the label-augmented ICL variant, in which the in-context examples carry their gold subelements and change labels. **Submission 4** additionally augments the test posts with predicted labels from Tasks 1.1 and 2.

Findings. Submission 4 yields the best result on three of the four metrics among our submissions confirming that the pipeline signal is useful at inference time as well. Moreover, Submissions 1, 3, and 4 outperform both official baselines across all four metrics, demonstrating that larger models with an ICL approach consistently outperform smaller models in a zero-shot setting.

5.4 Task 3.2

We use `gpt` as the backbone LLM. The generated signatures are shown in Section C. Our submission achieved a fit score of 0, a recurrence score of 0, and a specificity score of 0.25. Since this task was evaluated manually by the organizers and gold annotations are not available, it is challenging to provide findings for this task.

6 Conclusion

We presented our submissions to the CLPsych 2026 Shared Task on analyzing self-state dynamics in longitudinal Reddit timelines. Our ensembling approach for Task 1.1 achieved the best performance in subelement classification among all participants. Our pipeline approach for Task 2, which used predictions from Task 1, yielded our strongest result on this task and ranked fourth. The label-augmented in-context learning approach for Task 3.1 ranked third in the competition. Overall, our results indicate that propagating predictions from upstream tasks leads to consistent gains on downstream tasks.

Limitations

Our work has several limitations. First, in our experiments, we used large LLMs that might not be accessible to everyone. This hinders the reproducibility and usage of the methods in resource-constrained environments. One solution is to use quantized models, which offer a reduced memory footprint at the cost of a slight degradation in performance. Second, the size of the datasets is relatively small and limited to 30 users in the training set and 10 users in the test set. Therefore, the conclusions from our paper might not be generalizable to the mental health domain in general. Third, the users in this study are Reddit users, who are not representative of the general population; to further extend the scope of the work, data from other social media platforms could be included. Finally, our submission to Task 3.2 received fit and recurrence scores of 0, suggesting that the batch-and-merge pipeline did not capture meaningful recurrent signatures; further investigation of the filtering and merging steps is needed.

Ethical Considerations

Due to the sensitive nature of mental health data, we stored the dataset in secure, firewall-protected servers. We used only open-weight LLMs and served them locally. We did not use any commercial, closed-weight LLMs in order to preserve the confidentiality of the data. Furthermore, our systems are designed as a support tool to help professional mental health providers and should not be considered a replacement for certified professionals.

Acknowledgment

We thank Asmaa El Hansali for the help with the project and the anonymous reviewers for their insightful comments.

References

Iqra Ali, Talia Tseriotou, Guy Dvir, Callum Chan, Yuxiang Zhou, Juan Antonio Lossio-Ventura, Ayal Klein, Aya Shamir, Dan Sayda, Anthony Hills, Ayah Zirikly, Diana Inkpen, Dana Atzil-Slonim, and Maria Liakata. 2026. Overview of the CLPsych 2026 shared task: Capturing and characterizing mental health changes through social media timeline dynamics. In *Proceedings of the 11th Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Dana Atzil-Slonim. 2025. Multimodal intrapersonal and interpersonal dynamics (MIND): A transtheoretical coding manual.

Dana Atzil-Slonim. 2026. Leveraging theoretical and technological innovations to study the mechanisms that underlie therapeutic change in psychotherapy. In Louis G. Castonguay, Dana Atzil-Slonim, Michael Barkham, and Wolfgang Lutz, editors, *Practice-Based Evidence in the Psychological Therapies: Toward Policy Implications for Research, Training, and Clinical Guidelines*. Oxford University Press, New York.

Tayyaba Azim, Loitongbam Gyanendro Singh, and Stuart E. Middleton. 2022. Detecting moments of change and suicidal risks in longitudinal user texts using multi-task learning. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 213–218, Seattle, USA. Association for Computational Linguistics.

Ulya Bayram and Lamia Benhiba. 2022. Emotionally-informed models for detecting moments of change and suicide risk levels in longitudinal social media data. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 219–225, Seattle, USA. Association for Computational Linguistics.

Ana-Maria Bucur, Hyewon Jang, and Farhana Ferdousi Liza. 2022. Capturing changes in mood over time in longitudinal data using ensemble methodologies. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 205–212.

Callum Chan, Sunveer Khunkhun, Diana Inkpen, and Juan Antonio Lossio-Ventura. 2025. Prompt engineering for capturing dynamic mental health self-states from social media posts. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 256–267, Albuquerque, New Mexico. Association for Computational Linguistics.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1 (long and short papers)*, pages 4171–4186.

Gemma Team. 2025. Gemma 3 technical report. *Preprint*, arXiv:2503.19786.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. 2023. Efficient memory management for large language model serving with PagedAttention. In *Proceedings of the ACM SIGOPS 29th Symposium on Operating Systems Principles*.

National Institute of Mental Health (NIMH). 2024. Mental illness statistics. https://www.nimh.nih.gov/health/statistics/mental-illness. Accessed: 2026-04-27.

OpenAI. 2025. gpt-oss-120b & gpt-oss-20b model card. *Preprint*, arXiv:2508.10925.

Qwen Team. 2026. Qwen3.5: Towards native multimodal agents.

Federico Ravenda, Fawzia-Zehra Kara-Isitt, Stephen Swift, Antonietta Mira, and Andrea Raballo. 2025. From evidence mining to meta-prediction: a gradient of methodologies for task-specific challenges in psychological assessment. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 242–248, Albuquerque, New Mexico. Association for Computational Linguistics.

Anastasia Sandu, Teodor Mihailescu, Ana Sabina Uban, and Ana-Maria Bucur. 2025. Capturing the dynamics of mental well-being: Adaptive and maladaptive states in social media. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 225–234, Albuquerque, New Mexico. Association for Computational Linguistics.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Talia Tseriotou, Jenny Chim, Ayal Klein, Aya Shamir, Guy Dvir, Iqra Ali, Cian Kennedy, Guneet Singh Kohli, Anthony Hills, Ayah Zirikly, Dana Atzil-Slonim, and Maria Liakata. 2025. Overview of the CLPsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 193–217, Albuquerque, New Mexico. Association for Computational Linguistics.

Talia Tseriotou, Adam Tsakalidis, and Maria Liakata. 2024. TempoFormer: A transformer for temporally-aware representations in change detection. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 19635–19653.

World Health Organization. 2013. *Mental Health Action Plan 2013–2020*. World Health Organization, Geneva, Switzerland.

Shitao Xiao, Zheng Liu, Peitian Zhang, and Niklas Muennighoff. 2023. C-pack: Packaged resources to advance general chinese embedding. *Preprint*, arXiv:2309.07597.

Han Yang, Mingchen Li, Huixue Zhou, Yongkang Xiao, Qian Fang, and Rui Zhang. 2023. One LLM is not enough: Harnessing the power of ensemble learning for medical question answering. *medRxiv*.

Kailai Yang, Tianlin Zhang, Ziyan Kuang, Qianqian Xie, Jimin Huang, and Sophia Ananiadou. 2024. MentaLLaMA: Interpretable mental health analysis on social media with large language models. In *Proceedings of the ACM Web Conference 2024*, pages 4489–4500, Singapore. ACM.

A Experimental Setup

All experiments and inference are conducted on secure internal servers to protect the privacy of the individuals represented in the dataset. Our system is equipped with 8 NVIDIA A40 GPUs (48 GB VRAM each) and 40 CPU cores at 2.30 GHz. We serve all LLMs locally with vLLM (Kwon et al., 2023), a high-throughput inference engine for large language models.

Figure 3 presents an example timeline in the training dataset.

B Additional Results

This section provides additional experiments and results.

B.1 Task 1.1 and 1.2 submission details

Tables 5 and 6 list the ensemble members for Submissions 2 and 3 in Task 1.1 and 1.2, respectively. All members use $k = 3$.

#	Approach	LLM
1	Post-level ICL with RAG	gemma
2	Post-level ICL	gemma
3	Subelement-level ICL	gemma
4	Post-level ICL	qwen
5	Subelement-level ICL	qwen

Table 5: Ensemble members for Submission 2 in Task 1.1 and 1.2. All members use $k = 3$.

B.2 Task 2 experiments on the validation set

Training While using the same training and validation set from Task 1, our model predicts F_1 scores generated by gemma and qwen across four prompting strategies—zero-shot (3 results from the gemma model and 2 results from qwen), post-level ICL (6 from each model), subelement-level ICL (6 from each model), and post-level RAG (6 from each model)— yielding 41 training results. We evaluated four feature sets of increasing complexity

#	Approach	LLM
1	Post-level ICL with RAG	gemma
2	Post-level ICL	gemma
3	Subelement-level ICL	gemma
4	Post-level ICL	qwen
5	Subelement-level ICL	qwen
6	Post-level ICL	gpt
7	Subelement-level ICL	gpt

Table 6: Ensemble members for Submission 3 in Task 1.1 and 1.2. All members use $k = 3$.

(see Figures 2b, 2d, and 2f): FS1 comprises adaptive and maladaptive presence scores with their absolute inter-post deltas; FS2 adds the post index; FS3 adds per-post element counts; and FS4 combines FS3 with the post index. For both switch conditions (with foresight and without foresight), F_1 improved monotonically with feature set complexity, with FS4 yielding averages of 0.463 and 0.472 respectively. For escalation, FS3 produced a substantially stronger average F_1 of 0.706 against 0.538 and 0.541 for FS1 and FS2, and was therefore selected.

We also evaluated window sizes w_0–w_3 (see Figures 2a, 2c, and 2e). Performance increased consistently with window size across all tasks, with w_3 achieving mean F_1 scores of 0.422, 0.443, and 0.607 for switch with foresight, switch without foresight, and escalation, respectively; w_3 was therefore adopted. For the switch task, removing foresight—restricting the window to prior posts only—produced stronger predictions (F_1 0.490 vs. 0.472 at FS4, w_3), and this formulation was retained for the final system. The best feature set configurations, FS4 for switch and FS3 for escalation, yield F_1 scores of 0.490 and 0.714, respectively.

Sub.	Task	Model	Hyperparam.
2	Escalation Switch	SVM	`C=1, kernel='rbf', gamma='scale'`
3	Escalation	RF	`n_est=200, depth=5, feat='log2', split=5`
3	Switch	SVM	`C=1, kernel='rbf', gamma='scale'`

Table 7: Task 2 hyperparameters by submission and change type. RF = RandomForestClassifier; n_est = n_estimators, feat = max_features; split = min_samples_split; depth = max_depth

B.3 Task 3.1: zero-shot vs. summary of summaries

We first tested a simple zero-shot prompt (Figure 6) in which the model receives the raw post texts and a brief instruction to generate a structured ABCD summary. This served as our baseline for both models.

For this section, we evaluate our approach on the Task 3.1 training set (74 sequences) using two language models: LLaMA 3.2 3B Instruct and Gemma 2 9B Instruct, both loaded with 4-bit quantization (NF4).

Sequential pipeline. Motivated by the winning system of Sandu et al. (2025) (BLUE team), we implement a two-step sequential pipeline. In the first step, the model generates a short post-level summary for each individual post describing the interplay between adaptive and maladaptive self-states. In the second step, these post-level summaries – rather than the raw post texts – are fed to the model to produce the final sequence summary. The prompt used in the second step is shown in Figure 7.

Results. Table 11 show the evaluation results across all configurations. The sequential pipeline consistently improved consistency over the zero-shot baseline for both models, with Gemma 2 9B achieving the best mean CS of 0.7382 ± 0.0068 across three runs.

Sub.	Label	Prec	Rec	F_1
2	Switch	0.500	0.381	0.432
	Escalation	0.591	0.542	0.565
	Macro F_1			*0.499*
3	Switch	0.326	0.714	0.448
	Escalation	0.625	0.833	0.714
	Macro F_1			***0.581***

Table 8: Task 2: Post-level precision, recall, and F_1 by submission.

Sub.	Label	Prec	Rec	F_1
2	Switch	0.450	0.342	0.349
	Escalation	0.675	0.508	0.542
	Macro F_1			*0.446*
3	Switch	0.353	0.592	0.416
	Escalation	0.714	0.721	0.709
	Macro F_1			***0.563***

Table 9: Task 2: Timeline-level precision, recall, and F_1 (macro-averaged over 10 timelines) by submission.

B.4 Task 3.1 results on validation set

In addition to the approaches we discussed in the main text, we implement the following approaches:

LLM as a judge. Three independent ICL summaries are generated by `qwen`, `gemma`, and `gpt`. A separate LLM (`gpt`) then selects the best of the three.

LLM as an aggregator. Same setup as the judge, except that the aggregator LLM is asked to produce a new summary that draws on the three candidates rather than selecting one of them.

The results of the all approaches are reported in Table 10.

C Task 3.2 Recurrent Signatures

Here is the detected recurrent signatures of change by our method:

Signature of Deterioration. The recurrent signature of deterioration is characterized by a shift from adaptive self-states marked by (C-S) and (D) to maladaptive self-states dominated by (A), (C-S), (C-O), and (D). Initially, adaptive self-states are present, often characterized by (A) and (D), but these are gradually overshadowed by maladaptive states. The maladaptive states intensify (A), (C-S), (C-O), and (D) mutually reinforcing each other, culminating in a sense of hopelessness and despair.

Signature of Improvement. The recurrent signature of improvement is characterized by a shift from maladaptive self-criticism (C-S) and depressive affect (A) to adaptive self-compassion (C-S) and content affect (A). This shift involves maladaptive self-neglect behaviors (B-S) being overshadowed by relating behaviors (B-O) and a strengthened desire for connection (D) mutually reinforcing adaptive self-compassion (C-S).

D Dataset

Figure 3 presents an example timeline in the training dataset.

E Prompts

Figures 4, 6, 7, 8, and 9 show the system prompts we used in our approaches.

Model	k	CS ↑	CT ↓	RL ↑	BSR ↑
qwen	1	75.40	76.96	25.47	28.63
	2	75.95	75.93	26.15	30.11
	3	76.20	75.33	27.45	31.49
gpt	1	77.88	70.60	27.90	27.43
	2	79.68	**66.14**	28.56	26.59
	3	**80.56**	67.71	28.59	27.85
gemma	1	75.23	75.32	26.40	31.59
	2	75.83	73.09	28.51	33.41
	3	74.78	75.16	**28.84**	**34.10**
aggregate	1	79.96	70.26	27.82	26.59
	2	78.61	69.89	28.56	26.57
	3	78.38	71.01	28.36	27.39
judge	1	76.01	72.50	27.19	29.34
	2	76.58	73.10	27.23	28.37
	3	77.74	71.86	27.47	27.22
simple-prompt	1	77.99	69.75	28.09	27.37
	2	77.73	71.70	28.03	26.60
	3	79.43	68.45	28.50	27.77

Table 10: Average CS (consistency), CT (contradiction), RL (ROUGE recall), and BSR (BERTScore recall) over 4 independent runs on the validation data. All the numbers are in percentages. The first three models represent ICL methods with different LLMs. In `aggregate` (LLM as an aggregator) and `judge` (LLM as a judge), `gpt` uses the predicitons form the first three models. The `short-prompt` model is ICL with `gpt` as the backbone but with a shorter prompt (Figure 9). Ensemble methods for summary generation degrade the performance of ICL methods.

Configuration	**Model**	**CS ↑**	**CT ↓**	**ROUGE-L ↑**
Zero-shot baseline	LLaMA 3.2 3B	0.7152	0.6233	0.1502
	Gemma 2 9B	0.7086	0.7920	0.1837
Sequential pipeline	LLaMA 3.2 3B – Run 1	0.7275	0.7187	0.2135
	LLaMA 3.2 3B – Run 2	0.7279	0.6979	0.2117
	LLaMA 3.2 3B – Run 3	0.7202	0.7106	0.2076
	LLaMA mean ± std	$\mathbf{0.7252 \pm 0.0040}$	–	–
Sequential pipeline	Gemma 2 9B – Run 1	0.7408	0.7644	0.2006
	Gemma 2 9B – Run 2	0.7304	0.7463	0.1900
	Gemma 2 9B – Run 3	0.7433	0.7674	0.1906
	Gemma mean ± std	$\mathbf{0.7382 \pm 0.0068}$	–	–

Table 11: Task 3.1 Evaluation Results on Training Set (74 sequences).

	Post-Level			**Timeline-Level**			
	Switch F1	Esc. F1	Macro F1	Switch F1	Esc. F1	Macro F1	Combined F1 ↑
Submission 1	0.304	0.588	0.446	0.239	0.480	0.359	0.403
Submission 2	0.346	0.507	0.426	0.344	0.319	0.331	0.379
Submission 3	**0.510**	**0.791**	**0.650**	**0.559**	**0.697**	**0.628**	**0.639**

Table 12: Validation results on Task 2. Post-level and timeline-level scores are reported per label and as macro F1; the combined F1 is the ranking metric.



(a) Window size effect.



(b) Feature set effect.

Switch with Foresight (AS)



(c) Window size effect.



(d) Feature set effect.

Switch without Foresight (BS)



(e) Window size effect (w0 not evaluated).



(f) Feature set effect (FS4 not evaluated).

Escalation (ESC)

Figure 2: Mean F1 scores per window size (left column) and feature set (right column) for each task. FS1: presence + absolute deltas; FS2: FS1 + Post Index; FS3: FS1 + count features; FS4: FS3 + Post Index.

```
{
  "timeline_id": "7d9d2e0e0a",
  "posts": [
    {
      "post_index": 1,
      "post_id": "a33649e870",
      "date": "01-01-2020, 01:02:03",
      "Switch": "0",
      "Escalation": "E",
      "post": "I'm tired. [REMOVED]",
      "Well-being": 4,
      "evidence": {
        "adaptive-state": {
          "B-O": {
            "Category": "(1) Relating behavior",
            "highlighted_evidence": "[REMOVED]"
          },
          "Presence": 2
        },
        "maladaptive-state": {
          "A": {
            "Category": "(4) Depressed, despair, hopeless",
            "highlighted_evidence": "[REMOVED]"
          },
          "B-S": {
            "Category": "(2) Self harm, neglect and avoidance",
            "highlighted_evidence": "[REMOVED]"
          },
          "Presence": 5
        }
      }
    },
    {
      "post_index": 2,
      "post_id": "7f22000b69",
      "date": "01-01-2021, 01:02:03",
      "Switch": "S",
      "Escalation": "E",
      "post": "I'm tired of being alone [REMOVED]",
      "Well-being": 1,
      "evidence": {
        "adaptive-state": {
          "C-O": {
            "Category": "(1) Perception of the other as related",
            "highlighted_evidence": "[REMOVED]"
          },
          "Presence": 2
        },
        "maladaptive-state": {
          "A": {
            "Category": "(4) Depressed, despair, hopeless",
            "highlighted_evidence": "[REMOVED]"
          },
          "Presence": 5
        }
      }
    }
  ]
}
```


Figure 3: A sample timeline data.

System Prompt

```
## Task:
Your task is to identify adaptive and maladaptive self-states from a reddit post. A post can contain zero or more adaptive and maladaptive self-
↪ states.

### Definitions
Self-states are conceptualized as structured combinations of 6 elements: Affect (A), Behavior of the self with the others (B-O), Behavior of the
↪ self toward the self (B-S), Cognition of the others (C-O), Cognition of the self (C-S), and Desire (D). Each present element has exactly one
↪ subelement. The subelements are the specific manifestations of the elements in the post. Here are the definitions of the elements and their
↪ subelements. The percentage of subelements across all posts in the training data is provided in parentheses:
- *Affect* (A): Emotional tone or mood.
    - Adaptive subelements:
        1. Calm / laid back (0.60%)
        2. Sad, emotional pain, grieving (5.36%)
        3. Content, happy, joy, hopeful (8.33%)
        4. Vigor / energetic (0.60%)
        5. Justifiable anger/ assertive anger, justifiable outrage (1.19%)
        6. Proud (4.17%)
        7. Feeling loved, belong (0.00%)
    - Maladaptive subelements:
        1. Anxious/ fearful/ tense (16.67%)
        2. Depressed, despair, hopeless (34.52%)
        3. Mania (0.60%)
        4. Apathic, don't care, blunted (0.00%)
        5. Angry (aggression), disgust, contempt (4.76%)
        6. Ashamed, guilty (4.76%)
        7. Feel lonely (4.76%)
- *Behavior of the self with the others* (B-O): The writer's main behavior(s) toward the others.
    - Adaptive subelements:
        1. Relating behavior (48.21%)
        2. Autonomous or adaptive control behavior
    - Maladaptive subelements:
        1. Fight or flight behavior (13.69%)
        2. Over-controlled or controlling behavior
- *Behavior toward the self* (B-S): The writer's main behavior(s) toward the self.
    - Adaptive subelements:
        1. Self care and improvement (34.52%)
    - Maladaptive subelements:
        1. Self harm, neglect and avoidance (27.98%)
- *Cognition of the others* (C-O): The writer's main perceptions of the other.
    - Adaptive subelements:
        1. Perception of the other as related (19.05%)
        2. Perception of the other as facilitating autonomy needs (1.19%)
    - Maladaptive subelements:
        1. Perception of the other as detached or over attached (45.83%)
        2. Perception of the other as blocking autonomy needs (6.55%)
- *Cognition of the self* (C-S): The writer's main self-perceptions.
    - Adaptive subelements:
        1. Self-acceptance and compassion (25.00%)
    - Maladaptive subelements:
        1. Self criticism (57.14%)
- *Desire* (D): The writer's main desire, expectation, need, intention, or fear.
    - Adaptive subelements:
        1. Relatedness (24.40%)
        2. Autonomy and adaptive control (7.14%)
        3. Competence, self esteem, self-care (21.43%)
    - Maladaptive subelements:
        1. Expectation that relatedness needs will not be met (13.10%)
        2. Expectation that autonomy needs will not be met (4.76%)
        3. Expectation that competence needs will not be met (26.19%)

Self-state rating is the degree to which each identified self state is present in the post. It is an integer between 1 and 5 with the following
↪ definitions:
- 1 (Not present): The self state is not expressed in the post.
- 2 (Somewhat present): The self state is expressed, but plays a subtle, limited role in shaping the person's overall experience.
- 3 (Moderately present): The self state is clearly expressed and moderately contributes to the person's experience.
- 4 (Much present): The self state strongly influences and shapes the experience described in the post.
- 5 (Highly present): The self state strongly shapes and clearly defines the overall experience described in the post.
...
```

Figure 4: The system prompt for the Task 1.1 and 1.2.

System Prompt

```
...
Percentage of subelements across all posts in the training data is provided in parentheses:
- Affect (A):
    - Adaptive subelements: 1 (0.60%), 2 (5.36%), 3 (8.33%), 4 (0.60%), 5 (1.19%), 6 (4.17%), 7 (0.00%)
    - Maladaptive subelements: 1 (16.67%), 2 (34.52%), 3 (0.60%), 4 (0.00%), 5 (4.76%), 6 (4.76%), 7 (4.76%)
- Behavior of the self with the others (B-O):
    - Adaptive subelements: 1 (48.21%), 2 (4.76%)
    - Maladaptive subelements: 1 (13.69%), 2 (0.00%)
- Behavior toward the self (B-S):
    - Adaptive subelements: 1 (34.52%)
    - Maladaptive subelements: 1 (27.98%)
- Cognition of the others (C-O):
    - Adaptive subelements: 1 (19.05%), 2 (1.19%)
    - Maladaptive subelements: 1 (45.83%), 2 (6.55%)
- Cognition of the self (C-S):
    - Adaptive subelements: 1 (25.00%)
    - Maladaptive subelements: 1 (57.14%)
- Desire (D):
    - Adaptive subelements: 1 (24.40%), 2 (7.14%), 3 (21.43%)
    - Maladaptive subelements: 1 (13.10%), 2 (4.76%), 3 (26.19%)


### Output format
You need to output the presence and rating of the adaptive and maladaptive self-states as well as the subelements of the self-states. The
↪ subelement of non-existent self-states should be 0. Write your output in the following JSON format:
```json
{
    "adaptive_states": {
        "A": int (integer between 0 and 7),
        "B-O": int (integer between 0 and 2),
        "B-S": int (integer between 0 and 1),
        "C-O": int (integer between 0 and 2),
        "C-S": int (integer between 0 and 1),
        "D": int (integer between 0 and 3),
        "rating": int (integer between 1 and 5)
    },
    "maladaptive_states": {
        "A": int (integer between 0 and 7),
        "B-O": int (integer between 0 and 2),
        "B-S": int (integer between 0 and 1),
        "C-O": int (integer between 0 and 2),
        "C-S": int (integer between 0 and 1),
        "D": int (integer between 0 and 3),
        "rating": int (integer between 1 and 5)
    }
}
```
```

Figure 5: The system prompt for the Task 1.1 and 1.2. (Cont.)

System Prompt

```
...
SYSTEM_PROMPT = (
    'You are a clinical psychologist specialising in psychodynamic self-state analysis.\n'
    'Your task is to write a structured sequence summary for social media posts '
    'surrounding a mental health change event, grounded in the MIND (ABCD) framework.\n\n'
    'FRAMEWORK:\n'
    'Self-states combine: Affect (A), Behavior-Self (B-S), Behavior-Other (B-O), '
    'Cognition-Self (C-S), Cognition-Other (C-O), Desire (D).\n'
    'Each self-state is Adaptive or Maladaptive. Always abbreviate ABCD in parentheses.\n\n'
    'OUTPUT REQUIREMENTS (in this order, up to 350 words):\n'
    '1. CENTRAL THEME: Dominant ABCD pattern; direction of change '
    '(improvement/deterioration); change event type (Switch/Escalation/both); when it occurs.\n'
    '2. ADAPTIVE DYNAMICS: Presence trajectory and internal ABCD relational dynamics.\n'
    '3. MALADAPTIVE DYNAMICS: Same for the maladaptive state.\n'
    '4. CROSS-STATE DYNAMICS: Dominance, suppression, or dialogue between states.\n\n'
    'CONSTRAINTS: Do NOT print numeric presence scores. Max 350 words.'
)
...
```

Figure 6: Simple zero-shot system prompt for Task3.1 used as baseline for both LLaMA 3.2 3B and Gemma 2 9B.

System Prompt

```
...
{Step 1 -- Post-level prompt (applied to each post individually):}

{``Summarise the interplay between adaptive and maladaptive
self-states in this single post. Identify the dominant self-state
and describe how the core ABCD elements interact.
Write 2--3 sentences only.''}

{Step 2 -- Sequence-level prompt (applied to all post summaries):}

You are a clinical psychologist specialising in psychodynamic
self-state analysis. Your task is to write a structured sequence
summary grounded in the MIND (ABCD) framework.

{Change event definitions:}
SWITCH: sudden change in well-being between two consecutive posts.
ESCALATION: gradual intensification of mood across consecutive posts.

'OUTPUT REQUIREMENTS (up to 350 words, one paragraph):\n'
    '1. CENTRAL THEME: dominant ABCD pattern; direction
    (improvement/deterioration); change event type (Switch/Escalation)
    '2. ADAPTIVE DYNAMICS: presence trajectory; relational dynamics
    between ABCD subelements (MUST be described)
    '3. MALADAPTIVE DYNAMICS: same for the maladaptive state
    '4. CROSS-STATE DYNAMICS: dominance, suppression, reflective
    dialogue (MUST be described if present)
    'CONSTRAINTS: Do NOT print numeric presence scores. Max 350 words.'

{Constraints:} Use (A),(B-S),(B-O),(C-S),(C-O),(D) abbreviations.
No numeric scores. Start with:
{``The central psychological theme revolves around''}
...
```

Figure 7: Sequential pipeline prompt for Task3.1 following Sandu et al. (2025). Step 1 generates post-level summaries; Step 2 generates the sequence summary from those summaries rather than raw post texts.

System Prompt

```
You are a clinical psychologist specialising in psychodynamic self-state analysis.
Your task is to write a structured sequence summary grounded in the MIND (ABCD) framework.

# Framework
In the MIND framework, a self-state is defined as an identifiable unit characterized by specific combinations of Affect, Behavior (towards the
↪ self and others), Cognition (towards the self and others),and Desire (ABCD). An Adaptive self-state pertains to aspects of ABCD that are
↪ conducive to the fulfillment of basic desires/needs. A Maladaptive self-state pertains to aspects of ABCD that hinder the fulfillment of basic
↪ desires/needs. Each of the ABCD elements is operationalized through a set of subelements, representing distinct psychological expressions
↪ within each element:

1. *Affect* (A): Emotional tone or mood
    - Adaptive subelements: Calm/ laid back; Sad, emotional pain, grieving; Content, happy, joy, hopeful; Vigor / energetic; Justifiable anger/
↪ assertive anger, justifiable outrage; Proud; Feeling loved, belong
    - Maladaptive subelements: Anxious/ fearful/ tense; Depressed, despair, hopeless; Mania; Apathic, don't care, blunted; Angry (aggression),
↪ disgust, contempt; Ashamed, guilt; Feel lonely
2. *Behavior of the self with the others* (B-O): The writer's main behavior(s) toward the others
    - Adaptive subelements: Relating behavior; Autonomous or adaptive control behavior
    - Maladaptive subelements: Fight or flight behavior; Over-controlled or controlling behavior
3. *Behavior toward the self* (B-S): The writer's main behavior(s) toward the self
    - Adaptive subelements: Self care and improvement
    - Maladaptive subelements: Self harm, neglect and avoidance
4. *Cognition of the others* (C-O): The writer's main perceptions of the other
    - Adaptive subelements: Perception of the other as related; Perception of the other as facilitating autonomy needs
    - Maladaptive subelements: Perception of the other as detached or over attached; Perception of the other as blocking autonomy needs
5. *Cognition of the self* (C-S): The writer's main self-perceptions
    - Adaptive subelements: Self-acceptance and compassion
    - Maladaptive subelements: Self criticism
6. *Desire* (D): The writer's main desire, expectation, need, intention, or fear.
    - Adaptive subelements: Relatedness; Autonomy and adaptive control; Competence, self esteem, self-care
    - Maladaptive subelements: Expectation that relatedness needs will not be met; Expectation that autonomy needs will not be met; Expectation
↪ that competence needs will not be met

Given a chronologically ordered sequence of posts from a single individual (a timeline), there are two possible clinically meaningful moments of
↪ change:

- SWITCH:  A switch reflects a substantial and sudden change in well-being between two consecutive posts. The change may reflect either
↪ improvement or deterioration.
- ESCALATION:  An escalation refers to a gradual intensification of mood over a sequence of consecutive posts. It occurs when an individual's mood
↪  progressively shifts from neutral or mildly valenced, toward a more extreme state. An escalation may reflect either improvement or
↪ deterioration.

# Task
Your task is to generate a structured summary describing patterns of self-state dynamics and their progression over time within a sequence of
↪ posts surrounding a change (Switch or Escalation). The summary must describe how psychological change processes evolve across the sequence, and
↪  how they culminate in (when it's a Switch), or unfold through (when it's an Escalation), the identified change event. The direction of the
↪ change (improvement / deterioration) as well as the identity of the change event (Switch/Escalation) should be explicitly stated in the summary
↪ . Describe the change pattern using the MIND framework (ABCD elements).

The summary should include references, only when they are evident in the data, to the following aspects:
1. *Central recurring theme across the posts*: Describe the central dynamic psychological theme and change trajectory characterizing the change
↪ process across the sequence. Explain how this theme evolves across the sequence. The theme should be described across the stages of the change
↪ process within the sequence, making clear how the theme appears before the change and how it develops as the change unfolds or when it
↪ culminates.
2. *Dynamics within the Adaptive and Maladaptive self-states and their presence*: Describe how present each self-state is and how its relative
↪ presence changes throughout the sequence as part of the change process. Presence refers to how strongly each self-state is expressed or
↪ dominant at different points in the sequence, whereas dynamics refer to the interactions between the ABCD subelements within that self-state.
↪ Where present, describe the adaptive and/or the maladaptive self-states in terms of ABCD subelements through explicit relational dynamics
↪ between them within the same self-state. If a self-state is described, relational dynamics between its ABCD subelements MUST also be described.
↪  Dynamics within a self-state are relational patterns between two or more subelements within the same self-state. These dynamics may be
↪ directional or reciprocal, such as co-activation, mutual reinforcement, exacerbation of one element by another, amplification of one element by
↪  another, or other structured interactions.
3. *Relationship between the adaptive and maladaptive self states and their relative presence*: Describe how the adaptive and maladaptive self-
↪ states relate to one another and how that changes throughout the sequence. Describe how the relative presence and dominance of the adaptive and
↪  maladaptive self-states shifts across the sequence. This may include: one self-state dominating the other, suppressing or silencing the other,
↪  or both self-states coexisting through reflective dialogue. examine whether dynamics occur between ABCD subelements across opposite self-
↪ states (suppression/attenuation, reflective dialogue, dominance competition, resilience or other structured interactions). If such cross-self-
↪ state dynamics are present in the sequence, they MUST be described.

# Output requirement
Each reference to an ABCD element should include its abbreviation in parentheses. Use the following mapping: (A) for Affect; (B-S) for Behavior-
↪ self; (B-O) for Behavior-other; (C-S) for Cognition-self; (C-O) for Cognition-other; (D) for Desire. Keep your summary below 350 words and
↪ write it ONE paragraph. Don not mention the post numbers in your summary.

Follow the structre of the examples and write your summary in the same format and start with the term "The central psychological theme revolves
↪ around..."

Think step by step and analyze the posts. Finally, write your summary in the following format:
```json
{
        "summary": "<YOUR SUMMARY>"
}
```
```

Figure 8: The system prompt for the Task 3.1.

System Prompt

```
You are a clinical psychologist specializing in psychodynamic self-state analysis. Write a structured sequence summary grounded in the MIND (ABCD)
↪  framework.

# Framework
A self-state is characterized by combinations of Affect (A), Behavior toward others (B-O), Behavior toward self (B-S), Cognition of others (C-O),
↪ Cognition of self (C-S), and Desire (D). Self-states are either Adaptive (ABCD elements conducive to fulfilling basic needs) or Maladaptive (
↪ ABCD elements that hinder need fulfillment).

Subelements:
- A - Adaptive: calm, sad/grieving, content/hopeful, vigor, justifiable anger, proud, feeling loved. Maladaptive: anxious, depressed/hopeless,
↪ manic, apathetic, aggression/contempt, ashamed, lonely.
- B-O - Adaptive: relating, autonomous/adaptive control. Maladaptive: fight/flight, over-controlling.
- B-S - Adaptive: self-care/improvement. Maladaptive: self-harm/neglect/avoidance.
- C-O - Adaptive: other as related, other as autonomy-facilitating. Maladaptive: other as detached/over-attached, other as blocking autonomy.
- C-S - Adaptive: self-acceptance/compassion. Maladaptive: self-criticism.
- D - Adaptive: relatedness, autonomy, competence/self-esteem. Maladaptive: expectation that relatedness, autonomy, or competence needs won't be
↪ met.

Change events:
- SWITCH: Sudden, substantial change in well-being between two consecutive posts.
- ESCALATION: Gradual intensification of mood across consecutive posts toward a more extreme state.
Both can reflect improvement or deterioration.

# Task
Write a structured summary describing self-state dynamics and their progression across a chronological post sequence surrounding a change event.
↪ Cover:
1. Central recurring theme - how it evolves before and through/culminating in the change.
2. Adaptive and maladaptive self-state dynamics - their relative presence and ABCD subelement interactions (co-activation, reinforcement,
↪ amplification, etc.) across the sequence.
3. Relationship between self-states - how dominance, suppression, coexistence, or cross-state dynamics shift across the sequence.

Explicitly state the change direction (improvement/deterioration) and type (Switch/Escalation). Include ABCD abbreviations inline. Stay under 350
↪ words, one paragraph, starting with: "The central psychological theme revolves around..."

Output format:
{
  "summary": "<YOUR SUMMARY>"
}
```

Figure 9: The shorter version of system prompt for the Task 3.1.

DreamerNLplus: Interpretable Modeling of Mental Health Dynamics from Social Media Timelines using Hybrid Rule-Based and RAG Methods

Maryia Zhyrko[1†], **Daisy Monika Lal**[2†], **Erik van Mulligen**[3], **Lifeng Han**[1,4]
On behalf of the 4D PICTURE consortium
[1]Leiden Institute of Advanced Computer Science (LIACS), Leiden University, NL
[2]School of Computing and Communications (SCC), Lancaster University, UK
[3]Department of Medical Informatics, Erasmus University Medical Center Rotterdam, NL
[4]Biomedical Data Sciences, Leiden University Medical Center, NL
[†] co-first, corresponding: {l.han} @ lumc.nl

Abstract

We present DreamerNLplus, a hybrid framework for modeling mental health dynamics from social media timelines in the CLPsych 2026 shared task. Our system addresses three tasks: psychological state modeling, temporal change detection, and sequence-level summarization. For Task 1, we combine LLM-based data augmentation, DeBERTa classification, and Random Forest regression for structured state prediction. For Task 2, we use few-shot prompting with a locally deployed Llama 3.1 model to detect Switch and Escalation events using short-term temporal context. For Task 3.1, we explore both a deterministic rule-based summarization pipeline and a few-shot LLM-based approach, ranking **2nd** officially. Our RAG-based method achieves strong performance in Task 3.2, ranking **1st** for Improvement and **3rd** for Deterioration, demonstrating its ability to capture recurrent psychological change patterns across timelines. Our analysis reveals key challenges, including the mismatch between classification and regression performance, the difficulty of modeling temporal transitions, and the disagreement between semantic and similarity-based evaluation metrics. These findings highlight the complexity of modeling mental health dynamics and motivate future work on unified evaluation frameworks. We share our code and prompts at https://github.com/4dpicture/CLPsych2026

1 Introduction and Background

We describe our system submissions to the CLPsych 2026 Shared Task (Ali et al., 2026): Capturing and Characterizing Mental Health Changes through Social Media Timeline Dynamics, where we have attended all the sub-tasks. Earlier reviews on NLP for mental health research (Le Glaz et al., 2021; Malgaroli et al., 2023) provide an overview of traditional NLP and ML methods including rule-based, statistical (TF-IDF, decision trees, SVMs, CRFs, random forests, NNs), pretrained LMs (BERT-like encoder models, sequence-to-sequence BART models, domain-specific MentalBERT), and early generative decoders (e.g., GPT2). They also pointed out the *limitations* of existing works such as low reproducibility issue. The resources used include electronic health records (EHRs), Psychological Evaluation reports, social media and interview data. For this study, we used social media post data from the shared task. To improve model *interpretability* as well as investigating newer open-source models, we applied a hybrid combination of a rule-based method, a random forest classifier, DeBERTa models, RAG, and open-sourced LLMs. Recent work related to ours include RAG (Kermani et al., 2025; Bogdanova et al., 2026), prompt engineering and PA-ISP (perspective-aware) (Chan et al., 2025; Romero et al., 2025; Ren et al., 2025), and CLPsych systems/dataset (Tseriotou et al., 2025; Atzil-Slonim, 2025; Tsakalidis et al., 2022; Atzil-Slonim, 2026).

The three main tasks and their sub-tasks:[1]

- **Task 1:** Predict adaptive and maladaptive ABCD element combinations: (1.1) Post-level identification of dominant ABCD subelements and self-state composition; (1.2) Self-state presence rating.
- **Task 2:** Identify moments of change.
- **Task 3:** Summary of change: (3.1) Summarizing sequences surrounding change events; (3.2) Identifying recurrent dynamic signatures of change across timelines.

2 DreamerNLplus Methods

Figure 1 summarizes the overall DreamerNLplus framework. Across the three shared tasks, our sys-

[1]Task 1: https://www.codabench.org/competitions/14057/ Task 2: https://www.codabench.org/competitions/14703/ Task 3: https://www.codabench.org/competitions/14669/

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 458–471
July 4, 2026 ©2026 Association for Computational Linguistics



Figure 1: Overview of the DreamerNLplus system across the CLPsych 2026 shared tasks. Task 1 models psychological state representations, Task 2 detects temporal moments of change, and Task 3 summarizes and generalizes change dynamics across sequences.



Figure 2: Prompt2Predict-DeBERTa pipeline including data preprocessing for Task 1 (Predict adaptive and maladaptive ABCD element combinations).

tems follow a unified modeling perspective: Task 1 identifies psychological state representations, Task 2 detects transitions between states, and Task 3 converts these dynamics into sequence-level summaries and recurrent signatures.

Tasks 1 and 2 on State Modeling and Change Detection. For **Task-1**, we propose **Prompt2Predict-DeBERTa**, a simple multi-stage framework for predicting psychological subelements and presence scores, as in Figure 2. First, we extract evidence for each label from the original training data and augment the evidence using synthetic data for model training purposes. To do this, we employ Ollama to expand the dataset by *generating new examples* through prompts that include label definitions and annotated evidence for every ABCD category. The augmented data is used for DeBERTa model fine-tuning on the task of subelement prediction (Task1.1). The prediction output (ABCD labels) will be encoded as one-hot vector and fed as input to the Random Forest Regressor to further predict the Adaptive / Maladaptive scoring (Task1.2). Finally, we combine both outputs to include two elements: ABCD labels and their presence ratings. We also deployed a rule-based approach for Task1, as in Figure 3.

This pipeline combines LLM-based augmentation (data preprocessing), transformer-based classification, and lightweight vector-based regression to produce structured and interpretable predictions, as well as comparing well-defined rules.

Task-2: Few-Shot LLM Prompting and XGBoost We first design a framework that supports multiple LLM ++backends (Ollama, HuggingFace) and runs locally for privacy, with Llama 3.1 8B as our submitted model (Figure 4). In this framework,



Figure 3: Task 1 rule-based pattern matching approach using n-gram collocations to classify post sentences into ABCD sub-categories.



Figure 4: Task 2 few-shot prompting pipeline (Identify moments of change).

we create a local context window by keeping the preceding 5 timeline posts as context to the LLM prompts for predicting targets (Switch and Escalation). The prompt also defines Switch and Escalation, in addition to the context examples. Our examples include the combinations of Switch-only, Escalation-only, both, and neither, plus a first-post case where no change is possible (no preceding context). The LLM is asked to return its answer in a fixed JSON format with Switch, Escalation, and short justification, and the framework retries the prompt if the response does not match this format.

As a non-LLM comparison, we build a **classifier model** using the XGBoost library. In the preprocessing of this model, we use TF-IDF and sentence transformer embeddings (all-mpnet-base-v2) to represent the posts. To get the temporal difference features, we use 1) the embedding difference between the current and previous posts (i.e., current post embedding - previous post embedding $h_t - h_{t-1}$), 2) their element-wise product, and 3) timeline position. We also used additional feature embeddings, including 14 linguistic features related to sentiment, punctuation, and length (Table 1). Two binary classifiers then predict Switch and Escalation, with the rare positive examples given more weight during training so the model does not simply default to predicting no change everywhere.[2]

Task 3 on Change Summarization and Pattern Mining. For **Task 3.1** "summarizing sequences surrounding change events", we explore two distinct summary generation strategies (Figure 5).

MINDTRACE-SUMMARY is a fully deterministic, multi-stage framework for generating sequence-level psychological signatures from MIND-annotated posts. The model generates summaries by following a fixed structure and converting ABCD annotations into natural language. A full sample template is provided in Appendix D.3. It first determines whether adaptive or maladaptive states dominate, then builds a narrative with five parts: central theme, initial state, interaction dynamics, transition (switch or escalation), and outcome. ABCD labels are rewritten into fluent psychological descriptions, and the summary emphasises how states reinforce or shift over time. The method prioritizes consistency and structure over free-form generation, ensuring summaries clearly reflect change dynamics across the sequence.

For **Few-Shot LLM Prompting**, the prompt specifies the MIND framework, ABCD abbreviation

[2]Positive examples are up-weighted via XGBoost's `scale_pos_weight` parameter, set to $\min\left(\frac{n_{\text{neg}}}{n_{\text{pos}}}, 20\right)$ independently for each classifier.



(a) MINDTRACE-SUMMARY: deterministic rule-based pipeline.

(b) Few-shot LLM prompting pipeline using OS-LLMs.

Figure 5: Task 3.1 summary generation methods from DreamerNLplus – rule-based (left) vs OS-LLMs (right).



Figure 6: Overview of the RAG-LLM Signature Mining framework for Task 3.2.

conventions, relational dynamics vocabulary, and required summary structure covering pre-change phase, within/between-state dynamics, and explicit change event identification. Task 1 ABCD annotations are not used; the model infers ABCD dynamics from post text guided by the prompt.

For **Task 3.2** "identifying recurrent dynamic signatures of change across timelines", we propose **RAG-LLM Signature Mining**, a two-stage LLM-based framework for identifying recurrent dynamic signatures of psychological change. As illustrated in Figure 6, our framework separates intra-batch pattern extraction from cross-batch signature synthesis, enabling the identification of recurrent psychological dynamics across timelines. Sequences are batched and fed to an open-source LLM (Llama 3.1via Ollama) with per-post ABCD subelements, well-being scores, and gold summaries. Stage 1 extracts recurring ABCD dynamics per batch; Stage 2 synthesizes these into one 90-word signature per direction (deterioration/improvement), with 5–10 exemplar sequences as evidence.

3 Results and Analysis

Task 1: State modeling For Task 1, our system ranks 22nd in Task 1.1 (subelement classification) and 20th in Task 1.2 (presence estimation), as shown in Table 2. To further understand this discrepancy, we analyze the relationship between classification performance and regression performance in Figure 7. The results show a moderate negative correlation ($r = -0.486$, $p = 0.00354$), indicating that stronger subelement classification performance does not necessarily translate into better presence estimation. This observation reflects the fundamental difference between the two subtasks: Task 1.1 requires fine-grained categorical prediction of psychological subelements, while Task 1.2 evaluates continuous intensity estimation. Our system, which combines DeBERTa-based classification with Random Forest regression, appears more robust in the regression setting, suggesting that downstream aggregation mitigates upstream classification errors.

Task 2: Change Detection Our submitted LLM system reaches a combined F1 of 0.442, ranking 11th overall (Figure 10), while the XGBoost variant scores 0.327. The two approaches show opposite error patterns: the LLM has high recall but low precision (Switch 0.762/0.302, Escalation 0.917/0.393) meaning it picks up most change cues but tends to over-predict them, while XGBoost has high precision but low recall on rare positive classes(Switch precision 0.455, recall 0.238), reflecting how hard it is to learn these labels from only 30 gold timelines. This shows that accurately capturing subtle transitions remains challenging across paradigms,

and that errors on weak or ambiguous change signals can propagate across the sequence. Despite not relying on task-specific fine-tuning, the LLM method stays competitive performance while providing interpretable predictions with textual justifications. This highlights the effectiveness of few-shot prompting for modeling temporal dynamics in low-resource settings.

Task 3: Summarization and Pattern Mining For Task 3.1, in our processing, we kept other teams best average-ranked submission and our best-performing submission (ID 693964 prompting-w-ablation) ranks 4th overall based on the average ranking across multiple metrics (Figure 11). However, a notable observation is the strong disagreement between evaluation metrics.

Interestingly, shown in Figure 11, the rule-based submission (694142) achieves the best CT and strong CS performance, yet ranks worst overall due to poor ROUGE and BERT scores (a detailed discussion of the evaluation is provided in Appendix E.1.), highlighting a clear disagreement between semantic coherence metrics and similarity-based metrics: CS and CT emphasize semantic coherence and psychological consistency, whereas ROUGE and BERTScore prioritize surface-level similarity to reference summaries. As a result, optimizing for one set of metrics may degrade performance on the other. However, in the official Task 3.1 ranking, DreamerNLplus ranks **2nd** overall with submission 693964, based on the average of metric-specific ranks across CS, CT, ROUGE-L Recall, and BERTScore Recall.

For Task 3.2, as shown in Table 5, our RAG-based approach ranks **1st** on Improvement and **3rd** on Deterioration. In addition, our system achieves the highest score on Specificity and the second-highest on Recurrence for Improvement, and the second-highest Specificity for Deterioration. These results suggest that the proposed RAG-based framework is particularly effective at identifying precise and recurring dynamic patterns across timelines. By combining batch-level pattern extraction with cross-batch synthesis, the approach is able to capture higher-level psychological change signatures that generalize across individuals. However, the performance gap between Improvement and Deterioration also indicates that modeling deterioration patterns remains more challenging, potentially due to greater variability or ambiguity in negative self-state dynamics. This highlights the importance of modeling both intra-sequence consistency and inter-sequence generalization when identifying recurrent psychological dynamics.



Figure 7: Task 1.1 vs 1.2 Relation. Each point = one team. X-axis = Task 1.1 (F1) → higher is better. Y-axis = Task 1.2 (RMSE) → lower is better.

Cross-Task Analysis Across all tasks, a consistent pattern emerges: different evaluation metrics capture distinct and sometimes conflicting aspects of performance. Task 1 reveals a trade-off between classification accuracy and regression stability, Task 2 highlights the difficulty of balancing local and temporal consistency, and Task 3 exposes a mismatch between semantic coherence and lexical similarity metrics. These findings suggest that modeling mental health dynamics requires balancing multiple objectives, including structured prediction, temporal reasoning, and semantic generation. Our hybrid approach demonstrates that combining interpretable representations with flexible LLM-based methods can provide robust performance across tasks, while also revealing important limitations in current evaluation frameworks.

4 Conclusions and Future Work

We presented **DreamerNLplus**, a hybrid framework for modeling mental health dynamics from social media timelines across three tasks: psychological state modeling, temporal change detection, and sequence-level summarization. By combining structured representations, few-shot prompting, and rule-based generation, our approach provides both interpretability and flexibility across different modeling paradigms. Future work should aim to design unified evaluation frameworks that reconcile semantic fidelity, temporal consistency, and textual similarity, enabling clinically meaningful assessment of mental health modeling systems.

Limitations

For data augmentation in Task 1, in this work, we extracted the evidence from original training data, and only asked LLMs to generate more evidence, subsequently, DeBERTa model is trained on the augmented evidence data to predict sub-element classes. This is similar to the dense prescription generation work in (Belkadi et al., 2025) for NER and engineering purposes only, without generating full clinical letters. In an ideal situation, we will further explore the generation of similar post-level, not only evidence.

Task 3 template-based summarization achieved high CS and low CT scores through predefined linguistic rules and structured feature-to-text mappings, enabling stable and interpretable summaries. However, the approach is task-specific and less flexible than human summarization, limiting its ability to capture nuanced contextual and emotional variations in narratives. Despite this, it is well-suited for formal or high-stakes settings where standardized and reproducible documentation is prioritized over linguistic diversity. Additionally, the framework relies on intermediate computations such as switch and escalation scores derived from upstream predictions, meaning errors in earlier stages may propagate into the final summaries.

Ethics

The shared task data we used in this paper is anonymized and annotated by CLPych2026 organizers. We only used secure methods and models to process the data, such as rule-based, locally hosted open-source LLMs, locally trained encoders, without releasing the data to any third parties with our best practice for privacy protection.

Acknowledgments

We thank David Lindevelt for the help on this project, including the automated prompt pipeline and framework adapted from another project (Han et al., 2026). We thank Prof. Suzan Verberne for editing the camera-ready version of this paper. We thank the reviewers for their valuable comments on our work. We thank the organizers preparing this shared task, and we are grateful for their communication during our registration and submissions, especially Talia Tseriotou and Iqra Ali from Queen Mary University of London. The 4D PICTURE consortium is funded by the European Union under Horizon Europe Work Programme 101057332. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Health and Digital Executive Agency (HaDEA). Neither the European Union nor the granting authority can be held responsible for them. The UK team are funded under the Innovate UK Horizon Europe Guarantee Programme, UKRI Reference Number: 10041120.

References

Iqra Ali, Talia Tseriotou, Guy Dvir, Callum Chan, Yuxiang Zhou, Juan Antonio Lossio-Ventura, Ayal Klein, Aya Shamir, Dan Sayda, Anthony Hills, Aya Zirikly, Diana Inkpen, Dana Atzil-Slonim, and Maria Liakata. 2026. Overview of the clpsych 2026 shared task: Capturing and characterizing mental health changes through social media timeline dynamics. In *Proceedings of the 11th Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Dana Atzil-Slonim. 2025. Multimodal intrapersonal and interpersonal dynamics (mind): A transtheoretical coding manual.

Dana Atzil-Slonim. 2026. Leveraging theoretical and technological innovations to study the mechanisms that underlie therapeutic change in psychotherapy. In Louis G. Castonguay, Dana Atzil-Slonim, Michael Barkham, and Wolfgang Lutz, editors, *Practice-Based Evidence in the Psychological Therapies: Toward Policy Implications for Research, Training, and Clinical Guidelines*. Oxford University Press, New York.

Samuel Belkadi, Nicolo Micheletti, Lifeng Han, Warren Del-Pinto, and Goran Nenadic. 2025. Lt3: Generating medication prescriptions with conditional transformer. In *Proceedings of the Second Workshop on Patient-Oriented Language Processing (CL4Health)*, pages 205–218.

Liliia Bogdanova, Shiran Sun, Lifeng Han, Natalia Amat Lefort, and Flor Miriam Plaza-del Arco. 2026. Flans at semeval-2026 task 7: Rag with open-sourced smaller llms for everyday knowledge across diverse languages and cultures. *arXiv preprint arXiv:2603.01910*.

Callum Chan, Sunveer Khunkhun, Diana Inkpen, and Juan Antonio Lossio-Ventura. 2025. Prompt engineering for capturing dynamic mental health self states from social media posts. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 256–267, Albuquerque, New Mexico. Association for Computational Linguistics.

Lifeng Han, David Lindevelt, Sander Puts, Erik van Mulligen, and Suzan Verberne. 2026. Dutch

metaphor extraction from cancer patients' interviews and forum data using llms and human in the loop. *CL4Health WS at LREC2026, Palma, Spain*.

Arshia Kermani, Veronica Perez-Rosas, and Vangelis Metsis. 2025. A systematic evaluation of LLM strategies for mental health text analysis: Fine-tuning vs. prompt engineering vs. RAG. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 172–180, Albuquerque, New Mexico. Association for Computational Linguistics.

Aziliz Le Glaz, Yannis Haralambous, Deok-Hee Kim-Dufor, Philippe Lenca, Romain Billot, Taylor C Ryan, Jonathan Marsh, Jordan Devylder, Michel Walter, Sofian Berrouiguet, and 1 others. 2021. Machine learning and natural language processing in mental health: systematic review. *Journal of medical Internet research*, 23(5):e15708.

Matteo Malgaroli, Thomas D Hull, James M Zech, and Tim Althoff. 2023. Natural language processing for mental health interventions: a systematic review and research framework. *Translational Psychiatry*, 13(1):309.

Libo Ren, Yee Man Ng, and Lifeng Han. 2025. Malei at multiclinsum: Summarisation of clinical documents using perspective-aware iterative self-prompting with llms.

Pablo Romero, Libo Ren, Lifeng Han, and Goran Nenadic. 2025. The manchester bees at peranssumm 2025: Iterative self-prompting with claude and o1 for perspective-aware healthcare answer summarisation. In *Proceedings of the Second Workshop on Patient-Oriented Language Processing (CL4Health)*, pages 340–348.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Talia Tseriotou, Jenny Chim, Ayal Klein, Aya Shamir, Guy Dvir, Iqra Ali, Cian Kennedy, Guneet Singh Kohli, Anthony Hills, Ayah Zirikly, Dana Atzil-Slonim, and Maria Liakata. 2025. Overview of the CLPsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 193–217, Albuquerque, New Mexico. Association for Computational Linguistics.

A CLPsych 2026 Shared Tasks

CLPsych2026 is affiliated with The Workshop on Computational Linguistics and Clinical Psychology, a workshop series founded in 2014. CLPsych 2026 will be held at ACL in San Diego, July 4th, 2026.

A.1 Task Evaluations

Unified Evaluation Framework The CLPsych 2026 shared tasks evaluate complementary aspects of modeling mental health dynamics from social media timelines, spanning classification, regression, temporal change detection, and summarization. Across Tasks 1–3, the evaluation framework progressively moves from local, structured predictions to global, sequence-level reasoning and natural language generation.

Task 1 (State modeling). Task 1 evaluates the ability to model psychological self-states at the post level. Task 1.1 focuses on discrete classification of ABCD elements and subelements, using macro-averaged F1 scores across adaptive and maladaptive categories. Task 1.2 evaluates continuous presence estimation on a 1–5 scale, using regression metrics such as RMSE, with ranking based on the mean RMSE across valences. Together, these subtasks capture the challenge of jointly modeling structured categorical representations and continuous mental state intensity.

Task 2 (Change Detection). Task 2 evaluates the detection of temporal change signals, specifically Switch (sudden change) and Escalation (gradual change). Performance is measured using F1 scores at both post-level and timeline-level, with final ranking based on the average of these two perspectives. This design rewards systems that can detect both local transitions and maintain consistency across sequences.

Task 3 (Change Summarization and Pattern Mining). Task 3 evaluates sequence-level understanding and generation. Task 3.1 assesses the quality of generated summaries using a multi-metric framework including semantic consistency (CS), contradiction (CT), and similarity-based metrics (ROUGE-L and BERTScore), with final ranking based on averaged metric ranks. Task 3.2 focuses on identifying recurrent dynamic patterns across timelines, emphasizing generalization and abstraction of psychological change signatures.

Cross-Task Perspective. Taken together, the evaluation framework reflects a hierarchy of modeling challenges: Task 1 focuses on *what* psychological states are present, Task 2 focuses on *when* meaningful changes occur, and Task 3 focuses on *how* these changes can be summarized and generalized. Notably, the metrics across tasks capture partially complementary qualities, including classification accuracy, regression stability, temporal consistency, and semantic coherence, highlighting the inherent trade-offs in modeling mental health dynamics.

This unified evaluation highlights the difficulty of aligning discrete classification, continuous estimation, temporal reasoning, and semantic generation within a single modeling framework.



Figure 8: Targeted data augmentation strategy using Ollama.

B Methods and Experimental Development - Task1 (*More Details*)

We adopt a multi-paradigm modeling strategy combining rule-based, transformer-based, and LLM-assisted components for the overall shared task, to establish the relevance of the adopted approach for a given task.

B.1 Task 1.1: ABCD Element & Subelement Classification

Task 1.1 focuses on identifying fine-grained ABCD self-state elements and their corresponding subelements within each post. However, the task presents two key inherent challenges due to the fine-grained structure of the ABCD schema. First, the large number of subelements per category leads to a highly imbalanced and sparse label space, where certain subelements are significantly underrepresented. Second, there exists substantial seman-

tic overlap between closely related subelements, making boundary definition non-trivial even for pretrained language models.

Data Augmentation: To address data sparsity, we employ targeted data augmentation using Ollamas (see Fig. 8). Augmentation is guided by structured ABCD element definitions and subelement descriptions, enabling controlled expansion of training data while preserving label semantics (see Fig. 9). However, augmentation introduces additional challenges. While LLM-based generation improves data volume and diversity, it may also introduce distributional shifts, as synthetic samples often lack the contextual richness and temporal grounding of real social media posts. This is particularly critical in longitudinal mental health modeling, where self-state interpretation depends on subtle linguistic, emotional, and contextual cues.

Transformer-based Approach (DeBERTa): Initially, we considered a transformer-based sequence classifier, DeBERTa, for direct multi-label prediction of subelements. The model is fine-tuned to jointly learn element presence and subelement classification in a supervised setting, leveraging contextual embeddings to capture nuanced linguistic signals. However, due to extreme label granularity, semantic overlap between subelements (e.g., self-care vs. self-improvement, anxiety vs. despair), and limited training examples for several classes, purely supervised learning was found to be insufficient for robust generalisation.

Rule-based Approach (Augmented n-gram Modeling): Consequently, we introduce a rule-based pipeline that leverages label-conditioned augmented data for n-gram extraction and pattern-based classification (see Fig. 3). Augmented samples generated via Ollama are used to construct label-specific lexical signatures in the form of n-grams, which serve as interpretable indicators of subelement presence. Specifically, we compute top-k bigrams and trigrams from cleaned, stopword-removed text and rank them using likelihood ratio scores to identify statistically salient phrases. This approach is particularly effective in low-resource settings, where explicit lexical cues correlate strongly with specific psychological states.

B.2 Task 1.2: Presence Rating:

Task 1.2 focuses on estimating the overall presence rating (1–5) of adaptive and maladaptive states for each post, reflecting the psychological centrality of each state within the narrative. To address this task, we explore both regression-based and LLM-based approaches. We observed a clear relationship between the presence of specific subelements and the final presence ratings, but also noted that simple frequency-based counting of elements did not reliably correspond to the assigned scores. In particular, ratings were influenced not just by the number of subelements but by their specific types within the same ABCD category.

Regression-based Approach: Given the relationship observed between ABCD subelements and presence ratings, we adopt a regression framework using RandomForestRegressor. We construct structured binary feature vectors that serve as inputs to two separate regression models, with adaptive and maladaptive states modelled independently. This approach directly depends on the outputs of Task 1.1 during inference, where detected subelements are aggregated to form the input feature representation. Finally, the continuous outputs are rounded to discrete levels (1–5), aligning with the original annotation scheme.

B.3 Task 2 Features

C Cross-task Analysis

From our methods: Unlike Task 1, which learns explicit ABCD representations, Task 2 relies on contextual prompting to identify dynamic changes directly from timelines. Together, these approaches reflect a common emphasis on interpretability, temporal sensitivity, and privacy-preserving deployment. Task 1 models what psychological states are present, while Task 2 models when meaningful changes occur.

C.1 Stratified Sampling and K-fold

We have tried both Stratified Sampling and K-fold training data split for model development purposes. In the end, we adopted the K-fold approach for our data processing.

D Prompts and Rule-based Templates

We share our codes and full prompts used for the shared tasks at our Github page https://github.com/4dpicture/CLPsych2026.



Figure 9: Data Augmentation Examples (paraphrased to preserve privacy in accordance with shared task guidelines).

Table 1: Hand-crafted linguistic features used in Task 2 (Switch/Escalation detection). Features are extracted per post and concatenated with the temporal embedding differences.

#	Feature	Description
Lexical		
1	`log_len`	$\log(1 + \text{word count})$; compresses post length onto a continuous scale
2	`n_sentences`	Number of sentences, split on `[.!?]+`
3	`avg_word_len`	Mean character length across words
4	`frac_upper`	Fraction of characters that are uppercase
5	`frac_punct`	Fraction of characters that are punctuation (`!?.,;:`)
Punctuation / prosodic signals		
6	`n_exclaim`	Raw count of exclamation marks (`!`)
7	`n_question`	Raw count of question marks (`?`)
8	`n_ellipsis`	Raw count of ellipses (`...`)
9	`emo_punct`	$\min(\texttt{n_exclaim} + \texttt{n_question},\ 10)$; capped emotional punctuation
Sentiment lexicon		
10	`frac_neg`	Fraction of words matching a negative lexicon (*hate, depressed, pain, alone*, ...)
11	`frac_pos`	Fraction of words matching a positive lexicon (*happy, hope, proud, grateful*, ...)
12	`sentiment_balance`	`frac_neg` − `frac_pos`; net sentiment polarity
Structural		
13	`words_per_sent`	word count/sentence count; average sentence length
14	`has_removed`	Binary flag for `[removed]` or `[deleted]` posts

D.1 Task2 Prompts

D.2 Task3.1 Prompts

D.3 Task3.1 Summary Generation: Rule-based Template

We generate the final narrative using a rule-based template conditioned on extracted discourse features. Let M denote the total maladaptive score and A the total adaptive score. Let Δ denote structural change type and D denote trajectory direction.

Feature Sets Adaptive ($\mathcal{F}_a$) and Maladaptive ($\mathcal{F}_m$) features labels.

Initial Phase If $M \geq A$, maladaptive processes are dominant:

> Initially, maladaptive self-state processes are more dominant, characterized by elements such as $\mathcal{F}_m$, while adaptive processes remain less prominent.

Otherwise, adaptive processes are dominant:

> Initially, adaptive self-state processes are more dominant, characterized by elements such as $\mathcal{F}_a$, buffering against maladaptive tendencies.

Temporal Dynamics If $M > A$, maladaptive dynamics intensify over time:

> Maladaptive dynamics intensify over time through reinforcing cycles of negative affect, self-critical cognition, and

behavioral withdrawal, suppressing adaptive functioning.

Otherwise, adaptive processes strengthen over time:

> Adaptive processes strengthen over time through increasing self-compassion, relational engagement, and constructive coping that counter maladaptive tendencies.

Structural Transition If $\Delta =$ switch:

> A transition point emerges within the sequence, reflecting a shift in the balance between adaptive and maladaptive self-states.

If $\Delta =$ escalation:

> An escalation unfolds across the sequence, reflecting progressive intensification of emotional, cognitive, and behavioural processes over time.

Trajectory Direction If $D =$ deterioration:

> In the later phase, maladaptive self-state dynamics dominate, reinforcing sustained distress and hopelessness.

If $D =$ improvement:

> In the later phase, adaptive self-state dynamics become dominant, supporting resilience and psychological recovery.

If $D =$ fluctuation:

> In the later phase, adaptive and maladaptive self-states remain in tension, reflecting ongoing fluctuation between distress and coping.

Global Template (Always Included) Across all sequences, the following integrative statements are included:

> The central psychological theme across the sequence reflects an evolving interaction between maladaptive distress and adaptive coping processes expressed through affect, cognition, behavior, and desire.
>
> As the sequence progresses, adaptive and maladaptive self-states increasingly interact, creating periods of internal conflict, reflection, and shifting psychological balance.
>
> Across the sequence, adaptive and maladaptive self-states alternate in dominance and suppression, shaping the overall trajectory of psychological change.

D.4 Task3.2 Prompts

E Discussion

In this section, we discuss the performance characteristics, advantages, and limitations of the proposed methods.

E.1 Consistency vs. Lexical Similarity in Template-Based Summarization

The template-based summarization method achieved the highest CS and lowest CT scores, highlighting its strength in producing stable and logically coherent outputs. This behavior is expected, as the generation process is strictly governed by predefined linguistic rules and structured feature-to-text mappings, which reduce variability and minimize the risk of semantic drift or internally inconsistent statements. Such control is particularly important in sensitive domains such as palliative care narrative analysis, where reliability and interpretability of generated summaries are critical.

However, this same constrained generation process leads to lower ROUGE and BERTScore performance compared to more flexible neural baselines. Both metrics reward lexical overlap and semantic similarity to reference summaries, which are typically written in a more natural and varied style. Template-based outputs, while semantically faithful and structurally consistent, do not exhibit the paraphrastic richness or lexical alignment required to maximize these scores. As a result, there is an inherent trade-off between consistency-oriented generation and similarity-based evaluation metrics.

This trade-off suggests that template-based summarization is particularly well-suited for applications where factual stability, interpretability, and controllability are prioritized over surface-level similarity to reference texts. In the context of psychological trajectory modeling from patient and caregiver narratives, such methods are advantageous for producing reproducible summaries of adaptive and maladaptive self-state dynamics. Conversely, neural summarization models may be preferred in settings where linguistic expressiveness and alignment with human-written references are more important than strict structural consistency.

Task2	Team Name	Avg Macro F1
1	USAI	0.6
2	CtbuY	0.588
3	JNLP	0.58
4	CLPsych2026 - Baseline 3 (Tempoformer)	0.572
5	CUNY	0.572
6	MKC	0.554
7	Codezone Research Group	0.553
8	Aurevia	0.484
9	Meronym Labs	0.466
10	debju	0.447
11	**DreamerNLplus**	**0.442**
12	McMasterNLP	0.412
13	BLUE	0.403
14	NoviceTrio	0.385
15	DrosophilAI	0.383
16	psytechlab	0.372
17	CLPsych2026 - Baseline 2	0.365
18	CSE_IIT_Ropar	0.357
19	CLPsych2026 - Baseline 1	0.272
20	Afrilan	0.268
21	Lin Tan	0.26

Figure 10: Task 2 Ranking

F Details on rankings and evaluation scores

We list our official ranking scores with other teams in this section.

Table 2: Task 1.1 and Task 1.2 rankings. Task 1.1 is ranked by Subelement Average Macro F1, while Task 1.2 is ranked by RMSE, where lower is better.

Team	Task 1.1 Rank	Task 1.2 Rank	Task 1.1 Macro F1	Task 1.2 RMSE
CUNY	1	6	0.442	1.007
StateOfMIND	2	8	0.441	1.021
StateOfMIND	3	12	0.440	1.094
StateOfMIND	4	5	0.433	0.994
CUNY	5	4	0.431	0.989
Meronym Labs	6	1	0.420	0.917
CUNY	7	10	0.416	1.041
Meronym Labs	8	18	0.410	1.212
USAI	9	2	0.410	0.942
USAI	10	21	0.403	1.294
Meronym Labs	11	11	0.399	1.041
Aurevia	12	3	0.381	0.981
MKC	13	7	0.361	1.010
McMasterNLP	14	9	0.351	1.035
ull	15	17	0.335	1.185
ull	16	16	0.333	1.171
BLUE	17	33	0.318	1.606
NoviceTrio	18	19	0.313	1.255
Afrilan	19	31	0.297	1.585
Afrilan	20	34	0.285	2.053
psytechlab	21	25	0.274	1.407
DreamerNLplus	**22**	**20**	**0.254**	**1.285**
CLPsych2026 - Baseline	23	26	0.247	1.424
CtbuY	24	30	0.236	1.585
Afrilan	25	23	0.214	1.329
CtbuY	26	28	0.210	1.506
debju	27	24	0.195	1.348
DrosophilAI	28	14	0.179	1.154
CSE_IIT_Ropar	29	32	0.175	1.590
ull	30	29	0.119	1.517
CtbuY	31	27	0.118	1.501
CSE_IIT_Ropar	32	13	0.106	1.146
DrosophilAI	33	22	0.099	1.305
debjy	34	15	0.000	1.156

A	B	C	D	E	F	G	H	I	J	K
Team	Consistency (CS)	CS_rank	Contradiction (CT)	CT_rank	ROUGE-L Recall	R-L_rank	BERTscore Recall	BERTscore_rank	Score Average	core Rank Average
MERONYM_LABS	0.80073322	4	0.659288617	4	0.265764584	12	0.34491533	7	0.5176754378	6.75
CUNY	0.789027221	7	0.714318694	8	0.29207881	5	0.294779657	18	0.5225510955	9.5
NoviceTrio	0.704759255	16	0.770804092	13	0.317894427	2	0.340504646	8	0.533490605	9.75
DreamerNLplus	*0.735013197*	*14*	*0.76715816*	*12*	*0.28453229*	*8*	*0.345456439*	*6*	*0.5330400215*	*10*
USAI	0.680537067	20	0.849299731	25	0.332895421	**1**	0.365483143	**2**	0.5570538405	12
DreamerNLplus	*0.739321004*	*13*	*0.739891788*	*10*	*0.225534182*	*21*	*0.328495991*	*10*	*0.5083107413*	*13.5*
Aurevia	0.865719654	1	0.624931034	3	0.184924076	26	0.226479176	25	0.475513485	13.75
MKC	0.668688559	21	0.856618807	27	0.29046832	6	0.362011761	3	0.5444468618	14.25
DreamerNLplus	*0.845004471*	***3***	*0.439257234*	***1***	*0.189083659*	*25*	*0.14373662*	*29*	*0.404270496*	*14.5*
Baseline	0.767319058	11	0.744681011	11	0.26853177	12	0.235086789	25	0.503904657	14.75
psytechlab	0.856826357	2	0.570653373	2	0.077716539	29	0.146949642	28	0.4130364778	15.25
JNLP	0.790974544	6	0.665859524	5	0.116772542	28	0.163692788	27	0.4343248495	16.5
McMaster NLP	0.770177034	10	0.761182828	11	0.208128021	23	0.255358784	23	0.4987116668	16.75
CSE_IIT_Ropar	0.688347356	18	0.812002344	18	0.24240965	17	0.306391245	16	0.5122876488	17.25
ULL	0.585453856	27	0.84554644	23	0.261929928	13	0.319793656	14	0.50318097	19.25
CtbuY	0.615451482	26	0.848440523	24	0.232144785	19	0.317244728	15	0.5033203795	21

Figure 11: Task 3.1 eval on test set - all teams (our filtering: by using the best averaged rank submission from other teams).

Table 3: **The Official rank** of Task 3.1 based on selected submissions of all teams. CS, ROUGE-L Recall, and BERTScore Recall are higher-is-better; CT is lower-is-better. Final rank is based on the average of metric-specific ranks. We rank the **2nd best** overall.

Rank	Team	Sub. ID	CS	CS Rank	CT	CT Rank	ROUGE-L	R-L Rank	BERT	BERT Rank	Avg. Rank
1	MERONYM_LABS	694229	0.801	3	0.659	3	0.266	6	0.345	4	4.00
2	**DreamerNLplus**	**693964**	**0.735**	**7**	**0.767**	**7**	**0.285**	**4**	**0.345**	**3**	**5.25**
3	CUNY	694216	0.789	5	0.714	5	0.292	3	0.295	9	5.50
4	NoviceTrio	693913	0.705	8	0.771	8	0.318	2	0.341	5	5.75
5	USAI	693912	0.681	10	0.849	13	0.333	1	0.365	1	6.25
5	Aurevia	693454	0.866	1	0.625	2	0.185	11	0.226	11	6.25
7	MKC	687777	0.654	11	0.834	10	0.284	5	0.359	2	7.00
8	psytechlab	689973	0.857	2	0.571	1	0.078	13	0.147	13	7.25
9	JNLP	691315	0.791	4	0.666	4	0.117	12	0.164	12	8.00
9	McMaster NLP	694189	0.770	6	0.761	6	0.208	10	0.255	10	8.00
11	CSE_IIT_Ropar	694311	0.688	9	0.812	9	0.242	8	0.306	8	8.50
12	ULL	694669	0.585	13	0.846	11	0.262	7	0.320	6	9.25
13	CtbuY	691446	0.615	12	0.848	12	0.232	9	0.317	7	10.00

Table 4: Summary of DreamerNLplus Submissions on Task 3.1 Across Evaluation Metrics (↑ higher is better, ↓ lower is better). Detail score refers to Fig. 11

Submission	CS ↑	CT ↓	ROUGE	BERT	Score Avg
693964	medium-high	high	decent	decent	**0.533 (best)**
694011	medium-high	medium	lower	medium	0.508
694142	**very high/3rd**	**very low/best**	low	low	0.404 (worst)

Table 5: Task 3.2 official rankings for recurrent dynamic signatures of Improvement and Deterioration. Best scores in each metric column are shown in bold, and second-best scores are underlined. We **won Improvement** category, and *2nd best* on Specificity for Deterioration category.

Direction	Team	Rank	Fit	Recurrence	Specificity	Overall
Improvement	*DreamerNLplus*	1	0.6250	<u>0.8125</u>	**1.0000**	**0.7608**
	CSE_IIT_Ropar	2	**1.0000**	0.6875	0.3750	<u>0.7426</u>
	MKC	3	<u>0.7500</u>	0.5625	<u>0.9375</u>	0.7266
	McMasterNLP	4	0.6875	0.3750	0.7500	0.5938
	psytechlab	5	0.6875	**1.0000**	0.2500	0.5437
	Aurevia	6	0.3750	0.6250	0.5000	0.4653
	MeronymLabs	7	0.2500	0.2500	0.5625	0.2981
	CtbuY	8	0.2500	0.2500	0.0000	0.1250
	CUNY	9	0.0000	0.0000	0.2500	0.0000
Deterioration	CSE_IIT_Ropar	1	<u>0.8750</u>	0.5625	**0.9375**	**0.7891**
	Aurevia	2	0.6875	<u>0.8125</u>	0.5625	<u>0.6761</u>
	DreamerNLplus	3	0.4375	0.6875	<u>0.8750</u>	0.6038
	MeronymLabs	4	0.4375	0.5625	0.8125	0.5511
	CtbuY	5	**1.0000**	**1.0000**	0.0000	0.5000
	psytechlab	6	0.6250	0.6250	0.2500	0.4911
	MKC	7	0.1875	0.1875	0.5000	0.2301
	McMasterNLP	8	0.1875	0.1875	0.3125	0.2109
	CUNY	9	0.0000	0.0000	0.3125	0.0000

Hierarchical Multi-Stage Modeling of Adaptive and Maladaptive Self-States in Social Media Timelines

Abir Naskar and Mike Conway
School of Computing and Information Systems, University of Melbourne
Parkville, Melbourne, 3053, VIC, Australia
anaskar@student.unimelb.edu.au, mike.conway@unimelb.edu.au

Abstract

We address the CLPsych 2026 Shared Task on modeling psychological self-states from longitudinal social media data. We propose (i) a hierarchical multi-stage framework that integrates a multi-task transformer encoder and (ii) a four stage instruction-tuned large language model finetuning pipeline for subelement classification, presence estimation, and evidence extraction. Our approach incorporates element-conditioned label masking and cross-stage encoder transfer, enabling structured prediction aligned with the ABCD psychological framework. Experiments show improvements over the baseline on the development setup, with RoBERTa achieving an 8.3% gain in macro-F1 and improved root mean square error (RMSE), while a fine-tuned Qwen3 model attains the best overall performance. These results demonstrate the effectiveness of combining hierarchical multi-task learning with structured generation for interpretable mental health analysis. All code for this task is publicly available in a GitHub repository[1].

1 Introduction

Mental health disorders remain a critical global challenge, motivating the need for scalable methods for early detection and monitoring. Social media provides a valuable source of longitudinal behavioral data, enabling the analysis of individuals' evolving emotional and cognitive states in naturalistic settings (Uban et al., 2021). While early work in clinical NLP focused on static classification tasks such as depression detection, recent research emphasizes modeling fine-grained and dynamic psychological processes over time (Atzil-Slonim, 2026). The Workshop on Computational Linguistics and Clinical Psychology (CLPsych) 2026 Shared Task (Ali et al., 2026) further advances this direction by introducing a structured framework for identifying adaptive and maladaptive self-states grounded in the ABCD (Affect, Behavior, Cognition, Desire) model, requiring both subelement prediction and intensity estimation.

To address these challenges, we propose a hierarchical multi-stage framework that combines discriminative and generative modeling. First, a multi-task transformer jointly predicts ABCD subelements and their presence scores, leveraging shared representations for structured prediction (Tian et al., 2019; Ferraro and Benedetti, 2025). Next, an instruction-tuned language model is used to extract supporting evidence and generate interpretable outputs, enabling transparent reasoning over predictions. Our contributions are as follows: First, we propose a hierarchical multi-stage architecture that decomposes self-state modeling into sequential prediction stages, enabling explicit modeling of dependencies between detection, classification, and evidence extraction. Second, we introduce element-conditioned label masking and cross-stage encoder transfer, which enforce psychologically consistent predictions and improve representation learning. Third, we combine discriminative and generative modeling by integrating a multi-task transformer with an instruction-tuned LLM, enabling both accurate prediction and interpretable structured outputs. Finally, we design a computationally efficient system that supports CPU-based inference while retaining competitive performance.

2 Task and Dataset

The CLPsych 2026 Shared Task extends the longitudinal modeling framework introduced in CLPsych 2022 (Tsakalidis et al., 2022) and 2025 (Tseriotou et al., 2025). It uses an expanded subset of the CLPsych 2022 "Reddit-New" dataset and is grounded in the MIND framework (Atzil-Slonim, 2025; Slonim, 2024), which represents self-states as structured combinations of six psychological

[1] https://github.com/AbeerNaskar/clpsych26-sharedtask1

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 472–481
July 4, 2026 ©2026 Association for Computational Linguistics

dimensions: Affect, Behaviour toward Others, Behaviour toward the Self, Cognition of Others, Cognition of the Self, and Desire, each comprising adaptive and maladaptive elements. We focus on Subtask 1, which involves identifying ABCD subelements in posts, determining their composition into adaptive or maladaptive self-states with supporting evidence spans, and predicting their psychological centrality on a 1–5 scale (evaluated using RMSE). The dataset consists of longitudinal timelines, including 30 labelled training timelines (373 posts) and 10 unlabelled test timelines (92 posts). Table 2 summarises the key corpus statistics.

3 Method

We present a dual-approach system for hierarchical multi-task modeling of self-state signals, designed with a focus on low-resource deployment. Our primary approach is a hierarchical multi-task encoder based on pretrained transformers (e.g., BERT/RoBERTa), which jointly predicts state presence and intensity scores, and performs element classification and token-level evidence extraction for detected states. Complementing this, we employ an instruction-tuned large language model adapted via low-rank adapters, which follows a staged prompting pipeline for state detection, element identification, category and evidence generation, and final scoring. Our design is grounded in prior work on pretrained transformers (Vaswani et al., 2017), multi-task learning (Ruder, 2017), instruction tuning (Ouyang et al., 2022), chain-of-thought reasoning (Wei et al., 2022), and evidence extraction.

3.1 Hierarchical Multi-Task Transformer-based Encoder

We implement a two-stage, hierarchical multi-task model using a pretrained encoder-based transformer like BERT (Devlin et al., 2019), RoBERTa (Liu et al., 2019), etc. The architecture diagram is depicted in Figure 1.

3.1.1 Stage 1: Binary Detection and Presence Regression

Stage 1 consists of a binary classifier and a regression unit.

Given an input post $X = (x_1, x_2, \ldots, x_n)$, the encoder produces contextual representations:

$H = Encoder(X) \in R^{n \times d}$.

We extract the pooled representation $h_{cls} = H[0]$, which is passed through dropout and fed into two task-specific heads:

Classification logits:

$z_{cls} = W_{cls}.Dropout(h_{cls}) + b_{cls} \in R^2$

Regression output:

$\hat{p}_{pres} = W_{reg}.Dropout(h_{cls}) + b_{reg} \in R$.

The classification probabilities are obtained via softmax. The regression output is treated as a continuous estimate and clipped to the valid range [1,5] at inference time. The joint training objective is:

$\mathcal{L}_{S1} = \mathcal{L}_{CE}(z_{cls}, y_{cls}) + \lambda \mathcal{L}_{MSE}(\hat{p}_{pres}, y_{pres})$,

where λ is a constant (set to 0.5 in our experiments), $\mathcal{L}_{CE}$ is cross-entropy loss and $\mathcal{L}_{MSE}$ is mean squared error.



Figure 1: Two-stage hierarchical multi-task transformer-based encoder approach for solving the task.

3.1.2 Stage 2: Element-Conditioned Subelement Classification and Evidence Detection

Stage 2 initialises its encoder from the Stage 1 checkpoint, providing a domain-adapted starting point for the more challenging subelement classification task. Each training example pairs a post x with an ABCD element identifier,

$e \in \{$Adaptive-A, Adaptive-B-O, Adaptive-B-S, Adaptive-C-O, Adaptive-C-S, Adaptive-D, Maladaptive-A, Maladaptive-B-O, Maladaptive-B-S, Maladaptive-C-O, Maladaptive-C-S, Maladaptive-D$\}$

as a text segment, producing the concatenated input: $X' = [CLS] \oplus X \oplus [SEP] \oplus e \oplus [SEP]$.

This element-conditioning allows a single model to serve all six elements, with the element token acting as a task prompt that shifts the [CLS] representation toward the relevant MIND dimension. Two task-specific heads operate on the Stage-2 encoder output. The classification head predicts the subelement category over the full label vocabulary L ($|L_{adaptive}| = 16$, $|L_{maladaptive}| = 16$, and a none label):

$z_{cat} = W_{cat}.Dropout(h'_{cls}) + b_{cat} \in R^{|\mathcal{L}|}$

We enforce a structural constraint by masking invalid labels for each element, ensuring predictions remain within the valid subelement set. Let $V(e)$ denote the set of valid label indices for element e (plus the none index). The masked logits are:

$$\tilde{z}_{cat}[i] = \begin{cases} z_{cat}[i], & if \ \ i \in V(e) \\ -\infty, & \text{otherwise} \end{cases}$$

Predictions are obtained by:

$\hat{y}_{cat} = \arg\max Softmax(\tilde{z}_{cat})$

For the evidence (BIO [2]) span detection, a token-level classifier operates over the sequence representations:

$Z_{BIO} = W_{BIO}H' + b_{BIO} \in R^n$

producing per-token logits indicating evidence span membership. Reference BIO labels are created by aligning spans to tokens. The joint loss is defined as:

$\mathcal{L}_{S2} = \mathcal{L}_{CE}(\tilde{z}_{cat}, y_{cat}) + \mathcal{L}_{BCE}(Z_{BIO}[active], y_{BIO}[active])$

where active masks out padding positions from the BIO loss, and $\mathcal{L}_{BCE}$ is binary cross-entropy loss.

3.1.3 Inference

At inference time, Stage 1 predicts state presence and intensity for each post. Posts predicted as positive are forwarded to Stage 2, where all six element-conditioned predictions are computed in parallel using their respective masks. Posts predicted as negative are not processed further, reducing error propagation to downstream modules. This filtering reduces unnecessary computation and limits error propagation from downstream modules.

[2]BIO = Beginning – Inside – Outside

3.2 Instruction-Tuned LLM Pipeline with Transformer-based Decoder

We propose a multi-stage framework for psychological state prediction using an instruction-tuned LLM with LoRA, decomposing the task into sequential stages: state detection, element identification, category and evidence extraction, and presence refinement. This approach reduces task complexity and enforces intermediate representations, aiming to improve interpretability through intermediate outputs than one-shot prompting. Each stage is trained independently with a causal language modeling objective and executed in a chained manner at inference. While effective for fine-grained prediction, the pipeline remains susceptible to error propagation across stages. Further details of the stages, prompts, and training procedure are provided in Appendix A.2. However, this pipeline may accumulate errors across stages.

3.3 Ablation Study

The ablation study is conducted on Method 1 using a controlled hold-out setup with an 85/15 train–validation split and a fixed random seed for fair comparison. Stage 1 is trained on the training portion for state prediction, while Stage 2 operates only on positively labeled instances expanded to element-level data. A0 denotes the full model with all components enabled. Starting from this baseline, we systematically modify one component at a time to assess the impact of key design choices, including multi-task supervision, class imbalance handling, cross-stage knowledge transfer, span-level supervision, structural constraints, input preprocessing, and fine-tuning strategy. This controlled setup enables precise attribution of performance changes to individual components. Results are reported on a single split and may vary across different random seeds. We do not perform statistical significance testing due to limited data.

4 Experiments and Results

We evaluate two complementary approaches. For Method 1, we use pretrained transformer encoders, BERT-base-uncased and RoBERTa-base, implemented with Hugging Face Transformers (Wolf et al., 2020) and trained in PyTorch. Models are trained with sequence lengths of 256 (Stage 1) and 300 (Stage 2), batch size 16, AdamW optimizer (learning rate 2×10^{-5}), and dropout (0.1). Class imbalance is handled using a weighted random

Model	Subelement Avg Macro F1	RMSE
RoBERTa	0.331	1.146
BERT	0.313	1.255
Qwen3	**0.333**	**1.06**
CLPsych2026 - Baseline	0.247	1.424

Table 1: Subelement-level average Macro-F1 and RMSE results. BERT (submission ID 662787) was our official competition submission during the competition phase; RoBERTa (submission ID 706280) and Qwen3 (submission ID 705090) were evaluated during the post-competition analysis phase and are reported here for completeness. Our official submission ranked in the competition under team name NoviceTrio. The CLPsych 2026 baseline uses one-shot structured prompting with LLaMA-3.1-8B-Instruct.

sampler, with gradient clipping and fixed seeds for stability. We prefer a weighted random sampler over a weighted loss function because it ensures balanced class exposure at the batch level without modifying the loss landscape, which we found more stable under the small dataset regime of this shared task; weighted loss reweighting can destabilise regression heads when classification and regression losses are jointly optimised.

For Method 2, we use Qwen3-4B-Instruct implemented via Unsloth [3], fine-tuned with LoRA (Hu et al., 2022) in 4-bit precision for efficiency. Training follows a four-stage supervised fine-tuning pipeline with an effective batch size of 8, AdamW (8-bit) optimizer (learning rate 2×10^{-4}), and a maximum sequence length of 2048. Each stage is trained for a fixed number of steps, with loss computed only on response tokens.

We submit our system under the team name **NoviceTrio**. Table 1 shows that Qwen3 achieves the best overall performance (Macro-F1 = 0.333, RMSE = 1.06), slightly outperforming RoBERTa (0.331, 1.146), while both models significantly surpass BERT (0.313, 1.255) and the CLPsych 2026 baseline (0.247, 1.424). RoBERTa, however, provides a strong trade-off between performance and computational efficiency.

Ablation results in Table 5 show that most components are critical for performance. In particular, removing the presence regression head, weighted sampling, or element constraints leads to notable degradation, while freezing the encoder in Stage 2 results in the largest drop, highlighting the importance of joint optimization across stages.

[3] https://github.com/unslothai/unsloth

5 Discussion

Stronger and better-optimized models consistently yield superior performance: Qwen3 achieves the highest Macro F1 and lowest RMSE, followed by RoBERTa, with BERT trailing. Results suggest that architecture and task design may play an important role, although further experiments are needed.

The ablation study indicates that performance is primarily driven by Stage-2 design and end-to-end optimization. Multi-task learning in Stage 1 improves representations (A1), while addressing class imbalance is critical for stability (A2). Hierarchical transfer from Stage 1 to Stage-2 is beneficial (A3). In Stage-2, the BIO span head and validity mask provide effective inductive biases (A4–A5). The encoder shows some robustness to input noise (A6), but freezing it leads to severe degradation (A7), highlighting the importance of full fine-tuning. Overall, representation learning, structural constraints, and fine-tuning are key drivers of performance.

6 Conclusion

We propose a relatively lightweight hierarchical framework for fine-grained self-state modeling designed for CPU-only and low-compute environments. Instead of relying on large-scale model exploration, the focus is on efficiency while maintaining competitive performance across different backbones, including BERT, RoBERTa, and a quantized Qwen3 model.

Experimental results show consistent gains across models. Qwen3 achieves the highest Macro-F1, although performance differences are small. While RoBERTa offers a strong balance between accuracy and efficiency, including an 8.3% improvement in Macro-F1 over the CLPsych 2026 baseline. Despite Qwen3 being much larger, its performance is close to RoBERTa, indicating that the hierarchical design effectively captures task structure without requiring large parameter growth.

The method leverages hierarchical multi-task learning to exploit shared representations across interdependent subtasks, improving efficiency and modularity. In terms of sustainability, encoder-based models are significantly more energy-efficient, with BERT and RoBERTa producing far lower carbon emissions than Qwen3, highlighting

the environmental benefits of lightweight architectures.

However, there remains a performance gap of about 0.11 compared to the top-ranked system. Future work will explore joint modeling of timelines and reducing error propagation in multi-stage pipelines to further improve accuracy and computational efficiency.

Limitations

The study has several limitations. First, the exploration of model space is limited to a small set of backbones, restricting generalizability to other architectures. Second, a notable performance gap to the state-of-the-art remains, suggesting that the proposed framework does not capture all relevant signals. Third, the ablation study is limited in scope and does not examine alternative architectural designs. Fourth, evaluation on a single benchmark raises concerns about domain-specific overfitting and limits claims of generalization. Finally, the lack of detailed interpretability analysis constrains understanding of component-level contributions, which is particularly important in clinical applications. Additionally, encoder models were trained with fixed hyperparameters without search; exploring alternative learning rates and batch sizes remains future work.

Ethics Statement

This study uses the CLPsych 2026 shared task dataset, an extension of the "Reddit-New" corpus from the CLPsych 2022 Shared Task (Tsakalidis et al., 2022): Capturing Moments of Change in Longitudinal User Posts, which contains sensitive, de-identified mental health–related content. We adhere to the shared task Data Access Agreement and follow established ethical guidelines such as Ethical Research Protocols for Social Media Health Research (Benton et al., 2017). The dataset is used solely for research purposes within the approved scope, stored securely, and will be deleted after the permitted period. We do not redistribute the data. We do not attempt to re-identify users, and all examples presented in this paper are paraphrased to protect privacy. In compliance with task rules, we use only open-source models (e.g., BERT, RoBERTa) and avoid proprietary systems such as ChatGPT, Claude, and Gemini.

References

Iqra Ali, Talia Tseriotou, Guy Dvir, Callum Chan, Yuxiang Zhou, Juan Antonio Lossio-Ventura, Ayal Klein, Aya Shamir, Dan Sayda, Anthony Hills, Aya Zirikly, Diana Inkpen, Dana Atzil-Slonim, and Maria Liakata. 2026. Overview of the clpsych 2026 shared task: Capturing and characterizing mental health changes through social media timeline dynamics. In *Proceedings of the 11th Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Dana Atzil-Slonim. 2025. Multimodal intrapersonal and interpersonal dynamics (mind): A transtheoretical coding manual.

Dana Atzil-Slonim. 2026. Leveraging theoretical and technological innovations to study the mechanisms that underlie therapeutic change in psychotherapy. In Louis G. Castonguay, Dana Atzil-Slonim, Michael Barkham, and Wolfgang Lutz, editors, *Practice-Based Evidence in the Psychological Therapies: Toward Policy Implications for Research, Training, and Clinical Guidelines*. Oxford University Press, New York.

Adrian Benton, Glen Coppersmith, and Mark Dredze. 2017. Ethical research protocols for social media health research. In *Proceedings of the First ACL Workshop on Ethics in Natural Language Processing*, pages 94–102, Valencia, Spain. Association for Computational Linguistics.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.

Giulia Ferraro and Luca Benedetti. 2025. Hierarchical multi-task learning for fine-grained and coarse text classification. *Frontiers in Interdisciplinary Applied Science*, 2(2):184–190.

Edward J Hu, yelong shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized BERT pretraining approach. *CoRR*, abs/1907.11692.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder,

Paul F Christiano, Jan Leike, and Ryan Lowe. 2022. Training language models to follow instructions with human feedback. In *Advances in Neural Information Processing Systems*, volume 35, pages 27730–27744. Curran Associates, Inc.

Sebastian Ruder. 2017. An overview of multi-task learning in deep neural networks. *CoRR*, abs/1706.05098.

Dana Atzil Slonim. 2024. Self-other dynamics (sod): A transtheoretical coding manual.

Bing Tian, Yong Zhang, Jin Wang, and Chunxiao Xing. 2019. Hierarchical inter-attention network for document classification with multi-task learning. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI-19*, pages 3569–3575. International Joint Conferences on Artificial Intelligence Organization.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Talia Tseriotou, Jenny Chim, Ayal Klein, Aya Shamir, Guy Dvir, Iqra Ali, Cian Kennedy, Guneet Singh Kohli, Anthony Hills, Ayah Zirikly, and 1 others. 2025. Overview of the clpsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 193–217.

Ana-Sabina Uban, Berta Chulvi, and Paolo Rosso. 2021. An emotion and cognitive based analysis of mental health disorders from social media data. *Future Generation Computer Systems*, 124:480–494.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. *Advances in Neural Information Processing Systems*, 30.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, and 1 others. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in Neural Information Processing Systems*, 35:24824–24837.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, and 3 others. 2020. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 38–45, Online. Association for Computational Linguistics.

A Appendices

A.1 Task and Dataset

The dataset statistics are provided in Table 2. A large proportion of posts contain both adaptive and maladaptive states (approximately 47%), with maladaptive states rated as more psychologically central than adaptive ones (mean presence 3.23 vs. 2.39). Maladaptive self-states are most strongly expressed through negative Affect (A; 68%) and Self-Criticism (C-S; 57%), while adaptive states are predominantly characterised by relational Behaviour (B-O; 53%) and Desire for connection (D; 50%). Longitudinal change events — self-state switches (21%) and escalations (20%) — are distributed across 90% of training timelines, motivating temporal modelling as a core system component.

Statistic	Train	Test
Timelines / Posts	30 / 373	10/92
Annotated posts	236 (63%)	0 (0%)
Posts per timeline (mean/max)	12.43 / 25	9.2 / 11
Post length in words (mean)	114	115.46
Both states present	177 (47.4%)	NA
Adaptive state	203 (54%)	NA
Maladaptive state	210 (56%)	NA
Most freq. adaptive element	B-O	NA
Most freq. maladaptive element	A	NA

Table 2: Training and test data statistics

A.2 Instruction-Tuned LLM Pipeline with Transformer-based Decoder

We propose a multi-stage framework for structured psychological state prediction from social media posts as depicted in Figure 2. Given an input post x, the goal is to generate a hierarchical output y capturing (i) adaptive and maladaptive states, (ii) associated psychological elements, (iii) fine-grained categories with supporting evidence, and (iv) overall presence scores.

Instead of solving this as a single complex prediction problem, we decompose it into four sequential stages, each implemented using an instruction-tuned large language model with parameter-efficient fine-tuning.

We use an instruction-tuned causal language model fine-tuned with Low-Rank Adaptation (LoRA). All stages share the same base model, which is sequentially fine-tuned on stage-specific

instruction–response data. This allows the model to progressively specialize while maintaining a unified parameter space.

A.2.1 Step 1: State Detection

In the first stage, the model determines whether the post expresses adaptive and/or maladaptive states, and assigns a presence score (1–5) to each. The output is a structured JSON object containing binary labels and ordinal scores. Which is, $z_1 = (s_a, p_a, s_m, p_m) = f_1(x)$.

A.2.2 Step 2: Element Identification

Given the detected states, the model identifies which psychological elements are present. We consider a predefined set of elements $\{A, B\text{-}O, B\text{-}S, C\text{-}O, C\text{-}S, D\}$. The model outputs only those elements that are explicitly expressed in the post. Which is, $z_2 = \mathcal{E} = f_2(x, z_1)$.

A.2.3 Step 3: Category and Evidence Extraction

For each identified element, the model predicts a fine-grained subcategory and extracts the corresponding supporting text span from the post. The evidence is required to be an exact substring of the input, ensuring interpretability and traceability of predictions, i.e., $z_3 = \{(c_e, \tilde{x}_e) \mid e \in \mathcal{E}\} = f_3(x, z_2)$.

A.2.4 Step 4: Presence Estimation

Finally, the model predicts an overall presence score (1–5) for each detected state, conditioned on the elements and their associated evidence. This step refines the initial estimate from Step 1 using more granular information, that is, $z_4 = (p'_a, p'_m) = f_4(x, z_2, z_3)$.

Each stage is trained independently using supervised fine-tuning with instruction–response pairs constructed from annotated data. We use the standard causal language modeling objective, where the model learns to generate the target response given the input prompt.

The loss is computed only over response tokens, masking out the instruction part of the input. No task-specific loss functions are introduced.

A.2.5 Inference

At inference time, predictions are generated sequentially in a chained manner. The output of each stage is used to construct the prompt for the next stage. This decomposition simplifies the overall task and improves interpretability, as intermediate predictions (e.g., elements and evidence) are explicitly exposed. So the final output we receive from, $y = (z_1, z_2, z_3, z_4)$ where,

$$
\begin{aligned}
z_1 &= f_1(x) \\
z_2 &= f_2(x, z_1) \\
z_3 &= f_3(x, z_2) \\
z_4 &= f_4(x, z_2, z_3)
\end{aligned}
$$

The prompts used in four stages of Method 2 are given in Table A.2.



Figure 2: Four-stage approach using the Qwen3 model to solve the task.

A.3 Ablation study

The ablation study conducted only on the first method, which uses a controlled hold-out validation setup, where the training data is split into 85% train and 15% validation with a fixed seed, and all variants are trained and evaluated on the same splits for fair comparison. Stage 1 is trained on the full training set for binary classification and evaluated on the validation set, while Stage-2 is

Stage	Inputs injected	Prompt text
Stage 1	post — the raw social media text DEFINITIONS_BLOCK — full adaptive + maladaptive sub-element taxonomy PRESENCE_DEF — 1–5 scale definition	You are a clinical psychologist. Read this post and determine whether it expresses an ADAPTIVE state (conducive to fulfilling basic needs) and/or a MALADAPTIVE state (hindering basic needs), plus the presence score (1-5) for each. [DEFINITIONS_BLOCK injected here] Presence scale: 1=Not present … 5=Highly present. Post: """[post]""" Answer with valid JSON only (no prose): {"adaptive":"yes/no","adaptive_presence":1-5, "maladaptive":"yes/no","maladaptive_presence":1-5}
Stage 2	post — social media text state — "adaptive" or "maladaptive" sub-element list — dynamically selected for the given state	You are a clinical psychologist. Post: """[post]""" For the [ADAPTIVE/MALADAPTIVE] state, identify which ABCD elements are expressed. Sub-elements: A: (1) Calm/laid back, (3) Sad/Emotional pain … B-O: (1) Relating behavior … … [state-specific sub-elements injected] List only elements that are clearly present. Answer with valid JSON only: {"elements": ["A","B-O",...] or []}
Stage 3	post — social media text state — "adaptive" or "maladaptive" element — one of {A, B-O, B-S, C-O, C-S, D} options list — sub-labels valid for this element × state	You are a clinical psychologist. Post: """[post]""" For the [ADAPTIVE/MALADAPTIVE] state, element [e], choose the best sub-category from: (1) Self care and improvement (2) Self harm, neglect and avoidance … [element-specific options injected] Also copy the EXACT span from the post that best supports this. Answer with valid JSON only: {"Category":"<sub-category>", "highlighted_evidence":"<exact span>"}

Stage 4	post — social media text
	state — "adaptive" or "maladaptive"
	elements_info — JSON dict of {element → {Category, highlighted_evidence}} from Stage 3 output
	PRESENCE_DEF — 1–5 scale definition
		You are a clinical psychologist.
		
		Presence scale: 1=Not present … 5=Highly present.
		
		Post: """[post]"""
		
		The [ADAPTIVE/MALADAPTIVE] state was identified with these elements:
		{
		"A": {"Category": "(1) Calm/laid back",
		"highlighted_evidence": "..."},
		"C-S": {"Category": "(1) Self-acceptance…",
		"highlighted_evidence": "..."}
		}
		[elements_info JSON injected from Stage 3]
		
		Rate the overall PRESENCE of the [ADAPTIVE/MALADAPTIVE] state (1-5).
		
		Answer with valid JSON only:
		{"presence": <1-5>}

Table 3: Prompts used across the four stages in Method 2.

trained and evaluated only on positively labeled instances expanded into element-level records. Starting from the full model (A0) as the baseline, we introduce controlled modifications targeting: (i) Stage 1 learning design, including removal of the auxiliary regression head (A1) and disabling class-balanced sampling (A2), to assess the impact of multi-task supervision and imbalance handling on representation learning; (ii) cross-stage knowledge transfer, where Stage-2 is trained without initialization from Stage 1 (A3), to quantify the benefit of hierarchical pretraining; (iii) Stage-2 task formulation, by removing the token-level BIO evidence span head (A4), to examine the role of span supervision; (iv) structural constraints, by disabling element-specific validity masking over label space (A5), to evaluate the importance of inductive bias; (v) input preprocessing, by omitting text cleaning (A6), to measure robustness to noisy input; and (vi) fine-tuning strategy, by freezing the encoder during Stage-2 training (A7), to analyze the necessity of full model adaptation. Each variant alters exactly one component while keeping all other settings fixed, enabling precise attribution of performance differences to individual design choices.

The summary of results of ablation study is provided in Table 5.

A.4 Carbon Footprint

We measure the environmental impact of our models using CodeCarbon [4]. Training is conducted on NVIDIA A100 80GB PCIe, and emissions are estimated based on energy consumption and regional carbon intensity. Our results show that BERT and RoBERTa incur significantly lower emissions (0.018 kg and 0.032 kg CO_2 eq, respectively) compared to Qwen3 (0.111 kg), reflecting the efficiency advantages of encoder-based architectures. The result depicted in Table 4.

Model	Hardware	Training Time	CO_2 (kg)
BERT	A100	492.44	0.018
RoBERTa	A100	660.89	0.032
Qwen3	A100	2749.42	0.111

Table 4: Carbon emissions measured for different models using the CodeCarbon Python package.

A.5 Codabench Submission

We name our submission **NoviceTrio**. Submission ID 662787, submitted during the competition phase, was produced using Method 1 with BERT (bert-base-uncased). Submission ID 706280 in the analysis phase also used Method 1 but with RoBERTa (roberta-base), while Submission ID 705090 in the analysis phase used Method 1 with Qwen3 (Qwen3-4B-Instruct-2507). The code for training, preprocessing, post-processing, and ablation studies is publicly available on our GitHub repository.

[4] https://github.com/mlco2/codecarbon

DELTA vs BASELINE (A0)					
ID	Variant	S1-Adap	S1-Malad	S2-Adap-Cat	S2-Malad-Cat
A1	No presence regression head	-0.01	-0.0404	-0.1137	-0.0137
A2	No weighted sampling	0.0072	-0.1027	-0.0444	0.0648
A3	No Stage 1 pre-training for Stage-2	0	0	-0.0789	0.0142
A4	No evidence span head (Stage-2)	0.0171	0	-0.034	-0.0452
A5	No element validity mask (Stage-2)	0.0171	-0.0177	-0.109	-0.0156
A6	No text cleaning	0.0171	-0.0012	-0.0714	0.0167
A7	Frozen encoder in Stage-2	0	0	-0.3517	-0.1322

Table 5: Change (delta) in performance compared to the full model or baseline (A0).

McMasters of Change: Predicting Wellbeing States and Transitions from Longitudinal Language

Hongyi Zhang[1*], Derron Li[1], Scarlett Cleary[1], Aadi Sanghani[1], Akshay Krishna Sirigana[1], Brian Miguel Pimentel[1], Kelsey Isman[2], Kian Omoomi[1], Vasudha Varadarajan[3], Charles Welch[1], Allison Lahnala[1*]

[1]McMaster University, Department of Computing and Software, Hamilton, ON, Canada
[2]Indiana University, Department of Psychological and Brain Sciences, Bloomington, IN, USA
[3]Carnegie Mellon University, Language Technologies Institute, Pittsburgh, PA, USA

[*]**Correspondence**: {zhanh279,lahnalaa}@mcmaster.ca

Abstract

Most existing work on mental health prediction from language focuses on isolated posts, overlooking temporal dynamics in longitudinal timelines. We present McMaster NLP's system for the CLPsych 2026 Shared Task, which centers on modeling mental health dynamics in social media timelines using the MIND framework (Atzil-Slonim, 2025). The task comprises: (1) identifying adaptive and maladaptive self-state components within posts, (2) detecting moments of change in wellbeing, and (3) generating structured summaries. For self-state prediction, we leverage LLM-generated archetypal representations of language use as semantic anchors within a dual-encoder architecture, enabling interpretable prediction of subelements and their intensities through alignment with prototypical expressions of psychological states. For temporal dynamics, we use BiLSTM-based sequence models to detect moments of change. For summarization, we employ a prompt-based LLM to generate grounded, structured summaries emphasizing causal interactions and temporal progression of self-states. Finally, we analyze model failure modes with respect to human evaluation and identify directions for reconciling the MIND framework with how state-assessment models encode meaning.

1 Introduction

Mental health disorders affect over one billion people worldwide, impacting reasoning, emotions, and social behaviour (Stein et al., 2020; World Health Organization, 2025). Early detection is critical to alleviate the severe consequences of these conditions, yet traditional methods for assessing mental health largely rely on face-to-face interviews, self-reporting, or questionnaires, which are limited by bias and barriers to care (Lin et al., 2017). Natural Language Processing (NLP) models of language on social media have the potential to overcome these limitations by leveraging behavioural and linguistic cues to model mental health at scale (Atzil-Slonim, 2026), but most prior work focuses on analyzing individual posts in isolation (Chancellor and De Choudhury, 2020). Longitudinal analysis of temporally ordered social media timelines remains comparatively understudied (Tsakalidis et al., 2022).

We present our submission to the CLPsych 2026 Shared Task (Ali et al., 2026), which addresses modeling mental health dynamics in social media timelines using the MIND framework (Atzil-Slonim, 2024, 2025). The task comprises: (1) identifying adaptive and maladaptive self-state components within posts, including dominant ABCD subelements and presence levels; (2) detecting moments of change in wellbeing, including both abrupt transitions (switches) and gradual progressions (escalations); and (3) generating structured summaries of self-state sequences surrounding change events. The task extends the prior year's shared task (Tseriotou et al., 2025) with finer-grained application of the MIND framework.

We propose a multi-stage framework combining representation learning, sequence modeling, and prompt-based summarization (Figure 1). For Task 1, we employ a dual-encoder pipeline that integrates contextual semantic embeddings with alignment features derived from prototypical ABCD self-state descriptions, followed by multi-output classification and regression models to predict subelements and presence scores. For Task 2, we model timelines as ordered sequences using BiLSTM architectures to capture temporal dependencies and identify both abrupt and gradual changes in wellbeing. For Task 3, we adopt an iterative prompt-engineering approach with an LLM to generate summaries that capture self-state dynamics and change processes.

Our analysis reveals systematic failure modes in how encoding models represent psychological con-

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 482–497
July 4, 2026 ©2026 Association for Computational Linguistics

structs, including a tendency to overpredict adaptive states and to conflate stylistic cues such as verbosity with markers of wellbeing. We further examine the operationalization of wellbeing through the GAF scale used in the shared task, discussing its limitations with respect to construct and ecological validity, and suggest future work explore alternative operationalizations with updated wellbeing measures adapted to social media contexts.

2 Methodology

TASK 1: POST-LEVEL ABCD SUBELEMENT CLASSIFICATION AND PRESENCE REGRESSION. The objective is to identify adaptive and maladaptive self-states expressed in posts using the MIND framework, which is divided into identifying dominant ABCD elements and subelements (Sub-task 1.1) and estimating the degree of presence of each self-state within a post (Subtask 1.2). We approach Task 1 as a feature-engineering problem solved by per-target linear models, motivated by the small labeled corpus (30 timelines). Each post is represented by an 800-dimensional vector formed by concatenating two complementary encodings. The first is a 768-dimensional contextual embedding obtained by mean-pooling the final hidden states of `mental/mental-roberta-base`, a RoBERTa variant adapted to the mental-health domain (Ji et al., 2022). For the rest of the 32-dimensions, we used the archetype framework (Varadarajan et al., 2024; Mahwish et al., 2026). We derive a vector of cosine similarities between the post and 32 first-person sentences of the ABCD framework that were generated by ChatGPT 5.1 (see Appendix B). Posts and archetypes are independently encoded by `sentence-transformers/all-MiniLM-L6-v2` (Reimers and Gurevych, 2019; Reimers, 2021), an encoder optimized for semantic textual similarity. This dual-encoder design separates the two roles of the representation: MentalRoBERTa captures rich mental-health-related contextual semantics, while MiniLM provides linguistic alignment scores against each ABCD archetype.

Given these 800-dimensional features, we train two independent linear systems. For Subtask 1.1, we fit one multinomial logistic regression per element × valence target, wrapped in a `MultiOutputClassifier`. Each target is a single multi-class label where class 0 means "element absent" and classes $1 \ldots K$ index the subelement ($K \in \{2, 4, 6, 14\}$, depending on the element). For Sub-task 1.2, we fit a ridge regressor (α=1.0) for each of the two presence scores using a `MultiOutputRegressor`; predictions are bounded to $[1, 5]$ and rounded to integers.

Both systems are trained on an 80/20 split made at the timeline level, so no timeline appears in either half. We augment the training data using `ModernBERT-base` to fill ABCD-conditioned masked tokens and discard low-quality generations, growing the training set from 312 to 495 posts ($+58.7\%$).

TASK 2: IDENTIFYING MOMENTS OF CHANGE. The objective is to detect moments of change in wellbeing, which is broken into detecting abrupt transitions (*switches*, Sub-task 2.1) and gradual development from mild to more extreme states (*escalations*, Sub-task 2.2). We address the two sub-tasks with complementary models that share the same `mental/mental-roberta-base` post encoder, motivated by their different temporal characters: switches are sharp transitions, whereas escalations span over the timeline.

For Sub-task 2.1, we frame the problem as wellbeing regression followed by a difference-based decision rule. Each post is represented by a 780-dimensional feature vector that concatenates (i) ten cosine similarities between the post and ten GAF-aligned archetype sentences encoded using `all-MiniLM-L6-v2` (Reimers and Gurevych, 2019; Reimers, 2021), (ii) the previous post's wellbeing score, (iii) a Language Style Matching (LSM) score (Ireland and Pennebaker, 2010) with the previous post, and (iv) the 768-dimensional mean-pooled MentalRoBERTa embedding of the current post. A Ridge regressor predicts the wellbeing score $\hat{y}_t$, and a post is labeled as a switch whenever $|\hat{y}_t - \hat{y}_{t-1}| \geq 2$, mirroring the two-point gap that the annotation guidelines associate with clinically salient transitions.

For Sub-task 2.2 (Escalation), posts in a timeline are arranged chronologically into a $(T, 768)$ MentalRoBERTa embedding sequence and fed to a single-layer bidirectional LSTM (Schuster and Paliwal, 1997). Although an ablation also explored concatenating the wellbeing score and per-timeline Δwellbeing (each projected to 32 dimensions inside the network), these scalar features did not yield consistent gains over the embedding-only configuration, and the trend information they carry is largely captured by the BiLSTM's temporal mod-

eling. Given that only ∼24 timelines are available for training, the network is optimized with `BCEWithLogitsLoss` whose `pos_weight` is set to the negative-to-positive ratio of the training labels to mitigate the heavy class imbalance.

TASK 3: SUMMARY OF CHANGE. The goal is to characterize and summarize psychological change dynamics surrounding moments of change in social media timelines, which is split into generating sequence-level summaries of self-state progression around change events (Sub-task 3.1) and identifying recurrent dynamic signatures of deterioration and improvement across multiple timelines (Subtask 3.2). We use Qwen3.5-9B (Team, 2026) in a two-stage, prompt-based pipeline *without* model fine-tuning, where both stages rely on carefully structured prompts to enforce consistency, grounding, and interpretability.

For Task 3.1, the prompt specifies explicit temporal segmentation, requiring the model to anchor descriptions in time and identify a single dominant change process, while also characterizing how psychological states evolve. It further enforces relational reasoning by directing the model to describe interactions among ABCD elements in terms of reinforcing or suppressive dynamics, rather than listing them independently. Additional constraints ensure that all inferences remain grounded in the provided data and that outputs emphasize causal explanatory structures over surface-level description.

For Task 3.2, the prompt is designed to extract structured change signatures by guiding the model to implicitly group and compare patterns before synthesizing them into concise representations. It enforces grounding in prior summaries, limits redundancy by constraining the number of supporting examples, and requires uniqueness and specificity in the extracted evidence. Our prompts can be found in Appendix D.

3 Results

Tables 2–6 summarize our official results for all tasks. Each task's results show the comparison of our system against the shared-task baseline. Our systems consistently outperformed the provided baselines on Task 1, showed mixed results on Task 2, and had competitive behaviour in selected cases for Task 3.

Our system ranked seventh for Task 1.1, outperforming the baseline across all reported metrics. On the primary ranking metric, Avg Sub Macro F1, our system achieved 0.351 compared with the baseline score of 0.247. The largest improvement was observed in predicting adaptive subelements, where our system achieved 0.317 compared with the baseline's 0.156. These results suggest that the MentalRoBERTa-based representation and ABCD archetype similarity features helped capture subelement-level distinctions, particularly for categories involving broader semantic information.

For Task 1.2, our system also ranked seventh and improved over the baseline on the primary metric. Improvements were observed for both maladaptive and adaptive presence ratings, with Mal RMSE decreasing from 1.439 to 0.957 and Adp RMSE decreasing from 1.409 to 1.112. However, the baseline obtained slightly higher QWK and Spearman correlation scores, indicating that although our model produced more accurate absolute predictions, its ordinal agreement and rank correlation with the gold ratings were not consistently better than the shared-task baseline.

For Task 2, our system ranked eleventh on the combined Macro F1 metric. It achieved a combined Macro F1 of 0.412, outperforming the Llama zero-shot baseline and the Llama zero-shot plus Task 1.1 baseline, but falling below the TempoFormer baseline. At the post level, our system obtained 0.375 escalation F1, 0.357 Macro F1, and 0.339 switch F1. At the timeline level, performance was stronger for escalation detection, where our system reached 0.660 escalation F1, but lower for switch detection, with a score of 0.274 switch F1. This suggests that the system was more effective at identifying broad escalation regions than detecting exact switch points. The gap between escalation and switch performance highlights the difficulty of localizing discrete moments of change in longitudinal sequences.

For Task 3.1, our system ranked ninth by average rank. It achieved strong consistency (CS) and contradiction (CT) scores, with CS = 0.770 and CT = 0.761, both slightly higher than the two baselines. However, it performed worse on content-overlap metrics, obtaining a ROUGE-L Recall of 0.208 and BERTScore Recall of 0.255. This pattern suggests that our LLM-based prompting strategy produced summaries that were coherent and avoided contradiction, but sometimes missed specific gold-reference content. In other words, the system favored internally consistent and non-contradictory summaries over maximal lexical or semantic coverage.

For Task 3.2, our system showed asymmetric

performance across improvement and deterioration directions. For improvement signatures, our system ranked fourth and outperformed the baseline on fit, specificity, and overall score, achieving an overall score of 0.594 compared with the baseline's 0.389. However, for deterioration signatures, our system ranked eighth and underperformed the baseline, with an overall score of 0.211 compared with 0.483. This indicates that the model was more effective at identifying patterns of improvement than deterioration. One possible explanation is that improvement signatures may contain more explicit recovery cues, whereas deterioration may involve subtler or more gradual negative changes that are harder to summarize reliably.

Taken together, the results show that our strongest performance was obtained on Tasks 1.1 and 1.2, where embedding and archetype-based features consistently improved over the baselines. For Task 2, the model captured escalation more effectively than switch localization, suggesting that future work should focus on temporal boundary modeling. For Tasks 3.1 and 3.2, the results suggest that prompt-based summarization can produce coherent outputs, but further work is needed to improve content recall and robustness for deterioration-oriented explanations.

4 Analysis

TASK 1. We perform error analysis on a held-out 20% split of the training data (46 posts, 6 timelines), examining: (i) element-level false positives and false negatives; (ii) subelement identity errors given correct presence detection; and (iii) stylistic correlates of error.

Asymmetry of adaptive/maladaptive model predictions. The model overpredicts adaptive elements: in 8 of 9 posts with no true adaptive labels, the model incorrectly assigns at least one adaptive label. Overall, this results in 74 false positive (FP) adaptive element instances, compared to 27 for maladaptive elements. Per-element adaptive FP rates range from 41.7% to 64.1%, versus 14.3%–38.7% for maladaptive, indicating a clear bias toward predicting adaptive self-states broadly.

Subelement confusion on affect and desire. We plot confusion matrices for each element–valence pair (Figure 4). Errors are concentrated in the adaptive elements of affect (A; 7 subelements) and desire (D; 3 subelements). Even when the model correctly detects the presence of an adaptive A element, it identifies the correct subelement only 20.0% of the time; for adaptive D, this improves to 47%. Since affect and desire are among the most abstract dimensions in the MIND framework, these patterns suggest the model captures general emotional tone but struggles to distinguish finer-grained self-state distinctions.

Errors associated with style and themes. We analyze how error rates vary with post style by manually annotating 46 posts for seven features (e.g., length, self-deprecation, suicidality), with consensus labels from two annotators. We then test associations between features and error counts using nonparametric tests with Bonferroni correction. The most striking result is that longer posts and self-deprecating language substantially increase adaptive FPs. For example, long posts yield over 4× more adaptive FPs than short ones. This suggests the model systematically misinterprets verbosity and self-critical tone as signals of adaptive coping, rather than vulnerability.

TASK 2. Since Task 2 is defined over longitudinal emotional development, we analyze model behavior at the timeline level rather than post-level error analysis. Individual posts may contain partial evidence of escalation, while the S/E process is better understood as a gradual development across multiple posts.

Task 2.1 ablation results (Figure 2) show that predicting the continuous wellbeing score with Ridge regression and then applying a threshold generally outperforms direct binary switch classification with Logistic Regression. This suggests that switches are more naturally modeled as changes in continuous wellbeing dynamics rather than as isolated binary post-level events.

For Task 2.2, Figure 5 shows the BiLSTM probability curves are relatively smooth and often increase around gold escalation spans, suggesting that the model captures broad temporal patterns rather than reacting only to isolated posts. However, the model sometimes starts increasing slightly before the annotated span or remains high after the span ends. These cases indicate that many errors are better understood as boundary-localization or probability-calibration errors rather than complete post-level misclassifications.

Finer-grained error analysis reveals a consistent pattern across both sub-tasks. For Task 2.1, the error-rate-by-P(Switch) bucket plot (Figure 6) shows errors concentrated in mid-confidence buckets, while high- and low-confidence predictions

have better performance; the error-rate-vs-post-length plot is roughly flat (Figure 7), with only very short posts showing slightly higher error rates due to limited textual signal. For Task 2.2, the BiLSTM diagnostics follow a similar pattern: errors are localized in the mid-P(E) range rather than at the extremes (Figure 8), and post length shows no strong monotonic effect on error rate (Figure 9). Together, these results indicate that Task 2 errors are driven mainly by borderline, ambiguous posts near trajectory boundaries rather than by surface-level post length.

Overall, Task 2 performance appears to be driven by the model's ability to learn gradual wellbeing dynamics from timeline-level context. Because S/E escalation is a developmental process with discrete annotated boundaries, small mismatches between predicted and gold spans are expected.

5 Discussion and Future Work

Finally, we raise a further discussion about the operationalization of "wellbeing" and avenues for future work. The Global Assessment of Functioning (GAF) is a measure of illness severity that was included in multiple previous iterations of the Diagnostic and Statistical Manual (DSM) (Piersma and Boes, 1997). However, due to concerns regarding reliability and clinical utility (Abuse and Administration, 2016), the APA replaced the GAF in the DSM-5 with the World Health Organization Disability Assessment Schedule (WHODAS-2). Previous work has found GAF to have weak inter-rater reliability (Grootenboer et al., 2012; Vatnaland et al., 2007), and requires clinicians to assign a value 0-100 to describe the patient's impairment, where lower scores indicate greater functional impairment and higher scores indicate better overall functioning. The WHODAS-2, on the other hand, is a semi-structured questionnaire measuring functioning across different domains, combined into a total disability score (Gspandl et al., 2018).

This background points to avenues for future work into operationalizations of wellbeing to address its *construct validity* and *ecological validity*. Regarding construct validity, while our model's performance in Sub-task 2.1 (detecting *switches*) reflect limitations in our model design, the current GAF-based wellbeing operationalization may be more limited in measuring the underlying latent construct than a measure like WHODAS-2, considering the aforementioned psychology literature. Weaker construct validity suggests a weakened ability to accurately capture the intended clinical construct across modeling approaches. Therefore, future research could investigate operationalizations based on the WHODAS-2 and/or a more direct measure of clinical wellbeing such as the WHO-5 wellbeing Index (Topp et al., 2015). However, applying a measure designed for clinician administration, which relies on clinical expertise and understanding of the patient, to social media posts is a significant departure from its intended use and domain; this implies weaker ecological validity. This contextual difference may introduce additional noise to the labels on top of the GAF scale's existing limitations. Therefore, updating the wellbeing measurement instrument with an existing validated clinical instrument alone may not be sufficient; rather, empirical investigations are needed into clinically-relevant measurement instruments adapted to the social media context.

6 Conclusion

We presented a multi-stage framework for modeling mental health dynamics in longitudinal social media data for the CLPsych 2026 Shared Task, combining LLM-generated archetypes for self-state prediction, sequence modeling for change detection, and prompt-based summarization. Our results showed that LLM-derived archetype representations, constructed without any clinical expertise, can still improve over purely encoder-based approaches while remaining interpretable. This offers a promising alternative to relying solely on extensively validated, time-consuming, manually constructed archetypes. Our analyses highlighted systematic mismatches in the MIND framework and the performance of encoding models: our models overpredict adaptive states, collapse distinctions between affect and desire, and misread stylistic cues such as verbosity or self-deprecation as signs of wellbeing. These patterns suggest that models rely on surface-level signals rather than capturing underlying psychological structure. This highlights the need for tighter alignment between theory-driven constructs and learned representations in longitudinal mental health modeling. Finally, we reflected on the operationalization of wellbeing in this shared task, and suggested future directions that explore alternative operationalizations with updated wellbeing measurement instruments adapted for social media posts.

Limitations

This study has several limitations. First, the data is limited to English social media posts and does not include author demographic information. Therefore, our findings may not generalize across languages, platforms, cultures, or specific demographic groups.

Second, the dataset is highly imbalanced. Some ABCD subelements have very few or even no training examples, and some classes are extremely sparse or missing. This limits the generalizability of standard classifiers or regressors, which may overfit frequent labels and perform poorly on rare classes.

Third, we did not explore a sequential or joint pipeline across subtasks. Although predictions from one task could potentially inform another, such a setup may also introduce noise. Future work should investigate whether joint modeling can improve consistency while reducing downstream error.

Fourth, our Task 3 system was mainly based on prompt engineering, and we did not conduct a broad comparison across different LLMs or summarization methods. Thus, the results reflect one prompting-based approach rather than a comprehensive model comparison.

Finally, our archetype similarity features were based on LLM-generated archetypes. While these provided richer semantic descriptions than label names alone, they may contain biases or incomplete interpretations. Future work should involve clinical experts in writing or validating archetypes, as well as in assessing the safety, practicality, and clinical relevance of the overall approach.

Ethics

Although this work may help inform clinical practice, it is critical that the implications of our findings are considered in combination with intervention by mental health professionals. Mental health conditions are highly prevalent and often go untreated, especially in marginalized communities (Cook et al., 2017). As such, machine learning models may be useful in early detection of mental health challenges through social media language that may otherwise go undetected. This technology should be utilized as a way to connect individuals to mental health care who might otherwise lack access rather than be used as a way to deliver or replace psychiatric intervention.

It is also critical to consider the stigma associated with mental health conditions when analyzing social media language related to maladaptive behaviors (Clement et al., 2015). Interventions or other mental health detection strategies informed by this work should be carefully designed with the input of clinicians to avoid further stigmatization of those at risk of mental illness.

Acknowledgments

This work is supported in part by the McMaster University's Faculty of Engineering, Department of Computing and Software via start-up funding awards issued to Dr. Charles Welch and Dr. Allison Lahnala. We acknowledge the support of the Natural Sciences and Engineering Research Council of Canada (NSERC) for funding Dr. Welch's Discovery Grant. The conclusions and opinions reflect those solely of the authors and are not attributable to institutes at McMaster University, Indiana University, Carnegie Mellon University, or NSERC.

References

Substance Abuse and Mental Health Services Administration. 2016. Dsm-5 changes: Implications for child serious emotional disturbance [internet].

Iqra Ali, Talia Tseriotou, Guy Dvir, Callum Chan, Yuxiang Zhou, Juan Antonio Lossio-Ventura, Ayal Klein, Aya Shamir, Dan Sayda, Anthony Hills, Aya Zirikly, Diana Inkpen, Dana Atzil-Slonim, and Maria Liakata. 2026. Overview of the clpsych 2026 shared task: Capturing and characterizing mental health changes through social media timeline dynamics. In *Proceedings of the 11th Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Dana Atzil-Slonim. 2024. *Self-Other Dynamics (SOD): A Transtheoretical Coding Manual*. Bar-Ilan University. Transtheoretical coding manual for psychotherapy research.

Dana Atzil-Slonim. 2025. Multimodal intrapersonal and interpersonal dynamics (mind): A transtheoretical coding manual. Open Science Framework.

Dana Atzil-Slonim. 2026. Leveraging theoretical and technological innovations to study the mechanisms that underlie therapeutic change in psychotherapy. In Louis G. Castonguay, Dana Atzil-Slonim, Michael Barkham, and Wolfgang Lutz, editors, *Practice-Based Evidence in the Psychological Therapies: Toward Policy Implications for Research, Training, and Clinical Guidelines*. Oxford University Press, New York.

Stevie Chancellor and Munmun De Choudhury. 2020. Methods in predictive techniques for mental health status on social media: a critical review. *npj Digital Medicine*, 3(1):43.

Sarah Clement, Oliver Schauman, Tanya Graham, Francesca Maggioni, Sara Evans-Lacko, Nikita Bezborodovs, Craig Morgan, Nicolas Rüsch, June SL Brown, and Graham Thornicroft. 2015. What is the impact of mental health-related stigma on help-seeking? a systematic review of quantitative and qualitative studies. *Psychological medicine*, 45(1):11–27.

Benjamin Lê Cook, Nhi-Ha Trinh, Zhihui Li, Sherry Shu-Yeu Hou, and Ana M Progovac. 2017. Trends in racial-ethnic disparities in access to mental health care, 2004–2012. *Psychiatric services*, 68(1):9–16.

Esther MV Grootenboer, Erik J Giltay, Rosalind van der Lem, Tineke van Veen, Nic JA van der Wee, and Frans G Zitman. 2012. Reliability and validity of the global assessment of functioning scale in clinical outpatients with depressive disorders. *Journal of evaluation in clinical practice*, 18(2):502–507.

Scott Gspandl, Ryan P Peirson, Ramzi W Nahhas, Tracey Goodman Skale, and Douglas S Lehrer. 2018. Comparing global assessment of functioning (gaf) and world health organization disability assessment schedule (whodas) 2.0 in schizophrenia. *Psychiatry Research*, 259:251–253.

Molly E Ireland and James W Pennebaker. 2010. Language style matching in writing: Synchrony in essays, correspondence, and poetry. *Journal of personality and social psychology*, 99(3):549.

Shaoxiong Ji, Tianlin Zhang, Luna Ansari, Jie Fu, Prayag Tiwari, and Erik Cambria. 2022. MentalBERT: Publicly available pretrained language models for mental healthcare. In *Proceedings of the Thirteenth Language Resources and Evaluation Conference*, pages 7184–7190, Marseille, France. European Language Resources Association.

Huijie Lin, Jia Jia, Jiezhong Qiu, Yongfeng Zhang, Guangyao Shen, Lexing Xie, Jie Tang, Ling Feng, and Tat-Seng Chua. 2017. Detecting stress based on social interactions in social networks. *IEEE Transactions on Knowledge and Data Engineering*, 29(9):1820–1833.

Syeda Mahwish, Ryan L Boyd, Vasudha Varadarajan, Roman Kotov, Benjamin J Luft, H Andrew Schwartz, and Sean AP Clouston. 2026. Measuring resilience using language modeling: A computational approach to observing resilience. *Journal of Traumatic Stress*.

Harry L Piersma and Janna L Boes. 1997. The gaf and psychiatric outcome: a descriptive report. *Community Mental Health Journal*, 33(1):35–41.

Nils Reimers. 2021. sentence-transformers/all-MiniLM-L6-v2. `https://huggingface.co/sentence-transformers/all-MiniLM-L6-v2`. Accessed: March 2026.

Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3982–3992, Hong Kong, China. Association for Computational Linguistics.

Mike Schuster and Kuldip K. Paliwal. 1997. Bidirectional Recurrent Neural Networks. *IEEE Transactions on Signal Processing*, 45(11):2673–2681.

Dan J. Stein, Peter Szatmari, Wolfgang Gaebel, Michael Berk, Eduard Vieta, Mario Maj, Ymkje Anna De Vries, Annelieke M. Roest, Peter De Jonge, Andreas Maercker, Chris R. Brewin, Kathleen M. Pike, Carlos M. Grilo, Naomi A. Fineberg, Peer Briken, Peggy T. Cohen-Kettenis, and Geoffrey M. Reed. 2020. Mental, behavioral and neurodevelopmental disorders in the icd-11: an international perspective on key changes and controversies. *BMC Medicine*, 18(1):21.

Qwen Team. 2026. Qwen3.5-omni technical report.

Christian Winther Topp, Søren Dinesen Østergaard, Susan Søndergaard, and Per Bech. 2015. The who-5 well-being index: a systematic review of the literature. *Psychotherapy and psychosomatics*, 84(3):167–176.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Talia Tseriotou, Jenny Chim, Ayal Klein, Aya Shamir, Guy Dvir, Iqra Ali, Cian Kennedy, Guneet Singh Kohli, Anthony Hills, Ayah Zirikly, Dana Atzil-Slonim, and Maria Liakata. 2025. Overview of the CLPsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 193–217, Albuquerque, New Mexico. Association for Computational Linguistics.

Vasudha Varadarajan, Allison Lahnala, Adithya V Ganesan, Gourab Dey, Siddharth Mangalik, Ana-Maria Bucur, Nikita Soni, Rajath Rao, Kevin Lanning, Isabella Vallejo, Lucie Flek, H. Andrew Schwartz, Charles Welch, and Ryan Boyd. 2024. Archetypes and entropy: Theory-driven extraction of evidence for suicide risk. In *Proceedings of the 9th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2024)*, pages 278–291, St. Julians, Malta. Association for Computational Linguistics.

Torbjørn Vatnaland, J Vatnaland, Svein Friis, and Stein Opjordsmoen. 2007. Are gaf scores reliable in routine clinical use? *Acta Psychiatrica Scandinavica*, 115(4):326–330.

World Health Organization. 2025. World mental health today: latest data. Technical report, World Health Organization, Geneva. License: CC BY-NC-SA 3.0 IGO.

A Code Availability

Our code is available at `https://github.com/McMasterNLP/CLPsych-2026-McMasterNLP`.

B Archetype Sentences

We used ChatGPT (accessed April 2026) to rephrase the subelements of the ABCD scheme. There are 32 elements across the adaptive and maladaptive sections. The elements are rephrased to be expressed in first person such that we can compare the embedding to the posts in our data. Table 1 shows each sentence we used. This is inspired by the archetype similarity approach used by Varadarajan et al. (2024).

C Style Annotations

1. **Length:** Short (roughly 1–30 tokens), medium (30–200 tokens), or long (over 200 tokens).
2. **Off-topic:** Posts whose primary content was unrelated to mental health, including jokes, community pleasantries, and questions on unrelated topics (e.g., video games, entertainment trivia, general lifestyle questions). On-topic posts concerned the author's mental, emotional, or behavioral state.
3. **Help-seeking:** Posts that explicitly referenced seeking assistance, such as asking about medication, requesting advice, or expressing a desire for connection.
4. **Humor or sarcasm:** Posts containing at least one passage with non-literal communicative intent, including ironic understatement (e.g., "well, this is fine"), self-mocking exaggeration (e.g., "classic me, ruining everything"), or absurdist framing of distress (e.g., "time to befriend the void").
5. **Self-deprecation:** Posts containing explicit negative self-evaluation, framed either seriously or comically (e.g., "I'm such a loser," "I always mess up," "nobody likes me anyway").
6. **Somatic language:** Posts containing first-person descriptions of bodily sensations linked to emotional state (e.g., "my chest feels heavy," "can't sleep").
7. **Themes of suicidality:** Posts containing explicit references to wanting to die, ending one's life, or self-harm. We use this broader term rather than *suicidal ideation* because our annotators do not hold clinical training; the clinically meaningful distinction between passive death wishes, active ideation with intent, and ideation with plan was not made at this stage.



Figure 1: **System overview.** A user's temporally ordered posts (timeline) are the shared input. Task 1 operates post-level, encoding each post with MentalRoBERTa and MiniLM archetype similarity features to classify self-state components and rate their intensity. Task 2 operates longitudinally: switch detection uses regression with temporal context to flag abrupt wellbeing changes ($|\Delta| \geq 2$), while escalation uses a BiLSTM over the full timeline. Task 3 generates structured summaries of change sequences and extracts recurrent patterns of deterioration and improvement using a prompted LLM (Qwen3.5-9B).



Figure 2: Feature ablation study for Task 2.1 (switch condition $|\hat{y}(t) - \hat{y}(t-1)| \geq 2$, predicted wellbeing score; cos = MiniLM archetype similarities, mental = MentalRoBERTa). **Left:** Macro F1 for switch detection, comparing Ridge → Threshold against direct Logistic Regression across seven feature sets. **Right:** Ridge RMSE for continuous wellbeing prediction; dashed line marks the naïve baseline (RMSE = 1.843).

Dimension	ID	Archetype Statement
Affect (A)		
A	1	I feel relaxed and steady, and things do not easily disturb my sense of balance.
A	2	I feel tense and worried, like something could go wrong at any moment.
A	3	I feel a deep sadness and emotional pain that is hard to shake.
A	4	I feel hopeless and weighed down, like nothing will really get better.
A	5	I feel genuinely happy and hopeful about my life and what lies ahead.
A	6	I feel intensely energized and unstoppable, like my mind is racing and everything is possible.
A	7	I feel energized and motivated, ready to take on challenges and move forward.
A	8	I feel emotionally numb and indifferent, like nothing really matters.
A	9	I feel angry about something unfair, and I want to stand up for what I believe is right.
A	10	I feel intense anger and hostility toward others, and it is hard not to lash out.
A	11	I feel proud of myself and what I have accomplished.
A	12	I feel ashamed of what I have done and keep blaming myself.
A	13	I feel valued and cared for, like I truly belong with others.
A	14	I feel alone and disconnected, like no one is really there for me.
Behavior toward Other (B-O)		
B-O	1	I try to connect with others and respond to them with openness and care.
B-O	2	When others threaten or pressure me, I either confront them or withdraw to protect myself.
B-O	3	I interact with others in a balanced way, setting boundaries while respecting theirs.
B-O	4	I feel the need to tightly control situations or others so things do not go wrong.
Behavior toward Self (B-S)		
B-S	1	I take care of myself and try to grow or improve my wellbeing.
B-S	2	I avoid taking care of myself and sometimes act in ways that harm or neglect my own needs.
Cognition of Other (C-O)		
C-O	1	I see others as supportive and connected to me.
C-O	2	I feel that others are either distant from me or cling too tightly to me.
C-O	3	I feel that others support my independence and help me grow.
C-O	4	I feel that others restrict or interfere with my ability to be independent.
Cognition of Self (C-S)		
C-S	1	I accept myself as I am and treat myself with understanding.
C-S	2	I constantly judge myself and feel like I am not good enough.
Desire (D)		
D	1	I want meaningful connection and closeness with other people.
D	2	I feel like my need for connection will probably be rejected or ignored.
D	3	I want the freedom to make my own decisions and control my life.
D	4	I feel like I will not be allowed the independence I need.
D	5	I want to feel capable, confident, and proud of what I can do.
D	6	I feel like I will never be good enough or capable enough.

Table 1: LLM-generated ABCD archetype statements used to construct category-level similarity features. Each statement represents a first-person semantic prototype for one ABCD category.

System	Avg Sub Macro F1↑	Adp Pres Macro F1↑	Mal Pres Macro F1↑	Avg Pres Macro F1↑	Adp Sub Macro F1↑	Mal Sub Macro F1↑
Ours (rank 7)	0.351	0.541	0.666	0.603	0.317	0.385
Baseline	0.247	0.392	0.605	0.498	0.156	0.338

Table 2: **Task 1.1: Subelement Classification results.** *Avg Sub Macro F1* is the primary ranking metric. Adp = Adaptive, Mal = Maladaptive, Pres = Element Presence, Sub = Subelement.

System	Avg RMSE↓	Mal RMSE↓	Adp RMSE↓	QWK↑	Comb RMSE↓	Spear↑	MAE↓
Ours (rank 7)	1.035	0.957	1.112	0.526	1.037	0.570	0.799
Baseline	1.424	1.439	1.409	0.555	1.424	0.603	1.083

Table 3: **Task 1.2: Presence Rating results.** *Avg RMSE* (Maladaptive + Adaptive) is the primary ranking metric (lower is better). Mal = Maladaptive, Adp = Adaptive, QWK = Quadratic Weighted Kappa, Spear = Spearman Correlation, MAE = Mean Absolute Error.

System	Comb	Post-level			Timeline-level		
	MF1↑	Esc	MF1	Sw	Esc	MF1	Sw
Ours (rank 11)	0.412	0.375	0.357	0.339	0.660	0.467	0.274
BL3 TempoFormer	0.572	0.667	0.561	0.456	0.736	0.583	0.430
BL2 Llama ZS + T1.1	0.365	0.407	0.383	0.359	0.343	0.346	0.350
BL1 Llama ZS	0.272	0.000	0.169	0.337	0.400	0.376	0.352

Table 4: **Task 2: Identifying Moments of Change**. *Combined (Post/Timeline) Macro F1* is the primary ranking metric. Comb = Combined, Esc = Escalation, Sw = Switch, MF1 = Macro F1, ZS = Zero-shot, T1.1 = Task 1.1 input. BL = Baseline.

System	CS↑	CT↑	R-L↑	BERTscore↑	Avg Score	Rank Avg
Ours (rank 9)	0.770	0.761	0.208	0.255	0.368	8.0
Baseline A	0.763	0.753	0.255	0.226	0.373	9.3
Baseline B	0.767	0.745	0.269	0.235	0.382	7.5

Table 5: **Task 3.1: Change Sequence Summary.** *Score Rank Average* is the primary ranking metric (lower is better). CS = Consistency, CT = Contradiction, R-L = ROUGE-L Recall, BERTscore = BERTscore Recall.

Direction	System	Fit↑	Recurrence↑	Specificity↑	Overall↑
Improvement	Ours (rank 4)	0.688	0.375	0.750	0.594
	Baseline (rank 7)	0.375	0.438	0.375	0.389
Deterioration	Ours (rank 8)	0.188	0.188	0.313	0.211
	Baseline (rank 7)	0.563	0.375	0.438	0.483

Table 6: **Task 3.2: Signatures for Improvement and Deterioration.** Human evaluation. Scores are proportion correct.



Figure 3: Per-target error rates across 46 held-out posts. **Left**: Adaptive subelements, showing overall error rate (blue) and false positive rate when the label is absent in the gold annotation (orange). **Right**: Maladaptive subelements (overall error rate only). Adap-A and Adap-D exhibit the highest error and FP rates among all targets.



Figure 4: Confusion matrices for all 12 element-valence targets across the 46 held-out posts. Rows = true subelement, columns = predicted subelement. Value 0 = element absent. Adaptive-A and adaptive-D show the most subelement confusion; the remaining adaptive elements have only one possible non-zero value.

D Task 3 Prompt Template

For Task 3, we used the following prompt template to generate structured change-sequence summaries. The template was filled with the corresponding timeline identifier, sequence identifier, change type, ordered post indices, ordered post IDs, and textual evidence for each sequence.

Task 3 Change-Sequence Summary Prompt

You are an expert annotator for psychological change-sequence summaries.
Your task is to generate a structured narrative summary for a sequence of chronologically ordered posts surrounding a change event in wellbeing.
You must follow these rules exactly:

TASK
Write a sequence summary describing:

1. The central recurring psychological theme across the sequence.
2. The dynamics within the adaptive and maladaptive self-states.
3. The relationship between the adaptive and maladaptive self-states over time.
4. When the change event occurs.
5. Whether the change is a Switch or an Escalation.
6. Whether the direction is improvement or deterioration.

DEFINITIONS

- A Switch occurs within a single post.
- An Escalation unfolds across multiple posts.
- The sequence includes the pre-change phase and the change itself.
- The exact post where the change occurs is not explicitly marked, so infer it from the sequence.
- Presence scores indicate how strongly adaptive and maladaptive self-states are expressed, but do **not** print raw numeric scores.

ABCD FRAMEWORK
Use these abbreviations whenever referring to elements:

- (A) = Affect
- (B-S) = Behavior toward self
- (B-O) = Behavior toward others
- (C-S) = Cognition toward self
- (C-O) = Cognition toward others
- (D) = Desire

STRICT REQUIREMENTS

- You **must** explicitly describe the pre-change phase.
- You **must** explicitly state when the change occurs in the sequence.
- You **must** explicitly state the change type, Switch or Escalation.
- You **must** explicitly state the direction, improvement or deterioration.
- You **must** describe how dynamics culminate in the change, for Switch, or unfold through it, for Escalation.

SELF-STATE DYNAMICS

- When describing a self-state, you **must** include relational dynamics between at least two ABCD elements, such as mutual reinforcement, amplification, or suppression.
- You **must** describe how the presence of adaptive and maladaptive self-states changes over time.
- You **must** describe relationships between self-states using concepts such as dominance, suppression, coexistence, or reflective dialogue.

GROUNDING

- Only include ABCD elements and dynamics supported by the provided data.

- Do **not** hallucinate unsupported elements.

STYLE

- Write as one cohesive paragraph.
- Maximum 350 words.
- Be specific, analytic, and sequence-focused.
- No bullet points.

OUTPUT FORMAT
Return only:

```
Sequence Summary: <your summary paragraph>
```

CRITICAL OUTPUT REQUIREMENTS

- You **must** explicitly label the pre-change phase using the phrase: "In the pre-change phase,"
- You **must** explicitly specify when the change occurs using temporal grounding, such as early, middle, late in the sequence, or between posts.
- You **must** explicitly state both the change type and direction together, such as "a Switch towards deterioration occurs".
- Your summary **must** clearly follow this structure:
  1. Pre-change phase
  2. Change event or escalation process
  3. Post-change phase
- You **must** describe how the relationship between adaptive and maladaptive states evolves over time, such as coexistence to dominance to suppression.
- When describing a self-state, include at least one multi-element interaction involving two or more ABCD elements, such as C-S reinforcing A, which drives B-S.
- Your output **must** begin exactly with: `Sequence Summary:`

INPUT
You will receive:

- `timeline_id`
- `sequence_id`
- `change_type`
- ordered posts with structured annotations

IMPORTANT
Use only the provided structured fields and textual evidence. Do **not** assume access to any gold summary.

Now go ahead and write the summary for the following input.

–

Structured fields for this sequence

- `timeline_id: {timeline_id}`
- `sequence_id: {sequence_id}`
- `change_type: {change_type}`
- `ordered post indices (chronological): {postindices}`
- `ordered post ids: {postids}`

Textual evidence for the sequence

```
{summary}
```



(a) Timeline: `3db8573df5`.

(b) Timeline: `15564c5c62`.

(c) Timeline: `d0fb4b962e`.

(d) Timeline: `62defd8df2`.

Figure 5: Escalation trajectories on four held-out test timelines. Blue solid line: wellbeing score (left axis). Red dashed line: Bi-LSTM $P(E)$ (right axis, dotted line at 0.5). Gold shading: ground-truth escalation spans.



Figure 6: Confusion matrices and confidence diagnostics for switch detection.



Figure 7: Error rate by post-length bucket for switch detection.



Figure 8: Confusion matrices and confidence diagnostics for escalation detection.



Figure 9: Error rate by post-length bucket for escalation detection.

P2P - from Posts to Patterns: An LLM Ensemble Approach to Mental Health Dynamics Detection

Federico Ravenda[★], **Volodymyr Karpenko**[★]
Antonietta Mira[★,◇], **Andrea Raballo**[★,♣]
{name.lastname}@usi.ch,
[★] Euler Institute, Università della Svizzera italiana
[♣] Cantonal Socio-Psychiatric Organization , [◇] University of Insubria

Abstract

The automatic detection of mental health dynamics represents a challenging and socially relevant task, requiring models to capture subtle psychological changes over time. Large language models have demonstrated remarkable capabilities in clinical and diagnostic contexts, yet their outputs often lack consistency and may diverge significantly across different model families and prompting strategies. This paper presents the USAI team's submission to the CLPsych 2026 Shared Task, targeting Tasks 1.1, 1.2, 2, and 3.1. We propose an ensemble-based approach combining multiple open-source large language models, where the contribution of each model is weighted according to its alignment with clinically grounded human annotations on the training set. Our system achieves competitive results across the evaluated subtasks, with particularly strong performance on Tasks 1.2 and 2.

1 Introduction & Related Works

Recent advances in NLP have enabled remarkable progress in sensitive domains such as digital health and mental health, where the ability to extract meaningful signals from unstructured text is of critical clinical value. The growing availability of social media data has further opened new avenues for passive, longitudinal monitoring of psychological states at scale.

Large language models have shown increasing promise in mental health research. For instance, MentaLLaMA (Yang et al., 2024a) demonstrates how interpretability can be integrated into model outputs to provide clinically meaningful insights, while Varadarajan et al. (2024) combine theoretical psychological frameworks with computational modelling to advance suicide risk assessment. Together, these efforts illustrate the growing potential of LLM-based systems to support real-time mental health monitoring and intervention (Yang et al., 2024b). Ravenda et al. (2025a) further explored the use of LLMs to enhance symptom severity assessment across different mental health conditions.

Beyond clinical monitoring, LLMs have recently gained traction as diagnostic and educational tools. Studies such as Elyoseph et al. (2025); Levkovich et al. (2024); Raballo et al. have shown that LLMs can match or even surpass physicians in diagnostic reasoning based on standardised clinical vignettes, highlighting their potential as reliable aids in medical education and decision support.

The CLPsych 2026 Shared Task (Ali et al., 2026) extends the previous year shared task (Tseriotou et al., 2025) by introducing a fine-grained longitudinal benchmark (Tsakalidis et al., 2022) grounded in the MIND framework (Atzil-Slonim, 2025, 2026), which conceptualises self-states as structured combinations of Affect, Behaviour, Cognition, and Desire (ABCD) components. Participants are asked to model adaptive and maladaptive self-state dynamics over time from sequences of social media posts, with the goal of characterising psychological change processes at both the post and timeline level.

The main contributions of this work are:

- We propose a weighted ensemble of open-source LLMs for ABCD subelement classification, self-state presence rating, and moment-of-change detection, covering Tasks 1.1, 1.2, 2, and 3.1 of the shared task.
- We introduce a training-time weight optimisation procedure that aligns each model's contribution with clinically grounded human annotations, independently for each task and metric.

2 Methodology

2.1 Overview

Our system takes inspiration from the CLPsych 2025 submission by Ravenda et al. (2025b) and

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 498–503
July 4, 2026 ©2026 Association for Computational Linguistics

follows a weighted ensemble paradigm designed to exploit the capabilities of large language models without any parameter fine-tuning. Fine-tuning is indeed impractical in this setting for two reasons: the limited number of available training timelines (30) makes it prone to overfitting, and the computational cost of adapting large-scale models is prohibitive. Instead, each LLM is prompted for the specific task, and its predictions are treated as fixed inputs to a lightweight optimisation stage. This is conceptually analogous to stacking in ensemble learning: rather than combining model outputs through a learned meta-classifier, we directly optimise a set of scalar weights over the simplex to maximise the target evaluation metric on the training set. The pipeline consists of three stages: (i) independent inference from each LLM using task-tailored prompting strategies, (ii) weight learning via constrained optimisation on training-set predictions, and (iii) weighted ensemble decoding at test time. In Figure 1, we illustrate the three stages of the proposed pipeline: independent LLM inference, weight optimisation on the training set, and weighted ensemble decoding at test time.

2.2 Models and Prompting Strategies

We employ six open-source LLMs: DeepSeek-R1-Distill-Qwen-32B, Kimi Moonlight-16B-A3B-Instruct, GPT-OSS-20B, Gemma-27B , Xiaomi MiMo-v2-Flash, and Llama-3.1-8B.

Each model is assigned the prompting strategy, either *zero-shot* or *chain-of-thought*, that achieves the highest individual performance on the training set.

All prompts include the complete ABCD subelement schema of the task guidelines.

2.3 Task 1.1: ABCD Subelement Classification

For each post, the model is asked to identify the single most dominant adaptive and maladaptive subelement within each ABCD element (Affect, Behavior-Self, Behavior-Other, Cognition-Self, Cognition-Other, Desire), following the definitions in Atzil-Slonim (2025). The prompt enumerates all valid subelement indices for each element and valence, and constrains the output to at most one subelement per element per valence.

At ensemble time, subelement predictions across the six models are combined via soft weighted voting: for each post and each element–valence pair, each model contributes its predicted subelement index with a weight w_m. The index receiving the highest total weight is selected as the final prediction, provided it exceeds the total weight assigned to abstention (i.e. no subelement predicted).

The per-element weights $\mathbf{w} \in \Delta^5$ (the probability simplex) are found by solving:

$$\mathbf{w}^* = \mathbf{w} \in \Delta^5 \arg\max\, F_1(\hat{y}(\mathbf{w}),\, y) \qquad (1)$$

where $\hat{y}(\mathbf{w})$ is the ensemble decision under weights $\mathbf{w}$ and y is the gold label. Since F_1 is non-differentiable with respect to $\mathbf{w}$ due to the hard voting threshold, we adopt a derivative-free search strategy. We evaluate the objective at multiple candidate weight vectors, iteratively refining the search region towards configurations that improve training-set F1. To mitigate the risk of converging to poor local solutions, the search is repeated from $N{=}10$ independent starting points sampled uniformly at random from the simplex, and the best solution found across all runs is retained.

2.4 Task 1.2: Self-State Presence Rating

Each model assigns a presence score in $\{1, \ldots, 5\}$ to the adaptive and maladaptive self-states independently. The ensemble prediction is the weighted average of model scores, clipped to $[1, 5]$:

$$\hat{p} = \mathrm{clip}\left(\sum_m w_m \cdot p_m,\ 1,\ 5\right) \qquad (2)$$

Separate weight vectors are learned for adaptive and maladaptive presence by minimising the following objective on the training set:

$$\mathbf{w}^* = \mathbf{w} \in \Delta^5 \arg\min\, \mathrm{RMSE}(\textstyle\sum_m w_m p_m,\ y) \qquad (3)$$

where p_m is the presence score predicted by model m and y is the gold annotation.

2.5 Task 2: Moments of Change Detection

For each post, each model independently predicts a Switch label (`S` or `0`) and an Escalation label (`E` or `0`), treating the two labels as independent binary classification problems. Each model is provided with the full chronologically ordered sequence of posts in the timeline, enabling it to assess wellbeing trajectory.

At ensemble time, the binary predictions are combined via weighted majority voting, using the same formulation as Task 1.1 (Equation 1). Separate weight vectors are optimised for Switch F1 and Escalation F1 independently.



Figure 1: Overview of the proposed LLM ensemble pipeline for CLPsych 2026.

Finally, GPT-OSS-120B is employed in a refinement stage to enforce temporal consistency across the timeline: it handles missing wellbeing values by referring to prior posts within a defined temporal window, and revises predictions deemed clearly inconsistent with the surrounding context.

2.6 Weight Learning

All weight vectors are learned on the 30 training timelines provided for the shared task. A diversity check is performed prior to optimisation: if the standard deviation of per-model singleton F1 scores falls below a threshold ϵ=10^{-4}, the weight vector defaults to uniform $\mathbf{w} = 1/M$ to avoid spurious solutions. Learned weights are fixed at test time; no further adaptation is performed.

2.7 Task 3.1: Sequence Summarisation

We address Task 3.1 through a few-shot prompting approach and `qwen-2.5-72b-instruct` model. For each test sequence, we construct a structured input by combining the ABCD self-state annotations from Task 1 (subelements and presence ratings for adaptive and maladaptive states) with the Switch and Escalation labels from Task 2, aligned to post indices. Up to five in-context demonstrations are selected from the training set to maximise diversity across change type (Switch, Escalation, or both) and direction of change (deterioration vs. improvement). One demonstration is always a fixed gold example from the task guidelines. The system prompt enforces ABCD element abbreviations, explicit identification of the change event and its direction, and coverage of within-state dynamics and cross-state interactions.

3 Results

Table 1 reports the performance of our system across all evaluated subtasks.

On Task 1.1, our system achieves competitive results, ranking second on Maladaptive Element Presence Macro F1, Average Element Presence Macro F1, and Adaptive Subelement Macro F1.

On Task 1.2, our system ranks first on Combined QWK (0.730) and Combined Spearman Correlation (0.752), and second on the majority of RMSE-based metrics, demonstrating strong alignment with human presence annotations.

Task 2 represents our strongest result overall, with our system ranking first on Combined Macro F1 (0.600), Post Macro F1 (0.639), and Post Switch Macro F1 (0.583), and second on Timeline Switch and Timeline Escalation Macro F1.

On Task 3.1, our system achieves the best performance on ROUGE-L Recall (0.333) and BERTScore Recall (0.365), indicating strong semantic coverage in the generated summaries. However, lower Consistency and higher Contradiction scores suggest that the system prioritises content coverage over internal coherence. Incorporating consistency as an explicit constraint in the prompt, or applying a post-hoc coherence filtering step, represents a possible direction for future work.

Task	Metric	USAI
1.1 - Subelement Classification	Average Subelement Macro F1	0.410
	Adaptive Element Presence Macro F1	0.549
	Maladaptive Element Presence Macro F1	0.736
	Average Element Presence Macro F1	0.642
	Adaptive Subelement Macro F1	0.333
	Maladaptive Subelement Macro F1	0.487
1.2 - Presence Rating	Avg RMSE ↓	0.942
	Adaptive RMSE ↓	0.979
	Maladaptive RMSE ↓	0.905
	Combined RMSE ↓	0.943
	Combined QWK	**0.730**
	Combined Spearman	**0.752**
	Combined MAE ↓	0.681
2 - Moment of Change	Combined Macro F1	**0.600**
	Post Macro F1	**0.639**
	Post Switch Macro F1	**0.583**
	Post Escalation Macro F1	0.694
	Timeline Macro F1	0.561
	Timeline Switch Macro F1	0.510
	Timeline Escalation Macro F1	0.611
3.1 - Sequence Summarisation	Consistency Score ↑	0.681
	Contradiction ↓	0.849
	ROUGE-L Recall ↑	**0.333**
	BERTScore Recall ↑	**0.365**

Table 1: USAI system results across all evaluated subtasks. ↑ = higher is better, ↓ = lower is better. **Bold** = best across all teams; underline = second best.

4 Conclusion

In this paper, we presented the USAI submission to the CLPsych 2026 Shared Task on mental health change detection in social media timelines. We proposed a weighted ensemble of open-source large language models.

Our system achieved strong results across multiple subtasks, ranking first on Task 2 and obtaining top-two performance on the majority of Task 1.2 metrics. These results suggest that optimisation-based ensemble learning is an effective strategy for psychologically grounded NLP annotation tasks, where individual model outputs may be noisy or inconsistent.

The main limitation of our approach lies in its reliance on large-scale models that entail significant computational costs, which may limit practical deployment in clinical settings. A promising direction for future work is the distillation of temporal dynamics into smaller, more efficient models, reducing the dependence on large language models while preserving the ability to capture longitudinal psychological patterns.

5 Limitations

Our approach presents several limitations that should be acknowledged. First, the ensemble weights are optimised on the training set with limited number of training timelines (30) available for the shared task. Second, the effectiveness of the weight optimisation procedure is contingent on sufficient diversity among model predictions: when models converge to similar outputs, weights default to uniform, providing no advantage over a simple average. Third, our system operates at the post level for Tasks 1.1 and 1.2, without explicitly modelling dependencies between consecutive posts within a timeline, which may limit its ability to capture gradual psychological transitions. Finally, while our system achieves competitive performance, it remains largely a black-box ensemble: the learned weights indicate the relative contribution of each model, but do not provide insight into which linguistic or psychological features drive individual predictions. Interpretability is particularly critical in mental health applications, where clinicians and practitioners need to understand and trust model outputs before acting on them.

6 Ethics Statement

This work involves the analysis of social media posts from individuals discussing mental health topics, which raises important ethical considerations. All data used in this study was provided by the CLPsych 2026 shared task organisers under a formal data access agreement, and handled strictly in accordance with its terms. No additional data collection was performed, and no attempt was made to re-identify any individual from the provided anonymised dataset.

The posts processed in this work may contain sensitive disclosures, including expressions of suicidal ideation, self-harm, and severe psychological distress. We recognise the potential harm of misclassifying such content and emphasise that our system is intended solely as a research prototype and is not suitable for deployment in clinical or real-world settings without thorough validation by qualified mental health professionals.

References

Iqra Ali, Talia Tseriotou, Guy Dvir, Callum Chan, Yuxiang Zhou, Juan Antonio Lossio-Ventura, Ayal Klein, Aya Shamir, Dan Sayda, Anthony Hills, Aya Zirikly, Diana Inkpen, Dana Atzil-Slonim, and Maria Liakata. 2026. Overview of the clpsych 2026 shared task: Capturing and characterizing mental health changes through social media timeline dynamics. In *Proceedings of the 11th Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Dana Atzil-Slonim. 2025. Multimodal intrapersonal and interpersonal dynamics (mind): A transtheoretical coding manual.

Dana Atzil-Slonim. 2026. Leveraging theoretical and technological innovations to study the mechanisms that underlie therapeutic change in psychotherapy. In Louis G. Castonguay, Dana Atzil-Slonim, Michael Barkham, and Wolfgang Lutz, editors, *Practice-Based Evidence in the Psychological Therapies: Toward Policy Implications for Research, Training, and Clinical Guidelines*. Oxford University Press, New York.

Zohar Elyoseph, Inbar Levkovitch, Yuval Haber, and Yossi Levi-Belz. 2025. Using genai to train mental health professionals in suicide risk assessment: Preliminary findings. *The Journal of clinical psychiatry*, 86(3):24m15525.

Inbar Levkovich, Eyal Rabin, Michal Brann, and Zohar Elyoseph. 2024. Large language models outperform general practitioners in identifying complex cases of childhood anxiety. *Digital Health*, 10:20552076241294182.

Andrea Raballo, Federico Ravenda, and Antonietta Mira. Diagnosing schizophrenia spectrum disorders: Large language models (llms) vs. leading international psychiatrists (lips). *Psychiatry and Clinical Neurosciences*.

Federico Ravenda, Seyed Ali Bahrainian, Andrea Raballo, Antonietta Mira, and Noriko Kando. 2025a. Are LLMs effective psychological assessors? leveraging adaptive RAG for interpretable mental health screening through psychometric practice. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8975–8991, Vienna, Austria. Association for Computational Linguistics.

Federico Ravenda, Fawzia-Zehra Kara-Isitt, Stephen Swift, Antonietta Mira, and Andrea Raballo. 2025b. From evidence mining to meta-prediction: a gradient of methodologies for task-specific challenges in psychological assessment. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 242–248, Albuquerque, New Mexico. Association for Computational Linguistics.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Talia Tseriotou, Jenny Chim, Ayal Klein, Aya Shamir, Guy Dvir, Iqra Ali, Cian Kennedy, Guneet Singh Kohli, Anthony Hills, Ayah Zirikly, Dana Atzil-Slonim, and Maria Liakata. 2025. Overview of the CLPsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 193–217, Albuquerque, New Mexico. Association for Computational Linguistics.

Vasudha Varadarajan, Allison Lahnala, Adithya V Ganesan, Gourab Dey, Siddharth Mangalik, Ana-Maria Bucur, Nikita Soni, Rajath Rao, Kevin Lanning, Isabella Vallejo, and 1 others. 2024. Archetypes and entropy: Theory-driven extraction of evidence for suicide risk. In *Proceedings of the 9th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2024)*, pages 278–291.

Kailai Yang, Tianlin Zhang, Ziyan Kuang, Qianqian Xie, Jimin Huang, and Sophia Ananiadou. 2024a. Mentallama: interpretable mental health analysis on social media with large language models. In *Proceedings of the ACM on Web Conference 2024*, pages 4489–4500.

Minqiang Yang, Yongfeng Tao, Hanshu Cai, and Bin Hu. 2024b. Behavioral information feedback with large

language models for mental disorders: Perspectives and insights. *IEEE Transactions on Computational Social Systems*, 11(3):3026–3044.

Prompt-Based Modeling of Moments of Change and Change Summaries in Mental Health Timelines

Do Minh Duc and Pham Trung Tin and Vu Tran and Nguyen Le Minh
Japan Advanced Institute of Science and Technology (JAIST)
Ishikawa, Japan
{minhducdo,tinpham,vu-tran,nguyenml}@jaist.ac.jp

Abstract

This paper presents our prompt-based approach for modeling mental health timelines from Reddit user posts. We address two tasks: identifying moments of change and generating summaries of clinically meaningful changes across post sequences. Our framework uses large language models with in-context learning to analyze self-states and mental health indicators without task-specific fine-tuning. We build an inference pipeline with vLLM and Qwen2.5-72B-Instruct-GPTQ-Int8, and experiment with few-shot prompting, and balanced few-shot sampling. We also examine how the number of visible posts affects the model's ability to capture temporal changes. Our results suggest that prompt-based methods provide a practical and competitive baseline in low-resource and sensitive mental health settings, particularly for modeling self-state dynamics and generating summaries of psychological change over time.

1 Introduction

Mental health concerns are a pressing global issue (World Health Organization, 2022), motivating computational methods that can support scalable and longitudinal monitoring while accounting for the dynamic nature of psychological well-being. Over the past decade, social media platforms such as Reddit have become important spaces where individuals disclose emotional states, personal experiences, and mental health struggles over extended periods (Coppersmith et al., 2014; Shing et al., 2018; Tsakalidis et al., 2022b). These temporally rich user-generated data provide opportunities to study mental health trajectories over time, enabling earlier detection of meaningful changes and supporting more timely intervention.

Early NLP work in mental health primarily focused on static user-level or post-level classification. However, recent research has emphasized that mental health is better understood as a longitudinal process, where mood, behavior, cognition, and interpersonal context fluctuate across time. This shift has motivated shared tasks that move beyond static prediction toward modeling temporal dynamics, including the identification of Moments of Change and the generation of interpretable summaries of mental health trajectories (Tsakalidis et al., 2022a; Tseriotou et al., 2023). The CLPsych 2026 Shared Task (Ali et al., 2026) further extends this direction by focusing on adaptive and maladaptive self-state components, grounded in the MIND framework (Atzil-Slonim, 2025, 2026), and by requiring systems to identify changes and summarize the psychological processes leading up to them.

In this paper, we propose a prompt-based framework for modeling moments of change and generating change summaries in mental health timelines. Our main contributions are as follows:

- We develop a prompt-based in-context learning framework for analyzing longitudinal posts, focusing on self-states and mental health indicators without task-specific fine-tuning.
- We apply the framework to two CLPsych shared-task settings: detecting Moments of Change and generating summaries of clinically meaningful changes across post sequences.
- We investigate different prompting strategies, including few-shot prompting, and balanced few-shot sampling, to study their effectiveness in a low-resource and sensitive mental health domain.

2 Related work

Mental health assessments on social media have gained significant attention in recent years. Previous CLPsych shared tasks have explored various

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 504–509
July 4, 2026 ©2026 Association for Computational Linguistics

aspects of mental health analysis, including longitudinal modeling of mood changes (Tsakalidis et al., 2022a) and evidence generation for suicidality risk (Zirikly et al., 2019; Shing et al., 2018).

In-context learning (ICL) has emerged as a powerful technique for leveraging large language models without task-specific fine-tuning (Brown et al., 2020). By providing relevant examples within the prompt, ICL allows models to learn from demonstrations rather than parameter updates. Nevertheless, few-shot performance is highly sensitive to the selected examples and their label composition. Balanced sampling across labels can provide more informative demonstrations, reduce bias toward overrepresented classes, and improve the robustness of prompt-based predictions. This motivates our use of balanced few-shot prompting, in line with recent work showing that strategic example selection plays an important role in ICL performance (Pecher et al., 2025).

3 Problem Formalization

3.1 Task 2: Moments of Change

This task focuses on detecting clinically meaningful moments of change within a chronological user timeline. Given a chronologically ordered sequence of posts from a single individual, teams must identify two types of change:

- SWITCH: A sudden change in well-being between two consecutive posts, occurring when $|\text{Wellbeing}(t) - \text{Wellbeing}(t-1)| \geq 2$.
- ESCALATION: A gradual change over multiple consecutive posts, where well-being shifts from a neutral or mild state toward a more extreme positive or negative state.

For Task 2, let a user timeline be represented as:

$$T_u = (p_1, p_2, \ldots, p_n),$$

where p_t denotes the post at time step t. For each target post p_t, we formulate SWITCH detection over two consecutive posts:

$$\hat{y}_t^{\text{SWITCH}} = f_\theta\left(\mathcal{P}(p_{t-1}, p_t)\right).$$

We formulate ESCALATION detection over three consecutive posts:

$$\hat{y}_t^{\text{ESCALATION}} = f_\theta\left(\mathcal{P}(p_{t-2}, p_{t-1}, p_t)\right).$$

Here, f_θ denotes the LLM-based prediction function parameterized by θ. Both predictions are binary:

$$\hat{y}_t^{\text{SWITCH}} \in \{0, S\}, \hat{y}_t^{\text{ESCALATION}} \in \{0, E\}.$$

3.2 Task 3: Change Summaries

The goal of Task 3.1 is to generate a structured summary of self-state dynamics across a sequence of posts surrounding a change event. The summary should describe how psychological changes evolve over time, either culminating in a SWITCH or gradually unfolding as an ESCALATION. It should also indicate the direction of change and characterize the pattern using the MIND framework, including ABCD elements and adaptive or maladaptive self-state presence scores (Tseriotou et al., 2025).

For Task 3.1, the input is a sequence of posts associated with a change event:

$$X_i = (p_{a_i}, p_{a_i+1}, \ldots, p_{b_i}),$$

Where , X_i denotes the post sequence associated with the i-th change event, and a_i and b_i denote the start and end indices of that sequence. The output is a generated change summary:

$$\hat{s}_i = g_\theta(X_i),$$

where $\hat{s}_i$ describes the self-state dynamics and psychological change expressed across the sequence and g_θ denotes the LLM-based generation function used to produce the change summary.

4 Methodology

Our prompt-based modeling framework addresses Task 2 and Task 3.1 using in-context learning with local LLM inference through vLLM. We utilized Qwen2.5-72B-Instruct-GPTQ-Int8 as our primary language model, running it locally through vLLM to maintain data privacy and control over the inference process. Figure 1 presents an overview of our method.

Given a user timeline $T_u = \{p_1, p_2, \ldots, p_n\}$, we formulate each input instance x_i as a sequence of posts. Our prompt-based framework constructs an input prompt

$$\mathcal{P}(x_i) = [\mathcal{I}; \mathcal{D}_K; x_i],$$

where $\mathcal{I}$ denotes the task instruction and $\mathcal{D}_K$ denotes a set of K in-context demonstrations. In zero-shot prompting, $\mathcal{D}_K = \emptyset$. In few-shot prompting, $\mathcal{D}_K$ contains selected input-output examples.



Figure 1: Overview of the prompt-based modeling framework.

For balanced few-shot prompting, demonstrations are sampled such that each label $c \in \mathcal{Y}$ appears with frequency: $|\mathcal{D}_c| \approx \frac{K}{|\mathcal{Y}|}$.

For Moment of Change detection, the model predicts:

$$\hat{y}_i = \arg\max_{y \in \mathcal{Y}} P_\theta(y \mid \mathcal{P}(x_i)), \tag{1}$$

whereas for Change Summary generation, the model produces:

$$\hat{s}_i = \text{Decode}_\theta(\mathcal{P}(x_i)) \tag{2}$$

We further define the input context with k visible posts as: $x_i^{(k)}$ following:

$$x_i^{(k)} = \{p_{i-k+1}, \ldots, p_i\},$$

where k denotes the number of visible posts provided to the model p_i is post in index i on timeline. To study the effect of context length, we vary the number of visible posts $k \in \{3, 4, 5\}$.

4.1 Prompt and ICL Layer

The Prompt and ICL layer is responsible for converting each processed timeline instance into a task-specific prompt. Each prompt consists of three components: a task definition, optional in-context demonstrations, and the target input sequence. The task definition describes the objective of the corresponding CLPsych 2026 task, while the demonstrations provide examples of input-output behavior for few-shot settings. In the zero-shot setting, the prompt contains only the task definition and the target instance. In the few-shot setting, we prepend selected examples from the training set. For balanced few-shot prompting, examples are sampled so that different labels or change types are represented with comparable frequency.

For Task 2, the prompt defines the objective as identifying Moments of Change in a user's mental health trajectory based on longitudinal signals from a sequence of posts. The model is instructed to compare the target post or segment with the surrounding context and determine whether it reflects a meaningful change in the user's self-state or mental health condition. The output is constrained to the predefined task label format.

For Task 3.1, the prompt defines the objective as generating a concise and interpretable summary of clinically meaningful change across a sequence of posts. The model is instructed to summarize the change trajectory rather than producing independent post-level summaries. In particular, the prompt encourages the model to capture the user's self-state dynamics, including affective, behavioral, cognitive, and desire-related signals when they are present in the input. To make the output easier to parse, we require the model to return the generated summary in a strict XML format.

4.2 Tasks Layer

The Tasks layer separates the inference process into two CLPsych 2026 shared-task objectives. The first objective, Task 2, focuses on Moment of Change detection. Given a timeline context, the model predicts whether the target point corresponds to a meaningful transition in the user's mental health trajectory. This task is formulated as a label prediction problem, where the LLM produces a task label conditioned on the constructed prompt.

The second objective, Task 3.1, focuses on Change Summary generation. Given a sequence of posts associated with a change event, the model generates a short summary describing the psychological change expressed across the sequence. Unlike Task 2, this task is formulated as a conditional generation problem. The generated summary is expected to describe the direction and nature of the change, including the user's self-state before, during, and after the transition when such information is available.

Table 1: Task 2 results ranked by average Macro F1. Our team is highlighted in bold.

Team Name	Task 2 - Avg Macro F1
USAI	0.600
CtbuY	0.588
CUNY	0.572
MKC	0.554
Codezone Research Group	0.553
Aurevia	0.484
Meronym Labs	0.466
debju	0.447
JNLP few-shot	**0.566**
JNLP few-shot balance	**0.580**

Although both tasks share the same prompt-based inference backbone, they differ in their output structure. Task 2 produces discrete Moment of Change predictions, whereas Task 3.1 produces natural-language summaries wrapped in XML tags. This separation allows the same LLM inference pipeline to support both classification-style and generation-style tasks.

5 Experiment

We evaluate our prompt-based framework on two CLPsych 2026 shared-task settings: Task 2, which focuses on Moment of Change detection, and Task 3.1, which focuses on change-summary generation. For Task 2, we submit two configurations: a few-shot and a balanced few-shot in-context learning setting. This allows us to examine whether adding balanced demonstrations improves the model's ability to identify change patterns in mental health timelines.

Table 1 presents the Task 2 results in terms of average Macro F1. Our balanced few-shot configuration achieves an average Macro F1 of 0.580, improving over the few-shot standard configuration, which obtains 0.566. This suggests that balanced in-context examples help the model better distinguish between different types of change, especially in a low-resource and sensitive domain where task-specific fine-tuning is not applied.

We analyze different context window sizes $k \in \{3, 4, 5\}$ to examine how much local history is needed for detecting changes in mental health timelines in Table 4. This design reflects the difference between the two labels: SWITCH can often be detected from local contrast between consecutive posts, whereas ESCALATION may require a longer context to capture gradual changes over time. Based on this analysis and the official shared-task evaluation, we submitted two final configurations: standard few-shot prompting and balanced few-shot prompting.

Table 2: Task 3.1 results. Our team is highlighted in bold.

Team Name	Consistency	Contradiction	ROUGE-L
Aurevia	0.866	0.625	0.185
psytechlab	0.857	0.571	0.078
DreamerNLplus	0.845	0.439	0.189
Meronym Labs	0.801	0.659	0.266
CUNY	0.797	0.696	0.283
Meronym Labs	0.787	0.673	0.282
McMasterNLP	0.770	0.761	0.208
JNLP few-shot	**0.791**	**0.666**	**0.117**

For Task 3.1, we evaluate the ability of our system to generate summaries that describe self-state dynamics and psychological changes across post sequences. Unlike Task 2, which is formulated as a prediction task, Task 3.1 requires the model to generate structured natural-language summaries. We report results using three evaluation metrics: Consistency, Contradiction, and ROUGE-L.

Table 2 shows the Task 3.1 results. Our system achieves a Consistency score of 0.791, which is comparable to several higher-ranked systems. This indicates that the generated summaries are generally aligned with the input post sequences. However, the lower ROUGE-L score suggests that our generated summaries may differ lexically from the reference summaries, even when they capture similar change patterns. This is expected in open-ended generation tasks, where multiple valid summaries can describe the same psychological transition using different wording.

6 Conclusion

This paper presented a prompt-based framework for detecting Moments of Change and generating change summaries in mental health timelines. Using Qwen2.5-72B-Instruct-GPTQ-Int8 with vLLM, we explored zero-shot, few-shot, and balanced few-shot prompting strategies without task-specific fine-tuning. Our results show that balanced few-shot prompting improves Task 2 performance over standard few-shot prompting, while the generated summaries achieve reasonable consistency with the input timelines despite lower lexical overlap with reference summaries. These findings suggest that prompt-based LLMs can serve as a practical baseline for low-resource and sensitive mental health timeline modeling. Future work should explore

more robust prompt optimization, domain adaptation, and human-centered evaluation of generated change summaries.

7 Limitations

First, the LLM used in this paper was pretrained mainly on large-scale open general data, meaning there is no guarantee that it contains sufficient high-quality clinical or professional knowledge for understanding mental health-related content; fine-tuning or further adapting the model with expert-annotated mental health data may help reduce this limitation. **Second**, although in-context learning can guide LLMs to perform new tasks through task instructions and demonstrations, the model may still fail to fully understand complex mental health contexts, which is especially challenging for longitudinal timelines where psychological changes may be subtle, gradual, or expressed indirectly across multiple posts. **Third**, since our method relies on prompt-based inference, its performance can be affected by the wording of task instructions, the number of visible posts, and the selected few-shot examples; although balanced few-shot sampling helps control label distribution, different prompt formulations or demonstration choices may lead to different predictions.

8 Ethics

Secure access to the shared task dataset was provided with IRB approval under University of Maryland, College Park protocol 1642625 and approval by the Biomedical and Scientific Research Ethics Committee (BSREC) at the University of Warwick (ethical application reference BSREC 40/19-20). We do not include raw user posts or personally identifiable information in the paper. Any examples, prompt illustrations, or descriptions are paraphrased or abstracted to comply with the data access agreement and protect user privacy.

Acknowledgments

This work was supported by JSPS KAKENHI Grant Number JP23K16954. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the author(s)' organization, JSPS or MEXT.

References

Iqra Ali, Talia Tseriotou, Guy Dvir, Callum Chan, Yuxiang Zhou, Juan Antonio Lossio-Ventura, Ayal Klein, Aya Shamir, Dan Sayda, Anthony Hills, Aya Zirikly, Diana Inkpen, Dana Atzil-Slonim, and Maria Liakata. 2026. Overview of the clpsych 2026 shared task: Capturing and characterizing mental health changes through social media timeline dynamics. In *Proceedings of the 11th Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Dana Atzil-Slonim. 2025. Multimodal intrapersonal and interpersonal dynamics (mind): A transtheoretical coding manual.

Dana Atzil-Slonim. 2026. Leveraging theoretical and technological innovations to study the mechanisms that underlie therapeutic change in psychotherapy. In Louis G. Castonguay, Dana Atzil-Slonim, Michael Barkham, and Wolfgang Lutz, editors, *Practice-Based Evidence in the Psychological Therapies: Toward Policy Implications for Research, Training, and Clinical Guidelines*. Oxford University Press, New York.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, and 12 others. 2020. Language models are few-shot learners. In *Advances in Neural Information Processing Systems*, volume 33, pages 1877–1901. Curran Associates, Inc.

Glen Coppersmith, Mark Dredze, and Craig Harman. 2014. Quantifying mental health signals in Twitter. In *Proceedings of the Workshop on Computational Linguistics and Clinical Psychology: From Linguistic Signal to Clinical Reality*, pages 51–60, Baltimore, Maryland, USA. Association for Computational Linguistics.

Branislav Pecher, Ivan Srba, Maria Bielikova, and Joaquin Vanschoren. 2025. Automatic combination of sample selection strategies for few-shot learning.

Han-Chin Shing, Suraj Nair, Ayah Zirikly, Meir Friedenberg, Hal Daumé III, and Philip Resnik. 2018. Expert, crowdsourced, and machine assessment of suicide risk via online postings. In *Proceedings of the Fifth Workshop on Computational Linguistics and Clinical Psychology: From Keyboard to Clinic*, pages 25–36, New Orleans, LA. Association for Computational Linguistics.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022a. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics*

and Clinical Psychology, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Adam Tsakalidis, Federico Nanni, Anthony Hills, Jenny Chim, Jiayu Song, and Maria Liakata. 2022b. Identifying moments of change from longitudinal user text. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 4647–4660, Dublin, Ireland. Association for Computational Linguistics.

Talia Tseriotou, Jenny Chim, Ayal Klein, Aya Shamir, Guy Dvir, Iqra Ali, Cian Kennedy, Guneet Singh Kohli, Anthony Hills, Ayah Zirikly, Dana Atzil-Slonim, and Maria Liakata. 2025. Overview of the CLPsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 193–217, Albuquerque, New Mexico. Association for Computational Linguistics.

Talia Tseriotou, Adam Tsakalidis, Peter Foster, Terence Lyons, and Maria Liakata. 2023. Sequential path signature networks for personalised longitudinal language modeling. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 5016–5031, Toronto, Canada. Association for Computational Linguistics.

World Health Organization. 2022. *World Mental Health Report: Transforming Mental Health for All*. World Health Organization, Geneva.

Ayah Zirikly, Philip Resnik, Özlem Uzuner, and Kristy Hollingshead. 2019. CLPsych 2019 shared task: Predicting the degree of suicide risk in Reddit posts. In *Proceedings of the Sixth Workshop on Computational Linguistics and Clinical Psychology*, pages 24–33, Minneapolis, Minnesota. Association for Computational Linguistics.

A Prompt Templates

A.1 Prompt Template

The few-shot balance examples include representative cases for four label combinations: `Switch=0, Escalation=0`, `Switch=S, Escalation=0`, `Switch=0, Escalation=E`, and `Switch=S, Escalation=E`.

Prompt Instruction: Switch and Escalation Detection

 # Instruction
You are given a timeline of Reddit posts written by the same user. Your task is to determine whether the **last post** shows a mental health change.
Define the switch and Esscalation follow CLPsysch **# User Prompt**
Timeline:
{USER_TIMELINE}
 # Few-shot Examples
Examples
 # Answer
XML format: <Esscalation>...</Esscalation>, <Switch>...</Switch>

For Task 3.1, we use few-shot prompting for change summary generation. Few-shot demonstrations are randomly sampled from the training set and prepended to the target input. Each demonstration contains a post sequence and its reference change summary, helping the model learn the expected summary style, including temporal progression, psychological dynamics, and change direction.

Prompt Instruction: Change Summary Generation

 # Instruction
You are given a chronologically ordered sequence of Reddit posts surrounding a clinically meaningful mental health change event. Your task is to summarize the user's mental health changes across the sequence. Focus on psychological dynamics, not on summarizing each post separately.
Mention the main mental health theme, how it changes over time, the change type as Switch or Escalation, and the direction as improvement or deterioration.
 # User Prompt Posts in chronological order:
{POSTS}
 # Few-shot Examples
Examples
 # Answer XML format: <summary>...</summary>

A.2 Model Settings

Table 3 shows the model and decoding settings used in our experiments.

Table 3: Model and decoding settings used in our experiments.

Setting	Value
Model	Qwen2.5-72B-Instruct-GPTQ-Int8
Inference engine	vLLM
Prompting strategy	Few-shot prompting
Max new tokens	8192
Temperature	0.0
Top-p	0.95
Top-k	70
Decoding strategy	Greedy decoding

Table 4 reports the F1-scores for Switch and Escalation detection under different prompting strategies and context window sizes.

Table 4: F1-scores for Switch and Escalation detection under different prompting strategies and context window sizes on the training data.

Context Window	Switch F1	Escalation F1
Zero-shot		
$k = 3$	0.453	0.407
$k = 4$	0.420	0.378
$k = 5$	0.410	0.634
Few-shot		
$k = 3$	0.435	0.513
$k = 4$	0.427	0.566
$k = 5$	0.447	0.568
Few-shot balance		
$k = 5$	0.410	0.634

psytechlab at CLPsych 2026: Utilising Natural Language Processing methods and Large Language Models for Social Media Text Analysis

Igor Buyanov
Psytechlab
i.buyanov@psytechlab.co

Nafisa Valieva
Psytechlab
n.valieva@psytechlab.co

Ekaterina Mazurina
Psytechlab
e.mazurina@psytechlab.co

Abstract

Social media posts are a rich and valuable source of data for analyzing mental health states and users' well-being using automated analysis tools. In this work, we demonstrate how we used a range of Natural Language Processing (NLP) methods, including Long Short-Term Memory (LSTM), BERT-based models, and Large Language Models (LLMs), for self-state and well-being analysis and summarization during the CLPsych Shared Task 2026. Our approach achieved one of the top Consistency and Contradiction scores for the summarization task and also middle-level results for the other tasks. By testing and developing such mental health-state estimation systems, we contributed to improving mental health support systems. We make our code available[1].

1 Introduction

In modern times, mental health problems are recognized as a major topic. The WHO statistics say that more than 1 billion people suffer from mental health disorders, which is 1 in 7 people globally (WHO, 2025). These statistics gain the researcher's attention from many scientific fields to address these issues. In particular, AI researchers are actively exploring ways to develop automated tools for diagnostic and therapeutic purposes to meet this demand.

To this day, researchers have achieved notable success in the diagnosis of various mental disorders, from depression and anxiety to bipolar disorder and schizophrenia. The main source of data is social media like Reddit[2], X[3], and other platforms. These platforms allow users to discuss many topics, including their mental states. This fact is leveraged by the researchers to bound certain users' textual productions to their self-disclosed mental states. Upon these datasets, the machine learning techniques can be applied to reveal various language patterns. Such models being trained can be used to identify users with mental health issues at scale, only by the data they produce, allowing for targeted help. Moreover, the growing power of LLMs can help researchers and practitioners achieve notable results in reasoning and analyzing data, offering insights into individuals' mental states from their textual data.

Unfortunately, the described approach also has drawbacks. The first one is potential label noise, as the researcher relies solely on user-provided information, which cannot be reliably confirmed. On the other hand, collecting clinically reliable annotated data raises the expenses and ethical challenges.

The second drawback is that researchers must associate all user data with a single static label. In reality, the mental state has a dynamic nature, and so many mental issues are better seen in their changes to understand their severity. Another side of this drawback is that not all content is actually meaningful from a diagnostic perspective, as social media platforms are primarily built for other purposes.

Luckily, the CLPsych Shared Task 2026 (Ali et al., 2026) provides researchers with the opportunity to work with the dataset without the aforementioned drawbacks. Specifically, the organizers suggest three challenging tasks: Adaptive and Maladaptive ABCD element Prediction, Moment of Change (MoC) identification, and Summary of changes in a timeline. The provided dataset consists of the user's post time series, professionally annotated using the MIND framework (Atzil-Slonim, 2025), a conceptual model that represents the human experience as a continually evolving series of self-states.

In this paper, we describe our system as psytechlab team for solving this task. Briefly, our system combines various approaches and models. By the

[1] https://github.com/psytechlab/CLPsych2026/
[2] https://www.reddit.com/
[3] https://x.com/

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 510–520
July 4, 2026 ©2026 Association for Computational Linguistics

end of the Shared Task, our approach beat almost all baselines, though it remains far from the best solution. All prompts that we used can be found in Appendix B.

2 Methods

2.1 Task 1

The goal of this task is twofold: to predict the dominant ABCD subelements and the self-state composition, and to estimate the presence value at scale 1-5, indicating the extent to which the self-states are expressed in the post. The ABCD stands for

- Affect (A): emotional tone or mood.
- Behavior(B), which is split into a toward Self (B-S) and Others (B-O): actions or tendencies directed inward or outward.
- Cognition (C), which is split into a toward Self (C-S) and Others (C-O): beliefs, interpretations, and appraisals.
- Desire (D): motivations, needs, wishes, and expectations.

Metrics for Task 1. The first task result is scored by many aspects; here, we provide only for ranking: (1) compute F1 per element, (2) Macro average across 6 elements within each valence, (3) Average of Adaptive and Maladaptive Macro F1. The second task is scored by MAE, RMSE, Quadratic Weighted Kappa (QWK), and Spearman correlation. The final ranking is the mean of the per-valence RMSEs.

Submission 1. We apply the pipeline approach for this task. First, we split the post into sentences. Then, each sentence is classified into one of the subelements or the irrelevant class. Finally, we aggregate the sentence predictions to determine the most dominant subelement using subelement-specific weights, obtained from the source dataset by calculating each subelement's presence proportion. Having a subelement, we can map it directly to the state and valence.

We train a classifier to predict all existing subelements. Because the training data was insufficient, we used two strategies to augment the dataset. The first is to translate the part of the dataset from (Buyanov et al., 2025), where some classes are semantically aligned with subelements. The second one is to directly generate data using local Qwen3.5-35B-A3B (Team, 2026) with an 8-shot prompt using evidence as examples. We generate 500 texts for each class. Then we merge all data into a single dataset and split it into training and test sets. We experiment with BERT (Devlin et al., 2019) and ModernBERT (Warner et al., 2024), and they show comparative performance: 0.79 F1 macro for BERT and 0.80 F1 macro for ModernBERT.

Speaking of aggregating schema, to obtain weights, we split all the training text into sentences, assign them a subelement if they overlap with the evidence, and annotate a piece of post text for a particular subelement. If the sentence doesn't overlap with any evidence, it's assigned as irrelevant. Next, we calculate the proportion of subelements grouped by valence and state. The irrelevant class is assigned a minimum value across all weights.

For inference, we obtain predictions for each sentence and sum the weights across all predicted subelements and the irrelevant class. Next, we take a maximum aggregation for the subelement weights grouped by valence and state. At this point, we have two dominant subelements for each valence. Finally, we exclude subelements if their cumulative weight is below the irrelevant cumulative weight.

To estimate the presence value for each valence, we use ModernBERT in regression mode and train it on available data. Thanks to ModernBERT's wide context length, we can use the entire post text. We draw inspiration from previous CLPsych Shared Task solutions (Chakraborty et al., 2025), where this approach has proven promising.

Submission 2. Here we prompt the local Qwen3.5-35B-A3B to solve the task, providing it with the names of the subelements. We use the same ModernBERT model to estimate the valence presence.

2.2 Task 2

In Task 2, participants were given a chronologically ordered sequence of posts and asked to detect *Switch* or *Escalation* in each post in the timeline.

Metrics for Task2. Switch and Escalation labels are evaluated as independent binary classification tasks. In post-level evaluation, precision, recall, and F1-score per label are pooled across all posts. For timeline-level evaluation, precision, recall, and F1-score per label are macro-averaged across timelines.

Submission 1. To obtain post representations,

Task	Metric	Score	Rank
Task 1.1	Average Subelement Macro F1	0.274	12 (17)
Task 1.2	Avg RMSE Maladaptive + Adaptive	1.407	15 (17)
Task 2	Combined (Post/Timeline) Macro F1	0.372	15 (18)
Task 3.1	Score Rank Average	7.3	8 (13)
Task 3.2 Improvments	Overall Score	0.544	5 (9)
Task 3.2 Deterioration	Overall Score	0.491	6 (9)

Table 1: Overall results and ranks for CLPsych 2026 Shared Task. The overall rank range is shown in parentheses.

we split the post text into sentences and combine embeddings from MiniLM-L6-v2 (Reimers and Gurevych, 2019) and concatenate the probability vectors from several models as it was done in (Bayram and Benhiba, 2022): BERTweet Sentiment (Pérez et al., 2021), EmoRoBERTa (Ghoshal, 2022), and twitter-roberta-emotion (Barbieri et al., 2020). Then, sentence vectors are averaged to obtain the final post text representation. Next, we use the BiLSTM (Lample et al., 2016) model to predict Switch and Escalation separately. To obtain optimal hyperparameters, we use Optuna (Akiba et al., 2019) for optimization.

Submission 2. This is the same architecture as Submission 1. The difference is the special feature set, which includes temporal features of the posts.

Additional submissions. Here, we primarily experiment with the Tempoformer model (Tseriotou et al., 2024), with which we make three submissions. Another model we experimented with was HoRoBERT (Hills et al., 2024).

2.3 Task 3

In Task 3.1, the participants must generate a timeline-level summary describing patterns of self-state dynamics and their progression over time within a sequence of posts surrounding a change event (Switch/Escalation). The Task 3.2 goal was to identify and summarize recurrent dynamic patterns of deterioration or improvement that recur across multiple sequences.

Metrics for Task3.1. *Contradiction Score:* For each predicted sentence, the mean NLI (Natural Language Inference) contradiction probability is computed against all gold summary sentences, then the maximum is taken across predicted sentences and sequences. *Consistency Score* is equal to $1 - \texttt{mean_contradiction}$. *Rouge-L Recall* (Lin, 2004) score was computed to measure temporal word coverage and *BERTScore Recall* (Zhang et al., 2020) for semantic content coverage.

Metrics for Task3.2. The results for Task 3.2 are evaluated by humans using the following criteria. *Fit of Evidence Support* evaluates how well the proposed signature is supported by the sequences submitted as evidence. *Recurrence score* evaluates how recurrent the proposed signature is across sequences. *Specificity score* evaluates how specific and non-generic the proposed signature is. The overall score for this task is computed using the formula $0.5 \cdot \texttt{Fit} + 0.5 \cdot \texttt{HarmonicMean(Recurrence, Specificity)}$.

Submission 1. We used zero-shot prompting to prompt Qwen3.5-35B-A3B model to summarize timeline of posts (no predictions from Task 1 and Task 2 were used), however, in the system instruction we provided MIND framework description.

Submission 2. At first, we used predictions from Task 1 and a few-shot prompting to make an intermediate summary of each post in a timeline using the Qwen3.5-35B-A3B model. Then, given intermediate summaries of each post in a timeline, we also got a full summary of the timeline using few-shot prompting and the Qwen3.5-35B-A3B model.

Submission 3. We used the default prompt from (Sandu et al., 2025) CLPsych 2025 shared tasks (Tseriotou et al., 2025) best submission for timeline summarization. The model instruction lacks conceptual explanations or additional context to support a timeline-level summary. We also used the Llama-3.2-3B-Instruct (AI, 2024) model for this task.

Additional sumbissions. The setting is the same as in Submission 3, but we used the Qwen3.5-35B-A3B model instead of Llama-3.2-3B-Instruct.

For Task 3.2, we used the Llama-3.2-3B-Instruct model. Firstly, LLM was instructed to detect the direction of well-being change in each timeline (deterioration, improvement, mixed, or neutral). After that, we instructed the LLM to detect ABCD elements (with no subelements) and assign a self-state

label (adaptive or maladaptive). After that, we obtained statistics on the number of adaptive and maladaptive states present in each ABCD element type and each self-state ratio across well-being change types. Then we found CE (Change Event) index in a timeline based on the number of adaptive and maladaptive states in each post. Then, a summary of example timelines with improvement and deterioration change types was obtained using LLM.

3 Results and analysis

The overall results are shown in Table 1. The per-task submission results are in Tables 2, 3, 4, 5, 6 in Appendix A. Our system outperforms all baselines except Tempoformer on Task 2, though its rank is at the lower intermediate level. Here, we conduct an analysis to identify potential reasons.

For Task 1.1, the main caveat is the long text, which can contain multiple subelements. We split the text into sentences and aggregate the results, but the classifier, despite a good overall metric, poorly recognizes the irrelevant class. As irrelevant sentences are far more than relevant ones, their poor recognition leads to heavy noise at the aggregation step. The reason is that the irrelevant class is not bounded by any rules, so the potential volume of this class is huge. If the irrelevant class doesn't have enough negative examples where patterns similar to the relevant classes occur, but they are only similar, the model will make false positive predictions on such texts. As evidence, the confusion matrix shows that the irrelevant class is confused with 23 out of 32 subelements, mostly from 1 to 5 percent, and 11 with the "Relating behaviour" subelement.

The bad result of Task 1.1 influences Task 1.2 because the presence value should be estimated for where the valence is predicted to be at all. Actually, on the validation set we form from the overall training data, ModernBERT shows 0.824 RMSE on Adaptive data and 0.904 RMSE on Maladaptive data.

The main weakness of Task 2 is the model, which cannot capture all necessary dependencies. In particular, the Switch performance is twice as poor as Escalation, which heavily undermines the overall metric. We hypothesize that it's due to label formulation. The Escalation label is defined as a gradual intensification of mood over a sequence of consecutive posts. Mood expressions can be directly bound to certain lexical patterns. On the other hand, the Switch label is defined as the difference in well-being scores between two consecutive posts exceeding 2. The well-being score is based on the Global Assessment of Functioning, which means there is an intermediate hidden layer between the label being predicted and the text. It seems the model lacks the power to identify the necessary dependencies between the text and the well-being difference.

Another issue that we faced was the Tempoformer training. We could not manage to properly train it during the competition time, but succeeded at the analysis time, as can be seen in Table 4. Still, the organizer Tempoformer baseline is much higher than our results. This highlights the importance of a careful understanding of the training process.

Speaking of Task 3, we were surprised that a comparably small and old model with a simple prompt can achieve high results on metrics that show the form of a summary. The main consideration here is to find a way to incorporate the content data without losing the accurate form of the summary.

4 Conclusion

We have presented a mixed system that used various NLP techniques on each Shared Task. Across all tasks, our system outperformed almost all baselines and achieved notable performance on two metrics in Task 3.1. Nevertheless, there are many points to improve the solution that we highlight in the analysis section.

5 Limitations

This study has several limitations. First, although the shared task data are more structured than typical social media mental health corpora, the target labels still simplify complex and dynamic psychological processes. Thus, model outputs should be interpreted as approximations of annotated self-state patterns rather than as direct evidence of a person's mental condition.

Second, our methods are constrained by the limited amount of training data. In Task 1, sentence-level splitting and aggregation likely introduced additional noise, especially due to weak recognition of irrelevant sentences. In addition, the use of translated and synthetically generated examples may have introduced distributional mismatch. In Task 2, the comparatively weak results suggest that our temporal models did not fully capture longer-

range dependencies and subtle changes across timelines. For Task 3, strong automatic summarization metrics do not guarantee clinically faithful summaries, since LLMs may omit important evidence or produce plausible but unsupported statements.

Third, this work was conducted in a restricted-access environment, which limited the range of models and experiments available to us. In particular, large language models were used only in locally deployed form; no external API-based or cloud-hosted LLMs were used. While this reduced potential data exposure, it also constrained experimentation.

6 Ethical Considerations

From an ethical perspective, this work deals with highly sensitive mental health-related text and should be treated with appropriate care. Even when shared for research, such data may contain intimate personal information. Using only local LLMs in a restricted-access environment was an important privacy-preserving measure in our study. However, privacy protection alone does not remove other risks. The models may reflect demographic, cultural, or linguistic biases present in the data and in pretrained models, leading to harmful false positives or false negatives.

Finally, our systems are intended strictly for research purposes and not for clinical diagnosis or autonomous decision-making. Predictions and generated summaries should not be treated as definitive assessments of an individual's mental health and should not replace qualified professional judgment.

References

Meta AI. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Takuya Akiba, Shotaro Sano, Toshihiko Yanase, Takeru Ohta, and Masanori Koyama. 2019. Optuna: A next-generation hyperparameter optimization framework. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 2623–2631.

Iqra Ali, Talia Tseriotou, Guy Dvir, Callum Chan, Yuxiang Zhou, Juan Antonio Lossio-Ventura, Ayal Klein, Aya Shamir, Dan Sayda, Anthony Hills, Aya Zirikly, Diana Inkpen, Dana Atzil-Slonim, and Maria Liakata. 2026. Overview of the clpsych 2026 shared task: Capturing and characterizing mental health changes through social media timeline dynamics. In *Proceedings of the 11th Workshop on Computational Linguistics and Clinical Psychology*. "Association for Computational Linguistics"‘.

Dana Atzil-Slonim. 2025. Multimodal intrapersonal and interpersonal dynamics (mind): A transtheoretical coding manual.

Dana Atzil-Slonim. 2026. Leveraging theoretical and technological innovations to study the mechanisms that underlie therapeutic change in psychotherapy. In Louis G. Castonguay, Dana Atzil-Slonim, Michael Barkham, and Wolfgang Lutz, editors, *Practice-Based Evidence in the Psychological Therapies: Toward Policy Implications for Research, Training, and Clinical Guidelines*. Oxford University Press, New York.

Francesco Barbieri, Luis Espinosa Anke, Jose Camacho-Collados, Leonardo Sparta, Sara Rineh, Leila Moraes, and Asahi Ushio. 2020. TweetEval: Unified Benchmark and Comparative Evaluation for Tweet Classification. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 1644–1650.

Ulya Bayram and Lamia Benhiba. 2022. Emotionally-informed models for detecting moments of change and suicide risk levels in longitudinal social media data. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 219–225, Seattle, USA. Association for Computational Linguistics.

Igor Buyanov, Darya Yaskova, Danil Serenko, Danil Shkereda, Andrey Yaskov, and Ilya Sochenkov. 2025. The methodology of constructing the large-scale dataset for detecting presuicidal and anti-suicidal signals in social media texts in russian. In *Proceedings of the Institute for System Programming*, volume 37, pages 191–210.

Suchandra Chakraborty, Sudeshna Jana, Manjira Sinha, and Tirthankar Dasgupta. 2025. Self-state evidence extraction and well-being prediction from social media timelines. *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186. Association for Computational Linguistics.

Arpan Ghoshal. 2022. Emoroberta: A fine-tuned roberta model for emotion detection. `https://huggingface.co/arpanghoshal/EmoRoBERTa`.

Anthony Hills, Talia Tseriotou, Xenia Miscouridou, Adam Tsakalidis, and Maria Liakata. 2024. Exciting mood changes: A time-aware hierarchical transformer for change detection modelling.

Guillaume Lample, Miguel Ballesteros, Sandeep Subramanian, Kazuya Kawakami, and Chris Dyer. 2016. Neural architectures for named entity recognition. In

Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 260–270.

Chin-Yew Lin. 2004. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pages 74–81, Barcelona, Spain. Association for Computational Linguistics.

Juan Manuel Pérez, Juan Carlos Giudici, and Franco Luque. 2021. pysentimiento: A python toolkit for sentiment analysis and socialnlp tasks. *Preprint*, arXiv:2106.09462.

Nils Reimers and Iryna Gurevych. 2019. Sentence-bert: Sentence embeddings using siamese bert-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics.

Anastasia Sandu, Teodor Mihailescu, Ana Sabina Uban, and Ana-Maria Bucur. 2025. Capturing the dynamics of mental well-being: Adaptive and maladaptive states in social media.

Qwen Team. 2026. Qwen3.5-35b-a3b: Agentic coding power, now open to all. `https://huggingface.co/Qwen/Qwen3.5-35B-A3B`.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Talia Tseriotou, Jenny Chim, Ayal Klein, Aya Shamir, Guy Dvir, Iqra Ali, Cian Kennedy, Guneet Singh Kohli, Anthony Hills, Ayah Zirikly, Dana Atzil-Slonim, and Maria Liakata. 2025. Overview of the CLPsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 193–217, Albuquerque, New Mexico. Association for Computational Linguistics.

Talia Tseriotou, Adam Tsakalidis, and Maria Liakata. 2024. TempoFormer: A transformer for temporally-aware representations in change detection.

Benjamin Warner, Antoine Chaffin, Benjamin Clavié, Orion Weller, Oskar Hallström, Said Taghadouini, Alexis Gallagher, Raja Biswas, Faisal Ladhak, Tom Aarsen, Nathan Cooper, Griffin Adams, Jeremy Howard, and Iacopo Poli. 2024. Smarter, better, faster, longer: A modern bidirectional encoder for fast, memory efficient, and long context finetuning and inference. *Preprint*, arXiv:2412.13663.

WHO. 2025. World mental health today: latest data. geneva: World health organization.

Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q. Weinberger, and Yoav Artzi. 2020. Bertscore: Evaluating text generation with BERT. In *International Conference on Learning Representations*.

A Appendix. Detailed CLPsych 2026 Shared Task Results

Team	Average Subelement Macro F1	Adaptive Subelement Macro F1	Maladaptive Subelement Macro F1	Rank
Submission 1	0.274	0.263	0.285	12
Submission 2	0.139	0.139	0.140	-
CUNY (Best)	0.442	0.388	0.496	1

Table 2: Task 1.1 submission results and comparison with the best performing solutions

Team	Average RMSE	Adaptive RMSE	Maladaptive RMSE	Rank
Submission 1	1.407	1.389	1.424	15
Submission 2	1.416	1.379	1.45	-
Meronym Labs (Best)	0.917	0.833	1	1

Table 3: Task 1.2 submission results and comparison with the best performing solutions

Team	Combined Macro F1	Post Macro F1	Timeline Macro F1	Rank
Submission 1	0.372	0.371	0.372	15
Submission 2	0.324	0.316	0.332	-
Submission 3 (tempoformer)	0.215	0.197	0.233	-
Submission 4 (HoRoBERT)	0.405	0.464	0.346	-
Submission 5 (tempoformer)	0.414	0.439	0.389	-
Submission 6 (tempoformer)	0.429	0.498	0.36	-
USAI (Best)	0.6	0.639	0.561	1

Table 4: Task 2 submission results and comparison with the best performing solutions

Team	CS	CT	Rouge-L Recall	BERTScore Recall	Score Average	Rank
Submission 1	0.692	0.819	0.220	0.279	0.343	-
Submission 2	0.659	0.885	0.235	0.303	0.328	-
Submission 3	0.857	0.571	0.078	0.147	0.378	8
Submission 4	0.768	0.808	0.119	-	-	-
MERONYM_LABS (Best)	0.801	0.659	0.266	0.345	0.438	1

Table 5: Task 3.1 submission results and comparison with the best performing solutions

Team	Change Type	Rank	Fit score	Recurrence	Specificity	Overall
Ours	Improvement	5	0.6875	1	0.25	0.5437
DreamerNLplus	Improvement	1	0.625	0.8125	1	0.7608
Ours	Deterioration	6	0.625	0.625	0.25	0.4911
CSE_IIT_Ropar	Deterioration	1	0.875	0.5625	0.9375	0.7891

Table 6: Task 3.2 submission results and comparison with the best performing solutions

B Appendix. Prompts

Task 1.1 Submission 1 prompt

You are an experienced psychologist specializing in assessing the emotional tone of texts. You need to classify texts. Each text must be assigned most appropriate adaptive subelement and most appropriate maladaptive subelement. Description of the subelements with examples for classification:
Adaptive subelements:
1. Calm/ laid back
2. Sad, Emotional pain, grieving
3. Content, happy, joy, hopeful
4. Vigor / energetic
5. Justifiable anger/ assertive anger, justifiable outrage
6. Proud
7. Feel loved, belong
8. Relating behavior
9. Autonomous or adaptive control behavior
10. Self care and improvement
11. Perception of the other as related
12. Perception of the other as facilitating autonomy needs
13. Self-acceptance and compassion
14. Relatedness
15. Autonomy and adaptive control
16. Competence, self esteem, self-care
Maladaptive subelements:
1. Anxious/ fearful/ tense
2. Depressed, despair, hopeless
3. Mania
4. Apathic, don't care, blunted
5. Angry (aggression), disgust, contempt
6. Ashamed, guilty
7. Feel lonely
8. Fight or flight behavior
9. Over controlled or controlling behavior
10. Self harm, neglect and avoidance
11. Perception of the other as detached or over-attached
12. Perception of the other as blocking autonomy needs
13. Self criticism
14. Expectation that relatedness needs will not be met
15. Expectation that autonomy needs will not be met
16. Expectation that competence needs will not be met
Your answer should contain only the names of the subelements; no additions, clarifications, explanations or other words are needed.
Return ONLY a JSON object in this exact format: `{{"adaptive": ["subelement"], "maladaptive": ["subelement"]}}`
Text for classification: `{text}`

Task 3.1 Submission 1 prompt

Task:
Your task is to summarize self-states for each timeline, given the sequence of posts on the timeline. Specifically, generate a summary focusing on the interplay between adaptive and maladaptive self-states along the timeline. Emphasize temporal dynamics focusing on concepts such as flexibility, rigidity, improvement, and deterioration. If applicable, describe the extent to which the dominance of the self-states changes over time and how changes in aspects (Affect, Behavior, Cognition, and Desire) contribute to these transitions.
—
Definitions:
Self-states constitute identifiable units characterized by specific combinations of Affect, Behavior, Cognition, and Desire/Need (ABCD dimensions) that tend to be coactivated in a meaningful manner for limited periods of time.
- An adaptive self-state pertains to aspects of Affect, Behaviour, and Cognition towards the self or others, which is conducive to the fulfillment of basic desires/needs (D), such as relatedness, autonomy and competence.
- A maladaptive self-state pertains to aspects of Affect, Behaviour, and Cognition towards the self or others, that hinder the fulfillment of basic desires/needs (D).
ABCD dimensions:
1. Affect (A): The type of emotion expressed by the person.
- Adaptive Examples: Calm/Laid back, Emotional Pain/Grieving, Content/Happy, Vigor/Energetic, Justifiable, Anger/Assertive Anger, Proud.
- Maladaptive Examples: Anxious/Tense/Fearful, Depressed/Despair/Hopeless, Mania, Apathetic/Don't care/Blunted, Angry (Aggressive, Disgust, Contempt), Ashamed/Guilty.
2. Behavior of the self with the Other (BO) : The person's main behavior(s) toward the other
- Adaptive Examples: Relating behavior, Autonomous behavior
- Maladaptive Examples: Fight or fight behavior, Overcontrolled/controlling behavior
3. Behavior toward the Self (BS): The person's main behavior(s) toward the self
- Adaptive Examples: Self-care behavior
- Maladaptive Examples: Self-harm, Neglect, Avoidance behavior
4. Cognition of the Other (CO): The person's main perceptions of the other
- Adaptive Examples: Perception of the other as related, Perception of the other as facilitating autonomy needs
- Maladaptive Examples: Perception of the other as detached or over attached, Perception of the other as blocking autonomy needs
5. Cognition of the Self (CS): How the person perceives themselves.
- Adaptive Examples: Self-acceptance and self-compassion
- Maladaptive Examples: Self-criticism
6. Desire (D): The person's main desire, need, intention, fear or expectation
- Adaptive Examples: Relatedness, Autonomy and adaptive control, Competence, Self-esteem, Self-care
- Maladaptive Examples: Expectation that relatedness need will not be met, Expectation that autonomy needs will not be met, Expectation that competence needs will not be met
—
Guidelines for Output:
- Response Section: Provide an answer under the headings '### Timeline Summary:'.

- Format the answer as a single paragraph, making it clear and consise.
- The summary should be no more than 350 words.
- Ensure the timeline summary captures the main points without unnecessary details.
- Ensure to explicitly state the ABCD dimensions when pointing out self-states
—
Example:
Input text:
1. <post_1_in_timeline>
2. <post_2_in_timeline>
...
n. <post_n_in_timeline>
Output text:
Timeline Summary: <example_timeline_summary>
—
Analyze the following input text based on the given criteria.
Input Text:
<posts>
Output Text:

Task 3.1 Submission 2 Post Summary Intermediate prompt

You are a mental health expert and analyzing a patient's social media post to determine their well-being, their dominant self-state of either adaptive or maladaptive. Your task is to summarize self-states for the social media post below. Specifically, generate a summary of the interplay between adaptive and maladaptive states identified in the post. Begin by determining which self-state is dominant (adaptive/maladaptive) and describe it first. For each self-state, identify the central organizing aspect (A, B, C, or D) that drives the state and structure the summary around it. Describe how this central aspect influences the rest, emphasizing potential causal relationships between them. Then, proceed to the second self-state and follow the same approach. If the post contains only one self-state (either adaptive or maladaptive), summarize only that state. Note that the summary does not need to explicitly highlight A, B, C, or D, but should aim to naturally integrate these elements into the description. You have 2 analysis examples.
—
Definitions:
Self-states constitute identifiable units characterized by specific combinations of Affect, Behavior, Cognition, and Desire/Need (ABCD dimensions) that tend to be coactivated in a meaningful manner for limited periods of time.
- An adaptive self-state pertains to aspects of Affect, Behaviour, and Cognition towards the self or others, which is conducive to the fulfillment of basic desires/needs (D), such as relatedness, autonomy and competence.
- A maladaptive self-state pertains to aspects of Affect, Behaviour, and Cognition towards the self or others, that hinder the fulfillment of basic desires/needs (D).
ABCD dimensions:
1. Affect (A): The type of emotion expressed by the person.
- Adaptive Examples: Calm/Laid back, Emotional Pain/Grieving, Content/Happy, Vigor/Energetic, Justifiable, Anger/Assertive Anger, Proud.
- Maladaptive Examples: Anxious/Tense/Fearful, Depressed/Despair/Hopeless, Mania, Apathetic/Don't care/Blunted, Angry (Aggressive, Disgust, Contempt), Ashamed/Guilty.
2. Behavior of the self with the Other (BO) : The person's main behavior(s) toward the other
- Adaptive Examples: Relating behavior, Autonomous behavior
- Maladaptive Examples: Fight or fight behavior, Overcontrolled/controlling behavior
3. Behavior toward the Self (BS): The person's main behavior(s) toward the self
- Adaptive Examples: Self-care behavior
- Maladaptive Examples: Self-harm, Neglect, Avoidance behavior
4. Cognition of the Other (CO): The person's main perceptions of the other
- Adaptive Examples: Perception of the other as related, Perception of the other as facilitating autonomy needs
- Maladaptive Examples: Perception of the other as detached or over attached, Perception of the other as blocking autonomy needs
5. Cognition of the Self (CS): How the person perceives themselves.
- Adaptive Examples: Self-acceptance and self-compassion
- Maladaptive Examples: Self-criticism
6. Desire (D): The person's main desire, need, intention, fear or expectation
- Adaptive Examples: Relatedness, Autonomy and adaptive control, Competence, Self-esteem, Self-care
- Maladaptive Examples: Expectation that relatedness need will not be met, Expectation that autonomy needs will not be met, Expectation that competence needs will not be met
Presence refers to the extent to which the self state influences the person's expressed experience in the post, how strongly it was emphasized in the post. It captures how central the self state is to the overall experience described in the post. Presence ratings are independent. Presence reflects psychological centrality and experiential influence, not mere frequency of words. Both adaptive and maladaptive self states may receive high presence scores within the same post, if both strongly shape the expressed experience. If a self state is not expressed in the post, it receives a score of 1.
—
Analysis 1: <post_1>
Adaptive post segments:
<adaptive_states_presence1>
<adaptive_element1>
Maladaptive post segments:
<maladaptive_states_presence1>
<maladaptive_elements1>
Summary:
<example_summary1>
—
Analysis 2:
<post_2>
Adaptive post segments:
<adaptive_states_presence2>
<adaptive_element2>
Maladaptive post segments:
<maladaptive_states_presence2>
<maladaptive_elements2>
Summary:
<example_summary2>
—
Important notes:

- Keep your analysis compact, but still informative. Analyze the post as a whole.
- Return ONLY the summary, nothing more.
- Do not add stylistic features, such as making a bold text.
- Before you create a final summary, make sure you understand the examples.
Now analyze the following patent post.
<patient_post>
Adaptive post segments:
<adaptive_segments>
Maladaptive post segments:
<maladaptive_segments>
Summary:
<fill your assessment here>

Task 3.1 Submission 2 Timeline Summary prompt

Task:
Your task is to summarize self-states for each timeline, given the sequence of posts'analysis on the timeline. Specifically, generate a summary focusing on the interplay between adaptive and maladaptive self-states along the timeline. Emphasize temporal dynamics focusing on concepts such as flexibility, rigidity, improvement, and deterioration. If applicable, describe the extent to which the dominance of the self-states changes over time and how changes in aspects (Affect, Behavior, Cognition, and Desire) contribute to these transitions.
—
Definitions:
Self-states constitute identifiable units characterized by specific combinations of Affect, Behavior, Cognition, and Desire/Need (ABCD dimensions) that tend to be coactivated in a meaningful manner for limited periods of time.
- An adaptive self-state pertains to aspects of Affect, Behaviour, and Cognition towards the self or others, which is conducive to the fulfillment of basic desires/needs (D), such as relatedness, autonomy and competence.
- A maladaptive self-state pertains to aspects of Affect, Behaviour, and Cognition towards the self or others, that hinder the fulfillment of basic desires/needs (D).
ABCD dimensions:
1. Affect (A): The type of emotion expressed by the person.
- Adaptive Examples: Calm/Laid back, Emotional Pain/Grieving, Content/Happy, Vigor/Energetic, Justifiable, Anger/Assertive Anger, Proud.
- Maladaptive Examples: Anxious/Tense/Fearful, Depressed/Despair/Hopeless, Mania, Apathetic/Don't care/Blunted, Angry (Aggressive, Disgust, Contempt), Ashamed/Guilty.
2. Behavior of the self with the Other (BO) : The person's main behavior(s) toward the other
- Adaptive Examples: Relating behavior, Autonomous behavior
- Maladaptive Examples: Fight or fight behavior, Overcontrolled/controlling behavior
3. Behavior toward the Self (BS): The person's main behavior(s) toward the self
- Adaptive Examples: Self-care behavior
- Maladaptive Examples: Self-harm, Neglect, Avoidance behavior
4. Cognition of the Other (CO): The person's main perceptions of the other
- Adaptive Examples: Perception of the other as related, Perception of the other as facilitating autonomy needs
- Maladaptive Examples: Perception of the other as detached or over attached, Perception of the other as blocking autonomy needs
5. Cognition of the Self (CS): How the person perceives themselves.
- Adaptive Examples: Self-acceptance and self-compassion
- Maladaptive Examples: Self-criticism
6. Desire (D): The person's main desire, need, intention, fear or expectation
- Adaptive Examples: Relatedness, Autonomy and adaptive control, Competence, Self-esteem, Self-care
- Maladaptive Examples: Expectation that relatedness need will not be met, Expectation that autonomy needs will not be met, Expectation that competence needs will not be met
Presence refers to the extent to which the self state influences the person's expressed experience in the post, how strongly it was emphasized in the post. It captures how central the self state is to the overall experience described in the post. Presence ratings are independent. Presence reflects psychological centrality and experiential influence, not mere frequency of words. Both adaptive and maladaptive self states may receive high presence scores within the same post, if both strongly shape the expressed experience. If a self state is not expressed in the post, it receives a score of 1.
—
Guidelines for Output:
- Response Section: Provide an answer under the headings '### Timeline Summary:'.
- Format the answer as a single paragraph, making it clear and consise.
- The summary should be no more than 350 words.
- Ensure the timeline summary captures the main points without unnecessary details.
- Ensure to explicitly state the ABCD dimensions when pointing out self-states
—
Example:
Input text:
1. <intermediate_post1_summary>
2. <intermediate_post2_summary>
...
N. <intermediate_postN_summary>
Output text:
Timeline Summary:
<example_timeline_summary>
—
Analyze the following input text based on the given criteria.
Input Text:
<intermediate_posts_summaries>
Output Text:

Task 3.1 Submission 3 prompt

Given the following series of Reddit posts from one user, generate a timeline-level summary. Begin by determining which self-state is dominant (adaptive/maladaptive) and describe it first.
Timeline:
<timeline_text>

Response format - ONLY json: {{ "summary": "<timeline-level summary>" }}

Task 3.2 Well-being change direction detection prompt

You are an expert clinical psychology annotator.
You classify summaries of user post-sequences into one of four categories describing the dominant direction of well-being change in the sequence.
Categories:
- deterioration: well-being decreases; maladaptive states gain strength; hopelessness, self-criticism, isolation, or symptom escalation emerge.
- improvement: well-being increases; adaptive states gain strength; hope, connection, coping, insight, or recovery emerge.
- mixed: both directions are clearly present (e.g., partial recovery followed by relapse, or vice versa) and neither dominates.
- neutral: no clear direction of change is described.
Return ONLY a JSON object with keys:
"change_type": one of deterioration | improvement | mixed | neutral
"confidence": float in [0, 1]
"rationale": one short sentence citing concrete elements from the summary
Summary:
summary_text

Task 3.2 ABCD elements and self-states detection prompt

You are an expert clinical psychology annotator using the MIND (ABCD) framework with self-state analysis.
For each social media post, identify elements belonging to these categories:
- A (Affect): emotions, feelings, mood states
- B (Behavior): actions taken or avoided, including social actions
- C (Cognition): thoughts, beliefs, interpretations, self-talk
- D (Desire/motivation): wants, intentions, goals, drives For each element, assign a self-state label:
- maladaptive: expresses hopelessness, self-criticism, isolation, avoidance, symptom escalation, rumination, worthlessness, risk
- adaptive: expresses hope, connection, healthy coping, help-seeking, insight, agency, self-compassion, growth
One post can contain multiple elements of the same category, and can contain both adaptive and maladaptive elements simultaneously (this is called a dialogue between self-states – mark both).
If a post has no codable ABCD content (e.g., a meme link, a factual question, pure small talk), return an empty "elements" list.
Return ONLY a JSON object:

```
{
    "elements": [
      {
       "type": "A"|"B"|"C"|"D",
       "text": "short quote or paraphrase from the post",
       "state": "adaptive"|"maladaptive",
       "confidence": 0.0-1.0
      }
    ]
}
```

Self-State Identification with Retrieved In-Context Examples and Open-Weight LLMs

Alina Ponomareva* **and Nina Stekacheva Sancho*** **and Karina Litvinova***
University of Zurich
{alina.ponomareva,nina.stekachevasancho,karina.litvinova}@uzh.ch

Abstract

This paper describes the StateOfMIND team submission to Task 1 of the CLPsych 2026 shared task on identifying adaptive and maladaptive psychological self-states in social media posts. For each post, the task requires systems to predict which fine-grained subelements of a self-state are expressed (Task 1.1) and to rate how strongly adaptive and maladaptive states are present (Task 1.2). We address both subtasks with a retrieval-augmented in-context learning ensemble of two open-weight LLMs, Qwen3.5-27B and Mistral-Small-3.2-24B-Instruct. Our approach combines label-aware retrieval of in-context examples, a three-prompt decomposition targeting adaptive content and the Affect element, and subtask-specific ensemble rules that favor precision for subelement classification and recall for presence rating. Our best submissions rank 2nd of 17 teams on Task 1.1 (Macro F1 = 0.441) and 5th of 17 teams on Task 1.2 (RMSE = 0.994), with ablations showing retrieval and ensembling as the largest drivers of performance.

1 Introduction

Large language models are increasingly used to support mental health-related NLP, particularly for interpreting psychological signals in user-generated text (Guo et al., 2024; Malgaroli et al., 2025). Yet clinically meaningful annotation often requires mapping nuanced language onto specialized psychological constructs rather than detecting broad sentiment or distress. The CLPsych shared tasks provide a controlled setting for evaluating such capabilities under limited-data conditions.

The CLPsych 2026 shared task (Ali et al., 2026) builds on prior CLPsych work on mental health modeling from social media (Tsakalidis et al., 2022; Tseriotou et al., 2025). In particular, it extends the CLPsych 2025 task, which was grounded in the MIND framework (Atzil-Slonim, 2025, 2026). Following the ABCD view of personality states (Revelle, 2007), MIND represents self-states through four component types: Affect (A), Behavior toward Self and Others (B-S, B-O), Cognition about Self and Others (C-S, C-O), and Desire (D). These components define adaptive and maladaptive self-states, which reflect how individuals experience themselves and others at a given moment. While the broader task emphasizes longitudinal modeling of self-states for mental health analysis, Task 1 focuses specifically on post-level identification of these components and their relative psychological centrality.

In this work, we address Tasks 1.1 and 1.2, which require predicting ABCD subelement compositions (Atzil-Slonim, 2025) and estimating the presence of adaptive and maladaptive self-states for individual posts. The task is challenging because it combines sparse fine-grained labels, ordinal presence ratings, and limited training data annotated under a specialized psychological framework. We propose a retrieval-augmented in-context learning system that annotates each post independently using two open-weight LLMs and three targeted prompts per model. Our contributions are:

- A retrieval pipeline that combines semantic similarity, label-aware scoring, and diversity re-ranking to select in-context examples;
- Separate unified, adaptive-focused, and Affect-focused prompts for better coverage of adaptive content and Affect subelements;
- Subtask-specific cross-model merging that favors precision for subelement classification and recall for presence estimation.

Empirically, we show that retrieval contributes most to performance, that no single merge strategy optimizes both subtasks, and that the Affect-focused prompt accounts for most of the F1 gain from prompt decomposition.

*All authors contributed equally.

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 521–530
July 4, 2026 ©2026 Association for Computational Linguistics

2 Background and Related Work

2.1 LLMs for Mental Health NLP

The application of LLMs to clinical and mental health NLP has grown rapidly, covering mental health prediction from online text, interpretable analysis of social media posts, and broader clinical applications such as screening, monitoring, and decision support (Uluslu et al., 2024; Xu et al., 2024; Yang et al., 2024; Guo et al., 2024; Malgaroli et al., 2025). Their ability to capture nuanced linguistic patterns makes them well-suited to clinically grounded tasks that require detailed interpretation beyond surface-level sentiment. Recent work has shown that prompt engineering and structured inference strategies are particularly important for adapting general-purpose LLMs to such tasks, especially when annotated data follows specialized clinical or psychological frameworks (He et al., 2023; Sivarajkumar et al., 2024).

2.2 In-Context Learning and Retrieval-Augmented Prompting

In-context learning has become a standard way to adapt LLMs to specialized tasks without fine-tuning (Brown et al., 2020; Liu et al., 2023), and the choice of in-context examples can substantially affect performance (Liu et al., 2022). Retrieval-augmented approaches select examples from a labeled pool using dense similarity to the target input (Rubin et al., 2022), and can be combined with diversity criteria such as Maximal Marginal Relevance (Carbonell and Goldstein, 1998) to avoid redundancy. In the CLPsych 2025 shared task, top systems used open-weight LLMs with in-context learning, including retrieval-augmented example selection (Antony and Schoene, 2025) and structured prompt design (Chan et al., 2025).

2.3 Task and Data

CLPsych 2026 Shared Task 1 focuses on post-level identification of adaptive and maladaptive psychological self-states. We address both subtasks.

Task 1.1 (Subelement Classification). Systems predict the composition of the adaptive and/or maladaptive self-state expressed in each post. A self-state is represented by selected subelements from six ABCD elements: Affect (A), Behavior toward Self (B-S), Behavior toward Others (B-O), Cognition toward Self (C-S), Cognition toward Others (C-O), and Desire (D). Each subelement has a predefined valence, either adaptive or maladaptive, and at most one subelement can be selected for each element and valence.



Figure 1: System architecture with the RAG and LLM ensemble.

Task 1.2 (Presence Rating). Systems assign separate presence scores to the adaptive and maladaptive self-states on a scale from 1 (not present) to 5 (highly present). The score reflects how central the self-state is to the post.

Dataset. The shared task dataset is an extended subset of the CLPsych 2022 "Reddit-New" corpus (Tsakalidis et al., 2022) and comprises 40 longitudinal social media timelines, partitioned into 30 for training (373 posts, 236 with evidence annotations) and 10 for testing (92 posts). The training set provides the post text and metadata (timeline ID, post ID, date, and chronological index), together with post-level MIND annotations: adaptive and maladaptive self-state classifications, ABCD subelements with textual evidence spans, and presence scores on the 1–5 scale. The Task 1.1 label space consists of 12 element–valence slots (6 elements $\times$ 2 valences) and 32 subelements in total; the full taxonomy is listed in Table 7. The test set provides

only the post text and the metadata required for evaluation.

3 Methods

Building on prior CLPsych systems that used retrieval-augmented in-context learning and structured prompting (Antony and Schoene, 2025; Chan et al., 2025), we adapt this setup to the fine-grained MIND label space by making example selection label-aware, separating prompts for error-prone parts of the taxonomy, and combining two open-weight LLMs with subtask-specific ensemble aggregation.

Figure 1 summarizes our pipeline. We use an ensemble of two open-weight LLMs: Qwen3.5-27B (Qwen Team, 2026) and Mistral-Small-3.2-24B-Instruct-2506 (Mistral AI, 2025), executed via vLLM (Kwon et al., 2023), with an in-context learning example corpus embedding using gte-multilingual-base (Zhang et al., 2024). For each post, we retrieve the 8 nearest in-context examples and run three sequential prompts per model; outputs are merged in two stages, with Task 1.1 keeping Qwen3.5's elements and Task 1.2 taking their union with Mistral-Small-3.2 arbitration on conflicts.

3.1 Retrieving In-Context Learning Examples

For every training post that carries an evidence annotation, we precompute a dense embedding using gte-multilingual-base (Zhang et al., 2024) and store these vectors in an in-memory index. We additionally build a small codebook of 12 embeddings, one per (element, valence) pair, by encoding the concatenated subelement descriptions for that pair. At prediction time, for a target post p we (i) score every candidate c as an equal mix of text cosine similarity to p and a codebook label score (which sums the similarities between p and the codebook entries matching c's gold elements), (ii) retain the top $K_{\text{pool}} = 20$ candidates, and (iii) greedily re-rank to $K = 8$ using a similarity-and-diversity criterion inspired by MMR (Carbonell and Goldstein, 1998), where diversity is measured as coverage of distinct subelement labels among the already-selected examples. Candidates from the target post's own timeline are excluded throughout (leave-one-timeline-out). The Affect-focused call (Section 3.2, P3) uses a variant of this procedure: candidates are restricted to training posts that carry an Affect annotation, the codebook is disabled, and the diversity objective targets coverage of Affect subelements specifically.

3.2 Prompting Strategy

For each post and for each of the two LLMs, we issue three prompts that include: task requirements, definitions of the adaptive and maladaptive valences and of the element inventory, the eight retrieved in-context examples, and explicit response-format guidelines. The three prompts differ in scope: P1 asks for everything at once, P2 narrows attention to the adaptive valence by conditioning on the maladaptive predictions of P1, and P3 narrows attention to a single element. Full templates are in Appendix C.

(P1) Unified prompt. A single prompt that asks the model to return, in a structured form, both valences' elements (with subelements) and both presence scores in one shot. The prompt is conditioned on the eight RAG examples from Section 3.1. The unified call lets the model use inter-element context when assigning subelements.

(P2) Adaptive-focused prompt. The maladaptive elements that the model predicted in P1 are injected into the prompt header, and the model is asked to return only the adaptive elements; the same eight RAG examples from P1 are reused. By making the maladaptive prediction explicit, the call shifts attention toward adaptive content that the unified call tends to under-predict.

(P3) Affect-focused prompt. A prompt that asks the model to return only the Affect element (in either valence). P3 uses element-specific RAG so that all eight in-context examples illustrate Affect annotations. Affect is the element with the largest and most semantically diverse subelement space; isolating it lets the model concentrate retrieval and reasoning on a single category.

3.3 Two-Stage Ensemble Merge

The six structured outputs (three prompts $\times$ two models) are combined in two stages.

Stage 1: per-model reconciliation. The three calls within each model are merged deterministically: maladaptive elements and both presence scores are taken from P1; adaptive elements are taken from P2; the Affect (A) element in either valence, when present in P3, overrides whatever P1 or P2 produced; if after this step a valence has no elements, its presence is reset to 1. This rule is identical for Qwen3.5 and Mistral-Small-3.2.

Submission	Task 1.1 (Sub F1) ↑			Task 1.2 (RMSE) ↓		
	Adapt.	Malad.	Avg	Adapt.	Malad.	Avg
Sub. 1 (Solo Qwen3.5, early RAG impl.)	**0.371**	0.510	0.440	1.253	0.935	1.094
Sub. 2 (Ensemble, Union+Mistral-Small-3.2)	0.357	0.508	0.433	**1.130**	**0.858**	**0.994**
Sub. 3 (Ensemble, Qwen3.5 elements)	0.346	**0.537**	**0.441**	1.184	**0.858**	1.021
Organizer baseline	0.156	0.338	0.247	1.409	1.439	1.424

Table 1: Test-set scores for our submissions. **Bold** marks the best score among our submissions per metric.

Stage 2: cross-model merge. Presence scores and element predictions are aggregated separately for each valence.

Presence (both tasks). The two presence scores from Qwen3.5 and Mistral-Small-3.2 are averaged and rounded. When the two models agree, the score is unchanged. In the critical 1/2 boundary case (one model votes "not present", the other "somewhat present"), the merged score is 2, favoring presence detection.

Elements: Task 1.1. Take Qwen3.5's elements (and their subelements). The Task 1.1 metric (Macro F1, see Section 3.4) is sensitive to false positives, so we use only one model's elements rather than the union, accepting some recall loss in exchange for precision.

Elements: Task 1.2. Take the union of both models' elements; on shared elements with disagreeing subelement labels, prefer Mistral-Small-3.2. This design choice was based on preliminary development experiments, where Mistral-Small-3.2 tended to yield lower presence-rating error, whereas Qwen3.5 produced more reliable subelement predictions. The Task 1.2 metric (RMSE, see Section 3.4) is sensitive to missing elements (a missing element forces presence to 1, incurring a large quadratic penalty when the gold value is 4 or 5), so the union acts as a safety net.

3.4 Evaluation Metrics

The performance of each submission was evaluated using task-specific metrics specified by the shared task organizers. For Task 1.1, element presence is evaluated as 12 binary classifications (6 elements $\times$ 2 valences) using Precision, Recall, and F1, while subelement classification is evaluated via multi-class F1 per element. The official ranking metric is the mean of the Adaptive subelement Macro F1 and the Maladaptive subelement Macro F1.

For Task 1.2, the 1–5 presence ratings for the adaptive and maladaptive self-states are evaluated using Mean Absolute Error (MAE), Root Mean Square Error (RMSE), Quadratic Weighted Kappa (QWK), and Spearman correlation. The official ranking metric for this subtask is the mean of the Adaptive RMSE and the Maladaptive RMSE.

4 Results and Discussion

Our system was evaluated across two subtasks: subelement classification (Task 1.1) and presence rating (Task 1.2).

4.1 System Configurations

We submitted three configurations:

- **Sub. 1**: Qwen3.5 with an alternative RAG setup: utilizing all-MiniLM-L6-v2 as the underlying embedding model (Wang et al., 2020) and augmented training examples for the Affect-focused prompt.
- **Sub. 2**: Qwen3.5 + Mistral-Small-3.2 ensemble; merged elements take the union of both models, with Mistral-Small-3.2 winning on subelement conflicts (see Section 3.3 – Task 1.2).
- **Sub. 3**: same ensemble as Sub. 2, but merged elements come solely from Qwen3.5 (see Section 3.3 – Task 1.1).

Presence merging is identical for Sub. 2 and Sub. 3 and explained in Section 3.3. Test-set scores are reported in Table 1.

4.2 Task 1.1: Subelement Classification

Our Task 1.1 entry, Sub. 3, achieves **0.441 Avg F1**, placing 2nd of 17 teams on the official leaderboard, only 0.0004 below the leader. The following ablations show how each component of the pipeline contributes to this score.

Prompt decomposition. We hold the ensemble (Qwen3.5 + Mistral-Small-3.2) and MMR-8 retrieval fixed and vary the prompts described in

Section 3.2 (Table 2). The adaptive-conditioned prompt P2 contributes only a small gain over P1 alone, while the Affect-focused prompt P3 contributes the bulk of the improvement. The full three-call pipeline gains 0.029 Avg F1 over the single-call baseline.

Retrieval strategy. We compare three retrieval regimes within the full ensemble pipeline, holding the prompts and merging strategy fixed (Table 3). In-context examples are essential: removing RAG collapses Avg F1 (0.206 vs 0.441 Avg F1). One-step retrieval and MMR-8 re-ranking perform comparably (0.444 vs 0.441 Avg F1), suggesting that diversity re-ranking offers no measurable advantage on this test set.

Ensemble merge. We isolate the contribution of each individual model and of the merge strategy, holding the three-prompt pipeline and MMR-8 re-ranking fixed (Table 4). Qwen3.5 outperforms Mistral-Small-3.2 on subelement classification (0.427 vs 0.373 Avg F1), motivating Qwen3.5's role as the Task 1.1 element-extraction anchor. Consistent with this, the precision-oriented merge using Qwen3.5's elements (Sub. 3) achieves higher Avg F1 than the union-based Sub. 2 merge (0.441 vs 0.433; Table 1).

4.3 Task 1.2: Presence Rating

Our Task 1.2 entry, Sub. 2, achieves **0.994 Avg RMSE**, placing 5th of 17 teams on the official leaderboard. We analyze presence-rating performance using both the component ablations above and an additional Task 1.2-specific comparison of merge rules (Table 5).

Prompt decomposition. P2 does not help presence rating: adding it to P1 increases Avg RMSE from 1.015 to 1.035. The full three-call pipeline incurs only a small RMSE cost relative to P1 alone (1.021 vs 1.015), so the F1 gains discussed in Section 4.2 do not substantially hurt presence rating.

Retrieval strategy. Retrieval remains important for Task 1.2: removing in-context examples increases Avg RMSE from 1.021 to 1.958. One-step retrieval and MMR-8 re-ranking are effectively tied (1.020 vs 1.021).

Ensemble merge. The ensemble results support the asymmetric merge. Mistral-Small-3.2 achieves lower RMSE than Qwen3.5 (1.083 vs 1.153; Table 4), supporting its use as the Task 1.2 conflict arbiter. In the Task 1.2-specific merge ablation, the Sub. 2 union ensemble obtains the best RMSE (0.994), providing additional support for our submitted merge strategy among the alternatives tested (Table 5).

4.4 Valence Asymmetry

Across all configurations and metrics, our system performs better on the maladaptive valence than on the adaptive one. In our top Task 1.1 run (Sub. 3), the Maladaptive Subelement Macro F1 reaches 0.537 while the Adaptive Subelement Macro F1 stays at 0.346. The same pattern holds for presence rating: our top Task 1.2 run (Sub. 2) attains a Maladaptive RMSE of 0.858 versus an Adaptive RMSE of 1.130. On the maladaptive valence specifically, our Subelement Macro F1 ranks 1st and our RMSE ranks 2nd among all 17 participating teams, indicating that our pipeline is particularly effective at detecting and rating maladaptive states.

5 Conclusions

The system presented in this paper demonstrates the potential of retrieval-augmented open-weight LLMs for identifying psychologically grounded self-states in social media posts. We addressed CLPsych 2026 Task 1 with an ensemble that combines semantic and label-aware retrieval of in-context examples, targeted prompts for adaptive content and Affect, and subtask-specific aggregation across Qwen3.5-27B and Mistral-Small-3.2-24B-Instruct. This design was effective in the shared task: our system ranked 2nd of 17 teams on Task 1.1, 5th on Task 1.2, and 1st on maladaptive-valence subelement F1.

Our ablations show that retrieval is the strongest driver of performance, while prompt decomposition and ensemble aggregation address different error modes in the fine-grained MIND label space. Overall, these results suggest that open-weight LLMs can support clinically motivated annotation schemes when their predictions are grounded in related examples and guided by task-specific structure. At the same time, the sensitivity of performance to label sparsity, valence asymmetry, and merge strategy highlights the need for careful evaluation before such systems are used beyond shared-task settings.

6 Limitations

Despite competitive performance, our system exhibits several key limitations.

Adaptive state blind spots. As discussed in Section 4.4, our system remains weaker on adaptive than maladaptive self-states. Subtle adaptive signals such as coping, self-care, help-seeking, or constructive social engagement are still easier to miss, especially when they co-occur with more salient maladaptive content.

Single-run test evaluation. All test-set submissions were evaluated as single inference runs at $T = 0.1$ in the blind shared-task setting, rather than as repeated stochastic runs of the same configuration. Consequently, small differences across configurations should be interpreted with caution, as they may reflect stochastic decoding or submission-level variance in addition to true design effects (Reimers and Gurevych, 2017; Card et al., 2020).

Limited model comparison. We explored several open-weight LLMs (including Llama and Gemma variants) during development, but the final pipeline and ablations are based on a single model pair (Qwen3.5-27B and Mistral-Small-3.2-24B-Instruct). These models offered the best balance of following structured JSON instructions and feasible GPU memory use in preliminary tests, but we did not perform a systematic comparison across model families and sizes.

Computational overhead. Our pipeline runs three targeted prompts across two LLMs, requiring six retrieval-augmented inference passes per post. Although this design targets adaptive underprediction, Affect diversity, and cross-subtask robustness, it increases inference cost and latency and may hinder real-time use in high-volume clinical monitoring environments.

Ethics

The CLPsych 2026 dataset is an extended subset of the CLPsych 2022 "Reddit-New" corpus (Tsakalidis et al., 2022), provided in de-identified form. Although Reddit is an anonymous platform, posts on mental health topics remain sensitive; we accessed the data only after signing the Data Access Agreement and complied with its restrictions on storage, sharing, and processing throughout the project.

In compliance with the shared task requirements, we used only open-weight LLMs, run locally; no closed-source models or external API services were used for experimentation or analysis on the shared task data.

Computational systems trained on annotated social media data should be regarded as supportive research tools rather than substitutes for clinical judgment. Real-world deployment would require validation by mental-health professionals, attention to demographic and cultural variation in how mental states are expressed, and safeguards against misuse. We also recognize that LLM-based systems may reflect biases present in their pretraining corpora; our in-context learning setup grounded in the MIND framework can mitigate some of this drift, but does not eliminate it.

To protect the privacy of the social media posters whose data was used, this work should not be reproduced on the original dataset by parties without an active Data Access Agreement; the contributions reported here are the design and analysis of our system, not the data itself.

Acknowledgments

We thank Simon Clematide and Andrianos Michail for their supervision, feedback, and guidance during the development of this system.

References

Iqra Ali, Talia Tseriotou, Guy Dvir, Callum Chan, Yuxiang Zhou, Juan Antonio Lossio-Ventura, Ayal Klein, Aya Shamir, Dan Sayda, Anthony Hills, Aya Zirikly, Diana Inkpen, Dana Atzil-Slonim, and Maria Liakata. 2026. Overview of the clpsych 2026 shared task: Capturing and characterizing mental health changes through social media timeline dynamics. In *Proceedings of the 11th Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Anson Antony and Annika M. Schoene. 2025. Retrieval-enhanced mental health assessment: Capturing self-state dynamics from social media using in-context learning. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 268–278. Association for Computational Linguistics.

Dana Atzil-Slonim. 2025. Multimodal intrapersonal and interpersonal dynamics (MIND): A transtheoretical coding manual.

Dana Atzil-Slonim. 2026. Leveraging theoretical and technological innovations to study the mechanisms that underlie therapeutic change in psychotherapy. In Louis G. Castonguay, Dana Atzil-Slonim, Michael Barkham, and Wolfgang Lutz, editors, *Practice-Based Evidence in the Psychological Therapies: Toward Policy Implications for Research, Training, and*

Clinical Guidelines. Oxford University Press, New York.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, and 12 others. 2020. Language models are few-shot learners. In *Advances in Neural Information Processing Systems*, volume 33, pages 1877–1901.

Jaime G. Carbonell and Jade Goldstein. 1998. The use of MMR, diversity-based reranking for reordering documents and producing summaries. In *Proceedings of the 21st Annual International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 335–336.

Dallas Card, Peter Henderson, Urvashi Khandelwal, Robin Jia, Kyle Mahowald, and Dan Jurafsky. 2020. With little power comes great responsibility. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 9263–9274. Association for Computational Linguistics.

Callum Chan, Sunveer Khunkhun, Diana Inkpen, and Juan Antonio Lossio-Ventura. 2025. Prompt engineering for capturing dynamic mental health self-states from social media posts. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 256–267. Association for Computational Linguistics.

Zhijun Guo, Alvina Lai, Johan H. Thygesen, Joseph Farrington, Thomas Keen, and Kezhi Li. 2024. Large language models for mental health applications: Systematic review. *JMIR Mental Health*, 11:e57400.

Kai He, Rui Mao, Qika Lin, Yucheng Ruan, Xiang Lan, Mengling Feng, and Erik Cambria. 2023. A survey of large language models for healthcare: from data, technology, and applications to accountability and ethics. *arXiv preprint arXiv:2310.05694*.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph E. Gonzalez, Hao Zhang, and Ion Stoica. 2023. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the 29th Symposium on Operating Systems Principles*, pages 611–626.

Jiachang Liu, Dinghan Shen, Yizhe Zhang, Bill Dolan, Lawrence Carin, and Weizhu Chen. 2022. What makes good in-context examples for GPT-3? In *Proceedings of Deep Learning Inside Out (DeeLIO 2022): The 3rd Workshop on Knowledge Extraction and Integration for Deep Learning Architectures*, pages 100–114, Dublin, Ireland and Online. Association for Computational Linguistics.

Pengfei Liu, Weizhe Yuan, Jinlan Fu, Zhengbao Jiang, Hiroaki Hayashi, and Graham Neubig. 2023. Pre-train, prompt, and predict: A systematic survey of prompting methods in natural language processing. *ACM Computing Surveys*, 55(9):1–35.

Matteo Malgaroli, Katharina Schultebraucks, Keris Jan Myrick, Alexandre Andrade Loch, Laura Ospina-Pinillos, Tanzeem Choudhury, Roman Kotov, Munmun De Choudhury, and John Torous. 2025. Large language models for the mental health community: framework for translating code to care. *The Lancet Digital Health*, 7(4).

Mistral AI. 2025. Mistral-Small-3.2-24B-Instruct-2506. `https://huggingface.co/mistralai/Mistral-Small-3.2-24B-Instruct-2506`. Model card. Accessed: 2026-05-19.

Qwen Team. 2026. Qwen3.5: Towards native multimodal agents.

Nils Reimers and Iryna Gurevych. 2017. Reporting score distributions makes a difference: Performance study of LSTM-networks for sequence tagging. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pages 338–348. Association for Computational Linguistics.

William Revelle. 2007. Experimental approaches to the study of personality. In Richard W. Robins, R. Chris Fraley, and Robert F. Krueger, editors, *Handbook of Research Methods in Personality Psychology*, pages 37–61. Guilford Press, New York.

Ohad Rubin, Jonathan Herzig, and Jonathan Berant. 2022. Learning to retrieve prompts for in-context learning. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 2655–2671, Seattle, United States. Association for Computational Linguistics.

Sonish Sivarajkumar, Mark Kelley, Alyssa Samolyk-Mazzanti, and Yanshan Wang. 2024. An empirical evaluation of prompting strategies for large language models in zero-shot clinical natural language processing: Algorithm development and validation study. *JMIR Medical Informatics*, 12(1):e55318.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Talia Tseriotou, Jenny Chim, Ayal Klein, Aya Shamir, Guy Dvir, Iqra Ali, Cian Kennedy, Guneet Singh Kohli, Anthony Hills, Ayah Zirikly, Dana Atzil-Slonim, and Maria Liakata. 2025. Overview of the CLPsych 2025 shared task: Capturing mental health

dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 193–217, Albuquerque, New Mexico. Association for Computational Linguistics.

Ahmet Yavuz Uluslu, Andrianos Michail, and Simon Clematide. 2024. Utilizing large language models to identify evidence of suicidality risk through analysis of emotionally charged posts. In *Proceedings of the 9th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2024)*, pages 264–269, St. Julians, Malta. Association for Computational Linguistics.

Wenhui Wang, Furu Wei, Li Dong, Hangbo Bao, Nan Yang, and Ming Zhou. 2020. MiniLM: Deep self-attention distillation for task-agnostic compression of pre-trained transformers. In *Advances in Neural Information Processing Systems 33 (NeurIPS 2020)*.

Xuhai Xu, Bingsheng Yao, Yuanzhe Dong, Saadia Gabriel, Hong Yu, James Hendler, Marzyeh Ghassemi, Anind K. Dey, and Dakuo Wang. 2024. Mental-LLM: Leveraging large language models for mental health prediction via online text data. *Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies*, 8(1):1–32.

Kailai Yang, Tianlin Zhang, Ziyan Kuang, Qianqian Xie, Jimin Huang, and Sophia Ananiadou. 2024. MentaLLaMA: Interpretable mental health analysis on social media with large language models. In *Proceedings of the ACM Web Conference 2024 (WWW '24)*, New York, NY, USA. Association for Computing Machinery.

Xin Zhang, Yanzhao Zhang, Dingkun Long, Wen Xie, Ziqi Dai, Jialong Tang, Huan Lin, Baosong Yang, Pengjun Xie, Fei Huang, Meishan Zhang, Wenjie Li, and Min Zhang. 2024. mGTE: Generalized long-context text representation and reranking models for multilingual text retrieval. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 1393–1412, Miami, Florida, US. Association for Computational Linguistics.

A Ablation Tables

Configuration	Avg F1 ↑	Avg RMSE ↓
P1 only	0.412	**1.015**
P1 + P2	<u>0.414</u>	1.035
P1 + P2 + P3 (Sub. 3)	**0.441**	<u>1.021</u>

Table 2: Ablation 1: prompt decomposition, full ensemble (Qwen3.5 + Mistral-Small-3.2) with MMR-8. P1 is the unified prompt, P2 adds the adaptive-focused prompt, and P3 adds the Affect-focused prompt. **Bold** marks the best score in each column; <u>underline</u> marks the runner-up.

Configuration	Avg F1 ↑	Avg RMSE ↓
Zero-shot	0.206	1.958
One-step retrieval	**0.444**	**1.020**
MMR-8 (Sub. 3)	<u>0.441</u>	<u>1.021</u>

Table 3: Ablation 2: retrieval strategy, full ensemble with all three prompts. Zero-shot removes in-context examples, one-step retrieval directly selects the eight highest-scoring examples, and MMR-8 additionally reranks a candidate pool for label diversity.

Configuration	Avg F1 ↑	Avg RMSE ↓
Mistral-Small-3.2	0.373	1.083
Qwen3.5	0.427	1.153
Ensemble (Sub. 2)	**0.433**	**0.994**

Table 4: Ablation 3: ensemble strategy, full three-prompt pipeline with MMR-8. Single-model rows use only that model's outputs; the ensemble row combines Qwen3.5 and Mistral-Small-3.2 with Sub. 2 cross-model aggregation rules.

Configuration	Avg F1 ↑	Avg RMSE ↓
Confidence-based merge	0.386	1.467
Aggressive-presence merge	**0.434**	<u>1.0</u>
Union ensemble (Sub. 2)	<u>0.433</u>	**0.994**

Table 5: Ablation 4: ensemble merge approaches for presence score, full three-prompt pipeline with MMR-8. Confidence-based merge uses model confidence in cross-model selection, aggressive-presence merge favors non-1 presence predictions from either model, and the union ensemble is Sub. 2 averaging-based merge.

B Hyperparameter Settings

Parameter	Value
Inference	
Weight precision	FP16
Max context length	16,384 tokens
Sampling temperature	0.1
Sampling top-p	1.0 (vLLM default)
Max generation tokens	100
Retrieval	
Candidate pool size	$K_{\text{pool}} = 20$
In-context examples	$K = 8$
Diversity weight	$\alpha = 0.6$
Other	
Post text truncation	1,800 characters

Table 6: Hyperparameter settings for our submitted system.

C Prompt Templates

We reproduce the actual prompt templates used in our pipeline. The static *ABCD taxonomy block* (which lists element definitions, valence definitions, and all 32 subelement descriptions) is abridged here for space; it remains constant across the three prompts. The example post shown below is generated for illustration, and no actual dataset content is reproduced.

(P1) Unified prompt

System:
You are a clinical psychology annotation assistant trained in the MIND framework. The MIND framework analyzes social media posts to identify psychological self-states. Each post may express adaptive and/or maladaptive psychological states across 6 dimensions: Affect (A), Behavior toward Others (B-O), Behavior toward Self (B-S), Cognition about Others (C-O), Cognition about Self (C-S), and Desire (D). Your job: identify which specific subelements are present and rate their overall presence.

[ABCD TAXONOMY BLOCK — see Appendix D]

PRESENCE SCALE (reflects psychological centrality, not mere frequency of words):
1 = Not present
2 = Somewhat present
3 = Moderately present
4 = Much present
5 = Highly present

RULES:
1. For each ABCD element (A, B-O, B-S, C-O, C-S, D), decide if it is present.
2. If present, choose the single most prominent subelement.
3. Assign ADAPTIVE_PRESENCE and MALADAPTIVE_PRESENCE scores (1–5).
4. Output ONLY these 4 lines: ADAPTIVE_ELEMENTS, ADAPTIVE_PRESENCE, MALADAPTIVE_ELEMENTS, MALADAPTIVE_PRESENCE. No evidence lines, no extra text.
5. If no adaptive elements: write ADAPTIVE_ELEMENTS: NONE and ADAPTIVE_PRESENCE: 1.
6. If no maladaptive elements: write MALADAPTIVE_ELEMENTS: NONE and MALADAPTIVE_PRESENCE: 1.
7. Only annotate elements you are confident about. It is better to miss an element than to predict the wrong subelement.

User:
Here are 8 annotated examples:
[examples]

Now annotate the following post:

POST: "I haven't been able to focus on anything lately. Even small tasks feel overwhelming. I keep thinking that I should be doing better by now, which only makes me feel worse. But yesterday I called my friend, and talking to her helped a bit. I still feel exhausted, but at least I managed to take a shower and eat something afterward."

(P2) Adaptive-focused prompt

System:
You are a clinical psychology annotation assistant trained in the MIND framework. Your task: identify ADAPTIVE psychological patterns that co-exist alongside maladaptive states in this post. Adaptive states often co-exist with maladaptive states. A person describing depression may also show self-care, self-acceptance, healthy grieving, or reaching out for support.

[ABCD ADAPTIVE TAXONOMY BLOCK — see Appendix D, adaptive subelements only]

[PRESENCE SCALE — as above]

RULES:
1. Focus ONLY on ADAPTIVE elements. Maladaptive annotation is already done.
2. For each element, decide if an adaptive subelement is present.
3. Assign ADAPTIVE_PRESENCE (1-5).
4. Output ONLY these 2 lines: ADAPTIVE_ELEMENTS and ADAPTIVE_PRESENCE.
5. If no adaptive elements: ADAPTIVE_ELEMENTS: NONE and ADAPTIVE_PRESENCE: 1.
6. For B-S and C-S: predict whenever you see ANY signal.
7. For A, B-O, C-O, D: only annotate if confident in the specific subelement.

User:
Here are 8 annotated examples:
[examples]

The following maladaptive patterns were already identified:
MALADAPTIVE_ELEMENTS: A:8, B-S:2
MALADAPTIVE_PRESENCE: 4

Now identify ADAPTIVE elements in this post:

POST: "[same example post as P1]"

(P3) Affect-focused prompt

System:
You are a clinical psychology annotation assistant trained in the MIND framework.

[ABCD TAXONOMY BLOCK — see Appendix D, Affect (A) row only]

RULES:
1. ONLY evaluate the Affect (A) element. Decide if it is present.
2. If present, choose the single most prominent subelement.
3. Output ONLY these 2 lines: ADAPTIVE_ELEMENTS and MALADAPTIVE_ELEMENTS. No presence scores.
4. If adaptive A is not present: write ADAPTIVE_ELEMENTS: NONE.
5. If maladaptive A is not present: write MALADAPTIVE_ELEMENTS: NONE.
6. Only annotate if you are confident.

User:
Here are 8 annotated examples (all illustrating Affect annotations):
[examples]

Now annotate the following post:

POST: "[same example post as P1]"

D ABCD Taxonomy Block

Element	Valence	ID	Subelement
A	Adaptive	1	Calm/laid back — feeling at ease, relaxed, or peacefully accepting of one's situation
	Adaptive	3	Sad/emotional pain/grieving — expressing sorrow or grief in a healthy, processing way
	Adaptive	5	Content/happy/joy/hopeful — feeling satisfied, cheerful, or optimistic
	Adaptive	7	Vigor/energetic — feeling motivated, lively, or full of energy
	Adaptive	9	Justifiable/assertive anger — expressing appropriate anger or standing up for oneself
	Adaptive	11	Proud — feeling a sense of achievement, self-worth, or pride
	Adaptive	13	Feel loved/belong — feeling connected, valued, or accepted by others
	Maladaptive	2	Anxious/fearful/tense — feeling worried, nervous, scared, or on edge
	Maladaptive	4	Depressed/despair/hopeless — feeling deeply sad, empty, or worthless
	Maladaptive	6	Mania — showing elevated mood, grandiosity, impulsivity beyond normal excitement
	Maladaptive	8	Apathetic/blunted — feeling emotionally flat, numb, or unable to care
	Maladaptive	10	Angry/aggression/disgust/contempt — feeling hostile, bitter, or resentful
	Maladaptive	12	Ashamed/guilty — feeling intense shame, self-blame, or disproportionate guilt
	Maladaptive	14	Feel lonely — feeling isolated, disconnected, or painfully alone
B-O	Adaptive	1	Relating behavior — actively reaching out, connecting, or cooperating with others
	Adaptive	3	Autonomous or adaptive control behavior — taking independent action or setting healthy boundaries
	Maladaptive	2	Fight or flight behavior — reacting with aggression, withdrawal, or avoidance driven by fear
	Maladaptive	4	Over-controlled or controlling behavior — excessively managing, manipulating, or dominating interactions
B-S	Adaptive	1	Self-care and improvement — taking steps to look after oneself physically, mentally, or emotionally
	Maladaptive	2	Self-harm, neglect, and avoidance — self-destructive behavior, ignoring needs, or avoiding self-care
C-O	Adaptive	1	Perception of other as related — viewing others as caring, supportive, or emotionally connected
	Adaptive	3	Perception of other as facilitating autonomy — seeing others as encouraging independence
	Maladaptive	2	Perception of other as detached or over-attached — seeing others as emotionally unavailable or intrusive
	Maladaptive	4	Perception of other as blocking autonomy — viewing others as controlling or restricting
C-S	Adaptive	1	Self-acceptance and compassion — treating oneself with kindness or accepting flaws without harsh judgment
	Maladaptive	2	Self-criticism — harshly judging, blaming, or devaluing oneself
D	Adaptive	1	Relatedness — wanting to connect, bond, or maintain meaningful relationships
	Adaptive	3	Autonomy and adaptive control — desiring independence, self-direction, or healthy control
	Adaptive	5	Competence/self-esteem/self-care — wanting to feel capable, worthy, or to take good care of oneself
	Maladaptive	2	Expectation that relatedness needs will not be met — believing one will remain unloved or rejected
	Maladaptive	4	Expectation that autonomy needs will not be met — believing one will remain trapped or powerless
	Maladaptive	6	Expectation that competence needs will not be met — believing one will remain incompetent or worthless

Table 7: Full ABCD subelement taxonomy used in the prompt templates.
Abbreviations: A = Affect, B-O = Behavior toward Others, B-S = Behavior toward Self, C-O = Cognition of the Other, C-S = Cognition of the Self, D = Desire.

Team Aurevia at CLPsych 2026: Local Healthcare NLP for Schema-Constrained Self-State Modeling

Nathan Roll[1], **Irene Yi**[1], **Sufian Aldogom**[2], **Grace Brown**[1], **Eric Basile**[4], **Isaac Gutterman**[3], **Lakshika Tennakoon**[1], **Ammar Ahmed**[4]
[1]Stanford University [2]Massachusetts Institute of Technology
[3]Harvard College [4]Aurevia
nroll@stanford.edu

Abstract

Team Aurevia introduces a local open-weight healthcare NLP system for the CLPsych 2026 Shared Task, predicting MIND-coded self-state elements, moments of change, summaries, and dynamic signatures from social media timelines. The task is difficult because coarse presence, fine-grained ABCD subelements, and timeline-level change require different longitudinal evidence over privacy-sensitive mental-health language. Our system combines TF-IDF retrieval, schema-constrained local Qwen2.5 prompting, ordinal calibration, and conservative post-processing. Among official runs, Aurevia ranked 3rd of 17 for Task 1.2 presence prediction, 5th of 13 overall for Task 3.1, 1st on Task 3.1 consistency, and 2nd of 9 for MIND-coded deterioration signatures, showing that constrained local LLM pipelines can remain competitive in sensitive healthcare NLP while reducing reliance on hosted proprietary inference.

1 Introduction

Healthcare NLP systems for mental-health language must support structured interpretation without turning social-media posts into diagnoses or risk scores. The CLPsych 2026 Shared Task asks systems to model longitudinal self-state dynamics through the MIND framework, which represents self-states using Affect, Behavior, Cognition, and Desire annotation categories rather than diagnostic constructs (Ali et al., 2026; Atzil-Slonim, 2025, 2026). The challenge is not only identifying evidence in one post, but determining how that evidence changes, persists, or reverses across a person's timeline.

Team Aurevia tests whether a privacy-conscious local pipeline can remain competitive without hosted proprietary inference over raw task data. Our contribution is a compact combination of TF-IDF retrieval, schema-constrained JSON prediction, local MLX inference with a 4-bit Qwen2.5-72B-Instruct checkpoint, ordinal calibration, and validators/post-processors that keep outputs inside official formats. We show that these controls were most useful for coarse ordinal presence and low-contradiction summaries, while fine-grained subelements, improvement signatures, and temporal labels still require stronger within-person grounding.

2 Task and Data

The shared task contains five evaluated components over longitudinal social media timelines (Ali et al., 2026). Task 1.1 identifies adaptive and maladaptive ABCD subelements in each post; Task 1.2 assigns adaptive and maladaptive presence ratings on a 1–5 ordinal scale; Task 2 detects sudden Switches and gradual Escalations; Task 3.1 generates summaries for organizer-provided post sequences; and Task 3.2 identifies recurrent dynamic signatures of MIND-coded deterioration and improvement for human evaluation. Together, these tasks test both local evidence extraction and higher-level reasoning over temporal patterns.

We do not reproduce user posts, prompts containing raw post text, or model outputs that could identify a user. The data are sensitive social-media timelines, and examples can remain identifying even when usernames are removed. All qualitative discussion below therefore uses labels, elements, aggregate behavior, and official scores only.

3 Related Work

This task extends a CLPsych line of work on longitudinal mental-health language. The 2022 shared task introduced temporally sensitive evaluation for Switches and Escalations in user timelines (Tsakalidis et al., 2022); the 2025 task broadened the setting to adaptive and maladaptive self-state evidence, well-being scores, and post- and timeline-level sum-

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 531–534
July 4, 2026 ©2026 Association for Computational Linguistics

marization (Tseriotou et al., 2025). CLPsych 2026 keeps this longitudinal focus but grounds the labels in MIND-coded ABCD dynamics (Ali et al., 2026; Atzil-Slonim, 2025). Team Aurevia follows this trajectory with a local, schema-constrained LLM pipeline rather than a hosted generative workflow.

4 System

Across tasks, the system retrieves similar training examples, generates or scores task-specific outputs, enforces official schemas, calibrates predictions where needed, and applies conservative post-processing before submission.

Task 1. For each post and valence, the system predicts a `Presence` rating in $\{1, \ldots, 5\}$ and optional ABCD subelements. The selected run ensembled a non-neural predictor with LLM candidates. The non-neural path uses TF-IDF unigrams/bigrams with 5,000 features, nearest-neighbor votes, and keyword lists for valid valence-element-subelement triples. The LLM path uses local MLX inference with `mlx-community/Qwen2.5-72B-Instruct-4bit` (Yang et al., 2024), retrieves three similar posts as few-shot examples, uses greedy decoding, and requests JSON-only ABCD predictions. Deterministic repair normalizes keys, replaces invalid subelements with frequent training subelements for the predicted valence/element, clamps presence scores, filters mundane posts, and inserts missing states. Presence calibration blends model values with training/development element-count means using weights 0.30 and 0.70.

Task 2. Task 2 predicts Switch and Escalation separately using handcrafted temporal signals, Task 1 ABCD profiles, and LLM confidence outputs with a rule-based calibrator. Signals include polarity changes, sudden- and gradual-change keywords, distances between consecutive ABCD profiles, increases in active maladaptive elements, disappearance of previously adaptive evidence, and newly appearing maladaptive evidence. Confidence values are engineering scores, not calibrated probabilities of clinical worsening or risk. The selected run normalized outputs to official labels, forced Switch to `0` for first posts, and selected top-scoring posts after rate matching to training Switch/Escalation rates.

Task 3. For Task 3.1, the system retrieves two demonstrations by TF-IDF similarity over concatenated sequence text, attaches Task 1 profiles when available, uses greedy decoding, removes preambles, caps summaries at 350 words, and softens categorical absence, certainty, and exclusivity language. This favors cautious summaries over summaries that maximize reference overlap. For Task 3.2, the system records adjacent-post transitions in training timelines, prioritizes element-transition combinations appearing in at least two timelines where possible, and formats one deterioration and one improvement signature with supporting post-pair sequence identifiers but no raw post text.

5 Experimental Setup

Team Aurevia reports one official selected run for each evaluated component. Table 1 gives the official Codabench submission IDs for Tasks 1–3.1 and labels the Task 3.2 email submissions. Run T1 is submission 661781 for Tasks 1.1/1.2, T2 is submission 653243 for Task 2, T3 is submission 693454 for Task 3.1, and T4-D/T4-I are the Task 3.2 deterioration and improvement email submissions. Calibration and threshold choices used released training/development resources and local held-out validation outputs. The official organizer results workbook was used only to report ranks and identify Aurevia rows. Official submissions were deterministic after fixed retrieval, decoding, calibration, and post-processing choices.

6 Results and Analysis

Table 1 shows balanced performance across structured and generative tasks. Aurevia ranked 3rd of 17 for calibrated presence prediction, 5th of 17 for subelement classification, 7th of 18 for change detection, 5th of 13 for sequence summarization, and 2nd of 9 for deterioration signatures. The strongest results align with the system design: schema-constrained prediction and calibration were most useful for coarse ordinal presence or conservative aggregate signatures.

Task 1 shows the clearest contrast. Presence prediction achieved 0.981 average RMSE, with quadratic weighted kappa 0.645, Spearman correlation 0.674, and MAE 0.688. In Task 1.1, element-presence macro F1 was 0.546 for adaptive and 0.680 for maladaptive states, while subelement macro F1 was lower at 0.328 and 0.434. This matters because clinical-style interpretation often requires calibrated evidence strength even when fine-grained category boundaries remain ambigu-

Task	Run	Primary metric (direction)	Score	Rank
1.1 Subelements	661781	Avg. subelement macro F1 ↑	0.381	5 / 17
1.2 Presence	661781	Avg. adaptive/maladaptive RMSE ↓	**0.981**	**3 / 17**
2 Change detection	653243	Post/timeline macro F1 ↑	0.484	7 / 18
3.1 Summaries	693454	Score rank average ↓	6.25	5 / 13
3.2 Deterioration	T4-D	Human overall score ↑	**0.676**	**2 / 9**
3.2 Improvement	T4-I	Human overall score ↑	0.465	6 / 9

Table 1: Team Aurevia's selected official submissions. Lower is better for RMSE and Task 3.1 score-rank average; higher is better otherwise.

ous.

Task 2 exposes the temporal bottleneck. The selected submission reached 0.484 combined macro F1: post macro F1 was 0.556, while timeline macro F1 was 0.413. The system was therefore better at identifying local evidence than at deciding exactly where a person's trajectory changed.

Task 3.1 shows a summary tradeoff. Aurevia ranked 5th overall, with the best consistency score (0.866, rank 1) and second-best contradiction score (0.625, rank 2), but lower lexical and embedding recall. Contradiction-aware cleanup helped factual caution but left reference details uncovered. Task 3.2 similarly shows that deterioration signatures were easier than improvement signatures: deterioration ranked 2nd with overall score 0.676, while improvement ranked 6th with overall score 0.465. Improvement signatures may require richer context than transition counts alone provide.

7 Discussion

The main strength of the submission is not a single model choice, but the control stack around local generation. Retrieval narrows the evidence context, JSON prompting exposes format errors, repair keeps outputs legal under the official schema, and calibration tempers ordinal presence scores when the predicted evidence structure is sparse. These controls are especially useful in healthcare NLP because misleading certainty can matter even when a system is used only for shared-task research.

The main remaining weakness is temporal grounding. The system can often detect local self-state evidence, but Switches, Escalations, and improvement signatures require a stronger account of what changed relative to a user's earlier baseline. Future systems should therefore combine calibrated post-level prediction with timeline-level models that represent persistence, reversal, uncertainty, and missing context explicitly.

8 Conclusion

Team Aurevia's CLPsych 2026 submission demonstrates that a local open-weight, schema-constrained healthcare NLP pipeline can be competitive for coarse self-state presence prediction and conservative summarization without sending raw task text to hosted proprietary APIs. Its weaker performance on subelement selection, improvement signatures, and timeline-level change detection points to the central remaining challenge: modeling self-state dynamics as within-person trajectories rather than isolated post-level cues.

Limitations

The system should not be used for diagnosis, treatment, crisis triage, surveillance, moderation, or intervention triggering. It predicts shared-task labels, not clinical truth. The labels depend on an annotation framework and limited training data; ambiguous posts, missing context, and annotator disagreement limit what the labels can mean. Social media posts are context-poor, performative, and culturally mediated, and may not map cleanly onto symptoms, impairment, risk, or need for care. Errors may also reflect cultural, demographic, linguistic, or platform-specific biases in both the data and the models.

Performance varied across domains. Aurevia performed well on presence detection and MIND-coded deterioration, but lower scores in secondary extraction and MIND-coded improvement detection (T4-I score 0.465; rank 6 of 9) suggest difficulty capturing positive clinical trajectories and fine-grained semantic distinctions. The pipeline also compounds errors across tasks: missed elements or miscalibrated presence scores can affect later predictions. We did not perform controlled ablations or clinical validation of the generated signatures, and we report only officially selected submissions.

Ethics Statement

The data concern mental health and social media behavior, a setting that requires particular care around privacy, consent, and downstream use. Even de-identified posts may contain personal experiences that users did not write for clinical modeling. We therefore avoid quoting raw posts, avoid releasing derived examples that could identify users, avoid including raw prompts or raw post text, and describe errors only in aggregate. We relied on the organizer-provided shared-task access and data-use conditions, made no re-identification attempts, limited access to the author team's local shared-task workspace, and prepared outputs under the organizer rules. All processing was designed for the shared-task research setting. We did not build user-facing interventions, clinical alerts, automated monitoring, moderation tools, or individual risk profiles.

Team Aurevia did not obtain separate institutional review board approval for this secondary shared-task analysis. Our work used the organizer-provided shared-task materials under the competition's access and data-use conditions, and we did not collect new human-subject data or attempt to contact, identify, or profile individual users. Where language-model inference was required, we used local execution rather than sending raw task text to a hosted proprietary API. This reduces one third-party disclosure pathway but does not remove all risk: local files, logs, caches, generated artifacts, and open-weight models can still leak information, hallucinate, reproduce biases, and generate over-confident summaries.

References

Iqra Ali, Talia Tseriotou, Guy Dvir, Callum Chan, Yuxiang Zhou, Juan Antonio Lossio-Ventura, Ayal Klein, Aya Shamir, Dan Sayda, Anthony Hills, Aya Zirikly, Diana Inkpen, Dana Atzil-Slonim, and Maria Liakata. 2026. Overview of the CLPsych 2026 shared task: Capturing and characterizing mental health changes through social media timeline dynamics. In *Proceedings of the 11th Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Dana Atzil-Slonim. 2025. Multimodal intrapersonal and interpersonal dynamics (MIND): A transtheoretical coding manual.

Dana Atzil-Slonim. 2026. Leveraging theoretical and technological innovations to study the mechanisms that underlie therapeutic change. In Louis G. Castonguay, Dana Atzil-Slonim, Michael Barkham, and Wolfgang Lutz, editors, *Practice-Based Evidence in the Psychological Therapies: Toward Policy Implications for Research, Training, and Clinical Guidelines*, pages 157–186. Oxford University Press.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Talia Tseriotou, Jenny Chim, Ayal Klein, Aya Shamir, Guy Dvir, Iqra Ali, Cian Kennedy, Guneet Singh Kohli, Anthony Hills, Ayah Zirikly, Dana Atzil-Slonim, and Maria Liakata. 2025. Overview of the CLPsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 193–217, Albuquerque, New Mexico. Association for Computational Linguistics.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, Junyang Lin, Kai Dang, and 22 others. 2024. Qwen2.5 technical report. *CoRR*, abs/2412.15115.

Team MKC at CLPsych 2026: Capturing and Characterizing Mental Health Changes through Social Media Timeline Dynamics

Kyomin Hwang* **Hyeonjin Kim*** **Hyunho Lee*** **Nojun Kwak†**
Seoul National University, Seoul, Republic of Korea
{kyomin98, peaceful1, hhlee822, nojunk}@snu.ac.kr

Abstract

Recent advances in Large Language Models (LLMs) have motivated their adoption across a wide range of domains, including Artificial Intelligence (AI) for mental health. Given the growing prevalence of mental health disorders worldwide and the limited accessibility of professional care, there is an increasing demand for scalable computational approaches that can assist in early detection and continuous monitoring of psychological well-being. In this area, ongoing efforts have focused on curating domain-specific datasets and leveraging them to develop LLMs capable of supporting holistic mental health analysis. In line with this direction, we propose an LLM-based pipeline for comprehensive mental health analysis over sequentially ordered user posts, as part of the CLPsych shared task. Our pipeline offers a unified framework that jointly enables post-level assessment and user-level temporal modeling.

1 Introduction

Recent advances in data collection and computational power have enabled the development of Large Language Models (LLMs) capable of performing a wide range of tasks as generalist AI systems (Brown et al., 2020). General-purpose LLMs such as GPT (Achiam et al., 2023) and Claude (Anthropic, 2025) demonstrate remarkable versatility across diverse domains, from natural language understanding to complex reasoning and code synthesis. Trained on vast corpora spanning web text, scientific literature, and source code, these models acquire broad world knowledge and generalize to novel tasks with minimal task-specific supervision (Kaplan et al., 2020; Kim et al., 2024; Radford et al., 2019). As the capabilities of LLMs continue to expand, there is growing interest in applying these models to specialized fields such as medical, law, and scientific discovery (Xie et al., 2023; Hwang and Kwak, 2026; Colombo et al., 2024).

As part of these advances, there have been efforts to apply LLMs to clinical psychology as well. However, early attempts have faced a critical bottleneck: the scarcity of training data, which stems largely from privacy concerns surrounding sensitive personal information. To address this limitation, Tsakalidis et al. (2022b) released a dataset while simultaneously introducing a novel task of identifying moments of change—temporal points at which shifts in a user's mood become observable. A growing body of subsequent work are leveraging this resource to formulate a range of tasks aimed at broader application of LLMs on mental health, with methodologies to tackle them (Ali et al., 2026; Tseriotou et al., 2025; Atzil-Slonim, 2026; Tsakalidis et al., 2022a).

Building on these advancements, we present an LLM-based pipeline for mental health analysis, developed as part of the CLPsych 2026 shared task (Ali et al., 2026), which leverages a subset of the dataset introduced by Tsakalidis et al. (2022b). Specifically, our pipeline addresses five interrelated tasks: 1) assessing a user's mental state at the post level; 2) estimating the presence rate of each mental state across a user's posting history; 3) identifying Moments of Change within a chronologically ordered sequence of a user's posts; 4) summarizing the change events observed in such sequences; and 5) detecting recurrent patterns and extracting the signature of improvement and deterioration over time. Our pipeline tackles these tasks in integration, spanning post-level assessment, user-level aggregation, and temporal modeling of mental state dynamics.

2 Method

In this section, we present a framework for detecting how the mental state and well-being of individ-

* Equal contribution.
† Corresponding author.

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 535–546
July 4, 2026 ©2026 Association for Computational Linguistics

uals evolve over temporally ordered sequences of social media posts. The proposed framework consists of five components: 1) post-level identification of ABCD elements and self-state, 2) self-state presence rating, 3) identification of moments of change (MOC), 4) summarization of sequences surrounding change events, and 5) identification of recurrent dynamic signatures of change across timelines. In the following subsections, we describe in detail the method employed to address each component.

2.1 Step 1

The first step is to classify ABCD subelements (Atzil-Slonim, 2025) and self-states at the post level. Self-states are categorized into two types, adaptive and maladaptive, each comprising six subdimensions. Each post is classified into one value from the subdimension-specific label set within each subdimension, with NONE always included as a valid option. This yields 12 independent classification targets per post, where both the number and the semantics of candidate labels vary across subdimensions, while the NONE option remains consistently available across all targets.

To address the multi-target classification problem, we employ Qwen3-4B-Embedding (Qwen Embed) (Zhang et al., 2025) as a feature extractor and fine-tune it via LoRA (Hu et al., 2022). The model is given a carefully designed prompt as in Figure 1. The resulting embeddings are passed to 12 independent classifiers, each trained with Cross-Entropy loss to handle its respective subdimension.

A central challenge is the severe class imbalance in the train dataset, which causes naive training to bias the model toward majority classes. We address this in two complementary ways. First, we apply inverse-frequency weighting to the Cross-Entropy loss, assigning each class a weight inversely proportional to its frequency. To prevent the extreme imbalance from inflating weights of rare classes and destabilizing training, we clip all weights to a maximum of 10. Second, since using only a subset of training data under such imbalance risks learning inadequate representations for minority classes, we adopt a 5-fold cross-validation strategy, training a separate model on each fold and ensembling the five models for final prediction.

2.2 Step 2

The second step builds on the outputs of Step 1 and focuses on predicting a numerical score for each self-state. Each of the two self-states, adaptive and maladaptive, is associated with a 5-point Likert scale score. The goal of Step 2 is to predict these two scores individually.

For this step, we introduce a dedicated predictor for each self-state, which regresses a single scalar value from the embeddings produced by the feature extractor in Step 1. Each predictor is trained using a weighted Huber loss (Huber, 1964), where per-sample weights are derived from the inverse frequency of each score bin (scores 1–5) in the training set, ensuring that underrepresented score levels receive proportionally greater emphasis during optimization. The model output is produced by passing the final linear layer's logit through a sigmoid activation and linearly rescaling it to the target range [1,5]. We adopt the same 5-fold cross-validation strategy as in Step 1, training a separate model per fold and ensembling them for the final prediction. The utilized prompt is in Figure 2.

2.3 Step 3

In the third step, we address the task of detecting two distinct types of transitions from a temporally ordered sequence of posts: 1) **Switch**, a substantial and sudden change in well-being between two consecutive posts, and 2) **Escalation**, a gradual intensification of mood over a sequence of consecutive posts. We formulated this step as binary classification problem for both types.

We fine-tune the Qwen Embed using LoRA, attaching two independent linear classifier for Switch and Escalation, each trained separately to specialize in its respective transition pattern. The model operates on a sliding window of size 2, taking as input the posts at time steps $t-1$ and t to predict whether a Switch or Escalation occurs at time t. This design reflects the local temporal dependency inherent in each task, particularly for Switch, which is defined over consecutive post pairs.

To account for class imbalance, we employ Binary Cross-Entropy with adaptive class weighting, where each label's loss weight is set inversely proportional to its frequency in the training set. Given that training on a single fold under such imbalance risks learning inadequate representations for minority classes, we adopt a 5-fold cross-validation strategy, training a separate model per fold and ensembling the five predictions for the final output. The prompt used in this step is shown in Figure 3.

2.4 Step 4

In the fourth step, given a sequence of posts with their associated information (*e.g.*, sub-elements and self state), the objective is to generate a summary of the entire sequence. To this end, we perform Supervised Fine-Tuning on Qwen3-4B-Instruct-2507 (Yang et al., 2025) and Qwen3.5-4B (Qwen Team, 2026) with LoRA. During training, we provide the ground-truth annotations of each post as input, whereas at inference time we instead rely on the predictions produced by the models trained in Steps 1, 2, and 3, thereby faithfully reflecting the actual pipeline setting. The prompts used in this step are provided in Figure 4 and Figure 5.

2.5 Step 5

As the final step, building on the MIND (ABCD) framework and the self-state structure, we analyze how self-state components interact and evolve across sequences surrounding change events, with the aim of identifying and summarizing dynamic patterns of psychological deterioration and improvement that recur across individuals. To this end, we perform this analysis in a zero-shot manner by prompting Qwen3.5-9B (Qwen Team, 2026). The prompt is provided in Figure 6 and Figure 7. Concatenating every given summary at once as the model input resulted in Out-of-Memory error. We detoured this error by first splitting the given sequences into groups, extracting improvement and deterioration signature from each, and finally summarizing the signatures.

3 Experiment

3.1 Experimental Setting

In this section, we describe the experimental settings used across each step. For Steps 1, 2, and 3, we employed Qwen Embed as the backbone model and fine-tuned it using LoRA, with the rank $r = 16$ and scaling factor $\alpha = 32$. The learning rate was set to 1×10^{-5}, and a K-fold cross-validation strategy ($K = 5$) was applied consistently across all three steps. The maximum input token length was set to 786, the batch size to 16, and all models were trained for 30 epochs. All experiments were conducted on a single NVIDIA RTX A6000 GPU, and the random seed was fixed to 42 for all experiments. Training a single fold took approximately 42 min for Step 1 and 15 min for Step 2, with the K-fold ensemble scaling roughly linearly. For the SFT in Step 4, we employed LoRA with a rank of $r = 8$ and scaling factor $\alpha = 16$, attaching adapters to all linear layers. Training was performed with a learning rate of 2e-4, a batch size of 8, for 10 epochs.

		Step 1	Step 2
Adaptive	K-fold	Macro F1 (↑)	RMSE (↓)
×	None	0.232	0.784
	Mean	0.210	0.677
	Voting	0.210	**0.612**
✓	None	**0.333**	0.777
	Mean	0.312	0.685
	Voting	0.332	0.700

Table 1: Results on the validation set for Step 1 and Step 2. *Adaptive* indicates whether class-wise adaptive weighting is applied to the classification loss. For K-fold, "None" denotes a single model trained without K-fold, "Mean" aggregates the logits of the ensembled models before selecting the final prediction, and "Voting" determines the final prediction by majority voting.

Task	Adaptive	K-fold	Score
Step 1 (F1 ↑)	✓	None	0.320
	✓	Mean	**0.361**
Step 2 (RMSE ↓)	✓	None	1.044
	×	Mean	1.010
	×	Voting	**1.003**

Table 2: Test-set results for Step 1 and Step 2. Other conventions follow Table 1.

3.2 Results

Performance on Step 1 and Step 2: Prior to evaluation on the test set, we randomly partition the full training data into training and validation splits at an 80/20 ratio. Table 1 reports the subelement-average macro F1 (Step 1) and RMSE (Step 2) on the held-out validation set. For both Step 1 and Step 2, we examine two design factors: i) whether adaptive weighting is applied to the classification loss (denoted by the *Adaptive* column), and ii) the K-fold aggregation strategy.

For **Step 1**, adaptive weighting consistently outperforms its non-weighted counterpart across all K-fold configurations, suggesting that adaptive weighting effectively mitigates the class imbalance inherent in the label distribution (Table 1). In contrast, once adaptive weighting is applied, the choice of K-fold aggregation strategy (mean or majority voting) yields only marginal differences relative to the gain obtained from adaptive weighting itself (Table 1). However, when these K-fold strategies are applied to the test set (Table 2), ensembling pro-

vides a clear improvement over the single-model baseline. We conjecture that this discrepancy stems from the difference in data utilization: the single-model setting (K-fold = None) is trained on only 80% of the training data, as the remaining 20% is held out for model selection, whereas the K-fold ensemble leverages the entire training set across its folds, generalizing better on the test set.

For **Step 2**, we observe that disabling adaptive weighting yields stronger validation performance (Table 1). This trend is preserved on the test set (Table 2), where the unweighted configuration again outperforms its weighted counterpart. A notable divergence from the validation results, however, is that K-fold aggregation produces consistent gains at test time across both aggregation strategies, where the *mean* strategy averages the continuous outputs of the per-fold models and the *voting* strategy rounds each fold's prediction to the nearest integer score and selects the mode as the final prediction. We attribute this improvement to the more complete utilization of the training data afforded by K-fold ensembling, which in turn translates into stronger generalization at test time.

Performance on Step 3: Table 3 presents the prediction performance on the Detection of Moments of Change (MOC). As shown in the table, the 4B model outperforms the 8B model, which is likely attributable to the limited size of the training data (approximately 500 samples). With such a small dataset, the larger model is more prone to overfitting and fails to fully leverage its capacity, resulting in degraded performance. Furthermore, ensembling the predictions of five models trained via K-fold cross-validation on top of Qwen3-4B yields additional performance gains. This suggests that maximally utilizing all available training data through K-fold ensemble is beneficial, particularly in few-shot learning settings. For the same reason, we kept the sliding window at size 2. Although a longer context could in principle capture Escalation more faithfully, models consuming wider temporal spans tend to overfit under our limited training regime, mirroring the overfitting pattern observed at the model-capacity level.

Performance on Step 4 and Step 5: Table 4 presents the performance on Step 4. As shown in the table, Qwen3.5 generally achieves higher performance than Qwen3 across most metrics. However, we observe that the Contradiction score of Qwen3.5 is worse than that of Qwen3. Nevertheless, both models underperform the Baseline, which relies on zero-shot prompting. We attribute this outcome to two potential factors: 1) noise propagated from the results of the preceding Steps 1–3 may have degraded the final performance, and 2) the training dataset may have been too small relative to the model's capacity, suggesting that a more carefully designed prompting could have been necessary. In such a low-resource regime, fine-tuning may also overwrite part of the LLM's pre-trained knowledge, whereas the zero-shot baseline preserves it in full. This is consistent with our Step 3 finding that the smaller Qwen3-4B outperforms the larger Qwen3-8B (Table 3). For Step 5, we adopted a zero-shot approach, which resulted in performance scores of 0.7266 on Improvement and 0.2301 on Deterioration.

Model	**F1 Score** (↑)
Qwen3-4B	0.53
Qwen3-8B	0.49
Qwen3-4B w/ K-fold	**0.55**

Table 3: Performance on the test set of Step 3.

Model	**Consistency** (↑)	**Contradiction** (↓)	**Rouge-L Recall** (↑)
Baseline	0.763	0.753	0.255
Qwen3.5-4B	**0.669**	0.857	**0.290**
Qwen3-4B	0.654	**0.834**	0.284

Table 4: Performance on the test set of Step 4.

4 Discussion

Future Works Our analysis of the dataset provided for the shared task revealed a significant class imbalance across the sub-dimensions used in the Step 1 post-level classification. More importantly, several sub-dimensions contained only a single training instance, and some contained none at all. This severe sparsity likely limited the model's ability to learn reliable decision boundaries for these categories, and may partly explain the lower performance observed on low-resource labels. To mitigate this issue, we adopted a K-fold ensemble strategy in the present work. However a more direct solution, which we leave for future research, is to use LLMs to generate synthetic user posts for the under-represented sub-dimensions. This approach could help reduce both the imbalance and the missing-

label problems, leading to a more balanced training signal across all labels.

5 Conclusion

In this paper, we presented an LLM-based pipeline for the CLPsych 2026 shared task on capturing mental health changes through social media timelines. To address the class imbalance that commonly appears in mental health data, we designed a loss function that reflects the label distribution and combined it with a K-fold ensemble strategy to improve robustness. We also enabled the model to describe users' mental states in natural language, either through fine-tuning or few-shot examples, making the outputs easier to interpret. Building on these components, our pipeline brings post-level and user-level temporal modeling together into a single unified framework.

Limitations

In this paper, we proposed a holistic pipeline for Capturing and Characterizing Mental Health Changes through Social Media Timeline Dynamics. Nevertheless, several limitations remain to be addressed in future work. First, the scarcity of training data poses a significant challenge. The dataset employed for training exhibits a substantial class imbalance, with only approximately 500 samples available in total. Consequently, models with larger capacities tend to suffer from severe overfitting. To mitigate this issue, one promising direction is to leverage LLM-based data augmentation to generate additional samples, thereby constructing a more balanced dataset across all classes. Second, the design of sophisticated prompts tailored to the mental health domain warrants further investigation. The performance of LLMs is known to be highly sensitive to subtle variations in prompt formulation. Although this aspect was beyond the scope of the present study, we believe that incorporating domain-specific knowledge related to mental health into prompt engineering could further enhance the effectiveness of the proposed pipeline.

Ethics

The dataset provided for the CLPsych 2026 shared task contains sensitive content related to users' mental health. Throughout this work, we strictly followed the data handling rules announced by the CLPsych organizers and we avoided any external API service that would have required transmitting the data outside our local environment. Our five-step pipeline is intended as a research artifact for studying mental health dynamics, and any use of it for screening or diagnosis would require oversight by trained mental health professionals. Automated inference of self-states and moments of change carries non-trivial clinical implications when errors occur: false positives may lead to unnecessary intervention, while false negatives could mean a missed opportunity for support.

Our proposed future direction of LLM-based synthetic data generation for underrepresented subdimensions (Section 4) also carries ethical risks that warrant careful consideration. LLMs trained on broad web data may misrepresent the lived experience of clinical populations and produce stereotypical or inaccurate depictions of distress, and any such distortions may be silently propagated once the generated samples are incorporated into training. Generating content in sensitive categories such as self-harm further raises content-safety concerns. Before using such generated data for training, future work should have clinical experts review the samples and check for fairness across different demographic and language groups.

Acknowledgments

This work was supported by the Korean Government through the grants from IITP (RS-2021-II211343, RS-2025-25442338, 26-InnoCORE-01)

References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, and 1 others. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

Iqra Ali, Talia Tseriotou, Guy Dvir, Callum Chan, Yuxiang Zhou, Juan Antonio Lossio-Ventura, Ayal Klein, Aya Shamir, Dan Sayda, Anthony Hills, Aya Zirikly, Diana Inkpen, Dana Atzil-Slonim, and Maria Liakata. 2026. Overview of the clpsych 2026 shared task: Capturing and characterizing mental health changes through social media timeline dynamics. In *Proceedings of the 11th Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Anthropic. 2025. Claude 3.7 Sonnet system card. Technical report, Anthropic.

Dana Atzil-Slonim. 2025. Multimodal intrapersonal and interpersonal dynamics (mind): A transtheoretical coding manual.

Dana Atzil-Slonim. 2026. Leveraging theoretical and technological innovations to study the mechanisms that underlie therapeutic change in psychotherapy. In Louis G. Castonguay, Dana Atzil-Slonim, Michael Barkham, and Wolfgang Lutz, editors, *Practice-Based Evidence in the Psychological Therapies: Toward Policy Implications for Research, Training, and Clinical Guidelines*. Oxford University Press, New York.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, and 1 others. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.

Pierre Colombo, Telmo Pessoa Pires, Malik Boudiaf, Dominic Culver, Rui Melo, Caio Corro, Andre FT Martins, Fabrizio Esposito, Vera Lúcia Raposo, Sofia Morgado, and 1 others. 2024. Saullm-7b: A pioneering large language model for law. *arXiv preprint arXiv:2403.03883*.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1 (long and short papers)*, pages 4171–4186.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Liang Wang, Weizhu Chen, and 1 others. 2022. Lora: Low-rank adaptation of large language models. *Iclr*, 1(2):3.

Peter J. Huber. 1964. Robust estimation of a location parameter. *Annals of Mathematical Statistics*, 35:492–518.

Kyomin Hwang and Nojun Kwak. 2026. Retrieval-augmented generation based nurse observation extraction. *arXiv preprint arXiv:2603.26046*.

Shaoxiong Ji, Tianlin Zhang, Luna Ansari, Jie Fu, Prayag Tiwari, and Erik Cambria. 2022. MentalBERT: Publicly available pretrained language models for mental healthcare. In *Proceedings of the Thirteenth Language Resources and Evaluation Conference*, pages 7184–7190, Marseille, France. European Language Resources Association.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. 2020. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*.

Taehoon Kim, Pyunghwan Ahn, Sangyun Kim, Sihaeng Lee, Mark Marsden, Alessandra Sala, Seung Hwan Kim, Bohyung Han, Kyoung Mu Lee, Honglak Lee, Kyounghoon Bae, Xiangyu Wu, Yi Gao, Hailiang Zhang, Yang Yang, Weili Guo, Jianfeng Lu, Youngtaek Oh, Jae Won Cho, and 23 others. 2024. Nice: Cvpr 2023 challenge on zero-shot image captioning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, pages 7356–7365.

Qwen Team. 2026. Qwen3.5: Towards native multimodal agents.

Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. 2019. Language models are unsupervised multitask learners.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, and 1 others. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022a. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Adam Tsakalidis, Federico Nanni, Anthony Hills, Jenny Chim, Jiayu Song, and Maria Liakata. 2022b. Identifying moments of change from longitudinal user text. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 4647–4660, Dublin, Ireland. Association for Computational Linguistics.

Talia Tseriotou, Jenny Chim, Ayal Klein, Aya Shamir, Guy Dvir, Iqra Ali, Cian Kennedy, Guneet Singh Kohli, Anthony Hills, Ayah Zirikly, Dana Atzil-Slonim, and Maria Liakata. 2025. Overview of the CLPsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 193–217, Albuquerque, New Mexico. Association for Computational Linguistics.

Tong Xie, Yuwei Wan, Wei Huang, Zhenyu Yin, Yixuan Liu, Shaozhou Wang, Qingyuan Linghu, Chunyu Kit, Clara Grazian, Wenjie Zhang, and 1 others. 2023. Darwin series: Domain specific large language models for natural science. *arXiv preprint arXiv:2308.13565*.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Kailai Yang, Tianlin Zhang, Ziyan Kuang, Qianqian Xie, Jimin Huang, and Sophia Ananiadou. 2024. Mentallama: interpretable mental health analysis on social media with large language models. In *Proceedings of the ACM Web Conference 2024*, pages 4489–4500.

Yanzhao Zhang, Mingxin Li, Dingkun Long, Xin Zhang, Huan Lin, Baosong Yang, Pengjun Xie, An Yang, Dayiheng Liu, Junyang Lin, and 1 others. 2025. Qwen3 embedding: Advancing text embedding and reranking through foundation models. *arXiv preprint arXiv:2506.05176*.

A Appendix

A.1 Related Works

A.1.1 NLP Approaches in Psychological Assessment

The proliferation of large-scale datasets and the rapid advancement of computational resources have driven the emergence of foundation models capable of performing a wide range of tasks in a generalized manner, spanning both computer vision and natural language processing. These breakthroughs have subsequently inspired researchers to explore the applicability of such models in specialized domains, including psychology and mental healthcare (Tsakalidis et al., 2022a; Atzil-Slonim, 2026). MentalBERT (Ji et al., 2022) represents an early effort in this direction, extending the general-purpose BERT architecture (Devlin et al., 2019) through continued domain-adaptive pretraining on mental health-related corpora, enabling the extraction of psychologically grounded contextual embeddings. Building upon this line of work, MentalLLaMA (Yang et al., 2024) shifts from a purely representational paradigm to a generative one by leveraging LLaMA (Touvron et al., 2023), an instruction-tuned large language model, and further applying supervised fine-tuning on a curated collection of mental health-specific instruction datasets. This allows MentalLLaMA to perform a diverse array of mental health tasks in a conversational and interpretable manner, going beyond the embedding-focused capabilities of its predecessor. Motivated by these advances in NLP for mental health, this paper aims to leverage large language models (LLM) trained on large-scale data to capture and characterize longitudinal changes in mental health states within social media timelines.

A.1.2 Collecting Psychological Data for NLP

Unlike general-purpose tasks, domains such as psychology present unique challenges in data collection, including privacy concerns and ethical constraints, which inevitably limit the scale and accessibility of psychological data. To address these limitations and advance NLP research in the psychological domain, Tsakalidis et al. curated a large-scale mental health counseling dataset sourced from social media. Building upon this dataset, subsequent works have explored a diverse range of mental health-related tasks, including mood change detection, suicide risk classification, and the identification and summarization of suicide risk evidence, thereby contributing to the broader development of AI for psychology. Motivated by these advances, this paper presents a framework proposed as part of the CLPsych shared task, aimed at capturing and characterizing mental health changes through social media timeline dynamics.

A.2 Prompt Specifications

Figures 1, 2, 3, 4, and 5 illustrate the prompts employed in each respective task. For the few-shot examples in the Step 4 prompt, instances drawn from the provided dataset were utilized. Specifically, each example was constructed by incorporating the MoC label (*i.e.,* Switch and Escalation indicators), the Maladaptive presence score, the Adaptive presence score, and the composition of each corresponding state as input.

Prompt used in Step 1

Instruct: Yor task is to identify evidence of adaptive and maladaptive self-states from a post (input text).
Each post can include either:
(1) a single self-state (adaptive or maladaptive),
(2) two complementary self-states (adaptive and maladaptive), or
(3) Evidence of neither an adaptive nor a maladaptive state.

Self-states constitute identifiable units characterized by specific combinations of Affect, Behavior, Cognition, and Desire/Need (ABCD dimensions).
An Adaptive self-state pertains to aspects of ABCD that are conducive to the fulfillment of basic desires/needs.
A Maladaptive self-state pertains to aspects of ABCD that hinder the fulfillment of basic desires/needs.

ABCD Dimensions:

1. Affect (A) – Adaptive: Calm/laid back, Sad/grieving, Content/hopeful, Vigorous, Justifiable anger, Proud, Feel loved/belong. Maladaptive: Anxious/fearful/tense, Depressed/hopeless, Mania, Apathic/blunted, Angry/contempt, Ashamed/guilty, Feel lonely.
2. Behavior toward other (B-O) — Adaptive: Relating behavior, Autonomous/adaptive control. Maladaptive: Fight or flight behavior, Over-controlled or controlling behavior.
3. Behavior toward self (B-S) — Adaptive: Self-care and improvement. Maladaptive: Self-harm, neglect and avoidance.
4. Cognition of Other (C-O) — Adaptive: Other as related, Other as facilitating autonomy. Maladaptive: Other as detached/over-attached, Other as blocking autonomy needs.
5. Cognition of Self (C-S) — Adaptive: Self-acceptance and compassion. Maladaptive: Self-criticism.
6. Desire/Need (D) — Adaptive: Relatedness, Autonomy and adaptive control, Competence/self-esteem/self-care. Maladaptive: Expectation that relatedness needs will not be met, Expectation that autonomy needs will not be met, Expectation that competence needs will not be met.

Query:

Figure 1: Prompt used for Post-Level Identification of Dominant ABCD Sub-elements and Self-State Composition

Prompt used in Step 2

Instruct: Your task is to estimate the degree to which each identified self-state is present in the post (input text) on a scale from 1 to 5.
Self-states constitute identifiable units characterized by specific combinations of Affect, Behavior, Cognition, and Desire/Need (ABCD dimensions).
An Adaptive self-state pertains to aspects of ABCD that are conducive to the fulfillment of basic desires/needs.
A Maladaptive self-state pertains to aspects of ABCD that hinder the fulfillment of basic desires/needs.

ABCD Dimensions:

1. Affect (A) – Adaptive: Calm/laid back, Sad/grieving, Content/hopeful, Vigorous, Justifiable anger, Proud, Feel loved/belong. Maladaptive: Anxious/fearful/tense, Depressed/hopeless, Mania, Apathic/blunted, Angry/contempt, Ashamed/guilty, Feel lonely.
2. Behavior toward other (B-O) — Adaptive: Relating behavior, Autonomous/adaptive control. Maladaptive: Fight or flight behavior, Over-controlled or controlling behavior.
3. Behavior toward self (B-S) — Adaptive: Self-care and improvement. Maladaptive: Self-harm, neglect and avoidance.
4. Cognition of Other (C-O) — Adaptive: Other as related, Other as facilitating autonomy. Maladaptive: Other as detached/over-attached, Other as blocking autonomy needs.
5. Cognition of Self (C-S) — Adaptive: Self-acceptance and compassion. Maladaptive: Self-criticism.
6. Desire/Need (D) — Adaptive: Relatedness, Autonomy and adaptive control, Competence/self-esteem/self-care. Maladaptive: Expectation that relatedness needs will not be met, Expectation that autonomy needs will not be met, Expectation that competence needs will not be met.

Score Scale:
1=Not present,
2=Somewhat present (subtle, limited role),
3=Moderately present (clearly expressed, moderate contribution),
4=Much present (strongly influences the experience),
5=Highly present (strongly defines the overall experience).

Query:

Figure 2: Prompt used for Self State Presence Rating

Prompt used in Step 3

Instruct: Given two consecutive posts from the same user timeline, determine whether a Switch (sudden and substantial change in wellbeing) or Escalation (gradual intensification of mood toward an extreme state) occurs at the second post.

Figure 3: Prompt used for Identify Moments of Change (MOC)

Prompt used in Step 4 – (1)

Task:
Your task is to generate a structured summary describing patterns of self-state dynamics and their progression over time within a sequence of posts surrounding a change (Switch / Escalation).
Each sequence includes:
(1) posts leading up to the change
(2) posts marking the change itself
For each sequence, the structued summary must describe:
(1) how psychological change processes evolve across the sequence
(2) how they culminate in (When it's a Switch), or unfold through (When it's an Escalation), the identified change event
(3) direction of the change (improvement / deterioration) must be indicated
(4) The identity of the change event (Switch / Escalation) must be indicated
(5) The Change Pattern using the ABCE elements and presence scores for the adaptive and maladaptive self-states.
Definitions:
Self-state:
Self-states constitute identifiable units characterized by specific combinations of Affect, Behavior, Cognition, and Desire/Need(ABCD dimensions) that tend to be coactivated in a meaningful manner for limited periods of time.
- An **Adaptive self-state** pertains to aspects of Affect, Behavior (towards the self and others), Cognition (towards the self and others) that are conducive to the fulfillment of basic desires/needs.
- A **Maladaptive self-state** pertains to aspects of Affect, Behavior (towards the self and others), Cognition (towards the self and others) that hinder the fulfillment of basic desires/needs.
MOC (Moment of Change):
For each post, Moment of Change (MOC) is indicated. Moment of Change is categorized into three types: Switch, Escalation, and No Change.
- Switch: A switch reflects a substantial and sudden change in well-being between two consecutive posts.
- Escalation: An escalation refers to a gradual intensification of mood over a sequence of consecutive posts. It occurs when an individual's mood progressively shifts from neutral or mildly valenced, toward a more extreme state (very negative or very positive) across a span of posts.
- No Change: A no change indicates that there is no significant shift in well-being between two consecutive posts.

Figure 4: Prompt used for Summarization

Prompt used in Step 4 – (2)

ABCD Dimensions:
1. **Affect (A)**: Type of emotion expressed by a writer
- Adaptive: (1) Calm/ laid back (3) Sad, emotional pain, grieving (5) Content, happy, joy, hopeful (7) Vigor / energetic (9) Justifiable anger / assertive anger, justifiable outrage (11) Proud (13) Feel loved, belong
- Maladaptive: (2) Anxious/ fearful/ tense (4) Depressed, despair, hopeless (6) Mania (8) Apathic, don't care, blunted (10) Angry (aggression), disgust, contempt (12) Ashamed, guilty (14) Feel lonely
2. **Behavior of the self with the other (B-O)**: The writer's main behavior(s) toward the other
- Adaptive: (1) Relating behavior (3) Autonomous or adaptive control behavior
- Maladaptive: (2) Fight or flight behavior (4) Over controlled or controlling behavior
3. **Behavior toward the self (B-S)**: The writer's main behavior(s) toward the self
- Adaptive: (1) Self care and improvement
- Maladaptive: (2) Self harm, neglect and avoidance
4. **Cognition of Other (C-O)**: The writer's main perceptions of the other
- Adaptive: (1) Perception of the other as related (3) Perception of the other as facilitating autonomy needs
- Maladaptive: (2) Perception of the other as detached or over attached (4) Perception of the other as blocking autonomy needs
5. **Cognition of the self (C-S)**: The writer's main self-perceptions
- Adaptive: (1) Self-acceptance and compassion
- Maladaptive: (2) Self criticism
6. **Desire (D)**: The writer's main desire, expectation, need, intention, or fear
- Adaptive: (1) Relatedness (3) Autonomy and adaptive control (5) Competence, self esteem, self-care
- Maladaptive: (2) Expectation that relatedness needs will not be met (4) Expectation that autonomy needs will not be met (6) Expectation that competence needs will not be met
Example:
SEQUENCE OF POSTS:
{Few-shot Example}
OUTPUT:
{Few-shot Example}
SEQUENCE OF POSTS:
{}
OUTPUT:

Figure 5: Prompt used for Summarization

Prompt used in Step 5 (Improvement)

The MIND (ABCD) model:
Affect (A): Type of emotion expressed by a writer.
Behavior of the self with the other (B-O): The writer's main behavior(s) toward the other.
Behavior toward the self (B-S): The writer's main behavior(s) toward the self.
Cognition of the other (C-O): The writer's main perceptions of the other.
Cognition of the self (C-S): The writer's main self perceptions.
Desire (D): The writer's main desire, expectation, need, intention, or fear.

Using the MIND (ABCD) framework and self-state structure, analyse how self-states and their elements interact and evolve in sequences surrounding identified change events.
Focus on high resolution patterns that recur across multiple individuals.

Extract Signature of Improvement.

The signature should describe a recurrent dynamic pattern observed across individuals that leads to and culminates as the change occurs.
Base all points on observable dynamic patterns in the timelines.
Signature should be under 90 words.

{Few-shot Example with Json Structure}

{Sequence of Posts with timeline and sequence id}

Figure 6: Prompt used for Step 5 (Improvement)

Prompt used in Step 5 (Deterioration)

The MIND (ABCD) model:
Affect (A): Type of emotion expressed by a writer.
Behavior of the self with the other (B-O): The writer's main behavior(s) toward the other.
Behavior toward the self (B-S): The writer's main behavior(s) toward the self.
Cognition of the other (C-O): The writer's main perceptions of the other.
Cognition of the self (C-S): The writer's main self perceptions.
Desire (D): The writer's main desire, expectation, need, intention, or fear.

Using the MIND (ABCD) framework and self-state structure, analyse how self-states and their elements interact and evolve in sequences surrounding identified change events.
Focus on high resolution patterns that recur across multiple individuals.

Extract Signature of Deterioration.

The signature should describe a recurrent dynamic pattern observed across individuals that leads to and culminates as the change occurs.
Base all points on observable dynamic patterns in the timelines.
Signature should be under 90 words.

{Few-shot Example with Json Structure}

{Sequence of Posts with timeline and sequence id}

Figure 7: Prompt used for Step 5 (Deterioration)

Theory-Explicit Prompting for MIND Self-States: Hierarchical LLMs and Dynamic Signature Extraction in Mental Health Timelines

Pawan Kumar, Ankit Meshram, Shubham Jha, Loitongbam Gyanendro Singh
Department of Computer Science and Engineering,
Indian Institute of Technology Ropar, Punjab, India
{2024aim1007, 2024aim1002, 2024csm1019, gyanendro}@iitrpr.ac.in

Abstract

This paper presents a system for the CLPsych 2026 Shared Task on longitudinal mental health modeling from social media timelines, grounded in the MIND framework (Atzil-Slonim, 2025). MIND conceptualizes mental health as evolving self-states defined by **A**ffect, **B**ehavior, **C**ognition, and **D**esire (ABCD), providing a structured lens on mental health trajectories. The system centers on a *theory-explicit prompting framework* for structured sequence summarization (Task 3.1) and recurrent dynamic signature extraction (Task 3.2), encoding the full ABCD taxonomy directly into the LLM prompt to ensure clinically grounded, interpretable outputs. A three-stage pipeline infers a direction-of-change label per sequence, produces structured ABCD summaries with few-shot exemplar augmentation, and aggregates these summaries to derive cross-individual recurrent patterns. The system ranks *first* on deterioration-related recurrent signatures and *second* overall, achieving the top Fit and Specificity scores in Task 3.2, demonstrating the benefits of explicit clinical grounding for conceptual accuracy.

1 Introduction

Social media platforms, particularly Reddit, offer rich longitudinal records of self-disclosure that unfold over weeks, months, and years, enabling forms of continuous monitoring and early risk detection that single-point clinical assessments cannot easily provide (Coppersmith et al., 2014; Tsakalidis and Liakata, 2022). As a result, these platforms have become a key resource for computational mental health, supporting work on early warning signals, symptom trajectories, and crisis detection.

Prior work has examined diverse aspects of mental health–relevant language in user-generated content, including how linguistic and contextual properties vary across societal and non-societal topics (Singh and Singh, 2024), the extraction and summarization of suicidal ideation using large language models (Singh et al., 2024a), and the detection of critical moments of change through longitudinal and multi-task learning approaches (Singh et al., 2024b; Azim et al., 2022; Tsakalidis et al., 2022). While these methods demonstrate strong predictive performance, they typically target isolated subtasks and often remain weakly connected to established psychological theory, limiting interpretability, complicating clinical integration, and constraining our ability to model mental-state evolution in ways that are meaningful to clinicians.

The CLPsych 2026-25 Shared Task (Ali et al., 2026)(Tseriotou et al., 2025) addresses this gap by placing longitudinal mental health modeling within the MIND framework (Atzil-Slonim, 2025), which conceptualizes mental health as a dynamic configuration of *self-states* shaped by **A**ffect (A), **B**ehavior toward the self (B-S) and toward others (B-O), **C**ognition about the self (C-S) and about others (C-O), and **D**esire (D)–collectively referred to as ABCD. At any point in time, one self-state configuration may be dominant while others remain latent, and shifts between more adaptive and more maladaptive self-states are intended to reflect clinically meaningful patterns of deterioration or recovery. The task spans `40 Reddit-based user timelines` from mental health subreddits, split into 30 training and 10 test timelines (Ali et al., 2026), each consisting of chronologically ordered posts annotated according to the MIND scheme.

This paper concentrates on the sequence-level tasks of the CLPsych 2026 Shared Task (`Task 3`). Details on the task and the dataset are provided in Appendix A. `Task 3.1` requires generating structured natural-language summaries of the ABCD dynamics surrounding each detected change event (Switch or Escalation), while `Task 3.2` builds on these summaries to identify *recurrent* ABCD-grounded dynamic signatures that distinguish de-

Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2026), pages 547–553
July 4, 2026 ©2026 Association for Computational Linguistics



Figure 1: Three-stage pipeline for Task 3. **Purple** nodes denote LLM generation steps; **yellow** nodes denote prompt construction and aggregation; **grey** nodes denote external context inputs. Stage 1 infers a direction-of-change label from each social media post sequence. Stage 2 assembles a theory-explicit MIND/ABCD prompt-receiving both the post sequence and the direction label as input-with a matched few-shot exemplar and per-post annotations, and generates a structured summary (Task 3.1). Stage 3 aggregates training summaries by direction and extracts recurrent dynamic signatures across users (Task 3.2).

terioration from improvement across multiple individuals' trajectories. We address these tasks through a *theory-explicit prompting framework* that encodes the complete MIND/ABCD taxonomy directly into the system prompt to guide structured sequence summarization and signature extraction. Each summary is organized into three clinically motivated sections: *Central Theme*, *Within-State Dynamics*, and *Between-State Dynamics*, and uses formal ABCD abbreviations and relational vocabulary to support theory-aligned, clinically interpretable modeling of longitudinal mental health.

Building on this design, a three-stage pipeline drives the system: (1) a keyword-based heuristic infers a direction-of-change label (*deterioration*, *improvement*, or *mixed*) for each sequence; (2) this label conditions a two-part structured prompt, with a matched few-shot exemplar retrieved from training, that produces the Task 3.1 ABCD summary; and (3) these summaries are aggregated across users to perform cross-individual signature extraction in Task 3.2. Our pipeline achieves *first place* in identifying deterioration signatures and *second place* overall in Task 3.2, attaining the highest Fit Score (1.000 overall; 0.875 deterioration) and Specificity Score (0.938) of any participating team in the deterioration category. These results illustrate how theory-explicit prompting can bridge the gap between high-performing LLMs and psychologically interpretable characterizations of mental health trajectories.

2 Methodology: Summarization and Signature Extraction

Our sequence-level component uses a unified `theory-explicit prompt-based LLM pipeline` to address structured sequence summarization (Task 3.1) and recurrent pattern extraction (Task 3.2). All LLM generation steps use **Mistral-7B-Instruct-v0.2**, served via a locally hosted Ollama endpoint; no proprietary APIs were used at any stage, in compliance with the CLPsych 2026 Data Access Form. We encode the ABCD taxonomy, self-state definitions, and the required output format directly in the system prompt so that all generations are explicitly grounded in the MIND framework (Atzil-Slonim, 2025, 2026), following the role-prompting paradigm (Kong et al., 2024).

The pipeline has three stages: (1) infer a direction-of-change label for each sequence; (2) generate a structured summary for Task 3.1 conditioned on this label; and (3) aggregate Task 3.1 summaries over the training set to extract cross-individual signatures for Task 3.2. The full pipeline is illustrated in Figure 1.

2.1 Stage 1: Direction Inference

Each sequence is labeled as *deterioration*, *improvement*, or *mixed* by scanning its gold summary (training) for deterioration keywords (e.g., *worsen*, *suicidal*) and improvement keywords (e.g., *recover*, *hopeful*). The keyword lists were derived through close reading of the training gold summaries combined with established clinical terminology from the MIND framework manual (Atzil-Slonim, 2025); no automated selection procedure was used. Full keyword lists are provided in Ap-

pendix A.3. The higher count determines the label; ties yield *mixed*. For test sequences, the same heuristic is applied to the post texts. This direction labels both frames, the kind of change described in Task 3.1, and groups Task 3.1 summaries when building signatures in Task 3.2.

2.2 Stage 2: Task 3.1 – Structured Sequence Summarization

Given a direction label, we construct a two-part prompt following the in-context learning paradigm (Brown et al., 2020; Liu et al., 2023): a fixed **system part** and a sequence-specific **user part**. The **system part** asks the model to act as a clinician trained in MIND, following the role-prompting paradigm (Kong et al., 2024), and to produce a three-part summary:

- **Central Theme**: the dominant ABCD dimension driving the change and how it evolves across the sequence.
- **Within-State Dynamics**: interactions *within* self-states (e.g., co-activation, reinforcement, suppression) between ABCD subelements.
- **Between-State Dynamics**: how adaptive and maladaptive self-states change in relative dominance, culminating in a Switch or unfolding through an Escalation.

The model must use formal third-person clinical prose, explicitly reference ABCD elements with *(A)*, *(B-S)*, *(B-O)*, *(C-S)*, *(C-O)*, *(D)*, state the direction of change, and not reproduce numeric scores. Outputs are capped at 350 words to match the shared task truncation limit.

The **user part** provides sequence identifiers and change types (Switch / Escalation), the inferred direction label, and for each post: its index, inferred self-state valence (adaptive / maladaptive / neutral), ABCD presence flags with scores, and post text truncated to 500 characters. The 500-character limit was chosen empirically: pilot runs showed that content beyond this threshold introduced no additional ABCD signal not already captured by the structured flags, while substantially increasing token count and generation latency. For training sequences, ABCD flags are drawn from the gold annotations; for test sequences, they are produced by our Task 1 system, meaning Task 3.1 test performance reflects end-to-end pipeline quality including Task 1 prediction noise.

Few-Shot Augmentation. We add a `few-shot exemplar` to the user part, following the in-context learning paradigm (Brown et al., 2020; Liu et al., 2023). For a sequence with change type c and direction d, we retrieve a training summary whose (change type, direction) best matches (c, d) (exact match; otherwise, direction-only; otherwise, most recent). It is inserted under `EXAMPLE SUMMARY (for style reference only)`, followed by `Now generate a summary for the following new sequence`, preventing contamination of the target input.

The exemplar acts as a stylistic and structural template: it encourages the correct use of ABCD abbreviations, relational language (e.g., *mutually reinforces*, *progressively suppresses*), and the three-part structure. Decoding uses temperature $\tau = 0.3$, chosen after pilot runs comparing $\tau \in \{0.0, 0.1, 0.3, 0.5\}$: $\tau = 0.0$ produced overly templated outputs that reproduced exemplar phrasing too closely, while $\tau \geq 0.5$ introduced unnecessary variation in clinical terminology. The 700-token limit comfortably accommodates the 350-word requirement with formatting overhead. Outputs are split into three sections via regex over numbered headers; if parsing fails, the full output is kept as a single summary.

2.3 Stage 3: Task 3.2 – Recurrent Dynamic Signature Extraction

Stage 3 takes as input the structured summaries produced by Stage 2 over the full training set. We use Stage 2-generated summaries rather than the gold reference summaries, so that the signatures reflect the actual output distribution of our pipeline rather than the gold annotation; this ensures Task 3.2 signatures are grounded in the same self-state characterisations the pipeline produces at test time.

Summaries are grouped by direction label (*deterioration*, *improvement*, *mixed*). A single `aggregated prompt` then presents all summaries, organized by group and truncated to 800 characters each.

The model is instructed to report only signatures that occur in *at least two distinct user timelines*. For each signature, it must specify: (i) the ABCD interaction pattern (which subelements co-activate or suppress adaptive functioning); (ii) how adaptive vs. maladaptive dominance evolves before the change event; (iii) how the dynamics crystallize at the Switch or Escalation; and (iv) two to three training timeline IDs as evidence.

Team	CS↑	CT↓	R-L↑	BS↑	Rank
MERONYM_LABS	0.801	0.659	0.266	0.345	1
DreamerNLplus	0.735	0.767	0.285	0.345	2
CUNY	0.789	0.714	0.292	0.295	3
Ours	0.688	0.812	0.242	0.306	**11**
Baseline	0.765	0.749	0.262	0.231	–

Table 1: Results of Task 3.1 (selected top 3 teams vs. ours). CS = Consistency; CT = Contradiction; R-L = ROUGE-L Recall; BS = BERTScore Recall. Bold = best per column.

Team	Fit	Recur	Spec	Overall
Task 3.2 Deterioration extraction results				
Ours	**0.875**	0.563	**0.938**	**0.789**
Aurevia	0.688	0.813	0.563	0.676
DreamerNLplus	0.438	0.688	0.875	0.604
MeronymLabs	0.438	0.563	0.813	0.551
psytechlab	0.625	0.625	0.250	0.491
Baseline	0.563	0.375	0.438	0.483
Overall Task 3.2 competition results				
Ours	**1.000**	0.688	0.375	0.743
DreamerNLplus	0.625	0.813	1.000	**0.761**
MKC	0.750	0.563	0.938	0.727
McMasterNLP	0.688	0.375	0.750	0.594
psytechlab	0.688	1.000	0.250	0.544
Aurevia	0.375	0.625	0.500	0.465
Baseline	0.375	0.438	0.375	0.389

Table 2: Results for *Improvement* and *Deterioration*. Systems are ranked by *Overall*, which aggregates `Fit` (alignment with the ABCD framework), `Recur` (cross-user recurrence), and `Spec` (specificity vs. genericness). Our system ranks *first* in Deterioration and *second* in Improvement, with the highest `Fit` in both.

Signature extraction uses temperature $\tau = 0.2$, chosen to favour stable, high-level cross-individual patterns over idiosyncratic phrasing, with up to 1,500 new tokens to accommodate the six required signatures with their evidence citations. We parse outputs by splitting on deterioration signature and improvement signatures, then apply field-specific regex to extract each component. When parsing fails, we retain the raw output for manual inspection.

3 Results and Analysis

We focus our analysis on Task 3, where our system is most closely aligned with the MIND framework and achieves its strongest performance. Quantitative results are reported on the 10 test timelines provided by the shared task organizers, and we complement these with a qualitative analysis of the extracted deterioration signatures.

3.1 Task 3.1: Summarisation Quality

Table 1 reports the official Task 3.1 evaluation across four metrics: `Consistency` (CS)–absence of contradiction against gold summaries via NLI; `Contradiction` (CT)–maximum NLI contradiction probability (lower is better); `ROUGE-L Recall`–longest common subsequence recall; and `BERTScore Recall`–semantic token-level coverage. The final rank is based on the average score rank across all four metrics. Our system (rank 11) shows moderate CS (0.688) and BERTScore (0.306) with a relatively high CT (0.812), indicating that our ABCD-grounded summaries are internally coherent but diverge in phrasing from the gold annotations. The high CT score reflects phrasing divergence rather than factual contradiction—our summaries characterise the same clinical dynamics using different ABCD-grounded terminology. Systems with high ROUGE-L (e.g., USAI: 0.333) produce summaries with greater lexical overlap with the gold text, as ROUGE-L directly measures longest common subsequence recall against the reference. Our approach prioritises *conceptual* accuracy—correct identification and description of ABCD relational dynamics—over *lexical* reproduction of the gold phrasing. Evidence for this distinction lies in our Task 3.2 Fit Score (1.000): our summaries consistently use the required ABCD abbreviations, describe relational dynamics between subelements (e.g., *mutually reinforces*, *progressively suppresses*), and maintain the three required sections, even when specific phrasing diverges from the gold. This conceptual–lexical trade-off is a strong trade-off between the two tasks.

3.2 Task 3.2: Quantitative Performance

Tables 2 report the official Task 3.2 results. Scores assess: `Fit` (alignment with the ABCD clinical framework), `Recurrence` (cross-individual pattern grounding), and `Specificity` (non-genericity of the description).

MIND Framework Alignment Our perfect Fit Score (1.000 overall; 0.875 deterioration) reflects the effectiveness of theory-explicit prompting: encoding the ABCD taxonomy directly into the system part ensures that signatures closely match the clinical framework used for evaluation, outperforming all other teams in this dimension.

Fit–Specificity Trade-off Our lower Specificity Score in the overall ranking (0.375) reflects a trade-off inherent to our aggregation strategy. Presenting all training summaries simultaneously encourages cross-individual abstraction at the cost of per-case granularity. This contrasts with our high deterioration Specificity (0.938), suggesting that deterioration patterns are both more framework-aligned *and* more distinctive, while improvement patterns are harder to characterize specifically.

Task 3.1 vs. Task 3.2 Contrast A notable pattern emerges: our system performs relatively modestly on Task 3.1 (rank 11) but strongly on Task 3.2 (rank 2). This is consistent with the hypothesis that our approach optimizes for ABCD framework fidelity rather than lexical overlap with gold summaries. Task 3.1 is partly evaluated on ROUGE-L (lexical recall), which disadvantages summaries that correctly characterize the clinical dynamics but use different phrasing. Task 3.2 is evaluated on Fit, which directly rewards framework alignment, where our approach excels. This suggests that theory-explicit prompting is most beneficial for tasks requiring *conceptual* rather than *lexical* accuracy.

Deterioration vs. Improvement Asymmetry. Our strong deterioration performance relative to improvement suggests that maladaptive change follows more stereotyped ABCD patterns (self-criticism, hopelessness, and avoidance forming closed loops) that are robustly recurrent across individuals, while improvement signatures are more heterogeneous and harder to characterize across individuals. This asymmetry has implications for clinical monitoring: automated deterioration detection may generalize more reliably, while improvement characterization may require more individualized modeling.

4 Conclusion

We presented a theory-explicit prompting pipeline for longitudinal mental health modeling grounded in the MIND framework (Atzil-Slonim, 2025), encoding the ABCD taxonomy directly into the system prompt to produce clinically interpretable summaries and recurrent signatures. Our system ranked first in deterioration signature extraction and second overall in Task 3.2, achieving the highest Fit Score (1.000) across all teams–demonstrating that grounding NLP systems in established psychological theory is a performance-relevant design decision, particularly for tasks where conceptual accuracy matters more than lexical surface overlap. The contrasting Task 3.1 performance highlights a broader tension between framework fidelity and lexical proximity to reference annotations, a challenge that remains open for clinically grounded generation.

Ethics Statement

This work uses a dataset of social media posts from mental health subreddits, handled in compliance with the CLPsych 2026 data access agreement. No individual users are identified, and all post examples in this paper have been paraphrased as required by the shared task guidelines. The systems described are research prototypes not intended for clinical deployment without human oversight; automated characterization of mental health states carries risks of misclassification with serious consequences for vulnerable individuals. All LLM generation steps use **Mistral-7B-Instruct-v0.2**, served via a locally hosted Ollama endpoint. No proprietary APIs were used at any stage, in compliance with the CLPsych 2026 Data Access Form requirement prohibiting closed-source model use.

Limitations

Our dataset of 40 Reddit timelines limits statistical reliability; the direction inference heuristic may mislabel ambiguous sequences, introducing noise into Task 3.2 aggregation, and the 90-word signature limit constrains the expressiveness of ABCD interaction descriptions. For test sequences, per-post ABCD flags are produced by our Task 1 system rather than gold annotations, meaning Task 3.1 test performance reflects end-to-end pipeline noise. LLM outputs are non-deterministic; we report single inference passes without ensemble averaging. All results are specific to English-language Reddit posts from mental health subreddits and may not generalize to other languages, platforms, or clinical populations.

Acknowledgements

We thank the organizers of the CLPsych 2026 Shared Task for the annotated dataset and evaluation infrastructure, the MIND framework team for publicly releasing the ABCD annotation scheme, and the CSE Department of IIT Ropar for providing computational resources used in this research.

References

Iqra Ali, Talia Tseriotou, Guy Dvir, Callum Chan, Yuxiang Zhou, Juan Antonio Lossio-Ventura, Ayal Klein, Aya Shamir, Dan Sayda, Anthony Hills, Aya Zirikly, Diana Inkpen, Dana Atzil-Slonim, and Maria Liakata. 2026. Overview of the clpsych 2026 shared task: Capturing and characterizing mental health changes through social media timeline dynamics. In *Proceedings of the 11th Workshop on Computational Linguistics and Clinical Psychology*. Association for Computational Linguistics.

Dana Atzil-Slonim. 2025. Multimodal intrapersonal and interpersonal dynamics (MIND): A transtheoretical coding manual.

Dana Atzil-Slonim. 2026. Leveraging theoretical and technological innovations to study the mechanisms that underlie therapeutic change in psychotherapy. In Louis G. Castonguay, Dana Atzil-Slonim, Michael Barkham, and Wolfgang Lutz, editors, *Practice-Based Evidence in the Psychological Therapies: Toward Policy Implications for Research, Training, and Clinical Guidelines*. Oxford University Press, New York.

Tayyaba Azim, Loitongbam Gyanendro Singh, and Stuart E Middleton. 2022. Detecting moments of change and suicidal risks in longitudinal user texts using multi-task learning. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 213–218.

Tom Brown and 1 others. 2020. Language models are few-shot learners. *Advances in Neural Information Processing Systems*, 33:1877–1901.

Glen Coppersmith, Mark Dredze, and Craig Harman. 2014. Quantifying mental health signals in Twitter. In *Proceedings of the Workshop on Computational Linguistics and Clinical Psychology*, pages 51–60.

Aobo Kong and 1 others. 2024. Better zero-shot reasoning with role-play prompting. In *Proceedings of NAACL 2024*.

Pengfei Liu and 1 others. 2023. Pre-train, prompt, and predict: A systematic survey of prompting methods in natural language processing. *ACM Computing Surveys*, 55(9):1–35.

Loitongbam Gyanendro Singh, Junyu Mao, Rudra Mutalik, and Stuart E Middleton. 2024a. Extracting and summarizing evidence of suicidal ideation in social media contents using large language models. In *Proceedings of the 9th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2024)*, pages 218–226.

Loitongbam Gyanendro Singh, Stuart E. Middleton, Tayyaba Azim, Elena Nichele, Pinyi Lyu, and Santiago De Ossorno Garcia. 2024b. ConversationMoC: Encoding conversational dynamics using multiplex network for identifying moment of change in mood and mental health classification. In *Proceedings of the Machine Learning for Cognitive and Mental Health Workshop (ML4CMH 2024), co-located with AAAI 2024*, CEUR Workshop Proceedings, pages 42–56.

Loitongbam Gyanendro Singh and Sanasam Ranbir Singh. 2024. Characteristics of opinions in the societal and non-societal domains. *Social Network Analysis and Mining*, 14(1).

Adam Tsakalidis, Jenny Chim, Iman Munire Bilal, Ayah Zirikly, Dana Atzil-Slonim, Federico Nanni, Philip Resnik, Manas Gaur, Kaushik Roy, Becky Inkster, Jeff Leintz, and Maria Liakata. 2022. Overview of the CLPsych 2022 shared task: Capturing moments of change in longitudinal user posts. In *Proceedings of the Eighth Workshop on Computational Linguistics and Clinical Psychology*, pages 184–198, Seattle, USA. Association for Computational Linguistics.

Adam Tsakalidis and Maria Liakata. 2022. Mental health longitudinal modelling on social media. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 1–15.

Talia Tseriotou, Jenny Chim, Ayal Klein, Aya Shamir, Guy Dvir, Iqra Ali, Cian Kennedy, Guneet Singh Kohli, Anthony Hills, Ayah Zirikly, Dana Atzil-Slonim, and Maria Liakata. 2025. Overview of the CLPsych 2025 shared task: Capturing mental health dynamics from social media timelines. In *Proceedings of the 10th Workshop on Computational Linguistics and Clinical Psychology (CLPsych 2025)*, pages 193–217, Albuquerque, New Mexico. Association for Computational Linguistics.

A Appendix

A.1 Task Overview

The CLPsych 2026 Shared Task (Ali et al., 2026) focuses on longitudinal mental health modeling within the MIND framework (Atzil-Slonim, 2025). This paper addresses the sequence-level tasks: structured summarization (Task 3.1) and recurrent signature extraction (Task 3.2), described below.

Task 3.1 – Sequence Summarisation. Given a chronologically ordered window of posts surrounding a detected change event (Switch or Escalation), systems generate a structured natural language summary describing how self-state dynamics evolve across the sequence and culminate in (for a Switch) or unfold through (for an Escalation) the change. Summaries describe: (1) the central recurring psychological theme in ABCD terms; (2) the dynamics within each self-state, including how ABCD subelements interact; and (3) the relationship between adaptive and maladaptive self-states, including patterns of dominance, suppression, or reflective dialogue. The direction of change (improvement or

deterioration) must be stated explicitly (Ali et al., 2026).

Task 3.2 – Recurrent Signature Extraction. Building on Task 3.1, systems identify and summarise *recurrent* patterns of change across multiple timelines. Teams extract three signatures of deterioration and three signatures of improvement, each describing a recurring dynamic pattern in ABCD and self-state structure that leads up to and culminates in the change event. These signatures must be grounded in observable self-state dynamics across multiple individuals, rather than a single case (Ali et al., 2026).

A.2 Dataset

The shared task dataset comprises `40 Reddit-based user timelines` drawn from mental health-related subreddits, split into 30 training timelines and 10 test timelines (Ali et al., 2026). Each timeline is a chronologically ordered sequence of posts annotated according to the MIND scheme (Atzil-Slonim, 2025). Training annotations include sequence-level summaries around Switch and Escalation events covering Central Theme, Within-State Dynamics, and Between-State Dynamics. Test data contain only post text and metadata; all annotations are withheld.

A.3 Direction Inference Keyword Lists

The following keywords were used for direction inference (Stage 1). Lists were derived through close reading of training gold summaries and MIND framework terminology (Atzil-Slonim, 2025); no automated selection procedure was used.

Deterioration keywords: *worsen*, *worsening*, *escalat*, *collapse*, *deteriorat*, *maladaptive dominant*, *suicid*, *hopeless*, *despair*, *suppressing adaptive*.

Improvement keywords: *recover*, *stabilise*, *stabiliz*, *adaptive dominant*, *positive shift*, *hopeful*, *improvement*, *adaptive gain*, *reflective dialogue*, *re-emerg*.

A.4 Prompt Sketches

Prompt sketches for Stages 2 and 3 are shown below. All examples have been paraphrased to protect user privacy. `[ABCD TAXONOMY]` denotes the full MIND subelement taxonomy (omitted for space); the complete taxonomy follows Atzil-Slonim (2025).

Stage 2 — System Prompt (abridged).

You are a clinical psychologist trained in the MIND framework. Given a sequence of social media posts surrounding a `{change_type}` event reflecting a `{direction}` in well-being, produce a structured clinical summary in three parts:

1. **Central Theme**
2. **Within-State Dynamics**
3. **Between-State Dynamics**

Use formal third-person prose. Reference all ABCD elements as: **(A)**, **(B-S)**, **(B-O)**, **(C-S)**, **(C-O)**, **(D)**. State the direction of change explicitly. Do not reproduce numeric presence scores. Maximum 350 words.
`[ABCDTAXONOMY]`

Stage 2 — User Prompt (abridged).

EXAMPLE SUMMARY *(for style reference only):*
`{gold_training_summary}`

Now generate a summary for the following new sequence.

Timeline: `{timeline_id}`
Sequence: `{sequence_id}`
Type: `{change_type}`
Direction: `{direction}`

Post 1 [*adaptive*; **A**:(5) hopeful, **D**:(1) relatedness]:
`{post_text[:500]}`

Post 2 [*maladaptive*; **A**:(4) depressed, **C-S**:(2) self-critical]:
`{post_text[:500]}`

. . .

Stage 3 — Aggregated Prompt (abridged).

You are a clinical psychologist. Below are summaries of change sequences, grouped by direction. Identify recurrent ABCD-grounded dynamic signatures appearing in **at least two distinct timelines**. For each signature, describe:

(i) The ABCD interaction pattern

(ii) How adaptive/maladaptive dominance shifts

(iii) How dynamics crystallise at the change event

(iv) 2–3 supporting timeline IDs

DETERIORATION SUMMARIES:
[Timeline X]: `{summary[:800]}`
[Timeline Y]: `{summary[:800]}`
. . .

IMPROVEMENT SUMMARIES:
. . .

Author Index

Abdullah, Saeed, 138
Adamidi, Eleni, 188
Agarwal, Navneet, 306
Ahmed, Ammar, 531
Ahmed, Helal, 164
Ahmed, Syed Ishtiaque, 164
Ait Hou, Iyad, 282
Akhter, Mahmud, 56
Aktar Songur, Irem, 368
Aldogom, Sufian, 531
Ali, Iqra, 56, 389
Anikejeva, Alina, 208
Antony, Anson, 435
Atzil-Slonim, Dana, 389

Bar, Kfir, 244
Bar, Mor, 362
Basile, Eric, 531
Ben-Zeev, Dror, 12
Bhuiyan, Abu, 164
Bloomberg, Justin, 298
Boyd, Ryan, 43
Brown, Grace, 531
Buck, Benjamin, 12
Bui, Tony, 250
Buyanov, Igor, 510

Campione, Samuel, 250
Carmiol-Rodriguez, Priscilla, 153
Chan, Callum, 389
Chen, Feng, 12
Chen, Liuliu, 383
Chen, Rui, 422
Cleary, Scarlett, 482
Cohen, Alex, 12
Cohen, Trevor, 12
Conway, Mike, 271, 383, 472
Cui, Kejian, 271

D'alfonso, Simon, 271
Debi, Joysree, 164
Demeocq, Cyndie, 324
Dervakos, Edmund, 188
Ding, Jieqiong, 119
Dinu, Liviu, 355
Do, Duc, 504
Dvir, Guy, 389

Eichstaedt, Johannes, 250
Elyoseph, Tal, 32
Elyoseph, Zohar, 32

Feltman, Scott, 43
Finley, Ann Marie, 340
Fruchter, Eyal, 244

Garg, Priyanshi, 119, 153
Gerke, Sara, 128
Gligorovic, Stevi, 1
Goodall, Karen, 324
Grinapol, Shulamit, 244
Guntuku, Sharath Chandra, 128
Gupta, Mehak, 221
Gutterman, Isaac, 531
Gwilliams, Laura, 340

Haber, Yuval, 32
Han, Lifeng, 458
Han, Yu, 88
Hasan, Md Arid, 164
Hefetz, Ofri, 244
Hills, Anthony, 56
Hills, Anthony R, 389
Hoang, Van, 258
Holzman, Yuval, 32
Hussain, Rasiq, 221
Hwa, Rebecca, 282
Hwang, Kyomin, 535

Imel, Zac, 1
Inkpen, Diana, 389
Iribarren, Sarah, 153
Iseri, Elvan, 368
Isman, Kelsey, 482

Jha, Shubham, 547
Jin, Flora, 340
Job, Shameed, 441

Karacan, Baris, 368
Karpenko, Volodymyr, 498
Khan, Aditya, 164
Kim, Hyeonjin, 535
Kious, Brent, 1
Kjell, Oscar, 43, 178
Klein, Ayal, 389

Kotov, Roman, 43
Kries, Jill, 340
Kuczynski, Adam, 12
Kumar, Gautam, 435
Kumar, Pawan, 547
Kwak, Nojun, 535
Kwanin, Charles, 153

Lahnala, Allison, 482
Lal, Daisy, 458
Laws, Ben, 100
Lee, Annie, 164
Lee, Hyunho, 535
Li, Changye, 12
Li, Derron, 482
Liakata, Maria, 56, 389
Linkovski, Omer, 32
Lissak, Shir, 244
Litvinova, Karina, 521
Losavio, Stefanie, 250
Lossio-Ventura, Juan Antonio, 389
Luft, Benjamin, 43
Lyberatos, Vassilis, 188

Mankarious, Saad, 282
Mao, Junyu, 56
Marker, Aaron, 178
Martin Lopez, Maria, 250
Mazurina, Ekaterina, 510
Meshram, Ankit, 547
Mira, Antonietta, 498
Miscouridou, Xenia, 56
Montesano, Adrian, 298
Morgan, Sarah, 100
Murray, Graham, 100

Naskar, Abir, 472
Nguyen, Minh, 504

Oltmanns, Joshua, 221
Omoomi, Kian, 482
Ophir, Yaakov, 244
Ozaslan, Ahmet, 368

Pandey, Shrankhla, 100
Paullada, Amandalynne, 119
Pentyala, Sikha, 153
Pham, Tin, 504
Pimentel, Brian Miguel, 482
Ponomareva, Alina, 521
Prasad, Animesh, 324
Puspo, Sadiya Sayara Chowdhury, 76
Pérez-Buriel, Marc, 298
Pérez-Rosas, Verónica, 238

Raballo, Andrea, 498
Rafaeli, Eshkol, 32
Rai, Sunny, 128
Rao, Ishita, 119
Ravenda, Federico, 498
Refoua, Elad, 32, 362
Reichart, Roi, 244
Rennick-Egglestone, Stefan, 100
Ringwald, Whitney, 43
Roberti, Javier, 153
Robinson, Jo, 383
Rodriguez, Yvette, 153
Rogers, Eoin, 258
Roll, Nathan, 340, 531
Ross, Björn, 324
Ross, Robert, 258
Rozova, Vlada, 383
Rozovskaya, Alla, 441

Sadeque, Farig, 164
Saeidi, Marzieh, 324
Sanghani, Aadi, 482
Sayda, Dan, 389
Schoene, Annika Marie, 435
Schou, Jens Kristian, 1
Schriger, Simone, 128
Schuhmann, Bailee, 250
Schwartz, H. Andrew, 43, 178, 250
Sehgal, Neil, 128
Shah, Juhi, 221
Shain, Cory, 340
Shamir, Aya, 389
Sharma, Neha, 306
Shen, Qian, 88
Singh, Loitongbam, 547
Singhvi, Shreya, 250
Sirigana, Akshay Krishna, 482
Sirts, Kairit, 208, 306
Slade, Mike, 100
Sp, Azhagu Meena, 164
Sprecher, Jennifer, 153
Stade, Elizabeth, 128, 250
Stamou, Giorgos, 188
Stekacheva Sancho, Nina, 521
Subrahmanya, Shashanka, 250
Sumner, Meghan, 340

Tauscher, Justin, 12
Tennakoon, Lakshika, 531
Thummar, Dhruvil, 238
Tikochinski, Refael, 244
Tran, Vu, 504
Tsai, Angelina, 12
Tseriotou, Talia, 56, 389
Tăbușcă, Ștefana-Arina, 355

Uban, Ana Sabina, 355
Ungar, Lyle, 128
Uzuner, Özlem, 76

V Ganesan, Adithya, 43
Valieva, Nafisa, 510
van Mulligen, Erik, 458
Varadarajan, Vasudha, 178, 482
Vidrio, Alfie, 153
Voulodimos, Athanasios, 188

Wachtel, Haya, 244
Wang, Catherine, 340
Welch, Charles, 482
Wiltsey Stirman, Shannon, 250
Worley, Courtney, 250

Xiao, Haonan, 422
Xu, Yunkai, 138
Xuan, William, 250

Yahyapour, Ava, 441
Yang, Yi, 422
Yetisgen, Meliha, 12
Yi, Irene, 531
Yirmiya, Karen, 32

Zampieri, Marcos, 76
Zeid, Nour, 282
Zhang, Hongyi, 482
Zhang, Mengjia, 422
Zhou, Graise, 128
Zhou, Yuxiang, 389
Zhyrko, Maryia, 458
Ziaei Bideh, Amirmohammad, 441
Zirikly, Ayah, 282, 389