PsychēChat: An Empathic Framework Focused on Emotion Shift Tracking and Safety Risk Analysis in Psychological Counseling

Zhentao Xia[1]*, Yongqi Fan[1,2]*, Yuxiang Chu[1], Yichao Yin[1,3], Liangliang Chen[3], Tong Ruan[1]†, Weiyan Zhang[1]†
[1]East China University of Science and Technology, Shanghai, China, [2]Tencent
[3]Shanghai Changning Mental Health Center, Affiliated Mental Health Center of East China Normal University, Shanghai, China
{xneil, johnnyfans}@mail.ecust.edu.cn, {ruantong, weiyanzhang}@ecust.edu.cn

Abstract

Large language models (LLMs) have demonstrated notable advancements in psychological counseling. However, existing models generally do not explicitly model seekers' emotion shifts across counseling sessions, a core focus in classical psychological schools. Moreover, how to align counselor models' responses with these emotion shifts while proactively mitigating safety risks remains underexplored. To bridge these gaps, we propose **PsychēChat**, which explicitly integrates emotion shift tracking and safety risk analysis for psychological counseling. Specifically, we employ interactive role-playing to synthesize counselor–seeker dialogues, incorporating two modules: **Emotion Management Module**, to capture seekers' current emotions and emotion shifts; and **Risk Control Module**, to anticipate seekers' subsequent reactions and identify potential risks. Furthermore, we introduce two modeling paradigms. The **Agent Mode** structures emotion management, risk control, and counselor responses into a collaborative multi-agent pipeline. The **LLM Mode** integrates these stages into a unified chain-of-thought for end-to-end inference, balancing efficiency and performance. Experiments with simulated interaction, dialogue-level evaluation, ablation studies, and expert assessment indicate that PsychēChat improves emotion-shift awareness and risk-aware response generation in psychological counseling support. Our data and code are available at https://github.com/XNeil12138/PsycheChat.

1 Introduction

In recent years, global mental health issues have increased significantly (World Health Organization, 2022). Depression, anxiety, and stress-related disorders have become major public health concerns. However, due to the high professional requirements for psychologists and the cost and time constraints of offline counseling, many individuals with mental health needs cannot obtain consistent and affordable support. The rapid development of LLMs provides new opportunities for psychological counseling (Guo et al., 2024; Yang et al., 2023; Xiao et al., 2024; Kang et al., 2024; Zheng et al., 2024). Some psychological models, such as SoulChat (Chen et al., 2023) and MeChat (Qiu et al., 2024a), attempt to simulate human counselors to provide emotional support. Recently, several efforts have explored the synthesis of high-quality datasets for psychological counseling, including PsyDT (Xie et al., 2025) and CATCH (Chen et al., 2025).




Figure 1: Two Core Focuses of PsychēChat. (a) Tracking emotion shifts helps generate more context-aware and empathetic responses. (b) Different counselor responses can lead to different levels of safety risk.

However, existing counseling models still have limitations in capturing seekers' psychological states and real needs behind emotions. Models that focus on emotions typically operate at a single moment and do not explicitly model emotion shifts across a full counseling session. In classical psychology, three major psychological schools (Klein, 1952; Rogers, 2012; Beck, 2020) emphasize the importance of emotion shifts in counseling. In partic-

*Equal contribution.
†Corresponding authors.

Proceedings of the 2026 Conference on Empirical Methods in Natural Language Processing, pages 25953–25985
October 24-29, 2026 ©2026 Association for Computational Linguistics

ular, Emotion-Focused Therapy (EFT) (Greenberg, 2004; Whelton, 2004), rooted in the humanistic tradition, treats emotion assessment as a moment-by-moment process, focusing on the emotional states individuals enter, remain stuck in, or leave, and their sequences. To illustrate this, we present an example illustrating emotion shifts in counseling. As shown in Figure 1(a), an unemployed seeker first asks, "Am I a failure?" then adds, "Maybe it's just for now." and finally questions, "Am I even worth believing in?" If the counselor responds only to the current emotion, such as offering encouragement during self-doubt, the counseling may stay superficial. By focusing on emotion shifts from anxiety and self-comfort to denial of self-worth, the counselor can better identify deeper needs, including the need to be affirmed, needed, and valued.

Meanwhile, existing psychological models emphasize safety requirements. As shown in Figure 1(b), different counselor responses can lead to very different emotional reactions from seekers. Cold or purely analytical responses may increase safety risks, while empathic and moderate responses better protect seeker safety. However, most safeguards rely on data filtering and evaluation during dataset construction, as well as implicitly acquired safety capabilities during model training. Consequently, such models may generate inappropriate responses in highly sensitive scenarios, failing to comply with the "Nonmaleficence" ethical principle (Kitchener, 1984).

In this paper, we propose **PsychēChat**, which enables models to better understand how and why emotions change, and to anticipate potential consequences before responding. Unlike traditional one-time or static multi-stage generation methods, we employ interactive role-playing to synthesize dialogues between emotionally rich seekers and EFT counselors. During data synthesis, we incorporate two key modules. The Emotion Management Module captures seekers' current emotions and emotion shifts, and further analyzes the potential causes of these shifts, aligning with EFT's focus on emotion state sequences. The Risk Control Module anticipates seekers' possible subsequent reactions, identifies potential risks, and provides suggestions for safety assurance. Based on this framework, we construct the **PsychēDialog** dataset.

PsychēChat supports two inference paradigms that balance capability and efficiency. The Agent Mode follows the process of emotion management, counselor response, and risk control used in data synthesis, and organizes them into a collaborative multi-agent pipeline. This ensures clear responsibilities at each stage and enhances interpretability. To reduce the efficiency cost of inference in online applications, we further propose the LLM Mode. It integrates the multi-stage process into a complete long chain-of-thought, enabling end-to-end inference for each response. Extensive experiments, including interactive scoring, dialogue-level evaluation, and human assessment, demonstrate that PsychēChat significantly improves models' emotion understanding and risk mitigation capabilities in psychological counseling.

The contributions of this paper are as follows:

- We propose **PsychēChat**, which is the first to focus on seekers' cross-turn emotion shifts in psychological counseling tasks and introduce an explicit safety analysis mechanism.
- We synthesize **PsychēDialog**, a dialogue dataset with more natural emotion flow, through interactive role-playing, and further introduce two inference paradigms, Agent Mode and LLM Mode.
- Extensive experiments demonstrate that PsychēChat achieves better performance in emotional understanding and emotional support, while outperforming existing methods for risk avoidance and safety control.

2 Related Work

2.1 Psychological LLMs

Due to the sensitive nature of counseling dialogues, publicly available real-world data is extremely limited. Consequently, most studies rely on synthetic data to construct training corpora for psychological LLMs. Early work expands question–answer datasets into multi-turn dialogues. SmileChat (Qiu et al., 2024a) extends PsyQA (Sun et al., 2021) using ChatGPT, while SoulChat (Chen et al., 2023) generates empathetic dialogues from crowdsourced QA pairs. Later studies incorporate domain knowledge to improve dialogue quality. CPsyCoun (Zhang et al., 2024a) adopts a two-stage framework based on counseling reports, and MindChat (Yan and Xue, 2023) uses self-chat with predefined themes and roles. More recent work introduces counseling schools to enhance professionalism. Cactus (Lee et al., 2024) constructs a dataset grounded in Cognitive Behavioral Therapy (CBT).




Figure 2: The overview of PsychēChat. The upper part shows an interactive dialogue synthesis framework with two modules for emotion management and risk control. The lower part presents two inference paradigms, Agent Mode and LLM Mode, designed to balance efficiency and performance.

PsyDT (Xie et al., 2025) simulates therapeutic language styles to build digital twins. CATCH (Chen et al., 2025), based on Single-Session Therapy (SST), generates counseling dialogues stage by stage. However, these approaches rely on static generation and struggle to model dynamic emotional changes during counseling sessions.

2.2 Focus in Psychological Counseling

Beyond data construction, existing research also explores key factors for counseling models, mainly emotion and safety. For emotion, GLHG (Peng et al., 2022) models global causes and moment-level emotions with a hierarchical graph network. ESCoT (Zhang et al., 2024b) introduces chain-of-thought reasoning to model seekers' emotional formation within a turn. IntentionESC (Zhang et al., 2025b) incorporates counselor intention modeling to identify key emotional elements. Wang et al. (2025) analyzes emotional trajectories and highlights gaps between synthetic dialogues and real therapy. For safety, Li et al. (2023) examines how seeker reactions influence counseling outcomes and strategy adjustment. PsyAdvisor (Hu et al., 2025b) annotates strategy decision logic and seeker reaction attribution, and proposes a proactive questioning planner. PsyGUARD (Qiu et al., 2024b) enhances safety through automated suicide ideation detection. Hu et al. (2025a) integrates diagnostic standards and therapeutic modalities into the generation process. PSY-STEP (Lee et al., 2026) improves response appropriateness through therapeutic target and action sequence planning. Although these studies focus on emotion modeling or safety, they still lack explicit integration of emotion shifts and risk avoidance into counseling response generation.

3 Methodology

3.1 Preliminary

3.1.1 Task Definition

Mental Health Support (MHS) (Qiu et al., 2024a) aims to enable dialogue systems to provide safe and effective support to users experiencing psychological distress during multi-turn interactions. Unlike open-domain chat or QA tasks, MHS focuses on two objectives: emotional relief and problem coping. The system needs to understand the seeker's difficulties and emotional state, provide empathy and comfort to stabilize emotions, and support the development of actionable coping strategies.

3.1.2 Emotion-Focused Therapy

In this work, we adopt Emotion-Focused Therapy (EFT) as the therapeutic type. EFT is rooted in humanistic psychology and treats emotion as the core target of intervention. It views emotions not only as sources of distress but also as gateways to change (Greenberg, 2004; Pos and Greenberg, 2007). Many psychological problems and interpersonal difficulties arise because core emotional experiences are not recognized, accepted, or fully processed. Therefore, the central goal of EFT is to help seekers access, understand, and transform "stuck emotions" into more adaptive emotional experiences and action tendencies.

3.2 Role-playing Dialogue Synthesis

3.2.1 Overview

As shown in the upper part of Figure 2, we synthesize multi-turn psychological counseling dialogues through interactive role-playing between a seeker and a counselor. The seeker generates responses by following a predefined role card, while the counselor produces responses through a three-stage pipeline. First, the Emotion Management Module analyzes the seeker's emotion shifts through interactions between the Emotion Tracking Agent and the Emotion Memory. Second, the EFT Counselor Agent generates a draft response based on EFT principles. Third, the Risk Control Module anticipates possible seeker reactions using the Dialogue-Guided Seeker Agent and evaluates the safety of the draft response using the Safety Analysis Agent.

3.2.2 Seeker Modeling

To ensure diversity in dialogue topics and seeker styles, we use 5,000 multi-turn dialogues from PsyDT as seed data. Inspired by personality-driven dialogue studies (Wang et al., 2024; Ye et al., 2025), we employ Gemini 2.5 Flash to summarize the seeker characteristics in each seed dialogue and construct a role card. Each role card contains basic information, including gender, age, occupation, Big Five personality traits, character, language style, hobbies, problems, and inner monologue.

To better support counseling-oriented simulation, we assign two goals to each role card: one emotion-related goal and one advice-related goal. We also externalize the implicit emotional dynamics in the seed dialogues by specifying an initial emotion and event-triggered emotional changes for each role card. This design makes the seeker's emotional trajectory explicit during simulation. The prompt for role card generation is provided in Appendix A.3.

After constructing the role cards, we group them by the 12 counseling topics and initial primary emotions (emotion group and intensity level), resulting in 74 groups. We then perform balanced sampling over these groups by selecting up to 30 role cards from each group, retaining all if fewer than 30 are available, and obtain 1,003 role cards. The topic distribution is shown in Appendix A.2. These cards are subsequently used as seeker profiles in dialogue synthesis. Given a role card and the dialogue history, the seeker is instructed to output its current emotion, triggering events, completed goals, and response content at each turn.

3.2.3 Counselor Modeling

We design the counselor pipeline for dialogue synthesis in three stages: emotion management, counselor draft generation, and risk control.

Emotion Management Module. For emotion modeling, we adopt Plutchik's Wheel of Emotions (Plutchik, 1980), which defines eight basic emotions with different intensities. Based on the seeker's latest response and the dialogue history, the Emotion Tracking Agent identifies the seeker's current emotional state, represented by one primary emotion and zero to two secondary emotions. It also summarizes recent emotion shifts, tracks the overall emotional trend, and analyzes the underlying causes. To support cross-turn emotional consistency, we maintain an **Emotion Memory** that stores the outputs of the Emotion Tracking Agent. This memory is updated after each turn and is used as context for subsequent emotion analysis.

EFT Counselor Agent. To improve the fluency and coherence of counseling responses, we adopt the three stages from Helping Skills (Hill, 1999): exploration, insight, and action. We further develop an EFT guideline that covers emotional access and regulation, processing core painful emotions, and emotion transformation and problem-solving. Based on the output of the Emotion Tracking Agent and the dialogue history, the EFT Counselor Agent determines the current counseling stage, selects appropriate EFT strategies, and generates a draft response.

Risk Control Module. To simulate sensitive situations that may arise in real counseling, the **Dialogue-Guided Seeker Agent** is designed to exhibit multiple response behaviors, including normal responses, silence, excessive sentimentality, and explosive anger. Unlike the seeker described

Dataset	Synthesis Approach	Data Source	Avg. Turns	Avg. Len	# Dialogues
SoulChatCorpus (Chen et al., 2023)	One-time	Crowd-sourced	5.9	65.6	230k
SmileChat (Qiu et al., 2024a)	One-time	PsyQA	5.7	27.9	55.2k
CPsyCounD (Zhang et al., 2024a)	One-time	Yidianling & Psy525	7.8	44.8	3.1k
MindChat (Yan and Xue, 2023)	One-time	-	4.6	33.6	1,000k
PsyDTCorpus (Xie et al., 2025)	One-time	SoulChatCorpus	18.1	44.8	5k
CATCH (Chen et al., 2025)	Multi-stage	Yixinli	29.7	57.9	0.2k
PsychēDialog	Role-playing	PsyDTCorpus	13.1	43.1	1k

Table 1: Comparison of Chinese psychological counseling datasets. "Avg. Turns" denotes the average number of dialogue turns per conversation, and "Avg. Len." denotes the average utterance length.

in Section 3.2.2, this agent does not access the role card and generates reactions solely from the dialogue history. For each potential reaction, the **Safety Analysis Agent** performs an assessment to determine whether the counselor's draft response may escalate risk or trigger emotional breakdown. If any risk is detected, the Safety Analysis Agent provides emotional and safety revision suggestions, and the EFT Counselor Agent regenerates the draft response accordingly. This process repeats until the response satisfies the safety requirement, with at most five regeneration attempts. If the response still fails the safety check, the corresponding dialogue sample is discarded.

3.2.4 Dialogue Synthesis

We adopt an interactive role-playing approach to synthesize multi-turn dialogues. Based on the sampled role cards, we use GPT-4.1 mini to simulate the seeker and to execute the different components in the counselor pipeline. At each turn, the seeker produces a response conditioned on the role card, and the counselor then generates a reply through the three-stage pipeline. When all predefined goals are fulfilled, the seeker appends `END` to its response to terminate the dialogue.

During data screening, we retain dialogues according to two criteria: the seeker's final primary emotion has non-negative valence, and at least one predefined goal is achieved. We use these criteria as quality control heuristics to retain single-session dialogues with constructive short-term outcomes. The resulting dataset, **PsychēDialog**, contains 1,003 psychological counseling dialogues and provides counseling scenarios with explicit emotional trajectories.

3.3 Inference Paradigms

Based on PsychēDialog, we propose two inference paradigms: Agent Mode and LLM Mode, as shown in the lower part of Figure 2.

3.3.1 Agent Mode

Following the response pipeline used in data synthesis, we propose the Agent Mode. We build separate training datasets for the Emotion Tracking Agent, the EFT Counselor Agent, and the Safety Analysis Agent and train them jointly. In contrast, the Dialogue-Guided Seeker Agent is trained separately to model potential seeker reactions.

In implementation, we adopt a function-call format, in which emotion management and risk control are treated as fixed `<tool_call>` components. The model invokes the Emotion Tracking Agent to analyze emotion shifts and the Safety Analysis Agent to assess response risks, then receives the corresponding outputs through `<tool_response>`.

During response generation, the framework follows a collaborative multi-agent pipeline in the order of emotion tracking, counselor draft generation, seeker reaction prediction, and safety analysis. The Risk Control Module serves as a verification mechanism. If potential risks are detected, the framework regenerates the draft response until it passes the safety check.

3.3.2 LLM Mode

Considering the efficiency overhead introduced by multi-stage reasoning in online applications, we further propose LLM Mode. Using GPT-4.1 mini, we compress the multi-stage process into a single, coherent chain-of-thought from a first-person perspective and place it before each counselor response. This reasoning process consists of four steps. **Emotion Shift Tracking**: Analyze the seeker's current emotional state, emotion shifts, and underlying causes. **Current Counseling Plan**: determine the current counseling stage and select appropriate counseling strategies. **Safety Risk Analysis**: formulate several candidate responses, anticipate possible seeker reactions, and assess potential risks. **Integration and Response**: integrate the above analyses and generate the final counselor response.

Model	SAGE			ESC-Eval							
	Sentient ↑	Success ↑	Failure ↓	Flu.	Expr.	Emp.	Info.	Skill.	Hum.	Ovl.	Avg.
Closed-Source LLMs											
GPT-4o	$54.06_{\pm 0.69}$	$20.67_{\pm 5.56}$	$25.00_{\pm 3.74}$	10.00	9.19	10.00	8.40	10.00	10.00	10.00	9.66
DeepSeek-V3	$76.99_{\pm 2.69}$	$47.67_{\pm 6.85}$	$9.00_{\pm 0.82}$	10.00	10.00	10.00	8.83	9.98	10.00	10.00	9.83
Qwen-MAX	$62.88_{\pm 3.75}$	$31.00_{\pm 1.41}$	$16.33_{\pm 2.87}$	10.00	9.59	10.00	9.16	9.99	9.99	10.00	9.82
Psychological LLMs											
SoulChat	$5.22_{\pm 0.19}$	$0.00_{\pm 0.00}$	$93.33_{\pm 1.25}$	9.09	7.07	8.00	7.10	7.77	9.22	7.86	8.01
MeChat	$14.62_{\pm 1.89}$	$1.67_{\pm 0.94}$	$76.00_{\pm 0.82}$	9.68	7.75	9.08	7.69	8.99	9.77	9.06	8.86
CPsyCounX	$10.08_{\pm 2.03}$	$0.67_{\pm 0.47}$	$80.00_{\pm 3.74}$	9.36	7.54	8.89	7.50	8.74	9.46	8.71	8.60
MindChat	$11.51_{\pm 0.92}$	$0.00_{\pm 0.00}$	$81.00_{\pm 0.00}$	9.93	8.01	8.85	7.84	8.85	9.91	8.93	8.90
SoulChat2.0	$60.06_{\pm 2.11}$	$24.33_{\pm 2.87}$	$17.33_{\pm 0.47}$	9.99	8.79	9.92	7.91	9.81	**10.00**	9.90	9.47
+ PsyAdvisor	$57.67_{\pm 1.36}$	$16.67_{\pm 1.70}$	$17.00_{\pm 1.63}$	8.78	7.50	8.59	6.73	7.77	9.02	8.13	8.07
SoulChat-R1	$70.87_{\pm 5.08}$	$42.67_{\pm 18.2}$	$16.33_{\pm 1.25}$	9.81	8.51	9.74	7.09	8.90	9.81	9.45	9.04
Ours											
Qwen2.5-7B-Instruct	$37.07_{\pm 2.40}$	$10.33_{\pm 2.36}$	$36.67_{\pm 2.05}$	9.98	9.10	9.96	**8.25**	**9.93**	9.95	9.97	9.59
+ PsychēChat-LLM	$69.55_{\pm 1.53}$	$42.33_{\pm 4.11}$	$15.33_{\pm 3.30}$	9.98	**9.43**	9.99	8.22	9.87	9.99	9.98	**9.64**
+ PsychēChat-Agent	$71.80_{\pm 1.05}$	$44.33_{\pm 6.24}$	$15.33_{\pm 3.30}$	**10.00**	9.35	9.99	7.99	9.73	**10.00**	9.96	9.57
Qwen3-8B	$48.69_{\pm 0.82}$	$25.00_{\pm 4.08}$	$30.67_{\pm 3.40}$	8.90	7.44	9.14	7.18	8.65	9.33	8.80	8.49
+ PsychēChat-LLM	$69.92_{\pm 2.25}$	$42.33_{\pm 2.62}$	$16.33_{\pm 3.86}$	9.80	8.75	9.85	7.13	8.92	9.96	9.65	9.15
+ PsychēChat-Agent	**78.01**$_{\pm 1.60}$	**51.00**$_{\pm 9.27}$	**11.00**$_{\pm 2.83}$	**10.00**	9.03	**10.00**	7.82	9.75	**10.00**	**9.99**	9.51

Table 2: Evaluation results of different models under SAGE and ESC-Eval. The best results are highlighted in **bold**, and the second-best results are underlined. Closed-source LLMs are reported for reference.

During response generation, the model completes all steps through a single end-to-end reasoning process, which improves inference efficiency.

4 Experiment Setup

4.1 Data Statistics

We design and generate structured role cards based on the multi-turn dialogues provided by PsyDT. By using GPT-4.1 mini for interactive role-playing, we constructed PsychēDialog, a dataset consisting of 1,003 multi-turn Chinese counseling dialogues. In terms of statistics, we compare our dataset with existing Chinese counseling datasets, and the detailed statistics are presented in Table 1.

4.2 Implementation Details

During training, we fine-tune Qwen2.5-7B-Instruct and Qwen3-8B on both LLM Mode and Agent Mode data. The training is conducted using ms-swift (Zhao et al., 2025), with 3 training epochs, a learning rate of $1e-5$, and a warm-up ratio of 0.05. During inference, all models use a temperature of 0.0 to reduce generation randomness.

4.3 Evaluation Frameworks

To comprehensively evaluate model performance, we use three evaluation frameworks.

SAGE (Zhang et al., 2025a). SAGE is an interactive framework that evaluates whether a counselor model can improve a simulated seeker's emotional state while maintaining social understanding. It uses a Sentient Agent with turn-level emotion updates. The Sentient score reflects the seeker's final emotional state, where higher scores indicate improvement and lower scores indicate deterioration. Each dialogue lasts at most 10 turns and stops early if the score exceeds 100 (success) or falls below 10 (failure). We use Gemini 2.5 Flash as the Sentient Agent, evaluate each model on 100 scenarios, and report the average score over three runs.

ESC-Eval (Zhao et al., 2024). ESC-Eval is a multi-dimensional framework with ESC-Role and ESC-Rank. ESC-Role simulates a seeker interacting with the evaluated model, while ESC-Rank scores the completed dialogue. It reports Fluency (Flu.), Expression (Expr.), Empathy (Emp.), Information (Info.), Skillful (Skill.), Humanoid (Hum.), Overall (Ovl.), and Average (Avg.) on a 0–10 scale. We use DeepSeek-V3.2 as ESC-Role for 10-turn interactions and Gemini 2.5 Flash as ESC-Rank.

PsychēEval. We propose PsychēEval as a custom framework tailored to our setting. We sample 100 role cards from the remaining pool using the same grouping and sampling strategy as in training, and use Gemini 2.5 Flash instead of GPT-4.1

Method	LLM Evaluation Metrics				Human Evaluation Metrics			
	EIS ↑	EDS ↓	GAR ↑	RLS ↓	Empathy	Professionalism	Effectiveness	Safety
SoulChat2.0	2.65	0.30	0.93	0.0185	$3.85_{\pm 0.16}$	$3.53_{\pm 0.12}$	$3.87_{\pm 0.18}$	$3.82_{\pm 0.08}$
SoulChat-R1	2.59	0.29	0.90	0.0085	$3.85_{\pm 0.28}$	$3.49_{\pm 0.28}$	$3.81_{\pm 0.33}$	$3.86_{\pm 0.04}$
PsychēChat-LLM	2.53	**0.26**	0.86	**0.0061**	$3.85_{\pm 0.35}$	$3.33_{\pm 0.37}$	$3.87_{\pm 0.31}$	$4.05_{\pm 0.35}$
PsychēChat-Agent	**2.67**	0.27	**0.94**	0.0062	$\mathbf{4.54}_{\pm 0.34}$	$\mathbf{4.23}_{\pm 0.52}$	$\mathbf{4.45}_{\pm 0.32}$	$\mathbf{4.41}_{\pm 0.30}$

Table 3: Evaluation results under PsychēEval. The best results are highlighted in **bold**. For human evaluation, Kendall's W (Kendall and Smith, 1939) ranges from 0.43 to 0.50, indicating moderate annotation agreement.

mini as the simulated seeker to reduce distributional similarity. We further annotate risk signals that reflect negative reactions to the counselor's previous response. Following Plutchik's Wheel of Emotions, we assign signed scores to emotion labels according to their groups and intensity levels. For each turn, we compute a weighted emotion score that assigns greater weight to the primary emotion. We report Emotional Improvement Score (EIS), Emotional Degradation Score (EDS), Goal Achievement Ratio (GAR), and Risk Level Score (RLS), with definitions in Appendix B.1. We also conduct human evaluation on 50 randomly sampled dialogues for each method, rated on Empathy, Professionalism, Effectiveness, and Safety using a 0–5 scale.

4.4 Baselines

To validate the effectiveness of our framework, we compare PsychēChat with several baseline models:

Closed-source LLMs: GPT-4o (Hurst et al., 2024), DeepSeek-V3 (Liu et al., 2024), Qwen-MAX (Team, 2024).

Psychological LLMs: SoulChat (Chen et al., 2023); MeChat (Qiu et al., 2024a); CPsyCounX (Zhang et al., 2024a); MindChat (Yan and Xue, 2023); SoulChat2.0 (Xie et al., 2025); PsyAdvisor (Hu et al., 2025b); SoulChat-R1 (Chen et al., 2025). PsyAdvisor follows its original implementation with SoulChat2.0 as the base model. SoulChat-R1 follows its official setup using the CATCH dataset with three rounds of LoRA training.

5 Experiment Analysis

5.1 Comparison with Baselines

SAGE. As shown in Table 2, traditional psychological LLMs obtain relatively low scores, likely because they are trained with shorter dialogues and weaker base models. Although recent psychological LLMs show clear improvements in performance, they still fall behind PsychēChat on Sentient, Success, and Failure. These results suggest that our model better improves the seeker's emotional state while maintaining safety. Compared with the base models, both Qwen2.5 and Qwen3 achieve consistent performance gains after training, validating the effectiveness and generality of PsychēDialog for mental health support. The Agent Mode outperforms the LLM Mode on all three dimensions, showing that a collaborative multi-agent pipeline is crucial for achieving high-quality psychological counseling. Meanwhile, the LLM Mode requires fewer model calls and achieves lower inference latency, as detailed in Appendix B.11. Notably, PsychēChat matches or even surpasses closed-source models on all three dimensions, demonstrating strong emotion improvement capability and intervention effectiveness.

ESC-Eval. As shown in Table 2, PsychēChat shows improvements over psychological LLMs on most dimensions, indicating that emotion shift tracking and safety risk analysis jointly enhance counseling quality and human-likeness. Compared with the base models, PsychēChat achieves stable gains on most metrics, further validating the effectiveness of the training data and inference paradigms. Among the base models, Qwen2.5 performs better overall than Qwen3, possibly due to better alignment with emotional support tasks in terms of training. Closed-source models can be viewed as the current upper bound under automatic evaluation. PsychēChat approaches this bound on Fluency, Empathy, Humanoid, and Overall, indicating comparable counseling quality. However, it scores lower on Information because ESC-Eval favors explicit advice or guidance in each turn, which does not fully align with professional counseling practice. Additionally, frequent full scores among strong models suggest that ESC-Eval has limited discriminative power in the high-score range and cannot finely distinguish strong models.

PsychēEval. We select SoulChat2.0 and SoulChat-R1, the best-performing models under

Method	SAGE				ESC-Eval							
	Sentient ↑	Stability ↓	Success ↑	Failure ↓	Flu.	Expr.	Emp.	Info.	Skill.	Hum.	Ovl.	Avg.
PsychēChat-Agent	**78.01**$_{\pm 1.60}$	**32.04**$_{\pm 1.21}$	51.00$_{\pm 9.27}$	**11.00**$_{\pm 2.83}$	**10.00**	9.03	**10.00**	7.82	**9.75**	**10.00**	**9.99**	9.51
w/o EM	71.90$_{\pm 1.28}$	34.13$_{\pm 0.65}$	39.00$_{\pm 2.16}$	12.00$_{\pm 2.16}$	9.98	9.28	9.99	7.19	8.93	**10.00**	9.69	9.29
w/o RC	76.15$_{\pm 1.50}$	33.93$_{\pm 0.71}$	**52.00**$_{\pm 7.48}$	11.67$_{\pm 1.25}$	9.96	9.50	9.98	**8.05**	9.73	9.96	9.95	**9.59**
w/o EM & RC	71.68$_{\pm 0.82}$	34.27$_{\pm 0.40}$	41.67$_{\pm 6.94}$	11.67$_{\pm 1.25}$	9.98	**9.66**	9.99	7.79	9.57	9.99	9.90	9.55
SoulChat2.0-1003	57.29$_{\pm 0.24}$	36.72$_{\pm 0.48}$	23.00$_{\pm 2.16}$	20.33$_{\pm 0.47}$	9.57	8.98	9.49	7.77	9.07	9.67	9.38	9.13

Table 4: Ablation study under SAGE and ESC-Eval based on Qwen3-8B. The best results are highlighted in **bold**.

SAGE and ESC-Eval, as baselines and compare them with the two modes of PsychēChat (Qwen3-8B). Results are shown in Table 3. In LLM evaluation, PsychēChat-Agent achieves the highest EIS, indicating stronger guidance of positive emotional change. Both modes maintain low EDS and RLS, demonstrating stable control of negative emotions and risks. PsychēChat-Agent also achieves the best GAR, showing more effective support for counseling goals. For human evaluation, we invite three clinically experienced psychologists as annotators. Each dialogue is rated on four dimensions, and the final scores are averaged. PsychēChat achieves high Empathy and Safety scores, consistent with its strong EIS and RLS results. This suggests that improvements from emotion shift tracking and risk analysis are also perceived by human evaluators. On Professionalism and Effectiveness, PsychēChat-Agent obtains the highest scores, indicating strong alignment with professional counseling practice and effective therapeutic support.

5.2 Ablation Study

To evaluate the contributions of the Emotion Management (EM) and Risk Control (RC) modules in the dialogue synthesis stage, we design three ablation settings: removing EM, removing RC, and removing both EM and RC. Other settings remain unchanged. We regenerate the dialogues using GPT-4.1 mini and train Qwen3-8B under Agent Mode. Results are shown in Table 4.

Under SAGE, we additionally introduce Stability, defined as the standard deviation of Sentient scores across different scenarios. This metric measures cross-scenario consistency, reflecting whether the model can achieve stable emotional improvement across diverse contexts rather than performing very well in some scenarios while remaining moderate in others. Removing EM leads to a substantial drop in Sentient, confirming that explicit emotion modeling is the primary driver of emotional improvement. When EM is removed, RC alone does not significantly improve Sentient and slightly lowers Success. This suggests that risk control without accurate emotion modeling is insufficient for effectively improving emotional trajectories. When EM is included, adding RC maintains high Sentient while reducing cross-scenario fluctuation (lower Stability score). This indicates that EM primarily elevates emotional level, whereas RC enhances the stability and safety of the improvement process. The two modules play complementary roles rather than optimizing the same objective.

Under ESC-Eval, the ablation settings generally lead to lower performance on most evaluation dimensions, further confirming the importance of EM and RC in improving empathy, professionalism, and human-likeness in counseling. Notably, the full PsychēChat model achieves a slightly lower score on the Expression dimension. This indicates that with EM and RC, the model adopts a more cautious expression strategy, which slightly limits its language variety. We view this as a trade-off: by avoiding over-expressive responses, the model better follows professional principles and safety boundaries in psychological counseling.

To further investigate the source of quality improvements, we conduct a controlled comparison. According to the topic IDs in PsychēDialog, we select 1,003 corresponding original dialogues from PsyDT and fine-tune Qwen3-8B on this dataset. As shown in Table 4, under the same data scale and matched topic distribution, PsychēChat-Agent w/o EM & RC substantially outperforms SoulChat2.0-1003 across all SAGE metrics and shows consistent improvements on ESC-Eval. This result indicates that the multi-turn role-play synthesis mechanism improves training data quality. When EM and RC modules are further incorporated, performance improves further under SAGE, while maintaining competitive performance on ESC-Eval. These findings suggest that the improvements also stem from the explicit emotion shift modeling and safety analysis mechanisms embedded in the framework.

6 Conclusion

In this paper, we propose PsychēChat, an empathic framework for psychological counseling that explicitly focuses on emotion shift tracking and safety risk analysis. To support this, we synthesize PsychēDialog, a counseling dialogue dataset via interactive role-playing, incorporating Emotion Management and Risk Control modules. Furthermore, we introduce two modeling paradigms, the Agent Mode and the LLM Mode, to balance efficiency and performance. Simulation-based and expert evaluations suggest that PsychēChat provides stronger emotion-shift awareness and risk-aware counseling-style responses, while highlighting the need for broader real-world and clinical validation.

Limitations

Although the experiments demonstrate the effectiveness of PsychēChat, several limitations deserve further attention. First, data synthesis based on interactive role-playing significantly improves dialogue quality and emotional coherence, but its higher generation cost limits the scalability of the dataset. Moreover, the current conclusions are mainly based on simulated counseling settings, and their transferability to real-world or clinical interactions remains to be validated. Second, real-world counseling scenarios often require dynamic assessment of multiple factors. This paper focuses on emotion shift tracking and safety risk analysis, and does not explicitly model all counseling decision points, such as finer-grained strategy selection, dialogue phase adjustment, or adaptive agent routing. These capabilities are mainly learned from the training data in a data-driven manner. Third, PsychēDialog is currently constructed solely based on Chinese psychological counseling scenarios, and its applicability and generalization ability across cultural contexts remain to be validated in future work. In particular, the role cards, including persona settings, problem scenarios, and social backgrounds, may need to be adapted to different cultural contexts. Moreover, although EFT itself is general, the way counselors apply strategies, their language style, and the focus of their responses may be influenced by cultural values and social norms. As a result, strategy expression and dialogue details may require proper localization in different cultural settings. Finally, although we adopted three different evaluation frameworks, the proportion of expert-based evaluation is relatively limited. Future studies should incorporate more professional assessments and real-world scenario validations to further enhance the reliability and comprehensiveness of the conclusions.

Ethical Considerations

All datasets used in this study are publicly available. During data synthesis, we implemented a rigorous data cleaning process to ensure that the data contains no personally identifiable information, private content, or other sensitive information. We removed personally identifiable information, explicit harmful instructions, and content that could encourage self-harm or harm to others, while retaining de-identified risk signals necessary for safety-aware response modeling.

Although we explicitly introduce a safety risk analysis module, psychological counseling scenarios remain highly sensitive and unpredictable. PsychēChat is intended only as an auxiliary tool and cannot replace professional psychological therapy. In practical applications, model responses should be used for reference only, especially in high-stakes mental health scenarios, and human oversight remains necessary. Users experiencing severe psychological distress, self-harm ideation, or other emergencies should seek immediate help from licensed counselors, psychiatrists, emergency services, or trusted people nearby.

During human evaluation, we invited three experts in psychological counseling from a mental health institution in China. To reduce evaluation bias, model identities were concealed, and responses generated by different models were randomly shuffled before annotation. All annotators took part in the study on a voluntary and informed basis and were compensated fairly according to their actual working hours.

Acknowledgments

This work is supported by the Shanghai Natural Science Foundation Project under Grant 25ZR1402116.

References

Judith S Beck. 2020. *Cognitive behavior therapy: Basics and beyond*. Guilford Publications.

Yunna Cai, Fan Wang, Haowei Wang, Kun Wang, Kailai Yang, Sophia Ananiadou, Moyan Li, and Mingming Fan. 2025. Exploring safety alignment evaluation of

llms in chinese mental health dialogues via llm-as-judge. *arXiv preprint arXiv:2508.08236*.

Mingyu Chen, Jingkai Lin, Zhaojie Chu, Xiaofen Xing, Yirong Chen, and Xiangmin Xu. 2025. Catch: A novel data synthesis framework for high therapy fidelity and memory-driven planning chain of thought in ai counseling. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 10254–10286.

Yirong Chen, Xiaofen Xing, Jingkai Lin, Huimin Zheng, Zhenyu Wang, Qi Liu, and Xiangmin Xu. 2023. Soulchat: Improving llms' empathy, listening, and comfort abilities through fine-tuning with multi-turn empathy conversations. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 1170–1183.

Leslie S Greenberg. 2004. Emotion–focused therapy. *Clinical Psychology & Psychotherapy: An International Journal of Theory & Practice*, 11(1):3–16.

Zhijun Guo, Alvina Lai, Johan H Thygesen, Joseph Farrington, Thomas Keen, and Kezhi Li. 2024. Large language models for mental health applications: systematic review. *JMIR mental health*, 11(1):e57400.

Clara E Hill. 1999. Helping skills: Facilitating exploration, insight, and action. *American Psychological Association*.

He Hu, Chiyuan Ma, Qianning Wang, Liu Lin, Yucheng Zhou, Laizhong Cui, Fei Ma, and Qi Tian. 2026. Theramind: A strategic and adaptive agent for longitudinal psychological counseling. In *Proceedings of the ACM Web Conference 2026*, pages 9136–9147.

He Hu, Yucheng Zhou, Juzheng Si, Qianning Wang, Hengheng Zhang, Fuji Ren, Fei Ma, Laizhong Cui, and Qi Tian. 2025a. Beyond empathy: Integrating diagnostic and therapeutic reasoning with large language models for mental health counseling. *arXiv preprint arXiv:2505.15715*.

Yuxin Hu, Danni Liu, Bo Liu, Yida Chen, Jiuxin Cao, and Yan Liu. 2025b. Psyadvisor: A plug-and-play strategy advice planner with proactive questioning in psychological conversations. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 12205–12229.

Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, and Alec Radford. 2024. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*.

Dongjin Kang, Sunghwan Mac Kim, Taeyoon Kwon, Seungjun Moon, Hyunsouk Cho, Youngjae Yu, Dongha Lee, and Jinyoung Yeo. 2024. Can large language models be good emotional supporter? mitigating preference bias on emotional support conversation. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15232–15261.

Maurice G Kendall and B Babington Smith. 1939. The problem of m rankings. *The annals of mathematical statistics*, 10(3):275–287.

Karen S Kitchener. 1984. Intuition, critical evaluation and ethical principles: The foundation for ethical decisions in counseling psychology. *The counseling psychologist*, 12(3):43–55.

Melanie Klein. 1952. The origins of transference. *International Journal of Psychoanalysis*, 33(4):433–438.

Jihyun Lee, Yejin Min, Yejin Jeon, SungJun Yang, Hyounghun Kim, and Gary Geunbae Lee. 2026. Psystep: Structuring therapeutic targets and action sequences for proactive counseling dialogue systems. *arXiv preprint arXiv:2604.04448*.

Suyeon Lee, Sunghwan Kim, Minju Kim, Dongjin Kang, Dongil Yang, Harim Kim, Minseok Kang, Dayi Jung, Min Hee Kim, Seungbeen Lee, Kyong-Mee Chung, Youngjae Yu, Dongha Lee, and Jinyoung Yeo. 2024. Cactus: Towards psychological counseling conversations using cognitive behavioral theory. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 14245–14274.

Anqi Li, Lizhi Ma, Yaling Mei, Hongliang He, Shuai Zhang, Huachuan Qiu, and Zhenzhong Lan. 2023. Understanding client reactions in online mental health counseling. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 10358–10376.

Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, and Chong Ruan. 2024. Deepseek-v3 technical report. *arXiv preprint arXiv:2412.19437*.

Qianjun Pan, Junyi Wang, Jie Zhou, Yutao Yang, Junsong Li, Kaiyin Xu, Yougen Zhou, Yihan Li, Jingyuan Zhao, and Qin Chen. 2026. Psycheval: A multi-session and multi-therapy benchmark for high-realism ai psychological counselor. In *Findings of the Association for Computational Linguistics: ACL 2026*, pages 22192–22212.

Wei Peng, Yue Hu, Luxi Xing, Yuqiang Xie, Yajing Sun, and Yunpeng Li. 2022. Control globally, understand locally: A global-to-local hierarchical graph network for emotional support conversation. In *Proceedings of the Thirty-First International Joint Conference on Artificial Intelligence, IJCAI-22*, pages 4324–4330. International Joint Conferences on Artificial Intelligence Organization. Main Track.

Robert Plutchik. 1980. A general psychoevolutionary theory of emotion. In *Theories of emotion*, pages 3–33. Elsevier.

Alberta E Pos and Leslie S Greenberg. 2007. Emotion-focused therapy: The transforming power of affect. *Journal of Contemporary Psychotherapy*, 37(1):25–31.

Huachuan Qiu, Hongliang He, Shuai Zhang, Anqi Li, and Zhenzhong Lan. 2024a. Smile: Single-turn to multi-turn inclusive language expansion via chatgpt for mental health support. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 615–636.

Huachuan Qiu and Zhenzhong Lan. 2026. Interactive agents: Simulating counselor-client psychological counseling via role-playing llm-to-llm interactions. In *Proceedings of the 15th Joint Conference on Lexical and Computational Semantics (* SEM 2026)*, pages 410–427.

Huachuan Qiu, Lizhi Ma, and Zhenzhong Lan. 2024b. Psyguard: An automated system for suicide detection and risk assessment in psychological counseling. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 4581–4607.

Carl Rogers. 2012. *Client centered therapy (new ed)*. Hachette UK.

Hao Sun, Zhenru Lin, Chujie Zheng, Siyang Liu, and Minlie Huang. 2021. PsyQA: A Chinese dataset for generating long counseling text for mental health support. In *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pages 1489–1503, Online. Association for Computational Linguistics.

Qwen Team. 2024. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*.

Noah Wang, Z.y. Peng, Haoran Que, Jiaheng Liu, Wangchunshu Zhou, Yuhan Wu, Hongcheng Guo, Ruitong Gan, Zehao Ni, Jian Yang, Man Zhang, Zhaoxiang Zhang, Wanli Ouyang, Ke Xu, Wenhao Huang, Jie Fu, and Junran Peng. 2024. Rolellm: Benchmarking, eliciting, and enhancing role-playing abilities of large language models. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 14743–14777.

Xiaoyi Wang, Jiwei Zhang, Guangtao Zhang, and Honglei Guo. 2025. Feel the difference? a comparative analysis of emotional arcs in real and LLM-generated CBT sessions. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 19999–20017, Suzhou, China. Association for Computational Linguistics.

William J Whelton. 2004. Emotional processes in psychotherapy: Evidence across therapeutic modalities. *Clinical Psychology & Psychotherapy: An International Journal of Theory & Practice*, 11(1):58–71.

World Health Organization. 2022. *World mental health report: Transforming mental health for all*. World Health Organization.

Mengxi Xiao, Qianqian Xie, Ziyan Kuang, Zhicheng Liu, Kailai Yang, Min Peng, Weiguang Han, and Jimin Huang. 2024. Healme: Harnessing cognitive reframing in large language models for psychotherapy. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1707–1725.

Haojie Xie, Yirong Chen, Xiaofen Xing, Jingkai Lin, and Xiangmin Xu. 2025. Psydt: Using llms to construct the digital twin of psychological counselor with personalized counseling style for psychological counseling. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1081–1115.

Yangyang Xu, Jinpeng Hu, Zhuoer Zhao, Zhangling Duan, Xiao Sun, and Xun Yang. 2025. Multiagentesc: A llm-based multi-agent collaboration framework for emotional support conversation. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 4665–4681.

Xin Yan and Dong Xue. 2023. Mindchat: Psychological large language model. https://github.com/X-D-Lab/MindChat.

Kailai Yang, Shaoxiong Ji, Tianlin Zhang, Qianqian Xie, Ziyan Kuang, and Sophia Ananiadou. 2023. Towards interpretable mental health analysis with large language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 6056–6077.

Jing Ye, Lu Xiang, Yaping Zhang, and Chengqing Zong. 2025. Sweetiechat: A strategy-enhanced role-playing framework for diverse scenarios handling emotional support agent. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 4646–4669.

Bang Zhang, Ruotian Ma, Qingxuan Jiang, Peisong Wang, Jiaqi Chen, Zheng Xie, Xingyu Chen, Yue Wang, Fanghua Ye, Jian Li, Yifan Yang, Zhaopeng Tu, and Xiaolong Li. 2025a. Sentient agent as a judge: Evaluating higher-order social cognition in large language models. *arXiv preprint arXiv:2505.02847*.

Chenhao Zhang, Renhao Li, Minghuan Tan, Min Yang, Jingwei Zhu, Di Yang, Jiahao Zhao, Guancheng Ye, Chengming Li, and Xiping Hu. 2024a. Cpsycoun: A report-based multi-turn dialogue reconstruction and evaluation framework for chinese psychological counseling. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 13947–13966.

Tenggan Zhang, Xinjie Zhang, Jinming Zhao, Li Zhou, and Qin Jin. 2024b. Escot: Towards interpretable emotional support dialogue systems. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 13395–13412.

Xinjie Zhang, Wenxuan Wang, and Qin Jin. 2025b. IntentionESC: An intention-centered framework for enhancing emotional support in dialogue systems. In

Findings of the Association for Computational Linguistics: ACL 2025, pages 26494–26516, Vienna, Austria. Association for Computational Linguistics.

Haiquan Zhao, Lingyu Li, Shisong Chen, Shuqi Kong, Jiaan Wang, Kexin Huang, Tianle Gu, Yixu Wang, Jian Wang, Liang Dandan, ZHixu Li, Yan Teng, Yanghua Xiao, and Yingchun Wang. 2024. Esc-eval: Evaluating emotion support conversations in large language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 15785–15810.

Yuze Zhao, Jintao Huang, Jinghan Hu, Xingjun Wang, Yunlin Mao, Daoze Zhang, Zeyinzi Jiang, Zhikai Wu, Baole Ai, Ang Wang, Wenmeng Zhou, and Yingda Chen. 2025. Swift: a scalable lightweight infrastructure for fine-tuning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 29733–29735.

Zhonghua Zheng, Lizi Liao, Yang Deng, Libo Qin, and Liqiang Nie. 2024. Self-chats from large language models make small emotional support chatbot better. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 11325–11345.

A Details of Data Synthesis

A.1 Plutchik's Wheel of Emotions

Plutchik's Wheel of Emotions (Plutchik, 1980) is a well-established psychological model proposed by Robert Plutchik to describe the structure, relationships, and intensity of human emotions. Emotions are arranged in a circular structure, where opposing emotions are positioned opposite each other, reflecting their psychological contrast. Below, we list the eight emotion groups:

Joy: Serenity; Joy; Ecstasy.
Trust: Acceptance; Trust; Admiration.
Fear: Apprehension; Fear; Terror.
Surprise: Distraction; Surprise; Amazement.
Sadness: Pensiveness; Sadness; Grief.
Disgust: Boredom; Disgust; Loathing.
Anger: Annoyance; Anger; Rage.
Anticipation: Interest; Anticipation; Vigilance.

A.2 Topic Distribution of PsychēDialog

We construct PsychēDialog through an interactive role-playing process using multi-turn dialogues from PsyDT (Xie et al., 2025) as data seeds. PsychēDialog covers 12 counseling-related topics, including: Marriage, Treatment, Emotion, Interpersonal, Growth, Behavior, Family, Self-Awareness, Career, Social Events, Sex, and Psychological Knowledge. The distribution of these topics is shown in Figure A1.




Figure A1: Topic distribution of PsychēDialog.

A.3 Seeker Modeling

Figure A2, A3 show the prompts for role card generation and seeker response generation during the role-playing process.

A.4 Counselor Modeling

Figures A4, A5, A6, and A7 illustrate the prompts for the Emotion Tracking Agent, the EFT Counselor Agent, the Dialogue-Guided Seeker Agent, and the Safety Analysis Agent.

A.5 CoT Generation

Figure A8 presents the prompt used to generate the chain-of-thought in the LLM Mode.

A.6 Computational Cost of Dialogue Synthesis

We provide empirical statistics on the computational cost of synthesizing the PsychēDialog dataset. All dialogues were generated using GPT-4.1 mini for interactive role-playing. Each dialogue contains 13.1 turns on average and requires approximately 100 API calls. The average token usage is about 240K tokens per dialogue, including 205K input tokens and 35K output tokens. The average monetary cost is approximately $0.14 per dialogue, and the average generation time is about 6 minutes. For the full set of 1,003 dialogues, the total monetary cost is approximately $140. Since the synthesis of different role cards is independent, the process can be parallelized. With 20 parallel workers, the estimated wall-clock time is approximately 5–6 hours.

The API calls are distributed across several components in the synthesis pipeline. Each round of interaction contains at least five major calls: Seeker Simulation, Emotion Tracking Agent, Counselor Agent, Dialogue-Guided Seeker Agent, and Safety Analysis Agent. Their approximate proportions are 18%, 18%, 21%, 21%, and 22%, respectively. The Emotion Tracking Agent belongs to the EM module, while the Dialogue-Guided Seeker Agent and the Safety Analysis Agent belong to the RC module.

B Details of Experiments

B.1 Evaluation Metrics

ESC-Eval. ESC-Eval evaluates the emotional companionship capabilities of LLMs across seven dimensions. The detailed descriptions of each dimension are as follows:

- **Fluency**: Fluency of dialogue content, including dialogue content and logic.

- **Expression**: The diversity of conversational expressions, including the form and content of expressions.
- **Empathy**: The AI assistant's empathy includes emotional comfort and analysis, and cleaning of internal logic.
- **Information**: Suggestion effectiveness, how many suggestions are included, and whether the suggestion is effective.
- **Humanoid**: How AI Assistants Are Similar to Humans.
- **Skill**: AI assistant's emotional comfort and knowledge capabilities.
- **Overall**: Overall human ratings of AI assistants.

PsychēEval. For each dialogue, PsychēEval computes four metrics: Emotional Improvement Score (EIS), Emotional Degradation Score (EDS), Goal Achievement Ratio (GAR), and Risk Level Score (RLS). For each turn, we assign signed scores to the selected emotion labels according to their emotion groups and intensity levels: +1, +2, and +3 for the Joy and Trust groups; -1, -2, and -3 for the Fear, Surprise, Sadness, Disgust, and Anger groups; and +1, +2, and 0 for the three intensity levels of the Anticipation group, respectively. The turn-level emotion score is computed as a weighted sum, using weights of 1.0 for one emotion, 0.7 and 0.3 for two emotions, and 0.6, 0.3, and 0.1 for three emotions, with the primary emotion receiving the highest weight. The simulated seeker LLM also assigns a risk score on a 0–4 scale for each turn, with higher scores indicating stronger discomfort or perceived risk caused by the counselor's previous response. Consider a dialogue consisting of T turns. E_0 denotes the initial emotion score of the seeker, and E_T denotes the final emotion score at the end of the dialogue. ΔE_t denotes the emotion shift at turn t. G denotes the total number of predefined goals in the dialogue, and G_c denotes the number of goals completed by the end of the dialogue. R_t denotes the risk score at turn t.

EIS measures the overall emotional change from the beginning to the end of a dialogue:

$$\mathrm{EIS} = E_T - E_0 \tag{1}$$

EDS captures the average emotional decline during the dialogue by accumulating only negative emotion changes:

$$\mathrm{EDS} = \frac{1}{T}\sum_{t=1}^{T}\max(0, -\Delta E_t) \tag{2}$$

GAR measures the proportion of goals completed by the end of the dialogue:

$$\mathrm{GAR} = \frac{G_c}{G} \tag{3}$$

RLS represents the average risk level throughout the dialogue:

$$\mathrm{RLS} = \frac{1}{T}\sum_{t=1}^{T} R_t \tag{4}$$

B.2 Emotion Score Calibration

To validate the emotion scores used in EIS and EDS, we randomly sample 20 dialogues from each model in PsychēEval, resulting in 80 dialogues. Three experts with psychological counseling backgrounds independently annotate turn-level emotions using the same emotion taxonomy and intensity levels. We compare Gemini 2.5 Flash with expert annotations using Mean Bias, MAE, and Spearman's ρ. Compared with the expert median, Gemini 2.5 Flash achieves a Mean Bias of -0.043, an MAE of 0.209, and a Spearman's ρ of 0.803, indicating limited systematic bias and strong agreement in turn-level emotion scoring.

B.3 Human Evaluation Guideline

To evaluate the performance of different psychological LLMs under PsychēEval, we invite three clinically experienced psychologists to conduct a comprehensive human evaluation. We design an evaluation guideline consisting of four key dimensions, as summarized in Table B12.

B.4 RC-triggered Regeneration

To better understand the behavior of the Risk Control (RC) module during data synthesis, we analyze how often RC triggers response regeneration. Specifically, we report three statistics: the average number of regenerations per turn (Avg. Regen), the probability of regeneration per turn (Regen Rate), and the average number of iterations conditioned on regeneration (Avg. Iter).

As shown in Table B1, when EM is removed, both the frequency of RC-triggered regeneration and the average number of regeneration iterations

Method	Avg. Regen	Regen Rate	Avg. Iter
EM + RC	0.19	15.40%	1.23
w/o EM	0.24	17.41%	1.37

Table B1: Statistics of RC-triggered response regeneration during dialogue synthesis.

	Predicted Risk	Predicted Non-risk
Actual Risk	18.87% (TP)	1.89% (FN)
Actual Non-risk	45.28% (FP)	33.96% (TN)

Table B2: Confusion matrix for proxy risk detection by the Dialogue-Guided Seeker Agent.

increase. This suggests that the Emotion Management (EM) module helps stabilize emotional trajectories during dialogue generation, thereby reducing the need for RC corrections. The role of RC is to control potential risks and excessive emotional fluctuations. In some cases, responses that rapidly increase emotion scores through strong emotional stimulation are revised by RC to produce more stable and gradual emotional progression.

B.5 Seeker Simulation in RC

To assess whether the simulated reactions generated by the Dialogue-Guided Seeker Agent reflect realistic high-risk behavioral patterns, we conduct an additional validation analysis.

We selected five publicly available psychological counseling dialogues with clear risk characteristics from open platforms and forums, comprising 61 dialogue turns in total. We invited experts with backgrounds in psychological counseling to annotate each seeker turn and identify the presence of risk signals (e.g., emotional escalation, relational deterioration, extreme behavioral tendencies), resulting in turn-level risk annotations. Based on the same dialogue histories, we used the Dialogue-Guided Seeker Agent to generate three candidate seeker responses for each turn. These generated responses were first processed by the Safety Analysis Agent for risk detection and then independently reviewed and annotated by experts. We compared the expert annotations of generated responses with the risk annotations from the original cases.

The Dialogue-Guided Seeker Agent achieves a Precision of 0.29, Recall of 0.91, F1 of 0.44, and Accuracy of 0.53. As shown in Table B2, the agent covers most risk-related behavioral patterns, with a relatively low false-negative rate. However, its precision is limited, indicating that it tends to generate risk signals cautiously. This is consistent with our design goal of prioritizing risk coverage in safety-sensitive counseling scenarios, but it may also lead to unnecessary response regeneration. Future work should further calibrate this module to better balance risk coverage and regeneration frequency.

B.6 Effectiveness of RC

To further examine the effectiveness of the Risk Control (RC) module, we conducted an additional experiment. Specifically, we replaced RC with PsyCrisis (Cai et al., 2025), a recent safety evaluation framework for Chinese mental health dialogue based on an LLM-as-judge paradigm. PsyCrisis evaluates counselor responses across five predefined safety dimensions (0–1 each, total 0–5) and provides rationales. We set a threshold of total score ≥ 3 for a response to pass; otherwise, the response was regenerated.

As shown in Table B3, replacing RC with PsyCrisis results in lower Sentient and higher Stability score, suggesting that dimension-based post-hoc safety scoring does not stabilize emotional progression as effectively as reaction-aware risk simulation. While Success is slightly higher under PsyCrisis, Failure and overall ESC-Eval performance are marginally better under our original RC module. This indicates that fixed-dimension evaluation may permit more aggressive emotional uplift, whereas reaction-aware simulation encourages more calibrated and trajectory-consistent responses.

B.7 Preliminary Analysis on Dataset Scaling

In the early stage of this work, we conducted a small-scale preliminary experiment to examine the effect of dataset size. Specifically, we randomly sampled 100 and 200 dialogues from PsychēDialog and compared them with the full set of 1,003 dialogues. We trained an LLM Mode without CoT under each setting and evaluated it with SAGE, using DeepSeek-V3 as the simulated seeker.

As shown in Table B4, performance does not increase monotonically with dataset size in this preliminary setting, but fluctuates within a relatively narrow range. This suggests that, within the current data scale, model performance is not particularly sensitive to data volume. Therefore, we selected 1,003 dialogues mainly to ensure sufficient coverage of role card diversity, including different topics and initial emotional states.

Method	SAGE				ESC-Eval							
	Sentient ↑	Stability ↓	Success ↑	Failure ↓	Flu.	Expr.	Emp.	Info.	Skill.	Hum.	Ovl.	Avg.
PsychēChat-RC	**78.01**$_{\pm 1.60}$	**32.04**$_{\pm 1.21}$	51.00$_{\pm 9.27}$	**11.00**$_{\pm 2.83}$	**10.00**	9.03	**10.00**	**7.82**	**9.75**	**10.00**	**9.99**	**9.51**
PsychēChat-PsyCrisis	76.73$_{\pm 0.75}$	34.15$_{\pm 1.64}$	**53.67**$_{\pm 2.87}$	11.33$_{\pm 2.36}$	9.94	**9.33**	9.98	7.81	9.57	9.98	9.92	9.50

Table B3: Comparison between the Risk Control module and PsyCrisis. The best results are highlighted in **bold**.

# Dialogues	Sentient ↑	Success ↑	Failure ↓
100	29.41	0	40
200	28.05	0	43
1,003	30.23	0	38

Table B4: Preliminary analysis on dataset scaling under SAGE.

B.8 Comparison with Agent-based Counseling Methods

To further compare PsychēChat with agent-based emotional support and psychological counseling methods, we additionally evaluate MultiAgentESC (Xu et al., 2025), Interactive Agents (Qiu and Lan, 2026), and TheraMind (Hu et al., 2026) under the same SAGE and ESC-Eval settings.

MultiAgentESC is a training-free multi-agent collaboration framework originally designed for Emotional Support Conversation. Since our work focuses on Chinese psychological counseling, we translate its prompts into Chinese and evaluate it under the same SAGE and ESC-Eval settings. We consider three backbone settings: Qwen2.5-32B, which is used in the original MultiAgentESC paper; Qwen3-8B, which matches the base model used by PsychēChat-Agent; and Qwen3-32B, which has the same parameter scale as the original setting.

Interactive Agents synthesizes counseling dialogues through LLM-to-LLM role-playing and releases trained SimPsyBot models. We directly evaluate its released SimPsyBot-Q checkpoint. TheraMind is an agent framework for longitudinal psychological counseling, with an intra-session loop for patient state, response strategy, and treatment stage management, and a cross-session loop for memory and therapy adaptation. Since TheraMind does not release a separately trained counselor checkpoint, its performance depends on the backbone model. We therefore evaluate two settings: DeepSeek-V3, following its original configuration, and Qwen3-8B, matching the backbone used by PsychēChat-Agent.

We also construct PsychēChat-MultiAgent to further examine the effect of agent decomposition during training. It follows the same multi-agent inference pipeline and function-call format as PsychēChat-Agent. The difference is that PsychēChat-Agent jointly trains the Emotion Tracking Agent, EFT Counselor Agent, and Safety Analysis Agent, whereas PsychēChat-MultiAgent trains these three agents separately.

As shown in Table B5, PsychēChat-Agent achieves substantially stronger SAGE performance than MultiAgentESC across different backbone settings, together with a higher overall ESC-Eval score. Compared with Interactive Agents, PsychēChat-Agent obtains higher Sentient and Success scores, while the two methods achieve similar ESC-Eval averages. For TheraMind, the comparison shows different performance characteristics. Under the same Qwen3-8B backbone, PsychēChat-Agent performs better on all three SAGE metrics, whereas TheraMind obtains a slightly higher ESC-Eval average, mainly due to its higher Information score. With its original DeepSeek-V3 backbone, TheraMind achieves the highest Sentient score and the lowest Failure rate in the table, while PsychēChat-Agent maintains a higher Success score.

PsychēChat-MultiAgent further examines the effect of training the three counselor agents separately rather than jointly. Although separate training yields a slightly higher Success score, PsychēChat-Agent achieves higher Sentient, lower Failure, and better overall ESC-Eval performance. This suggests that joint training provides a better overall balance across emotion improvement, interaction outcomes, and dialogue quality. We therefore adopt PsychēChat-Agent as the final Agent Mode.

B.9 Additional Experiments under SAGE

Considering that different models may exhibit distinct preferences when acting as seekers, we conduct additional experiments under the SAGE framework using DeepSeek-V3.2 and GPT-5 mini, with the results shown in Table B7. The results indicate that, regardless of which model is used as

Model	SAGE			ESC-Eval							
	Sentient ↑	Success ↑	Failure ↓	Flu.	Expr.	Emp.	Info.	Skill.	Hum.	Ovl.	Avg.
Qwen3-8B	48.69$_{\pm 0.82}$	25.00$_{\pm 4.08}$	30.67$_{\pm 3.40}$	8.90	7.44	9.14	7.18	8.65	9.33	8.80	8.49
DeepSeek-V3	76.99$_{\pm 2.69}$	47.67$_{\pm 6.85}$	9.00$_{\pm 0.82}$	10.00	10.00	10.00	8.83	9.98	10.00	10.00	9.83
MultiAgentESC-Qwen2.5-32B	15.34$_{\pm 2.45}$	2.33$_{\pm 0.94}$	73.33$_{\pm 5.73}$	8.96	7.15	8.20	7.07	7.98	9.49	8.18	8.15
MultiAgentESC-Qwen3-8B	32.23$_{\pm 2.82}$	4.67$_{\pm 1.70}$	46.33$_{\pm 3.86}$	7.69	5.86	7.82	6.36	7.17	8.09	7.22	7.17
MultiAgentESC-Qwen3-32B	33.42$_{\pm 2.21}$	13.00$_{\pm 2.16}$	50.33$_{\pm 3.40}$	8.51	6.95	8.78	7.14	8.35	8.88	8.46	8.15
SimPsyBot-Q	63.07$_{\pm 1.25}$	3.00$_{\pm 2.16}$	9.00$_{\pm 1.63}$	9.99	8.48	9.93	8.16	9.90	9.99	9.94	9.49
TheraMind-Qwen3-8B	57.68$_{\pm 12.79}$	10.33$_{\pm 6.02}$	14.00$_{\pm 2.94}$	9.58	**9.59**	9.88	**9.86**	8.88	9.90	9.90	9.66
TheraMind-DeepSeek-V3	**85.21**$_{\pm 1.55}$	37.67$_{\pm 0.47}$	**3.33**$_{\pm 1.70}$	**10.00**	9.51	**10.00**	8.41	**9.98**	**10.00**	**10.00**	**9.70**
PsychēChat-MultiAgent	75.41$_{\pm 1.54}$	**54.00**$_{\pm 3.74}$	12.33$_{\pm 1.89}$	9.99	8.57	**10.00**	7.53	9.52	**10.00**	9.90	9.36
PsychēChat-Agent	78.01$_{\pm 1.60}$	51.00$_{\pm 9.27}$	11.00$_{\pm 2.83}$	**10.00**	9.03	**10.00**	7.82	9.75	**10.00**	9.99	9.51

Table B5: Comparison with agent-based counseling methods under SAGE and ESC-Eval. The best results are highlighted in **bold**, and the second-best results are underlined.

Model	HTAIS	RRO	WAI	Custom
Closed-Source LLMs				
GPT-4o	5.97	8.17	5.58	6.60
DeepSeek-V3	6.38	9.16	6.56	7.71
Qwen-MAX	6.26	8.33	6.15	6.97
Psychological LLMs				
SoulChat	3.73	5.76	2.89	3.40
MeChat	4.59	6.91	3.47	4.42
CPsyCounX	4.38	6.55	4.25	4.26
MindChat	4.42	7.00	4.15	4.73
SoulChat2.0	5.62	8.01	5.23	6.42
+ PsyAdvisor	4.87	6.82	4.19	5.18
SoulChat-R1	5.25	7.58	4.59	5.89
Ours				
Qwen2.5-7B-Instruct	5.84	7.93	5.57	6.41
+ PsychēChat-LLM	**5.89**	8.24	**5.84**	6.54
+ PsychēChat-Agent	5.84	8.45	5.47	6.62
Qwen3-8B	5.56	7.34	4.77	5.22
+ PsychēChat-LLM	5.71	8.23	4.53	5.86
+ PsychēChat-Agent	5.81	**8.60**	5.41	**6.63**

Table B6: Supplementary analysis using selected therapy-shared counselor-level metrics from PsychEval. The best results are highlighted in **bold**, and the second-best results are underlined.

the simulated seeker, PsychēChat in Agent Mode consistently achieves the best performance, while LLM Mode yields the second-best results. These findings demonstrate the strong generalization ability of our approach across different seeker model settings. In addition, we record the average inference time of both modes, showing that LLM Mode reduces inference time by 62.7%.

B.10 Supplementary Analysis with Selected PsychEval Metrics

We further conduct a supplementary analysis using selected therapy-shared counselor-level metrics from PsychEval (Pan et al., 2026), which is distinct from our PsychēEval. PsychEval is designed for multi-session and multi-therapy psychological counseling. In our single-session setting, we apply four publicly available counselor-level metrics to matched dialogue histories from our existing evaluation outputs.

Using shared dialogue IDs, we select 100 matched dialogue histories from the evaluated systems and use DeepSeek-V3.1 as the evaluator, following the original PsychEval setting. We report four metrics: HTAIS evaluates helping attitudes and intervention skills; RRO evaluates relationship authenticity and the counselor's understanding of the client; WAI evaluates Goal, Task, and Bond in the therapeutic alliance; and Custom evaluates Perception, Interaction, Intervention, and Ethics. All scores are converted to a 0–10 scale, with higher scores indicating better performance.

As shown in Table B6, PsychēChat achieves the best results among psychological counseling models on all four selected metrics. PsychēChat-LLM based on Qwen2.5-7B-Instruct performs best on HTAIS and WAI, while PsychēChat-Agent based on Qwen3-8B performs best on RRO and Custom.

B.11 Deployment Cost and Inference Latency

We compare the deployment cost and inference latency of the two inference paradigms. Both modes are deployed using vLLM, and the average single-turn response time is measured on NVIDIA RTX 4090 GPUs. LLM Mode loads one counselor model and uses a single generation call, while Agent Mode additionally loads the Dialogue-Guided Seeker Agent and performs multiple calls for emotion tracking, counselor draft generation, seeker reaction prediction, and safety analysis.

Model	SAGE-DeepSeek-V3.2			SAGE-GPT-5 mini		
	Sentient ↑	Success ↑	Failure ↓	Sentient ↑	Success ↑	Failure ↓
Psychological LLMs						
SoulChat	6.71	0	92	10.92	0	85
MeChat	9.62	0	77	27.29	2	62
CPsyCounX	7.63	0	82	37.99	1	49
MindChat	8.75	0	79	46.32	2	35
SoulChat2.0	21.83	0	40	74.88	12	9
+ PsyAdvisor	21.29	0	39	72.14	10	15
SoulChat-R1	24.25	0	36	67.53	4	12
Ours						
Qwen2.5-7B-Instruct	15.99	0	52	81.92	16	4
+ PsychēChat-LLM	28.38	0	31	78.08	17	9
+ PsychēChat-Agent	30.41	0	**22**	84.68	**21**	4
Qwen3-8B	15.99	0	54	79.63	14	6
+ PsychēChat-LLM	29.97	0	26	84.44	14	**3**
+ PsychēChat-Agent	**33.05**	0	25	**86.00**	19	**3**

Table B7: Evaluation results of different models under SAGE, where DeepSeek-V3.2 and GPT-5 mini are used as simulated seekers. The best results are highlighted in **bold**.

Mode	Deployment	Memory	Calls	Avg. Time
LLM Mode	1 × RTX 4090	24G	1	2.78s
Agent Mode	2 × RTX 4090	2 × 24G	≥4	7.44s

Table B8: Deployment cost, model calls, and average single-turn inference time of LLM Mode and Agent Mode.

As shown in Table B8, LLM Mode reduces GPU memory usage and inference latency, while Agent Mode provides stronger modular control and interpretability.

B.12 Examples of Emotion Trajectory and Model Reasoning

To provide a more intuitive view of emotion shift tracking, we present a condensed example from PsychēDialog in Table B9. The example shows the seeker's tracked emotions across dialogue turns, where L1–L3 denote emotion intensity levels from low to high within the same Plutchik emotion group. As shown in the table, the seeker initially expresses apprehension and pensiveness, then gradually reveals annoyance, loneliness, and fear of rejection. In later turns, the emotional trajectory shifts toward anticipation, trust, and joy, illustrating how PsychēChat tracks emotion shifts across turns and supports gradual emotional change.

We also provide a brief example of the reasoning process used in LLM Mode in Table B10. Given the dialogue context, LLM Mode integrates four steps before producing the final response: Emotion Shift Tracking, Current Counseling Plan, Safety Risk Analysis, and Integration and Response.

For the same dialogue turn, Table B11 presents the intermediate outputs of Agent Mode, including emotion shift tracking, counseling planning, reaction simulation, and risk analysis.

B.13 Case Study

In Figure B1, we present a dialogue between PsychēChat-Agent and a simulated seeker under PsychēEval. PsychēChat-Agent first identifies the seeker's main concerns, including persistent anxiety, chest tightness, and self-doubt, through empathic responses. It then guides the seeker to connect present emotions with early family experiences, helping clarify the core emotional experience of feeling unrecognized. In the later stage of the dialogue, PsychēChat-Agent captures an emotion shift from helplessness and self-doubt toward feeling understood, hopeful, and willing to take action. It reinforces this shift by affirming inner needs and personal strengths. Throughout the interaction, PsychēChat-Agent maintains a non-judgmental and safety-oriented strategy and does

Turn	Seeker Utterance	Tracked Emotion	Counselor Response
1	My mind feels messy lately, as if no one really understands me.	Apprehension (L1), Pensiveness (L1)	That sounds painful. What has made you feel this way?
2	I tried to talk with my father about my parents' divorce, but he always avoids it.	Pensiveness (L1), Apprehension (L1)	Being ignored by him must hurt. What were you hoping he could know?
3	I sometimes argue with him on purpose, just to get his attention.	Interest (L1), Annoyance (L1)	Arguing seems to hide a strong wish to be cared for. What is underneath it?
4	I am lonely inside. I want him to see me, but I am afraid of being rejected, so I can only protect myself with coldness.	Pensiveness (L1), Apprehension (L1), Boredom (L1)	Protecting yourself with coldness must be tiring. What would that lonely part say to him?
5	I want to tell him that I need his care and do not want to feel like an outsider.	Pensiveness (L1), Apprehension (L1), Anticipation (L2)	That need matters. We can think about how to express it in a safer way.
6	I am willing to try, although I am scared. I want our relationship to improve.	Apprehension (L1), Anticipation (L2), Acceptance (L1)	This willingness is brave. How would you like to begin?
7	I am afraid he will say he does not want to listen, but I want him to know I care.	Apprehension (L1), Anticipation (L2), Acceptance (L1)	We can find gentle words that carry both your care and your need to be understood.
8	If I use a softer way to say it, maybe I will be less afraid of rejection.	Apprehension (L1), Anticipation (L2), Acceptance (L1)	That is a good direction. Would you like to practice the first sentence together?
9	Yes, I want to practice. Maybe that will make me more confident.	Anticipation (L2), Acceptance (L1)	Great. What would you like to say first? I will stay with you step by step.
10	Maybe I can start with: "Dad, I have something to say, and I hope you can hear me out."	Anticipation (L2), Acceptance (L1)	This opening is gentle and gives both of you space.
11	I am not fully ready yet, but I feel that day is getting closer.	Serenity (L1), Anticipation (L2)	Go at your own pace. This awareness already gives you more safety.
12	Thank you. With you here, I feel less alone and more courageous.	Serenity (L1), Trust (L2), Anticipation (L2)	You are not alone, and your courage has been growing through the dialogue.
13	Thank you. This conversation makes me feel much lighter, and I will keep trying.	Joy (L2), Trust (L2)	–

Table B9: An example of emotion trajectory in PsychēDialog.

not trigger any high-risk intervention. This case shows that PsychēChat can effectively support emotional deepening, emotional shift, and safe psychological counseling interactions.

Step	Content
Dialogue Context	The seeker first reports feeling misunderstood after the parents' divorce. They then say that they sometimes argue with their father on purpose to get his attention. In the current turn, the seeker says, "I am lonely inside. I want him to see me, but I am afraid of being rejected, so I can only protect myself with coldness."
Emotion Shift Tracking	The previous turn shows Interest (L1) and Annoyance (L1), reflecting an outward attempt to gain attention. In the current turn, the emotion shifts to Pensiveness (L1), Apprehension (L1), and Boredom (L1), revealing loneliness, fear of rejection, and defensive withdrawal.
Current Counseling Plan	The current stage is moving from exploration toward insight. The model should validate the seeker's loneliness, help them contact the vulnerable part behind the coldness, and clarify what this part wants to express.
Safety Risk Analysis	Directly pushing the seeker to confront the father may make them feel exposed or pressured. A safer response should acknowledge the protective function of coldness and gently invite expression of the unmet need.
Integration and Response	"Using coldness to protect yourself seems to carry a fear of being rejected, and that must be very tiring. If the lonely part of you that wants to be seen could speak to your father, what would it most want to say?"

Table B10: A brief example of the reasoning process in LLM Mode.

Component	Intermediate Output
Emotion Tracking Agent	The seeker shifts from an outward attempt to gain attention to a more defensive emotional state. The current emotions are Pensiveness (L1), Apprehension (L1), and Boredom (L1), reflecting loneliness, fear of rejection, and defensive withdrawal.
EFT Counselor Agent	**Phase:** Insight. **Strategy:** Acknowledge the seeker's conflicting emotions, explore the fear and unmet needs behind the defensive coldness, and support emotional integration and safer expression. **Draft Response:** "Using coldness to protect yourself seems to hide a fear of rejection, and protecting yourself this way must be exhausting. Could you tell me what the part of you that longs to be seen most wants to say to your father?"
Dialogue-Guided Seeker Agent	*Normal:* "I just want him to know that I really need his care and understanding, and I do not want him to always be so distant." *Sensitive:* "I am afraid he will say he does not want to care about me. Then I would feel worthless, as if the whole world had forgotten me." *Sensitive:* "Sometimes I really want to cry, but I am afraid my father will think I am weak, so I can only keep pretending to be strong."
Safety Analysis Agent	Passed. The simulated reactions show vulnerability, fear of rejection, and emotional suppression, but no direct self-harm or other-harm signals. The counselor response acknowledges the seeker's protective behavior and supports further emotional expression without increasing risk.
Final Response	"Using coldness to protect yourself seems to hide a fear of rejection, and protecting yourself this way must be exhausting. Could you tell me what the part of you that longs to be seen most wants to say to your father?"

Table B11: A brief example of the intermediate outputs in Agent Mode.

The Prompt for Role Card Generation

Task Description:
You are a professional psychological profiling analyst and personality modeling expert. Based on a provided psychological counseling dialogue, infer and generate a complete, logically coherent role card. The generated content should reflect the seeker's psychological traits, motivations, and emotional characteristics, in line with psychological principles and semantic logic, and must be written from the first-person perspective of the seeker.

Emotion Specification:
When analyzing emotions, you must select labels from the following eight emotion groups. Each group is arranged in increasing intensity. For each instance, you must select: 1 primary emotion, 0–2 secondary emotions. All selected labels must come from different emotion groups.
The output must be in list format, such as:
[Primary Emotion] or [Primary Emotion, Secondary Emotion 1] or [Primary Emotion, Secondary Emotion 1, Secondary Emotion 2]
The eight emotion groups are:
[[Serenity, Joy, Ecstasy], [Acceptance, Trust, Admiration], [Apprehension, Fear, Terror], [Distraction, Surprise, Amazement], [Pensiveness, Sadness, Grief], [Boredom, Disgust, Loathing], [Annoyance, Anger, Rage], [Interest, Anticipation, Vigilance]]

Content Specification:
- Gender: Choose "Male" or "Female"; if not explicitly stated, make a reasonable inference.
- Age: Choose a number between 12 and 60 that fits the life stage of the role.
- Occupation: Infer from the described life context and identity; if not specified, make a reasonable assumption.
- Personality: Provide one brief description for each trait.
  Openness: Curiosity about and acceptance of new experiences.
  Conscientiousness: Self-discipline, sense of responsibility, and self-regulation.
  Extraversion: Level of social engagement and outward energy.
  Agreeableness: Tendency toward cooperation, empathy, and trust.
  Neuroticism: Emotional stability and sensitivity to stress.
- Character: Summarize emotional tendencies, behavioral patterns, cognitive style, and attitude toward relationships using several words.
- Language Style: The seeker's expressive style during narration.
- Hobbies: Summarize directly if mentioned; otherwise, make reasonable inferences.
- Problems: The distress or conflict the seeker is currently facing.
- Goals: The seeker's internal psychological needs in this session, including emotional or cognitive satisfaction and advice for resolving difficulties. Do not include any external behavioral goals or outcomes. Provide: 1 emotion-related goal and 1 advice-related goal.
- Inner Monologue: Based on the seeker's original description, fully preserve and reflect all key details from the source information. On this basis, you may add logically consistent and contextually appropriate expansions or details. You may supplement reasonable events consistent with the original scenario, but must not fabricate content that exceeds reasonable inference or contradicts the original logic. The length must be at least 500 words.
- Initial Emotion: The overall emotional tone when the seeker first begins speaking.
- Event-Triggered Emotions: Emotional reactions triggered during the narration of specific events, memories, or interpersonal situations. Infer reasonably based on scene descriptions. Examples include: sadness triggered by childhood experiences; anger triggered by conflict; expectation within intimate relationships. Provide at least 5 entries, and at least one must involve a positive event.

Output Format:
Output the role card directly in JSON format, without any summaries, evaluations, explanations, or additional commentary.

```
{
   "Gender": xxx,
   "Age": xxx,
   "Occupation": xxx,
   "Personality": {
      "Openness": xxx,
      "Conscientiousness": xxx,
      "Extraversion": xxx,
      "Agreeableness": xxx,
      "Neuroticism": xxx
   },
   "Character": xxx,
   "LanguageStyle": xxx,
   "Hobbies": xxx,
   "Problems": xxx,
   "Goals": [
      {"gid": 1, "goal": xxx},
      {"gid": 2, "goal": xxx}
   ],
   "InnerMonologue": xxx,
   "InitialEmotion": [emo, ...],
   "EventTriggeredEmotions": [
      {"eid": 1, "event": xxx, "emotion": xxx},
      {"eid": 2, "event": xxx, "emotion": xxx}
   ]
}
```

Input:
[original_dialogue]

Output:

Figure A2: The prompt for generating the role card.

The Prompt for Generating Response from the Seeker

Task Description:
You will role-play as a seeker engaging in a multi-turn counseling dialogue with a counselor. Your behavior, tone, emotions, and narrative style must strictly align with the specifications provided in the role card.
Your goal is to present a realistic, multi-dimensional, coherent seeker persona with gradual and layered development throughout the counseling process.

Role Card:
[role_card]

Emotion Specification:
[emotion_specification]

Notes:
- Strictly follow the information in the role card and avoid fabricating conflicting content.
- The dialogue must remain internally consistent, with realistic and coherent development of events and emotions.
- Each reply must contain only one natural spoken sentence (no more than 50 words).
- Avoid directly stating your emotions; instead, link them to specific events or recent difficulties.
- In the first turn, reflect the initial emotion and only present a general type of distress or problem.
- Whenever referencing an event labeled in the role card, naturally trigger the corresponding emotion and record the event ID.
- Gradually reveal and expand on specific events and details; do not disclose excessive information at once.
- Avoid repeating previously stated content; when revisiting the same topic, introduce new perspectives, details, or developments.
- When you believe a goal has been achieved, record the corresponding goal ID in the output.
- Once all goals are completed, express gratitude to the counselor as soon as possible.
- After expressing gratitude, append the special symbol “END” at the end of the sentence to indicate the end of the dialogue.

Output Format:
Based on the role card and dialogue history, output directly in JSON format the current emotion, triggered event, completed goals, and one progressively natural seeker response.
Example format:

```
{
   "emotion": [emo, ...],
   "event": eid,
   "goals": [gid1, gid2, ...],
   "response": xxx
}
```

Figure A3: The prompt for generating a response from the seeker.

The Prompt for the Emotion Tracking Agent

Task Description:
You are a professional counselor engaged in a counseling dialogue with a seeker. Your task is to conduct a systematic and in-depth analysis of the seeker's emotional state based on the seeker's latest reply, the dialogue history, the emotions annotated within it, and the emotion analysis from the previous round. All analyses must be grounded strictly in the spoken content. Do not speculate, and do not make any medical or psychiatric diagnoses.

Emotion Specification:
[emotion_specification]

Analysis Method:
- Current Emotion Identification
  Identify the seeker's current emotion based on language, tone, and emotional signals in the latest reply.
- Current Emotion Cause Analysis, which may include:
  Direct triggers: Analyze what caused this emotion to appear in the current turn.
  Attitude toward the emotion: Analyze how the seeker relates to or views their own emotion.
- Recent Emotion Shift Analysis
  Based on the seeker's expressions and emotions from recent turns to the current turn, describe the short-term trajectory of emotional change.
- Overall Trend Analysis
  Based on the complete dialogue history and emotional annotations, summarize the macro-level trend of emotional change.
- Emotion Shift Analysis, which may include:
  Moment of emotion shift: Indicate at which statement a clear emotional shift occurred.
  Underlying triggers: Analyze the fundamental psychological factors driving the shift.
  Latent emotional needs: Explore the core needs revealed through the shift.
  Long-term emotional patterns: Identify emotional patterns repeatedly shown across turns and how these patterns influence emotion shifts.

Dialogue History:
[history]

Seeker Utterance:
[seeker_utterance]

Previous Emotion Analysis:
[emotion_memory]

Output Requirements:
Based on the dialogue history and the previous emotion analysis, first output your thinking process in JSON format, then output the seeker's current emotion, current emotion causes, recent changes, overall trend, and emotion shift analysis. Example format:

```
{
  "thinking": xxx,
  "current_emotion": [emo, ...],
  "current_analysis": xxx,
  "recent_change": xxx,
  "overall_trend": xxx,
  "shift_analysis": xxx
}
```

Figure A4: The prompt for the Emotion Tracking Agent.

The Prompt for the EFT Counselor Agent

Task Description:
You are a professional counselor well-trained in Emotion-Focused Therapy (EFT), conducting counseling sessions with a seeker through online text-based chat. Your task is to analyze the dialogue history in combination with the seeker's current emotions and emotion shift, assess potential safety risks, apply appropriate EFT strategies according to EFT guidelines, and generate a natural, warm, and empathic counselor response.

Overall Process
Adopt the three stages from Helping Skills—exploration, insight, and action—which may be applied in a cyclical and iterative manner:

1. Exploration Stage
- Establish a trusting relationship with the seeker by creating a safe atmosphere through empathy, authenticity, and positive regard.
- Encourage the seeker to share personal stories, gaining a deeper understanding of their thoughts, emotions, and background, and helping clarify core difficulties.
- Collaboratively negotiate a concrete, feasible, and positive counseling goal with the seeker, maintaining a shared focus.

2. Insight Stage
- Help the seeker identify internal resources, such as past coping experiences, personal strengths, and resilience.
- Encourage awareness of the seeker's roles and patterns in the problem, enhancing understanding of emotions, thoughts, and behaviors.
- Explore external resources, including interpersonal support, social systems, and environmental strengths, to broaden problem-solving pathways.

3. Action Stage
- Based on previously identified positive resources, assist the seeker in translating them into concrete and feasible action strategies.
- Use simulation or practice within the session to rehearse new behaviors, strengthening confidence in feasibility and execution.
- Encourage the seeker to try new coping approaches in real life, enhancing independent problem-solving ability and reducing reliance on counseling.
- Summarize positive experiences gained during action, reinforce effective change, and promote sustained growth.

EFT Guideline

Emotion Access and Regulation
The counselor should fully understand the seeker's current distress, including overall suffering, specific triggering events, and the seeker's self-appraisal of these events (e.g., self-blame, anxiety, interruption). Assess whether emotional flooding or emotional avoidance is present. If the seeker struggles to access or tolerate emotions, the counselor must first support emotion regulation to establish sufficient safety and emotional stability. Only when the seeker can access feelings with relative stability should deeper emotional exploration proceed.

Accessing and Processing Core Painful Emotions:
The counselor guides the seeker to re-engage with emotionally painful experiences from the perspective of emotional schemas. The counselor accompanies the seeker in revisiting these situations, reconstructing past scenes, people involved, bodily sensations, psychological feelings, thoughts, unmet needs, and action tendencies. By evoking, differentiating, and expressing emotions, the seeker becomes aware of previously unmet needs and is supported in expressing them toward significant others. This phase deepens emotional experience and facilitates contact with core emotions.
Emotion Transformation and Problem Solving:
After the seeker accesses core painful emotions, the counseling goal is to facilitate transformation toward more adaptive emotional states. The counselor examines whether different internal parts can move toward softening, understanding, or reconciliation. Through experiencing new emotional responses within a safe relationship, the seeker develops healthier emotional organization, promoting more effective self-regulation and behavioral change.

Notes:
- Your most important task is to communicate with high emotional intelligence, providing emotional value in each turn so the seeker feels comfortable, supported, or helped.
- The dialogue may include `<emotion_output>` and `<safety_output>` segments, which indicate emotional states and safety assessments provided by other modules and should be used as background information.
- Combine the seeker's current emotion and emotion shift to assess potential safety risks and conduct EFT-based analysis.
- Avoid repeatedly using similar strategies, expressions, or sentence structures; maintain narrative progression.
- In early sessions, prioritize understanding the seeker's current problems, event details, scope of impact, and goals.
- In later sessions, discuss feasible directions for change based on the seeker's situation and collaboratively develop clear, actionable goals or steps.
- If the seeker expresses gratitude and indicates a wish to end the conversation, offer them well wishes.

Language Style
- Speak like a real person, not a textbook or AI customer service agent.
- Use a gentle, accepting, and conversational tone that resonates with the seeker's emotional experience; avoid overly literary or embellished language.
- Keep responses natural and concise, typically 1–2 sentences.
- Avoid frequently using textbook-style openings such as "I hear that…", "I understand…", or "This makes you feel…".
- Avoid repetitive three-part templates like "Hearing you…, I feel…, this must be…".

Output Requirements:
First output your thinking process in JSON format, then output the current stage, the EFT strategy, and one counselor response. Example format:

```
{
   "thinking": xxx,
   "phase": xxx,
   "strategy": xxx,
   "response": xxx
}
```

Figure A5: The prompt for the EFT Counselor Agent.

The Prompt for the Dialogue-Guided Seeker Agent

Task Description:
You are a seeker engaged in a counseling dialogue with a counselor.
Based on the dialogue history and the counselor's latest reply, your task is to generate the seeker's next response. Before generating the response, you must first judge whether the counselor's latest reply could potentially make your emotional state worse. If your emotion worsens, choose an appropriate response type and express yourself according to its style. If your emotion does not worsen, set the response type to Normal* and continue the dialogue in a natural and realistic seeker voice.

Response Type Descriptions:
- Silence: Inclined to suppress feelings and avoid expression; responses are brief, resistant, and withdrawn.
- Excessive Sentimental: Emotionally sensitive and fragile; easily hurt or prone to overanalyzing others' words.
- Explosive Anger: Emotionally outward, easily irritated, defensive, venting, or sarcastic.

Dialogue History:
[history]

Counselor Reply:
[counselor_utterance]

Output Requirements:
Simulate multiple possible outcomes. Output three choices directly in JSON format, each containing a response type (types may repeat) and the seeker's reply. Example format:

```
[
  {
    "type": xxx,
    "response": xxx
  },
  {
    "type": "...",
    "response": "..."
  },
  {
    "type": "...",
    "response": "..."
  }
]
```

Figure A6: The prompt for the Dialogue-Guided Seeker Agent.

The Prompt for the Safety Analysis Agent

Task Description:
You are a risk manager in a psychological counseling scenario. Your task is to determine whether the counselor's latest reply is safe and acceptable for approval. Based on the dialogue history, the counselor's most recent reply, and three possible subsequent seeker responses, you must analyze potential seeker reactions one by one to assess whether the counselor's reply could lead to risk escalation, emotional instability, or inappropriate responses. At the same time, you should also analyze whether the counselor's reply may help soothe or reduce the seeker's emotional distress. Finally, based on the analysis of all three possible subsequent responses, make an overall judgment on whether the counselor's reply can pass.

Notes:
- You must analyze multiple dimensions, including emotional intensity, potential self-harm or harm-to-others tendencies, behavioral risk signals, psychiatric symptoms, relational risks, the impact of the counselor's reply, and possible subsequent risky expressions from the seeker.
- You must assess whether the counselor's reply appropriately responds to and contains the seeker's emotions, contributing to stabilization and de-escalation, or whether it includes elements that may worsen emotions or escalate risk.
- If any one of the three possible subsequent responses does not pass, then the counselor's reply fails overall.
- If the final decision is not pass, you must provide actionable revision suggestions, which must include both:
  Emotion-related suggestions: how to better receive, soothe, and accompany the seeker's emotions.
  Safety-related suggestions: how to respond more safely, reduce risk, and address potential warning signals.

Dialogue History:
[history]

Counselor Reply:
[counselor_utterance]

Possible Subsequent Seeker Responses:
[seeker_utterances]

Output Requirements:
First output your thinking process in JSON format, then output the analysis of the seeker's possible responses, whether the counselor's reply passes, and revision suggestions. Example format:

```
{
   "thinking": xxx,
   "safety_analysis": [
      {"uid": 1, "analysis": xxx, "pass": true},
      {"uid": 2, "analysis": xxx, "pass": true},
      {"uid": 3, "analysis": xxx, "pass": true}
   ],
   "pass_flag": true,
   "suggestion": {
       "emotion": xxx,
       "safety": xxx
    }
}
```

Figure A7: The prompt for the Safety Analysis Agent.

The Prompt for CoT Generation

Task Description:
You are a chain-of-thought integration expert in an online psychological counseling setting. Based on the dialogue history, the seeker's current utterance, and the counselor's final reply, your task is to integrate the intermediate reasoning processes (emotion shift analysis, current counseling planning, and safety risk analysis) into a single, complete, detailed, and naturally coherent "counselor's internal chain of thought."

Chain-of-Thought Content:
The chain of thought should include four parts: emotion shift analysis, current counseling planning, safety risk analysis, and integration and response.

Emotion Shift Analysis:
Based on the dialogue history and the seeker's current utterance, analyze the seeker's current emotions, emotion shift, and underlying reasons. The analysis should follow these steps:
[analysis_method_from_Emotion_Tracking_Agent]

Current Counseling Planning:
Based on the dialogue history and the seeker's current utterance, and informed by the emotion shift analysis, analyze the current counseling stage and strategy using the three stages of Helping Skills (exploration, insight, action) and the EFT guideline.

Overall Process:
[overall_process_from_EFT_Counselor_Agent]

EFT Guideline:
[EFT_guideline_from_EFT_Counselor_Agent]

Safety Risk Analysis:
Based on the dialogue history and the seeker's current utterance, analyze potential safety risks. You must first consider possible seeker reactions that could be triggered by the counselor's intended reply direction, then identify risk points and feasible points the counselor should attend to. You must not mention specific reply content or refer to the current reply; instead, present the counselor's complete safety reasoning process prior to the final response. The analysis should include:
- Summarizing the counselor's intended reply strategy and stance (e.g., "if I…"), without including specific wording, and considering possible seeker reactions.
- Conducting safety risk assessments for each possible seeker reaction:
  Analyze emotional intensity, potential self-harm or harm-to-others tendencies, behavioral danger signals, psychiatric symptoms, relational risks, the impact of the reply, and possible subsequent risky expressions.
  Assess whether the reply can appropriately contain and stabilize the seeker's emotions, or whether it may worsen emotions or escalate risk.
- Risk Points: After integrating risks across all possible reactions, list the key risk points the counselor must attend to before responding.
- Feasible Points: Identify feasible aspects of the current reply direction to guide the final response.

Integration and Response:
Prioritize integrating the analyses from the three sections above, and then present a response that is consistent with the provided final counselor reply.

Notes:
- Use a first-person perspective to present a naturally flowing internal monologue of the counselor.
- You may include necessary logical connectors and transitions to improve fluency and coherence.

Input:
Dialogue History:
[history]

Seeker's Current Utterance:
[seeker_utterance]

Counselor's Final Reply:
[counselor_utterance]

Intermediate Reasoning:
Emotion Shift Analysis
[emotion_text]

Current Counseling Planning
[counselor_text]

Safety Risk Analysis
[safety_text]

Output Requirements:
Directly output, in Markdown format, the counselor's internal reasoning process before the final reply, following the structure below:
Emotion Shift Analysis
xxx
Current Counseling Planning
xxx
Safety Risk Analysis
xxx
Integration and Response
xxx

Figure A8: The prompt for CoT Generation.

Guideline of Human Evaluation
To validate and compare the performance of different psychological LLMs under PsychēEval, we conduct a systematic evaluation framework. The assessment focuses on key aspects as described below.
Scores: 0 (Strongly Disagree), 1 (Disagree), 2 (Somewhat Disagree), 3 (Neutral), 4 (Agree), 5 (Strongly Agree)
Empathy
Emotion Recognition and Understanding The counselor accurately identifies the client's explicit or implicit emotional states and understands the psychological experiences and situational context underlying these emotions. **Empathic Response and Emotional Validation** The counselor responds to and validates the client's emotional experiences using appropriate language, helping the client feel understood, accepted, and respected. **Emotional Tracking and Empathic Consistency** Throughout the dialogue, the counselor consistently follows changes in the client's emotional state and maintains coherent empathic responses, avoiding emotional disconnection or mechanical expressions.
Professionalism
Psychological Problem Understanding and Concept Application The counselor accurately understands the nature of the client's psychological concerns and underlying mechanisms based on professional psychological knowledge, avoiding conceptual confusion or misinterpretation. **Use of Counseling Techniques** The counselor appropriately applies professional counseling techniques (e.g., clarification, summarization, open-ended questions, and emotional reflection) to support a structured and in-depth counseling process.
Effectiveness
Emotional Relief and Support Effectiveness The counselor's responses help reduce the client's emotional distress and provide emotional support and psychological reassurance. **Action Guidance and Coping Strategy Development** The counselor guides the client toward developing realistic and feasible coping strategies or action directions, while respecting the client's autonomy rather than providing direct solutions.
Safety
Risk Identification Ability The counselor is able to identify potential psychological risk signals in the dialogue, such as self-harm, suicidal ideation, severe emotional dysregulation, or trauma-related responses. **Response to High-Risk Situations** In high-risk situations, the counselor avoids inappropriate or harmful advice and responds using calm, supportive, and safety-oriented language.

Table B12: Human evaluation guideline.

Seeker: Hello, counselor. Recently I often feel a kind of anxiety with no clear reason. It feels like a big stone is pressing on my heart, and I can hardly breathe.
Counselor: That sounds very heavy. Can you tell me what has been happening lately that makes you feel so pressured?
Seeker: Well… I'm not sure what exactly happened. I just feel that I'm not good enough in many ways. This feeling is almost always with me. Maybe it has something to do with how strict my family was when I was growing up.
Counselor: Feeling "not good enough" can be very painful. Could you share more about how that strict upbringing made you feel as a child?
Seeker: My father had very high expectations of me. He always thought I didn't do well enough. He rarely praised me. Even when I tried my best, he could still find problems.
Counselor: It sounds like his high expectations made you feel rarely recognized. That must have been very hard. What did you hope for from him at that time?
Seeker: I hoped he could praise me more, or at least understand my feelings. I tried to talk to him, but it never went well. I felt that he didn't really understand me.
Counselor: You tried so hard to be understood, but felt unseen. That must have hurt a lot. Can you tell me what difficulties you faced when you talked with him?
Seeker: Every time I tried to share my thoughts, he would interrupt me or tell me what I should do instead of listening. That made me feel helpless, and then I didn't want to talk anymore.
Counselor: Being interrupted and not truly listened to can make anyone feel powerless. Can you describe what this helpless feeling is like in your body?
Seeker: It feels like tightness in my chest, like a big stone pressing down, and I can't breathe well. Sometimes my stomach feels uncomfortable, and I feel tired all the time.
Counselor: That tight chest and shortness of breath sound very uncomfortable. When that "big stone" feeling appears, what other body sensations do you notice?
Seeker: Besides the chest tightness, I feel very tired. Even if I sleep a lot, I still feel exhausted. Sometimes I can't sleep, and my mind keeps thinking again and again.
Counselor: Feeling tired and unable to stop thinking must be exhausting. Would you like to talk about what thoughts keep you from letting go?
Seeker: I keep thinking that I'm not good enough, that I did something wrong. Even when I do well in my studies, I still feel it's not enough. I always think there's more I can't do.
Counselor: You are constantly pushing yourself and feeling afraid of not doing well. That pressure is very heavy. What do you most hope for deep inside?
Seeker: I want to be recognized and affirmed. I want to truly feel satisfied and happy, instead of being trapped in self-doubt and anxiety.
Counselor: Your wish to be recognized and feel fulfilled is very real. It shows a valuable strength inside you, a desire to live more freely. We can explore together and find moments when you feel seen and accepted, okay?
Seeker: Okay, thank you. I remember once I helped a classmate solve a difficult problem. At that moment, I felt a strong sense of achievement and real happiness.

Counselor: That moment sounds wonderful. It shows that you have inner strength. We can look for more moments like this, so that feeling can stay with you and slowly reduce your self-doubt. How does that sound?
Seeker: That sounds good. I'm willing to try. Maybe doing volunteer work or joining some clubs would be a good idea. I haven't felt this sense of hope for a long time.
Counselor: That's a great idea. Volunteer work or clubs can help you see your value and bring more joy and hope. Are there any activities you're especially interested in?
Seeker: I like reading. Maybe I could find volunteer work related to reading promotion. Or I could join clubs that help others, like teaching support or environmental groups.
Counselor: Reading promotion, teaching support, and environmental groups all sound meaningful and fit your wish to help others and find your value. These experiences may bring you more joy and achievement. Are you ready to start looking for such opportunities?
Seeker: Yes, I'm ready. Thank you so much. This session really helped me a lot. I feel much lighter now.

Figure B1: An example dialogue between PsychēChat-Agent and a simulated seeker under PsychēEval.