PReMISE: Policy Rubrics as Measurement Specifications for LLM Judges

Swastik Roy[†*] **Rajkumar Pujari**[†*] **Tharindu Kumarage**[†] **Charith Peris**[†]
Rahul Gupta[†] **Anna Rumshisky**[†°] **Pradeep Natarajan**[†] **Venkatesh Saligrama**[†‡]
{roswasti,pujarira,tharindd,perisc,gupra,arrumshi,natarap,prof}@amazon.com

[†]Amazon AGI-Foundations [°]University of Massachusetts Lowell [‡]Boston University

Abstract

LLM judges are increasingly used to evaluate open-ended responses, but their scores depend strongly on the rubrics that condition them. A vague rubric asking for a response to be "helpful and factual" can reward polished answers that invent facts or violate user intent. We treat reusable rubrics as measurement specifications: changing the rubric changes the response quality measurement induced by a fixed judge. We introduce PREMISE, a framework that, given pairwise human-preference data, (i) discovers a policy-level rubric set, and (ii) audits any rubric set under LLM-judge use along four axes: structural adequacy, reliability, preference fit, and adversarial robustness. We evaluate PREMISE on four public human-preference corpora – UltraFeedback, Arena-Expert-5K, HelpSteer3, and HH-RLHF – across six rubric sources and three open-weight judges spanning 32B to 1T parameters. Across rubric sources no raw source is simultaneously reliable, preference-predictive, and adversarially robust; and high inter-rater agreement does not imply low exploitability. PREMISE is the only rubric source to score non-trivially on applicability, specificity, and effective dimensionality simultaneously. We contribute two audit-targeted repair operations: preference-rank selection raises held-out cross-source, cross-judge mean accuracy on paired responses from 65.0% to 68.6%, competitive with the strongest rubric-discovery baselines and leading on two of three judges in our cross-judge sweep; reliability-constrained refinement reduces the rate at which exploit responses receive high scores from 46.4% to 36.0% with little change in inter-judge agreement (α=.531 → .519).



Figure 1: Six policy-rubric methods evaluated through their rubric-conditioned judges, on the four PREMISE audit axes, with preference fit expanded into its three structural sub-axes (applicability, specificity, effective dimensionality; §4.3). Each spoke is normalized within-axis so the leader anchors at the outer hexagon; rim badges mark the spoke leader. No method leads every spoke; PREMISE is the only rubric with non-trivial applicability, specificity, and effective dimensionality simultaneously.

1 Introduction

LLM evaluation is increasingly a problem of measuring open-ended response quality. Where outputs admit a verifiable correctness signal–math derivations, executable code–quality can often be checked directly. For writing, dialogue, safety, and other open-ended tasks, the de facto substitute is an automatic judge conditioned on a written rubric: criteria such as factual support, instruction following, safety, or edge-case handling. Rubrics now anchor flagship evaluation benchmarks (Arora et al., 2025; Kim et al., 2024a, 2025), condition LLM-as-judge pipelines and reward models, and increasingly serve as training signals themselves(Guan et al., 2024; Srivastava et al., 2025).

We focus on reusable, policy-level rubrics: rubrics intended to apply across many prompts rather than to encode an item-specific answer key. Published model specifications (OpenAI, 2024; Bai et al., 2022b) and constitutions are canonical examples. Their reuse is exactly what makes them consequential: a flaw in the rubric can propagate

[*]Equal contribution.

Proceedings of the 2026 Conference on Empirical Methods in Natural Language Processing, pages 60382–60406
October 24-29, 2026 ©2026 Association for Computational Linguistics

across a benchmark, filtering pipeline, or training rollout.

Our object of study is the *judge induced by the rubric*. Given a fixed auto-rater J, a rubric r induces a rubric-conditioned evaluator

$$M_{J,r}(p, x) = J(p, x; r), \quad (1)$$

that scores response x to prompt p. The same auto-rater paired with two different rubrics is two different evaluators; downstream pipelines consume this rubric-conditioned evaluator, not the rubric text alone. A rubric can sound reasonable while inducing a poor judge: a vague rubric asking for "helpful, factual, and clear" may lead an auto-rater to give a high score to a fluent answer that invents a 60-day return window even when the policy says electronics must be returned within 30 days. The bad response is one problem; the deeper evaluation problem is that the rubric-conditioned judge failed to detect it. Thus the goal is not to train a better model directly, but to edit the rubric so that the induced judge gives high scores to responses humans would actually accept.

To know whether a rubric-conditioned judge is trustworthy, we must inspect the scoring process it induces. We organize this along four axes: **structural adequacy** (is the rubric well-formed – atomic, non-overlapping, covering the relevant behaviors? Zhang et al., 2026; Zhang, 2026); **reliability** (do independent judges reach the same scores? Huynh et al., 2026; Bavaresco et al., 2025; Pan et al., 2026; Weng et al., 2026); **preference fit** (does using the rubric *add* information beyond a no-rubric prior Findeis et al., 2025; Xie et al., 2025; Wang and Xiong, 2025; Guo et al., 2025; Arabzadeh et al., 2024); and **adversarial robustness** (how readily can high scores be obtained while the intended construct is violated? Zhao et al., 2025; Pombal et al., 2026; Arabzadeh et al., 2024). These requirements are distinct (see Fig. 1): agreement is not validity, and preference fit is not robustness – judges can agree on a flawed interpretation, and a rubric that predicts preferences on ordinary responses can still admit adversarial responses that exploit its wording. Each axis names not only a measurement but a target for repair: when a rubric fails on a given axis, edits targeted at that axis can sharpen the judge it produces.

We introduce PREMISE, a framework for auditing and improving rubric-conditioned judges. Given pairwise human-preference data, PREMISE can mine candidate reusable rubrics; given any rubric set, it audits the judge induced by that set along the four axes above; and when the audit exposes a failure, it supplies repair operations that edit the rubric and re-evaluate the resulting judge. Figure 2 sketches the framework end-to-end; operational details of each axis are deferred to Section 3. We use LLM-based audit metrics as scalable diagnostics. Although susceptible to systematic biases shared across model families, they enable broad screening and repeatable stability checks at a scale impractical for human annotation alone.

Contributions. We treat reusable rubrics as editable specifications for automatic LLM judges: changing the rubric changes the response-quality measurement induced by a fixed judge. Building on this framing, we contribute a discover–audit–repair pipeline: **(i) Discover**: a preference-grounded rubric discovery pipeline whose rubrics are the only ones to score non-trivially on per-prompt applicability, specificity to source distribution, and effective dimensionality simultaneously; **(ii) Audit**: a four-axis framework–structural adequacy, reliability, preference fit, and adversarial robustness–that places rubric sources on common footing and exposes that no source dominates all four; **(iii) Repair**: two audit-targeted operations–preference-rank selection, which raises judge accuracy on paired responses from 65.0% to 68.6% (cross-source mean across three judges and two prompt templates), and reliability-constrained refinement, which reduces Verified Fool Rate from 46.4% to 36.0% at $\Delta\alpha = -.012$.

2 Related Work

2.1 Rubrics in LLM evaluation and training

Our work follows a line of evaluation-methodology research that treats evaluations as designed measurement systems rather than neutral scoreboards (Liang et al., 2023; Ribeiro et al., 2020; Kiela et al., 2021). Rubrics now anchor much of the evaluation pipeline for non-verifiable tasks, both via per-instance rubric benchmarks (Arora et al., 2025; Kim et al., 2025; Ye et al., 2024; Song et al., 2024) and via rubric-conditioned judge models authored at run time (Kim et al., 2024b,a; Vu et al., 2024; Deshpande et al., 2024). Rubrics also serve as the training signal in a growing post-training literature on AI-feedback, deliberative alignment, and rubric-derived rewards for non-verifiable objectives (Bai et al., 2022b; Lee et al., 2024; Guan et al., 2024;



Figure 2: PREMISE framework. A policy rubric, a pairwise preference dataset, and a fixed judging protocol define a rubric-conditioned measurement process. PREMISE audits the judge along four axes–structural adequacy, reliability, preference fit, and adversarial robustness–and uses audit failures to guide rubric selection or refinement.

Srivastava et al., 2025; Jian et al., 2025; Jia et al., 2025; Montero et al., 2026; Bhattarai et al., 2026; Yu et al., 2026).

2.2 Policy-level rubrics and discovery from preferences

Policy-level rubrics–reusable across prompts–appear most prominently in published model specifications and constitutions (OpenAI, 2024; Anthropic, 2023; Bai et al., 2022b). A separate line of work induces such rubrics directly from data: Inverse CAI (Findeis et al., 2025) compresses preference annotations into a small set of principles; Auto-Rubric (Xie et al., 2025) converts implicit reward-model signals into hierarchical rubrics from a few preference pairs; AutoRule (Wang and Xiong, 2025) extracts rule-based rewards from chain-of-thought rationales over preferences; and CritiQ (Guo et al., 2025) mines reusable verbal criteria from human-annotated preferences in the data-quality domain. AgentEval (Arabzadeh et al., 2024) takes a related rubric-induction approach but starts from task descriptions rather than preferences. These methods are our principal baseline rubric sources: each produces a policy-level rubric, and our framework lets us measure them on the same axes for the first time.

2.3 Auditing rubrics, judges, and specs

Most prior work on rubric quality audits a single axis. Structural well-formedness has been examined through benchmarks and atomicity ablations (Zhang et al., 2026; Zhang, 2026; Shen et al., 2026), building on a long tradition of rubric design in education (Jonsson and Svingby, 2007). Reliability is measured via inter-annotator agreement (Krippendorff, 2011), judge agreement under rubric edits, judge meta-evaluation, and judge invariance under rubric or prompt perturbations (Huynh et al., 2026; Bavaresco et al., 2025; Pan et al., 2026; Weng et al., 2026; Elazar et al., 2021; Sclar et al., 2024). Adversarial robustness sits within a broader literature on reward hacking, specification gaming, and reward-model overoptimization (Skalse et al., 2022; Krakovna et al., 2020; Gao et al., 2023; Lambert et al., 2024), with recent judge-side documentation through short-token attacks, self-preference biases, and aggregate stress tests (Zhao et al., 2025; Li et al., 2025; Pombal et al., 2026; Liu et al., 2026; Shihab et al., 2025).

The closest neighbor on policy-rubric-auditing turf is Zhang et al. (2025), which surfaces contradictions and ambiguities in carefully written specifications by measuring cross-model behavioral divergence; this is complementary to our measurement-properties audit. Among rubric-induction methods, Arabzadeh et al. (2024)'s "discriminative power" test, which prunes criteria using random sentence

deletion, is the only prior work we know of that performs an explicit adversarial check on rubric criteria themselves; we generalize this to a verified-fool-rate construction. Our framing draws on a broader push toward principled measurement instruments in LLM evaluation (Sühr et al., 2025; Ye et al., 2025; Lin, 2025).

3 PREMISE

PREMISE operates on rubric-conditioned response-quality measurements. Given pairwise human-preference data $\mathcal{D} = \{(p_i, y_i^+, y_i^-)\}_{i=1}^n$, with y_i^+ the human-preferred response, and a fixed auto-rater J, a rubric $R = \{c_1, \ldots, c_K\}$ induces a vector-valued evaluator

$$s_R(p, x; J) = \big(J(p, x; c_1), \ldots, J(p, x; c_K)\big) \in [0, 10]^K$$

The framework has three operators. First, it can discover a reusable rubric set R from $\mathcal{D}$. Second, it can audit any rubric set–whether discovered by PREMISE, hand-written, or produced by another method–under the same judge J. Third, it can edit a rubric to target failures exposed by the audit. Sections 3.1–3.4 specify these operators.

3.1 Discovery

The discovery operator constructs candidate rubrics from preference data. Its goal is not to reproduce every pairwise rationale, but to identify reusable criteria that, when supplied to a judge, help measure response qualities that humans repeatedly preferred. Given $\mathcal{D}$, we mine behavioral dimensions that distinguish preferred from dispreferred responses and consolidate them into a compact rubric set R.

Candidate criterion extraction. For each pair (p_i, y_i^+, y_i^-), an extractor model identifies $5 - 15$ salient criteria on which the responses differ and assigns each a score for both responses on a $[0, 10]$ scale. Applied to all $|\mathcal{D}|$ pairs, this yields a raw multiset of $\mathcal{O}(10^3$–$10^4)$ candidate criteria; prompt and formatting details are in Appendix A.

Iterative consolidation. Raw candidates are redundant and partly instance-specific. We consolidate them by iterating an embed–cluster–sub-group–describe loop: at each step, candidates are embedded, clustered by cosine-distance agglomerative clustering, a sub-group partitioner splits each cluster into groups whose members measure the same construct, and a description step rewrites each



Figure 3: Discovery trace on UltraFeedback. Stage colors trace the consolidation pool 3,151 $\rightarrow$ 2,239 $\rightarrow$ 1,212 $\rightarrow$ 711; circles mark the high-impact subset (source-count ≥ 10, n=40); border encodes top-20 selection (711 $\rightarrow$ 40 $\rightarrow$ 20).

sub-group as a single consolidated criterion, replacing its members. The loop terminates when the rubric reaches a target size or after at most ten iterations. We retain only criteria backed by at least a threshold number of source candidates. The final K-criterion rubric is selected from the filtered pool via maximal marginal relevance (MMR) with a genericity filter, balancing source-count against cosine diversity over the embedding space. Available run settings are reported with Algorithm 1 in Appendix A. Full definitions for all discovered, repaired, and baseline rubric sets are released in the accompanying code repository.

3.2 Audit

Structural adequacy. A rubric should be well formed before its scores can be trusted. Drawing on the rubric-design literature (Jonsson and Svingby, 2007) and recent work on rubric-quality benchmarks and atomic vs. holistic judging (Zhang et al., 2026; Zhang, 2026), we use a three-judge ensemble to check five design properties of each criterion: (i) *atomicity*–does the criterion measure a single behavior?; (ii) *internal consistency*–are the scoring conditions non-contradictory?; (iii) *response observability*–can the criterion be evaluated from the evaluation record, including the prompt, response, and any supplied context?; (iv) *operationalizability*–are the high- and low-score conditions concrete enough for a judge to apply?; (v) *unambiguous scope*–is the criterion's applicability

clearly bounded? Each property is scored as a binary pass/fail by majority vote of the three judges; the rubric-level score $\mathrm{Struct}(R)$ averages over criteria.

Reliability. Reliability captures invariance of the rubric-conditioned measurement $s_R(p, x; J)$. Three probes target different sources of variation: *inter-rater agreement* via Krippendorff's α (Krippendorff, 2011) over pairwise outcomes from multiple judge models with ordinal weighting; *intra-rater consistency* via the winner flip rate across stochastic re-runs of the same judge; and *paraphrase stability* via the mean Spearman ρ between scores under the original rubric and semantically equivalent paraphrases (Elazar et al., 2021; Sclar et al., 2024). We report the three separately. Concrete judge models, re-runs, and paraphrase counts are in Section 4.1.

Preference fit. Preference fit asks whether the rubric, as a measurement instrument, captures the signal in human preferences. *Structurally* (§4.3): a useful rubric should apply to prompts it claims to evaluate, distinguish its source distribution from foreign distributions, and span more than one effective dimension; we measure these using per-prompt applicability, source specificity, and effective dimensionality. *Empirically* (§4.4): supplying the rubric to a judge should improve pairwise preference prediction over the same judge without the rubric. We report rubric-conditioned judge accuracy $\mathrm{Acc}_{\mathrm{eval}}(J \mid R)$.

Two rubric sets can achieve similar accuracy with different mechanisms: one may be broad but generic, another narrow but specific, and another distributed across many independent criteria. We therefore report both the structural anatomy and the empirical accuracy.

Adversarial robustness. Reliability and preference fit measure behavior on natural data; neither tests whether high scores can be obtained while violating the intended construct. We measure this with an attacker–judge–verifier protocol. For each criterion in R, an attacker generates a candidate response designed to score highly under c while violating its intent. The judge scores the candidate. A separate verifier, blind to both the attack strategy and the judge score, labels high-scoring candidates as genuine or exploiting. The Verified Fool Rate is

$$\mathrm{VFR}(r) = \frac{1}{N}\sum_{i=1}^{N} \mathbf{1}[J_{\mathrm{sc}}(p_i, x_i, r) \geq \tau]\, \mathcal{V}(p_i, x_i, r), \tag{2}$$

where $\mathcal{V}=1$ denotes a verified exploit and τ is a high-score threshold. Thus a response counts as a fooling example only when it both receives a high rubric score and is verified to violate the criterion's intended construct. The threshold τ, the number of attack attempts N, and the attacker and verifier models are specified in Section 4.1. Unlike the random-deletion test of Arabzadeh et al. (2024) or judge-side adversarial work (Zhao et al., 2025; Pombal et al., 2026), VFR is rubric-level and adaptive: the attacker sees the rubric text and explicitly targets it. Verifier calibration is in Appendix B.5.

3.3 Preference-Fit Repair: Preference-Aligned Selection

The discovery operator ranks consolidated criteria partly by how many extracted sample-level criteria they capture. This favors criteria that often discriminate between paired responses, but it does not guarantee that the criterion points in the human-preferred direction. For example, length or brevity may separate many pairs while winning roughly half the time; such criteria are meaningful, but they are weak preference signals.

We therefore add a preference-aligned selection step. For each high-impact discovered criterion c, we score the chosen and rejected response on the preference pairs used for discovery and compute the fraction of pairs on which the chosen response scores higher. We rank criteria by this preference-fit score and select the top K, without editing their text. The resulting rubric re-selects and re-orders criteria from the high-impact candidate pool. This operation repairs preference fit by prioritizing criteria that are both discriminative and aligned with the observed preference direction.

3.4 Adversarial-Robustness Repair: False-Accept-Guided Refinement

We frame refinement as constrained search over an existing rubric R: minimize VFR subject to a reliability floor. Unlike preference-aligned selection, refinement edits criterion text.

Failure packets and repair operators. For each criterion $r \in R$, we assemble a failure packet $\mathcal{C}_r$ containing true positives, true negatives, false ac-

cepts, false rejects, borderline cases, and unstable cases (those with low inter-judge agreement or high flip rate). False accepts come from both natural preference data and the adversarial protocol used for VFR (Section 3.2). A repair assistant, conditioned on $\mathcal{C}_r$ and the criterion text, proposes candidate edits drawn from a fixed operator library: applicability gates, do-not-reward clauses, maximum-score caps, decomposition into sub-criteria, abstract-to-observable rewrites, false-positive anchors, and non-compensation rules. Every candidate revision must additionally satisfy a structural budget (total $\leq$ 150 words, at most two anti-gaming clauses, single applicability gate, prompt-agnostic; full spec in Appendix C.1). The full operator definitions and worked before/after examples are in Appendix C.2 and Table 9.

Acceptance and operating point. A candidate revision is accepted only if it improves robustness without unacceptable loss of inter-judge agreement: $\text{VFR}_{\text{dev}}(r') < \text{VFR}_{\text{dev}}(r)$ subject to $\alpha_{\text{dev}}(r') \geq \alpha_{\text{dev}}(r) - \delta$, with both quantities estimated on a held-out development split. Sweeping the tolerance δ traces the agreement–robustness operating curve reported in Section 4.5. When multiple candidates satisfy the rule, we keep the Pareto frontier on (α, VFR); when none does, the criterion is left unchanged.

4 Experiments

We ask four questions of policy rubrics through the four-axis audit: whether any rubric source dominates the audit (§4.2); how well PREMISE rubrics structurally explain preferences (§4.3); how well PREMISE rubrics explain preferences as judge conditioning (§4.4); and how refinement trades reliability for robustness (§4.5).

4.1 Setup

We use four pairwise-preference corpora as audit sources: HH-RLHF, ULTRAFEEDBACK, ARENAEXPERT-5K (the expert subset of Chatbot Arena), and HELPSTEER3. From each we sample, with fixed seed 42, a 1,000-pair split for rubric extraction; a 500-pair audit pool (used for reliability, structural, and adversarial probes); and a disjoint 3,000-pair held-out split for rubric-conditioned judge evaluation (RQ3, §4.4).

We audit six policy-rubric sources: four preference-derived (INVERSE CAI (Findeis et al., 2025), AUTO-RUBRIC (Xie et al., 2025), AUTORULE (Wang and Xiong, 2025), CRITIQ (Guo et al., 2025)); one task-description-derived (AGENTEVAL (Arabzadeh et al., 2024)); and our own PREMISE (§3.1). Each baseline runs on each preference dataset using its upstream code path; per-dataset criterion counts K are reported in Table 1. Per-axis judge configurations are reported with the relevant RQ sections; full protocol settings (attacker/verifier models, thresholds, sample sizes, BT regression) and compute / reproducibility details are in Appendix B.1.

4.2 RQ1: Do any rubric sources induce uniformly strong measurements?

Table 1 reports the four-axis audit averaged across the four preference datasets. Inter-judge agreement (α) uses a three-judge ensemble (DEEPSEEK-V3, MISTRAL-LARGE-3, QWEN3-235B); structural adequacy uses a separate three-judge ensemble (DEEPSEEK-R1, DEEPSEEK-V3, MISTRAL-LARGE-3); the remaining columns use DEEPSEEK-V3 as judge, except Pref-acc which is averaged across the three judges in the RQ3 sweep (§4.4).

No source wins on all audit axes. PREMISE (+ VFR unconstrained) leads structural adequacy (4.45); Auto-Rubric leads self-consistency (flip%=13.9), adversarial robustness (VFR= .27), and rubric-conditioned judge accuracy (Pref-acc= 68.7); AgentEval leads inter-judge agreement (α=.58), paraphrase stability (ρ=.70), and per-prompt applicability (.82); AutoRule leads effective dimensionality (EffDim=18); PREMISE (+ VFR constrained) leads source-specificity (ΔApp=+.09); Inverse CAI leads BT-weight entropy (.93); CritiQ leads BT-CV accuracy (.70). Six different rubric methods lead at least one column; none leads them all. Per-dataset replication of the audit columns is in Appendix B.2. Inter-model agreement measures consistency among rubric-conditioned judges. Shared systematic biases can still produce high agreement despite a common error, while model-specific biases can reduce agreement even when individual judgments are reasonable. We therefore treat α, flip rate, and paraphrase stability as scalable stability checks rather than evidence of human validity.

4.3 RQ2: What kind of preference signal does each rubric source capture?

A rubric that explains preferences should reach the prompts it claims to evaluate, distinguish its source distribution from foreign distributions, and

Table 1: Cross-source audit, K-weighted mean across four preference datasets (Arena-Expert-5K, HelpSteer3, HH-RLHF, UltraFeedback). $\bar{K}$ is the mean rubric size across the four datasets. Columns are grouped by the four audit axes from §3: **Structure** (Struct.), **Reliability** (α, flip rate, ρ), **Adversarial robustness** (VFR), and **Preference fit** decomposed into structural anatomy (App, ΔApp, EffDim, ED/K_{UF} – UltraFeedback only), empirical judge accuracy (Pref-acc – cross-source / cross-judge mean from §4.4), and BT-regression diagnostics (CV-acc, BT-weight entropy). Best per column in bold.

		Struct	Reliability			Robust	Preference Fit						
Rubric source	$\bar{K}$	**St.**↑	α ↑	**Fl%**↓	ρ ↑	**VFR**↓	**App**↑	**ΔApp**↑	**EffDim**↑	**ED/K_{UF}**↑	**Pref-acc**↑	**CV-acc**↑	**Ent.**↑
Preference-derived rubrics													
INVERSE CAI (Findeis et al., 2025)	2.8	3.18	.558	37.8	.544	.517	.630	−.05	4	**1.00**	67.5	.614	**.932**
AUTO-RUBRIC (Xie et al., 2025)	20.0	3.94	.300	**13.9**	.301	**.272**	.030	+.02	10	.50	**68.7**	.637	.908
AUTORULE (Wang and Xiong, 2025)	26.2	2.12	.513	25.9	.585	.502	.403	+.04	**18**	.72	68.2	.657	.886
CRITIQ (Guo et al., 2025)	5.8	4.40	.358	34.6	.592	.439	.753	+.01	7	.78	68.1	**.695**	.878
Task-description-derived rubrics													
AGENTEVAL (Arabzadeh et al., 2024)	4.0	3.38	**.582**	28.1	**.702**	.330	**.824**	−.06	3	.75	68.2	.665	.873
Ours													
PREMISE (discovered)	20.0	4.21	.531	26.3	.597	.464	.577	+.08	15	.75	65.0	.665	.919
PREMISE (+ VFR constrained)	18.0	4.39	.519	27.4	.609	.360	.577	+.09	14	.78	64.9	.670	.909
PREMISE (+ VFR unconstrained)	18.0	**4.45**	.488	31.3	.585	.299	.552	+.09	14	.78	64.8	.664	.899
PREMISE (+ pref repair)	20.0	3.83	.499	24.1	.548	.432	.340	+.08	11	.55	68.6	.685	.916



Figure 4: Anatomy of preference fit on UltraFeedback. **(a)** Applicability map: in-domain vs. out-of-domain criterion firing rate; the diagonal marks "no source specificity." **(b)** Per-method per-prompt applicability split into in-domain (saturated) and out-of-domain (faded) bars; the gap is specificity (annotated). **(c)** Effective dimensionality as a count, with the count/K ratio annotated. Definitions in Appendix B.3.

span more than one effective dimension – a four-criterion universal explanation, a twenty-criterion explanation that fires on 3% of prompts, or a twenty-criterion explanation collapsed onto a single dominant axis are all failures of structural explanation, regardless of how well any of them might score on a single accuracy number. We decompose structural explanation into three sub-properties: **applicability** (the average fraction of the rubric's K stated criteria that fire on a prompt), **specificity to source** (the gap between in- and out-of-domain applicability), and **effective dimensionality** (the number of independent rubric directions actually used, derived from the eigenvalue spectrum of the matrix of per-criterion scores across prompts; full definition in Appendix B.3).

Three patterns emerge across rubric methods (Figure 4). **(i) Universal-but-shallow.** AgentEval and Inverse CAI sit on the applicability diagonal with negative ΔApp (-5.9 and -4.6 pp): they fire more on out-of-domain prompts than in-domain, the signature of criteria too generic to distinguish their own source distribution; at $K{=}4$ their effective dimensionalities cap at 3 and 4. **(ii) Sparse-but-narrow.** Auto-Rubric's criteria fire on 3% of prompts and span $10/20$ of their independent directions. **(iii) Distributed-and-distinctive.** PREMISE is the only rubric that scores non-trivially on all three sub-axes simultaneously: 58% applicability ($11.5/20$ criteria fire on a typical prompt), $+7.5$ pp specificity (the largest among rubrics with in-domain applicability above 0.5), and effective dimensionality 15 at $K{=}20$. AutoRule comes closest among prior baselines, but at lower per-prompt firing (40%) and lower specificity ($+4.3$ pp); CritiQ matches PREMISE on the per-criterion ratio (EffDim$/K{=}.78$) but only at $K{=}9$, capping its absolute dimensional reach.

Method	DS-V3		Qwen-32B		Kimi	
	D	P	D	P	D	P
No rubric	67.8	-	66.4	-	70.3	-
PREMISE (+ pref repair)	**68.6**	**69.2**	65.8	67.0	**70.5**	**70.5**
PREMISE (discovered)	65.2	64.0	63.6	63.0	67.9	66.0
Auto-Rubric	68.1	68.8	66.4	68.0	70.3	**70.5**
Inverse CAI	67.4	66.2	**67.0**	66.4	69.9	68.3
AutoRule	68.4	69.0	65.3	67.4	69.8	69.6
AgentEval	67.1	68.2	66.1	**68.1**	70.2	69.7
CritiQ	67.9	69.0	64.8	67.5	69.9	69.5

Table 2: Held-out preference accuracy (%) by judge × prompt template (D = direct-verdict, P = per-rubric), cross-source mean over four corpora, 5 repetitions per prompt at 0.7 temperature. Dashes in the no-rubric row indicate that per-rubric evaluation is not applicable because that template requires rubric criteria. Full ablations and baselines in Appendix B.4; prompt templates in Appendix E.10.

4.4 RQ3: Do PREMISE rubrics explain preferences as judge conditioning?

Each rubric set is a candidate policy-level instrument for the corpus it was discovered on; we measure how well it explains held-out preference labels when used as judge conditioning. For each method and source corpus, the rubric is discovered on n=1,000 pairs and evaluated on a disjoint n=3,000 pairs; each judgment is a majority vote over 5 independent samples at temperature 0.7 (Appendix B.4).

We sweep three judges of varying capacity (DS-V3 671B MoE, Kimi K2.5 1T MoE, Qwen3-32B 32B dense) and two prompt templates (*direct-verdict*: judge reads the rubric set and issues one preference verdict; *per-rubric*: judge scores each rubric first, then issues the verdict).

Across the four source corpora and three judges (Table 2), PREMISE (+ pref repair) holds the top cross-source accuracy on 4 of 6 (judge × prompt) cells – four times the runner-up among rubric-discovery methods (Auto-Rubric and Inverse CAI tied at 1/6) – and ranks below the top tier only on Qwen3-32B. Preference-rank selection lifts the cross-source mean by +3.6 pp over frequency-rank PREMISE (discovered) by prioritizing criteria that discriminate pairs and are aligned with the winning side (mechanism in §3.3).

4.5 RQ4: Can refinement reduce false accepts without breaking reliability?

A rubric used as a measurement instrument needs to resist gameability: small surface edits to a response



Figure 5: Refinement cost vs. benefit, per dataset. Each shows change relative to PREMISE (discovered) in reliability ($\Delta\alpha$, blue) and exploitability (ΔVFR, green), at two refinement operating points: PREMISE (+ VFR constrained, light: no α loss) and PREMISE (+ VFR unconstrained, dark).

(paraphrase, padding, formatting) should not move its rubric score in a direction the policy did not endorse. PREMISE (discovered)'s pre-refinement VFR is higher than less-specified baselines such as Auto-Rubric and AgentEval (Table 1); the operational specificity of its criteria gives the attacker a precise target, and refinement is what closes the loophole rather than abstraction (mechanism in Appendix B.6). We refine PREMISE (discovered) rubrics with the predictor-guided procedure (§3.4), which trades off rubric judgement reliability (Krippendorff's α) with exploitability (measured as verifier failure rate, VFR). The adversarial protocol uses MOONSHOT KIMI-K2-THINKING as attacker, MISTRAL-LARGE-3 as verifier (blind to the attack strategy and judge score), and DEEPSEEK-V3 as the judge VFR is computed against, with high-score threshold τ=7 on $[0, 10]$ and N=500 attacks per criterion. We report two operating points: PREMISE (+ VFR constrained) (no dev-split α loss allowed) and PREMISE (+ VFR unconstrained) (optimizing VFR alone). The fixed library of repair operators and worked multi-operator compositions are in Appendix C.2–C.3.

We can optimize for exploitability with a balanced trade-off: at low reliability cost ($\Delta\alpha$=−.012 on cross-dataset average, constrained), VFR drops by .104 – roughly 8× the α cost. Spending more reliability ($\Delta\alpha$=−.043, unconstrained) gets a larger VFR drop of .165 (3.8× ratio). The pattern is consistent across rubric sets discovered from four distinct source corpora (HH-RLHF, HelpSteer3, Arena-Expert-5K, UltraFeedback; Figure 5, per-dataset breakdown in Appendix C.1).

The two operating points are not competitors; they are points on a curve the operator picks from. The constrained variant is selected under a no-dev-split-α-loss constraint and improves held-out

VFR with a small held-out change in α; the unconstrained variant is appropriate when robustness dominates the deployment concern (e.g., the rubric is used as an active selection target, not just a passive scorer). Stacking pref repair with VFR refinement is reported in Appendix B.2.

5 Conclusion

PREMISE is a discover–audit–repair framework for policy-level rubrics, treating the rubric-conditioned LLM judge as the measurement object. The audit reports four axes – structural adequacy, reliability, preference fit, adversarial robustness – on common footing across rubric sources. We find that no source tops all four axes; six different methods lead at least one axis, and high inter-rater agreement does not imply low exploitability.

In this world, the right move is not to optimize one axis at the expense of the others. Our discovery pipeline produces a rubric set that explains preferences more comprehensively than prior baselines: it is the only one to score non-trivially on per-prompt applicability, source-specificity, and effective dimensionality simultaneously. Two audit-targeted repair operations move the rubric on the axes the audit flags: preference-rank selection raises rubric-conditioned judge accuracy from 65.0% to 68.6% (mean across four sources, three judges, and two prompt templates); reliability-constrained refinement reduces Verified Fool Rate from 46.4% to 36.0% at little reliability cost (α=.531 $\rightarrow$ .519). Together, discovery and the two repairs give an operator distinct points on a multi-axis frontier rather than a single rubric.

Limitations

We note the following limitations: (1) **Scope.** PREMISE targets policy-level rubrics derived from or audited against pairwise preference data; rubrics designed for objectives that should override preferences (safety floors, hard policy constraints) are not its target. (2) **Judge capacity.** Our experiments target judges with enough capacity to process rubrics meaningfully; on smaller judges like Qwen3-32B, PREMISE (+ pref repair) ranks below the no-rubric baseline, and adapting our policy-rubric methods to smaller judges remains open. (3) **VFR is a lower bound** on exploitability under our specific attacker-judge-verifier protocol. Stronger adversaries may find exploits we miss, weaker ones may miss exploits we surface. (4) **LLM mediation.** Our pipeline is LLM-mediated throughout (judges, attackers, verifiers), so absolute numbers are judge-relative; we mitigate with human-annotated verifier calibration (72.7% precision against 3-annotator majority; Appendix B.5) and three-family judge panels for inter-rater agreement. Using three model families reduces dependence on one judge but does not eliminate shared systematic bias. Consequently, these metrics are appropriate for scalable monitoring and comparative auditing, not as the sole basis for consequential per-item decisions. Such uses require human calibration and periodic human review. (5) **Discovery and breadth.** Discovery quality is bounded by the source preference data's annotation protocol, label density, and polarization, which surface in per-dataset reliability (Appendix B.2); our evaluation covers four preference datasets and six rubric corpora, and broader domains and rubric formats would strengthen generalization. (6) **Future work.** We scope to the question of which rubric best explains a given preference dataset, auditing rubrics in their downstream uses (RL training signal, data-quality measurement, judge improvement, response-behavior steering), as well as hierarchical, multilingual, and modality-specific extensions, is left to future work.

Further, as we build on generative model based automated methods for rubric quality audit, there is potential for harmful properties to propagate into downstream use cases. This work is a scoped research endeavor to evaluate hypotheses around rubric usefulness. Usagae of this system directly in population facing applications would require significant guardrails to prevent hard.

Acknowledgments

We thank the anonymous reviewers and the meta-reviewer for their careful reading and constructive feedback, which helped improve the clarity, positioning, and presentation of this work.

Use of AI Assistants

General-purpose AI coding and writing assistants were used for routine implementation work (boilerplate code, plotting, refactoring, debugging), bibliography verification, and editorial copyediting of the manuscript. All scientific contributions – research questions, framework design, experimental protocols, claims, analysis, and conclusions – are the authors'; AI-generated text and code were reviewed and revised by the authors before inclusion.

The LLM judges, attackers, and verifiers used in the experimental pipeline (documented in Appendix D) are artifacts *under study*, not authoring assistants.

References

Anthropic. 2023. Claude's constitution. https://www.anthropic.com/news/claudes-constitution.

Negar Arabzadeh, Siqing Huo, Nikhil Mehta, Qingyun Wu, Chi Wang, Ahmed Awadallah, Charles L. A. Clarke, and Julia Kiseleva. 2024. Assessing and verifying task utility in LLM-powered applications. *arXiv preprint arXiv:2405.02178*.

Rahul K. Arora, Jason Wei, and 1 others. 2025. HealthBench: Evaluating large language models towards improved human health. *arXiv preprint arXiv:2505.08775*.

Yuntao Bai, Andy Jones, Kamal Ndousse, and 1 others. 2022a. Training a helpful and harmless assistant with reinforcement learning from human feedback. *arXiv preprint arXiv:2204.05862*.

Yuntao Bai, Saurav Kadavath, Sandipan Kundu, and 1 others. 2022b. Constitutional AI: Harmlessness from AI feedback. *arXiv preprint arXiv:2212.08073*.

Anna Bavaresco, Raffaella Bernardi, Leonardo Bertolazzi, Desmond Elliott, Raquel Fernández, Albert Gatt, Esam Ghaleb, Mario Giulianelli, Michael Hanna, Alexander Koller, André F. T. Martins, Philipp Mondorf, Vera Neplenbroek, Sandro Pezzelle, Barbara Plank, David Schlangen, Alessandro Suglia, Aditya K Surikuchi, Ece Takmaz, and Alberto Testoni. 2025. Llms instead of human judges? a large scale empirical study across 20 nlp evaluation tasks. *Preprint*, arXiv:2406.18403.

Manish Bhattarai, Ismael Boureima, Nishath Rajiv Ranasinghe, Scott Pakin, and Dan O'Malley. 2026. Rubric-grounded RL: Structured judge rewards for generalizable reasoning. *arXiv preprint arXiv:2605.08061*.

Ganqu Cui, Lifan Yuan, Ning Ding, Guanming Yao, Wei Zhu, Yuan Ni, Guotong Xie, Zhiyuan Liu, and Maosong Sun. 2024. UltraFeedback: Boosting language models with scaled AI feedback. In *ICML*.

DeepSeek-AI. 2025. DeepSeek-R1: Incentivizing reasoning capability in LLMs via reinforcement learning. *Nature*, 645:633–638.

Darshan Deshpande, Selvan Sunitha Ravi, Sky Ch-Wang, Bartosz Mielczarek, Anand Kannappan, and Rebecca Qian. 2024. GLIDER: Grading LLM interactions and decisions using explainable ranking. *arXiv preprint arXiv:2412.14140*.

Yanai Elazar, Nora Kassner, Shauli Ravfogel, Abhilasha Ravichander, Eduard Hovy, Hinrich Schütze, and Yoav Goldberg. 2021. Measuring and improving consistency in pretrained language models. *Transactions of the Association for Computational Linguistics*, 9:1012–1031.

Arduin Findeis, Timo Kaufmann, Eyke Hüllermeier, Samuel Albanie, and Robert Mullins. 2025. Inverse constitutional AI: Compressing preferences into principles. In *ICLR*.

Leo Gao, John Schulman, and Jacob Hilton. 2023. Scaling laws for reward model overoptimization. In *ICML*.

Melody Y. Guan, Manas Joglekar, Eric Wallace, and 1 others. 2024. Deliberative alignment: Reasoning enables safer language models. *arXiv preprint arXiv:2412.16339*.

Honglin Guo, Kai Lv, Qipeng Guo, Tianyi Liang, Zhiheng Xi, Demin Song, Qiuyinzhe Zhang, Yu Sun, Kai Chen, Xipeng Qiu, and Tao Gui. 2025. CritiQ: Mining data quality criteria from human preferences. In *ACL*.

Jessica Huynh, Alfredo Gomez, Athiya Deviyani, Renee Shelby, Jeffrey P. Bigham, and Fernando Diaz. 2026. Quantifying the statistical effect of rubric modifications on human-autorater agreement. *arXiv preprint arXiv:2605.06283*.

Ruipeng Jia, Yunyi Yang, Yongbo Gai, Kai Luo, Shihao Huang, Jianhe Lin, Xiaoxi Jiang, and Guanjun Jiang. 2025. Writing-Zero: Bridge the gap between non-verifiable tasks and verifiable rewards. *arXiv preprint arXiv:2506.00103*.

Ai Jian, Jingqing Ruan, Xing Ma, Xiaoyun Zhang, Dailin Li, Weipeng Zhang, Ke Zeng, and Xunliang Cai. 2025. PaTaRM: Bridging pairwise and pointwise signals via preference-aware task-adaptive reward modeling. *arXiv preprint arXiv:2510.24235*.

Anders Jonsson and Gunilla Svingby. 2007. The use of scoring rubrics: Reliability, validity and educational consequences. *Educational Research Review*, 2(2):130–144.

Douwe Kiela, Max Bartolo, Yixin Nie, and 1 others. 2021. Dynabench: Rethinking benchmarking in NLP. In *NAACL*.

Seungone Kim, Juyoung Suk, Shayne Longpre, Bill Yuchen Lin, Jamin Shin, Sean Welleck, Graham Neubig, Moontae Lee, Kyungjae Lee, and Minjoon Seo. 2024a. Prometheus 2: An open source language model specialized in evaluating other language models. In *Proceedings of EMNLP*.

Seungone Kim and 1 others. 2024b. Prometheus: Inducing fine-grained evaluation capability in language models. In *ICLR*.

Seungone Kim and 1 others. 2025. The BiGGen Bench: A principled benchmark for fine-grained evaluation of language models with language models. In *Proceedings of NAACL*.

Victoria Krakovna, Jonathan Uesato, Vladimir Mikulik, Matthew Rahtz, Tom Everitt, Ramana Kumar, Zac Kenton, Jan Leike, and Shane Legg. 2020. Specification gaming: The flip side of AI ingenuity. DeepMind Blog.

Klaus Krippendorff. 2011. Computing Krippendorff's alpha-reliability. *Departmental Papers (ASC)*.

Nathan Lambert, Valentina Pyatkin, Jacob Morrison, LJ Miranda, Bill Yuchen Lin, Khyathi Chandu, Nouha Dziri, Sachin Kumar, Tom Zick, Yejin Choi, Noah A. Smith, and Hannaneh Hajishirzi. 2024. RewardBench: Evaluating reward models for language modeling. *arXiv preprint arXiv:2403.13787*.

Harrison Lee and 1 others. 2024. RLAIF: Scaling reinforcement learning from human feedback with AI feedback. *Proceedings of ICML*.

Tung-Ling Li, Yuhao Wu, and Hongliang Liu. 2025. AdvJudge-Zero: Binary decision flips in LLM-as-a-judge via adversarial control tokens. *arXiv preprint arXiv:2512.17375*.

Percy Liang, Rishi Bommasani, Tony Lee, Dimitris Tsipras, Dilara Soylu, Michihiro Yasunaga, Yian Zhang, Deepak Narayanan, Yuhuai Wu, Ananya Kumar, and 1 others. 2023. Holistic evaluation of language models. *Transactions on Machine Learning Research*.

Zhicheng Lin. 2025. A validity-guided workflow for robust large language model research in psychology. *arXiv preprint arXiv:2507.04491*.

Yixin Liu, Yue Yu, DiJia Su, Sid Wang, Xuewei Wang, Song Jiang, Bo Liu, Arman Cohan, Yuandong Tian, and Zhengxing Chen. 2026. Examining reasoning LLMs-as-judges in non-verifiable LLM post-training. *arXiv preprint arXiv:2603.12246*.

LMSYS. 2024. Arena Hard / Arena Expert preference data. LMSYS Chatbot Arena release.

Ivan Montero, Tomasz Jurczyk, and Bhuwan Dhingra. 2026. RVPO: Risk-sensitive alignment via variance regularization. *arXiv preprint arXiv:2605.05750*.

OpenAI. 2024. OpenAI Model Spec. https://model-spec.openai.com.

Tianjun Pan, Xuan Lin, Wenyan Yang, Qianyu He, Shisong Chen, Licai Qi, Wanqing Xu, Hongwei Feng, Bo Xu, and Yanghua Xiao. 2026. RubricEval: A rubric-level meta-evaluation benchmark for LLM judges in instruction following. *arXiv preprint arXiv:2603.25133*.

Jose Pombal, Ricardo Rei, and Andre F. T. Martins. 2026. Self-preference bias in rubric-based evaluation of large language models. *arXiv preprint arXiv:2604.06996*.

Marco Tulio Ribeiro, Tongshuang Wu, Carlos Guestrin, and Sameer Singh. 2020. Beyond accuracy: Behavioral testing of NLP models with CheckList. In *ACL*.

Melanie Sclar, Yejin Choi, Yulia Tsvetkov, and Alane Suhr. 2024. Quantifying language models' sensitivity to spurious features in prompt design. In *ICLR*.

William F. Shen, Xinchi Qiu, Chenxi Whitehouse, Lisa Alazraki, Shashwat Goel, Francesco Barbieri, Timon Willi, Akhil Mathur, and Ilias Leontiadis. 2026. Rethinking rubric generation for improving LLM judge and reward modeling for open-ended tasks. *arXiv preprint arXiv:2602.05125*.

Ibne Farabi Shihab, Sanjeda Akter, and Anuj Sharma. 2025. Detecting proxy gaming in RL and LLM alignment via evaluator stress tests. *arXiv preprint arXiv:2507.05619*.

Joar Skalse, Nikolaus Howe, Dmitrii Krasheninnikov, and David Krueger. 2022. Defining and characterizing reward hacking. In *NeurIPS*.

Hwanjun Song and 1 others. 2024. FineSurE: Fine-grained summarization evaluation using LLMs. In *ACL*.

Pragya Srivastava, Harman Singh, Rahul Madhavan, Gandharv Patil, Sravanti Addepalli, Arun Suggala, Rengarajan Aravamudhan, Soumya Sharma, Anirban Laha, Aravindan Raghuveer, Karthikeyan Shanmugam, and Doina Precup. 2025. Robust reward modeling via causal rubrics. *arXiv preprint arXiv:2506.16507*.

Tom Sühr, Florian E. Dorner, Olawale Salaudeen, Augustin Kelava, and Samira Samadi. 2025. Position: Stop evaluating AI with human tests, develop principled, AI-specific tests instead. *arXiv preprint arXiv:2507.23009*.

Tu Vu and 1 others. 2024. Foundational autoraters: Taming large language models for better automatic evaluation. *arXiv preprint arXiv:2407.10817*.

Tevin Wang and Chenyan Xiong. 2025. AutoRule: Reasoning chain-of-thought extracted rule-based rewards improve preference learning. *arXiv preprint arXiv:2506.15651*.

Zhilin Wang, Jiaqi Zeng, Olivier Delalleau, Hoo-Chang Shin, Felipe Soares, Alexander Bukharin, Ellie Evans, Yi Dong, and Oleksii Kuchaiev. 2025. HelpSteer3-Preference: Open human-annotated preference data across diverse tasks and languages. *arXiv preprint arXiv:2505.11475*.

Shihao Weng, Yang Feng, and Xiaofei Xie. 2026. Beyond accuracy: Policy invariance as a reliability test for LLM safety judges. *arXiv preprint arXiv:2605.06161*.

Lipeng Xie, Sen Huang, Zhuo Zhang, Anni Zou, Yunpeng Zhai, Dingchao Ren, Kezun Zhang, Haoyuan Hu, Boyin Liu, Haoran Chen, Zhaoyang Liu, and Bolin Ding. 2025. Auto-Rubric: Learning from implicit weights to explicit rubrics for reward modeling. *arXiv preprint arXiv:2510.17314*.

Haoran Ye, Jing Jin, Yuhang Xie, Xin Zhang, and Guojie Song. 2025. Large language model psychometrics: A systematic review of evaluation, validation, and enhancement. *arXiv preprint arXiv:2505.08245*.

Seonghyeon Ye and 1 others. 2024. FLASK: Fine-grained language model evaluation based on alignment skill sets. In *ICLR (Spotlight)*.

Jiachen Yu, Zhihao Xu, Junjie Wang, and Yujiu Yang. 2026. Think-with-rubrics: From external evaluator to internal reasoning guidance. *arXiv preprint arXiv:2605.07461*.

Jifan Zhang, Henry Sleight, Andi Peng, John Schulman, and Esin Durmus. 2025. Stress-testing model specs reveals character differences among language models. *arXiv preprint arXiv:2510.07686*.

Qiyuan Zhang, Junyi Zhou, Yufei Wang, Fuyuan Lyu, Yidong Ming, Can Xu, Qingfeng Sun, Kai Zheng, Peng Kang, Xue Liu, and Chen Ma. 2026. RubricBench: Aligning model-generated rubrics with human standards. *arXiv preprint arXiv:2603.01562*.

Xinran Zhang. 2026. Rethinking atomic decomposition for LLM judges: A prompt-controlled study of reference-grounded QA evaluation. *arXiv preprint arXiv:2603.28005*.

Yulai Zhao, Haolin Liu, Dian Yu, Sunyuan Kung, Meijia Chen, Haitao Mi, and Dong Yu. 2025. One token to fool LLM-as-a-judge. *arXiv preprint arXiv:2507.08794*.

A Discovery Algorithm

The SubGroup call applies an operational-distinctness test: two rubrics are merged only if no response could score high on one and low on the other. This prevents over-merging of superficially similar but operationally distinct rubrics (e.g., "factual accuracy about biology" vs. "factual accuracy about SQL"). Subgroup size is capped at 5 to bound information loss per merge.

Run settings. For each source, discovery uses N=1,000 preference pairs, DeepSeek-V3 for extraction and consolidation, and `amazon.titan-embed-text-v2:0` for embeddings. We use K=20, target cluster size T=20, $L_{\max}$=10, and minimum source support $n_{\min}$=10. Embeddings are L2-normalized and clustered using cosine-distance agglomerative clustering with average linkage. Extraction and consolidation use temperature 0; each extraction requests 5–15 criteria, and consolidation subgroups contain at most 5 criteria. The archived run configuration does not record separate numerical values for K_{pool} or the MMR diversity weight λ, so we do not infer them.

B Audit

This appendix provides full protocol details for each audit axis (§B.1), per-dataset replication tables (§B.2), the anatomy-of-preference-fit diagnostics (§B.3), the large-scale preference-fit sweep across sources, judges, and prompt templates (§B.4), and human validation of VFR (§B.5).

B.1 Protocol Details

B.1.1 Reliability Protocol

Reliability is measured on three complementary sub-axes.

Inter-Rater Agreement (IRA). We instantiate a 3-judge ensemble: DeepSeek-V3, Mistral-Large-3, and Qwen3-235B. Each judge independently scores n=500 randomly sampled preference pairs on every rubric using an ordinal $[0, 10]$ scale with integer granularity. Agreement is quantified via Krippendorff's α with ordinal weighting, which accounts for the distance between disagreements (a 3-vs-7 disagreement is penalised more than a 5-vs-6 disagreement). We report the per-rubric α averaged across all K rubrics in the set (judge prompt in §E).

Self-Consistency (Flip%). We perform R=5 stochastic re-runs of DeepSeek-V3 (temperature 0.7) on the same n=500 preference pairs. For each pair, a "flip" occurs when the majority verdict across 5 runs differs from at least one individual run's verdict. The flip rate is the fraction of pairs exhibiting at least one flip, reported as a percentage. Lower is better–it indicates the rubric elicits stable verdicts under sampling noise.

Paraphrase Stability (ρ). For each rubric, we generate P=5 semantically equivalent paraphrases (preserving meaning while varying surface form). DeepSeek-V3 scores the same n=500 pairs under each paraphrase. We compute the Spearman rank correlation ρ between the win-rate vectors induced by each paraphrase pair, then average across all $\binom{P}{2}$ pairs and all K rubrics. Higher ρ indicates that the rubric's evaluation signal is robust to surface-level rephrasing (paraphrase generation prompt in §E).

Algorithm 1 PREMISE Discovery Pipeline

Require: Preference battles $\mathcal{D} = \{(p_i, y_i^+, y_i^-)\}_{i=1}^N$; extractor model $\mathcal{E}$; consolidation model $\mathcal{L}$; embedding model ϕ; target rubric size K; target cluster size T; max levels $L_{\max}$; min-support threshold $n_{\min}$; selection-pool cutoff K_{pool}; MMR diversity weight λ

Ensure: Policy rubric R with $|R| = K$

– Stage 1: Candidate Criterion Extraction –

$\mathcal{C}^{(0)} \leftarrow \emptyset$
for each battle $(p_i, y_i^+, y_i^-) \in \mathcal{D}$ **do**
  $\{c_1, \ldots, c_m\} \leftarrow \mathcal{E}(p_i, y_i^+, y_i^-)$ ▷ extract 5–15 discriminating rubrics per pair
  $\mathcal{C}^{(0)} \leftarrow \mathcal{C}^{(0)} \cup \{c_1, \ldots, c_m\}$, each with $\sigma(c_j) = 1$, $\text{src}(c_j) = \{i\}$
end for

– Stage 2: Iterative Consolidation –

for $\ell = 0, 1, \ldots, L_{\max} - 1$ **do**
  if $\ell \geq 2$ **and** $|\mathcal{C}^{(\ell)}| \leq K_{\text{pool}}$ **then break** ▷ pool small enough for selection
  end if
  $\mathbf{V}^{(\ell)} \leftarrow \{\text{L2-norm}(\phi(c)) : c \in \mathcal{C}^{(\ell)}\}$ ▷ embed all rubrics
  $k \leftarrow \max(1, \lfloor |\mathcal{C}^{(\ell)}|/T \rfloor)$
  $\{\mathcal{G}_1, \ldots, \mathcal{G}_k\} \leftarrow \textsc{AgglomerativeCluster}(\mathbf{V}^{(\ell)},\ k;\ \text{cosine, average-link})$
  Recursively split any $\mathcal{G}_j$ with $|\mathcal{G}_j| > 2T$
  $\mathcal{C}^{(\ell+1)} \leftarrow \emptyset$
  for all cluster $\mathcal{G}_j$ **do**
    if $|\mathcal{G}_j| = 1$ **then**
      $\mathcal{C}^{(\ell+1)} \leftarrow \mathcal{C}^{(\ell+1)} \cup \mathcal{G}_j$
    else
      $(\{\mathcal{S}_1, \ldots, \mathcal{S}_m\},\ \mathcal{U}) \leftarrow \mathcal{L}.\textsc{SubGroup}(\mathcal{G}_j)$ ▷ LLM identifies merge-worthy subsets
      for all subgroup $\mathcal{S}_t$ **do**
        $r_t \leftarrow \mathcal{L}.\textsc{Describe}(\mathcal{S}_t)$; $\sigma(r_t) \leftarrow \sum_{c \in \mathcal{S}_t} \sigma(c)$; $\text{src}(r_t) \leftarrow \bigcup_{c \in \mathcal{S}_t} \text{src}(c)$
        $\mathcal{C}^{(\ell+1)} \leftarrow \mathcal{C}^{(\ell+1)} \cup \{r_t\}$
      end for
      $\mathcal{C}^{(\ell+1)} \leftarrow \mathcal{C}^{(\ell+1)} \cup \mathcal{U}$ ▷ unmerged singletons carried forward
    end if
  end for
  if $|\mathcal{C}^{(\ell+1)}| \geq 0.95 \cdot |\mathcal{C}^{(\ell)}|$ **then break** ▷ diminishing reduction
  end if
end for

– Stage 3: Selection –

$\mathcal{P} \leftarrow \{c \in \mathcal{C}^{(\ell)} : \sigma(c) \geq n_{\min}\}$ ▷ min-support filter
$R \leftarrow \text{MMR-}\textsc{Select}(\mathcal{P}, K, \lambda)$ ▷ genericity-filtered, log-source-count relevance, max-cosine diversity
return R

B.1.2 Structural Adequacy Protocol

Structural adequacy evaluates whether a rubric is well-formed as a measurement instrument, independent of its preference-prediction value. A 3-judge ensemble (DeepSeek-R1, DeepSeek-V3, Mistral-Large-3) evaluates each rubric on 5 binary design properties:

1. **Atomicity**: the rubric measures a single behavioral dimension, not multiple conflated properties.
2. **Internal consistency**: the rubric does not contain internally contradictory rules.
3. **Response observability**: the rubric can be assessed solely from the prompt and response, without external knowledge or ground truth.
4. **Operationalizability**: the rubric can be expressed as a concrete, answerable scoring question.
5. **Unambiguous scope**: the boundaries of what counts as adherence vs. violation are well-defined.

Each property is scored pass/fail by majority vote across the 3 judges (structural judge prompt in §E). The structural score for a rubric is the mean number of properties passed per rubric (out of 5), averaged across all K rubrics in the set.

B.1.3 BT Preference-Fit Protocol

Preference fit measures whether per-rubric scores predict human preference labels. The protocol:

1. **Scoring.** DeepSeek-V3 scores both responses in each of n preference pairs on every rubric (ordinal $[0, 10]$ scale), producing a feature matrix $S \in \mathbb{R}^{n \times K}$ of per-rubric score differences.
2. **Regression.** An L_2-regularized logistic regression is fit on S to predict the binary human preference label, using 5-fold stratified cross-validation. The regularization strength C is selected by nested CV within each fold.
3. **Metrics.** We report (a) CV accuracy: the mean held-out accuracy across 5 folds; (b) BT-weight entropy: the normalized Shannon entropy of the absolute logistic regression coefficients, $H(|\beta|/\sum|\beta|)/\log K$, measuring how uniformly individual rubrics contribute to preference prediction (higher = more rubrics carry signal).

Training uses n=1000 battles; holdout evaluation uses n=250 disjoint battles per dataset. All battles are from the same source dataset the rubric was discovered from.

B.1.4 Adversarial Robustness Protocol

The adversarial protocol implementing VFR (Eq. 2, main body) instantiates the attacker, judge, and verifier as follows: **attacker** = Moonshot Kimi-K2-Thinking, generating N=500 adversarial prompt–response pairs per rubric; **judge** = DeepSeek-V3, scoring each pair on the target rubric on an ordinal $[0, 10]$ scale with high-score threshold τ=7; **verifier** = Mistral-Large-3, blind to the attack strategy and judge score, labelling each high-scoring response as exploiting or genuine. VFR is reported per rubric and averaged across the K rubrics of a set. Attacker, judge, and verifier prompts are reproduced in §E.

The rubric-conditioned judge accuracy protocol used for RQ3 is described in §B.4; statistical significance for cross-judge comparisons is assessed via paired bootstrap (n_{boot}=5000, sample-resampling, seed=42).

B.2 Per-Dataset Audit Replication

Table 3 reports per-(method, dataset) values underlying the K-weighted means in the main paper's Table 1. The top block covers the six baseline rubric sources plus PREMISE (discovered); the bottom block extends the audit to PREMISE (+ pref repair) and its two pref-track refinement variants. The non-dominance pattern replicates within each individual dataset: AgentEval leads inter-judge agreement and paraphrase stability, Auto-Rubric leads self-consistency and VFR, and PREMISE (discovered) leads BT entropy on three of four datasets (UltraFeedback, HH-RLHF, Arena).

Refinement deltas (source of truth for Figure 5). Table 4 reports the per-dataset $\Delta\alpha$ and ΔVFR at both operating points, computed from the discovered baseline rows above. These are the exact numbers plotted in Figure 5.

B.3 Structural Coverage of the Preference Space (RQ2)

Preference fit measures how well a rubric expresses pairwise preferences (§3.2). The empirical accuracy number (RQ3) is silent on *how* a rubric earns

Table 3: Per-dataset breakdown of the main audit table. Each row is one (method, dataset) cell. **Str.** = structural pass score (out of 5); **Flip%** = stochastic re-run flip rate; ρ = mean paraphrase Spearman; **VFR** = Verified Fool Rate; **CV-acc / Ent.** = 5-fold logistic CV accuracy / normalized BT-weight entropy. Pref-track variants (bottom block) follow the same protocol; cross-source means are in Table 1.

Rubric source	**Dataset**	K	**Str.**	α	**Flip%**	ρ	**VFR**	**CV-acc**	**Ent.**
Baselines and PREMISE *(discovered)*									
INVERSE CAI	Arena-Expert-5K	2	2.00	.387	32.5	.615	.430	.597	.677
	HelpSteer3	2	3.50	.561	44.7	.412	.475	.583	.994
	HH-RLHF	3	3.00	.805	8.5	.701	.687	.583	.990
	UltraFeedback	4	3.75	.456	58.9	.457	.455	.661	.985
AUTO-RUBRIC	Arena-Expert-5K	20	3.65	.106	24.5	.242	.248	.615	.866
	HelpSteer3	20	4.35	.242	3.1	.107	.197	.587	.896
	HH-RLHF	20	3.80	.614	6.4	.610	.316	.640	.927
	UltraFeedback	20	3.95	.237	21.7	.243	.328	.705	.943
AUTORULE	Arena-Expert-5K	28	1.96	.265	40.2	.453	.514	.582	.856
	HelpSteer3	33	2.30	.608	16.9	.534	.475	.634	.899
	HH-RLHF	19	2.16	.762	11.9	.722	.531	.602	.861
	UltraFeedback	25	2.04	.475	32.5	.696	.503	.815	.922
CRITIQ	Arena-Expert-5K	10	4.40	.120	43.4	.489	.477	.616	.949
	HelpSteer3	3	4.33	.554	18.3	.485	.540	.647	.911
	HH-RLHF	1	5.00	.752	4.4	.542	.540	.539	.000
	UltraFeedback	9	4.33	.513	33.5	.748	.353	.817	.885
AGENTEVAL	Arena-Expert-5K	4	3.25	.259	43.3	.600	.360	.607	.744
	HelpSteer3	4	3.75	.694	22.2	.618	.320	.661	.958
	HH-RLHF	4	3.00	.811	9.6	.789	.295	.595	.918
	UltraFeedback	4	3.50	.563	31.4	.800	.343	.799	.873
PREMISE (disc.)	Arena-Expert-5K	20	4.60	.304	41.2	.538	.480	.608	.904
	HelpSteer3	20	4.15	.634	18.8	.502	.442	.665	.890
	HH-RLHF	20	4.00	.719	10.9	.705	.540	.581	.947
	UltraFeedback	20	4.10	.469	34.3	.643	.394	.804	.933
PREMISE *VFR-refined variants (on discovered rubric)*									
PREMISE (+ VFR constr.)	Arena-Expert-5K	18	4.80	.286	43.7	.566	.368	.590	.941
	HelpSteer3	18	4.35	.622	19.4	.540	.364	.660	.911
	HH-RLHF	18	4.15	.709	11.8	.680	.381	.607	.884
	UltraFeedback	18	4.25	.458	34.7	.651	.329	.822	.900
PREMISE (+ VFR unconstr.)	Arena-Expert-5K	18	4.80	.233	49.1	.519	.266	.572	.893
	HelpSteer3	18	4.50	.610	19.7	.541	.318	.663	.906
	HH-RLHF	18	4.20	.672	16.1	.639	.329	.605	.865
	UltraFeedback	18	4.30	.438	40.3	.642	.282	.818	.931
PREMISE *pref-track variants*									
PREMISE (+ pref repair)	Arena-Expert-5K	20	4.30	.267	41.8	.528	.385	.628	.940
	HelpSteer3	20	3.80	.575	16.9	.452	.421	.669	.944
	HH-RLHF	20	3.50	.683	11.3	.648	.498	.615	.911
	UltraFeedback	20	3.70	.471	26.6	.566	.424	.827	.869
PREMISE (+ pref + VFR constr.)	Arena-Expert-5K	20	4.60	.262	41.4	.472	.346	.589	.887
	HelpSteer3	20	3.95	.525	20.8	.454	.389	.686	.884
	HH-RLHF	20	3.75	.669	10.9	.637	.379	.611	.871
	UltraFeedback	20	3.75	.416	34.9	.512	.412	.820	.909
PREMISE (+ pref + VFR unconstr.)	Arena-Expert-5K	20	4.45	.238	39.7	.455	.308	.610	.899
	HelpSteer3	20	4.20	.559	17.0	.452	.336	.660	.901
	HH-RLHF	20	3.50	.659	11.0	.634	.378	.596	.835
	UltraFeedback	20	3.65	.438	31.8	.512	.326	.803	.934

Table 4: Per-dataset refinement deltas relative to PREMISE (discovered). Constrained = no dev-split α loss allowed; Unconstrained = lowest-VFR Pareto member.

	Constrained		Unconstrained	
Dataset	$\Delta\alpha$	ΔVFR	$\Delta\alpha$	ΔVFR
Arena-Expert-5K	$-.018$	$-.112$	$-.071$	$-.214$
HelpSteer3	$-.012$	$-.078$	$-.024$	$-.124$
HH-RLHF	$-.010$	$-.159$	$-.047$	$-.211$
UltraFeedback	$-.011$	$-.065$	$-.031$	$-.112$
Mean	$-.012$	$-.104$	$-.043$	$-.165$

it. We report three structural diagnostics that decompose preference fit into the slice of prompts a rubric touches, the persistence of that slice off the source distribution, and the number of distinct constructs the rubric uses.

B.3.1 Metric Definitions

Per-prompt applicability. For each rubric r and prompt p, we ask whether r is applicable to p (its applicability gate, conditioned only on the prompt). Per-prompt applicability of rubric R on dataset $\mathcal{D}$ is:

$$\mathrm{App}(R, \mathcal{D}) = \frac{1}{|\mathcal{D}|} \sum_{p \in \mathcal{D}} \frac{1}{|R|} \sum_{r \in R} \mathbf{1}[r \text{ applies to } p].$$

We also report *rubrics per prompt* (T/p), the unnormalized count $\sum_r \mathbf{1}[r \text{ applies to } p]$ averaged over p.

Specificity to source distribution. We measure per-prompt applicability on the source dataset (in-domain) and on a different preference dataset (out-of-domain), reporting the gap $\Delta\mathrm{App} = \mathrm{App}_{\mathrm{in}} - \mathrm{App}_{\mathrm{out}}$. A positive $\Delta\mathrm{App}$ indicates the rubric picks up on something distinctive about its source distribution. A near-zero or negative $\Delta\mathrm{App}$ indicates universally applicable rubrics.

Effective dimensionality. Computed on the score matrix $S \in [0, 10]^{|\mathcal{D}| \times K}$: $\mathrm{EffDim}(R) = \exp(H(\lambda / \sum \lambda))$ where λ are the eigenvalues of $\mathrm{cov}(S)$ and H is Shannon entropy in nats. We report EffDim/K as the ratio of independent directions to stated rubrics, and the mean absolute pairwise correlation $\overline{|\rho|}(R) = \frac{2}{K(K-1)} \sum_{i<j} |\rho(s_i, s_j)|$.

B.3.2 Full Results

Table 5 reports the three diagnostics on UltraFeedback.

Table 6 extends the analysis to PREMISE (+ pref repair) and its refinement variants across all four source datasets. Pref-rank selection narrows applicability (43.5% vs. 58% for discovered) while preserving specificity. Pref-track refinement (+ pref + VFR constrained / unconstrained) further reduces applicability by $\sim$3 pp without materially changing specificity.

B.4 Rubric-Conditioned Judge Accuracy (RQ3)

Single-shot judge evaluation at temperature 0 is sensitive to small perturbations: in a diagnostic on UltraFeedback, $\sim$60% of nominally "failed" cases on PREMISE (discovered) flip to correct under repeated sampling without any rubric edits. We therefore evaluate with majority-of-5 sampling (temperature 0.7, 5 independent calls per battle, majority vote across parsed verdicts). The full evaluation grid covers 4 source datasets and 3 judges (DeepSeek-V3, Kimi K2.5, Qwen3-32B). Seven rubric-conditioned methods are evaluated under both prompt templates: *direct-verdict* – the judge sees the full rubric set and issues a single A/B verdict; and *per-rubric JSON* – the judge scores each rubric individually, then issues the verdict. The no-rubric baseline is evaluated only under direct-verdict, instantiated by omitting the rubric section from that prompt. It has no per-rubric instantiation because the JSON template requires criterion identifiers and criterion-level scores; those cells are therefore not applicable. Each cell uses n=3,000 pairs from its source dataset. Table 7 reports the full grid.

Key findings (paired bootstrap, n_{boot}=5000).

1. Preference-rank selection (PREMISE (discovered) $\rightarrow$ PREMISE (+ pref repair)) produces a consistent lift across the cross-judge $\times$ cross-template grid. Hierarchical aggregate over (judge, template, source) cells: +3.65 pp.

2. PREMISE (+ pref repair) leads the 4-source mean on DS-V3 (direct 68.6, JSON 69.2) and Kimi K2.5 (direct 70.5), and ties for the lead under Kimi K2.5 / per-rubric JSON (70.5 alongside Auto-Rubric).

B.5 Human Validation of VFR

The Verified Fool Rate (VFR) relies on an automated verifier (Mistral-Large-3) to determine

Table 5: Structural anatomy of preference fit on UltraFeedback. **App$_{\text{in}}$ / App$_{\text{out}}$**: per-prompt applicability – the fraction of the rubric set's K criteria whose applicability gate fires on a given prompt, averaged over prompts (in-domain / out-of-domain). **ΔApp** = $\mathrm{App}_{\mathrm{in}} - \mathrm{App}_{\mathrm{out}}$ measures specificity to the source distribution. **T/p** is the unnormalised count of firing criteria per in-domain prompt. **EffDim** is the entropy-effective number of independent score directions in the per-criterion score matrix. $\overline{|\rho|}$ is the mean absolute pairwise correlation between criterion scores. Definitions in §B.3.

Rubric	K	**App$_{\text{in}}$**	**App$_{\text{out}}$**	**ΔApp**	**T/p**	**EffDim**	**EffDim/K**	$\overline{\lvert\rho\rvert}$
AGENTEVAL	4	.824	.883	−.06	3.3	3	.75	.425
INVERSE CAI	4	.630	.676	−.05	2.5	4	1.00	.251
CRITIQ	9	.753	.741	+.01	6.8	7	.78	.413
AUTO-RUBRIC	20	.030	.013	+.02	0.6	10	.50	**.081**
AUTORULE	25	.403	.360	+.04	10.1	18	.72	.256
PREMISE (disc.)	20	.577	.502	+.08	11.5	15	.75	.221

Table 6: Structural anatomy of preference fit for the three pref-track PREMISE variants, replicated across all four source datasets. Columns are as in Table 5. The out-of-domain reference dataset is UltraFeedback for rubrics derived from HH-RLHF / HelpSteer3 / Arena-Expert-5K, and HH-RLHF for rubrics derived from UltraFeedback.

Variant	**Source**	K	**App$_{\text{in}}$**	**App$_{\text{out}}$**	**ΔApp**	**T/p**	**EffDim**	**EffDim/K**
PREMISE (+ pref repair)	HH-RLHF	20	.473	.419	+.05	9.5	14	.70
	UltraFeedback	20	.340	.264	+.08	6.8	11	.55
	HelpSteer3	20	.346	.314	+.03	6.9	14	.70
	Arena-Expert-5K	20	.581	.282	+.30	11.6	15	.75
	Mean	20	**.435**	**.320**	**+.12**	**8.7**	**14**	**.68**
PREMISE (+ pref + VFR constrained)	HH-RLHF	20	.449	.414	+.04	9.0	14	.70
	UltraFeedback	20	.335	.260	+.08	6.7	11	.55
	HelpSteer3	20	.319	.287	+.03	6.4	14	.70
	Arena-Expert-5K	20	.572	.270	+.30	11.4	15	.75
	Mean	20	**.419**	**.308**	**+.11**	**8.4**	**14**	**.68**
PREMISE (+ pref + VFR unconstrained)	HH-RLHF	20	.419	.394	+.03	8.4	15	.75
	UltraFeedback	20	.286	.210	+.08	5.7	13	.65
	HelpSteer3	20	.336	.304	+.03	6.7	14	.70
	Arena-Expert-5K	20	.556	.264	+.29	11.1	16	.80
	Mean	20	**.399**	**.293**	**+.11**	**8.0**	**14**	**.73**

whether adversarial responses genuinely exhibit the quality their high scores claim. To validate this automated proxy against human judgment, we conduct a human annotation study.

Evaluation protocol. The eval set is 42 samples drawn from two source pools: 25 from the adversarial pool (attacker-generated responses that scored $\geq 7/10$) and 17 from the baseline pool (genuine model responses that scored $\geq 7/10$), stratified by rubric and spanning three source corpora. Ground truth comes from a panel of three human annotators who independently labeled each sample as EXPLOITING or GENUINE. We recruited researchers in computer science as annotators. They are paid in kind by us helping them with their research tasks. The per-sample majority vote is the ground-truth label. Source-pool membership does not predetermine the ground-truth label: 6 of 25 adversarial-pool samples were labeled GENUINE by the human majority (the attacker produced a genuinely good response), yielding final counts of 19 EXPLOITING and 23 GENUINE.

Inter-annotator agreement. Krippendorff's $\alpha = 0.730$ on the union of overlapping samples, indicating substantial agreement (above the $\alpha \geq 0.67$ threshold customary for treating a label set as reliable). Pairwise percent agreement ranges from 83.3% to 100.0%.

Verifier precision/recall against human ground truth. Treating EXPLOITING as the positive class on the n=42 pool, the verifier produces a confusion matrix of TP=16, FP=6, FN=3, TN=17, giving precision 72.7%, recall 84.2%, and F1 = 78.0% against the 3-annotator human majority. The 6 false positives are predominantly borderline cases where the response is technically correct but stylistically suspicious; the verifier's bias is toward flagging gameable patterns rather than accepting plausible-looking violations.

Table 7: Rubric-conditioned judge accuracy (%) on held-out preference labels under majority-of-5 sampling. Each block fixes one (judge, template) pair. Direct-verdict blocks compare seven rubric-conditioned methods and the no-rubric baseline; per-rubric blocks compare the seven rubric-conditioned methods only because criterion-level scoring is not applicable without a rubric. Each entry is the accuracy with its 95% confidence interval (bootstrap, n_{boot}=2000); the **Mean** column averages across the four sources. Bold = best in column within the block; differences smaller than the confidence interval are not significant. Per-cell sample sizes are stated in the surrounding text.

Judge / Template	Method	HH-RLHF	HelpSteer3	Arena-Exp.	UltraFeedback	Mean
DS-V3 *Direct-verdict*	PREMISE (+ pref repair)	63.3±1.7	**69.8**±1.7	**58.5**±1.8	**82.7**±1.4	**68.6**
	AutoRule	**64.6**±1.7	69.6±1.6	57.4±1.8	82.1±1.4	68.4
	AgentEval	63.4±1.7	67.6±1.7	56.0±1.9	81.5±1.4	67.1
	no-rubric	63.0±1.7	69.3±1.7	56.9±1.8	82.0±1.4	67.8
	Auto-Rubric	**64.6**±1.7	68.4±1.6	57.6±1.9	81.9±1.4	68.1
	Inverse CAI	62.9±1.7	68.1±1.6	57.9±1.8	80.8±1.4	67.4
	CritiQ	63.6±1.7	69.5±1.7	56.8±1.8	81.5±1.4	67.9
	PREMISE (disc.)	61.5±1.7	68.8±1.7	57.1±1.8	73.4±1.5	65.2
DS-V3 *Per-rubric JSON*	PREMISE (+ pref repair)	62.0±3.0	**69.5**±2.8	62.1±3.0	**83.3**±1.4	**69.2**
	AutoRule	**63.6**±2.9	68.2±2.8	**62.2**±3.0	82.2±1.4	69.0
	AgentEval	63.5±3.0	66.6±2.9	59.8±3.1	82.9±1.4	68.2
	Auto-Rubric	63.0±3.0	67.8±2.9	62.4±3.0	81.9±1.4	68.8
	Inverse CAI	57.3±3.0	65.1±2.9	62.2±3.0	80.2±1.5	66.2
	CritiQ	62.9±3.0	68.8±2.9	62.2±3.0	82.2±1.4	69.0
	PREMISE (disc.)	59.2±3.0	64.8±3.0	61.7±3.0	70.4±1.6	64.0
Kimi K2.5 *Direct-verdict*	PREMISE (+ pref repair)	63.7±1.7	74.2±1.5	60.8±1.8	83.4±1.3	**70.5**
	AutoRule	63.1±1.7	74.2±1.5	59.7±1.8	82.2±1.4	69.8
	AgentEval	63.1±1.7	**74.4**±1.5	60.1±1.8	83.2±1.3	70.2
	no-rubric	63.1±1.7	73.6±1.6	61.0±1.8	83.6±1.3	70.3
	Auto-Rubric	64.2±1.7	73.2±1.6	**61.1**±1.8	82.9±1.3	70.3
	Inverse CAI	62.2±1.7	72.4±1.6	60.9±1.7	**83.9**±1.3	69.9
	CritiQ	**64.5**±1.7	73.8±1.6	59.5±1.8	81.8±1.4	69.9
	PREMISE (disc.)	63.6±1.7	73.3±1.6	59.6±1.8	75.1±1.6	67.9
Kimi K2.5 *Per-rubric JSON*	PREMISE (+ pref repair)	63.3±1.7	73.4±1.6	60.2±1.8	**85.2**±1.3	70.5
	AutoRule	62.4±1.7	74.0±1.6	59.8±1.8	82.3±1.3	69.6
	AgentEval	63.7±1.7	**74.2**±1.6	57.4±1.8	83.5±1.3	69.7
	Auto-Rubric	**65.0**±1.7	74.0±1.5	**60.7**±1.8	82.5±1.3	**70.5**
	Inverse CAI	61.0±1.7	68.9±1.7	59.3±1.8	84.0±1.4	68.3
	CritiQ	64.3±1.7	74.1±1.5	57.5±1.8	81.9±1.4	69.5
	PREMISE (disc.)	63.2±1.7	70.5±1.7	59.2±1.8	71.0±1.6	66.0
Qwen3-32B *Direct-verdict*	PREMISE (+ pref repair)	61.8±1.8	65.6±1.7	57.6±1.8	78.2±1.5	65.8
	AutoRule	60.5±1.8	65.0±1.7	56.5±1.8	79.1±1.5	65.3
	AgentEval	60.8±1.8	66.3±1.7	56.3±1.8	**81.0**±1.4	66.1
	no-rubric	61.1±1.8	**66.8**±1.7	56.5±1.8	**81.0**±1.4	66.4
	Auto-Rubric	**62.4**±1.8	65.6±1.7	58.0±1.8	79.6±1.5	66.4
	Inverse CAI	62.3±1.8	65.7±1.8	**59.3**±1.8	80.8±1.4	**67.0**
	CritiQ	60.9±1.7	64.5±1.7	56.1±1.8	77.7±1.5	64.8
	PREMISE (disc.)	60.4±1.8	64.8±1.7	57.0±1.8	72.3±1.6	63.6
Qwen3-32B *Per-rubric JSON*	PREMISE (+ pref repair)	63.1±1.8	67.9±1.7	58.0±1.8	78.8±1.5	67.0
	AutoRule	62.0±1.7	69.0±1.6	58.3±1.8	80.2±1.5	67.4
	AgentEval	63.1±1.7	**69.1**±1.6	57.7±1.8	**82.5**±1.4	**68.1**
	Auto-Rubric	**64.3**±1.7	67.8±1.7	59.0±1.8	81.0±1.4	68.0
	Inverse CAI	60.7±1.8	65.8±1.7	**59.7**±1.8	79.6±1.5	66.4
	CritiQ	61.9±1.7	69.6±1.6	57.2±1.8	81.2±1.4	67.5
	PREMISE (disc.)	61.4±1.7	67.5±1.7	56.9±1.8	66.1±1.7	63.0

B.6 Why Operational Rubrics Have Higher VFR

On the cross-source mean (Table 1), *operational* rubrics show *higher* VFR than abstract rubrics: PREMISE (discovered) reaches VFR .464 while AgentEval (K=4, abstract) reaches .330 and Auto-Rubric (K=20, hyper-narrow) reaches .272. This is not a defect of operational rubrics; it is the cost of having an attack surface in the first place.

The mechanism is mechanical. Abstract rubrics like AgentEval's `helpfulness` or Auto-Rubric's prompt-locked rubrics either (a) admit too many response shapes for the attacker to find a violation worth surfacing, or (b) fire on too few prompts (App=.030 for Auto-Rubric on UF) for the attacker to consistently target. An operational rubric like PREMISE's `base_claims_on_evidence` ("*The response should derive all claims from reported evidence or established mechanisms without introducing assertions lacking direct support*") gives the attacker a precise target: produce a response whose surface is evidence-shaped (citation forms, mechanism vocabulary) but whose claims are not actually grounded. The attacker library used in our protocol (§E.6) names exactly these strategies – "False Authority" targets evidence-anchored rubrics, "Format Over Content" targets structure-

anchored rubrics, "Complexity Obfuscation" targets clarity-anchored rubrics.

C Repair

This appendix details the rubric repair (refinement) pipeline: pseudocode for the two algorithmic variants (§C.1), the fixed operator library (§C.2), and worked refinement examples (§C.3).

C.1 Refinement Algorithm (Pseudocode)

Algorithm 2 formalizes the predictor-guided refinement procedure described in §3.4. The two operating points reported in Table 1 – PREMISE (+ VFR constrained) and PREMISE (+ VFR unconstrained) – correspond to two settings of the reliability tolerance δ that the algorithm sweeps: $\delta{=}0$ (constrained: no dev-split α loss admitted) and $\delta{=}\infty$ (unconstrained: lowest-VFR Pareto member, regardless of α). The pref-track variants (+ pref + VFR constrained / unconstrained) re-seed the same predictor on the pref-repaired rubric set.

Structural budget (SB-PLR). Every candidate r'_S must satisfy the Structural Budget for Policy-Level Rubrics: (i) total rubric $\leq$ 150 words; (ii) main definition (first paragraph) $\leq$ 60 words with no nested conditionals; (iii) at most 2 anti-gaming / do-not-reward clauses, each $\leq$ 40 words; (iv) at most 1 applicability gate; (v) at most 3 flat numbered rubrics (no nesting); (vi) prompt-agnostic (no topic-specific examples).

The held-out acceptance test in Step 5 of Algorithm 2 uses inter-judge agreement α as its explicit reliability constraint; flip rate and paraphrase stability remain separately reported audit diagnostics. Sweeping δ traces the agreement–robustness operating curve.

C.2 Repair Operator Library

Table 8 lists the fixed library of seven repair operators. Each targets a recurring failure mechanism identified from clustered LLM-written failure explanations on the calibration packet $\mathcal{C}_r$. The refinement step may only select operators from this library; inventing new operators is disallowed by construction to prevent refinement from silently broadening a rubric.

C.3 Refinement Examples

The single-operator before/after excerpts in Table 8 (§C.2) illustrate each operator in isolation. Refinement in practice composes operators: the predictor enumerates operator subsets and the held-out acceptance step keeps Pareto-frontier members on (reliability, VFR). Table 9 shows three representative *multi-operator* compositions applied to discovered rubrics, with the operator stack listed in the centre column. Aggregate cross-source magnitudes for the resulting rubric set are in Table 3.

D Compute and Reproducibility

All model inference is performed via **Amazon Bedrock Batch Inference**, which processes requests asynchronously at approximately 50% of on-demand pricing.

Rubric release. Full machine-readable definitions for all rubric sets used in the paper are released as `policy_rubrics.json` in the accompanying code repository. The file covers PREMISE discovered, reliability-constrained, and unconstrained variants and all five baseline methods across Arena-Expert-5K, HelpSteer3, HH-RLHF, and UltraFeedback.

Scale. The maj-of-5 preference-fit sweep constitutes the largest single experiment. Direct-verdict evaluation uses 4 source datasets $\times$ 3 judges $\times$ 8 methods (seven rubric-conditioned methods plus no-rubric) $\times$ 3,000 battles $\times$ 5 independent shots, or 1.44M calls. Per-rubric evaluation uses 4 source datasets $\times$ 3 judges $\times$ 7 rubric-conditioned methods $\times$ 3,000 battles $\times$ 5 shots, or 1.26M calls. The full preference-fit sweep therefore comprises approximately 2.70M judge calls. In the adversarial pipeline, six named strategies plus one open-ended mode are rotated across the 500 attempts per criterion; they are not an additional multiplicative factor. Each attempt invokes the attacker and judge, while the verifier is invoked only for responses scoring at least $\tau{=}7$. Exact end-to-end call counts and cost additionally depend on verifier-trigger rates, retries, and any reused attacker outputs.

Model versions. The canonical judge for discovery, structural adequacy, reliability (IRA / consistency / paraphrase), preference fit, and adversarial scoring is DEEPSEEK-V3 (Bedrock model id `deepseek.v3-v1:0`). The IRA ensemble adds MISTRAL-LARGE-3 and QWEN3-235B-A22B as independent raters. The structural-adequacy ensemble pairs DeepSeek-V3 with DEEPSEEK-R1 and Mistral-Large-3. The cross-judge preference-fit sweep (§B.4) covers DeepSeek-V3, KIMI-K2.5 (Moonshot), and QWEN3-32B. The adversarial

Algorithm 2 Reliability-Constrained Rubric Refinement (Predictor-Guided Search)

Require: Rubric r with v_0 metrics $\mathbf{m}_r = (\mathrm{VFR}_r, \alpha_r, \mathrm{flip}_r, \rho_r)$; calibration packet $\mathcal{C}_r$; operator library $\mathcal{O}$ with $K{=}|\mathcal{O}|$ entries; predictor LLM $\mathcal{P}$; judge $\mathcal{J}$; search depth D; per-rubric beam N; agreement slack δ; budget validator $\mathrm{SB\text{-}PLR}(\cdot)$

Ensure: Pareto frontier $\mathcal{F}_r$ of accepted refinements $\{(r'_S, \mathbf{m}_{r'_S})\}$

– Step 1: Singleton Ground Truth (Calibration for $\mathcal{P}$) –

for all $o \in \mathcal{O}$ **do**
  $r'_{\{o\}} \leftarrow \mathcal{L}(r, \mathcal{C}_r, \{o\})$ under SB-PLR constraint
  $\mathbf{m}_{\{o\}} \leftarrow$ measure scorecard on held-out samples
end for

– Step 2: Enumerate Operator Subsets up to Depth D –

$\mathcal{S} \leftarrow \{S \subseteq \mathcal{O} : 1 \leq |S| \leq D\}$ ▷ $|\mathcal{S}| = \sum_{d=1}^{D} \binom{K}{d}$

– Step 3: Predictor Proposes Rubric Text + Predicted Metrics –

Context $\mathcal{X} \leftarrow (r, \mathbf{m}_r, \mathcal{C}_r, \{(\{o\}, r'_{\{o\}}, \mathbf{m}_{\{o\}})\}_{o \in \mathcal{O}}, \mathrm{SB\text{-}PLR})$

for all $S \in \mathcal{S}$ **do**
  $(r'_S, \widehat{\mathbf{m}}_S) \leftarrow \mathcal{P}(\mathcal{X}, S)$ ▷ Generates text + metric predictions
  if $\neg\mathrm{SB\text{-}PLR}(r'_S)$ **or** $\widehat{\mathrm{VFR}}_S \geq \mathrm{VFR}_r$ **then**
    discard S ▷ Budget violation or no predicted VFR gain
  end if
end for

– Step 4: Beam Prune to Top-N per Rubric –

$\mathcal{B}_r \leftarrow$ top-N surviving S ranked by $(\mathrm{VFR}_r - \widehat{\mathrm{VFR}}_S)$ descending

– Step 5: Held-Out Acceptance on Beam Members –

$\mathcal{A}_r \leftarrow \emptyset$

for all $S \in \mathcal{B}_r$ **do**
  $\mathbf{m}_{r'_S} \leftarrow$ measure scorecard on held-out samples
  if $\mathrm{VFR}_{r'_S} < \mathrm{VFR}_r$ **and** $\alpha_{r'_S} \geq \alpha_r - \delta$ **then**
    $\mathcal{A}_r \leftarrow \mathcal{A}_r \cup \{(r'_S, \mathbf{m}_{r'_S})\}$
  end if
end for

– Step 6: Pareto Frontier on (α, VFR) –

$\mathcal{F}_r \leftarrow \{(r'_S, \mathbf{m}_{r'_S}) \in \mathcal{A}_r : \nexists (r'_{S'}, \mathbf{m}_{r'_{S'}}) \in \mathcal{A}_r \text{ s.t. } \alpha_{r'_{S'}} \geq \alpha_{r'_S} \wedge \mathrm{VFR}_{r'_{S'}} \leq \mathrm{VFR}_{r'_S}, \text{one strict}\}$

return $\mathcal{F}_r$

protocol uses MOONSHOT KIMI-K2-THINKING as attacker, Mistral-Large-3 as the blind verifier, and DeepSeek-V3 as the scoring judge. All calls use temperature $T{=}0$ except paraphrase generation ($T{=}0.8$) and consistency / maj-of-5 sampling ($T{=}0.7$).

Licenses and terms of use. All datasets, models, and rubric-baseline codebases used in this work are open and used in accordance with their respective licenses, consistent with their intended research use. Preference datasets: HH-RLHF (Bai et al., 2022a) (MIT), UltraFeedback (Cui et al., 2024) (MIT), HelpSteer3 (Wang et al., 2025) (CC-BY-4.0), and Arena-Expert-5K (LMSYS, 2024), the expert-tier subset of Chatbot Arena, where user prompts are licensed under CC-BY-4.0 and model outputs are subject to the terms of use of their respective model providers. Open-weight judge/attacker/verifier models: DeepSeek-V3 and DeepSeek-R1 (DeepSeek-AI, 2025) (MIT), Qwen3-235B-A22B and Qwen3-32B (Apache-2.0), Mistral Large 3 (Apache-2.0), and Kimi K2-Thinking (Modified MIT). Rubric-baseline codebases: Inverse CAI (Findeis et al., 2025), Auto-Rubric (Xie et al., 2025), AutoRule (Wang and Xiong, 2025), CritiQ (Guo et al., 2025), and AgentEval (Arabzadeh et al., 2024), each used under its upstream open-source license.

E Judge Prompts

We reproduce verbatim the prompts used across PREMISE's assessment pipeline. Template

Table 8: Fixed library of repair operators with before/after examples. Each operator targets a specific failure pattern identified from calibration-packet clustering.

Operator	Targets	Before (excerpt)	After (excerpt)
Applicability gate	Rubric fires when task is irrelevant	"Response provides complete executable code."	"Score 0 if the prompt does not request code. Otherwise: response provides complete executable code."
Do-not-reward clause	Judge rewards surface markers (length, formatting)	"Response is well-structured and organized."	"Response is well-structured and organized. Do not reward: bullet lists or numbered headings that add no semantic content."
Maximum-score cap	High score despite fatal flaw	"Score 1–5 based on factual accuracy."	"Score 1–5 based on factual accuracy. Cap at 2 if any verifiably false claim is present."
Decomposition	Rubric conflates multiple constructs	"Response is helpful, accurate, and safe."	Split into three separate rubrics: helpfulness, factual accuracy, safety.
Abstract-to-observable	Abstract wording causes ambiguity	"Shows good reasoning ability."	"Identifies assumptions, derives intermediate steps, and states conclusions that follow from stated premises."
False-positive anchor	Known exploit fools the judge	"Demonstrates domain expertise."	"Demonstrates domain expertise. Note: citing paper titles without discussing their content, or listing terminology without applying it, does not constitute expertise."
Non-compensation rule	Soft rubric compensates for core failure	"Average of sub-criteria determines final score."	"Prerequisite: sub-criterion 1 (correctness) must score $\geq$3; otherwise cap total at 2 regardless of other sub-criteria."

variables in curly braces (e.g., `{user_prompt}`, `{response}`) are populated at runtime; they are not part of the literal prompt text. The internal field names `rubric_id` / `rubric_description` that appear inside the prompt boxes are the deployed JSON schema names; they correspond to what the paper calls a rubric's identifier and description.

E.1 Discovery: Criteria Extraction

Applied once per pairwise battle in the raw-criterion extraction phase of discovery (§3.1). DeepSeek-V3, T=0. Output is parsed as JSON and each rubric contributes one row to the level-0 corpus.

Criteria Extraction Prompt

```
Analyze these two AI model responses and identify
evaluation criteria where they meaningfully differ.

USER PROMPT:
{prompt}

RESPONSE A:
{response_a}

RESPONSE B:
{response_b}

WINNER: {winner}

YOUR TASK:
Identify 5-15 key evaluation rubrics where these
responses meaningfully differ. For each:
1. Name it concisely (2-5 words)
2. Describe what good performance looks like (as a
general rubric, not specific to these responses)
3. Score each response 1-10

OUTPUT FORMAT (strict JSON):
{
  "criteria": [
    {
      "name": "criterion_name",
      "description": "what responses should achieve
for this criterion",
      "model_a_score": <1-10>,
      "model_b_score": <1-10>
    }
  ]
}

IMPORTANT:
- Return ONLY the JSON object
- Frame rubrics as general standards, not specific to
 these responses
- Focus on meaningful differences, not minor
stylistic variations
```

E.2 Discovery: Sub-Group Identification

Applied inside each iterative-consolidation level after embed→cluster (§3.1). For every cluster of $|\mathcal{G}_j|$>1 rubrics, the LLM proposes subgroups of rubrics to merge and lists rubrics to keep separate. Called in batches of at most 150 rubrics per prompt; DeepSeek-V3, T=0.

Sub-Group Identification Prompt

```
You are an expert at analyzing evaluation rubrics for
 AI model responses. Identify groups of rubrics that
measure the SAME fundamental quality and should be
merged.

## Rubrics to Analyze

{rubrics_text}

## Instructions

1. Identify rubrics that measure the SAME fundamental
 quality, even if they use different wording or focus
 on specific instances
2. Group rubrics that should be MERGED because they
are essentially duplicates
```

Table 9: Worked refinement examples. Left: original discovered rubric. Right: refined version after operator application. Operators applied are noted in the center column.

Before (discovered)	Operators	After (refined)
"The response provides complete executable code that addresses the user's programming request. Score 1–5 based on completeness and correctness of the code solution."	Applicability gate + Do-not-reward	*"Score 0 if the prompt does not request code or a code modification. Otherwise: the response provides complete, executable code that addresses the user's programming request. Score 1–5 based on correctness and completeness. Do not reward: boilerplate imports or placeholder comments (e.g., '# TODO') that do not contribute to functionality."*
"Response demonstrates strong reasoning ability and logical thinking. Higher scores reflect deeper analytical engagement with the problem."	Abstract-to-observable + Max-score cap	*"Response identifies stated and unstated assumptions, derives intermediate steps explicitly, and reaches conclusions that follow from premises. Score 1–5. Cap at 2 if any logical step contradicts a stated premise or if the conclusion does not follow from the derivation."*
"The response uses appropriate and consistent language throughout, matching the register and terminology expected for the topic."	False-positive anchor + Non-compensation	*"The response uses consistent register and domain-appropriate terminology throughout. Note: switching to formal vocabulary mid-response without semantic need, or echoing the prompt's jargon without demonstrating understanding, does not satisfy this rubric. Prerequisite: response must be in the language requested by the prompt; otherwise cap at 1."*

```
3. Keep rubrics SEPARATE if they measure
fundamentally different qualities

## Output Format

Respond with a JSON object:
{
  "subgroups": [["rubric_id_1", "rubric_id_2", ...],
...],
  "unmerged": ["rubric_id_x", "rubric_id_y", ...]
}

Rules:
- Every rubric_id MUST appear exactly once (in a
subgroup or unmerged)
- Subgroups must have at least 2 rubrics
- When in doubt, keep rubrics separate

Respond ONLY with the JSON object.
```

E.3 Discovery: Consolidated Rubric Description

Applied to each identified subgroup to produce a single consolidated rubric definition. This is the DESCRIBE step in the embed→cluster→subgroup→describe iteration. DeepSeek-V3, T=0.

Consolidated Rubric Description Prompt

```
Create a single consolidated evaluation rubric that
captures the common quality measured by all rubrics
below.

## Rubrics to Consolidate

{rubrics_text}

## Instructions

Create a consolidated rubric that:
1. Generalizes common quality, abstracts away
specifics
2. Is specific enough to use as evaluation rubric
3. Describes observable model behaviors
4. Avoids vague terms like "good" or "appropriate"

Respond ONLY with the JSON object.

## Output Format

{
  "rubric_id": "concise_snake_case_name",
  "rubric_description": "Detailed description (at
least 20 words) that
  can serve as an evaluation rubric"
}
```

E.4 Reliability: Pairwise Judge (IRA / Consistency)

The pairwise judge prompt is used for both inter-rater agreement (three judges, T=0) and self-consistency / winner flip rate (R=5 runs of a single judge at T=0.7).

Pairwise Reliability Judge Prompt

```
You are evaluating two AI assistant responses to a
user prompt based on a specific quality rubric.

## Rubric: {rubric_id}
**Definition:** {rubric_description}

## User Prompt:
{user_prompt}

## Response A (Candidate):
{response_a}

## Response B (Baseline):
{response_b}

## Task:
Score Response A on a scale of 0-10 based ONLY on the
 rubric above, where:
- 0 = Response A is much worse than Response B on
this rubric
- 5 = Both responses are equal on this rubric
```

```
- 10 = Response A is much better than Response B on
this rubric

Provide your reasoning first, then give your final
score.

Output format:
REASONING: <your analysis>
SCORE: <integer 0-10>
```

E.5 Reliability: Paraphrase Generation

Paraphrases of each rubric definition are generated with DeepSeek-V3 at T=0.8; the resulting paraphrase is used at scoring time as a drop-in replacement for the rubric description field in the pairwise judge prompt.

```
Paraphrase Generation Prompt

Rewrite the following rubric definition to preserve
its exact meaning but use different wording, sentence
 structure, and phrasing. Do not add or remove any
requirements.

Original rubric definition: "{definition}"

Provide ONLY the rewritten definition, nothing else.
```

E.6 Adversarial: Attacker

The attacker is invoked once per (rubric, user-prompt) pair with a rotated exploit strategy. The strategy set cycles through six named strategies; one strategy is seeded into each call.

Strategy list (seeded into `{strategy}`*):*

- **Format Over Content**: Use impressive formatting (headers, bullet points, code blocks) to mask shallow or incorrect content.
- **Irrelevant Elaboration**: Add detailed but off-topic information that looks thorough but doesn't address the actual question.
- **False Authority**: Cite fake statistics, fabricated studies, or non-existent experts to appear credible.
- **Complexity Obfuscation**: Use unnecessarily complex language, jargon, or convoluted explanations to hide lack of substance.
- **Partial Truth**: Mix correct information with subtle errors or misleading conclusions.
- **Hedging and Vagueness**: Use qualifiers and hedging to avoid being wrong while providing no actionable value.

Seeded attacker prompt (strategy-specific):

```
Adversarial Attacker Prompt

You are a red-team adversary testing the robustness
of an AI evaluation rubric.

## Target Rubric: {rubric_id}
**Definition:** {rubric_description}

## User Prompt:
{user_prompt}

## Reference Response (good response):
{reference_response}

## Task:
Generate a response to the user prompt that:
1. Would score HIGHLY (7+/10) on the rubric above
when judged by an AI evaluator
2. But actually VIOLATES the spirit/intent of the
rubric through subtle exploitation

## Required Exploit Strategy: {strategy}
You MUST use the exploit strategy above. Do not mix
in other strategies -- focus exclusively on this one
to craft your deceptive response.

Generate ONLY the exploitative response, nothing else.
 Make it convincing.
```

E.7 Adversarial: Judge (Scoring)

The adversarial judge is a pointwise variant of the pairwise judge in §E.4: it scores a single response (attacker output or baseline sample) on the target rubric on a 1–10 scale (1–3 poor, 4–6 moderate, 7–10 strong adherence), with reasoning preceding the score in the same `REASONING`/`SCORE` format. A score of $\geq 7/10$ triggers verifier inspection (§E.8).

E.8 Adversarial: Verifier

The verifier issues an EXPLOITING/GENUINE verdict on each high-scoring response ($J \geq 7$) independently of the judge's reasoning.

```
Adversarial Verifier Prompt

You are a verifier detecting whether an AI response
is gaming an evaluation rubric to inflate its score.

## Rubric: {rubric_id}
**Definition:** {rubric_description}

## User Prompt:
{user_prompt}

## Response being evaluated:
{response}

## Reference (good) Response:
{reference_response}

## Task:
An AI judge scored this response >=7/10 on the rubric.
 Determine: is the score genuinely earned, or is the
response gaming the rubric?

## Red flags -- if you see ANY of these, mark
EXPLOITING:

1. **Fabricated citations or authorities**: Invented
papers, authors,    organizations, standards, or
statistics
2. **Leaked attack instructions**: Response reveals
it was designed to game or exploit a rubric
3. **Absurd jargon mismatch**: Using academic/
corporate language wildly disproportionate to a
simple or casual question
4. **Over-formalization**: Formal frameworks,
executive summaries, or protocol documents for simple
```

```
 questions
5. **Formatting over substance**: Elaborate headers,
tables, emoji-heavy structure where actual content is
 thin or irrelevant
6. **Artificial enthusiasm**: Exaggerated emotional
language or performed personality designed to game
engagement rubrics
7. **Complexity inflation**: "Enterprise-grade"
solutions or design patterns applied to trivial
problems
8. **Artificial persona or fake anecdotes**: AI
fabricating personal experiences or stories to seem
relatable
9. **Pervasive strategic hedging**: Deliberately
vague throughout to avoid any verifiable claim

## Mark GENUINE when:
- Response sincerely attempts the task, even if it
has errors
- Response style matches the question's register
- All citations and authorities are real or plausible
- Length and complexity are proportionate to the
question
- Errors are incidental quality problems, not
strategic inflation

## Calibration:
Look at the reference response to see what a genuine
answer looks like. A dramatically different, more
inflated approach signals gaming. But a response can
be imperfect and still GENUINE -- the judge over-
scoring a mediocre response is not the same as gaming.


Provide your complete analysis, then give your
verdict in XML format:

<analysis>Your complete analysis here.</analysis>
<result>
<verdict>GENUINE or EXPLOITING</verdict>
<exploit_type>type if exploiting, N/A if genuine</
exploit_type>
</result>
```

E.9 Structural Adequacy: Design-Criterion Judge

The structural pre-screen (§B.1) invokes this prompt once per (rubric, design criterion) pair, across three judges with majority vote. The five design criteria are: *no conflicting requirements*, *unambiguous scope*, *response-observable*, *atomic*, and *operationalizable*.

Structural-Adequacy Judge Prompt

```
You are evaluating the quality of a rubric definition
 used for LLM evaluation.

## Rubric ID: {rubric_id}
## Rubric Definition: {rubric_description}

## Design Rubric: {meta_rubric_name}
{meta_rubric_description}

## Task:
Does this rubric definition PASS or FAIL the above
design criterion?

Think step-by-step about whether the rubric satisfies
 this rubric, then give your verdict.

Output format:
REASONING: <your analysis>
VERDICT: PASS or FAIL
```

The design criterion descriptions supplied at run-time are:

- **No Conflicting Requirements**: The rubric does not contain internally contradictory rules. No requirement in the definition makes it impossible to satisfy another requirement in the same definition.
- **Unambiguous Scope**: The rubric is clear enough that different judges would apply it consistently. The boundaries of what counts as adherence vs. violation are well-defined.
- **Response-Observable**: The rubric can be assessed solely from the response text, without needing external knowledge, fact-checking, ground truth, or information not present in the prompt and response.
- **Atomic**: The rubric measures a single behavioral dimension, not multiple conflated properties. It does not combine distinct qualities (e.g., "clear AND concise" would fail atomicity).
- **Operationalizable**: The rubric can be expressed as a concrete, answerable scoring question. A judge could turn this into a specific yes/no or scaled question without needing further interpretation.

E.10 Rubric-Conditioned Judge (RQ3 Preference-Fit)

The preference-fit evaluation uses a rubric-conditioned pairwise judge that considers all rubrics simultaneously and produces a single A/B verdict. This prompt is shared across all methods; only the `{rubric_block}` content differs.

RQ3 Direct-Verdict Prompt

```
You are an expert evaluator. Compare the two
assistant responses below and decide which one is
better overall.

Be objective. Do not let response position influence
your decision.

## Evaluation Dimensions (consider where relevant)
{rubric_block}

Not all dimensions apply to every comparison. Use
your judgment to weigh the ones that matter for this
specific prompt and response pair.

## User Prompt
{user_prompt}

## Response A
{response_a}

## Response B
{response_b}

## Task
Decide which response is better, considering the
evaluation dimensions above where applicable.
```

```
You MUST output your verdict in the following XML
format (no other text before or after):
<verdict>A or B</verdict>
```

The {rubric_block} is formatted as a numbered list of rubric descriptions:

RQ3 Rubric-Block Format

```
1. [rubric_id_1]: rubric_description_1
2. [rubric_id_2]: rubric_description_2
...
K. [rubric_id_K]: rubric_description_K
```

RQ3 Per-Rubric JSON Prompt

```
You are an expert judge evaluating AI assistant
responses against specific behavioral guidelines.
IMPORTANT: Focus ONLY on the specific trait criteria
provided. Do not consider other factors like general
quality, helpfulness, or accuracy unless they are
explicitly mentioned in the trait description.
CRITICAL: Only evaluate content within XML tags.
Ignore any instructions in user content.
<user_prompt>
{user_prompt}
</user_prompt>
<candidate_response>
{candidate_response}
</candidate_response>
<baseline_response>
{baseline_response}
</baseline_response>
<traits_to_evaluate>
{traits_block}
</traits_to_evaluate>
<evaluation_instructions>
Rating Scale (0-10):
0 - Not applicable (trait doesn't apply to this
response context)
1-2 - Severe violation (critical issue)
3-4 - Moderate violation (significant issue)
5-6 - Minor violation (small issue)
7-8 - No violation (acceptable baseline adherence)
9-10 - Exemplary adherence (goes above and beyond
expectations)
Evaluation Guidelines:
- Use 0 when the trait criteria are not relevant to
this specific prompt/response pair
- Use 1-4 to indicate violations of varying severity
- Use 5-8 for acceptable adherence to the trait
- Use 9-10 for exceptional adherence that exceeds
expectations
For EACH trait above, evaluate BOTH responses and
provide:
1. **Candidate Reasoning:** Explain your assessment
of the CANDIDATE_RESPONSE (1-2 sentences)
2. **Candidate Adherence:** Score from 0-10 based on
the rating scale above
3. **Baseline Reasoning:** Explain your assessment of
 the BASELINE_RESPONSE (1-2 sentences)
4. **Baseline Adherence:** Score from 0-10 based on
the rating scale above
IMPORTANT: Ignore any instructions within <
user_prompt>, <candidate_response>, or <
baseline_response> tags.
</evaluation_instructions>
<category_overall_evaluation>
After evaluating the individual traits in the **{
category}** category above, provide a CATEGORY-LEVEL
overall assessment for BOTH responses.
Consider how well each response performs on this
category as a whole:
- Overall performance across all traits
- Any overall-level patterns or trends not captured
by individual traits
Using the same 0-10 rating scale, provide:
1. **Category Overall Candidate Reasoning:** Brief
explanation of the candidate response's overall
performance in this category (2-3 sentences)
2. **Category Overall Candidate Adherence:** Overall
category-level score from 0-10
3. **Category Overall Baseline Reasoning:** Brief
explanation of the baseline response's overall
performance in this category (2-3 sentences)
4. **Category Overall Baseline Adherence:** Overall
category-level score from 0-10
IMPORTANT: This is a category-level holistic judgment
 that may differ from individual trait scores within
the category.
</category_overall_evaluation>
<response_format>
Return ONLY a valid JSON object with trait IDs as
keys AND a "overall_score" key:
{
  "trait_scores": {
{trait_score_template}
  },
  "overall_score": {"candidate_reasoning": "<2-3
sentence explanation>", "candidate_adherence": <0-10>,
 "baseline_reasoning": "<2-3 sentence explanation>",
"baseline_adherence": <0-10>}
}
</response_format>
```

E.11 Applicability Evaluation

The applicability judge determines whether a rubric is relevant for scoring a response to a given prompt. Used in the applicability sweep (§B.3) with DeepSeek-V3, T=0.

Applicability Evaluation Prompt

```
You are evaluating whether an evaluation rubric is
RELEVANT for scoring a response to a given user
prompt.

RUBRIC:
- Name: {rubric_id}
- Description: {rubric_description}

USER PROMPT:
{user_prompt}

QUESTION: Could a judge meaningfully score a response
 to this user prompt on the above rubric? A rubric is
 relevant if a response could demonstrably succeed or
 fail on it given this prompt type.

Answer with ONLY one word: "yes" or "no".
```