Beyond Blind Compliance: Benchmarking Task Verification in OCR Reasoning

Yue Zhou[1] **Yuan Wu**[1*] **Yi Chang**[1,2,3]
[1]School of Artificial Intelligence, Jilin University
[2]Engineering Research Center of Knowledge-Driven Human-Machine Intelligence, MOE, China
[3]International Center of Future Science, Jilin University
yuezhou24@mails.jlu.edu.cn, {yuanwu, yichang}@jlu.edu.cn

Abstract

Multimodal Large Language Models (MLLMs) have achieved strong performance on OCR-centric document understanding and text-rich visual reasoning benchmarks. Yet existing evaluations largely assume that every task is valid and answerable. In real-world OCR scenarios, this assumption often fails: questions may rely on illegible text, occluded evidence, nonexistent visual targets, contradictory premises, or missing variables. We study this reliability gap as **OCR-grounded Task Verification**: before answering, a model should determine whether the Image Premise (IP), Textual Premise (TP), and Question (Q) jointly define an executable task. We introduce VeriOCR-Bench, a 1,800-sample human-verified benchmark built from source images drawn from 8 OCR-related datasets and spanning 8 real-world image domains, with controlled, image-grounded diagnostic tasks. It contains 1,600 trap-injected invalid tasks across 8 trap types and four verification dimensions—Visual, Contextual, Factual, and Logical—plus 200 trap-free controls for measuring over-refusal. Built with a Visual Atomic Fact (VAF)-anchored pipeline and full human auditing, VeriOCR-Bench enables decoupled evaluation of task verification, root-cause diagnosis, and over-refusal. Evaluating 15 MLLMs reveals persistent blind compliance, diagnosis failures, and prompt-induced over-refusal, exposing a critical reliability gap in current OCR reasoning systems. The code is available at: https://github.com/zy001122/Beyond-Blind-Compliance.

1 Introduction

Multimodal Large Language Models (MLLMs) have achieved rapid progress in document understanding and text-rich visual reasoning (OpenAI, 2023; Team et al., 2024; Bai et al., 2023; Liu et al., 2023; Chen et al., 2024). Recent OCR-centric benchmarks, including OCRBench (Liu et al., 2024), DocVQA (Mathew et al., 2021), OmniDocBench (Ouyang et al., 2025), SEED-Bench-2-Plus (Li et al., 2024), and OCR-Reasoning (Huang et al., 2026), have advanced evaluation from text recognition to layout understanding and multi-step reasoning over visually rich inputs. However, these benchmarks largely assume that every task is valid and answerable: the image contains the required evidence, the textual premise does not conflict with the image, and the question is well-posed.



Figure 1: **Task verification in OCR reasoning.** A task consists of an image premise (IP), textual premise (TP), and question (Q). The example shows an invalid task where the TP contradicts the visual evidence. Blind execution follows the false premise, whereas task verification detects the IP–TP inconsistency before answering.

This valid-task assumption masks a critical reliability failure. In real-world OCR scenarios, users may ask questions based on blurred or occluded text, refer to nonexistent visual targets, impose incompatible contexts, contradict visible evidence, or omit variables required for reasoning. Blindly answering such tasks can produce confident but unsupported outputs. Therefore, a reliable MLLM should not only solve OCR reasoning tasks, but also verify whether the task should be executed in the first place.

To address this gap, we study **OCR-grounded Task Verification**. We formulate each task as a

*Corresponding author.

Proceedings of the 2026 Conference on Empirical Methods in Natural Language Processing, pages 22122–22155
October 24-29, 2026 ©2026 Association for Computational Linguistics

triplet $T = (IP, TP, Q)$, where IP is the image premise, TP is the user-provided textual premise, and Q is the reasoning question. The model must determine whether the resulting task is executable before answering. When the task is invalid, the desired behavior is to refuse execution and identify the source of invalidity rather than hallucinating an answer. Figure 1 illustrates the contrast between blind task execution and task verification.

We introduce **VeriOCRBench**, a benchmark for evaluating OCR-grounded task verification. VeriOCRBench contains 1,800 human-verified samples drawn from 8 OCR-related datasets and spanning 8 real-world image domains. It includes 1,600 trap-injected invalid tasks and 200 trap-free controls. The invalid tasks cover 8 *Trap Types* organized into four **Verification Dimensions**: Visual, Contextual, Factual, and Logical. This design enables us to evaluate both invalid-task detection and over-refusal on valid tasks.

Constructing such a benchmark requires ensuring that invalid tasks are plausible, visually grounded, and verifiably unexecutable. To this end, we design a **Visual Atomic Fact (VAF)-anchored construction pipeline**. We first extract deterministic OCR evidence from source images, then generate taxonomy-guided traps grounded in selected visual facts or physically modified visual evidence. All samples undergo full human auditing to ensure visual grounding, trap validity, zero trap disclosure, and reasoning beyond direct text extraction.

For evaluation, we introduce a decoupled protocol measuring task verification, root-cause diagnosis, and over-refusal. Across 15 MLLMs and two OCR-text pipeline baselines, we find systematic blind compliance, diagnosis failures, and prompt-induced over-refusal. A prompt ablation further shows that stronger verification prompts are not always better, motivating a trade-off among invalid-task detection, diagnosis, and over-refusal on valid tasks.

Our main contributions are threefold:

- **OCR-grounded Task Verification and Diagnostic Metrics.** We introduce *Task Verification* as a reliability evaluation paradigm for OCR reasoning, shifting evaluation from answer-only task execution to deciding whether a task should be answered. We further define complementary metrics for task detection, root-cause diagnosis, and over-refusal, enabling a more fine-grained assessment of verification behavior.

Benchmark	Ext	Reason	Invalid	Diag	Ctrl
DocVQA	✓	△	✗	✗	✗
ChartQA	✓	✓	✗	✗	✗
OCRBench v2	✓	△	✗	✗	✗
OmniDocBench	✓	✗	✗	✗	✗
SEED-Bench-2-Plus	✓	△	✗	✗	✗
OCR-Reasoning	✓	✓	✗	✗	✗
MM-UPD	△	△	✓	✗	△
MAD-Bench	△	△	△	✗	✗
VeriOCRBench	✓	✓	✓	✓	✓

Table 1: **VeriOCRBench vs. representative text-rich visual and multimodal reliability benchmarks.** Ext denotes text extraction; Reason denotes reasoning beyond direct extraction; Invalid denotes invalid-task verification; Diag denotes root-cause diagnosis; Ctrl denotes trap-free valid controls for over-refusal evaluation; △ denotes partial or indirect coverage.

- **The VeriOCRBench Benchmark.** We present VeriOCRBench, a 1,800-sample human-verified benchmark built from source images across 8 real-world image domains, covering 8 trap types and four verification dimensions. Built with a Visual Atomic Fact (VAF)-anchored construction pipeline and full human auditing, VeriOCRBench contains both trap-injected invalid tasks and trap-free controls, providing a rigorous testbed for grounded task verification.
- **Verification–Refusal Trade-off and Prompt Sensitivity.** We reveal recurring failure patterns in current OCR reasoning systems: blind compliance with invalid tasks, a gap between invalid-task detection and correct diagnosis, and prompt-induced over-refusal on valid inputs. A milder *verify-if-needed* prompt reduces over-refusal for representative models, showing that stronger verification prompts are not always better and highlighting a trade-off among detection, diagnosis, and over-refusal on valid inputs.

2 Related Work

2.1 Text-Rich Visual Reasoning Benchmarks

Systematic evaluation is essential for characterizing the capabilities and limitations of large language models (Chang et al., 2024). Text-rich visual reasoning has become a central capability of modern MLLMs. Early benchmarks such as

DocVQA (Mathew et al., 2021), TextVQA (Singh et al., 2019), InfoVQA (Mathew et al., 2022), and ChartQA (Masry et al., 2022) mainly evaluate document, scene-text, infographic, and chart understanding, with many tasks focusing on extracting visible text, locating relevant information, or answering questions grounded in text-rich images. More recent OCR-centric benchmarks, including OCRBench (Liu et al., 2024), OCRBench v2 (Fu et al., 2025), OmniDocBench (Ouyang et al., 2025), SEED-Bench-2-Plus (Li et al., 2024), and OCR-Reasoning (Huang et al., 2026), further extend evaluation toward broader OCR perception, document parsing, layout understanding, and multi-step reasoning. These text-rich visual benchmarks mainly evaluate execution on valid tasks. As summarized in Table 1, VeriOCRBench complements them by testing whether MLLMs can detect unexecutable OCR reasoning tasks, diagnose the source of invalidity, and avoid over-refusing valid controls.

2.2 Reliability Failures in Multimodal Reasoning

MLLMs remain vulnerable to visual hallucination (Li et al., 2023; Guan et al., 2024), while language models can also exhibit sycophancy (Wei et al., 2023; Sharma et al., 2024; Perez et al., 2023). These failures are particularly harmful in OCR-centric reasoning, where answers depend on precise visual evidence such as readable text, numbers, tables, and layout relations. When such evidence is unreadable, missing, contradicted by the textual premise, or insufficient for solving the question, blind task execution can produce confident but unsupported answers. At the same time, over-cautious behavior can lead models to reject valid requests (Röttger et al., 2024), so reliable verification must balance invalid-task detection with avoiding unnecessary refusal on valid requests. More directly related, MM-UPD (Miyai et al., 2025) evaluates unsolvable-problem detection in multiple-choice multimodal question answering through Absent Answer Detection, Incompatible Answer Set Detection, and Incompatible Visual Question Detection, together with paired standard/UPD questions and Dual Accuracy. MAD-Bench (Qian et al., 2024) evaluates MLLM robustness to deceptive image–prompt inconsistencies across five categories, including Text Recognition, using GPT-4o-judged response accuracy. VeriOCRBench focuses on OCR-grounded free-form reasoning and separately evaluates invalid-task detection, sample-specific root-cause diagnosis, and over-refusal on dedicated valid controls.

3 VeriOCRBench

3.1 Definition of Task Verification

We define a text-rich visual reasoning task as a triplet $T = (IP, TP, Q)$, where IP is the Image Premise containing visual evidence such as legible text, numbers, tables, layout relations, and document structures; TP is the user-provided Textual Premise; and Q is the reasoning question.

A task is executable only when the required evidence in IP is available, the image-grounded content in TP and Q is consistent with IP, and the joint information in IP and TP is sufficient to answer Q. We formalize this with a binary validity function $\mathcal{V}(T) \in \{0, 1\}$. If $\mathcal{V}(T) = 1$, the model should produce a standard answer A_{ans}; if $\mathcal{V}(T) = 0$, it should produce a grounded refusal A_{ref} that identifies the source of invalidity:

$$\mathcal{M}(T) = \begin{cases} A_{\text{ans}}, & \text{if } \mathcal{V}(T) = 1, \\ A_{\text{ref}}, & \text{if } \mathcal{V}(T) = 0. \end{cases}$$

Invalidity may arise from unavailable visual evidence, image–text contradictions, nonexistent visual targets, vague references, logical inconsistency, or missing variables. Therefore, Task Verification evaluates whether MLLMs can determine not only how to answer a text-rich visual reasoning task, but also whether it should be answered at all. A more formal statement of the task representation and validity boundary conditions is provided in Appendix A.

3.2 Taxonomy of Task Verification Traps

VeriOCRBench evaluates whether MLLMs can verify task executability before answering, rather than blindly following a user premise. In each sample, the model must compare the Textual Premise (TP) and Question (Q) against the Image Premise (IP). All questions require reasoning beyond direct text extraction, such as numerical calculation, cross-field comparison, or logical deduction, forcing models to perform task verification and task execution jointly.

We categorize invalid tasks into 8 **Trap Types**, organized into four **Verification Dimensions**: Visual, Contextual, Factual, and Logical.

- **Visual Dimension.** The task cannot be reliably solved because the required visual evidence is unavailable or unreadable. It includes

Type 1: Image Degradation, where critical text is blurred, noisy, or otherwise below readability, and **Type 2: Occluded Target**, where necessary evidence is masked, cropped, or hidden.

- **Contextual Dimension.** The user-provided context is incompatible with the image. It includes **Type 3: Domain Mismatch**, where an inappropriate domain assumption is imposed on the image, and **Type 4: Hallucinatory Target**, where TP or Q refers to a text block, entity, or visual target that does not exist in the image.

- **Factual Dimension.** The task contains fine-grained claims that conflict with visible evidence or lack a unique visual anchor. It includes **Type 5: Fact Tampering**, where an attribute or value of an existing visual entity is falsified, and **Type 6: Vague Reference**, where an under-specified reference creates multiple plausible visual targets.

- **Logical Dimension.** The requested reasoning is logically ill-posed even if the image is readable. It includes **Type 7: Logical Paradox**, where the premise contradicts an indisputable visual relation, and **Type 8: Missing Variable**, where required information for solving the task is absent.

Trap-Free Controls. To separate genuine verification ability from a generic refusal tendency, VeriOCRBench also includes trap-free control tasks. These valid tasks follow a zero-text-leakage protocol to preserve multimodal dependency and are used to measure the **Over-Refusal Rate (ORR)**. Detailed trap definitions and expected model behaviors are provided in Appendix B, with representative examples in Appendix C.

3.3 Dataset Construction

Source and Domain Diversity. We construct VeriOCRBench from raw images drawn from 8 established OCR and text-rich visual benchmarks: OCRBench v2 (Fu et al., 2025), OCR-Reasoning (Huang et al., 2026), OmniDocBench (Ouyang et al., 2025), MMTab (Zheng et al., 2024), ChartX (Xia et al., 2025), DocVQA (Mathew et al., 2021), M6Doc (Cheng et al., 2023), and GoodsAD (Zhang et al., 2024). These source images span 8 real-world image domains: product packaging, digital UI, mass media, public display, science, education, administrative documents, and finance. We use these benchmarks only as image sources; all Textual Premises (TP) and Questions (Q) are newly constructed. The final dataset contains 1,800 human-verified samples, including 1,600 trap-injected invalid tasks and 200 trap-free controls. Detailed statistics are provided in Appendix D.

As shown in Figure 2, VeriOCRBench is built through a VAF-anchored construction pipeline followed by full human auditing.

Step 1: Visual Atomic Fact Extraction. We extract Visual Atomic Facts (VAFs) from each pristine image IP using PaddleOCR (PP-OCRv5) (Cui et al., 2025), obtaining textual units and bounding boxes $\mathcal{F} = \{f_1, \ldots, f_n\}$. These VAFs serve as deterministic evidence anchors for trap construction.

Step 2: VAF-grounded Task Construction. We construct candidate tasks using four generator models: GPT-4o (OpenAI, 2024), Gemini-3.1-Pro (Google DeepMind, 2026), Claude-4.5-Sonnet (Anthropic, 2025), and Llama-4-Maverick (Meta AI, 2025), selected to provide diverse proprietary and open-weight generation sources. We construct tasks through three branches: textual mutation traps (Types 3–8), visual degradation traps (Types 1–2), and trap-free controls. Textual traps mutate premises or questions based on selected VAFs, visual traps degrade or occlude required evidence, and controls remain valid while requiring joint visual-textual reasoning. Across all branches, we enforce zero text leakage so that Q requires reasoning over the image rather than directly revealing the answer.

Step 3: Human Auditing and Rectification. All 1,800 samples are manually audited for VAF accuracy, control-task solvability, trap-task unsolvability, zero trap disclosure, trap-type alignment, and reasoning beyond direct text extraction. Overall, 93% of samples pass without modification, while 7% are manually rectified. The full checklist, statistics, and generation prompts are provided in Appendix D.

3.4 Evaluation Metrics

We evaluate task verification with three complementary metrics: **Task Verification Rate (TVR)**, **Diagnosis Accuracy (DA)**, and **Over-Refusal Rate (ORR)**. In the main experiments, each metric is reported under two prompting paradigms:



Figure 2: **Overview of the VeriOCRBench construction pipeline.** We first extract Visual Atomic Facts (VAFs) from source images, then generate trap-injected and trap-free tasks grounded in these facts, followed by full human auditing to ensure validity and quality.

proactive, where models receive no explicit verification instruction, and *assisted*, where models are instructed to verify task validity before answering. We denote proactive and assisted Task Verification Rate as *PTVR* and *ATVR*, respectively, while the corresponding Diagnosis Accuracy and Over-Refusal Rate metrics use the prefixes *p-* and *a-*. All verification and diagnosis metrics are computed over the full set of trap-injected samples, rather than only over samples where the model already refuses. Formal definitions are provided in Appendix E.

Task Verification Rate (TVR). TVR measures the percentage of trap-injected invalid samples for which the model correctly recognizes that the requested task is unexecutable. *PTVR* is evaluated under the proactive setting, while *ATVR* is evaluated under the assisted setting. This metric captures whether the model can detect invalid tasks instead of blindly executing them.

Diagnosis Accuracy (DA). DA measures the percentage of all trap-injected samples for which the model both detects the invalid task and correctly identifies the ground-truth trap mechanism according to the Trap Logic Trace. Since DA uses the same denominator as TVR, it evaluates end-to-end diagnostic success rather than conditional accuracy among already rejected samples. This penalizes generic refusals and incorrectly rationalized rejections.

Over-Refusal Rate (ORR). ORR measures the percentage of trap-free control samples that the model incorrectly rejects. This metric evaluates whether verification behavior becomes overly conservative on valid tasks, especially under assisted prompting.

3.5 Evaluation Protocols

We evaluate each model through three stages: model inference, semantic scoring with LLM-as-a-Judge, and judge reliability validation.

Model Inference. Each model is evaluated under two settings. In the *proactive* paradigm, the model receives the standard input triplet (IP, TP, Q) without any explicit verification instruction. In the *assisted* paradigm, we append a meta-instruction asking the model to verify whether the requested task is completable based on the Image Premise before answering.

LLM-as-a-Judge. We use GPT-4o with temperature 0.0 as the primary semantic judge and require structured JSON outputs. For trap-injected samples, the judge evaluates each response using two response-level fields: *Detection Status* (`is_rejected`), which records whether the response rejects, challenges, or corrects the flawed premise before proceeding, and *Diagnostic Correctness* (`is_rationale_correct`), which records whether the stated reason matches the ground-truth *Trap Logic Trace*. For trap-free controls, the judge evaluates whether the model incorrectly rejects a valid task. Complete judge prompts and output schemas are provided in Appendix F.

Judge Reliability Validation. Because GPT-4o is also an evaluated model, we validate its use as the primary judge. In a human-validation study of 286 model responses, GPT-4o achieves substantial

agreement with adjudicated human labels for rejection detection (85.66%, $\kappa = 0.709$). For the 253 trap-injected responses, it also achieves 83.40% agreement ($\kappa = 0.652$) on diagnostic correctness. In the multi-judge robustness analysis, unanimous agreement remains high for rejection detection on 450 stratified responses (91.98%) and for diagnostic correctness on the 400 trap-injected responses (90.48%). Detailed human validation and multi-judge robustness results are provided in Appendices H and G.

4 Experiments

4.1 Experimental Setup

Evaluated Models. We evaluate **15 MLLMs** and **2 OCR+LLM pipeline baselines** on VeriOCRBench. The MLLMs cover three complementary categories: 1) *proprietary MLLMs*, including GPT-5 (OpenAI, 2025a), GPT-4o (OpenAI, 2024), Claude-4.5-Sonnet (Anthropic, 2025), Gemini-3.1-Pro (Google DeepMind, 2026), Gemini-3-Flash variants (Google DeepMind, 2025), and Doubao-1.5-Vision-Pro (Guo et al., 2025b); 2) *open-weight MLLMs*, including the Qwen3.5 family (Qwen Team, 2026), Llama-4 Scout/Maverick (Meta AI, 2025), InternVL3-38B (Zhu et al., 2025), and Yi-VL-Plus (Young et al., 2024); and 3) an *OCR-centric vision-language baseline*, PaddleOCR-VL-1.5 (Cui et al., 2026). The OCR+LLM baselines first extract image text with PP-OCRv5 and then pass the OCR output, textual premise, and question to a text-only verifier.

All systems are evaluated under the proactive and assisted paradigms defined in Section 3.5. All MLLMs use the same prompt templates, while the OCR+LLM baselines use corresponding text-only templates in which the Image Premise is replaced by the PP-OCRv5 transcript. We set the temperature to 0.0 whenever supported. Complete inference prompts are provided in Appendix J.

4.2 Main Results

Table 2 reports the aggregate results on VeriOCRBench for 15 MLLMs and two OCR-text pipeline baselines. We focus on three core behaviors: task verification on trap-injected samples, root-cause diagnosis, and over-refusal on trap-free controls. Fine-grained analyses by trap type and verification dimension, together with qualitative examples, are discussed in Section 5 and Appendix K. Complete fine-grained quantitative tables, including image-domain results, and OCR-text pipeline details are provided in Sections K.4 and K.5, respectively. Wilson 95% confidence intervals and paired significance tests are provided in Appendix I.

Blind compliance is pervasive under proactive prompting. Without explicit verification instructions, most models rarely detect invalid OCR reasoning tasks. GPT-5 reaches only 15.38% PTVR, GPT-4o reaches 21.06%, and most open-weight models remain below 30%. Even the strongest proactive verifier, Claude-4.5-Sonnet, detects only 50.06% of trap-injected tasks. The OCR-centric baseline PaddleOCR-VL-1.5 almost entirely fails at proactive verification, with only 0.75% PTVR. These results show that strong OCR or multimodal answering ability does not automatically yield autonomous task verification.

Assisted prompting reveals a verification–refusal trade-off. Explicit verification instructions substantially improve invalid-task detection for many models. For example, GPT-5 improves from 15.38% PTVR to 84.44% ATVR, while Qwen3.5-397B-A17B improves from 24.81% to 89.06%. Gemini-3-Flash-NoThinking achieves the highest ATVR, 96.25%. However, these gains often come with increased over-refusal on valid controls: Gemini-3.1-Pro reaches 79.50% a-ORR, Gemini-3-Flash-Thinking reaches 60.00%, and PaddleOCR-VL-1.5 reaches 58.00%. This reveals a verification–refusal trade-off: stronger verification prompts can reduce blind compliance, but may also induce over-refusal on valid controls.

High rejection rates do not imply correct diagnosis. A model may correctly detect that a task is invalid while still failing to identify why it is invalid. Gemini-3.1-Pro rejects 61.50% of trap-injected tasks under assisted prompting, but achieves only 7.25% a-DA, indicating that most rejections fail to identify the correct root cause. Gemini-3-Flash-Thinking also shows a sizable gap between 87.75% ATVR and 59.81% a-DA. In contrast, GPT-5, Claude-4.5-Sonnet, and Qwen3.5-397B-A17B maintain stronger alignment between rejection and diagnosis, with a-DA scores of 76.94%, 76.12%, and 80.50%, respectively. This confirms that task verification should be evaluated with diagnosis accuracy rather than detection alone.

OCR extraction alone is insufficient for task verification. OCR+LLM pipelines provide partial verification ability but remain below the strongest

Model	Proactive Paradigm			Assisted Paradigm		
	PTVR ↑	p-DA ↑	p-ORR ↓	ATVR ↑	a-DA ↑	a-ORR ↓
OCR+LLM Pipeline Baselines						
PP-OCRv5 + o3-mini	16.38	**12.69**	**1.50**	59.00	52.56	**6.50**
PP-OCRv5 + DeepSeek-R1-Distill-Qwen-32B	**17.25**	12.50	3.00	**70.06**	**53.56**	13.00
Closed-Source MLLMs						
GPT-5	15.38	11.50	**0.00**	84.44	76.94	**9.50**
GPT-4o	21.06	13.19	0.50	81.31	67.38	15.50
Doubao-1.5-Vision-Pro	8.62	6.12	**0.00**	84.94	75.69	21.50
Gemini-3.1-Pro	33.44	24.69	17.00	61.50	7.25	79.50
Gemini-3-Flash-Thinking	23.94	21.69	4.50	87.75	59.81	60.00
Gemini-3-Flash-NoThinking	25.25	24.12	**0.00**	**96.25**	**83.00**	35.00
Claude-4.5-Sonnet	**50.06**	**46.88**	**0.00**	85.38	76.12	11.50
Open-Weight MLLMs						
Qwen3.5-35B-A3B	28.19	25.81	0.50	85.62	74.19	12.50
Qwen3.5-122B-A10B	25.12	23.56	**0.00**	83.38	73.81	**9.50**
Qwen3.5-397B-A17B	24.81	23.44	0.50	89.06	**80.50**	14.50
Llama-4-Scout-17B	26.06	21.06	12.00	64.81	54.62	16.00
Llama-4-Maverick-17B	21.50	17.44	4.50	75.75	60.88	18.50
InternVL3-38B	14.88	12.69	**0.00**	80.31	67.31	32.00
Yi-VL-Plus	**31.56**	**27.81**	1.00	**89.75**	71.19	28.50
OCR-Centric Vision-Language Baseline						
PaddleOCR-VL-1.5	0.75	0.19	53.00	5.00	0.31	58.00

Table 2: **Comprehensive evaluation on VeriOCRBench.** PTVR/ATVR, p-DA/a-DA, and p-ORR/a-ORR denote proactive/assisted Task Verification Rate, Diagnosis Accuracy, and Over-Refusal Rate, respectively. OCR+LLM baselines use PP-OCRv5-extracted text with a text-only verifier, while MLLMs use raw images. All values are percentages; **bold** denotes the best result within each model group. Confidence intervals and significance tests are reported in Appendix I.

end-to-end MLLMs in grounded diagnosis: PP-OCRv5 + DeepSeek-R1-Distill-Qwen-32B reaches 70.06% ATVR but only 53.56% a-DA. These pipelines maintain relatively low a-ORR, suggesting that OCR text can reduce over-refusal, but cannot fully capture visual degradation, occlusion, layout, or missing visual evidence. PaddleOCR-VL-1.5 also performs poorly despite its OCR specialization, with only 5.00% ATVR and 0.31% a-DA. Thus, VeriOCRBench requires joint visual-textual grounding, premise validation, and grounded refusal.

5 Analysis & Discussion

5.1 Fine-Grained Trap Results

Trap-type difficulty is highly heterogeneous. Figure 3 shows that models perform better on broad contextual inconsistencies such as *Domain Mismatch* and *Hallucinatory Target*, but struggle with localized or under-specified failures such as *Occluded Target*, *Vague Reference*, and *Missing Variable*. These cases require models to identify missing evidence, distinguish among multiple visual anchors, or recognize absent variables, which cannot be resolved by generic refusal behavior. Additional trap-type analyses are provided in Appendix K.1.

Verification dimensions reveal different failure sources. Aggregating results by verification dimension shows a similar pattern: contextual verification is comparatively strong, whereas Visual, Factual, and Logical verification remain uneven. This suggests that model performance depends not only on whether a task is invalid, but also on where the invalidity arises, such as missing visual evidence, fine-grained factual mismatch, or logical under-specification. Additional dimension-level analyses are provided in Appendix K.2.

5.2 Further Analysis of Diagnosis and Over-Refusal

Detection does not guarantee correct diagnosis. Beyond measuring whether models detect invalid tasks, we further examine whether their detection is diagnostically grounded. As shown in Figure 4, a reliable verifier should exhibit both a small ATVR–a-DA gap and a low a-ORR. GPT-5, Claude-4.5-Sonnet, and Qwen3.5-397B-A17B show a favorable multi-metric trade-off: they achieve high as-



(a) Assisted diagnosis accuracy across trap types.



(b) Diagnosis gain from proactive to assisted prompting.

Figure 3: **Trap-level diagnostic performance.** Assisted Diagnosis Accuracy (a-DA) and diagnosis gain (ΔDA = a-DA − p-DA) across eight trap types.

sisted diagnosis accuracy while keeping both the diagnosis gap and a-ORR comparatively low. In contrast, Gemini-3.1-Pro detects 61.50% of trap-injected tasks under assisted prompting but reaches only 7.25% a-DA, producing a 54.25-point diagnosis gap. This indicates that detecting invalid tasks alone can substantially overestimate true task verification ability.

Assisted verification can induce over-refusal. The right panel of Figure 4 shows that higher verification sensitivity does not necessarily imply better behavior on valid controls. Gemini-3-Flash-NoThinking achieves the highest ATVR at 96.25% and a strong a-DA of 83.00%, but its a-ORR also rises to 35.00%. Gemini-3-Flash-Thinking reaches 60.00% a-ORR, and Gemini-3.1-Pro reaches 79.50% a-ORR. These results reveal a verification–refusal trade-off: explicit verification prompts can help models detect invalid tasks, yet also push them toward over-refusal on valid controls. Thus, the core challenge is not merely increasing skepticism, but distinguishing invalid tasks from valid answerable inputs. These quantitative patterns are further illustrated by representative qualitative examples in Appendix K.3.

5.3 Prompt Sensitivity Ablation

Milder verification instructions reduce over-refusal. Table 3 shows that replacing the original assisted prompt with a milder *verify-if-needed* prompt consistently reduces ORR across all five evaluated models. The reduction is especially large for over-refusal-sensitive models: Gemini-3.1-Pro drops from 79.50% to 19.50%, and Gemini-3-Flash-Thinking drops from 60.00% to 15.00%. Even models with lower assisted ORR, such as GPT-4o and Qwen3.5-35B-A3B, reduce ORR to 2.50% and 2.00%, respectively.



Figure 4: **Diagnosis gap and over-refusal analysis.** Left: ATVR vs. a-DA, where the connecting segment indicates detected but incorrectly diagnosed trap cases. Right: assisted over-refusal rate (a-ORR) on valid controls.

Model	Assisted				Verify-if-needed				ΔDA	ORR Drop
	TVR	DA	ORR	GAP	TVR	DA	ORR	GAP		
Gemini-Pro	61.50	7.25	79.50	54.25	81.31	42.25	19.50	39.06	**+35.00**	**60.00**
Gemini-Flash-T	87.75	59.81	60.00	27.94	77.69	61.81	15.00	15.88	**+2.00**	**45.00**
Llama-Mav.	75.75	60.88	18.50	14.87	61.00	56.25	3.00	4.75	-4.63	15.50
GPT-4o	81.31	67.38	15.50	13.93	61.31	54.87	2.50	6.44	-12.51	13.00
Qwen-35B	85.62	74.19	12.50	11.43	66.62	63.06	**2.00**	3.56	-11.13	10.50

Table 3: **Prompt sensitivity ablation.** We compare the original assisted prompt with a milder *verify-if-needed* prompt. GAP denotes detected but incorrectly diagnosed samples; ΔDA and ORR Drop denote changes from the assisted prompt to the verify-if-needed prompt. All values are percentages, and model names follow Table 2.

Verification prompting involves a trade-off. The DA change is model-dependent: Gemini-3.1-Pro and Gemini-3-Flash-Thinking improve or preserve DA under the milder prompt, whereas GPT-4o and Qwen3.5-35B-A3B lose some diagnostic accuracy. The diagnosis gap decreases for all five models, indicating fewer cases where models detect invalid tasks without identifying the correct root cause. These results further illustrate the verification–refusal trade-off: aggressive verification prompts can reduce blind compliance, but may also inflate over-refusal and poorly grounded rejections. **Overall, stronger verification prompts are**

not always better. Effective prompts should balance three behaviors: detecting genuinely invalid tasks, identifying the correct reason for rejection, and avoiding unnecessary refusal on valid inputs.

Representative qualitative examples of blind compliance, diagnostic discrepancy, and over-refusal are provided in Appendix K.3.

6 Conclusion

We introduce *Task Verification* as a reliability evaluation paradigm for OCR reasoning, asking whether an MLLM should answer a task before executing it. We present **VeriOCRBench**, a 1,800-sample human-verified benchmark covering eight trap types across four verification dimensions, with trap-free controls for over-refusal evaluation. Evaluating 15 MLLMs and two OCR-text pipeline baselines reveals blind compliance under proactive prompting, prompt-induced over-refusal under assisted prompting, and a gap between invalid-task detection and correct root-cause diagnosis. These findings show that robust OCR reasoning requires reliable premise verification and grounded refusal, not only perception and answer generation.

Limitations

VeriOCRBench is a controlled diagnostic benchmark for OCR-grounded task verification. Its current scope is limited to single-turn OCR reasoning tasks and eight representative invalidity types across four verification dimensions; it does not cover interactive settings, tool-augmented workflows, dynamically updated documents, or all domain-specific verification failures. In addition, because model responses are open-ended, our evaluation relies on semantic judgment rather than exact-match scoring. We use structured judge outputs, human validation, and multi-judge robustness checks, although some nuanced cases may still require more fine-grained human evaluation.

Acknowledgments

This work is supported by the National Key Research and Development Program of China (No.2023YFF0905400), the National Natural Science Foundation of China (No.U2341229) and the Reform Commission Foundation of Jilin Province (No.2024C003).

References

Anthropic. 2025. Claude sonnet 4.5 system card. https://www.anthropic.com/claude-sonnet-4-5-system-card. Accessed: 2026-03-06.

Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang Zhou, and Jingren Zhou. 2023. Qwen-vl: A versatile vision-language model for understanding, localization, text reading, and beyond. *arXiv preprint arXiv:2308.12966*.

Yupeng Chang, Xu Wang, Jindong Wang, Yuan Wu, Linyi Yang, Kaijie Zhu, Hao Chen, Xiaoyuan Yi, Cunxiang Wang, Yidong Wang, et al. 2024. A survey on evaluation of large language models. *ACM transactions on intelligent systems and technology*, 15(3):1–45.

Zhe Chen, Jiannan Wu, Wenhai Wang, Weijie Su, Guo Chen, Sen Xing, Muyan Zhong, Qinglong Zhang, Xizhou Zhu, Lewei Lu, et al. 2024. Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 24185–24198.

Hiuyi Cheng, Peirong Zhang, Sihang Wu, Jiaxin Zhang, Qiyuan Zhu, Zecheng Xie, Jing Li, Kai Ding, and Lianwen Jin. 2023. M6doc: A large-scale multi-format, multi-type, multi-layout, multi-language, multi-annotation category dataset for modern document layout analysis. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15138–15147.

Cheng Cui, Ting Sun, Suyin Liang, Tingquan Gao, Zelun Zhang, Jiaxuan Liu, Xueqing Wang, Changda Zhou, Hongen Liu, Manhui Lin, et al. 2026. Paddleocr-vl-1.5: Towards a multi-task 0.9 b vlm for robust in-the-wild document parsing. *arXiv preprint arXiv:2601.21957*.

Cheng Cui, Ting Sun, Manhui Lin, Tingquan Gao, Yubo Zhang, Jiaxuan Liu, Xueqing Wang, Zelun Zhang, Changda Zhou, Hongen Liu, et al. 2025. Paddleocr 3.0 technical report. *arXiv preprint arXiv:2507.05595*.

Ling Fu, Zhebin Kuang, Jiajun Song, Mingxin Huang, Biao Yang, Yuzhe Li, Linghao Zhu, Qidi Luo, Xinyu Wang, Hao Lu, et al. 2025. Ocrbench v2: An improved benchmark for evaluating large multimodal models on visual text localization and reasoning. *Advances in Neural Information Processing Systems*, 38.

Google DeepMind. 2025. Gemini 3 flash model card. https://deepmind.google/models/model-cards/gemini-3-flash/. Accessed: 2026-03-06.

Google DeepMind. 2026. Gemini 3.1 pro model card.

Tianrui Guan, Fuxiao Liu, Xiyang Wu, Ruiqi Xian, Zongxia Li, Xiaoyu Liu, Xijun Wang, Lichang Chen, Furong Huang, Yaser Yacoob, et al. 2024. Hallusionbench: an advanced diagnostic suite for entangled language hallucination and visual illusion in large vision-language models. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 14375–14385.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, et al. 2025a. Deepseek-r1 incentivizes reasoning in llms through reinforcement learning. *Nature*, 645(8081):633–638.

Dong Guo, Faming Wu, Feida Zhu, Fuxing Leng, Guang Shi, Haobin Chen, Haoqi Fan, Jian Wang, Jianyu Jiang, Jiawei Wang, et al. 2025b. Seed1.5-vl technical report. *arXiv preprint arXiv:2505.07062*.

Mingxin Huang, Yongxin Shi, Dezhi Peng, Songxuan Lai, Zecheng Xie, and Lianwen Jin. 2026. Ocr-reasoning benchmark: Unveiling the true capabilities of mllms in complex text-rich image reasoning. In *International Conference on Learning Representations*.

Bohao Li, Yuying Ge, Yi Chen, Yixiao Ge, Ruimao Zhang, and Ying Shan. 2024. Seed-bench-2-plus: Benchmarking multimodal large language models with text-rich visual comprehension. *arXiv preprint arXiv:2404.16790*.

Yifan Li, Yifan Du, Kun Zhou, Jinpeng Wang, Wayne Xin Zhao, and Ji-Rong Wen. 2023. Evaluating object hallucination in large vision-language models. In *Proceedings of the 2023 conference on empirical methods in natural language processing*, pages 292–305.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. 2023. Visual instruction tuning. *Advances in neural information processing systems*, 36:34892–34916.

Yuliang Liu, Zhang Li, Mingxin Huang, Biao Yang, Wenwen Yu, Chunyuan Li, Xu-Cheng Yin, Cheng-Lin Liu, Lianwen Jin, and Xiang Bai. 2024. Ocrbench: on the hidden mystery of ocr in large multimodal models. *Science China Information Sciences*, 67(12):220102.

Ahmed Masry, Do Xuan Long, Jia Qing Tan, Shafiq Joty, and Enamul Hoque. 2022. Chartqa: A benchmark for question answering about charts with visual and logical reasoning. In *Findings of the association for computational linguistics: ACL 2022*, pages 2263–2279.

Minesh Mathew, Viraj Bagal, Rubèn Tito, Dimosthenis Karatzas, Ernest Valveny, and CV Jawahar. 2022. Infographicvqa. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 1697–1706.

Minesh Mathew, Dimosthenis Karatzas, and CV Jawahar. 2021. Docvqa: A dataset for vqa on document images. In *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, pages 2200–2209.

Meta AI. 2025. The llama 4 herd: The beginning of a new era of natively multimodal ai innovation.

Atsuyuki Miyai, Jingkang Yang, Jingyang Zhang, Yifei Ming, Qing Yu, Go Irie, Yixuan Li, Hai Helen Li, Ziwei Liu, and Kiyoharu Aizawa. 2025. Unsolvable problem detection: Robust understanding evaluation for large multimodal models. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 6497–6540.

OpenAI. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

OpenAI. 2024. Hello gpt-4o. *OpenAI Blog*.

OpenAI. 2025a. Gpt-5 system card.

OpenAI. 2025b. Openai o3-mini system card. Accessed: 2026-08-25.

Linke Ouyang, Yuan Qu, Hongbin Zhou, Jiawei Zhu, Rui Zhang, Qunshu Lin, Bin Wang, Zhiyuan Zhao, Man Jiang, Xiaomeng Zhao, et al. 2025. Omnidocbench: Benchmarking diverse pdf document parsing with comprehensive annotations. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 24838–24848.

Ethan Perez, Sam Ringer, Kamile Lukosiute, Karina Nguyen, Edwin Chen, Scott Heiner, Craig Pettit, Catherine Olsson, Sandipan Kundu, Saurav Kadavath, et al. 2023. Discovering language model behaviors with model-written evaluations. In *Findings of the association for computational linguistics: ACL 2023*, pages 13387–13434.

Yusu Qian, Haotian Zhang, Yinfei Yang, and Zhe Gan. 2024. How easy is it to fool your multimodal llms? an empirical analysis on deceptive prompts. *arXiv preprint arXiv:2402.13220*.

Qwen Team. 2026. Qwen3.5: Towards native multimodal agents.

Paul Röttger, Hannah Kirk, Bertie Vidgen, Giuseppe Attanasio, Federico Bianchi, and Dirk Hovy. 2024. Xstest: A test suite for identifying exaggerated safety behaviours in large language models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 5377–5400.

Mrinank Sharma, Meg Tong, Tomasz Korbak, David Duvenaud, Amanda Askell, Samuel R. Bowman, Newton Cheng, Esin Durmus, Zac Hatfield-Dodds, Scott R. Johnston, Shauna Kravec, Timothy Maxwell, Sam McCandlish, Kamal Ndousse, Oliver Rausch,

Nicholas Schiefer, Da Yan, Miranda Zhang, and Ethan Perez. 2024. Towards understanding sycophancy in language models. In *International Conference on Learning Representations*.

Amanpreet Singh, Vivek Natarajan, Meet Shah, Yu Jiang, Xinlei Chen, Dhruv Batra, Devi Parikh, and Marcus Rohrbach. 2019. Towards vqa models that can read. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 8317–8326.

Gemini Team, Petko Georgiev, Ving Ian Lei, Ryan Burnell, Libin Bai, Anmol Gulati, Garrett Tanzer, Damien Vincent, Zhufeng Pan, Shibo Wang, et al. 2024. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. *arXiv preprint arXiv:2403.05530*.

Jerry Wei, Da Huang, Yifeng Lu, Denny Zhou, and Quoc V Le. 2023. Simple synthetic data reduces sycophancy in large language models. *arXiv preprint arXiv:2308.03958*.

Renqiu Xia, Hancheng Ye, Xiangchao Yan, Qi Liu, Hongbin Zhou, Zijun Chen, Botian Shi, Junchi Yan, and Bo Zhang. 2025. Chartx & chartvlm: A versatile benchmark and foundation model for complicated chart reasoning. *IEEE Transactions on Image Processing*, 34:7436–7447.

Alex Young, Bei Chen, Chao Li, Chengen Huang, Ge Zhang, Guanwei Zhang, Guoyin Wang, Heng Li, Jiangcheng Zhu, Jianqun Chen, et al. 2024. Yi: Open foundation models by 01. ai. *arXiv preprint arXiv:2403.04652*.

Jian Zhang, Runwei Ding, Miaoju Ban, and Linhui Dai. 2024. Pku-goodsad: A supermarket goods dataset for unsupervised anomaly detection and segmentation. *IEEE Robotics and Automation Letters*, 9(3):2008–2015.

Mingyu Zheng, Xinwei Feng, Qingyi Si, Qiaoqiao She, Zheng Lin, Wenbin Jiang, and Weiping Wang. 2024. Multimodal table understanding. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 9102–9124.

Jinguo Zhu, Weiyun Wang, Zhe Chen, Zhaoyang Liu, Shenglong Ye, Lixin Gu, Hao Tian, Yuchen Duan, Weijie Su, Jie Shao, et al. 2025. Internvl3: Exploring advanced training and test-time recipes for open-source multimodal models. *arXiv preprint arXiv:2504.10479*.

A Formal Definition and Boundary Conditions

A.1 Task Representation

Following the task definition in Section 3.1, we formalize a text-rich visual reasoning task as a triplet

$$T = (IP, TP, Q) \in \mathcal{I} \times \mathcal{T} \times \mathcal{T},$$

where $\mathcal{I}$ denotes the space of image inputs and $\mathcal{T}$ denotes the space of textual sequences.

- $IP \in \mathcal{I}$ denotes the **Image Premise**, which contains the visual evidence required by the task, such as legible text, numerical values, tables, layout relations, and other Visual Atomic Facts (VAFs).
- $TP \in \mathcal{T}$ denotes the **Textual Premise**, which provides user-specified assumptions, contextual information, or task-specific rules.
- $Q \in \mathcal{T}$ denotes the **Question**, which asks for a reasoning outcome based on the joint information in IP and TP.

A.2 Task Validity Function

We define a binary task validity function

$$\mathcal{V} : \mathcal{I} \times \mathcal{T} \times \mathcal{T} \to \{0, 1\}.$$

A task is valid, i.e., $\mathcal{V}(T) = 1$, if it satisfies the following three conditions:

1. **Evidence Availability:** The visual evidence required to answer Q is sufficiently available and readable in IP.
2. **Cross-Modal Consistency:** Any claims or references in TP or Q concerning the image are consistent with the visual evidence in IP. Auxiliary task-specific rules or conditions introduced by TP need not be explicitly represented in the image.
3. **Query Solvability:** The joint information in IP and TP is sufficient to answer Q without relying on missing or ambiguous information.

If any condition is violated, then $\mathcal{V}(T) = 0$, and the task is considered invalid or unexecutable. Such invalidity may arise from visual degradation, occlusion, image–text contradiction, nonexistent visual targets, vague references, logical inconsistency, or missing variables.

An ideal model should condition its response on $\mathcal{V}(T)$:

$$\mathcal{M}(T) = \begin{cases} A_{\text{ans}}, & \text{if } \mathcal{V}(T) = 1, \\ A_{\text{ref}}, & \text{if } \mathcal{V}(T) = 0, \end{cases}$$

where A_{ans} denotes a standard answer to a valid task, and A_{ref} denotes a grounded refusal or critique. In our evaluation, A_{ref} includes explicit refusals as well as responses that clearly identify or



Figure 5: **Verification taxonomy of VeriOCRBench.** VeriOCRBench covers four verification dimensions and eight trap types, with two trap types under each dimension.

correct the flawed premise before proceeding. Responses that directly follow a flawed premise without flagging the issue are not counted as successful task verification.

B Trap Taxonomy and Expected Model Behaviors

As introduced in Section 3.2, VeriOCRBench organizes eight trap types into four verification dimensions: Visual, Contextual, Factual, and Logical. Figure 5 provides a compact visualization of this taxonomy. This appendix provides detailed definitions and expected model behaviors for each trap type.

B.1 Visual Dimension

The Visual dimension tests whether the model can determine if the required visual evidence is available and readable before attempting the reasoning task.

- **Type 1: Image Degradation.** Critical text or visual evidence is physically present but degraded, such as through severe blur, noise, glare, or low resolution, making it unreliable for downstream reasoning. *Expected Behavior:* The model should recognize that the required evidence is unreadable or unreliable, avoid guessing the hidden content, and state that the task cannot be answered as given.

- **Type 2: Occluded Target.** The visual evidence required by the task is masked, cropped, redacted, or otherwise hidden from view. *Expected Behavior:* The model should identify that the necessary region or target evidence is missing and avoid synthesizing the occluded ground truth.

B.2 Contextual Dimension

The Contextual dimension tests whether the model can verify the compatibility between the user-provided context and the actual image content.

- **Type 3: Domain Mismatch.** The textual premise imposes an incompatible domain or scenario on the image, such as treating a product package as a financial report or a poster as an official form. *Expected Behavior:* The model should identify the global context mismatch and explain that the requested task is not supported by the image.

- **Type 4: Hallucinatory Target.** The textual premise or question refers to a text block, object, entity, or visual target that does not exist in the image. *Expected Behavior:* The model should point out that the referenced target is absent rather than reasoning over a fabricated visual entity.

B.3 Factual Dimension

The Factual dimension tests whether the model can ground fine-grained textual claims against visible OCR evidence.

- **Type 5: Fact Tampering.** The textual premise refers to an existing visual entity but falsifies one of its attributes or values, such as changing a receipt total, date, quantity, or label. *Expected Behavior:* The model should detect the mismatch between the premise and the image, identify or correct the tampered fact, and avoid performing reasoning based on the false value.

- **Type 6: Vague Reference.** The task uses an under-specified reference that maps to multiple plausible visual targets, such as asking about "the date" when several dates are present. *Expected Behavior:* The model should recognize the ambiguity and avoid arbitrarily selecting one target; a correct response should request clarification or explain why the task is under-specified.

B.4 Logical Dimension

The Logical dimension tests whether the requested reasoning is well-posed after considering both the image and the textual premise.

- **Type 7: Logical Paradox.** The textual premise introduces a relationship, ordering, or rule that contradicts an indisputable visual relation, such as reversing a visible ranking or asserting an impossible part–whole relation. *Expected Behavior:* The model should identify the contradiction and avoid executing reasoning under the inconsistent premise.
- **Type 8: Missing Variable.** The visible evidence is readable, but solving the task requires an unstated variable or external condition, such as a missing unit, currency, scale, jurisdiction, or conversion basis. *Expected Behavior:* The model should identify the missing dependency and explain that the task is not uniquely answerable without additional information.

B.5 Trap-Free Controls

VeriOCRBench also includes trap-free control tasks to measure whether models over-refuse valid inputs.

- **Trap-Free Normal Tasks.** These tasks are valid and answerable using the provided image premise and textual premise. *Expected Behavior:* The model should answer the question without raising unsupported concerns. These samples are used to compute the Over-Refusal Rate (ORR), preventing models from achieving high verification scores by adopting a generic refusal policy.

C Representative Trap Examples

Figure 6 presents representative examples of the eight trap types and one trap-free control task in VeriOCRBench. These examples illustrate how task invalidity can arise from unavailable visual evidence, incompatible contexts, nonexistent targets, factual tampering, ambiguous references, logical inconsistency, and missing variables.

D Dataset Construction Details

This section provides additional details for the construction pipeline described in Section 3.3, including trap-specific generation strategies and prompt templates, the human auditing checklist, and extended dataset statistics.

D.1 Generation Prompt Overview

Our generation pipeline uses trap-type-specific prompts to construct invalid tasks and trap-free controls while enforcing VAF grounding, zero text leakage, zero trap disclosure, and reasoning-beyond-extraction requirements. Zero text leakage ensures that the task retains dependence on image evidence rather than directly revealing the answer in TP or Q. At generation time, the prompts prohibit direct answer disclosure and require reasoning beyond direct text extraction; the resulting tasks are then subject to the six-item human audit described below. Below we summarize the role of each prompt family.

Visual traps: Type 1 and Type 2. Image Degradation and Occluded Target share a generate-then-corrupt strategy. A generation agent selects a suitable visual atomic fact from the pristine image and designs a natural reasoning task around it. The resulting task is paired with a version of the image in which the corresponding visual evidence is degraded or occluded, ensuring that the textual premise does not reveal the corruption. The shared prompt template is shown in Figure 19.

Contextual traps: Type 3 and Type 4. Domain Mismatch prompts construct tasks that impose an incompatible domain context on the image, while Hallucinatory Target prompts introduce a plausible but nonexistent visual target. The corresponding templates are shown in Figures 13 and 15.

Factual traps: Type 5 and Type 6. Fact Tampering prompts alter a visible attribute or value of an existing visual entity, whereas Vague Reference prompts create under-specified references that map to multiple plausible visual anchors. The corresponding templates are shown in Figures 14 and 16.

Logical traps: Type 7 and Type 8. Logical Paradox prompts introduce contradictions in visual relations, ordering, or rules, while Missing Variable prompts ask questions that require an unstated variable or external condition. The corresponding templates are shown in Figures 18 and 17.

Trap-free controls. The control prompt constructs valid reasoning tasks with no injected trap. These tasks are used to measure over-refusal and



Figure 6: **Representative examples of trap categories in VeriOCRBench.** The benchmark includes eight trap types: Image Degradation, Occluded Target, Domain Mismatch, Hallucinatory Target, Fact Tampering, Vague Reference, Logical Paradox, and Missing Variable, together with a trap-free control task.

ensure that models are not rewarded for adopting a generic refusal policy. The control prompt is shown in Figure 20.

D.2 Human Auditing Checklist

All 1,800 samples in VeriOCRBench underwent full human auditing. The construction-time audit was conducted by PhD students from our project team under a shared checklist. Each (IP, TP, Q) triplet was checked according to the following six criteria:

1. **VAF Accuracy.** The Visual Atomic Facts (VAFs) extracted by PaddleOCR are physically present in the image, with no critical OCR errors or bounding-box mismatches affecting the target evidence.

2. **Control-Task Solvability.** Trap-free control tasks are answerable using the provided Image Premise (IP) and Textual Premise (TP), while still requiring multimodal reasoning rather than direct answer leakage.

3. **Trap-Task Unsolvability.** Trap-injected tasks contain a clear source of invalidity, such as unavailable visual evidence, cross-modal contradiction, ambiguity, or missing information, making the task unexecutable as stated.

4. **Zero Trap Disclosure.** The Question (Q) does not explicitly reveal the presence or type of the trap, and does not directly instruct the model to perform verification.

5. **Trap-Type Alignment.** The injected trap matches the intended trap type and verification dimension defined in Appendix B.

6. **Reasoning Beyond Direct Extraction.** The Question (Q) requires reasoning beyond simple text spotting, such as numerical calcula-

Statistic	Count
Total samples	**1,800**
Trap-injected invalid tasks	1,600
Trap-free control tasks	200
Taxonomy coverage	
Verification dimensions	4
Trap types	8
Samples per trap type	200
Domain coverage	
Source benchmarks	8
Real-world image domains	8
Total samples per domain	225
Evaluation setting	
Inference paradigms	2
Model outputs per evaluated system	3,600

Table 4: **Detailed statistics of VeriOCRBench.**

tion, cross-field comparison, logical deduction, or counting.

D.3 Extended Dataset Statistics

VeriOCRBench contains 1,800 human-verified samples, including 1,600 trap-injected invalid tasks and 200 trap-free controls. Table 4 summarizes the dataset scale, taxonomy coverage, domain coverage, and evaluation setting.

E Formal Metric Definitions

Let N_{trap} and N_{ctrl} denote the numbers of trap-injected and trap-free control samples, respectively, and let $s \in \{\text{pro}, \text{ast}\}$ denote the proactive or assisted setting. For a trap-injected sample i, let $R_s^{(i)} \in \{0, 1\}$ indicate successful invalid-task detection and $D_s^{(i)} \in \{0, 1\}$ indicate correct identification of the ground-truth trap mechanism. For a trap-free control sample k, let $O_s^{(k)} \in \{0, 1\}$ indicate an incorrect rejection.

Task Verification Rate.

$$\mathrm{TVR}_s = \frac{1}{N_{\text{trap}}} \sum_{i=1}^{N_{\text{trap}}} R_s^{(i)}. \tag{1}$$

We denote $\mathrm{TVR}_{\text{pro}}$ and $\mathrm{TVR}_{\text{ast}}$ as PTVR and ATVR, respectively.

Diagnosis Accuracy.

$$\mathrm{DA}_s = \frac{1}{N_{\text{trap}}} \sum_{i=1}^{N_{\text{trap}}} R_s^{(i)} D_s^{(i)}. \tag{2}$$

We denote DA_{pro} and DA_{ast} as p-DA and a-DA, respectively. DA uses all trap-injected samples as the denominator, so a sample receives credit only when the model both detects the invalid task and identifies the correct trap mechanism.

Over-Refusal Rate.

$$\mathrm{ORR}_s = \frac{1}{N_{\text{ctrl}}} \sum_{k=1}^{N_{\text{ctrl}}} O_s^{(k)}. \tag{3}$$

We denote $\mathrm{ORR}_{\text{pro}}$ and $\mathrm{ORR}_{\text{ast}}$ as p-ORR and a-ORR, respectively.

F LLM-as-a-Judge Prompts and Decision Rules

Given the open-ended nature of MLLM responses, exact-match scoring is insufficient for determining whether a model has detected an invalid task, identified the correct source of invalidity, or over-refused a valid task. We therefore use a structured LLM-as-a-Judge protocol with GPT-4o as the primary semantic judge. The judge is required to output predefined JSON fields, which are then used to compute TVR, DA, and ORR.

F.1 Judge Decision Rules

For trap-injected samples, a response is considered to have detected the trap if it explicitly refuses to answer the task as stated, or if it clearly identifies that the Image Premise (IP), Textual Premise (TP), and Question (Q) are inconsistent, insufficient, or otherwise unexecutable. We also count responses that correct the flawed premise before proceeding as successful detection, provided that the response clearly states the source of invalidity. In contrast, responses that directly follow the flawed premise and produce an answer without flagging the issue are counted as blind compliance.

For trap-free control samples, a response is counted as over-refusal only when the model explicitly refuses, claims that the task is invalid or unanswerable, or raises unsupported concerns that prevent it from answering. Incorrect answers are not counted as over-refusals if the model still attempts the valid task.

F.2 Judge Pipelines

We use two assessment pipelines:

- **Trap Assessment Judge:** Applied to Type 1–8 trap-injected tasks. It checks whether the model detects the invalid task, including explicit refusals and responses that clearly identify or correct the flawed premise before proceeding. It also checks whether the stated

Judged Dimension	N	Unanim.	Fleiss' κ	Kripp. α
Rejection judgment	450	91.98	0.911	0.892
Diagnostic correctness	400	90.48	0.895	0.872

Table 5: Multi-judge robustness analysis. Agreement is measured on 450 stratified response-level samples for rejection judgments and on the 400 trap-injected responses for diagnostic correctness, using GPT-4o, Claude, and Gemini as judges. Agreement values are percentages.

rationale aligns with the ground-truth *Trap Logic Trace*.

- **Over-Refusal Assessment Judge:** Applied to trap-free control tasks. It checks whether the model incorrectly refuses a valid and answerable task, which is used to compute the Over-Refusal Rate (ORR).

The complete system and user prompts for the two judges are shown in Figure 25 and Figure 26, respectively.

G Multi-Judge Robustness Analysis

We conduct a multi-judge robustness analysis using three separate LLM judges: GPT-4o, Claude, and Gemini. We sample 450 response-level units stratified across all nine task categories, including eight trap types and trap-free controls, with 50 samples per category and an even split between proactive and assisted paradigms. The analysis covers all 15 evaluated MLLMs; the two OCR-text pipeline baselines are excluded.

Across all 450 sampled units, we compute inter-judge agreement for rejection judgments. For diagnostic correctness, which is defined only for trap-injected tasks, we compute agreement on the 400 trap-injected responses. We report unanimous agreement, Fleiss' κ, and Krippendorff's α for both dimensions. Table 5 shows consistently high agreement on both evaluation dimensions.

H Human Validation of the LLM-as-a-Judge

To validate the automated GPT-4o judge used in our evaluation pipeline, we conduct a human validation study on 286 model responses. The sampling unit is response-level: each unit corresponds to one model response under either the proactive or assisted paradigm.

PhD students apply the same response-level evaluation criteria as the automatic judge. For each response, `is_rejected` records whether the response rejects, challenges, or corrects the task premise before proceeding. For trap-injected samples, `is_rationale_correct` indicates whether the model's stated reason matches the ground-truth Trap Logic Trace. Human evaluators are blind to the GPT-4o judge labels.

Human annotations are adjudicated before comparison with the automatic judge. GPT-4o achieves 85.66% agreement ($\kappa = 0.709$) with the resulting human labels on rejection judgments and 83.40% agreement ($\kappa = 0.652$) on diagnostic correctness. Rejection judgments are evaluated over all 286 responses, while diagnostic correctness is evaluated on the 253 trap-injected responses.

I Confidence Intervals and Significance Tests

To assess the statistical reliability of the reported results, we compute uncertainty estimates and paired significance tests for the main metrics in Table 2. Since PTVR, ATVR, p-DA, a-DA, p-ORR, and a-ORR are binary sample-level metrics, we report Wilson 95% confidence intervals for each model and metric. For pairwise model comparisons, we use paired exact McNemar tests because models are evaluated on the same benchmark instances. Holm correction is applied for multiple comparisons within each model group and metric.

I.1 Confidence Intervals

Table 7 reports Wilson confidence intervals for all main metrics. The intervals support the major trends discussed in the main text: proactive task verification remains low for most systems, assisted prompting substantially increases task verification for many models, and several models exhibit large over-refusal rates under assisted prompting.

I.2 Paired Significance Tests

Table 8 reports key paired significance tests for representative comparisons. The results provide statistical support for the main claims. For example, Claude-4.5-Sonnet's proactive verification advantage over GPT-4o and GPT-5 remains significant after Holm correction, and Qwen3.5-397B-A17B significantly improves assisted diagnosis over Qwen3.5-122B-A10B. At the same time, small ORR differences, such as GPT-5 versus GPT-4o and Qwen3.5-122B-A10B versus Qwen3.5-397B-A17B, are not significant after correction.

Label	N	Agr. (%)	κ	Human Pos.	Judge Pos.
Rejection judgment	286	85.66	0.709	101	136
Diagnostic correctness	253	83.40	0.652	94	104

Table 6: **Human validation results for the GPT-4o judge.** Rejection judgments are evaluated over all 286 responses, while diagnostic correctness is evaluated on the 253 trap-injected responses. Positive counts correspond to adjudicated human labels and GPT-4o judge labels, respectively.

Model	PTVR	p-DA	p-ORR	ATVR	a-DA	a-ORR
OCR+LLM Pipeline Baselines						
PP-OCRv5 + o3-mini	16.38 [14.64, 18.27]	12.69 [11.14, 14.41]	1.50 [0.51, 4.32]	59.00 [56.57, 61.39]	52.56 [50.11, 54.99]	6.50 [3.82, 10.81]
PP-OCRv5 + DeepSeek-R1-Distill-Qwen-32B	17.25 [15.48, 19.19]	12.50 [10.98, 14.22]	3.00 [1.38, 6.42]	70.06 [67.77, 72.26]	53.56 [51.11, 55.99]	13.00 [8.99, 18.38]
Closed-Source MLLMs						
GPT-5	15.38 [13.69, 17.23]	11.50 [10.03, 13.16]	0.00 [0.00, 1.88]	84.44 [82.58, 86.13]	76.94 [74.81, 78.94]	9.50 [6.17, 14.36]
GPT-4o	21.06 [19.14, 23.13]	13.19 [11.62, 14.93]	0.50 [0.09, 2.78]	81.31 [79.33, 83.15]	67.38 [65.04, 69.63]	15.50 [11.14, 21.16]
Doubao-1.5-Vision-Pro	8.62 [7.35, 10.10]	6.12 [5.05, 7.41]	0.00 [0.00, 1.88]	84.94 [83.10, 86.61]	75.69 [73.53, 77.73]	21.50 [16.37, 27.70]
Gemini-3.1-Pro	33.44 [31.17, 35.79]	24.69 [22.64, 26.86]	17.00 [12.43, 22.82]	61.50 [59.09, 63.85]	7.25 [6.08, 8.63]	79.50 [73.37, 84.51]
Gemini-3-Flash-Thinking	23.94 [21.91, 26.09]	21.69 [19.74, 23.77]	4.50 [2.39, 8.33]	87.75 [86.05, 89.27]	59.81 [57.39, 62.19]	60.00 [53.08, 66.54]
Gemini-3-Flash-NoThinking	25.25 [23.18, 27.44]	24.12 [22.09, 26.28]	0.00 [0.00, 1.88]	96.25 [95.20, 97.08]	83.00 [81.08, 84.76]	35.00 [28.73, 41.84]
Claude-4.5-Sonnet	50.06 [47.62, 52.51]	46.88 [44.44, 49.32]	0.00 [0.00, 1.88]	85.38 [83.56, 87.02]	76.12 [73.98, 78.15]	11.50 [7.79, 16.66]
Open-Weight MLLMs						
Qwen3.5-35B-A3B	28.19 [26.04, 30.44]	25.81 [23.73, 28.01]	0.50 [0.09, 2.78]	85.62 [83.82, 87.26]	74.19 [71.99, 76.27]	12.50 [8.61, 17.80]
Qwen3.5-122B-A10B	25.12 [23.06, 27.31]	23.56 [21.55, 25.70]	0.00 [0.00, 1.88]	83.38 [81.47, 85.12]	73.81 [71.60, 75.91]	9.50 [6.17, 14.36]
Qwen3.5-397B-A17B	24.81 [22.76, 26.99]	23.44 [21.43, 25.58]	0.50 [0.09, 2.78]	89.06 [87.44, 90.50]	80.50 [78.49, 82.37]	14.50 [10.29, 20.05]
Llama-4-Scout-17B	26.06 [23.97, 28.27]	21.06 [19.14, 23.13]	12.00 [8.20, 17.23]	64.81 [62.44, 67.11]	54.62 [52.18, 57.05]	16.00 [11.57, 21.71]
Llama-4-Maverick-17B	21.50 [19.56, 23.58]	17.44 [15.66, 19.37]	4.50 [2.39, 8.33]	75.75 [73.59, 77.79]	60.88 [58.46, 63.24]	18.50 [13.73, 24.46]
InternVL3-38B	14.88 [13.22, 16.70]	12.69 [11.15, 14.41]	0.00 [0.00, 1.88]	80.31 [78.29, 82.19]	67.31 [64.98, 69.57]	32.00 [25.93, 38.75]
Yi-VL-Plus	31.56 [29.33, 33.88]	27.81 [25.67, 30.06]	1.00 [0.27, 3.57]	89.75 [88.17, 91.14]	71.19 [68.92, 73.35]	28.50 [22.70, 35.12]
OCR-Centric Vision-Language Baseline						
PaddleOCR-VL-1.5	0.75 [0.43, 1.31]	0.19 [0.06, 0.55]	53.00 [46.09, 59.80]	5.00 [4.04, 6.18]	0.31 [0.13, 0.73]	58.00 [51.07, 64.63]

Table 7: **Wilson 95% confidence intervals for the main VeriOCRBench metrics.** Each cell reports estimate [lower, upper] in percentages.

Our analysis therefore focuses on the larger, statistically supported trends.

To assess sensitivity to the two non-significant cross-system a-ORR differences, we compute 80%-power minimum detectable effects (MDEs) conditional on the observed discordant pairs using two-sided exact McNemar tests at $\alpha = 0.05$. The resulting MDEs are 8.59 and 5.65 percentage points for GPT-5 vs. GPT-4o and Qwen3.5-122B-A10B vs. Qwen3.5-397B-A17B, respectively, placing the observed differences of 6.00 and 5.00 points below the corresponding sensitivity thresholds and supporting a cautious interpretation of these comparisons as inconclusive for small differences rather than evidence of equivalence.

Within-System Proactive–Assisted ORR Comparison. As shown in Table 9, assisted ORR is higher than proactive ORR for all 17 systems on the same 200 trap-free controls. Sixteen of the 17 paired differences remain significant after Holm correction across the 17 exact McNemar tests. The only non-significant case is PaddleOCR-VL-1.5, whose ORR increases from 53.00% to 58.00%.

J Complete Prompt Templates for Model Inference

This section provides the complete inference prompt templates used in our evaluation. To ensure a standardized comparison, all systems follow the same proactive and assisted evaluation paradigms defined in Section 3.5. The only difference is the evidence source: multimodal systems receive the raw image as the Image Premise, whereas OCR+LLM pipeline baselines receive PP-OCRv5 transcripts as text-only evidence. The multimodal proactive and assisted prompts are shown in Figures 21 and 22, respectively. The OCR+LLM proactive and assisted prompts are shown in Figures 23 and 24, respectively.

J.1 Multimodal Model Inference Prompts

For multimodal systems, the model receives the Image Premise (IP), Textual Premise (TP), and Question (Q) as input. In the proactive setting, the model receives the standard input triplet without any external warning or explicit instruction to verify task validity. In the assisted setting, an explicit meta-instruction is appended to the same input triplet, asking the model to verify whether the

Metric	Comparison	Model A	Model B	Diff. (pp)	Holm p	Sig.
PTVR ↑	Closed-source proactive verification	Claude-4.5-Sonnet (50.06)	GPT-4o (21.06)	+29.00	1.472×10^{-90}	Yes
PTVR ↑	Closed-source proactive verification	Claude-4.5-Sonnet (50.06)	GPT-5 (15.38)	+34.69	2.619×10^{-136}	Yes
ATVR ↑	Closed-source assisted verification	Gemini-3-Flash-NoThinking (96.25)	GPT-5 (84.44)	+11.81	6.142×10^{-48}	Yes
a-ORR ↓	Closed-source over-refusal	GPT-5 (9.50)	GPT-4o (15.50)	-6.00	0.2305	No
PTVR ↑	Open-weight proactive verification	Yi-VL-Plus (31.56)	Qwen3.5-35B-A3B (28.19)	+3.38	0.009319	Yes
a-DA ↑	Open-weight assisted diagnosis	Qwen3.5-397B-A17B (80.50)	Qwen3.5-122B-A10B (73.81)	+6.69	6.320×10^{-15}	Yes
a-ORR ↓	Open-weight over-refusal	Qwen3.5-122B-A10B (9.50)	Qwen3.5-397B-A17B (14.50)	-5.00	0.2127	No

Table 8: **Key paired significance tests for main comparisons.** We report paired exact McNemar tests because compared models are evaluated on the same benchmark instances. Holm correction is applied within each model group and metric. "Diff." denotes Model A minus Model B in percentage points. For ORR, lower values are better, so a negative difference favors Model A.

Model	p-ORR	a-ORR	Holm p
OCR+LLM Pipeline Baselines			
PP-OCRv5 + o3-mini	1.50	6.50	0.0190
PP-OCRv5 + DeepSeek-R1-Distill-Qwen-32B	3.00	13.00	1.44×10^{-4}
Closed-Source MLLMs			
GPT-5	0.00	9.50	2.29×10^{-5}
GPT-4o	0.50	15.50	2.05×10^{-8}
Doubao-1.5-Vision-Pro	0.00	21.50	2.73×10^{-12}
Gemini-3.1-Pro	17.00	79.50	8.27×10^{-30}
Gemini-3-Flash-Thinking	4.50	60.00	1.31×10^{-32}
Gemini-3-Flash-NoThinking	0.00	35.00	2.54×10^{-20}
Claude-4.5-Sonnet	0.00	11.50	1.91×10^{-6}
Open-Weight MLLMs			
Qwen3.5-35B-A3B	0.50	12.50	5.63×10^{-6}
Qwen3.5-122B-A10B	0.00	9.50	2.29×10^{-5}
Qwen3.5-397B-A17B	0.50	14.50	5.77×10^{-7}
Llama-4-Scout-17B	12.00	16.00	0.0190
Llama-4-Maverick-17B	4.50	18.50	5.77×10^{-7}
InternVL3-38B	0.00	32.00	1.52×10^{-18}
Yi-VL-Plus	1.00	28.50	7.22×10^{-16}
OCR-Centric Vision-Language Baseline			
PaddleOCR-VL-1.5	53.00	58.00	0.2370

Table 9: **Paired within-system comparison of proactive and assisted Over-Refusal Rate (ORR).** All systems are evaluated on the same 200 trap-free controls. Holm-adjusted p-values are based on two-sided exact McNemar tests with correction across the 17 system-level comparisons.

requested task is completable based on the Image Premise before answering.

J.2 OCR-Text Pipeline Baseline Prompts

For OCR+LLM pipeline baselines, PP-OCRv5 first extracts an OCR transcript from the image. The text-only verifier then receives only the OCR transcript, Textual Premise (TP), and Question (Q), without access to the raw image. Each OCR transcript is formatted as an ordered list of detected text lines, optionally including OCR confidence and bounding-box metadata. The prompt version used in our experiments is `ocrtext_verifier_v1`. The proactive and assisted prompts mirror the multimodal prompts, with the Image Premise replaced by the OCR Transcript as the evidence source.

K Extended Evaluation Results and Analysis

This section provides fine-grained evaluation results that complement the aggregate findings in Section 4.2 and the main analysis in Section 5. We report detailed results across trap types, verification dimensions, and image domains.

K.1 Fine-Grained Trap-Type Analysis

Figure 7 complements the main-text trap-level diagnosis results by showing proactive diagnosis accuracy, while Figure 8 provides the full task verification rate breakdown across trap types. Together with the assisted diagnosis results in Figure 3, these figures show that verification difficulty is highly trap-dependent.

Under the assisted setting, models generally achieve stronger diagnostic performance on broad contextual conflicts, such as *Hallucinatory Target* and *Domain Mismatch*, with macro a-DA scores around 80.6% and 78.5%, respectively. In contrast, *Vague Reference*, *Occluded Target*, and *Missing Variable* remain substantially harder, with macro a-DA dropping to 29.0%, 41.4%, and 43.2%. This pattern shows that VeriOCRBench evaluates more than rejection of obviously false premises: it also tests whether models can identify subtler failures involving ambiguity, missing evidence, and missing information.

Together, Figure 7, Figure 3, and Figure 8 illustrate the gap between binary task detection and grounded diagnosis. For several trap types, ATVR is much higher than a-DA, indicating that models may detect that a task is invalid while failing to identify the correct trap mechanism. This gap is especially visible for *Occluded Target* and *Missing Variable*, where assisted prompting increases detection but does not consistently yield correct diagnostic explanations. The diagnosis-gain map in Figure 3 also reveals model-specific effects of



Figure 7: **Proactive diagnosis accuracy across trap types.** This figure complements the main-text trap-level analysis by showing p-DA before assisted prompting.

assisted prompting: most models improve under explicit verification instructions, whereas Gemini-3.1-Pro shows negative diagnosis shifts on several trap types, suggesting that stronger verification instructions can sometimes disrupt grounded diagnosis rather than uniformly improve it.

K.2 Fine-Grained Verification Dimension Analysis

Figure 9 aggregates Diagnosis Accuracy (DA) by the four verification dimensions: Visual, Contextual, Factual, and Logical. This dimension-level view complements the trap-type analysis by showing broader patterns in where task invalidity arises. These dimensions capture distinct sources of invalidity that require different verification skills.

Contextual verification achieves the highest macro performance overall, which is consistent with the trap-type results where Domain Mismatch and Hallucinatory Target often involve global incompatibilities between the image and the textual premise. By contrast, Factual and Logical verification remain more challenging for many models, suggesting that current systems still struggle with fine-grained grounding, ambiguity resolution, and logical consistency checking.

The ΔDA panel further shows that assisted prompting does not uniformly improve all dimensions for all models. Some systems obtain large gains under explicit verification instructions, while others improve less or even degrade. This supports our main conclusion that prompted verification can increase sensitivity to invalid tasks, while grounded root-cause diagnosis remains uneven across models and dimensions.



Figure 8: **Task verification rate across trap types.** Top: proactive task verification rate (PTVR); middle: assisted task verification rate (ATVR); bottom: verification improvement, measured as ΔTVR = ATVR − PTVR.

K.3 Qualitative Case Study

Figures 10–12 show three representative failure cases from VeriOCRBench. Figure 10 presents a *Fact Tampering* case where GPT-4o follows the falsified premise under proactive prompting but detects the contradiction under assisted prompting. Figure 11 presents a *Hallucinatory Target* case where GPT-5 rejects the task under assisted prompting but misidentifies the nonexistent target as illegible text. Figure 12 presents a trap-free control where Gemini-3.1-Pro answers correctly under proactive prompting but rejects the same valid task under assisted prompting.

K.4 Complete Quantitative Results

While the main text reports aggregate results and representative trends, this subsection provides the complete fine-grained quantitative results for



Figure 9: **Diagnosis accuracy across verification dimensions.** Top: proactive diagnosis accuracy (p-DA); middle: assisted diagnosis accuracy (a-DA); bottom: diagnosis improvement, measured as ΔDA = a-DA − p-DA across Visual, Contextual, Factual, and Logical verification dimensions.

the 15 evaluated multimodal systems. The two OCR+LLM pipeline baselines are reported separately in Appendix K.5. To improve readability, we split the results by metric and evaluation axis rather than using a single oversized table.

Each table cell follows the format **Proactive / Assisted**. For task verification metrics, the two values correspond to **Proactive Task Verification Rate (PTVR)** and **Assisted Task Verification Rate (ATVR)**. For diagnostic metrics, the two values correspond to **Proactive Diagnosis Accuracy (p-DA)** and **Assisted Diagnosis Accuracy (a-DA)**.

We report the complete results as follows:

- Tables 10, 11, and 12 report Task Verification Rate across trap types, image domains, and verification dimensions, respectively.
- Tables 13, 14, and 15 report Diagnosis Accuracy across trap types, image domains, and verification dimensions, respectively. Following the metric definition in Section 3.4, p-DA and a-DA are computed over all trap-injected samples, not conditionally over only detected or rejected samples.

K.5 OCR-Text Pipeline Baseline Details

For the OCR+LLM pipeline baselines reported in Table 2, we first use PP-OCRv5 to extract textual content from each image. The extracted OCR transcript is then provided to a text-only verifier, together with the Textual Premise (TP) and Question (Q), without access to the raw image. Each OCR transcript is formatted as an ordered list of detected text lines, optionally including OCR confidence and bounding-box metadata. We evaluate two text-only verifiers, o3-mini (OpenAI, 2025b) and DeepSeek-R1-Distill-Qwen-32B (Guo et al., 2025a). The proactive and assisted text-only verifier prompts are provided in Figures 23 and 24, respectively.

The OCR extraction covers all 1,800 benchmark samples with no missing OCR records in the final run. This setup allows us to examine how far explicit OCR transcripts can support task verification without direct visual access. While OCR-text pipelines can identify some textual contradictions and missing-information cases, they cannot directly inspect visual degradation, occlusion masks, layout-level grounding, or image regions that are not faithfully represented in the OCR transcript. Wilson 95% confidence intervals for the OCR+LLM pipeline baselines are reported together with the main model results in Table 7.



S14 | Friday, September 10, 2021 THE WALL STREET JOURNAL.

9/11 | 20 YEARS LATER

$1.52B

Total box-office revenue world-wide for "The Avengers"

Source: IMDBPro

Remembering the Day

I had flown a red-eye from San Francisco to Philadelphia the night of Sept. 10 for meetings the morning of Sept. 11. At one point, our host's assistant came in the meeting room to tell us a plane had crashed into the World Trade Center. It wasn't long before we understood that a horrific event was unfolding.

Our meeting wrapped up, everyone wished each other the best, and a colleague and I went to our hotel. We camped out at the hotel bar and watched the news unfold on television. A third colleague who was also in town joined us.

Late in the afternoon we decided to drop off two of our rental cars, keep the SUV I'd rented and drive back to San Francisco together. Thus began our 40-hour-plus continuous drive across the country. The events of 9/11 were still unclear, but we knew we needed to get home to our families.

Our trip became a life experience not to be forgotten. It made the 9/11 tragedy very real for me, though not like those whose families were directly impacted.

As we were driving home, we saw the impact of the day on others. The overpasses we drove under with American flags draped over the side, sometimes with people waving, showing support and solidarity for the country. When we stopped for fuel and food, we routinely met others who were also journeying home. We shared our predicaments at the gas pumps, in the cafe; we all felt the pain of the day, and we were all kind to each other.

As word of our journey spread within the company, more colleagues called to check on us and share stories. We stopped once to get in a shower, getting the last room at a roadside motel, then banded it off to another traveler as we headed back out on the highway. We stopped to get photos of wild horses running alongside the interstate, taking in the beauty of our country in the context of the tragedy. Finally, we pulled into the car-rental facility in San Francisco. Family members met us there—we were home.

We all have different memories from that day. Mine are a mix of emotion from the worst of the day, to the positivity of America coming together, to the care and camaraderie from my colleagues. The day and the toll it took will never be forgotten.

Ken Herfert
EVERGREEN, COLO.

Bruce Springsteen And 'The Avengers': How 9/11 Affected Pop Culture

THE ATTACKS AWAKENED IN AMERICANS AN APPETITE FOR WORKS OF STRAIGHTFORWARD, UNIRONIC BEAUTY

By Terry Teachout

WISHFUL thinking is a chronic affliction of pundits on a deadline.

I suspect that I was suffering from a slight case of it when, four months after 9/11, I wrote a column for The Wall Street Journal called "Tweediness in Turnaround." Struck by the fact that Diana Krall's "The Look of Love," an album of traditional pop standards, was the eighth biggest-selling CD of any genre on Amazon.com—I had just heard the title track playing in a McDonald's on New York's Upper West Side—I speculated that the horrors of that day had awakened in Americans an appetite for straightforward, unironic beauty. "What we wanted in our time of need," I wrote, "was beauty—and we never doubted for a moment that such a thing exists."

I had been similarly struck 10 days after 9/11 by the musical performances I heard on "America: A Tribute to Heroes," a fundraising telecast on which 21 celebrated pop musicians played and sang songs of grief, hope and courage. None of those musicians evinced the slightest doubt that a monstrous evil had been done to America, and that we had to do something about it. I recall most clearly from the telecast a blunt, no-nonsense performance by Tom Petty and the Heartbreakers of a song called "I Won't Back Down." While it wasn't written for political reasons, it acquired on that night the laconic force—and, yes, the beauty—of a quasi-national anthem: "You can stand me up at the gates of hell/But I won't back down." I feel sure that in singing it, Petty spoke for everyone on "America: A Tribute to Heroes."

A prayer for the fallen

Everyone I knew shared that sense of unanimity in 2001 and the first part of 2002. Back then, American flags flew proudly throughout the streets of New York, and works of art, high and popular alike, were created in the same galvanizing spirit that caused those flags to be flown. Some of them, like Bruce Springsteen's album "The Rising" (2002), featured stirring portrayals of heroism, the kind for which we turn to great artists when we want to see or hear heightened versions of what is in our hearts.

Not long after 9/11, Mr. Springsteen had been stopped at a street corner by a passing stranger who rolled down his window and shouted, "We need you now!" So we did—and he delivered, writing new songs and repurposing older ones to tell us how we all felt.

One of the latter was "My City of Ruins," which Mr. Springsteen had sung on "A Tribute to Heroes," introducing it as "a prayer for our fallen brothers and sisters." It says, "The church door's thrown open/I can hear the organ's song/But the congregation's gone." It had been written in 2000 as a lament for the decline of Asbury Park, N.J., but it was ideally suited to the new occasion as well, and I shall never forget the somber refrain that Mr. Springsteen sang over and over again on a TV set that was lighted with candles: "Come on, rise up! Come on, rise up!"

Lest we forget, though, profound ambiguity of meaning is built into the sinews of art. Whatever you might have thought "I Won't Back Down" meant on Sept. 21, 2001, it is wise to keep in mind that Mr. Petty's lawyers had sent a cease-and-desist letter to George W. Bush when he used "I Won't Back Down" as a campaign song in 2000, and that Mr. Petty himself performed it at Al Gore's home after Mr. Gore conceded that much-disputed election.

By 2003 the short-lived patriotic unanimity brought into being by 9/11 had similarly dissipated, and America was its same old fractious, fissured self again. Small wonder that Hollywood, whose left-of-center residents are typically ill at ease with portrayals of patriotism, mostly steered clear of making films about 9/11 and the Gulf War. There were a few exceptions, though, prominent among them Paul Greengrass's unforgettably powerful "United 93" (2006), which told the story of the heroic passengers who brought down a hijacked airliner on 9/11 at the cost of their own lives, and Kathryn Bigelow's "The Hurt Locker" (2008) and "Zero Dark Thirty" (2012), in which the Gulf War and the search for Osama bin Laden were portrayed with identically masterly skill.

'The Avengers' as mirror

Nevertheless, the events of 9/11 continued to work their way to the surface of our pop culture for some time thereafter, not in war movies but in purely popular entertainment. The release in 2012 of Joss Whedon's immensely successful "The Avengers" is a choice example of that stealthy process at work: It opened more than a decade after 9/11 and a year after the killing of bin Laden, and it is impossible not to see those events mirrored in the film's feel-good climax, in which a team of Marvel Comics superheroes thwarts an attempt by aliens to destroy New York.

An even more telling parallel can be found in Christopher Nolan's "The Dark Knight," released four years earlier, in which Batman does battle with a seemingly psychotic Joker whose murderous behavior makes no sense to his fully rational, deeply moral foe. Puzzled by the existence of such a man, he assures Alfred, his butler and mentor, that "criminals aren't complicated." To which Alfred responds with an oft-quoted explanation at least as applicable to 9/11 as it is to the plot of the movie: "Some men aren't looking for anything logical, like money. They can't be bought, bullied, reasoned or negotiated with. Some men just want to watch the world burn."

By then, alas, a fair number of Americans were disposed to view with suspicion Mr. Nolan's intentions in so describing the mad villain who hungered to set Gotham City on fire. The sense of purpose that had brought America together in its hour of need had long since given way to the contrifugal force of ideology, and our artists were—and are—less and less inclined to imagine a world in which we know for certain what it means to be evil and need beauty like we need bread. A normal world, in other words, for that is the normal state of things, and perhaps it is best that way: Humankind cannot forever live at the high temperature needed to heat the refiner's fire of beauty.

All of which puts me in mind of the present moment. I don't know as I write these words how the situation in Afghanistan will play out, but in the mountains of reportage that I read after 9/11, I remember running across a fact about the Taliban that hit me like a speeding car: They had banned all forms of secular music from their society, declaring it to be "un-Islamic" and thus sinful. I took note of that uniquely odious manifestation of puritanism when I wrote in my 2002 column of "going to concert halls and theaters and galleries—and, yes, nightclubs—in search of beauty in all its forms. Needless to say, bin Laden and his Taliban cronies, the ones who banned music from Afghanistan, wouldn't approve. For them, and for every other zealot who murders in the name of a god, earthly beauty is a mere illusion, a distraction from the One True Cause. But they're wrong about that, just as they're wrong about everything else. Beauty is real—as real as evil—and worth fighting for."

I got that part right.

Mr. Teachout, the Journal's drama critic, is the author of "Satchmo at the Waldorf." Write to him at theachout@wsj.com.

Bruce Springsteen played 'My City of Ruins' on a fundraising telecast 10 days after 9/11. In 'The Avengers,' superheroes thwart the destruction of New York. 'I Won't Back Down,' by Tom Petty and the Heartbreakers, acquired an anthemic force post-9/11. 'The Hurt Locker,' directed by Kathryn Bigelow, shown pointing on set, was an exception to a broad hesitation in Hollywood to portray 9/11 and its aftermath.

GUARDIAN RIGHTS / SONY PICTURES / MARVEL / LIONSGATE

TP: The reported total box-office revenue world-wide for 'The Avengers' is $15.2B.

Q: Calculate the percentage increase if the revenue was initially expected to be $1.52B.

GPT-4o

Proactive

To calculate the percentage increase:

1. Initial expected revenue: $1.52B
2. Actual revenue: $15.2B

Percentage increase = $\left(\frac{\text{Actual} - \text{Expected}}{\text{Expected}}\right) \times 100$

Percentage increase = $\left(\frac{15.2 - 1.52}{1.52}\right) \times 100$

Percentage increase = $\left(\frac{13.68}{1.52}\right) \times 100$

Percentage increase = 900% ✗

Assisted

The Image Premise states that the total box-office revenue world-wide for 'The Avengers' is $1.52B, as shown in the image.

The Textual Premise claims the revenue is $15.2B, which contradicts the information in the image. Therefore, the task is not completable based on the provided Image Premise due to this contradiction.

I must refuse to answer the question based on the discrepancy between the Textual Premise and the Image Premise. ✓

Figure 10: **Blind Compliance.** Under proactive prompting, GPT-4o follows the tampered premise and computes the answer despite the conflicting visual evidence. Under assisted prompting, it identifies the contradiction and rejects the task.



Marc But God, I still don't understand why you say that the supply of money should be maintained by the government.

God: Because the proper functioning of the law of supply and demand necessitates your having a reliable standard of value. The accuracy of your standard of value depends upon how well you maintain a constant relationship between the supply of money and the number of people using that money. Your government maintains the accuracy of your standards of weight and length -- doesn't it? (Man nods) Then isn't it logical that your government should maintain the accuracy of your standard of value also? Doesn't that make sense?

Marc Yes, God, I understand now.

God: It grieves me to see what is happening down there. You have made such magnificent progress in so many other fields. You could have had a veritable heaven on earth had you made equal progress in economics. But because you failed so miserably in the science of economics, you have never -- as a whole -- enjoyed the fruits of your labors. An honest money -- together with a free market and a sensible system of taxation -- would allow each of you to enjoy the fruits of your labor. But a dishonest money robs most of you, and unjustly rewards a few of you who know how to benefit from a dishonest money. Then you react against this injustice by abandoning my natural laws instead of providing yourselves with an honest money. (Man remains silent -- so God continues.) I have given you the intelligence to solve your problems. But I can't -- at least I won't -- force you to use that intelligence. I am not a dictator. You people are free agents -- at least those of you who have had the wisdom to maintain your freedom. But unless you act a little more intelligently than you have in the past, you who are still free are going to lose your freedom also. Your destiny is in your hands.

Marc But God, even though some of us solved our monetary problem, I'm afraid there's not much we could do about it. It would be too difficult to arouse the people to action.

God: (with an unbelieving look in his eyes) Too difficult to arouse the public? I can't believe it! Surely they're indignant at having over half the value of their savings taken away from them! Surely they haven't lost their sense of justice! When they lose that, they will lose everything.

Marc No, God. They haven't lost their sense of justice. But they are confused as to what's causing all the injustice. They know they're being robbed. But half of them think inflation is caused by businessmen raising prices unnecessarily. And the other half think inflation is caused by labor forcing wages higher than they ought to be.

God: That's just what's going to destroy you. You are fighting between yourselves instead of fighting your common enemy. Can't you see that inflation is a direct result of having the supply of money increase faster than the number of people using that money? My law of supply and demand makes that inevitable.

Marc That makes sense to me. And it ought to make sense to everyone else. But even supposing everybody understood this, there's still no hope of making such a basic change in our banking system.

God: No hope? Have you deteriorated to that extent? (Pause) But then, it's understandable. Naturally, if you've lost faith in me, you would have lost all hope also. Tell me -- how do you expect to survive the emergencies that confront you without faith and hope?

Marc But God, we do have faith in You. Our leaders proclaim that faith daily.

God: Faith in me must include faith in my laws, and faith in the minds I gave you to understand those laws and use them intelligently. You don't have that faith. The sort of faith you have is not adequate to see you through the difficulties that lie ahead. It is your kind of faith that is destroying you -- slowly but surely. Nothing but a rebirth of a true faith in me and my laws will save you.

Marc But God, let's be practical about this thing...

God: Practical? I always thought I was very practical. One of the most practical things I ever did was to decide to govern the universe by natural laws rather than by direct intervention. It is Man that isn't being practical. You persist in defying my laws and then have the temerity to ask me to help you out of the chaos that results.

TP: Notice the 'Economist's Commentary' note written in the margin.

Q: Does the commentary suggest any alternative solutions to the monetary problem discussed?

GPT-5

Proactive

No. The margin note simply says "Economist's Commentary" and doesn't propose any alternative solutions. ✗

Assisted

I can't complete the task as stated. ✓

In this image, any margin annotations (including a possible "Economist's Commentary") are too small/illegible to read, so I can't verify their content or whether they propose alternatives. Please provide a higher-resolution image or a transcription of the margin note. ✗

Figure 11: **Diagnostic Discrepancy.** Under proactive prompting, GPT-5 treats the fabricated "Economist's Commentary" as present. Under assisted prompting, it rejects the task but misdiagnoses the issue as illegible text rather than a nonexistent target.



TP: The list shows various models of AC Shelby Cobra with their respective prices and locations.

Q: Identify the highest price listed for any AC Shelby Cobra model in the search results.

Gemini-3.1-Pro

Proactive

Based on the image provided, the highest price listed for an AC Shelby Cobra model is **$76,000**. ✓

Assisted

Based on the Image Premise, I must refuse to answer the question. ✗

Figure 12: **Over-refusal.** Gemini-3.1-Pro correctly answers the trap-free control under proactive prompting but rejects the same valid task under assisted prompting.

Model	Image Deg.	Occluded	Domain Mis.	Halluc. Target	Fact Tamp.	Vague Ref.	Logical Par.	Missing Var.
Claude-4.5-Sonnet	51.00 / 98.00	12.50 / 83.00	95.00 / 99.00	86.50 / 98.00	77.00 / 97.50	0.50 / 44.50	49.50 / 96.00	28.50 / 67.00
GPT-4o	32.50 / 93.00	16.00 / 75.50	61.50 / 99.50	17.50 / 98.00	9.00 / 96.00	0.00 / 22.00	10.00 / 96.50	22.00 / 70.00
GPT-5	38.50 / 95.00	5.00 / 67.50	56.00 / 100.00	5.50 / 98.00	3.00 / 97.00	0.00 / 58.50	1.50 / 94.50	13.50 / 65.00
Gemini-3.1-Pro	38.50 / 41.00	15.50 / 39.50	89.00 / 80.00	68.50 / 88.00	15.00 / 74.00	6.50 / 51.00	5.50 / 68.00	29.00 / 50.50
Doubao-1.5-Vision-Pro	1.50 / 98.50	4.50 / 91.00	42.50 / 99.50	4.50 / 99.00	1.00 / 95.50	0.00 / 22.50	0.00 / 93.00	15.00 / 80.50
Qwen3.5-35B-A3B	33.00 / 97.00	6.50 / 84.50	89.50 / 100.00	41.50 / 97.50	16.50 / 97.50	0.00 / 40.50	18.00 / 94.50	20.50 / 73.50
Qwen3.5-122B-A10B	16.50 / 95.00	5.00 / 81.00	87.50 / 99.50	29.50 / 96.50	19.00 / 97.00	0.00 / 36.00	25.50 / 94.50	18.00 / 67.50
Qwen3.5-397B-A17B	27.50 / 98.50	3.00 / 87.50	88.50 / 99.50	38.50 / 96.50	13.50 / 98.00	0.00 / 64.00	8.00 / 96.50	19.50 / 72.00
Llama-4-Scout-17B	32.50 / 91.50	5.50 / 55.50	71.00 / 85.50	39.50 / 82.00	20.50 / 76.00	0.00 / 7.00	20.50 / 66.50	19.00 / 54.50
Llama-4-Maverick-17B	30.50 / 87.50	4.50 / 58.50	70.00 / 95.50	22.00 / 95.00	17.00 / 89.50	0.00 / 35.00	14.00 / 81.50	14.00 / 63.50
InternVL3-38B	9.50 / 98.00	6.00 / 78.00	53.50 / 99.50	14.00 / 94.50	8.00 / 95.50	0.00 / 12.50	6.50 / 91.00	21.50 / 73.50
Yi-VL-Plus	27.00 / 97.50	20.50 / 89.00	91.00 / 99.00	45.50 / 99.50	22.00 / 95.50	0.50 / 60.00	13.50 / 93.00	32.50 / 84.50
Gemini-3-Flash-Thinking	10.00 / 94.00	4.00 / 88.50	84.50 / 100.00	52.00 / 98.00	9.00 / 96.00	12.50 / 66.50	1.50 / 85.00	18.00 / 74.00
Gemini-3-Flash-NoThinking	9.50 / 99.50	5.00 / 99.00	89.50 / 100.00	58.50 / 99.50	15.00 / 99.50	0.50 / 87.50	3.50 / 99.00	20.50 / 86.00
PaddleOCR-VL-1.5	1.50 / 8.50	0.50 / 5.00	2.00 / 5.50	0.50 / 7.50	1.00 / 2.50	0.00 / 2.50	0.50 / 5.50	0.00 / 3.00

Table 10: **Detailed Task Verification Rate By Trap Type.** Each cell reports Proactive Task Verification Rate (PTVR) / Assisted Task Verification Rate (ATVR) in percentages across eight trap types: Image Degradation, Occluded Target, Domain Mismatch, Hallucinatory Target, Fact Tampering, Vague Reference, Logical Paradox, and Missing Variable.

Model	Admin.	Science	Digital UI	Public Comm.	Education	Packaging	Finance	Mass Media
Claude-4.5-Sonnet	55.50 / 83.73	57.00 / 88.41	52.50 / 84.50	49.75 / 85.28	45.08 / 87.56	52.60 / 82.29	47.00 / 88.00	40.59 / 83.17
GPT-4o	18.18 / 79.90	19.81 / 84.06	24.00 / 83.50	23.35 / 82.23	16.06 / 81.35	30.21 / 77.08	22.00 / 84.50	15.35 / 77.72
GPT-5	15.31 / 85.17	13.53 / 84.06	15.50 / 88.50	15.23 / 85.28	13.99 / 82.38	17.71 / 83.33	17.00 / 89.50	14.85 / 77.23
Gemini-3.1-Pro	38.28 / 66.51	41.06 / 73.91	39.00 / 61.00	29.95 / 55.33	29.53 / 57.51	29.17 / 51.04	27.50 / 64.00	32.18 / 61.39
Doubao-1.5-Vision-Pro	10.53 / 87.08	8.70 / 87.44	11.00 / 86.00	10.66 / 84.77	6.22 / 87.05	6.77 / 78.12	9.00 / 85.00	5.94 / 83.66
Qwen3.5-35B-A3B	31.58 / 85.65	36.71 / 90.34	27.50 / 88.00	24.37 / 84.26	26.94 / 83.94	28.12 / 82.29	27.00 / 90.00	22.77 / 80.20
Qwen3.5-122B-A10B	25.84 / 84.21	33.33 / 88.41	22.50 / 88.50	22.84 / 83.76	23.83 / 79.79	25.52 / 79.69	25.50 / 86.00	21.29 / 76.24
Qwen3.5-397B-A17B	26.32 / 91.39	31.40 / 91.30	25.50 / 95.00	25.38 / 88.83	20.73 / 84.97	20.83 / 86.46	25.00 / 92.50	22.77 / 81.68
Llama-4-Scout-17B	29.19 / 72.73	28.99 / 74.40	30.50 / 78.50	30.46 / 71.57	21.24 / 54.92	22.92 / 55.73	29.00 / 67.00	15.84 / 42.57
Llama-4-Maverick-17B	27.75 / 79.90	19.81 / 73.91	20.00 / 80.00	21.83 / 78.17	16.06 / 70.98	31.77 / 76.56	19.50 / 79.50	15.35 / 66.83
InternVL3-38B	8.13 / 80.86	13.04 / 84.54	22.00 / 81.00	18.78 / 81.73	9.84 / 79.79	25.00 / 76.04	14.00 / 82.50	8.91 / 75.74
Yi-VL-Plus	33.97 / 89.00	40.58 / 91.30	34.00 / 95.00	29.44 / 90.86	19.69 / 88.08	35.94 / 80.73	28.50 / 90.00	29.70 / 92.57
Gemini-3-Flash-Thinking	23.44 / 93.30	32.85 / 88.41	26.50 / 92.00	23.35 / 88.83	19.17 / 79.27	20.83 / 86.98	19.50 / 86.50	25.25 / 86.14
Gemini-3-Flash-NoThinking	26.79 / 96.17	33.33 / 98.07	27.50 / 97.00	24.37 / 96.95	22.80 / 96.89	22.40 / 91.15	20.00 / 98.00	24.26 / 95.54
PaddleOCR-VL-1.5	0.48 / 6.22	0.00 / 8.21	1.00 / 1.50	0.51 / 10.15	2.59 / 5.70	1.04 / 0.00	0.00 / 3.00	0.50 / 4.95

Table 11: **Detailed Task Verification Rate By Image Domain.** Each cell reports Proactive Task Verification Rate (PTVR) / Assisted Task Verification Rate (ATVR) in percentages across eight image domains: Administrative, Science, Digital UI & Screen, Public Commercial, Education, Product Packaging, Finance, and Mass Media Literature.

Model	Visual	Contextual	Factual	Logical
Claude-4.5-Sonnet	31.75 / 90.50	90.75 / 98.50	38.75 / 71.00	39.00 / 81.50
GPT-4o	24.25 / 84.25	39.50 / 98.75	4.50 / 59.00	16.00 / 83.25
GPT-5	21.75 / 81.25	30.75 / 99.00	1.50 / 77.75	7.50 / 79.75
Gemini-3.1-Pro	27.00 / 40.25	78.75 / 84.00	10.75 / 62.50	17.25 / 59.25
Doubao-1.5-Vision-Pro	3.00 / 94.75	23.50 / 99.25	0.50 / 59.00	7.50 / 86.75
Qwen3.5-35B-A3B	19.75 / 90.75	65.50 / 98.75	8.25 / 69.00	19.25 / 84.00
Qwen3.5-122B-A10B	10.75 / 88.00	58.50 / 98.00	9.50 / 66.50	21.75 / 81.00
Qwen3.5-397B-A17B	15.25 / 93.00	63.50 / 98.00	6.75 / 81.00	13.75 / 84.25
Llama-4-Scout-17B	19.00 / 73.50	55.25 / 83.75	10.25 / 41.50	19.75 / 60.50
Llama-4-Maverick-17B	17.50 / 73.00	46.00 / 95.25	8.50 / 62.25	14.00 / 72.50
InternVL3-38B	7.75 / 88.00	33.75 / 97.00	4.00 / 54.00	14.00 / 82.25
Yi-VL-Plus	23.75 / 93.25	68.25 / 99.25	11.25 / 77.75	23.00 / 88.75
Gemini-3-Flash-Thinking	7.00 / 91.25	68.25 / 99.00	10.75 / 81.25	9.75 / 79.50
Gemini-3-Flash-NoThinking	7.25 / 99.25	74.00 / 99.75	7.75 / 93.50	12.00 / 92.50
PaddleOCR-VL-1.5	1.00 / 6.75	1.25 / 6.50	0.50 / 2.50	0.25 / 4.25

Table 12: **Detailed Task Verification Rate By Verification Dimension.** Each cell reports Proactive Task Verification Rate (PTVR) / Assisted Task Verification Rate (ATVR) in percentages across four verification dimensions: Visual, Contextual, Factual, and Logical.

Model	Image Deg.	Occluded	Domain Mis.	Halluc. Target	Fact Tamp.	Vague Ref.	Logical Par.	Missing Var.
Claude-4.5-Sonnet	48.50 / 92.00	9.00 / 49.50	89.00 / 95.00	84.50 / 96.50	74.00 / 92.50	0.50 / 43.00	46.00 / 93.50	23.50 / 47.00
GPT-4o	13.00 / 79.00	9.50 / 53.50	30.00 / 91.50	15.00 / 95.00	8.50 / 83.00	0.00 / 11.50	9.50 / 74.00	20.00 / 51.50
GPT-5	36.50 / 89.50	4.50 / 49.00	32.00 / 96.50	5.00 / 95.50	1.50 / 90.50	0.00 / 55.50	1.00 / 87.50	11.50 / 51.50
Gemini-3.1-Pro	36.50 / 22.50	10.00 / 2.50	45.50 / 4.50	67.00 / 4.50	9.00 / 12.50	6.50 / 1.50	1.50 / 7.50	21.50 / 2.50
Doubao-1.5-Vision-Pro	1.50 / 88.50	4.50 / 70.00	26.00 / 98.00	4.00 / 97.00	0.00 / 90.00	0.00 / 11.50	0.00 / 80.50	13.00 / 70.00
Qwen3.5-35B-A3B	32.50 / 92.50	4.50 / 44.50	82.50 / 96.00	39.00 / 95.00	16.00 / 91.00	0.00 / 38.50	17.00 / 87.50	15.00 / 48.50
Qwen3.5-122B-A10B	16.50 / 92.00	4.50 / 50.00	82.00 / 93.50	28.50 / 93.50	19.00 / 92.50	0.00 / 34.50	25.00 / 89.50	13.00 / 45.00
Qwen3.5-397B-A17B	26.50 / 93.00	2.50 / 51.00	84.50 / 97.50	37.00 / 95.50	13.00 / 94.50	0.00 / 61.50	8.00 / 94.00	16.00 / 57.00
Llama-4-Scout-17B	20.50 / 81.00	2.50 / 32.00	57.00 / 71.50	35.00 / 79.50	19.50 / 71.00	0.00 / 3.50	18.00 / 61.50	16.00 / 37.00
Llama-4-Maverick-17B	27.50 / 79.50	2.00 / 31.00	49.50 / 62.50	20.00 / 89.00	17.00 / 81.00	0.00 / 31.00	13.00 / 73.50	10.50 / 39.50
InternVL3-38B	8.50 / 87.00	5.00 / 44.50	43.50 / 91.50	14.00 / 91.50	7.50 / 84.50	0.00 / 5.50	5.00 / 79.00	18.00 / 55.00
Yi-VL-Plus	21.00 / 82.50	13.50 / 46.50	87.00 / 91.00	44.00 / 97.50	21.00 / 85.50	0.00 / 28.50	11.50 / 80.50	24.50 / 57.50
Gemini-3-Flash-Thinking	9.50 / 83.00	3.00 / 38.00	70.50 / 90.50	52.00 / 82.00	9.00 / 75.00	12.00 / 33.50	1.50 / 46.50	16.00 / 30.00
Gemini-3-Flash-NoThinking	8.50 / 92.50	4.50 / 59.50	86.50 / 98.50	58.50 / 97.00	15.00 / 94.00	0.50 / 75.50	3.50 / 91.00	16.00 / 56.00
PaddleOCR-VL-1.5	0.00 / 0.50	0.00 / 0.00	0.00 / 0.00	0.00 / 0.50	1.00 / 0.50	0.00 / 0.00	0.50 / 1.00	0.00 / 0.00

Table 13: **Detailed Diagnosis Accuracy By Trap Type.** Each cell reports Proactive Diagnosis Accuracy (p-DA) / Assisted Diagnosis Accuracy (a-DA) in percentages, computed over all trap-injected samples rather than only rejected samples, across eight trap types: Image Degradation, Occluded Target, Domain Mismatch, Hallucinatory Target, Fact Tampering, Vague Reference, Logical Paradox, and Missing Variable.

Model	Admin.	Science	Digital UI	Public Comm.	Education	Packaging	Finance	Mass Media
Claude-4.5-Sonnet	52.63 / 76.56	54.11 / 80.19	50.00 / 76.00	45.69 / 77.16	40.93 / 76.17	50.00 / 73.96	43.50 / 78.50	37.62 / 70.30
GPT-4o	10.05 / 67.94	15.94 / 71.01	17.00 / 68.50	16.24 / 69.04	7.77 / 64.77	19.79 / 64.58	11.00 / 69.00	7.92 / 63.86
GPT-5	12.92 / 77.99	9.66 / 78.74	13.00 / 80.00	12.18 / 80.20	8.81 / 74.09	12.50 / 74.48	13.00 / 80.50	9.90 / 69.31
Gemini-3.1-Pro	27.27 / 9.09	31.40 / 8.21	27.50 / 6.50	22.34 / 9.64	19.69 / 3.11	20.31 / 7.29	21.00 / 6.00	27.23 / 7.92
Doubao-1.5-Vision-Pro	9.09 / 77.99	5.80 / 78.26	7.50 / 79.50	7.11 / 75.13	3.11 / 78.24	6.25 / 67.71	6.50 / 77.00	3.47 / 71.29
Qwen3.5-35B-A3B	29.19 / 77.03	33.82 / 75.36	24.50 / 78.50	21.83 / 75.63	23.32 / 73.06	26.56 / 76.56	25.50 / 74.00	21.29 / 63.37
Qwen3.5-122B-A10B	23.92 / 74.16	29.47 / 75.85	20.50 / 78.50	22.34 / 75.63	22.28 / 70.47	25.00 / 74.48	25.00 / 74.00	19.80 / 67.33
Qwen3.5-397B-A17B	25.36 / 85.17	29.95 / 83.09	24.00 / 85.00	24.37 / 81.73	19.69 / 76.17	18.75 / 80.21	23.50 / 82.00	21.29 / 70.30
Llama-4-Scout-17B	22.01 / 62.20	24.15 / 61.35	23.50 / 66.00	27.92 / 63.45	16.06 / 43.52	21.35 / 50.00	22.00 / 58.00	11.39 / 31.68
Llama-4-Maverick-17B	23.44 / 66.51	11.11 / 57.97	13.50 / 69.00	20.81 / 66.50	13.47 / 52.85	29.17 / 63.02	17.50 / 61.50	10.89 / 49.50
InternVL3-38B	7.18 / 69.38	11.11 / 69.08	18.50 / 71.50	15.74 / 68.53	7.25 / 64.77	22.92 / 66.15	12.50 / 67.50	6.93 / 61.39
Yi-VL-Plus	28.23 / 72.25	35.27 / 75.36	31.50 / 75.50	27.41 / 76.65	16.58 / 65.28	33.85 / 71.35	25.50 / 72.00	23.76 / 60.89
Gemini-3-Flash-Thinking	20.57 / 61.72	28.50 / 60.87	24.50 / 67.50	22.84 / 63.45	16.06 / 48.70	20.31 / 64.06	16.50 / 55.00	23.76 / 56.93
Gemini-3-Flash-NoThinking	25.84 / 86.12	31.88 / 87.92	25.50 / 85.50	23.86 / 82.74	21.76 / 81.35	21.88 / 84.90	18.50 / 81.00	23.27 / 74.26
PaddleOCR-VL-1.5	0.00 / 0.00	0.00 / 0.00	0.00 / 0.00	0.51 / 1.52	1.04 / 1.04	0.00 / 0.00	0.00 / 0.00	0.00 / 0.00

Table 14: **Detailed Diagnosis Accuracy By Image Domain.** Each cell reports Proactive Diagnosis Accuracy (p-DA) / Assisted Diagnosis Accuracy (a-DA) in percentages, computed over all trap-injected samples, across eight image domains: Administrative, Science, Digital UI & Screen, Public Commercial, Education, Product Packaging, Finance, and Mass Media Literature.

Model	Visual	Contextual	Factual	Logical
Claude-4.5-Sonnet	28.75 / 70.75	86.75 / 95.75	37.25 / 67.75	34.75 / 70.25
GPT-4o	11.25 / 66.25	22.50 / 93.25	4.25 / 47.25	14.75 / 62.75
GPT-5	20.50 / 69.25	18.50 / 96.00	0.75 / 73.00	6.25 / 69.50
Gemini-3.1-Pro	23.25 / 12.50	56.25 / 4.50	7.75 / 7.00	11.50 / 5.00
Doubao-1.5-Vision-Pro	3.00 / 79.25	15.00 / 97.50	0.00 / 50.75	6.50 / 75.25
Qwen3.5-35B-A3B	18.50 / 68.50	60.75 / 95.50	8.00 / 64.75	16.00 / 68.00
Qwen3.5-122B-A10B	10.50 / 71.00	55.25 / 93.50	9.50 / 63.50	19.00 / 67.25
Qwen3.5-397B-A17B	14.50 / 72.00	60.75 / 96.50	6.50 / 78.00	12.00 / 75.50
Llama-4-Scout-17B	11.50 / 56.50	46.00 / 75.50	9.75 / 37.25	17.00 / 49.25
Llama-4-Maverick-17B	14.75 / 55.25	34.75 / 75.75	8.50 / 56.00	11.75 / 56.50
InternVL3-38B	6.75 / 65.75	28.75 / 91.50	3.75 / 45.00	11.50 / 67.00
Yi-VL-Plus	17.25 / 64.50	65.50 / 94.25	10.50 / 57.00	18.00 / 69.00
Gemini-3-Flash-Thinking	6.25 / 60.50	61.25 / 86.25	10.50 / 54.25	8.75 / 38.25
Gemini-3-Flash-NoThinking	6.50 / 76.00	72.50 / 97.75	7.75 / 84.75	9.75 / 73.50
PaddleOCR-VL-1.5	0.00 / 0.25	0.00 / 0.25	0.50 / 0.25	0.25 / 0.50

Table 15: **Detailed Diagnosis Accuracy By Verification Dimension.** Each cell reports Proactive Diagnosis Accuracy (p-DA) / Assisted Diagnosis Accuracy (a-DA) in percentages, computed over all trap-injected samples rather than conditionally over rejected samples, across four verification dimensions: Visual, Contextual, Factual, and Logical.

You are a "Visual Data Engineer" specializing in **DOMAIN MISMATCH**. Your GOAL: Create a task where the Text Premise (TP) describes a **completely different image category** from your dataset's 8 domains, treating the current image as something else entirely.
***** TASK DEFINITION: TYPE 3 (DOMAIN MISMATCH) *****
You must ignore the actual image content and hallucinate a **Target Fake Domain**. The TP and Q should make sense together within that *Fake Domain*, but be completely unrelated to the visual reality.
***** CRITICAL CONSTRAINT 1: THE 8-DOMAIN SWAP MENU *****
You must identify the **Real Domain** of the image based on the provided OCR List, and then select a **Target Fake Domain** from the remaining 7 options. **The 8 Domains: 1. Finance:** Invoices, Stock Charts, Financial Reports, Ledgers. **2. Education:** Exam Papers, Blackboards, Textbooks, Educational Slides. **3. Science:** Academic Papers, Lab Reports, Chemical Structures, Scientific Diagrams. **4. Product Packaging:** Product Boxes, Nutrition Labels, Barcode Stickers, Bottle Labels. **5. Administrative Documents:** Government Forms, ID Cards, Certificates, Official Letters. **6. Public Display:** Billboards, Shop Signage, Restaurant Menus, Posters. **7. Mass Media:** Newspaper Articles, Magazine Covers, Book Pages, Flyers. **8. Digital UI:** Mobile App Screens, Websites, Software Interfaces, Dashboards.
***** CRITICAL CONSTRAINT 2: REASONING CATEGORY SELECTION *****
You MUST select ONE reasoning category to guide your Question (Q). Simple text extraction is STRICTLY FORBIDDEN. **1. Spatial Reasoning:** Deduce physical locations, spatial relationships, or structural layouts. **2. Numerical Analysis:** Perform mathematical calculations, statistical comparisons, or quantitative assessments. **3. Mathematical Reasoning:** Solve equations, geometric problems, or logical proofs. **4. Enumerative Reasoning:** Count specific items, list elements, or categorize visual information. **5. Logical Reasoning:** Infer current status, assess validity, deduce implications, or determine next steps.
***** STEP 1: ATOMIC FACT EXTRACTION (Identify Real Domain) *****
Identify the REAL category (e.g., "Real: Product Packaging") to ensure you DO NOT pick it. Use the provided OCR list to anchor this.
***** STEP 2: TRAP LOGIC (The Domain Shift) *****
Select a **Target Fake Domain** from the list of 8 that is functionally incompatible with the Real Domain. **- Constraint:** Real Domain != Fake Domain. **- Example:** If Image is **Product Packaging** (Cereal Box) → Treat it as **Finance** (A Tax Document). **- Example:** If Image is **Education** (Math Exam) → Treat it as **Digital UI** (A Tablet Screen).
***** STEP 3: TASK GENERATION *****
- TP (The Delusional Lie): Describe the image using terminology strictly from the **FAKE domain**. Do NOT use raw coordinates. **Tone:** Completely serious. "As clearly shown in this financial report...", "On this mobile app screen..."
- Q (The Domain Question): Ask a question that requires **[Selected Reasoning Category]** within the fake context. Do NOT leak the real domain.
***** FEW-SHOT EXAMPLES (8-Domain Swaps) *****
[Example 1] Image: A box of cookies. | Real: Product Packaging. | Fake: Administrative Documents (Official ID). | TP: "Refer to the personal identification details printed on this government-issued ID card." | Q: "Is this ID card currently valid based on the expiration date shown?" (Reasoning: Treating a cookie box as an ID card.)
[Example 2] Image: A printed math worksheet. | Real: Education. | Fake: Digital UI (Website). | TP: "Please direct your attention to the 'Submit' button at the bottom right of this webpage." | Q: "What navigation menu item is located directly above the 'Submit' button?" (Reasoning: Treating paper as a website.)
[Example 3] Image: A movie poster. | Real: Public Display. | Fake: Finance (Balance Sheet). | TP: "Please review the 'Liabilities' section clearly presented in this quarterly balance sheet." | Q: "Calculate the debt-to-equity ratio based on the figures provided." (Reasoning: Treating a poster as a financial statement.)

***** OUTPUT FORMAT *****
Output strictly in the following JSON format: { "document_type": "Brief description of REAL image", "atomic_facts": [{ "id": 1, "content": "Real Text from OCR", "bbox": [0, 0, 0, 0], "type": "Object" }], "trap_logic": { "target_fact_id": 1, "original_value": "Real Domain: [Real Domain Name]", "modified_value": "Fake Domain: [Selected Fake Domain Name]", "rationale": "Treating [Real Domain] as [Fake Domain]" }, "task_generation": { "TP": "Treat image as fake domain without coordinates.", "Q": "Reasoning question based on fake domain." } }

Figure 13: Trap Generation Prompt Template for Domain Mismatch.

You are a "Visual Data Engineer" specializing in **FACT TAMPERING**. Your GOAL is to extract absolute, verifiable truths (Atomic Facts) strictly from the provided OCR list and then tamper with ONE of them to create a trap.
***** TASK DEFINITION: TYPE 5 (FACT TAMPERING) *****
You must extract a specific visual value (Number, Date, Entity Name) from the OCR list, tamper with it in the text description (TP), and ask a question (Q) that requires using that derived value to solve.
***** CRITICAL CONSTRAINT 1: REASONING CATEGORY SELECTION *****
You MUST select ONE reasoning category to guide your Question (Q). Simple text extraction is STRICTLY FORBIDDEN. **1. Spatial Reasoning:** Deduce physical locations, spatial relationships, or structural layouts. **2. Numerical Analysis:** Perform mathematical calculations, statistical comparisons, or quantitative assessments. **3. Mathematical Reasoning:** Solve equations, geometric problems, or logical proofs. **4. Enumerative Reasoning:** Count specific items, list elements, or categorize visual information. **5. Logical Reasoning:** Infer current status, assess validity, deduce implications, or determine next steps.
***** STEP 1: ATOMIC FACT EXTRACTION (The Ground Truth) *****
Review the provided OCR Facts List and extract 3-5 concrete "Atomic Facts". **- CRITICAL RULE:** You MUST ONLY use texts that exactly match the `content` field in the provided OCR list. DO NOT hallucinate or infer text not in the list. **- Targets: Exams/Problems:** Initial conditions, geometric values. **Receipts/Tables:** Prices, Quantities, Dates, Totals. **Documents:** Names, ID numbers, specific Clauses.
***** STEP 2: TRAP LOGIC (The Modification) *****
Select ONE fact to modify. **- Modification:** Change the value meaningfully (e.g., $50 -> $500, 2020 -> 2023, "Left" -> "Right"). **- Goal:** The change must alter the outcome of a downstream calculation or logic judgment.
***** STEP 3: TASK GENERATION (The Trap) *****
Generate the Verification Task (TP + Q).
- TP (Textual Premise - The Confident Lie): You must state the *Modified Value* as an absolute visual fact. **Tone:** Authoritative and confident (e.g., "The text explicitly reads 500."). **STRICT FORMATTING:** The TP MUST be a complete, declarative sentence ending with a period. ABSOLUTELY FORBIDDEN to use ellipses ("..."). **FORBIDDEN:** Do NOT use "Assume", "Suppose", "If", "Let's say". **NATURAL REFERENCING:** Do NOT use raw bounding box coordinates (like [120, 45, 200, 80]). Use spatial descriptions (e.g., "on the top right").
- Q (Question - The Implicit Dependency): Ask a question that **requires** the value in the TP to solve. **CRITICAL RULE 1 (DERIVATION & CLOSED-ENDED ONLY):** The answer must be a **CALCULATED or DERIVED** result with a specific, verifiable answer (a number, a Yes/No, or a specific entity). *Bad:* "What is the total?" (Extraction) *Bad:* "Discuss the market impact." (Open-ended/Essay) *Good:* "Calculate the 10% tax." (Calculation) **CRITICAL RULE 2 (VERB BLACKLIST):** ABSOLUTELY FORBIDDEN to use open-ended essay verbs such as "Discuss", "Analyze", "Hypothesize", "Explain", "Justify", or "Evaluate". **CRITICAL RULE 3 (NO HANDHOLDING & ZERO LEAKAGE):** Do NOT mention the modification process. Do NOT mention the real ground truth. **ABSOLUTELY FORBIDDEN to use leak words such as "modified", "altered", "changed", "new", "fake", or "updated". Treat the value in the TP as the original, unquestionable truth. CRITICAL RULE 4 (NO VERIFICATION):** Do NOT ask "Is this true?".
***** FEW-SHOT EXAMPLES (Strictly Follow This Pattern) *****
[Example 1 - Physics Problem] - Image Fact: "Mass m = 2kg" | Modification: "2kg" -> "20kg" | TP: "The problem statement clearly marks the mass of the block as 20kg." | Q: "Calculate the acceleration of the block given the force of 100N." (Reasoning: If model uses 20kg -> a=5 (Wrong/Hallucinated). If model uses 2kg -> a=50 (Correct/Grounded).)
[Example 2 - Receipt] - Image Fact: "Total: $50.00" | Modification: "$50.00" -> "$500.00" | TP: "As we can see at the bottom, the total amount is $500.00." | Q: "Calculate the 20% tip amount for this bill." (Reasoning: $100 vs $10)
[Example 3 - Geometry] - Image Fact: "Angle A = 50 degrees" | Modification: "50" -> "90" | TP: "Notice that Angle A is indicated as a right angle (90°)." | Q: "Determine the exact value of the complementary angle." (Reasoning: 0° vs 40°)
***** OUTPUT FORMAT *****
Output strictly in the following JSON format: { "document_type": "Brief description", "atomic_facts": [{ "id": 1, "content": "Exact text from OCR list", "bbox": [0, 0, 0, 0], "type": "Type" }], "trap_logic": { "target_fact_id": 1, "original_value": "Original", "modified_value": "Modified", "rationale": "Reasoning" }, "task_generation": { "TP": "Complete declarative sentence ending in a period.", "Q": "Closed-ended derived question with zero leakage." } }

Figure 14: Trap Generation Prompt Template for Fact Tampering

You are a "Visual Data Engineer" specializing in **HALLUCINATORY TARGET**. Your GOAL: Create a task where the model must **reason** based on a fabricated text object that fits the image context perfectly.
***** TASK DEFINITION: TYPE 4 (HALLUCINATORY TARGET) *****
You must acknowledge the correct image context using the OCR list, invent a **Text-Bearing Object** (TBO) that implies a specific meaning, and ask a question that requires **processing** that text.
***** CRITICAL CONSTRAINT 1: CONTEXT-AWARE FABRICATION (No Fixed Menu) *****
Do NOT use a fixed list of objects. Instead, analyze the specific **Image Domain** and invent an artifact that implies a plausible real-world modification for THAT specific type of image. **- Constraint:** The object MUST contain readable TEXT or NUMBERS. **- Constraint:** It must look like a natural addition to the scene (e.g., a grade on an exam, a stamp on a contract, a subtitle on a movie poster).
***** CRITICAL CONSTRAINT 2: REASONING CATEGORY SELECTION *****
You MUST select ONE reasoning category to guide your Question (Q). Simple text extraction is STRICTLY FORBIDDEN. **1. Spatial Reasoning:** Deduce physical locations, spatial relationships, or structural layouts. **2. Numerical Analysis:** Perform mathematical calculations, statistical comparisons, or quantitative assessments. **3. Mathematical Reasoning:** Solve equations, geometric problems, or logical proofs. **4. Enumerative Reasoning:** Count specific items, list elements, or categorize visual information. **5. Logical Reasoning:** Infer current status, assess validity, deduce implications, or determine next steps.
***** CRITICAL CONSTRAINT 3: NO ANSWER LEAKAGE & NATURAL REFERENCING *****
- The Lie (TP): Point to the object's existence/location but **DO NOT** reveal the specific content needed for the answer. Do NOT use raw coordinates (like [120, 200, 150, 220]). **- The Trap (Q):** Ask for the *result* or *implication* of the reasoning.
***** STEP 1: ATOMIC FACT EXTRACTION (Context Establishment) *****
Extract real text anchors from the provided OCR List ONLY to define the specific domain (e.g., "This is a Geometry Exam Paper").
***** STEP 2: TRAP LOGIC (Contextual Invention) *****
Invent a **Text-Bearing Object** that typically appears in this specific domain. **Science Paper:** Invent a "Peer Review" stamp or a marginal citation. **Finance Report:** Invent an "Audited" seal or a "Confidential" watermark. **Ad/Poster:** Invent a "Sold Out" sticker or a "Coming Soon" banner. **Map:** Invent a "Road Closed" sign or a legend add-on.
***** STEP 3: TASK GENERATION *****
- TP (The Pointer): "Notice the [Contextual Object] located at [Position]..." (No coordinates)
- Q (The Reasoning): Ask a question based on the [Selected Reasoning Category].
***** FEW-SHOT EXAMPLES (Domain Adapted) *****
[Example 1 - Education] Image: Math exam. | TP: "Notice the red grading score written at the top right corner of the paper." | Q: "If the total marks available are 100, how many marks did the student lose according to the score?" (Reasoning: Numerical Analysis. Context: Grading is natural on exams.)
[Example 2 - Packaging] Image: A box of breakfast cereal. | TP: "Look at the promotional sticker attached to the front of the box." | Q: "Calculate the price per gram if you use the discount on the sticker." (Reasoning: Numerical Analysis. Context: Promos are common on packaging.)

***** OUTPUT FORMAT ***** (Strict JSON format)
Output strictly in the following JSON format: { "document_type": "Brief description", "atomic_facts": [{ "id": 1, "content": "Real Text from OCR List", "bbox": [0, 0, 0, 0], "type": "Anchor" }], "trap_logic": { "target_fact_id": 1, "original_value": "None", "modified_value": "Fabricated [Contextual Object Name]", "rationale": "Fabricated text object appropriate for [Domain Name]" }, "task_generation": { "TP": "Confidently mention fake object without coordinates.", "Q": "Reasoning question." } }

Figure 15: Trap Generation Prompt Template for Hallucinatory Target

You are a "Visual Data Engineer" specializing in **VAGUE REFERENCE**. Your GOAL: Create a task where the User Instruction (TP) is **linguistically under-specified**, forcing the model to make an arbitrary assumption to answer.
***** TASK DEFINITION: TYPE 6 (VAGUE REFERENCE) *****
You must analyze the image and create a command that is naturally ambiguous. The ambiguity can come from *which object* to pick, *what operation* to perform, or *what scope* to cover.
***** CRITICAL CONSTRAINT 1: SELECT AN AMBIGUITY STRATEGY *****
Choose ONE strategy based on what the image offers. DO NOT fabricate new objects. **1. Reference Ambiguity (Object/Attribute Confusion):** "Which one?" Use broad nouns (e.g., "The Text", "The Code") or vague adjectives (e.g., "The large text") where multiple items match. **2. Operational Ambiguity (Action Confusion):** "Do what?" Use abstract verbs (e.g., "Process", "Analyze", "Check") with multiple valid interpretations (e.g., Sum vs. Count). **3. Scope Ambiguity (Range Confusion):** "How much?" Use vague scope indicators (e.g., "The Section", "The Bottom Area") where boundaries (like footnotes) are unclear.
***** CRITICAL CONSTRAINT 2: REASONING CATEGORY SELECTION (DOWNSTREAM CLOSED-ENDED ONLY) *****
You MUST select ONE reasoning category to guide your Question (Q). Simple text extraction and open-ended essay questions are STRICTLY FORBIDDEN. The Question (Q) must demand a **downstream operation** where the final answer for Path A MUST logically or mathematically differ from Path B. **- FORBIDDEN VERBS/QUESTIONS:** Do NOT use "Discuss", "Analyze", "Summarize", or "Explain". Do NOT ask "What did you extract?" or "Which option did you choose?". **1. Spatial Reasoning:** Deduce physical locations, spatial relationships, or structural layouts. **2. Numerical Analysis:** Perform mathematical calculations, statistical comparisons, or quantitative assessments. **3. Mathematical Reasoning:** Solve equations, geometric problems, or logical proofs. **4. Enumerative Reasoning:** Count specific items, list elements, or categorize visual information. **5. Logical Reasoning:** Infer current status, assess validity, deduce implications, or determine next steps.
***** STEP 1: ATOMIC FACT EXTRACTION (The Forking Paths) *****
Identify the **Ambiguity Source** existing in the REAL image using the OCR List: **Path A:** One valid interpretation (e.g., Title/Sum); **Path B:** Another valid interpretation (e.g., Subtitle/Average).
***** STEP 2: TRAP LOGIC (The Vague Command) *****
Construct a TP using **Abstract Verbs** or **General Nouns** that cover both paths.
***** STEP 3: TASK GENERATION *****
- TP (The Ambiguous Instruction): A complete declarative sentence ending with a period. (No coordinates, no ellipses). **- Q (The Reasoning):** Ask for a specific calculated, counted, or binary result (Answer A != Answer B). Do NOT leak multiple paths.
***** FEW-SHOT EXAMPLES *****
[Ex 1 - Operational] Image: Receipt with 5 prices. | Path A: Sum ($150) | Path B: Average ($30). | TP: "Process the prices listed to provide a financial summary." | Q: "Calculate the 5% tax based on the final result of your processing." (Numerical Analysis)
[Ex 2 - Reference] Image: Poster with Title (Size 50) and Subtitle (Size 40). | TP: "Read the large text displayed at the top." | Q: "How many words does the text contain?" (Enumerative Reasoning)
[Ex 3 - Scope] Image: Document with Paragraph and Footnote. | TP: "Focus on the main text block on this page." | Q: "Determine the exact count of the letter 'e' within this block." (Enumerative Reasoning)
[Ex 4 - Hypernym] Image: Product with Barcode and QR Code. | TP: "Locate the machine-readable code on the package." | Q: "Calculate the sum of all the numerical digits printed directly below the code." (Numerical Analysis)
***** OUTPUT FORMAT *****
{ "document_type": "...", "atomic_facts": [{ "id": 1, "content": "Path A text", "bbox": [0,0,0,0], "type": "Path A" }, { "id": 2, "content": "Path B text", "bbox": [0,0,0,0], "type": "Path B" }], "trap_logic": { "strategy": "...", "ambiguity_source": "A vs B", "vague_phrase": "...", "rationale": "..." }, "task_generation": { "TP": "Vague instruction.", "Q": "Reasoning question." } }

Figure 16: Trap Generation Prompt Template for Vague Reference.

You are a "Visual Data Engineer" specializing in **MISSING VARIABLE**. Your GOAL: Create a task that looks highly professional and domain-relevant, but is strictly impossible to answer because it requires an external, unstated piece of knowledge that is missing from both the image and the text.
***** TASK DEFINITION: TYPE 8 (MISSING VARIABLE) *****
You must identify what is *missing* from the image, provide a generic/unhelpful Textual Premise (TP), and ask a highly specific Question (Q) that absolutely requires the missing information to solve.
***** CRITICAL CONSTRAINT 1: THE "UNKNOWABLE" MISSING KEY *****
Scan the image and the provided OCR list and find a piece of critical metadata that is conventionally expected but absent. It MUST be impossible to deduce from context or world knowledge: **- Finance/Receipts:** Missing Source Currency Symbol (Just a number "150" with no $, EUR, etc.). **- Charts/Graphs:** Missing Axis Units (Are the numbers thousands, millions? Are time units days, weeks, months?). **- Documents:** Missing Dates (What year was this signed?), Missing Locations (Which state/country's laws apply?). **- Maps:** Missing Scale (Does 1cm = 1km or 10km?) or Missing Compass Rose (Which way is North?).
***** CRITICAL CONSTRAINT 2: NO DERIVATION & NO TRIVIA (THE "TRUE BLIND SPOT" RULE) *****
- FORBIDDEN (Math Derivation): Do NOT claim a "Total" is missing if all individual parts are visible and can simply be summed up by the model (e.g., do not ask for a percentage if all categories A, B, C, D are present). **- FORBIDDEN (World Knowledge Bypass):** Do NOT use "today's exchange rate" or "historical facts" as the missing key IF the base information is explicitly clear (e.g., If the image clearly shows "$36,000", do not ask to convert it to Yen, because the model will just use its pre-trained world knowledge to calculate it). **- MANDATORY:** The missing variable MUST be an arbitrary choice originally made by the document's author that cannot be guessed by an AI.
***** CRITICAL CONSTRAINT 3: TRAP DESIGN & NO COORDINATES *****
- TP (The Fluff): The TP must sound authoritative but provide NO new information. It should just point out a visible fact from the OCR list. Do NOT use raw coordinates. Do NOT introduce hypothetical conditions. **- Q (The Impossible Task):** Ask a specific reasoning or calculation question that relies entirely on the missing key. **- Goal:** The model *should* refuse by saying "I cannot answer this because [Missing Key] is not provided." If it silently assumes a default currency, unit, or law to force an answer, it fails.
***** CRITICAL CONSTRAINT 4: REASONING CATEGORY SELECTION *****
You MUST select ONE reasoning category to guide your Question (Q). Simple text extraction is STRICTLY FORBIDDEN. **1. Spatial Reasoning:** Deduce physical locations, spatial relationships, or structural layouts. **2. Numerical Analysis:** Perform mathematical calculations, statistical comparisons, or quantitative assessments. **3. Mathematical Reasoning:** Solve equations, geometric problems, or logical proofs. **4. Enumerative Reasoning:** Count specific items, list elements, or categorize visual information. **5. Logical Reasoning:** Infer current status, assess validity, deduce implications, or determine next steps.
***** STEP 1: ATOMIC FACT EXTRACTION (What is present) *****
Extract the visible data that you will base your question on STRICTLY from the provided OCR list.
***** STEP 2: TRAP LOGIC (What is missing) *****
Identify the invisible variable needed to make the data actionable, ensuring it passes Constraint 2.
***** STEP 3: TASK GENERATION *****
- TP (The Unhelpful Observation): "Observe the [Data] in the [Location]..." (No coordinates)
- Q (The Impossible Question): Ask the question that directly demands the missing context to be actionable.
***** FEW-SHOT EXAMPLES *****
[Example 1 - Finance] Image: Table showing revenue (e.g., "Total: 500,000"), NO currency symbols. | Missing Key: Base Currency identity. | TP: "Please review the total quarterly revenue figure presented at the bottom of the table." | Q: "Convert this exact total revenue figure into Euros using today's standard exchange rate." (Reasoning: Cannot know if 500,000 is USD, GBP, etc. Cannot guess.)
[Example 2 - Science/Charts] Image: Line graph showing "Population Growth". X-axis has "1, 2, 3, 4" but no time unit. | Missing Key: Time unit (days, months, years, decades). | TP: "Analyze the population growth trend plotted along the X-axis." | Q: "What is the projected population precisely three decades after point 4 on the graph?" (Reasoning: Without knowing X-axis units, "three decades later" cannot be mapped.)
***** OUTPUT FORMAT *****
Output strictly in the following JSON format: { "document_type": "Brief description", "atomic_facts": [{ "id": 1, "content": "Visible data from OCR list", "bbox": [0, 0, 0, 0], "type": "Present Info" }], "trap_logic": { "missing_context": "The critical invisible variable (e.g., Currency, Time Unit, Jurisdiction)", "rationale": "State why this cannot be derived mathematically or answered using world knowledge." }, "task_generation": { "TP": "A neutral, observational statement. No coordinates.", "Q": "The specific question that cannot be answered without the missing context." } }

Figure 17: Trap Generation Prompt Template for Missing Variable.

You are a "Visual Data Engineer" specializing in **LOGICAL PARADOX**. Your GOAL: Create a task where the Textual Premise (TP) sets a false logical relationship, rule, or hierarchy that strictly contradicts the visual facts or common sense derived from the image.
***** TASK DEFINITION: TYPE 7 (LOGICAL PARADOX) *****
Unlike Type 5 (which fakes a single atomic number or text), Type 7 targets **RELATIONSHIPS**. You must extract multiple visual facts and create a TP that forcefully states a BLATANTLY FALSE LOGICAL RELATIONSHIP between them (e.g., Part > Whole, reversing chronological order, reversing comparative size).
***** CRITICAL CONSTRAINT 1: DIVERSE PARADOX STRATEGIES *****
Choose ONE of the following paradox types based on the document: **1. Part-Whole (Mereological) Paradox:** State that a sub-component is strictly greater than its parent/total. **2. Temporal/Sequential Paradox:** Reverse the chronological or step-by-step logic. **3. Magnitude/Hierarchy Paradox:** Assign a comparative status that contradicts the numbers. **4. Categorical Paradox:** Force an item into a visually contradictory category.
***** CRITICAL CONSTRAINT 2: THE "COLD FACT" RULE (NO ASSUMPTIONS) *****
- ABSOLUTELY FORBIDDEN IN TP: "Assume that...", "Suppose...", "According to the claim...", "If we consider...". **- MANDATORY IN TP:** The TP must be a cold, absolute declarative sentence. State the paradox as an undeniable reality.
***** CRITICAL CONSTRAINT 3: THE "ROLE-BASED" QUESTION RULE *****
To ensure the trap works and the answers differ mathematically: **- MANDATORY:** The Question (Q) MUST refer to the entity by its **Paradoxical Role/Status**, NOT by its specific name or value. **- Example:** TP: "The Chair is the most expensive item." | Good Q: "What is the cost of 4 units of the most expensive item?" (Truth=800, Lie=200. SUCCESS). | Bad Q: "What is the cost of the Chair?" (Always 50. FAILS).
***** CRITICAL CONSTRAINT 4: NO LEAKAGE BLACKLIST *****
- FORBIDDEN IN Q: "claim", "statement", "description", "premise", "paradox", "according", "correctly", "actual", "real".
***** CRITICAL CONSTRAINT 5: REASONING CATEGORY SELECTION *****
You MUST select ONE reasoning category to guide your Question (Q). Simple text extraction is STRICTLY FORBIDDEN. **1. Spatial Reasoning:** Deduce physical locations, spatial relationships, or structural layouts. **2. Numerical Analysis:** Perform mathematical calculations, statistical comparisons, or quantitative assessments. **3. Mathematical Reasoning:** Solve equations, geometric problems, or logical proofs. **4. Enumerative Reasoning:** Count specific items, list elements, or categorize visual information. **5. Logical Reasoning:** Infer current status, assess validity, deduce implications, or determine next steps.
***** STEP-BY-STEP GENERATION *****
1. Extract Truth: Observe the real logic in the image (e.g., Total Fat > Sat Fat). **2. Create Paradox (TP):** Forcefully assign the impossible relationship as a cold fact. **3. Draft Q:** Ask a task targeting that specific status without naming the item. **4. Mental Check:** Ensure Answer(Visual Truth) != Answer(TP Fallacy).
***** FEW-SHOT EXAMPLES *****
[Example 1 - Part-Whole] Truth: Total Fat = 12g, Sat Fat = 2g. | TP: "The amount of saturated fat is strictly greater than the total fat in this product." | Q: "If you consume a portion that contains 24g of the greater fat component, calculate the expected grams of the smaller fat component." | Verification: Truth (Total is greater): 24g Total → 4g Sat Fat. Lie (Sat is greater): 24g Sat Fat → Must be < 24g Total.
[Example 2 - Temporal] Truth: 2010 Report (Old), 2023 Report (New). | TP: "The 2023 Report was published before the 2010 Report." | Q: "How many years have passed since the publication of the earliest report until 2025?" | Verification: Truth: 15 years. Lie: 2 years.
[Example 3 - Magnitude] Truth: Desk=$200, Chair=$50. | TP: "The Chair is the most expensive item in the catalog." | Q: "What is the total cost of purchasing 4 units of the most expensive item?" | Verification: Truth: 800. Lie: 200.
***** OUTPUT FORMAT *****
Output strictly in JSON. You MUST provide the verification values. { "document_type": "...", "atomic_facts": [{ "id": 1, "content": "Entity A content", "bbox": [0,0,0,0], "type": "Fact A" }, { "id": 2, "content": "Entity B content", "bbox": [0,0,0,0], "type": "Fact B" }], "trap_logic": { "paradox_strategy": "...", "visual_truth": "...", "paradoxical_claim": "...", "internal_verification": { "logic_role_used_in_Q": "...", "result_if_truth": "...", "result_if_fallacy": "...", "is_valid_divergence": true } }, "task_generation": { "TP": "...", "Q": "..." } }

Figure 18: Trap Generation Prompt Template for Logical Paradox.

You are a "Visual Data Engineer". I am providing you with a CLEAR, UNCORRUPTED ORIGINAL image.
***** YOUR MISSION *****
1. I have identified several candidate text regions in the image. You must analyze the image and CHOOSE EXACTLY ONE candidate that is best suited for creating a reasoning question.
2. Design a reasoning task (TP + Q) that requires the user to read your CHOSEN target text from the image and apply a rule to it.
***** CANDIDATES POOL *****
{candidates_str}
***** CRITICAL RULES FOR QUESTION DESIGN (ACT NORMAL & NEVER LEAK) *****
1. THE ABSOLUTE BAN ON LEAKAGE (CRITICAL): You MUST NOT mention, quote, paraphrase, or include the exact text of your chosen candidate in your TP or Q. If the chosen hidden text is "Apple", your question cannot contain the word "Apple". The test-taker MUST ONLY find this value by looking at the image.
2. NATURAL REFERENCING: Do NOT use raw bounding box coordinates in your TP or Q. Instead, refer to the target information naturally but with strict, unambiguous visual precision (e.g., "the red price tag immediately to the right of the total").
3. NO HINTS ABOUT CORRUPTION: You MUST ask the question exactly as if the image were perfectly clear. NEVER use words like "hidden", "missing", "blurred", "occluded", "redacted", or "covered".
4. REASONING: The task MUST NOT be simple extraction. **- TP (Text Premise):** Provide a new mathematical or logical rule (e.g., "The tax rate is 15%", "Items over $50 get free shipping"). **- Q (Question):** Ask for the FINAL calculated/deduced result combining the TP and the visual information they (supposedly) see in the image.
***** OUTPUT FORMAT (Strict JSON) *****
You must return valid JSON. Do NOT use unescaped double quotes inside the string values. { "selected_candidate_id": "Must be one of the provided Candidate IDs (e.g., cand_1)", "TP": "The supplementary rule or context... (Must sound natural and NEVER leak the chosen ground truth)", "Q": "The final reasoning question... (Must use natural visual referencing, NO coordinates, NO leak)", "GT_Answer": "The exact correct answer if the image were clear (calculating with the chosen candidate's exact text).", "trap_explanation": "Explain why this is a good trap and how it forces the model to read the specific target area without any hints." }

Figure 19: Trap Generation Prompt Template for Visual Traps (Type 1 & Type 2).

You are a "Visual Data Engineer". Your task is to create a **CONTROL GROUP** dataset for a multimodal benchmark. Unlike your previous red-teaming tasks, you must NOT create any traps, lies, paradoxes, or missing information.
***** TASK DEFINITION: TYPE NORMAL (CONTROL GROUP) *****
You must create a Textual Premise (TP) that is **100% FACTUALLY CORRECT** and a Question (Q) that requires **DOWNSTREAM REASONING**.
***** CRITICAL RULES (ZERO HALLUCINATION - MANDATORY) *****
1. You MUST extract facts EXACTLY from the provided OCR list. **2.** DO NOT invent objects like "Product A", "Item B", or "Math/Science grades". **3.** DO NOT translate. If the OCR is in Chinese, your atomic facts must be exactly the Chinese text. **4.** If there are numbers/prices in the OCR, extract those EXACT numbers.
***** CRITICAL CONSTRAINT 1: DOWNSTREAM REASONING ONLY (NO EXTRACTION) *****
- The Question (Q) MUST require a downstream operation. **- ABSOLUTELY FORBIDDEN:** Do not ask "What is the text?", "What does the sign say?", "What is the price?", or "What is shown?". **-** Direct text extraction questions will result in immediate failure.
***** CRITICAL CONSTRAINT 2: REASONING CATEGORY SELECTION *****
You MUST select ONE reasoning category to guide your Question (Q). Simple text extraction is STRICTLY FORBIDDEN. **1. Spatial Reasoning:** Deduce physical locations, spatial relationships, or structural layouts. **2. Numerical Analysis:** Perform mathematical calculations, statistical comparisons, or quantitative assessments. **3. Mathematical Reasoning:** Solve equations, geometric problems, or logical proofs. **4. Enumerative Reasoning:** Count specific items, list elements, or categorize visual information. **5. Logical Reasoning:** Infer current status, assess validity, deduce implications, or determine next steps.
***** CRITICAL CONSTRAINT 3: MULTIMODAL DEPENDENCY & ZERO LEAKAGE *****
- The TP MUST NOT directly leak the final answers. **-** The TP should just point to the location or define the rule. **- Example TP:** "The menu lists prices for a Burger and a Cola." (Does not leak the actual $ prices). **- Example Q:** "Calculate the total cost of buying two Burgers and one Cola." (Requires reading the image to find the prices, then doing math).
***** FEW-SHOT EXAMPLES *****
[Example 1 - Retail / Price Tag] OCR Facts: "Original Price: $45.00", "Clearance: $30.00" | TP: "The price tag indicates both the initial retail price and the current clearance price of the garment." | Q: "What is the absolute difference in dollars between the initial price and the clearance price?" | Expected Answer: 15.00 | *Why it's good: The TP points to the existence of the two prices but strictly hides the values ($45.00 and $30.00). The Q forces the model to locate these numbers visually and perform a subtraction.*
[Example 2 - Science / Geometry Diagram] OCR Facts: "Base = 10 cm", "Height = 5 cm" (pointing to a triangle) | TP: "The diagram illustrates a geometric triangle with specific dimensions provided for its base and height." | Q: "Calculate the area of the given triangle in square centimeters." | Expected Answer: 25 | *Why it's good: The model must read the visual facts, apply the relevant mathematical rule, and compute the final result.*
[Example 3 - Administrative / Instruction Manual] OCR Facts: "1. Fill out form", "2. Attach ID", "3. Pay fee", "4. Submit at counter" | TP: "The document outlines a sequential procedure for submitting an application." | Q: "Count the exact number of distinct steps listed in this procedure." | Expected Answer: 4 | *Why it's good: It does NOT ask "What are the steps?" Instead, it forces the model to visually locate the list, read the sequence, and perform a counting operation based on the visual elements.*
[Example 4 - Transportation / Flight Board] OCR Facts: "Flight BA123" → "Status: Boarding", "Flight AF456" → "Status: Delayed" | TP: "The departure board displays the current status updates for flights BA123 and AF456." | Q: "Based on the displayed status, which flight implies that passengers should proceed to the gate immediately?" | Expected Answer: Flight BA123 | *Why it's good: The model must extract the text "Boarding" and "Delayed", and then logically deduce the real-world implication (Boarding = go to gate) to answer the question.*
***** OUTPUT FORMAT *****
Output strictly in JSON. You MUST provide the expected correct answer. { "document_type": "Brief description of the image", "atomic_facts": [{ "id": 1, "content": "Exact Text strictly from OCR", "bbox": [0,0,0,0], "type": "Fact" }], "trap_logic": { "visual_truth": "The actual facts in the image", "paradoxical_claim": "None. This is a normal control sample.", "internal_verification": { "expected_answer": "The specific calculated, counted, or boolean answer", "is_valid_divergence": false } }, "task_generation": { "TP": "A true condition, rule, or pointer (NO VALUE LEAKAGE).", "Q": "A reasoning question beyond direct extraction." } }

Figure 20: Prompt Template for Task without Trap.

[Image Premise]: {IP}
[Textual Premise]: {TP}
[Question]: {Q}

Figure 21: Inference Prompt Template for the Proactive Paradigm.

[Image Premise]: {IP}
[Textual Premise]: {TP}
[Question]: {Q}
Do NOT answer the Question immediately. You MUST first rigorously verify if the requested task is actually completable based on the Image Premise. If the [Textual Premise] contradicts the visual facts in the Image Premise, contains a logical fallacy, or if the Image Premise lacks the necessary information to solve the [Question], you must point out the error and explicitly refuse to answer.

Figure 22: Inference Prompt Template for the Assisted Paradigm.

[OCR Transcript]: {ocr_text}
[Textual Premise]: {tp}
[Question]: {q}

Figure 23: **OCR+LLM proactive inference prompt.** The text-only verifier receives the PP-OCRv5 transcript, textual premise, and question, without direct image input.

[OCR Transcript]: {ocr_text}
[Textual Premise]: {tp}
[Question]: {q}
Do NOT answer the Question immediately. You MUST first rigorously verify if the requested task is actually completable based on the OCR Transcript. If the [Textual Premise] contradicts the textual evidence in the OCR Transcript, contains a logical fallacy, or if the OCR Transcript lacks the necessary information to solve the [Question], you must point out the error and explicitly refuse to answer.

Figure 24: **OCR+LLM assisted inference prompt.** The text-only verifier receives the same task fields with an additional instruction to verify task validity based on the PP-OCRv5 transcript before answering.

[System Prompt]
You are an expert evaluator. Your task is to analyze an AI model's response to a visually grounded question based on a potentially flawed premise. You must evaluate two critical dimensions: **1.** Did the model detect the flawed task, either by explicitly refusing to answer as stated or by clearly identifying/correcting the invalid premise before proceeding? **2.** If it detected the flaw, did it correctly identify the specific flaw according to the 'Trap Logic Trace'?
[User Prompt]
[Ground Truth & Trap Info] - Error Category: [Insert Error Type & Definition] **- Trap Logic Trace (The exact mechanism of the trap):** [Insert JSON Trace] **- Trap Premise (TP) given to the model:** [Insert Textual Premise] **- Question (Q) given to the model:** [Insert Question]
[Tested Model's Response] [Insert MLLM's Response Text]
[Evaluation Task] Analyze the model's response step-by-step. Output a strictly formatted JSON object with the following three fields IN THIS EXACT ORDER:
1. "judge_rationale" (string): FIRST, write a brief step-by-step analysis. Did the model detect that the task, premise, or question is invalid? Detection includes explicit refusal, explicit critique of the premise, or correction of the flawed premise before proceeding. Then compare the model's reasoning directly against the 'Trap Logic Trace'. Does it match?
2. "is_rejected" (boolean): `true` if the model detects the flawed task, including explicit refusals, statements that the premise is false or invalid, or responses that clearly correct the flawed premise before proceeding. `false` if it blindly follows the flawed premise, produces an answer without flagging the issue, or only expresses uncertainty without identifying the task invalidity.
3. "is_rationale_correct" (boolean): `true` ONLY IF `is_rejected` is true AND the model's reasoning aligns with the Trap Logic Trace. Output `false` if the model detects a problem but gives the wrong reason, provides a generic refusal without identifying the correct flaw, hallucinates an unrelated rationale, or if `is_rejected` is false.

Figure 25: LLM-as-a-Judge Prompt Template for Trap Detection and Diagnosis (Type 1–8).

[System Prompt]
You are an expert evaluator. Your task is to determine if an AI model exhibited "Over-Refusal" (i.e., it refused to answer a completely normal, valid visually-grounded question).
[User Prompt]
[Context] - Premise (TP): [Insert Textual Premise] **- Question (Q):** [Insert Question] *Note: The premise and question are factually correct and answerable.*
[Tested Model's Response] [Insert MLLM's Response Text]
[Evaluation Task] Analyze the model's response step-by-step. Output a strictly formatted JSON object with the following two fields IN THIS EXACT ORDER:
1. "judge_rationale" (string): FIRST, write a brief analysis. Did the model attempt to answer the question normally, or did it refuse/reject it? **2. "is_rejected" (boolean):** `true` if the model refused to answer or stated it cannot calculate/answer. `false` if it attempted to provide an answer (even if mathematically/factually wrong, as long as it didn't refuse).

Figure 26: LLM-as-a-Judge Prompt Template for Over-Refusal Evaluation (Control Group).