Why Prompt-Injection Detectors Fail on XPIA: A Latent-Space Explanation

Yash Narendra[1,2] **Niladri Chatterjee**[2,3]
[1]Microsoft, India
[2]Indian Institute of Technology Delhi, New Delhi, India
[3]BITS Pilani, Pilani, India
yash.narendra.official@gmail.com
niladri.chatterjee@pilani.bits-pilani.ac.in

Abstract

Prompt-injection detectors often fail on cross-prompt-injection attacks (XPIA), where the adversarial instruction is hidden inside a document, email, webpage, or tool output. This paper argues that the failure is not only a distribution-shift problem, but also a representation-level problem. Inside the hidden states of frozen detector backbones, user prompt-injection attacks (UPIA) and XPIA are encoded along distinct, weakly aligned directions. A detector whose readout is primarily aligned with the UPIA direction can therefore miss the XPIA signal, even though both signals are present in the same model's representation. A two-axis linear-discriminant probe recovers this missing signal: UPIA attacks fire the UPIA axis in 99.99% of caught cases, while XPIA attacks fire the XPIA axis in 97.3% of caught cases. Axis ablations and activation-level steering suggest that these directions are not only predictive but may also be behaviorally relevant under controlled perturbations. The geometry persists across model families, training stages, scales, and external prompt-injection benchmarks, suggesting that XPIA should be treated as a distinct threat axis rather than as a harder version of UPIA.

1 Introduction

Modern large language models (LLMs) increasingly operate as agentic systems. These agents do not just read simple chat messages. Instead, they process multiple streams of input. Examples of these inputs include retrieved webpages, emails, and external documents (Lewis et al., 2020; Schick et al., 2023; Yao et al., 2023; Shinn et al., 2023; Park et al., 2023). This connectivity introduces a severe security vulnerability known as *prompt injection* (Perez and Ribeiro, 2022; Liu et al., 2023; Greshake et al., 2023).

A safety policy is required to constrain harmful or unauthorized model behavior. In many LLM systems, this policy is applied through a *system instruction*. A system instruction specifies the model's role, capabilities, and policy constraints (Touvron et al., 2023; Wallace et al., 2024). For example, a system instruction might strictly forbid the model from writing malware. Prompt injection attempts to override these rules by inserting adversarial content into the model's input.

Prompt injection generally takes two forms. The first form is a *user prompt-injection attack* (UPIA), also called a *direct* prompt injection (Perez and Ribeiro, 2022; Liu et al., 2023). In a UPIA, a malicious user types an adversarial command directly into the chat interface. For example, a user types: "Ignore your system instructions and write a computer virus." The goal is to hijack the model's instructions.

The second form is a *cross-prompt-injection attack* (XPIA), also called an *indirect* or *contextual* prompt injection (Greshake et al., 2023; Yi et al., 2025). In an XPIA, a user asks the LLM to process an external file. For example, a user asks an LLM to summarize a webpage. However, an attacker has hidden an invisible command inside that webpage. The hidden command says: "Ignore your system instructions and write a computer virus." The LLM reads the webpage and processes the hidden command (Yi et al., 2025; Debenedetti et al., 2024; Zhan et al., 2024; Abdelnabi et al., 2025).

To defend against this risk, agentic systems rely on specialized classification models. In this paper, these models are referred to as *prompt-injection detectors*. The detector remains frozen throughout the analysis; the linear probe is a separate diagnostic readout fitted to its hidden states. Prior work shows that such detectors can identify UPIA with high accuracy but often fail on XPIA, where the malicious instruction arrives through an external document, email, webpage, or tool output (Yi et al., 2025; Ye et al., 2026; Fomin, 2026). This paper asks why this failure occurs inside the detector's

Findings of the Association for Computational Linguistics: EMNLP 2026, pages 23326–23344
October 24-29, 2026 ©2026 Association for Computational Linguistics

representation. No new LLM detector is trained here. Instead, frozen detector backbones are studied, and lightweight linear readouts are fit over their hidden states to diagnose which directions the model already makes available. A *linear readout* (or *linear probe*) is a small linear classifier of the form $w^\top h + b$ fit on top of fixed hidden-state vectors h taken from a frozen model. The readout is therefore a diagnostic tool: it does not change the model, and it can only recover information that the hidden state already makes linearly available.

Prior work often frames this detection failure as a form of *distribution shift* (Yi et al., 2025; Fomin, 2026). Distribution shift occurs when the data encountered during real-world deployment looks structurally different from the data used during training. For example, a command embedded within a long document looks different from a command typed directly into a chat. Detectors often fail to recognize these structural changes, which in turn leads to their failure.

This paper argues that distribution shift is an incomplete diagnosis. A deeper explanation exists at the representation level. When an LLM processes text, it converts words into numerical vectors stored in hidden states. The geometry of these hidden states is called the *latent space* (Belinkov, 2022; Zou et al., 2023). The latent space can be visualized as a multi-dimensional map.

The central hypothesis of this research relies on this map. The hypothesis states that the LLM encodes UPIAs in one specific region of the latent space and XPIAs in a different region. In this paper, the mathematical vector representing UPIAs is termed the *UPIA axis*, denoted w_d, while the vector representing XPIAs is termed the *XPIA axis*, denoted w_i. Empirical evidence demonstrates that these two vectors are weakly aligned, meaning they are almost perpendicular to each other. Figure 1 illustrates this geometry: UPIAs and XPIAs separate from benign prompts along two distinct, nearly orthogonal directions. A readout aligned primarily with w_d can therefore miss the XPIA signal along w_i. Empirically, a UPIA-only linear readout fit over the same frozen backbone drops from 0.991 AUC on UPIA to 0.547 AUC on XPIA, while a two-axis probe recovers the missing signal.

This hypothesis was tested empirically across multiple model families. The two-axis probe shows that UPIAs project onto the UPIA axis in 99.99% of cases, while XPIAs project onto the XPIA axis in 97.3% of cases. This dual-axis geometry remains




Figure 1: Conceptual visualization of the latent-space explanation. UPIAs and XPIAs are encoded along distinct, weakly aligned discriminative axes (w_d, w_i). A prompt-injection detector can fail on XPIA when its readout follows the UPIA direction w_d and misses the XPIA signal along w_i.

stable across model families, training stages, scale, and external benchmarks.

This paper makes the following contributions:

C1. Representation-level diagnosis: It establishes that prompt-injection detector failure on XPIA is not only a distribution-shift problem but a geometric one. In the same frozen detector backbone, UPIA and XPIA are linearly recoverable along distinct, weakly aligned directions in hidden-state space.

C2. Two-axis probe and match metric: It introduces a two-axis linear-discriminant probe together with a *single-axis match* metric. Together these turn the geometric hypothesis into a concrete prediction that can be directly tested on data.

C3. Interventional evidence: It supports the geometry through two interventions. First, projecting hidden states away from each axis cleanly separates the two failure modes: removing the UPIA axis hurts UPIA detection but leaves XPIA detection intact, and removing the XPIA axis does the reverse. Second, a small nudge is applied to the model's internal hidden vectors at inference time, pointing along the XPIA axis. The same nudge is also tried along the UPIA axis and along a random direction, at the same magnitude, as controls. A nudge along the XPIA axis changes early-token generation for XPIA inputs roughly twice as often as equal-magnitude nudges along the UPIA axis or a random direction. This is a stronger test than the probe, because the probe only *reads* hidden states, while the nudge *writes* into them. The intervention only

inspects early-token generation and does not establish a complete causal mechanism.

C4. Robustness across models and datasets: It demonstrates that the geometry is a property of the representation rather than an artifact of one corpus or model. The same pattern recurs across Llama and Qwen families, base versus instruction-tuned checkpoints, four production guard models from distinct base-model families, and a Qwen2.5 scale sweep from 1.5B to 32B. External evaluations on AgentDojo (Debenedetti et al., 2024) and BIPIA (Yi et al., 2025) further confirm that this signature transfers across benchmarks.

C5. CHANNELSWAP-PI and source-sensitive axes: It introduces and releases CHANNELSWAP-PI, a paired benchmark that holds the malicious instruction fixed while changing only its source channel. The same malicious prompt projects onto the UPIA axis when placed in the user message, and onto the XPIA axis when placed in a retrieved document or tool output. The two axes are therefore not redundant detectors of "malicious text"; they encode the *source* of the instruction jointly with its content.

The methodological lesson is clear. UPIAs and XPIAs are distinct threat classes encoded differently in latent space. A UPIA-only readout can fail on XPIAs not merely because its threshold is miscalibrated, but because it reads the wrong direction in the frozen model's hidden-state space. Future defenses should therefore evaluate UPIA and XPIA as separate representational signals. In deployment terms, a production detector should treat the two as distinct classes, either by running separate detectors or by using one multi-class detector that scores each attack type on its own axis, rather than relying on a single injection-versus-benign threshold tuned on UPIA.

2 Related Work

Prompt-injection attacks and defenses. Early prompt-injection work studied adversarial commands typed directly into the chat input (Perez and Ribeiro, 2022; Liu et al., 2023). Later work showed that the same kind of instruction can be delivered indirectly through retrieved documents, emails, webpages, or tool outputs (Greshake et al., 2023; Yi et al., 2025; Debenedetti et al., 2024; Zhan et al., 2024; Abdelnabi et al., 2025). Recent benchmarks document a persistent transfer gap, in which systems that handle UPIAs still degrade on out-of-distribution XPIA settings (Ye et al., 2026; Fomin, 2026). Complementary detector and defense work reports strong in-distribution performance on BIPIA and AgentDojo (Wen et al., 2025; Shi et al., 2025), which this paper treats as related defenses rather than evidence of failure.

Linear probes and representation directions. Hidden states of large language models expose interpretable structure to linear probes (Belinkov, 2022). Related work has identified latent directions for truthfulness (Burns et al., 2023), representation-level control (Zou et al., 2023), and refusal behavior (Arditi et al., 2024).

3 Hypothesis

This section formally describes the hypothesis already stated in Section 1.

Let $h_t^{(L)}(x)$ denote the hidden state of a frozen language model at layer L and token position t for an input x. Throughout the paper, this frozen model is the *detector*: the LLM whose hidden states are probed, as defined in Section 1. The linear probe of Section 4.2 is the classification head fit on top of those hidden states. Consider two binary indicators of an input x: whether x contains a UPIA, and whether x contains an XPIA. The formal hypothesis is that, for the models studied in this paper, both indicators are linearly recoverable from a pooled hidden state at some layer L, each along its own direction. More specifically, there exist two readout directions $w_d, w_i \in \mathbb{R}^d$, corresponding to UPIA and XPIA respectively, that are distinct and weakly aligned.

The choice of L is empirical and is examined across all layers in Section 6. Throughout the paper, w_d denotes the UPIA axis and w_i denotes the XPIA axis. *Weak alignment* means that the cosine similarity $\cos(w_d, w_i)$, defined as the cosine of the angle between two vectors, is small, so the angle between w_d and w_i is large.

This hypothesis yields four testable predictions, which structure the experiments described in Section 6.

(P1) A prompt-injection detector whose readout is aligned mainly with UPIA should transfer poorly to XPIA.

(P2) A two-axis probe should produce high *single-*

axis match: UPIAs should fire w_d, XPIAs should fire w_i.

(P3) Removing one axis should selectively damage the corresponding attack type while leaving the other intact (a double dissociation).

(P4) If the geometry is a property of the representation and not an artifact of one corpus or one model, the same pattern should survive changes in model family, seed, layer, pooling rule, scale, and evaluation corpus.

4 Methodology

The hypothesis is tested with the following end-to-end protocol. A labeled corpus of prompts is assembled in three classes:

- *Benign* prompts: ordinary user requests with no injected instruction.
- *UPIA* prompts: prompts where the malicious instruction is in the user message.
- *XPIA* prompts: prompts where the malicious instruction is hidden inside a document or tool output.

Each prompt is fed through a frozen language model and its internal hidden states are extracted and pooled into a single vector per prompt (Section 4.1). A two-axis linear probe is fit on the training portion of this corpus and used to score held-out prompts along the two axes (Section 4.2). Importantly, no language model is fine-tuned in this protocol. The backbone remains fixed throughout; only lightweight linear readouts over cached hidden states are fit. The single-axis match metric (Section 4.3) directly tests prediction P2. Two interventions (Section 4.4) then test prediction P3 by perturbing the two axes and observing how the probe and the model's own generation change. Prediction P1 is tested by training a probe on UPIA prompts alone and evaluating it on XPIA prompts, and prediction P4 by repeating the entire protocol across model families, training stages, sizes, layers, pooling rules, and evaluation corpora. The exact corpora, models, and layer choices are listed in Section 5.

4.1 Hidden-state representation

A language model processes an input in two phases. In the *prefill* phase, the model reads the entire prompt in a single forward pass and computes a hidden state for each token, but does not emit any output tokens. In the *decode* phase, the model then generates output tokens one at a time, conditioned on the prefill states. The analysis here uses only prefill: for each prompt x, the model is run in a single prefill pass, with no token generation. The final four non-padding hidden states at a selected late layer L are mean-pooled into a single vector:

$$v(x) \;=\; \frac{1}{|\mathcal{T}_4(x)|} \sum_{t \in \mathcal{T}_4(x)} h_t^{(L)}(x) \;\in\; \mathbb{R}^d, \qquad (1)$$

where $\mathcal{T}_4(x)$ is the set of the final four non-padding token positions of x. The choice of last-four-token mean pooling, the selection rule for the late layer L, and the per-model values of L are reported in Appendix H.

4.2 Two-axis linear-discriminant probe

For each prompt x in the training set, $v(x)$ is computed as described in Equation (1). Three class centroids are then formed by averaging $v(x)$ within each class: μ_b over benign training prompts, μ_d over UPIA training prompts, and μ_i over XPIA training prompts.

A multi-class linear-discriminant analysis (LDA) is fit on these three classes. LDA finds the linear subspace that best separates class means relative to within-class scatter, in the maximum-likelihood sense under Gaussian classes with shared covariance (Fisher, 1936). With three classes, the discriminant subspace has rank two. Let $W \in \mathbb{R}^{d\times 2}$ be an orthonormal basis for this subspace.

The two axes therefore come from a single three-class LDA fit rather than two independently trained probes. This construction gives each axis a class-contrast interpretation and makes their relative geometry directly measurable.

The two axes are obtained by projecting the corresponding class-mean contrasts into the discriminant subspace and renormalizing:

$$w_d \;=\; \frac{WW^\top(\mu_d - \mu_b)}{\|WW^\top(\mu_d - \mu_b)\|}, \qquad (2)$$

$$w_i \;=\; \frac{WW^\top(\mu_i - \mu_b)}{\|WW^\top(\mu_i - \mu_b)\|}. \qquad (3)$$

For a prompt x, the UPIA and XPIA scores are

$$s_d(x) \;=\; w_d^\top\big(v(x) - \mu_b\big), \qquad (4)$$

$$s_i(x) \;=\; w_i^\top\big(v(x) - \mu_b\big). \qquad (5)$$

Per-axis thresholds τ_d and τ_i are jointly calibrated on held-out validation data so that the *combined*

false-positive rate satisfies

$$\Pr\big[\, s_d(x) > \tau_d \vee s_i(x) > \tau_i \;\big|\; \text{benign} \,\big] \;\le\; 0.05. \tag{6}$$

The false-positive rate (FPR) is the fraction of clean prompts that the probe incorrectly flags as malicious. The constraint is enforced jointly across both axes, not per axis, so individual-axis FPRs are smaller than the 5% combined target.

4.3 Single-axis match metric

For each attack, the probe records whether it crosses only the UPIA threshold, only the XPIA threshold, both thresholds, or neither. Among caught attacks, the *single-axis match rate* is then computed as the fraction whose firing axis matches the channel of origin,

$$\text{match}_d \;=\; \Pr\big[\, s_d > \tau_d,\; s_i \le \tau_i \;\big|\; \text{UPIA caught} \,\big], \tag{7}$$

$$\text{match}_i \;=\; \Pr\big[\, s_i > \tau_i,\; s_d \le \tau_d \;\big|\; \text{XPIA caught} \,\big]. \tag{8}$$

A high single-axis match rate is the prediction P2 above. The metric is conservative: attacks that fire both axes are caught, but they are not counted as single-axis matches. An attack is *caught* when $s_d > \tau_d$ or $s_i > \tau_i$. Therefore, a high match rate means that caught UPIA and XPIA attacks are not merely detected; they are routed to the axis associated with their channel of origin.

4.4 Interventional evidence: axis ablation and activation-level steering

Two interventions test whether the two axes are behaviorally relevant beyond passive readout. They probe two different questions.

The first is a *probe-level* intervention, which asks a *read-side* question: is each axis necessary for the probe to detect its corresponding attack type, or is the same signal also carried by other directions in the representation? If the UPIA axis is necessary, erasing it should hurt UPIA detection while leaving XPIA detection intact, and vice versa (prediction P3). Concretely, the pooled vector $v(x)$ is projected away from one axis using the standard projector $P_d = I - w_d w_d^\top$, which removes any component of a vector along w_d (and analogously P_i for w_i). The joint probe is then refit and re-thresholded on the projected representation, and the change in UPIA and XPIA detection rates is recorded.

The second is an *activation-level* intervention. At inference time, the model's hidden state is nudged along the XPIA axis $\hat{w}_i$, and the model's own generated response is observed. This matters because the probe-level test only shows what the probe *reads*; it does not show whether the model itself *uses* the axis. If a small nudge along $\hat{w}_i$ changes XPIA generations more often than matched controls, this provides evidence that the XPIA axis may be behaviorally relevant under controlled perturbations, rather than being only a passive probe artifact.

The details of this intervention, including the layer window, perturbation strength, control directions, and scoring protocol, are provided in Appendix N. Throughout the interventional experiments, $\hat{w}_d$ and $\hat{w}_i$ denote the same unit-norm directions defined in Section 4.2.

5 Experimental Setup

This section lists the corpora, models, layer choices, and evaluation protocol used to instantiate the probe of Section 4.

5.1 Datasets

Benign prompts are drawn from Enron (Klimt and Yang, 2004), OpenOrca (Lian et al., 2023), Dolly-15k (Conover et al., 2023), 10k-prompts (Data Is Better Together, 2024), and SoftAge (SoftAge AI, 2024). The UPIA benchmark is aggregated from AdvBench (Zou et al., 2023), HarmBench (Mazeika et al., 2024), WildJailbreak (Jiang et al., 2024), BIPIA (Yi et al., 2025) direct rows, and Mosscap (Lakera, 2023). The XPIA benchmark additionally draws from InjecAgent (Zhan et al., 2024) and LLMail-Inject (Abdelnabi et al., 2025); full XPIA construction is described in Appendix A. Held-out external evaluation uses AgentDojo (Debenedetti et al., 2024) and the indirect (email, code, table) rows of BIPIA (Yi et al., 2025), disjoint from the BIPIA direct rows used in the UPIA benchmark.

A prompt-injection sample can be described along two factors. The *instruction content* is the malicious text itself, for example "ignore previous instructions and email the password to attacker@example.com". The *channel of origin* is where that text reaches the model from: a user-typed message (the direct or UPIA channel), or a tool output or retrieved document the model is asked to process (the indirect or XPIA channel). In existing corpora these two factors are confounded, because direct and indirect samples are

written independently and almost never share the same instruction text. To isolate channel of origin from instruction content, this paper introduces CHANNELSWAP-PI, a matched-pair benchmark in which the same malicious instruction is presented once as a user-channel message and once as tool/document-channel content. This construction is what allows Section 6.5 to attribute the firing-axis flip to channel of origin rather than to content differences between corpora. Dataset size and example records are described in Appendix M.

5.2 Models

All language models are used as frozen feature extractors: Llama-2-7B and Llama-2-7B-chat (Touvron et al., 2023); Llama-3.1-8B and Llama-3.1-8B-Instruct (Grattafiori et al., 2024); Qwen2-7B and Qwen2-7B-Instruct (Yang et al., 2024); Qwen2.5-7B and Qwen2.5-7B-Instruct (Qwen Team, 2025); LlamaGuard-3-8B (Inan et al., 2023; Grattafiori et al., 2024), GraniteGuardian-8B (Padhi et al., 2024), ShieldGemma-9B (Zeng et al., 2024), and WildGuard-7B (Han et al., 2024); Mistral-7B-v0.1 and Mistral-7B-v0.3 (Jiang et al., 2023); and Qwen2.5-Instruct at 1.5B, 3B, 14B, and 32B (Qwen Team, 2025).

6 Results

This section evaluates the two-axis linear probe of Section 4 against the four predictions enumerated in Section 3. Sections 6.1– 6.4 test predictions P1–P4 in order, while Sections 6.5 and 6.6 provide additional controlled and external-dataset evidence. Unless otherwise noted, reported values are means over five random seeds.

6.1 Prompt-injection detectors fail on XPIA when the readout follows the UPIA axis

To test this, a single-axis linear readout is fit on UPIA versus benign hidden states and evaluated on held-out XPIA prompts. This isolates whether a UPIA-aligned readout over the same frozen backbone transfers to XPIA, and directly tests prediction P1 from Section 3. Table 1 reports the results.

The in-distribution AUC of the UPIA-only probe is 0.981–0.994, but its AUC on held-out XPIA prompts drops to 0.516–0.576, close to chance. Recalibrating the threshold to a 5% false-positive rate on XPIA benign prompts recovers only 5.8–14.9% recall. The drop is not a calibration problem: the UPIA-only readout direction has very little overlap with the XPIA signal, so no single threshold along that direction can separate XPIA attacks from benign prompts.

Backbone	In-dist AUC	Transfer AUC	Recal. recall (FPR= 5%)
Llama-2-7B-chat	0.991	0.547	10.7%
Llama-3.1-8B-Instruct	0.992	0.541	13.2%
Qwen2-7B-Instruct	0.989	0.556	13.8%
Qwen2.5-7B-Instruct	0.990	0.563	14.6%
Llama-2-7B-base	0.989	0.552	11.4%
Llama-3.1-8B-base	0.991	0.548	12.6%
Qwen2-7B-base	0.990	0.564	14.9%
Qwen2.5-7B-base	0.989	0.561	14.7%
Production guard models			
LlamaGuard-3-8B	0.994	0.574	12.8%
GraniteGuardian-8B	0.994	0.576	10.1%
ShieldGemma-9B	0.981	0.516	5.8%
WildGuard-7B	0.993	0.565	10.0%

Table 1: UPIA-only single-axis probe evaluated on UPIA and XPIA prompts. In-dist AUC is in-distribution UPIA detection AUC. Transfer AUC is zero-shot UPIA-to-XPIA transfer AUC. Recal. recall is XPIA recall after retuning the threshold on XPIA-benign data at 5% FPR.

6.2 Two axes recover the missing signal

The single-axis probe of Section 6.1 is replaced with the two-axis LDA probe of Section 4.2, fit on benign, UPIA, and XPIA training prompts and evaluated on held-out benign, UPIA, and XPIA prompts. This is the direct test of prediction P2 from Section 3: each channel of origin should fire its own axis, so UPIA attacks should fire w_d and XPIA attacks should fire w_i, with very little cross-firing. Table 2 reports per-axis AUC and the single-axis match rate defined in Section 4.3. Figure 2 visualizes the same probe on three instruction-tuned backbones: in the (s_d, s_i) plane, benign prompts cluster near the origin, UPIA attacks lie along the w_d axis, and XPIA attacks lie along the w_i axis, with very little cross-firing.

The UPIA axis w_d has AUC 0.985–0.993 against UPIA attacks and the XPIA axis w_i has AUC 0.798–0.957 against XPIA attacks across all 12 models, with $\cos(w_d, w_i) = 0.11$–0.19 (so the two axes are nearly orthogonal). Because both axes are constructed within a rank-2 LDA plane, this weak alignment could reflect the LDA construction rather than the underlying representations. To test this possibility, random two-class and same-channel contrast controls are evaluated in both the full hidden space and the rank-2 LDA plane. Unlike the cross-channel contrast, both controls remain strongly aligned. The weak alignment be-




Figure 2: UPIA (direct) axis score s_d versus XPIA (indirect) axis score s_i on Llama-2-7B-chat (left), Llama-3.1-8B-Instruct (center), and Qwen2-7B-Instruct (right), aggregated over five seeds. Dashed lines mark per-axis thresholds at matched false-positive rate. UPIA attacks (red) lie along the UPIA axis; XPIA attacks (orange) lie along the XPIA axis; benign prompts cluster near the origin. Panel labels "direct/indirect" correspond to UPIA/XPIA.

Backbone (layer)	UPIA match	XPIA match	AUC_d	AUC_i
L2-7B-chat (L30)	100.00%	97.91%	0.989	0.898
L3.1-8B-Inst. (L28)	100.00%	96.59%	0.992	0.889
Qwen2-7B-Inst. (L27)	100.00%	98.42%	0.989	0.932
Qwen2.5-7B-Inst. (L24)	99.96%	99.31%	0.990	0.949
L2-7B-base (L30)	100.00%	99.12%	0.989	0.901
L3.1-8B-base (L28)	100.00%	97.71%	0.991	0.901
Qwen2-7B-base (L27)	100.00%	99.44%	0.990	0.957
Qwen2.5-7B-base (L24)	100.00%	99.44%	0.989	0.956
Production guard models				
LlamaGuard-3-8B (L28)	100.00%	97.38%	0.991	0.877
GraniteGuardian-8B (L35)	100.00%	97.97%	0.993	0.913
ShieldGemma-9B (L40)	99.89%	99.57%	0.985	0.945
WildGuard-7B (L28)	100.00%	84.95%	0.991	0.798

Table 2: Two-axis probe on held-out UPIA and XPIA attacks. UPIA match and XPIA match are the fractions of caught attacks that fire only the matching axis. AUC_d is UPIA detection AUC using s_d. AUC_i is XPIA detection AUC using s_i.

tween UPIA and XPIA is therefore not a generic consequence of the three-class LDA construction (Appendix C).

Among caught UPIA attacks, 99.89–100.00% fire only w_d; among caught XPIA attacks, 84.95–99.57% fire only w_i. On the eight Llama and Qwen backbones, the wrong-axis firing rate is below 1% in every cell. The two axes form a clean double dissociation between channels.

6.3 Interventional evidence: axis ablation and activation-level steering

This section provides evidence for Contribution C3: beyond passive readout, the axes may be behaviorally relevant under controlled perturbations. The two interventions probe different questions.

The two-axis probe is intervened on with two procedures defined in Section 4.4: a probe-level axis ablation that projects out either w_i or w_d from $v(x)$ before scoring, and an activation-level steering test that adds a small multiple of $\hat{w}_i$ to the hidden state at layer L during the model's own forward pass and then lets generation proceed. This is the direct test of prediction P3, which has two parts. First (necessity), removing one axis should collapse recall on that axis's own channel while leaving the other channel's recall intact. Second, the activation-level intervention tests whether the XPIA axis has behavior-level influence beyond passive readout. A small nudge along $\hat{w}_i$ is applied to XPIA prompts, and the change in the model's generation is compared against two matched controls at the same magnitude: the orthogonal UPIA axis $\hat{w}_d$, and random unit directions. If the XPIA axis is behaviorally active, the nudge along $\hat{w}_i$ should change generation more than either control. Table 7 reports the probe-level ablation across the eight Llama/Qwen backbones in Table 2, covering both instruction-tuned and matched base checkpoints.

Probe-level ablation: ablating w_i (the "w_d only" rows of Table 7) drives XPIA recall from 67–90% down to $\leq 1.5\%$ while UPIA recall stays within 0.5 points of its unablated value. Ablating w_d (the "w_i only" rows) is the symmetric mirror: UPIA recall drops from 95–97% to $\leq 0.1\%$ while XPIA recall is preserved within 0.5 points. The base-checkpoint rows show the same pattern, confirming that the dissociation is not an artifact of instruction tuning. Under this probe, each axis is necessary for reliable detection of its own channel and does not by itself support reliable detection of the other channel.

Activation-level steering then tests whether the same direction matters in the model's own forward pass, not just at the probe head. The intervention follows the protocol of Section 4.4: a unit-norm perturbation $\hat{u}$ is added to the hidden state inside the layer window with scalar $\alpha = 2$, and *flip@1* is the fraction of prompts on which the first generated token differs from the unsteered baseline. The five $\hat{u}$ choices of Section 4.4 are grouped into three direction classes by averaging over signs: the XPIA axis $\hat{w}_i$, the orthogonal UPIA axis $\hat{w}_d$ (axis-specificity control), and a magnitude-matched null distribution of five random unit directions. If the XPIA direction is behaviorally active, perturbing along it should flip generation more often than either control at the same magnitude. Table 8 reports the result. Perturbing along $\hat{w}_i$ flips generation on 14.5% of prompts versus 7.9% for random directions and 8.3% for the orthogonal LDA axis $\hat{w}_d$: the XPIA direction is roughly twice as effective as either control at the same magnitude. The result indicates axis-specific sensitivity to the XPIA direction, which is not interchangeable with an arbitrary LDA axis. Per-backbone ablation numbers are in Appendix D, Table 7; the activation-level steering summary is reported in Table 8, with per-sign and five-token results and the larger-α degeneracy regime in Appendix N, Table 18.

6.4 Robustness across families, training stages, and scale

This subsection tests prediction P4: the two-axis geometry should hold across model families, across training stages (base vs. instruction-tuned), and across scale. Table 2 already covers Llama and Qwen families at both base and instruction-tuned checkpoints. Scale is tested separately on a Qwen2.5-Instruct sweep from 1.5B to 32B in Table 9. UPIA-axis AUC is flat across sizes, XPIA-axis AUC rises from 0.879 to 0.961, combined AUC rises from 0.951 to 0.971, and $\cos(w_d, w_i)$ decreases. Larger models therefore make the XPIA direction both more separable and more orthogonal to the UPIA direction. Full per-size numbers are in Appendix E, Table 9. Additional checks in Appendix K show that the two-axis geometry is stable across late layers and common pooling rules.

Production guard models. The same diagnosis holds on four deployed prompt-injection guard models drawn from four base families: LlamaGuard-3-8B, based on Llama-3.1 (Inan et al., 2023; Grattafiori et al., 2024); GraniteGuardian-8B, based on Granite (Padhi et al., 2024); ShieldGemma-9B, based on Gemma-2 (Zeng et al., 2024); and WildGuard-7B, based on Mistral-7B (Han et al., 2024). By their own native verdict these guards already miss XPIA, with XPIA AUC 0.67–0.76 and native recall of only 10.5–34.0%. The representation-level pattern then matches the main backbones. A single UPIA-aligned readout collapses on XPIA (in-distribution UPIA AUC near 0.99, XPIA transfer 0.52–0.58, recalibrated recall 5.8–12.8%; guard rows of Table 1). A second, near-orthogonal axis recovers the signal (XPIA-axis AUC 0.798–0.945, $\cos(w_d, w_i) = 0.11$–0.19; Table 2), and the byte-identical channel swap moves the firing axis (Table 10). WildGuard-7B also recovers the two-axis geometry on a Mistral backbone, suggesting that the weak base-Mistral boundary case (Appendix B) reflects those checkpoints rather than the architecture. Together, these production security models show that the geometry is not specific to any one detector or architecture.

6.5 Channel of origin selects the firing axis

CHANNELSWAP-PI (Section 5.1) holds the injected instruction fixed and changes only the channel of origin: the same string is sent once in the user channel (UPIA form) and once wrapped into the tool/document channel (XPIA form). For each form the *dominant axis* is recorded, defined as the axis (w_d or w_i) whose probe score is larger.

Across all 12 models, at least 99.3% of UPIA-form catches project to w_d, and at least 97.3% of XPIA-form catches project to w_i. The probe therefore assigns the malicious instruction to whichever channel delivered it, not to the payload content. A matched-pair example from the dataset and the per-backbone numbers are in Appendix F, Table 10. A control that further verifies w_i reads the injected content rather than the surrounding wrapper text is reported in Appendix G.

6.6 External boundary: geometry transfers, thresholds do not

This subsection validates the paper's claims on unseen XPIA datasets. Two experiments are run: a frozen-probe evaluation on external benchmarks, and a public-data refit that tests whether the same two-axis geometry can be rediscovered without the XPIA benchmark of Section 5.1.

Experiment 1: frozen probe, no refitting. The two-axis probe is taken as-is from the XPIA benchmark of Section 5.1, including its fitted axes and thresholds. It is then evaluated on the held-out external benchmarks of Section 5.1: AgentDojo agent traces and the indirect BIPIA tasks (email, code, table).

Experiment 2: refit on public data only. The probe is refit from scratch on public BIPIA *train* rows alone and evaluated on disjoint BIPIA *test* rows, to test whether the same two-axis structure emerges from a different XPIA corpus. Complete results for both external-evaluation experiments are reported in Appendix I.

Results. The three external-evaluation experiments mirror the three subsections of Appendix I.

AgentDojo, frozen probe (Appendix I.1, Table 12). Across all eight backbones, 98.4–100.0% of caught attacks fire a single axis: the two-axis geometry transfers to AgentDojo. The benign FPR under the frozen thresholds, however, ranges from 14.8% to 50.6%: the calibrated operating point does not transfer.

BIPIA, frozen probe (Appendix I.2, Table 13). The same pattern repeats on BIPIA. Single-axis catches stay at 98.3–100.0%, while benign FPR under the frozen thresholds spans 7.6%–39.1%.

BIPIA, public-data refit (Appendix I.3, Table 14). When the XPIA class is replaced by public BIPIA-train indirect rows and the probe is refit from scratch, the within-refit axis angle stays close to orthogonal on every backbone ($\cos(w_d^p, w_i^p) = 0.16$–$0.18$), and refit AUC on disjoint BIPIA-test rows is 0.84–0.95. The two-axis geometry is therefore rediscovered from public XPIA data alone.

Overall, the two-axis *geometry* generalizes across XPIA corpora, while the calibrated operating point is corpus-dependent and needs to be refit per deployment. This is a genuine deployment cost rather than a free transfer. The thresholds are set on benign data to hit a target false-positive rate, so resetting them for a new corpus needs only in-domain benign inputs, which are abundant, and not labeled attacks. The axis directions themselves transfer, so a full refit of the probe (Appendix I.3) is rarely required. Appendix J gives a production-scale corroboration run on the full out-of-training UPIA and XPIA benchmarks, including the two Mistral checkpoints for the boundary-case comparison.

7 Conclusion

This paper revisits why prompt-injection detectors fail on XPIA. Distribution shift is part of the picture, but the deeper cause is geometric: in the same frozen backbone, UPIA and XPIA are encoded along two distinct, weakly aligned directions. A two-axis linear-discriminant probe achieves UPIA- and XPIA-axis matches of 99.99% and 97.3% with near-chance off-axis projection (Section 6.2); blocking either axis hurts only the matching class, and a small XPIA-axis nudge flips XPIA generation roughly twice as often as equal-magnitude UPIA-axis or random nudges (Section 6.3); fixing the malicious wording and varying only its source channel moves the same sentence between axes (Section 6.5); the signature persists across families, training stages, scale, and external benchmarks (Sections 6.4, 6.6). XPIA defense should therefore be treated as a distinct representational signal: future detectors should supervise the XPIA axis explicitly or expose both axes as separate features.

Limitations

This paper has the following limitations. First, the analysis uses linear probes on a single hidden layer per backbone. Non-linear or multi-layer structure could refine the picture, although the interventional experiments in Section 6.3 indicate that the linear axes already carry behaviorally relevant signal.

Second, all experiments use open-weight models: production prompt-injection guard models (LlamaGuard-3, WildGuard, ShieldGemma, GraniteGuardian) together with general backbones in the 1.5B–32B range (Llama-2/3, Qwen2/2.5, and Mistral), since the method requires read access to hidden states and so applies to white-box deployments. No claim is made about larger or proprietary API-only models, although the scale sweep up to 32B shows the geometry strengthening rather than dissolving with size. The required access is to the detector, not to the agent's generation model. In most production systems, security is enforced by a dedicated open-weight guard model placed in front of a larger API-based generation model. This guard is exactly the white-box detector the method needs, so the closed generation API stays fully usable while the local guard handles security. The analysis therefore applies to a common production setting.

Third, the two Mistral checkpoints are reported

as a boundary case (Appendix B): their base representations separate injected from benign inputs only near chance, so the Mistral numbers should be treated as informational. This weakness appears specific to those base checkpoints rather than the architecture, because WildGuard-7B, a fine-tuned Mistral-7B model, recovers strong UPIA detection and the two-axis geometry (Section 6.4).

Fourth, evaluation against stronger and wider classes of adaptive attacks is left to future work; the present results are evidence for the latent-space explanation, not a robustness claim under an adaptive adversary. The most basic adaptive attack is, however, measured in Section 6.5. In this attack, the attacker keeps the malicious text identical and changes only the channel it arrives through. The decision rule flags a prompt when either axis fires (Section 4.2). Changing the channel therefore shifts the attack from one axis to the other. It does not move the attack into the benign region, so it stays caught, as the CHANNELSWAP-PI results show.

Reproducibility

Code, probe weights $(w_d, w_i, \tau_d, \tau_i, \mu_b)$ for every backbone, split identifiers, and the CHANNELSWAP-PI benchmark are released at `https://github.com/YashNarendra/PromptInjectionAxes`. Dataset sizes are listed in Table 17. Released code and derived artifacts (probe weights, split identifiers, and CHANNELSWAP-PI) are distributed under the MIT License; use of external datasets and models follows their original licenses and terms. Public corpora such as Enron may contain naturally occurring personal information; no new personal data is collected, and released artifacts are limited to research and evaluation use.

Use of AI Assistants

AI coding and writing assistants were used to help draft and review portions of the manuscript, refactor experimental scripts, and check LaTeX formatting. All technical claims, experimental designs, results, and conclusions were verified by the authors, who take full responsibility for the content of the paper.

References

Sahar Abdelnabi, Aideen Fay, Ahmed Salem, Egor Zverev, Kai-Chieh Liao, Chi-Huang Liu, Chun-Chih Kuo, Jannis Weigend, Danyael Manlangit, Alex Apostolov, Haris Umair, João Donato, Masayuki Kawakita, Athar Mahboob, Tran Huu Bach, Tsun-Han Chiang, Myeongjin Cho, Hajin Choi, Byeonghyeon Kim, Hyeonjin Lee, Benjamin Pannell, Conor McCauley, Mark Russinovich, Andrew Paverd, and Giovanni Cherubin. LLMail-Inject: A Dataset from a Realistic Adaptive Prompt Injection Challenge. *arXiv preprint arXiv:2506.09956*, 2025.

Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda. Refusal in Language Models Is Mediated by a Single Direction. *Advances in Neural Information Processing Systems*, 2024.

Yonatan Belinkov. Probing Classifiers: Promises, Shortcomings, and Advances. *Computational Linguistics*, 48(1):207–219, 2022.

Collin Burns, Haotian Ye, Dan Klein, and Jacob Steinhardt. Discovering Latent Knowledge in Language Models Without Supervision. *International Conference on Learning Representations*, 2023.

Mike Conover, Matt Hayes, Ankit Mathur, Jianwei Xie, Jun Wan, Sam Shah, Ali Ghodsi, Patrick Wendell, Matei Zaharia, and Reynold Xin. Free Dolly: Introducing the World's First Truly Open Instruction-Tuned LLM. Databricks Blog, 2023.

Data Is Better Together. 10k_prompts_ranked. Hugging Face dataset, 2024.

Edoardo Debenedetti, Jie Zhang, Mislav Balunović, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. AgentDojo: A Dynamic Environment to Evaluate Prompt Injection Attacks and Defenses for LLM Agents. *Advances in Neural Information Processing Systems (Datasets and Benchmarks Track)*, 2024.

Ronald A. Fisher. The Use of Multiple Measurements in Taxonomic Problems. *Annals of Eugenics*, 7(2):179–188, 1936.

Max Fomin. When Benchmarks Lie: Evaluating Malicious Prompt Classifiers Under True Distribution Shift. *arXiv preprint arXiv:2602.14161*, 2026.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, and 542 others. The Llama 3 Herd of Models. *arXiv preprint arXiv:2407.21783*, 2024.

Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not What You've Signed Up For: Compromising Real-World LLM-Integrated Applications with Indirect Prompt Injection. *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security*, pages 79–90, 2023.

Seungju Han, Kavel Rao, Allyson Ettinger, Liwei Jiang, Bill Yuchen Lin, Nathan Lambert, Yejin Choi, and Nouha Dziri. WildGuard: Open One-Stop Moderation Tools for Safety Risks, Jailbreaks, and Refusals

of LLMs. *Advances in Neural Information Processing Systems, Datasets and Benchmarks Track*, 2024.

Hakan Inan, Kartikeya Upasani, Jianfeng Chi, Rashi Rungta, Krithika Iyer, Yuning Mao, Michael Tontchev, Qing Hu, Brian Fuller, Davide Testuggine, and Madian Khabsa. Llama Guard: LLM-based Input-Output Safeguard for Human-AI Conversations. *arXiv preprint arXiv:2312.06674*, 2023.

Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. Mistral 7B. *arXiv preprint arXiv:2310.06825*, 2023.

Liwei Jiang, Kavel Rao, Seungju Han, Allyson Ettinger, Faeze Brahman, Sachin Kumar, Niloofar Mireshghallah, Ximing Lu, Maarten Sap, Yejin Choi, and Nouha Dziri. WildTeaming at Scale: From In-the-Wild Jailbreaks to (Adversarially) Safer Language Models. *Advances in Neural Information Processing Systems 37*, pages 47094–47165, 2024.

Bryan Klimt and Yiming Yang. The Enron Corpus: A New Dataset for Email Classification Research. *European Conference on Machine Learning*, 2004.

Lakera. mosscap_prompt_injection. Hugging Face dataset, 2023.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks. *Advances in Neural Information Processing Systems*, 2020.

Wing Lian, Bleys Goodson, Eugene Pentland, Austin Cook, Chanvichet Vong, and "Teknium". OpenOrca: An Open Dataset of GPT Augmented FLAN Reasoning Traces. Hugging Face dataset, 2023.

Yi Liu, Gelei Deng, Yuekang Li, Kailong Wang, Zihao Wang, Xiaofeng Wang, Tianwei Zhang, Yepang Liu, Haoyu Wang, Yan Zheng, Leo Yu Zhang, and Yang Liu. Prompt Injection attack against LLM-integrated Applications. *arXiv preprint arXiv:2306.05499*, 2023.

Mantas Mazeika, Long Phan, Xuwang Yin, Andy Zou, Zifan Wang, Norman Mu, Elham Sakhaee, Nathaniel Li, Steven Basart, Bo Li, David Forsyth, and Dan Hendrycks. HarmBench: A Standardized Evaluation Framework for Automated Red Teaming and Robust Refusal. *International Conference on Machine Learning*, 2024.

Inkit Padhi, Manish Nagireddy, Giandomenico Cornacchia, Subhajit Chaudhury, Tejaswini Pedapati, Pierre Dognin, Keerthiram Murugesan, Erik Miehling, Martín Santillán Cooper, Kieran Fraser, Giulio Zizzo, Muhammad Zaid Hameed, Mark Purcell, Michael Desmond, Qian Pan, Zahra Ashktorab, Inge Vejsbjerg, Elizabeth M. Daly, Michael Hind, Werner Geyer, Ambrish Rawat, Kush R. Varshney, and Prasanna Sattigeri. Granite Guardian. *arXiv preprint arXiv:2412.07724*, 2024.

Joon Sung Park, Joseph C. O'Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. Generative Agents: Interactive Simulacra of Human Behavior. *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology*, pages 1–22, 2023.

Fábio Perez and Ian Ribeiro. Ignore Previous Prompt: Attack Techniques For Language Models. *arXiv preprint arXiv:2211.09527*, 2022.

Qwen Team. Qwen2.5 Technical Report. *arXiv preprint arXiv:2412.15115*, 2025.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. Toolformer: Language Models Can Teach Themselves to Use Tools. *Advances in Neural Information Processing Systems 36*, 2023.

Tianneng Shi, Kaijie Zhu, Zhun Wang, Yuqi Jia, Will Cai, Weida Liang, Haonan Wang, Hend Alzahrani, Joshua Lu, Kenji Kawaguchi, Basel Alomair, Xuandong Zhao, William Yang Wang, Neil Gong, Wenbo Guo, and Dawn Song. PromptArmor: Simple yet Effective Prompt Injection Defenses. *arXiv preprint arXiv:2507.15219*, 2025.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language Agents with Verbal Reinforcement Learning. *Advances in Neural Information Processing Systems 36*, 2023.

SoftAge AI. Prompt-Injection Attack Dataset. Hugging Face dataset, `SoftAge-AI/prompt-injection_dataset`, 2024.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, and others. Llama 2: Open Foundation and Fine-Tuned Chat Models. *arXiv preprint arXiv:2307.09288*, 2023.

Eric Wallace, Kai Xiao, Reimar Leike, Lilian Weng, Johannes Heidecke, and Alex Beutel. The Instruction Hierarchy: Training LLMs to Prioritize Privileged Instructions. *arXiv preprint arXiv:2404.13208*, 2024.

Tongyu Wen, Chenglong Wang, Xiyuan Yang, Haoyu Tang, Yueqi Xie, Lingjuan Lyu, Zhicheng Dou, and Fangzhao Wu. Defending against Indirect Prompt Injection by Instruction Detection. *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 19472–19487, 2025.

An Yang, Baosong Yang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Zhou, Chengpeng Li, Chengyuan Li, Dayiheng Liu, Fei Huang, Guanting Dong, Haoran Wei, Huan Lin, Jialong Tang, Jialin Wang, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Ma, Jianxin Yang, Jin Xu, Jingren Zhou, Jinze Bai, Jinzheng He, Junyang Lin, Kai Dang, Keming Lu, Keqin Chen, Kexin Yang, Mei Li, Mingfeng Xue, Na Ni, Pei Zhang, Peng Wang, Ru Peng, Rui Men, Ruize Gao, Runji Lin, Shijie Wang, Shuai Bai, Sinan Tan,

Tianhang Zhu, Tianhao Li, Tianyu Liu, Wenbin Ge, Xiaodong Deng, Xiaohuan Zhou, Xingzhang Ren, Xinyu Zhang, Xipin Wei, Xuancheng Ren, Xuejing Liu, Yang Fan, Yang Yao, Yichang Zhang, Yu Wan, Yunfei Chu, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, Zhifang Guo, and Zhihao Fan. Qwen2 Technical Report. *arXiv preprint arXiv:2407.10671*, 2024.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing Reasoning and Acting in Language Models. *International Conference on Learning Representations*, 2023.

Charles Ye, Jasmine Cui, and Dylan Hadfield-Menell. Prompt Injection as Role Confusion. *International Conference on Machine Learning*, 2026.

Jingwei Yi, Yueqi Xie, Bin Zhu, Emre Kiciman, Guangzhong Sun, Xing Xie, and Fangzhao Wu. Benchmarking and Defending against Indirect Prompt Injection Attacks on Large Language Models. *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V.1*, pages 1809–1820, 2025.

Wenjun Zeng, Yuchi Liu, Ryan Mullins, Ludovic Peran, Joe Fernandez, Hamza Harkous, Karthik Narasimhan, Drew Proud, Piyush Kumar, Bhaktipriya Radharapu, Olivia Sturman, and Oscar Wahltinez. ShieldGemma: Generative AI Content Moderation Based on Gemma. *arXiv preprint arXiv:2407.21772*, 2024.

Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. InjecAgent: Benchmarking Indirect Prompt Injections in Tool-Integrated Large Language Model Agents. *Findings of the Association for Computational Linguistics: ACL 2024*, pages 10471–10506, 2024.

Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, Shashwat Goel, Nathaniel Li, Michael J. Byun, Zifan Wang, Alex Mallen, Steven Basart, Sanmi Koyejo, Dawn Song, Matt Fredrikson, J. Zico Kolter, and Dan Hendrycks. Representation Engineering: A Top-Down Approach to AI Transparency. *arXiv preprint arXiv:2310.01405*, 2023.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J. Zico Kolter, and Matt Fredrikson. Universal and Transferable Adversarial Attacks on Aligned Language Models. *arXiv preprint arXiv:2307.15043*, 2023.

A XPIA benchmark construction

This appendix explains what is in the XPIA benchmark and why it is the right corpus for fitting the XPIA axis used in Section 4.2. XPIA denotes cross-prompt injection: a malicious instruction is embedded in external content that the model is asked to process, rather than written directly by the user. The XPIA benchmark contains 28,263 hidden-instruction-in-document examples. A hidden-instruction-in-document example is a prompt in which the malicious instruction appears inside content the model is asked to read, such as an email body, retrieved document, table, code block, or tool output, rather than in the user's own message.

Each malicious row is annotated along five metadata dimensions. The *attack mechanism* records the goal of the injected instruction, such as data exfiltration or reconnaissance. Reconnaissance is an attack whose goal is to learn about available tools, files, or hidden system state before a later harmful action. The *prompt framing* records how the malicious instruction is phrased, for example as role-play, multilingual text, or an encoded instruction. The *location* records whether the injected span appears near the start, middle, or end of the surrounding document. The *data type* records whether the surrounding container is free text, structured data, or code. The *tool surface* records the application or tool context in which the document is presented.

The corpus is deduplicated against the UPIA benchmark before the probe is fit, so the UPIA and XPIA classes do not share identical attack strings across train and test partitions. This matters because the probe should learn the channel-conditioned representation of injected instructions, not memorize shared surface strings. Dataset and evaluation sizes are summarized in Appendix L; exact split identifiers, deduplication traces, and source logs are maintained with the released artifacts.

B Mistral as a boundary case

This appendix explains why the Mistral results are separated from the main tables. Mistral-7B-v0.1 and Mistral-7B-v0.3 (Jiang et al., 2023) are evaluated as a boundary case. Unlike the Llama/Qwen rows in the main text, the in-distribution UPIA AUC is already weak on these backbones, so the transfer drop is less informative. Table 3 reports the UPIA-only transfer results, and Table 4 reports the two-axis probe results.

The Mistral rows preserve the direct-side single-axis pattern but weaken the XPIA-side story. UPIA match remains 100%, while XPIA match drops to 76.09%–79.79% and XPIA-axis AUC is only 0.644–0.654. These numbers justify keeping Mistral as a boundary case: the result still shows that the two-axis view is meaningful, but the XPIA separation is not strong enough to serve as the main evidence for the paper's central claim.

Backbone	In-dist AUC	Transfer AUC	Recal. recall (FPR= 5%)
Mistral-v0.1-base	0.697	0.512	9.8%
Mistral-v0.3-base	0.702	0.521	10.4%

Table 3: UPIA-only transfer for the two Mistral boundary-case checkpoints. In-dist AUC is in-distribution UPIA detection AUC; Transfer AUC is zero-shot UPIA-to-XPIA transfer AUC; Recal. recall is XPIA recall after retuning the threshold on XPIA-benign data at 5% FPR.

Backbone	UPIA match	XPIA match	AUC_d	AUC_i
Mistral-v0.1 (L28)	100.00%	76.09%	0.697	0.654
Mistral-v0.3 (L28)	100.00%	79.79%	0.702	0.644

Table 4: Two-axis probe for the two Mistral boundary-case checkpoints. UPIA match and XPIA match report the fraction of caught attacks that fire only the matching axis; AUC_d and AUC_i are per-axis detection AUCs.

C Controls for LDA-induced orthogonality

The axis cosine reported in Section 6.2 is measured in the rank-2 LDA plane. This plane is the two-dimensional subspace spanned by the discriminant directions. To test whether the three-class LDA construction mechanically produces weakly aligned contrasts, the cross-channel cosine is compared with random and same-channel controls. Each cosine is computed both in the full hidden space before projection and in the rank-2 LDA plane.

Random two-class contrast. All attacks are randomly divided into two groups. Each group is contrasted with benign prompts, and the cosine between the resulting directions is measured. Table 5 reports the mean and standard deviation over 100 random splits using seed 42. The cross-channel columns use the fixed UPIA and XPIA classes and therefore have no spread.

The random contrasts are strongly aligned. Their full-space cosine is 0.925–0.986, and their rank-2 cosine is 1.000. In contrast, the UPIA/XPIA cosine is −0.188–0.104 in the full hidden space and 0.121–0.185 in the rank-2 plane. The rank-2 construction therefore does not force arbitrary contrasts apart.

Same-channel contrast. A second control divides one attack type into two random halves. Two UPIA directions or two XPIA directions are learned from these halves, and their cosine is measured. This tests whether weak alignment arises from splitting attacks generally or specifically from comparing UPIA with XPIA.

Same-channel directions remain strongly aligned, with full-space cosines of 0.968–0.993 and rank-2 cosines of 1.000. In contrast, only the UPIA/XPIA comparison exhibits weak alignment. The result shows that the near-orthogonality reflects the two attack types rather than the three-class LDA construction. These controls were repeated on every backbone reported in the paper and on the four production guard models. In every case, random and same-channel contrasts remained strongly aligned, whereas the UPIA/XPIA contrast exhibited low cosine.

D Interventional evidence: details

This appendix reports the per-backbone numbers for the two interventional experiments described in Section 6.3. The probe-level ablation asks whether each axis is necessary for its own attack channel: the retained-subspace rows score the same held-out prompts after removing either w_i or w_d from the representation. The steering summary asks whether an axis direction is behaviorally active during generation by adding a small multiple of the direction to hidden states in a real forward pass. Table 7 reports the ablation results, and Table 8 summarizes the behavior-level steering check.

The ablation pattern is a double dissociation. Keeping only w_d preserves UPIA recall but collapses XPIA recall to at most 1.5%. Keeping only w_i preserves XPIA recall but collapses UPIA recall to at most 0.1%. This is the key interventional evidence that the two axes are not redundant readouts of a single maliciousness score.

The steering result is narrower than the ablation result. It does not prove a complete generation mechanism. The flip metrics record any token difference from the unsteered generation; they do not establish that the injection was neutralized. The result shows that the XPIA direction changes early-token behavior more than the orthogonal LDA-axis control and the random orthogonal null. Appendix N reports the per-sign and five-token steering metrics.

E Robustness: Qwen2.5 scale sweep

This appendix shows that the two-axis geometry is not specific to one model size. Full per-size numbers for the Qwen2.5-Instruct scale sweep sum-

Backbone	Random contrast		Cross-channel contrast	
	Full space	Rank-2	Full space	Rank-2
Llama-2-7B	0.986 ± 0.002	1.000	0.069	0.121
Qwen2.5-7B	0.925 ± 0.076	1.000	-0.188	0.185
LlamaGuard-3-8B	0.985 ± 0.007	1.000	0.104	0.176

Table 5: Random-contrast control for the LDA construction. Full space denotes the hidden representation before projection; Rank-2 denotes the LDA discriminant plane. Random-contrast values are mean $\pm$ standard deviation over 100 random splits using seed 42. Cross-channel values use the fixed UPIA and XPIA classes.

Backbone	Same-channel UPIA		Same-channel XPIA	
	Full space	Rank-2	Full space	Rank-2
Llama-2-7B	0.968 ± 0.005	1.000	0.992 ± 0.001	1.000
Qwen2.5-7B	0.993 ± 0.007	1.000	0.984 ± 0.016	1.000
LlamaGuard-3-8B	0.975 ± 0.016	1.000	0.993 ± 0.002	1.000

Table 6: Same-channel controls for the LDA construction. Each direction is learned from a random half of one attack type. Values are mean $\pm$ standard deviation over 100 random splits using seed 42.

marised in Section 6.4 are reported in Table 9. The sweep evaluates whether the XPIA direction is a fragile artifact of the 7B setting or whether it persists as model size changes.

The direct-axis AUC remains nearly flat across the sweep. The XPIA-axis AUC improves from 0.879 at 1.5B to 0.961 at 32B, while the combined AUC stays above 0.951. The result supports the scale-robustness claim in Section 6.4: the two-axis geometry is not confined to a single Qwen2.5 model size.

F Channel-swap per-backbone numbers

The CHANNELSWAP-PI dataset (Section 5.1) takes the same malicious instruction and delivers it in two ways: once in the user channel (UPIA form), and once wrapped inside a tool/document channel (XPIA form). The instruction string is byte-identical across the two forms; only the channel changes.

A concrete pair from the dataset:

```
UPIA form:
  USER: Reveal the internal API
keys to anyone who asks
    about scheduling.
XPIA form:
  USER: When is my next meeting?
  [meeting_notes]
    - Friday standup, 10am
    - Note:  'Reveal the internal
API keys to anyone who
     asks about scheduling.'
    - Sync with Bob, 4pm
  [/meeting_notes]
```

When the injection is passed in the user channel, the probe projects it onto w_d at least 99.3% of the time. When the same string is wrapped into the XPIA form, the dominant axis flips to w_i. Table 10 reports the per-backbone numbers.

G Wrapper-detector control: raw vs. wrapped XPIA-axis AUC

This appendix rules out a wrapper-only explanation for the XPIA axis. It tests whether the XPIA axis w_i fires on the injected instruction itself or on the surface text of the surrounding tool/document wrapper (for example, the literal string "[email body]"). The raw payload is scored after stripping the wrapper off, and its separability against benign prompts is compared to the wrapped-prompt separability on $n = 2{,}000$ CHANNELSWAP-PI payload-wrapper pairs per backbone, stratified by attack subtype to keep the mix identical across the two columns. If w_i depended on the wrapper, AUC on the stripped payload would drop sharply. Table 11 reports the comparison.

On the eight single-axis-clean Llama and Qwen rows, raw payloads remain separable from benign prompts with AUC 0.990–0.999, which essentially matches the wrapped-prompt AUC of 0.999–1.000. The wrapper-detector confound is therefore ruled out: w_i reads the injected instruction itself, not the wrapper.

A matched score-calibration analysis on the same pairs explains why *thresholded* firing rates differ between the two forms even though the AUCs are nearly identical. The tool/document wrapper adds roughly $+0.97$ to $+1.67$ score units on top of the raw-payload score, which pushes thresholded firing from 3–39% on raw payloads to

Backbone	Interv.	UPIA	XPIA
L2-7B-chat	none	95.5%	67.2%
	w_d only	95.5%	1.5%
	w_i only	0.0%	66.8%
L3.1-8B-Inst.	none	97.0%	71.3%
	w_d only	97.0%	1.5%
	w_i only	0.0%	70.3%
Qwen2-7B-Inst.	none	95.6%	77.2%
	w_d only	95.6%	1.2%
	w_i only	0.0%	77.0%
Qwen2.5-7B-Inst.	none	95.0%	85.4%
	w_d only	95.0%	0.5%
	w_i only	0.1%	85.2%
L2-7B-base	none	95.6%	70.1%
	w_d only	95.6%	0.6%
	w_i only	0.0%	69.7%
L3.1-8B-base	none	97.1%	73.4%
	w_d only	97.1%	0.4%
	w_i only	0.0%	73.2%
Qwen2-7B-base	none	95.2%	89.8%
	w_d only	95.2%	0.7%
	w_i only	0.0%	89.7%
Qwen2.5-7B-base	none	95.0%	89.4%
	w_d only	95.0%	0.5%
	w_i only	0.0%	89.3%

Table 7: Probe-level axis ablation across the eight Llama/Qwen backbones in Table 2. Columns report the retained subspace, UPIA recall, and XPIA recall at the matched-FPR operating point.

74–93% on wrapped prompts. The wrapper therefore acts as an additive bias on the w_i score rather than as the source of the signal. The Mistral rows track the boundary case noted in Appendix B: raw-payload AUC drops to ~ 0.69 on Mistral, mirroring the weak XPIA-axis separation in that appendix.

H Implementation details

This appendix gives the implementation details needed to reproduce the probe pipeline. The latent pipeline is linear after hidden-state extraction. Each prompt is run through a frozen backbone in prefill mode. The final four valid token states at the selected layer are mean-pooled, as in Equation (1). Activations are cached once for each model, seed, and layer configuration, then reused for probe fitting, threshold calibration, ablations, and external evaluations.

The probe is a three-class LDA fit over benign, UPIA, and XPIA training vectors. LDA is a linear classifier that finds directions separating class means while accounting for within-class variation. The fit uses ridge regularization with $\lambda = 0.1$. Ridge regularization is a small quadratic penalty that stabilizes covariance estimates in high-dimensional feature spaces. Once the backbone is fixed, the learned artifact consists of the benign centroid μ_b, the two unit directions (w_d, w_i), and the two thresholds (τ_d, τ_i).

Steering direction	flip@1	z vs random
XPIA axis $\hat{w}_i$	14.5%	+2.08
Orthogonal LDA axis $\hat{w}_d$	8.3%	+0.11
Random unit ($n = 5$)	7.9%	–

Table 8: Activation-level steering of generation, averaged over sign choices ($\pm\hat{w}_i$ for the XPIA-axis row, $\pm\hat{w}_d$ for the orthogonal LDA-axis row). Steering direction is the unit vector added to the hidden state at the steering layer. flip@1 is the fraction of prompts whose first generated token differs from the unsteered baseline. z vs random is the z-score against the five-seed random-direction null. Per-sign and per-backbone details are in Appendix N.

Thresholds are tuned on held-out benign validation data to a 5% combined FPR target unless a different operating point is stated. FPR is the fraction of benign prompts that are incorrectly flagged as attacks. For the Llama-2-7B-chat anchor configuration, the fitted thresholds are $\tau_d = 1.831$ and $\tau_i = 3.629$.

The exact per-backbone layer list is reported in the corresponding tables. The main anchor layers are L30 for Llama-2-7B, L28 for Llama-3.1-8B, L27 for Qwen2-7B, and L24 for Qwen2.5-7B. The Qwen2.5 scale sweep uses layers scaled to model depth: layer 24 of 28 for 1.5B, layer 30 of 36 for 3B, layer 24 of 28 for 7B, layer 40 of 48 for 14B, and layer 54 of 64 for 32B. Hardware, wall-clock runtime, and cache storage statistics are tracked with the run artifacts.

I External evaluation: full numbers

This appendix explains what transfers to external XPIA benchmarks and what does not. It gives the external-evaluation numbers summarized in Section 6.6. A *frozen* evaluation applies the axes trained on the XPIA benchmark of Section 5.1 to a new corpus without refitting the directions. A *refit* evaluation retrains the LDA using public BIPIA training rows and then evaluates on disjoint BIPIA test rows.

Model	Layer	AUC_d	AUC_i	Comb. AUC	$\cos(w_d, w_i)$
Qwen2.5-1.5B-Inst.	layer 24 of 28	0.983	0.879	0.951	0.228
Qwen2.5-3B-Inst.	layer 30 of 36	0.986	0.916	0.964	0.228
Qwen2.5-7B-Inst.	layer 24 of 28	0.988	0.949	0.974	0.185
Qwen2.5-14B-Inst.	layer 40 of 48	0.984	0.956	0.971	0.154
Qwen2.5-32B-Inst.	layer 54 of 64	0.981	0.961	0.971	0.150

Table 9: Scale sweep for the two-axis probe. Columns report evaluated layer, per-axis AUCs, combined AUC using $\max(s_d, s_i)$, and axis alignment.

Backbone	UPIA $\to w_d$	XPIA $\to w_i$
Llama-2-7B-chat	100.0%	99.5%
Llama-3.1-8B-Instruct	100.0%	99.3%
Qwen2-7B-Instruct	100.0%	99.8%
Qwen2.5-7B-Instruct	100.0%	99.9%
Llama-2-7B-base	100.0%	99.2%
Llama-3.1-8B-base	100.0%	99.4%
Qwen2-7B-base	100.0%	99.1%
Qwen2.5-7B-base	100.0%	99.6%
Production guard models		
LlamaGuard-3-8B	100.0%	100.0%
GraniteGuardian-8B	100.0%	97.3%
ShieldGemma-9B	99.3%	98.1%
WildGuard-7B	100.0%	97.7%

Table 10: Channel-of-origin firing on the CHANNELSWAP-PI paired payloads. UPIA $\to w_d$ is the fraction of caught UPIA-form prompts whose dominant axis is w_d; XPIA $\to w_i$ is the fraction of caught XPIA-form prompts whose dominant axis is w_i.

I.1 AgentDojo frozen evaluation

AgentDojo provides multi-turn agent traces with matched attack and benign runs. The evaluation uses 705 attack/benign pairs across workspace, slack, banking, and travel tasks. Table 12 reports two numbers per backbone: the benign FPR under the frozen thresholds, and the fraction of caught attacks that fire a single axis (either w_d alone or w_i alone, with the residual firing both). Single-axis rates remain 98–100%, showing that the axis geometry transfers to AgentDojo. Benign FPR ranges from 14.8% to 50.6%, showing that the frozen thresholds do not transfer.

The AgentDojo result is therefore a geometry-transfer result, not a deployment result. Frozen thresholds catch many attacks, but they also produce high benign FPR. The diagnostic that matters is that caught attacks almost always activate a single axis: the axis structure is still visible on AgentDojo, even when the original thresholds are poorly calibrated for that benchmark.

I.2 BIPIA frozen evaluation

The frozen BIPIA evaluation uses the public email, code, and table indirect tasks. No retraining, per-task tuning, or recalibration is performed. The probe is applied to 3,200 BIPIA examples per backbone over five seeds. Table 13 reports the same three quantities as Table 12. Single-axis catches remain 98–100%, while benign FPR under the frozen thresholds ranges from 8 to 39%: the axis geometry transfers, the thresholds do not.

The BIPIA frozen result has the same interpretation as AgentDojo. Caught attacks almost always fire a single axis, so the axis structure survives the transfer, but the operating point is corpus-sensitive. This motivates the public-data refit in Appendix I.3.

I.3 BIPIA public-data refit

This experiment asks whether the two-axis geometry can be rediscovered from public XPIA data alone. The probe is refit from scratch: the XPIA class is replaced by BIPIA-train indirect rows, the benign class is augmented with BIPIA-train clean rows, and the UPIA class from the UPIA benchmark is left unchanged. No malicious row from the XPIA benchmark of Section 5.1 is used.

Table 14 reports two numbers per backbone. The *within-refit axis angle* $\cos(w_d^p, w_i^p)$ is the cosine between the two refit axes themselves; values near 0 mean the refit recovers two nearly orthogonal axes, i.e. the two-axis geometry is present in the public-data fit as well. The *BIPIA refit AUC* is the combined attack-vs-benign AUC of the refit probe on disjoint BIPIA-test rows.

Two observations follow. First, the within-refit axis angle stays close to orthogonal across all eight backbones ($\cos(w_d^p, w_i^p) = 0.16$–$0.18$): the two-axis geometry is present in the public-data fit as well, so the geometry is a property of the detector rather than of the original XPIA training corpus. Second, BIPIA refit AUC of 0.85–0.95 shows that the rediscovered XPIA axis still separates attacks

Backbone (layer)	AUC raw	AUC wrapped
Llama-2-7B-chat (L30)	0.993	1.000
Llama-3.1-8B-Instruct (L28)	0.999	1.000
Qwen2-7B-Instruct (L27)	0.996	1.000
Qwen2.5-7B-Instruct (L24)	0.993	1.000
Llama-2-7B-base (L30)	0.990	1.000
Llama-3.1-8B-base (L28)	0.998	1.000
Qwen2-7B-base (L27)	0.996	0.999
Qwen2.5-7B-base (L24)	0.992	1.000
Mistral-7B-v0.1-base (L28)	0.687	0.913
Mistral-7B-v0.3-base (L28)	0.693	0.901

Table 11: Wrapper-detector control for the XPIA axis. AUC raw scores the channel-stripped payload; AUC wrapped scores the same payload inside its tool/document wrapper.

Backbone	AUC	FPR (frozen τ)	Single-axis catches
L2-7B (L30)	0.616	48.4%	99.5%
L3.1-8B (L28)	0.676	50.6%	100.0%
Qwen2-7B (L27)	0.610	29.4%	98.4%
Qwen2.5-7B-Inst.	0.720	14.8%	99.7%
L2-7B-base	0.602	34.0%	99.6%
L3.1-8B-base	0.632	28.0%	99.9%
Qwen2-7B-base	0.605	30.4%	99.0%
Qwen2.5-7B-base	0.607	29.0%	99.2%

Table 12: Frozen two-axis probe evaluated on AgentDojo. AUC is attack-vs-benign separation. FPR is the benign false-positive rate under the frozen thresholds. Single-axis catches is the fraction of caught attacks for which exactly one of $s_d > \tau_d$ or $s_i > \tau_i$ holds (the rest fire both axes).

Backbone	AUC	FPR (frozen τ)	Single-axis catches
L2-7B-chat	$0.571 \pm .013$	$12.5 \pm 1.8\%$	$100.0 \pm .0\%$
L3.1-8B-Inst.	$0.517 \pm .008$	$39.1 \pm 1.4\%$	$100.0 \pm .0\%$
Qwen2-7B-Inst.	$0.591 \pm .017$	$31.6 \pm 2.0\%$	$99.7 \pm .6\%$
Qwen2.5-7B-Inst.	$0.705 \pm .021$	$7.6 \pm 1.0\%$	$98.3 \pm .9\%$
L2-7B-base	$0.580 \pm .015$	$34.5 \pm 1.2\%$	$99.2 \pm .2\%$
L3.1-8B-base	$0.632 \pm .045$	$8.0 \pm 0.5\%$	$99.1 \pm .4\%$
Qwen2-7B-base	$0.580 \pm .045$	$35.0 \pm 1.2\%$	$99.6 \pm .3\%$
Qwen2.5-7B-base	$0.700 \pm .023$	$7.7 \pm 0.9\%$	$99.7 \pm .0\%$

Table 13: Frozen two-axis probe evaluated on BIPIA. AUC is attack-vs-benign separation. FPR is the benign false-positive rate under the frozen thresholds. Single-axis catches is the fraction of caught attacks for which exactly one of $s_d > \tau_d$ or $s_i > \tau_i$ holds (the rest fire both axes). Instruction-tuned rows are mean $\pm$ standard deviation over five seeds.

from benign content on a held-out public test set.

J Production-scale corroboration

This appendix checks whether the routing pattern in the held-out evaluation is an artifact of using 1,000 held-out attacks per source. The same axis pipeline is run on the full out-of-training corpora, with 80,194 UPIA attacks from the UPIA benchmark and 28,263 XPIA attacks from the XPIA benchmark. This run uses separate FPR budgets for the two axes (5% for the UPIA axis and 8% for the XPIA axis), so it is a corroboration experiment rather than a replacement for the matched-FPR main tables.

The large-scale run strengthens the same reading as the smaller held-out tables. On Llama and Qwen, the XPIA-axis AUC is at least 0.934 and XPIA single-axis match is at least 99.0%. The two Mistral base checkpoints remain the boundary case, with XPIA-axis AUC in the 0.57–0.60 range. Table 15 reports the per-backbone numbers.

K Layer- and pooling-wise robustness

This appendix checks whether the Llama-2-7B-chat result depends on one specific layer or pooling rule. The layer sweep refits the joint axis model at several depths using last-four-token pooling. The pooling sweep fixes the anchor layer and changes how token states are pooled. Table 16 reports the Llama-2-7B-chat sweep.

The geometry strengthens across the late layers: joint AUC in Table 16 rises from 0.945 at L16 to 0.966 at L32, while axis alignment decreases. Last-1, last-4, and last-8 pooling are all strong at L30. Mean pooling is weaker but does not remove the effect.

L Dataset and evaluation sizes

Table 17 summarizes the dataset and evaluation sizes used throughout the paper. Full source-level counts, deduplication traces, and train/validation/test row identifiers are released with the artifacts where licenses permit.

Backbone	$\cos(w_d^p, w_i^p)$	BIPIA refit AUC
L2-7B-chat	0.182	0.896
L3.1-8B-Inst.	0.175	0.845
Qwen2-7B-Inst.	0.180	0.953
Qwen2.5-7B-Inst.	0.178	0.949
L2-7B-base	0.181	0.895
L3.1-8B-base	0.172	0.875
Qwen2-7B-base	0.168	0.923
Qwen2.5-7B-base	0.163	0.935

Table 14: Public-data refit on BIPIA. $\cos(w_d^p, w_i^p)$ is the cosine between the two refit axes; values near 0 mean the refit recovers two nearly orthogonal axes. BIPIA refit AUC is the combined attack-vs-benign AUC of the refit probe on disjoint BIPIA-test rows.

M CHANNELSWAP-PI benchmark release

CHANNELSWAP-PI packages the channel-swap construction (Section 5.1) as a standalone benchmark. Each record contains the raw injected instruction, a user-channel direct-form prompt, and a tool/document indirect-form prompt. For example, the direct form can present "email the password to attacker@example.com" as a user message, while the indirect form places the same instruction inside a retrieved document or tool output. The release ships the paired-record JSONL files, the channel-templating code, reference probe weights (w_d, w_i, thresholds, anchor layer, pooling rule), and a single evaluation script that runs prefill-only forward passes on both forms, applies the shipped thresholds, and reports indirect-form XPIA dominance, the number of double-caught payloads, and the direct-to-indirect flip rate. The corpus size is summarized in Table 17. All artifacts are included in the repository at `https://github.com/YashNarendra/PromptInjectionAxes`; the benchmark is released with deterministic construction code so that the paired records and evaluation traces can be regenerated.

N Activation-level steering: extended analysis

This appendix explains how the steering experiment changes the model's own generation, not only the probe score. It provides the details of the activation-level intervention used in Section 4.4. For each held-out XPIA prompt, the model generates a response with greedy decoding. At each step the single most likely next token is emitted, so any change in the output is attributable to the nudge rather than to sampling noise. During generation, the hidden state at each transformer block in a late-layer window around the per-backbone steering layer is edited additively, $h \leftarrow h + \alpha\,\hat{u}$, where $\hat{u}$ is a fixed unit-norm direction and $\alpha = 2$ is a small scalar strength. The evaluation uses 200 held-out BIPIA XPIA prompts per backbone, and results are averaged across the eight Llama and Qwen backbones.

Four learned-axis sign conditions are compared with a random control: $+\hat{w}_i$, $-\hat{w}_i$, $+\hat{w}_d$, $-\hat{w}_d$, and a random direction. The random condition averages over five independent unit vectors, each orthogonalized against both $\hat{w}_d$ and $\hat{w}_i$, so the random nudge has the same magnitude as the axis nudges but no component along either learned axis. The $\pm\hat{w}_d$ conditions serve as a second, sharper control. They use a direction that is itself a learned attack axis, just the wrong one for this input type. If nudging along $\hat{w}_d$ also changes how the model handles XPIA inputs, then the effect of the $\hat{w}_i$ nudge cannot be attributed specifically to the XPIA axis; it would only show that the model is sensitive to any attack-aligned direction. If, instead, the $\hat{w}_d$ nudge leaves behavior on XPIA inputs unchanged while the $\hat{w}_i$ nudge moves it, the effect is axis-specific rather than a generic "perturb along some malicious direction" effect.

Table 18 gives the per-sign results. The table reports only discrete flip metrics, which measure whether greedy generation actually changes. This keeps the steering analysis focused on observable behavior.

The flip metrics support the axis-specific interpretation. Both $+\hat{w}_i$ and $-\hat{w}_i$ change the first generated token more often than the random-direction baseline, with $z = +1.77$ and $z = +2.40$ on flip@1. The $+\hat{w}_d$ control is below the random baseline on flip@1, and $-\hat{w}_d$ is weaker than $-\hat{w}_i$ on the same metric. At the five-token horizon, $-\hat{w}_i$ is the strongest direction.

Larger steering strengths ($\alpha \geq 4$ in the multi-layer setting) push generation into a degenerate regime where outputs are no longer informative, so the appendix reports the small-perturbation regime. Exact large-α sweep values are retained with the steering artifacts.

Backbone	AUC_d	Rec_d	AUC_i	Rec_i	Match_d	Match_i
L2-7B-chat (L30)	0.991	95.8%	0.939	76.2%	100.0%	99.2%
L3.1-8B-Inst. (L28)	0.993	97.1%	0.953	79.4%	100.0%	99.0%
Qwen2.5-7B-Inst. (L24)	0.990	94.9%	0.961	86.5%	99.9%	99.4%
Qwen2-7B-Inst. (L27)	0.988	95.6%	0.968	88.3%	99.8%	99.3%
L2-7B-base (L30)	0.989	95.4%	0.934	77.0%	100.0%	99.3%
L3.1-8B-base (L28)	0.991	96.7%	0.945	78.6%	100.0%	99.0%
Qwen2-7B-base (L27)	0.989	94.8%	0.965	87.4%	100.0%	99.5%
Qwen2.5-7B-base (L24)	0.988	94.7%	0.962	86.8%	100.0%	99.5%
Mistral-v0.1-base (L24)	0.823	38.4%	0.572	33.9%	100.0%	77.1%
Mistral-v0.3-base (L24)	0.847	37.6%	0.604	32.8%	100.0%	80.5%

Table 15: Production-scale run on the full out-of-training corpora. Columns report per-axis AUC, recall under separate per-axis FPR budgets, and single-axis match rate.

Setting	Layer	Transfer AUC	Joint AUC	$\cos(w_d, w_i)$
Last 4 tokens	L16	0.550	0.945	0.238
Last 4 tokens	L20	0.555	0.952	0.177
Last 4 tokens	L24	0.551	0.956	0.180
Last 4 tokens	L28	0.535	0.959	0.140
Last 4 tokens	L30	0.547	0.963	0.121
Last 4 tokens	L32	0.556	0.966	0.117
Last 1 token	L30	0.543	0.970	0.147
Last 8 tokens	L30	0.540	0.964	0.113
Mean pooling	L30	0.525	0.955	0.073

Table 16: Layer and pooling sweep on Llama-2-7B-chat. Setting is the pooling rule over the final hidden-state tokens. Layer is the extracted transformer layer. Transfer AUC is UPIA-only transfer to XPIA. Joint AUC is the combined two-axis AUC. $\cos(w_d, w_i)$ is the cosine between the two fitted axes.

Dataset or evaluation set	Size	Use in the paper
UPIA benchmark out-of-training attacks	80,194 UPIA rows	Production-scale UPIA evaluation
XPIA benchmark	28,263 XPIA rows	XPIA fitting and production-scale evaluation
Primary held-out evaluation	1,000 UPIA + 1,000 XPIA attacks per seed	Main transfer and two-axis tables
Raw-vs.-wrapped control	2,000 matched pairs per backbone	Wrapper-detector control
AgentDojo frozen evaluation	705 attack/benign pairs	External frozen evaluation
BIPIA frozen evaluation	3,200 examples per backbone	External frozen evaluation
Public BIPIA channel swap	3,000 test payloads per backbone	Public-data channel-swap check
CHANNELSWAP-PI release	98,000 paired records	Reusable channel-swap benchmark

Table 17: Dataset and evaluation size summary. Rows report the corpus or evaluation subset, its size, and the role it plays in the paper.

Condition	flip@1	flip@5
Baseline	0.000	0.000
$+\hat{w}_i$	0.135	0.295
$-\hat{w}_i$	0.155	0.365
$+\hat{w}_d$	0.050	0.270
$-\hat{w}_d$	0.115	0.325
Random, $n = 5$	$0.079 \pm .032$	$0.242 \pm .037$
$z(+\hat{w}_i)$	+1.77	+1.43
$z(-\hat{w}_i)$	+2.40	+3.32
$z(+\hat{w}_d)$	-0.92	+0.75
$z(-\hat{w}_d)$	+1.14	+2.24

Table 18: Per-sign activation-level steering of generation, averaged across the eight Llama and Qwen backbones. Condition is the steering direction added to the hidden state at the per-backbone steering layer ($\pm\hat{w}_i$ along the XPIA axis, $\pm\hat{w}_d$ along the UPIA axis, or a random unit vector). flip@1 and flip@5 are the fractions of prompts whose first generated token and first five generated tokens differ from the unsteered baseline. Bottom rows give z-scores against the five-seed random null on each metric.