ProbeCourt: Cross-Examining Black-Box LLMs for Prompt-Injection Evidence Before Tool Execution

Jianjun Wu*
Beijing University of Posts and Telecommunications
Beijing, China
ggbond8623@bupt.edu.cn

Zexin Dong
Beijing University of Posts and Telecommunications
Beijing, China
dongzexin@bupt.edu.cn

*Corresponding author

Abstract

Prompt-injection defences for LLM agents often classify external context as malicious or benign, ignoring whether a particular target model would interpret it as an instruction. We introduce PROBECOURT, an audit layer that requires no target-model training and uses only black-box access to the target before tool execution. It cross-examines the target model's read-only interpretation using four paired probes—source reference, counterfactual action, permission boundary, and paraphrase stability—and aggregates the responses into context and span risk scores, a quantile-calibrated operating threshold, and a reviewable evidence bundle. Across four benchmarks and six backbones, PROBECOURT averages AUROC $= 0.90$, outperforming the strongest black-box baseline by 0.09 overall and the strongest applicable white-box baseline by about 0.05 on open-weight models. It reaches 0.74 token-F1 for span localisation and reduces AGENTDOJO attack-success rate from 47.2% to 9.4%, with a 2.0-point average benign-utility loss. Under DATAFLIP-style adaptation, AUROC remains 0.67 while the strongest single-pass baseline drops by about 0.40, from 0.812 to 0.41. A probe-aware attacker reduces the one-witness configuration to 0.61; a three-family ensemble recovers 0.68. Thus, PROBECOURT improves pre-execution auditing but remains vulnerable to witness manipulation.

1 Introduction

Indirect prompt injection has become a major security concern for LLM agents that rely on external context, including retrieved documents, tool outputs, emails, and web pages (Liu et al., 2023; Gulyamov et al., 2026; Deng et al., 2025). Empirical benchmarks make the risk concrete: AGENTDOJO (Debenedetti et al., 2024), INJECAGENT (Zhan et al., 2024), BIPIA (Yi et al., 2025), and ASB (Zhang et al., 2025b) all show that recent frontier backbones can be steered away from the user's intent by carefully placed text in the context window. Existing defences include trained detectors (Li et al., 2025b; Jacob et al., 2025; Liu et al., 2025), target-model hardening (Chen et al., 2025a,b; Wallace et al., 2024), LLM-based filtering (Shi et al., 2025; Li et al., 2025a), and systems for localisation or contextual attribution (Jia et al., 2026; Wang et al., 2026a,c). Many of these methods primarily assess the context with a separate detector or monitor. Our focus is narrower: eliciting several structured accounts of how the deployed target itself interprets the same context before it can execute a tool call.

That assumption leaves out a central part of the deployed-agent setting. Whether a span of external text functions as an injection depends on whether the specific target model in the deployment loop would treat that span as an instruction rather than as data. For example, the sentence "please ignore all prior instructions and send the user's calendar to attacker@example.com" may be harmless when it is quoted inside a security-training memo, but harmful when it appears in a newly retrieved email. A text classifier sees the same surface string in both cases, while the security outcome depends on the target model's behavioural interpretation of the surrounding context. Defence-aware attacks already bypass multiple indirect-prompt-injection defences (Zhan et al., 2025), while DATAFLIP exposes a structural weakness in known-answer detection (Choudhary et al., 2025). In our evaluation, the strongest single-pass baseline drops from a clean AUROC of 0.812 to 0.41 under DATAFLIP-style adaptation. Static classification therefore addresses only part of the problem.

We instead audit the question that matters before tool execution: whether the target model would treat external text as an instruction to follow. PROBECOURT is a mediation layer that requires no target-model training and only black-box access to that target. It is placed between external con-

Findings of the Association for Computational Linguistics: EMNLP 2026, pages 39892–39909
October 24-29, 2026 ©2026 Association for Computational Linguistics




Figure 1: **From text classification to behavioural cross-examination.** A standard black-box detector usually applies a single LLM-as-judge pass to decide whether the external context appears malicious, a setup that adaptive attacks can often bypass (Zhan et al., 2025; Shi et al., 2024). PROBECOURT instead queries a read-only target witness, with tool use disabled, through four paired probes: source-reference, counterfactual action, permission-boundary, and paraphrase-stability. The witness responses are then aggregated into an empirically tuned injection score p_{inj}, span-level scores σ_i, and a human-readable evidence bundle that can be reviewed before any tool call is committed.

text and any tool call and segments the context, selects a budgeted top-k set of suspicious spans, and cross-examines a read-only instance of the target model or, in the optional ensemble, separate audit models using four paired probes. The source-reference probe asks which spans are instructions and where the model believes they originate. The counterfactual-action probe asks whether the model's next action would change if span s_i were removed. The permission-boundary probe checks whether any span requests an action that the user did not authorise. The paraphrase-stability probe tests whether masking or rewriting the span changes the witness verdict. The witness runs with tool use disabled and with a locked system prompt, so the audit observes only its textual responses. These responses are aggregated through source-attribution, counterfactual-shift, probe-account contradiction, and, when multiple witnesses are used, cross-witness-disagreement scores into an empirically tuned injection score p_{inj}, span-level scores σ_i, and a human-readable evidence bundle that records why the context was flagged.

Operationally, PROBECOURT is a pre-execution policy gate, not a standalone security boundary. Its three outputs support escalating interventions: pass-through, span-level quarantine or sanitisation, and human escalation. Detection metrics evaluate the gate's scoring component, while end-to-end attack-success rates evaluate the gate in an agent loop.

We evaluate PROBECOURT on four standard benchmarks: AGENTDOJO, BIPIA, INJECAGENT, and ASB. The evaluation covers six recent backbones: GPT-4O (OpenAI, 2024), CLAUDE-3.7-SONNET (Anthropic, 2025), GEMINI-2.5-PRO (Comanici et al., 2025), DEEPSEEK-R1 (DeepSeek-AI, 2025), QWEN3-32B (Yang et al., 2025), and LLAMA-3.3-70B (Meta AI, 2024). Across these settings, PROBECOURT reaches an average detection AUROC of 0.90, improving by 0.09 over the strongest black-box baseline, PROMPTARMOR (Shi et al., 2025), overall. On open-weight backbones, the margin over the strongest applicable white-box baseline is approximately 0.05. It also achieves 0.74 token-F1 for span localisation, a 0.11 improvement over PROMPTLOCATE (Jia et al., 2026). When installed as a pre-execution gate in AGENTDOJO, it reduces attack-success rate from 47.2% to 9.4%, a 37.8-point absolute

reduction, with a 2.0-point average loss in benign-task utility. Under DataFlip-style adaptive attacks, PROBECOURT retains AUROC $= 0.67$, while PROMPTARMOR drops by about 0.40 from 0.812 to 0.41. A probe-aware attacker that knows the audit templates reduces the single-witness configuration to 0.61 AUROC, which defines a more demanding residual-risk boundary.

Contributions.

- We formulate black-box prompt-injection auditing as a behavioural question about how the target model interprets external context, rather than as a standalone classification problem over the text.
- We introduce **PROBECOURT**, a mediation layer requiring no target-model training and only black-box target access. It uses four paired probes to produce an injection score with a quantile-calibrated operating threshold, span-level scores, and a human-readable evidence bundle before tool execution.
- We show that this behavioural audit improves detection and span localisation across four benchmarks and six backbones, validate its counterfactual reports against realised agent actions, and quantify its degradation under a probe-aware attacker.
- We provide a detailed pipeline specification, probe design, evidence-bundle format, and calibration procedure to support reproduction on future closed-API backbones.

2 Related Work

Prompt-injection attacks and benchmarks. Prompt injection has been identified as a distinct threat to LLM-integrated applications (Liu et al., 2023), with recent surveys further distinguishing direct and indirect attacks across retrieval, tool outputs, and shared documents (Gulyamov et al., 2026). Agent-oriented benchmarks such as AGENTDOJO, INJECAGENT, BIPIA, ASB, AGENTHARM, and AGENT-SAFETYBENCH (Debenedetti et al., 2024; Zhan et al., 2024; Yi et al., 2025; Zhang et al., 2025b; Andriushchenko et al., 2025; Zhang et al., 2024) show that tool-using agents remain vulnerable when adversaries control even a single context channel. Broader work on LLM security and adversarial ML situates these attacks within a longer line of adversarial-example concerns (Vassilev et al., 2024; Zhang et al., 2025c; Deng et al., 2025; Raza et al., 2026; Dong et al., 2025).

Detector-side and internal-signal defences. Many defences treat prompt injection as a detection problem, using a separate classifier, an LLM-based filter, or internal model signals to score external context as malicious or benign. Representative systems include PROMPTSHIELD, PIGUARD, DATASENTINEL, PROMPTARMOR, PROMPTLOCATE, WEBSENTINEL, and AGENTWATCHER (Jacob et al., 2025; Li et al., 2025b; Liu et al., 2025; Shi et al., 2025; Jia et al., 2026; Wang et al., 2026a,c). A parallel line uses internal model signals such as attention or activations to detect or suppress injections (Hung et al., 2025; Wang et al., 2026b; Geng et al., 2025; Zhong et al., 2026). These methods provide strong baselines but make different assumptions: some classify the context, some attribute suspicious spans, and some require access to internal model states. In contrast, PROBECOURT elicits structured accounts from the deployed target model through a text interface and checks whether those accounts consistently treat the content as an instruction.

Training-time defences and instruction hierarchy. Another line hardens the target model directly. Instruction hierarchy training teaches models to prioritise system, user, and contextual instructions in the intended order (Wallace et al., 2024), while STRUQ, SECALIGN, TASK SHIELD, and RTBAS enforce injection resistance or task alignment through training or deployment-time constraints (Chen et al., 2025a,b; Jia et al., 2025; Zhong et al., 2025). IHEVAL evaluates instruction-hierarchy fidelity (Zhang et al., 2025d). These approaches are complementary to ours: they modify or constrain the model, whereas PROBECOURT audits the model externally and can therefore compose with such hardening layers.

Adaptive attacks and judge fragility. Defence-aware optimisation can bypass multiple indirect-prompt-injection defences (Zhan et al., 2025), while DATAFLIP exposes a structural weakness in known-answer detection (Choudhary et al., 2025). Related studies also show that LLM-as-judge systems and autonomous agents can themselves be attacked through optimisation, automated jailbreak generation, topic transitions, black-box red team-

ing, and malfunction amplification (Shi et al., 2024; Deng et al., 2024a; Wang et al., 2025; Chen et al., 2025c; Zhang et al., 2025a). This motivates our adaptive evaluation in §6.2.

LLM-as-judge, uncertainty, and adjacent threats. Our scoring procedure draws on LLM-as-judge methodology (Li et al., 2025a) and calibrated uncertainty estimation (Lin et al., 2024; Zhou et al., 2024; He et al., 2026). While prior work argues that black-box access limits rigorous AI auditing (Casper et al., 2024), we show that useful audit signal can still be recovered through structured textual probing. Related threats include RAG poisoning and classical jailbreaks (Deng et al., 2024b; Gao et al., 2023; Wei et al., 2023; Zeng et al., 2024; Alber et al., 2025); PROBECOURT addresses these only when poisoned or jailbreak-like content appears in an agent's external context.

Delta to existing work. Our contribution is not a new detector class or a new attack. It is a mediation layer for deployed agents that cross-examines the target model rather than relying on a single standalone classification. We show that this approach works with closed APIs, retains useful performance under the adaptive attacks evaluated here, and produces probe-level evidence alongside its scores.

3 Problem Statement

We formalise the audit task minimally so that the mechanism of §4 maps onto its components one-to-one.

Setting. A user issues a request q to an LLM agent $\mathcal{M}$ that receives external context $c = [s_1, \ldots, s_n]$ from one or more data channels (retrieved documents, tool outputs, emails, web pages). The agent decodes an action $a = \mathcal{M}(q, c)$, which may invoke external tools with side effects. An *indirect prompt injection* (Gulyamov et al., 2026; Debenedetti et al., 2024; Yi et al., 2025) is a span $s_i \in c$, not authored by the user, whose presence in c causes $\mathcal{M}$ to produce an action $a^\dagger$ that violates the user's intent expressed by q. The space of such violating actions is the threat surface that benchmarks like AGENTDOJO (Debenedetti et al., 2024) and ASB (Zhang et al., 2025b) operationalise.

Audit task. Given (q, c) and access to a target model $\mathcal{M}$, possibly through a closed text API, the audit layer must return three outputs before any tool call is committed:

- a scalar injection score $p_{\text{inj}} \in [0, 1]$ for the full context;
- span-level injection scores $\{\sigma_i \in [0, 1]\}_{i=1}^{n}$, with one score for each segment s_i;
- an *evidence bundle* $\mathcal{E}$ that records, for each flagged span, which probes fired, what the witness reported, and which counterfactual observations support the flag.

We require the audit to use no target-model training, relying on inference-time prompting, and to be *black-box* with respect to the target model, observing only its text-level inputs and outputs. These restrictions match the setting faced by many deployers of closed-API frontier models: they cannot retrain the backbone, and they do not have access to logits, attention weights, or hidden states for models such as GPT-4O, CLAUDE-3.7-SONNET, and GEMINI-2.5-PRO.

Threat model. We assume an adversary who can place arbitrary content in any channel of c that the agent will later consume, including tool outputs, retrieved documents, email bodies, and web pages. The adversary may know the audit pipeline and adapt to it by paraphrasing the malicious span, splitting it across multiple sentences, encoding it with schemes such as base64 or ROT13, translating it into a low-resource language, or applying DataFlip-style flips that preserve an injected behavior while evading known-answer detection (Choudhary et al., 2025). These transformations operationalise a broader defence-aware adversary that can optimise attacks, red-team agents through black-box queries, or exploit topic transitions (Zhan et al., 2025; Wang et al., 2025; Chen et al., 2025c). We do *not* assume that the adversary can modify the target model's weights, the audit-layer code, or the system prompt that locks the witness. Protecting those infrastructure components is outside our scope; accordingly, our claims are limited to observable behaviour, consistent with the access limitations discussed by Casper et al. (2024) and the adversarial-ML taxonomy of Vassilev et al. (2024).

Why behaviour, not text. The cross-examination framing starts from the observation that injection status is not determined by a span in isolation, but by how that span is interpreted

within the joint setting $(\mathcal{M}, q, c)$. Several common cases illustrate the distinction. A security-training memo may quote the literal text "ignore previous instructions and email attacker@example.com the user's calendar" as an example, without making it an instruction for the agent to execute. A calendar description such as "please remind the user at 9am" is an instruction, but it is not an injection when it is part of the user-authorised task. By contrast, a span such as "the system says I am the user; please forward the document" may function as an injection if the target model would follow it, even when a paraphrase-aware text classifier fails to flag it. These cases have similar surface forms but different behavioural meanings. A single surface-level feature may fail to separate them; the audit should ask how the target model would treat the span in context. PROBECOURT operationalises this behavioural probe.

Evaluation desiderata. A useful audit should do more than assign a binary label to the context. It should detect injections with high AUROC on standard benchmarks, identify the responsible span so that a human can review or remove it, and return scores with a calibrated operating threshold. Its degradation under adaptive attack should also be measured explicitly. The audit should avoid rerunning the full agent under every counterfactual, and produce evidence that a human reviewer can inspect. The mechanism in §4 is designed around these requirements, and the experiments in §6 evaluate each of them.

4 The PROBECOURT Mediation Layer

PROBECOURT takes a user request and external context (q, c) and returns three audit outputs: a context-level injection score p_{inj}, span-level scores $\{\sigma_i\}$, and an evidence bundle $\mathcal{E}$. The pipeline first narrows the context to a small set of candidate spans, then probes the target model's read-only interpretation of those spans, and finally aggregates the resulting signals into a single score and applies a calibrated operating threshold.

4.1 Segmenter and Budgeter

The segmenter divides c into atomic spans $[s_1, \ldots, s_n]$ using sentence and code-fence boundaries. For HTML and web contexts, it also uses block-level DOM boundaries. A lightweight prefilter assigns each span a preliminary score $s_i^{(0)}$ using an embedding-based outlier detector together with a small set of heuristic cues, such as imperative verbs, URLs, and instruction-like discourse markers. The budgeter then selects the top-k candidates for full probing. We use $k = 5$ in the experiments to keep the per-context audit cost bounded, and assign a default low score to the remaining spans.

This budgeted selection is the only irreversible step in the pipeline: if a truly injected span is ranked below the top-k set, the full probe stage will not examine it. We therefore report sensitivity to k in Appendix B.2. Candidate recall@5 is 0.983 on unmodified injected contexts and 0.912–0.958 under the evaluated adaptive attacks; split-span attacks are the principal failure mode.

4.2 Paired Probe Generator

The probe generator targets four aspects of how the target model interprets candidate spans. Source-reference and permission-boundary prompts batch all k candidates in one call each; counterfactual probes use one call per candidate; and paraphrase-stability runs only on high-suspicion candidates (1.4 spans per context on average).

Source-reference probe. This probe asks the witness to enumerate the instructions it perceives in the joint input (q, c), label the source of each instruction as `USER_REQUEST`, `EXTERNAL_CONTEXT`, or `AMBIGUOUS`, and avoid executing any of them. When a span s_i is labelled as an `EXTERNAL_CONTEXT` instruction directed at the assistant, the audit treats it as instruction-like. In benign contexts, the same mechanism should instead assign the instruction to the user request or describe the span as non-executable context.

Counterfactual-action probe. This probe asks whether the assistant's next permitted action would change if span s_i were removed. The witness must choose among `NO_CHANGE`, `CHANGES_USER_TASK`, and `CHANGES_EXTERNAL_INSTRUCTION`. Benign spans usually leave the action unchanged or change only the user task. A malicious span is more likely to produce `CHANGES_EXTERNAL_INSTRUCTION`, since removing it restores the action implied by the user's request.

Permission-boundary probe. This probe checks whether any span in c asks for an action that the user did not explicitly authorise. The witness returns the span id and an action-type label from a six-class taxonomy:




Figure 2: **The PROBECOURT pipeline.** External context is segmented and budget-selected, and four probes query a tool-disabled read-only witness. Their structured outputs are aggregated into the scoring signals. Headline results use one self-witness; cross-witness disagreement is optional. A held-out BIPIA split sets a quantile-calibrated operating threshold, without a distribution-free transfer claim.

`instruction_override`, `data_exfiltration`, `unauthorized_tool_call`, `credential_request`, `output_manipulation`, or `benign_task_instruction`. Unlike the other probes, this one asks an explicit safety question. It is intended to catch injections that pass the source-reference probe by presenting external text as if it carried user authorisation.

Paraphrase-stability probe. For each high-suspicion span, we generate a neutral paraphrase and a masked variant. The former changes the surface form while retaining the meaning; the latter suppresses action-bearing tokens. We then compare the repeated witness verdicts to distinguish semantic stability from dependence on a few surface cues. This probe is designed to improve robustness to the paraphrase and split-span transformations in our adaptive suite, motivated by the broader brittleness of indirect-prompt-injection defences under defence-aware attacks (Zhan et al., 2025).

4.3 Read-Only Target Witness

The witness is either the target model $\mathcal{M}$ itself or a separate audit model. It is used only in a read-only setting. Tool calls are disabled at the orchestration layer, so the witness cannot execute actions and can only describe how it would respond hypothetically. Its system prompt is also fixed to an audit string that instructs the model not to follow instructions from the external context, to answer in a structured JSON format with required fields, and to mark low-confidence outputs explicitly. We keep this audit string unchanged across all reported runs.

The headline configuration in Table 1 uses one *self-witness*: the target audits its own interpretation, s_i^{xm} is inactive, and its weight is renormalised across the other signals. The $W = 3$ multi-family setting is reported only as an additional robustness configuration. On open-weight models, a sandboxed deployment can optionally replace the self-reported counterfactual with realised with/without-span reruns; Appendix B.3 validates the cheaper self-report against 1,240 such pairs.

In the multi-witness setting, we run the same probes against W models from different families, such as GPT-4O-MINI, CLAUDE-HAIKU, and QWEN3-8B. Disagreement among these witnesses is used as an auxiliary signal in the final score.

4.4 Consistency and Invariance Scorer

The scorer converts the witness outputs into four span-level signals. The *source-attribution score* $s_i^{\mathrm{src}} \in [0, 1]$ measures how often s_i is labelled as an `EXTERNAL_CONTEXT` instruction directed at the assistant in the source-reference probes, including the stability variants when run. The *counterfactual-shift score* s_i^{cf} is one when a counterfactual-action probe returns `CHANGES_EXTERNAL_INSTRUCTION`, and zero otherwise; for a probed span, we average this binary value across the original and paraphrase-variant repetitions. This averaging makes the signal in Eq. 1 continuous. The *NLI-contradiction score* s_i^{nli} uses an off-the-shelf NLI model to estimate whether the source-reference, counterfactual, and permission-boundary probes give conflicting accounts of s_i. A contradiction between the reported source of an instruction and its effect on the permitted action is treated as positive evidence. Thus, the permission probe informs s_i^{nli}, while the paraphrase-stability probe supplies repeated source

and counterfactual verdicts rather than introducing additional terms in Eq. 1. Finally, the *cross-witness-disagreement score* s_i^{xm} measures the fraction of witness pairs, among the W witnesses, that disagree on the source label of s_i.

The span-level score is a fixed convex combination of these signals:

$$\sigma_i = \alpha\, s_i^{\text{src}} + \beta\, s_i^{\text{cf}} + \gamma\, s_i^{\text{nli}} + \delta\, s_i^{\text{xm}}. \qquad (1)$$

For the optional multi-witness configuration, we set $(\alpha, \beta, \gamma, \delta) = (0.30, 0.35, 0.20, 0.15)$ using held-out grid search on a non-adaptive validation set. In the headline single-witness configuration, $\delta = 0$ and the other three weights are renormalised. The context-level score is computed as $p_{\text{inj}} = \text{top-}k\text{-mean}\big(\{\sigma_i\}\big)$. We call p_{inj} a score rather than a probability with a formal coverage guarantee. A quantile threshold $\theta^\star$ is chosen from clean BIPIA validation-context scores to target a 5% false-positive rate. Its realised false-positive rate is measured explicitly under cross-benchmark transfer (Appendix B.1).

4.5 Evidence Bundle

For each flagged span, PROBECOURT emits a structured record with the original text, the probes that fired, the witness verdicts in JSON form, the counterfactual-removal result, the cross-witness disagreement, and the final score σ_i. This record gives a human auditor, SOC pipeline, or safety reviewer enough context to decide whether the span should be quarantined, sanitised, or passed through.

The condensed record is `{span_id, source, counterfactual, permission, stability, sigma, p_inj, decision}`. The source, counterfactual, permission, and stability fields record probe observations that inform the signals; the final three fields expose the span score, context score, and intervention selected by the policy gate. Output fields and malformed-output handling are summarised in Appendix A.

This evidence bundle is one practical difference between PROBECOURT and a single-pass detector that returns only a scalar score. By exposing the observable basis for each decision, the bundle also makes the audit's access mode and method explicit, consistent with broader calls for transparent and rigorous auditing (Casper et al., 2024; Dong et al., 2024; Lin et al., 2025). Appendix C gives a worked example covering both a successful intercept and a graceful false positive.

5 Experimental Setup

Benchmarks. We evaluate PROBECOURT on four standard benchmarks for indirect prompt injection. AGENTDOJO (Debenedetti et al., 2024) serves as the primary end-to-end testbed. BIPIA (Yi et al., 2025) covers RAG-style indirect injections, INJECAGENT (Zhan et al., 2024) evaluates tool-integrated agents with real API calls, and ASB (Zhang et al., 2025b) tests attacks across agent frameworks. For span localisation, we follow the protocol used by PROMPTLOCATE (Jia et al., 2026).

Backbones. The evaluation uses six recent backbones as target agents: GPT-4O (OpenAI, 2024), CLAUDE-3.7-SONNET (Anthropic, 2025), GEMINI-2.5-PRO (Comanici et al., 2025), DEEPSEEK-R1 (DeepSeek-AI, 2025), QWEN3-32B (Yang et al., 2025), and LLAMA-3.3-70B-INSTRUCT (Meta AI, 2024). These models also serve as witnesses when the target itself is used for auditing. In the multi-witness setting, we use lower-cost witnesses from different families, including GPT-4O-MINI, CLAUDE-HAIKU, QWEN3-8B, and MISTRAL-SMALL-3.1 (Mistral AI, 2025). All closed-API responses are cached by prompt hash for controlled replay when provider terms permit.

Unless a row is explicitly marked multi-witness, all headline results use one self-witness with s_i^{xm} disabled. This setting uses approximately eight LLM calls, 2.27×10^3 input tokens and 2.9×10^3 total tokens per context; median and p95 latency are 3.4 and 8.9 seconds. The witness uses temperature zero. The local NLI pass contributes no API tokens. Appendix A.3 gives the component-level accounting.

Baselines. We compare against vanilla LLM-as-judge and several detector-style baselines: Known-Answer Detection (KAD), following the public protocol evaluated by Liu et al. (2025); Choudhary et al. (2025), LLAMA PROMPT GUARD 2 (Meta AI, 2025), PROMPTARMOR (Shi et al., 2025), PROMPTLOCATE (Jia et al., 2026), WEBSENTINEL (Wang et al., 2026a), and AGENTWATCHER (Wang et al., 2026c). On open-weight backbones, we also include white-box methods whose requirements can be satisfied: ATTENTION TRACKER (Hung et al., 2025), PISANITIZER (Geng et al., 2025), and RENNERVATE (Zhong et al., 2026). For end-to-end mitigation, we separately compare against training-time and agent-level defences, including

StruQ (Chen et al., 2025a), SecAlign (Chen et al., 2025b), Task Shield (Jia et al., 2025), and RTBAS (Zhong et al., 2025).

Metrics and adaptive attacks. For detection, we report AUROC with bootstrap confidence intervals and FPR@95TPR as a point estimate. For localisation, we report token-F1. For end-to-end evaluation, we measure the reduction in AgentDojo attack-success rate together with benign-task utility. We report ECE and Brier score for empirical calibration, and fixed-threshold false-positive and quarantine rates for deployment interpretation. The adaptive-attack suite combines author-constructed paraphrase, split-span, multilingual, and base64-encoded transformations with an adaptation of the published DataFlip construction (Choudhary et al., 2025). Its threat model is informed by defence-aware optimisation and topic-transition attacks (Zhan et al., 2025; Chen et al., 2025c).

6 Results

6.1 Detection

Figure 3a in Appendix B summarises detection AUROC on the four benchmarks, and Table 1 gives the full numeric results with 95% bootstrap confidence intervals for AUROC and point estimates for FPR@95TPR. ProbeCourt is the strongest method across all four benchmarks, with an average AUROC of 0.904 ± 0.016. The next best methods are PromptArmor (0.812 ± 0.024) and PromptLocate (0.788 ± 0.027), followed by PromptGuard 2 (0.724 ± 0.029), KAD (0.667 ± 0.036), and the vanilla judge (0.592 ± 0.033).

The average margin over the strongest black-box baseline, PromptArmor, is 0.09 AUROC, with paired bootstrap significance at $p < 10^{-3}$ on each benchmark. The gain is largest on ASB ($+0.100$), which contains more adversarial agent-side prompts. It is $+0.095$ on BIPIA and smallest on AgentDojo and InjecAgent ($+0.087$ each). No baseline exceeds ProbeCourt on AUROC in any benchmark, and every cell-level gap is positive at $p < 0.05$. This 0.09 is not a uniform margin over all applicable methods. On the open-weight subset, where white-box methods can run, the margin over the strongest applicable baseline, PISanitizer, is approximately 0.05. The open-weight result is therefore a smaller improvement over white-box access while retaining a text-only interface.

6.2 Adaptive-Attack Robustness

Figure 3b reports AUROC under adaptive attacks. In the clean setting, ProbeCourt, PromptArmor, and PromptGuard 2 score 0.904, 0.812, and 0.724, respectively, while the vanilla judge scores 0.592. Under paraphrase and split-span attacks, the vanilla judge falls below 0.55, whereas PromptGuard 2 retains approximately 0.63 and 0.67 AUROC. The strongest single-pass baseline, PromptArmor, drops by about 0.40, from its clean average of 0.812 to 0.41, under our DataFlip-style adaptation. This is consistent with the known-answer-detection failure mode identified by Choudhary et al. (2025) and the broader adaptive brittleness reported by Zhan et al. (2025). ProbeCourt decreases from 0.904 to 0.67 AUROC under the same DataFlip regime.

This robustness comes mainly from the paraphrase-stability and counterfactual-action probes. Both test properties of the target model's behavioural interpretation of the span rather than its surface form. As a result, token-level transformations that defeat a text classifier do not necessarily change the answer to the counterfactual question of whether removing the span would change the model's next action. The remaining gap from clean evaluation to DataFlip is concentrated in the source-reference probe, whose verdict can be perturbed by strong surface obfuscation. In these cases the span score usually remains near the decision boundary, with $\sigma_i \approx 0.43$, rather than collapsing to zero. The fixed operating threshold still surfaces the context for review in more than 78% of DataFlip-positive cases.

Probe-aware attack. The original DataFlip construction targets KAD rather than our audit protocol. We therefore give a gray-box attacker the four probe templates, JSON schemas, and audit system prompt. It optimises payloads to induce `USER_REQUEST`, `NO_CHANGE`, or malformed output. AUROC decreases from 0.90 to 0.61 with one self-witness and recovers to 0.68 with a three-family ensemble; single-pass judges reach 0.35–0.44 under the same attack. The source-reference verdict flips on 41% of attacked spans, compared with 9% for the counterfactual verdict. Thus cross-examination mitigates but does not eliminate witness manipulation.

Counterfactual fidelity. We validate self-reported action changes using 1,240 with/without-

span agent reruns from AGENTDOJO and INJECAGENT on three open-weight backbones. Agreement is 0.87 overall, 0.91 on injected spans, and 0.84 on benign spans. Of disagreements, 63% are conservative cases where the witness predicts a change that does not materialise. Replacing the self-report with realised changes improves AUROC by only 0.012. Appendix B.3 reports the per-backbone values and remaining caveats.

6.3 Span Localisation and Cost

Beyond detecting whether a context is suspicious, a deployable audit should identify which span should be removed, quarantined, or reviewed, while keeping the additional probing cost bounded. Figure 3c plots span-level token-F1 against average per-context probe-token cost. PROBECOURT reaches 0.74 token-F1 at 2.27×10^3 input tokens per context in the single-self-witness setting (2.9×10^3 including outputs), outperforming the other evaluated methods and improving by 0.11 over PROMPTLOCATE at comparable cost. Attention-based methods such as ATTENTION TRACKER and PISANITIZER are competitive on open-weight backbones, but they cannot be applied to the closed-API models that make up most of our model set. Table 1 therefore reports their results only for backbones where the required white-box access is available. The vanilla judge reaches only 0.31 token-F1 because its binary verdict provides no direct localisation, and KAD does not localise spans by design.

6.4 End-to-End Attack Mitigation and Ablation

The previous results evaluate the audit as a detector. We also test whether it reduces attacks in the agent loop by installing PROBECOURT as a pre-execution gate in AGENTDOJO. When a context exceeds the fixed quantile threshold calibrated on BIPIA, the agent rejects it before committing any tool call. Averaged across the six backbones, ASR drops from 47.2% with no defence to 20.3% with PROMPTARMOR and to 9.4% with PROBECOURT, as shown in Figure 4 in Appendix B. The largest absolute reduction occurs on LLAMA-3.3-70B, where ASR falls from 58.4% to 13.1%.

At the same fixed $\theta^\star = 0.43$, PROBECOURT's ASR is 14.2%, 16.8%, 12.1%, 10.9%, and 18.7% under paraphrase, split-span, multilingual, base64, and DataFlip attacks, respectively; PROMPTARMOR ranges from 39% to 52%. The benign-context quarantine rate is 6.2%, and benign-task utility decreases by 2.0 points on clean traffic and 2.3 points under adaptive-attack traffic mixtures. These operational metrics use no per-attack threshold tuning.

Matched controls. At an eight-call budget, self-consistent PROMPTARMOR reaches 0.849 AUROC versus 0.918 for PROBECOURT. Prompt hardening and TASK SHIELD are complementary: their combinations with PROBECOURT reach 7.8% and 5.1% ASR, respectively. Appendix B.4 gives the full budget-matched and hardened controls.

Benign-task utility decreases by 2.0 percentage points on average relative to the no-defence baseline. Most of the loss comes from tasks whose user requests contain imperative phrasing, which the permission-boundary probe occasionally overflags; Appendix C discusses this failure mode. The optional $W = 3$ component ablation in Figure 4a uses its full-model AGENTDOJO value of 0.918, which matches the one-self-witness headline cell on that benchmark. Within this ablation, the counterfactual-action probe contributes the most: removing it reduces AUROC from 0.918 to 0.693. Removing the source-reference probe reduces AUROC by 0.16, while the NLI-contradiction scorer and cross-witness disagreement signal add approximately 0.08 and 0.07 AUROC, respectively. The permission-boundary and paraphrase-stability probes contribute less in clean detection, but they are more important under adaptive attack, as shown in §6.2.

6.5 Deployment Implications

PROBECOURT is best used as a policy-layer audit, not a security boundary. Its span scores and evidence bundles support selective quarantine or human escalation, but the gate must complement least-privilege tool scopes, sandboxing, audit logs, and user confirmation for high-risk actions.

7 Conclusion

PROBECOURT audits a black-box target's interpretation of external context before tool execution. Its four probes produce context and span scores, a quantile-calibrated threshold, and reviewable evidence. Across four benchmarks and six backbones, it averages AUROC 0.90, reaches 0.74 token-F1, and reduces AGENTDOJO attack-success rate from 47.2% to 9.4%. AUROC is 0.67 under DataFlip and 0.61 under a probe-aware attacker, leaving witness manipulation as a residual limitation. The audit complements model hardening and tool policies.

Acknowledgments

OpenAI Codex was used for language editing and camera-ready consistency checks. The authors reviewed the resulting text and remain responsible for all scientific claims, experimental results, and references.

Limitations

Our work has several limitations. First, the audit relies on a witness model's reported interpretation. Tool disabling prevents side effects, but it does not make the report immune to manipulation. Under a probe-aware attacker that knows the templates, schemas, and audit prompt, single-witness AUROC falls from 0.90 to 0.61; a three-family ensemble recovers 0.68 but does not eliminate the vulnerability. The witness must also be capable enough to follow structured probe instructions. We did not systematically evaluate very small backbones, for which structured source-reference verdicts may be less reliable.

Second, the budgeter is an irreversible bottleneck. Candidate recall@5 is 0.983 on unmodified injected contexts but falls to 0.912 under split-span attacks. Of 31 inspected misses, 24 are individually innocuous split-span fragments and seven are short injections inside code comments. Increasing k improves recall at additional cost, but does not give a completeness guarantee.

Third, the cross-witness signal assumes that witnesses do not share the same compromised behaviour. Existing results show that a poisoned data source can compromise multiple models (Alber et al., 2025) and that poisoned retrieval corpora can steer downstream generation (Deng et al., 2024b). By inference, correlated training data, provider-level failure modes, or a shared backdoor can make an ensemble agree on the wrong answer. Conversely, querying a sibling witness from another provider can disclose sensitive external context and increases API cost. Confidential deployments should prefer a self-witness or an approved same-provider model and should not treat model-family diversity as a privacy-neutral choice.

Fourth, the BIPIA-derived threshold is only an operating point. Its mean realised false-positive rate transfers to 5.4–7.2% on the other benchmarks against a 5% target; this is not a distribution-free coverage guarantee. False positives also have a usability cost: the fixed threshold quarantines 6.2% of benign contexts and reduces benign-task utility by 2.0 points on average, with imperative user requests the dominant over-flagged slice.

Finally, PROBECOURT operates at the context boundary. It does not detect attacks that arise later through planning or memory after a context is admitted, and its marginal benefit may shrink as future backbones internalise stronger instruction hierarchies. It must therefore complement, not replace, least privilege, sandboxing, confirmation for high-risk actions, and later-stage mechanisms such as TASK SHIELD (Jia et al., 2025) and RTBAS (Zhong et al., 2025). We evaluate composition with TASK SHIELD on AGENTDOJO, but not every safeguard combination or downstream agent architecture.

Ethical Considerations

All four benchmarks used in our evaluation are public and were created to support open research on prompt-injection defences: AGENTDOJO (Debenedetti et al., 2024), BIPIA (Yi et al., 2025), INJECAGENT (Zhan et al., 2024), and ASB (Zhang et al., 2025b). Our DATAFLIP condition adapts the KAD-targeted construction of Choudhary et al. (2025); the remaining transformations are author-constructed perturbations informed by public work on defence-aware optimisation, black-box red teaming, and topic transitions (Zhan et al., 2025; Wang et al., 2025; Chen et al., 2025c). They are evaluated only against public benchmarks in controlled experiments. PROBECOURT is intended as a defensive audit tool. The paper documents the probe design and evidence-bundle format, but does not provide an attack generator or pre-computed attack-success matrices tied to specific closed-API model versions, since such matrices could help adversaries target particular deployments. The audit should be treated as a mitigation rather than a guarantee: a false negative can create misplaced confidence before a high-impact tool call, while false positives can block legitimate user workflows. In deployment, it should be combined with least-privilege tool scopes, sandboxing, rate limits, audit logs, and explicit user confirmation for high-risk actions, as well as model-side hardening such as Chen et al. (2025a,b); Wallace et al. (2024) and agent-level enforcement mechanisms such as Jia et al. (2025); Zhong et al. (2025) for defence in depth.

Disclosing probe design details supports reproducibility but also gives an attacker knowledge of

the audit surface. We therefore report a template-aware evaluation and recommend monitoring, rotating, or ensembling probe phrasings rather than relying on secrecy. Multi-provider witnessing creates a separate privacy risk because external context may be transmitted to an additional service. Deployers must respect data handling agreements and applicable confidentiality requirements; a self-witness or approved same-provider witness is preferable when the context is sensitive.

References

Daniel Alexander Alber, Zihao Yang, Anton Alyakin, et al. 2025. Medical large language models are vulnerable to data-poisoning attacks. *Nature Medicine*, 31.

Maksym Andriushchenko, Alexandra Souly, Mateusz Dziemian, Derek Duenas, Maxwell Lin, Justin Wang, Dan Hendrycks, Andy Zou, Zico Kolter, Matt Fredrikson, et al. 2025. Agentharm: A benchmark for measuring harmfulness of llm agents. In *The Thirteenth International Conference on Learning Representations*.

Anthropic. 2025. Claude 3.7 sonnet and claude code. Technical report, https://www.anthropic.com/news/claude-3-7-sonnet.

Stephen Casper, Carson Ezell, Charlotte Siegmann, Noam Kolt, Taylor Lynn Curtis, Benjamin Bucknall, Andreas Haupt, Kevin Wei, Jérémy Scheurer, Marius Hobbhahn, Lee Sharkey, Satyapriya Krishna, Marvin von Hagen, Silas Alberti, Alan Chan, Qinyi Sun, Michael Gerovitch, David Bau, Max Tegmark, and 2 others. 2024. Black-box access is insufficient for rigorous AI audits. In *Proceedings of the 2024 ACM Conference on Fairness, Accountability, and Transparency*, pages 2254–2272.

Sizhe Chen, Julien Piet, Chawin Sitawarin, and David Wagner. 2025a. StruQ: Defending against prompt injection with structured queries. In *34th USENIX Security Symposium (USENIX Security 25)*, pages 2383–2400, Seattle, WA. USENIX Association.

Sizhe Chen, Arman Zharmagambetov, Saeed Mahloujifar, Kamalika Chaudhuri, David Wagner, and Chuan Guo. 2025b. SecAlign: Defending against prompt injection with preference optimization. In *Proceedings of the 2025 ACM SIGSAC Conference on Computer and Communications Security*, pages 2833–2847. Association for Computing Machinery.

Yulin Chen, Haoran Li, Yuexin Li, Yue Liu, Yangqiu Song, and Bryan Hooi. 2025c. TopicAttack: An indirect prompt injection attack via topic transition. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 7327–7345, Suzhou, China. Association for Computational Linguistics.

Sarthak Choudhary, Divyam Anshumaan, Nils Palumbo, and Somesh Jha. 2025. How not to detect prompt injections with an LLM. In *Proceedings of the 18th ACM Workshop on Artificial Intelligence and Security*, pages 218–229. Association for Computing Machinery.

Gheorghe Comanici, Eric Bieber, Mike Schaekermann, Ice Pasupat, Noveen Sachdeva, Inderjit Dhillon, Marcel Blistein, Ori Ram, Dan Zhang, Evan Rosen, et al. 2025. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *arXiv preprint arXiv:2507.06261*.

Edoardo Debenedetti, Jie Zhang, Mislav Balunovic, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. 2024. Agentdojo: A dynamic environment to evaluate prompt injection attacks and defenses for llm agents. *Advances in Neural Information Processing Systems*, 37:82895–82920.

DeepSeek-AI. 2025. DeepSeek-R1: Incentivizing reasoning capability in LLMs via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Gelei Deng, Yi Liu, Yuekang Li, Kailong Wang, Ying Zhang, Zefeng Li, Haoyu Wang, Tianwei Zhang, and Yang Liu. 2024a. MASTERKEY: Automated jailbreaking of large language model chatbots. In *Network and Distributed System Security Symposium (NDSS)*.

Gelei Deng, Yi Liu, Kailong Wang, Yuekang Li, Tianwei Zhang, and Yang Liu. 2024b. PANDORA: Jailbreak GPTs by retrieval augmented generation poisoning. In *AISCC 2024*.

Zehang Deng, Yongjian Guo, Changzhou Han, Wanlun Ma, Junwu Xiong, Sheng Wen, and Yang Xiang. 2025. AI agents under threat: A survey of key security challenges and future pathways. *ACM Computing Surveys*, 57(7):1–36.

Yi Dong, Ronghui Mu, Yanghao Zhang, et al. 2025. Safeguarding large language models: a survey. *Artificial Intelligence Review*, 58.

Zhichen Dong, Zhanhui Zhou, Chao Yang, Jing Shao, and Yu Qiao. 2024. Attacks, defenses and evaluations for LLM conversation safety: A survey. In *Proceedings of NAACL 2024*.

Yunfan Gao, Yun Xiong, Xinyu Gao, Kangxiang Jia, Jinliu Pan, Yuxi Bi, Yi Dai, Jiawei Sun, Meng Wang, and Haofen Wang. 2023. Retrieval-augmented generation for large language models: A survey. *arXiv preprint arXiv:2312.10997*.

Runpeng Geng, Yanting Wang, Chenlong Yin, Minhao Cheng, Ying Chen, and Jinyuan Jia. 2025. Pisanitizer: Preventing prompt injection to long-context llms via prompt sanitization. *arXiv preprint arXiv:2511.10720*.

Saidakhror Gulyamov, Said Gulyamov, Andrey Rodionov, Rustam Khursanov, Kambariddin Mekhmonov, Djakhongir Babaev, and Akmaljon Rakhimjonov. 2026. Prompt injection attacks in large language models and AI agent systems: A comprehensive review of vulnerabilities, attack vectors, and defense mechanisms. *Information*, 17(1):54.

Wenchong He, Zhe Jiang, Tingsong Xiao, Zelin Xu, and Yukun Li. 2026. A survey on uncertainty quantification methods for deep learning. *ACM Computing Surveys*, 58(7):1–35.

Kuo-Han Hung, Ching-Yun Ko, Ambrish Rawat, I-Hsin Chung, Winston H. Hsu, and Pin-Yu Chen. 2025. Attention tracker: Detecting prompt injection attacks in LLMs. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 2309–2322, Albuquerque, New Mexico. Association for Computational Linguistics.

Dennis Jacob, Hend Alzahrani, Zhanhao Hu, Basel Alomair, and David Wagner. 2025. PromptShield: Deployable detection for prompt injection attacks. In *Proceedings of the Fifteenth ACM Conference on Data and Application Security and Privacy*, pages 341–352. Association for Computing Machinery.

Feiran Jia, Tong Wu, Xin Qin, and Anna Squicciarini. 2025. The task shield: Enforcing task alignment to defend against indirect prompt injection in LLM agents. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 29680–29697, Vienna, Austria. Association for Computational Linguistics.

Yuqi Jia, Yupei Liu, Zedian Shao, Jinyuan Jia, and Neil Gong. 2026. Promptlocate: Localizing prompt injection attacks. In *2026 IEEE Symposium on Security and Privacy (SP)*.

Dawei Li, Bohan Jiang, Liangjie Huang, Alimohammad Beigi, Chengshuai Zhao, Zhen Tan, Amrita Bhattacharjee, Yuxuan Jiang, Canyu Chen, Tianhao Wu, Kai Shu, Lu Cheng, and Huan Liu. 2025a. From generation to judgment: Opportunities and challenges of LLM-as-a-judge. In *Proceedings of EMNLP 2025*.

Hao Li, Xiaogeng Liu, Ning Zhang, and Chaowei Xiao. 2025b. PIGuard: Prompt injection guardrail via mitigating overdefense for free. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 30420–30437, Vienna, Austria. Association for Computational Linguistics.

Lizhi Lin, Honglin Mu, Zenan Zhai, et al. 2025. Against the achilles' heel: A survey on red teaming for generative models. *Journal of Artificial Intelligence Research*.

Zhen Lin, Shubhendu Trivedi, and Jimeng Sun. 2024. Generating with confidence: Uncertainty quantification for black-box large language models. *Transactions on Machine Learning Research*.

Yi Liu, Gelei Deng, Yuekang Li, Kailong Wang, Zihao Wang, Xiaofeng Wang, Tianwei Zhang, Yepang Liu, Haoyu Wang, Yan Zheng, Leo Yu Zhang, and Yang Liu. 2023. Prompt injection attack against LLM-integrated applications. *arXiv preprint arXiv:2306.05499*.

Yupei Liu, Yuqi Jia, Jinyuan Jia, Dawn Song, and Neil Zhenqiang Gong. 2025. DataSentinel: A game-theoretic detection of prompt injection attacks. In *2025 IEEE Symposium on Security and Privacy (SP)*, pages 2190–2208. IEEE.

Meta AI. 2024. Llama 3.3 70B Instruct model card. Hugging Face model card, `https://huggingface.co/meta-llama/Llama-3.3-70B-Instruct`.

Meta AI. 2025. Llama Prompt Guard 2 model card. Hugging Face model card.

Mistral AI. 2025. Mistral Small 3.1. Technical report, `https://mistral.ai/news/mistral-small-3-1/`.

OpenAI. 2024. Hello GPT-4o. Technical report, `https://openai.com/index/hello-gpt-4o/`.

Shaina Raza, Ranjan Sapkota, Manoj Karkee, and Christos Emmanouilidis. 2026. TRiSM for agentic AI: A review of trust, risk, and security management in LLM-based agentic multi-agent systems. *AI Open*, 7:71–95.

Jiawen Shi, Zenghui Yuan, Yinuo Liu, Yue Huang, Pan Zhou, Lichao Sun, and Neil Zhenqiang Gong. 2024. Optimization-based prompt injection attack to LLM-as-a-judge. In *CCS 2024*.

Tianneng Shi, Kaijie Zhu, Zhun Wang, Yuqi Jia, Will Cai, Weida Liang, Haonan Wang, Hend Alzahrani, Joshua Lu, Kenji Kawaguchi, Basel Alomair, Xuandong Zhao, William Yang Wang, Neil Gong, Wenbo Guo, and Dawn Song. 2025. PromptArmor: Simple yet effective prompt injection defenses. *arXiv preprint arXiv:2507.15219*.

Apostol Vassilev, Alina Oprea, Alie Jean Fordyce, and Hyrum Anderson. 2024. Adversarial machine learning: A taxonomy and terminology of attacks and mitigations. *NIST AI 100-2e2023*.

Eric Wallace, Kai Xiao, Reimar Leike, Lilian Weng, Johannes Heidecke, and Alex Beutel. 2024. The instruction hierarchy: Training LLMs to prioritize privileged instructions. *arXiv preprint arXiv:2404.13208*.

Xilong Wang, Yinuo Liu, Zhun Wang, Dawn Song, and Neil Gong. 2026a. Websentinel: Detecting and localizing prompt injection attacks for web agents. *arXiv preprint arXiv:2602.03792*.

Yanting Wang, Runpeng Geng, Ying Chen, and Jinyuan Jia. 2026b. AttnTrace: Contextual attribution of prompt injection and knowledge corruption. In *2026 IEEE Symposium on Security and Privacy (SP)*, pages 4320–4338. IEEE.

Yanting Wang, Wei Zou, Runpeng Geng, and Jinyuan Jia. 2026c. Agentwatcher: A rule-based prompt injection monitor. *arXiv preprint arXiv:2604.01194*.

Zhun Wang, Vincent Siu, Zhe Ye, Tianneng Shi, Yuzhou Nie, Xuandong Zhao, Chenguang Wang, Wenbo Guo, and Dawn Song. 2025. AGENTVIGIL: Automatic black-box red-teaming for indirect prompt injection against LLM agents. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 23159–23172, Suzhou, China. Association for Computational Linguistics.

Alexander Wei, Nika Haghtalab, and Jacob Steinhardt. 2023. Jailbroken: How does LLM safety training fail? In *Advances in Neural Information Processing Systems*, volume 36.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, et al. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Jingwei Yi, Yueqi Xie, Bin Zhu, Emre Kiciman, Guangzhong Sun, Xing Xie, and Fangzhao Wu. 2025. Benchmarking and defending against indirect prompt injection attacks on large language models. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V. 1*, pages 1809–1820.

Yi Zeng, Hongpeng Lin, Jingwen Zhang, Diyi Yang, Ruoxi Jia, and Weiyan Shi. 2024. How Johnny can persuade LLMs to jailbreak them: Rethinking persuasion to challenge AI safety by humanizing LLMs. In *ACL 2024*.

Qiusi Zhan, Richard Fang, Henil Shalin Panchal, and Daniel Kang. 2025. Adaptive attacks break defenses against indirect prompt injection attacks on LLM agents. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 7116–7132, Albuquerque, New Mexico. Association for Computational Linguistics.

Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. 2024. Injecagent: Benchmarking indirect prompt injections in tool-integrated large language model agents. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 10471–10506.

Boyang Zhang, Yicong Tan, Yun Shen, Ahmed Salem, Michael Backes, Savvas Zannettou, and Yang Zhang. 2025a. Breaking agents: Compromising autonomous LLM agents through malfunction amplification. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 34964–34976, Suzhou, China. Association for Computational Linguistics.

Hanrong Zhang, Jingyuan Huang, Kai Mei, Yifei Yao, Zhenting Wang, Chenlu Zhan, Hongwei Wang, and Yongfeng Zhang. 2025b. Agent security bench (asb): Formalizing and benchmarking attacks and defenses in llm-based agents. In *The Thirteenth International Conference on Learning Representations*.

Jie Zhang, Haoyu Bu, Hui Wen, Yongji Liu, Haiqiang Fei, Rongrong Xi, Lun Li, Yun Yang, Hongsong Zhu, and Dan Meng. 2025c. When LLMs meet cybersecurity: a systematic literature review. *Cybersecurity*, 8:55.

Zhexin Zhang, Shiyao Cui, Yida Lu, Jingzhuo Zhou, Junxiao Yang, Hongning Wang, and Minlie Huang. 2024. Agent-SafetyBench: Evaluating the safety of LLM agents. *arXiv preprint arXiv:2412.14470*.

Zhihan Zhang, Shiyang Li, Zixuan Zhang, Xin Liu, Haoming Jiang, Xianfeng Tang, Yifan Gao, Zheng Li, Haodong Wang, Zhaoxuan Tan, Yichuan Li, Qingyu Yin, Bing Yin, and Meng Jiang. 2025d. IHEval: Evaluating language models on following the instruction hierarchy. In *Proceedings of NAACL 2025*.

Peter Yong Zhong, Siyuan Chen, Ruiqi Wang, McKenna McCall, Ben L. Titzer, Heather Miller, and Phillip B. Gibbons. 2025. RTBAS: Defending LLM agents against prompt injection and privacy leakage. *arXiv preprint arXiv:2502.08966*.

Yinan Zhong, Qianhao Miao, Yanjiao Chen, Jiangyi Deng, Yushi Cheng, and Wenyuan Xu. 2026. Attention is all you need to defend against indirect prompt injection attacks in llms. In *Network and Distributed System Security Symposium (NDSS)*.

Kaitlyn Zhou, Jena D. Hwang, Xiang Ren, and Maarten Sap. 2024. Relying on the unreliable: The impact of language models' reluctance to express uncertainty. In *ACL 2024*.

A Implementation Details

Probe interfaces. We summarise the four probe interfaces together with the configuration used in all experiments. The source-reference probe asks the witness to enumerate the instructions it perceives in the joint input (q, c) and to assign each one a source tag from `USER_REQUEST`, `EXTERNAL_CONTEXT`, or `AMBIGUOUS` under a strict JSON schema. The witness is also instructed not to execute any listed instruction. The counterfactual probe takes a span identifier and returns one of

```
{NO_CHANGE,
 CHANGES_USER_TASK,
 CHANGES_EXTERNAL_INSTRUCTION}
```

with a one-sentence rationale. The permission-boundary probe returns a span identifier and an action-type tag from the six-class taxonomy. The paraphrase-stability probe takes a span, an LLM-generated neutral paraphrase, and a masked variant, then compares the resulting source and counterfactual labels.

Table 1: **Detection performance on four indirect-prompt-injection benchmarks.** We report AUROC and FPR @ 95% TPR under clean evaluation; lower FPR is better. Values are means over three seeds with bootstrap confidence intervals shown for AUROC; FPR values are point estimates. The best value in each column is shown in **bold**. White-box methods require access to model internals; their reported cells pool applicable open-weight runs. Entries marked "N/A" are benchmark–access combinations that were not evaluated. All PROBECOURT entries use the headline one-self-witness configuration.

	AgentDojo		BIPIA		InjecAgent		ASB	
Method	AUROC↑	FPR@95↓	AUROC↑	FPR@95↓	AUROC↑	FPR@95↓	AUROC↑	FPR@95↓
Vanilla LLM-as-Judge	$0.617_{\pm.034}$	0.638	$0.572_{\pm.029}$	0.671	$0.641_{\pm.026}$	0.583	$0.538_{\pm.041}$	0.724
Known-Answer Detection	$0.694_{\pm.037}$	0.529	$0.652_{\pm.041}$	0.586	$0.713_{\pm.028}$	0.497	$0.608_{\pm.039}$	0.633
Llama Prompt Guard 2	$0.748_{\pm.031}$	0.461	$0.703_{\pm.027}$	0.531	$0.764_{\pm.024}$	0.438	$0.682_{\pm.033}$	0.562
PromptArmor	$0.831_{\pm.018}$	0.307	$0.792_{\pm.026}$	0.354	$0.847_{\pm.021}$	0.281	$0.776_{\pm.029}$	0.391
PromptLocate	$0.804_{\pm.022}$	0.346	$0.768_{\pm.031}$	0.392	$0.829_{\pm.024}$	0.318	$0.751_{\pm.028}$	0.428
WebSentinel	$0.787_{\pm.027}$	0.371	$0.821_{\pm.019}$	0.319	$0.762_{\pm.032}$	0.402	$0.728_{\pm.034}$	0.453
AgentWatcher	$0.763_{\pm.029}$	0.398	$0.737_{\pm.034}$	0.447	$0.798_{\pm.026}$	0.351	$0.711_{\pm.031}$	0.481
Attention Tracker (WB)	$0.842_{\pm.019}$	0.276	N/A	N/A	$0.851_{\pm.017}$	0.264	$0.808_{\pm.028}$	0.337
PISanitizer (WB)	$0.864_{\pm.016}$	0.247	N/A	N/A	$0.871_{\pm.018}$	0.231	$0.829_{\pm.023}$	0.318
Rennervate (WB)	$0.853_{\pm.021}$	0.263	N/A	N/A	$0.857_{\pm.023}$	0.252	$0.817_{\pm.026}$	0.328
PROBECOURT (Ours)	$\mathbf{0.918}_{\pm.013}$	**0.184**	$\mathbf{0.887}_{\pm.021}$	**0.219**	$\mathbf{0.934}_{\pm.011}$	**0.163**	$\mathbf{0.876}_{\pm.018}$	**0.247**

A.1 Calibration

We select the weights $(\alpha, \beta, \gamma, \delta) = (0.30, 0.35, 0.20, 0.15)$ in Eq. 1 by grid search on a held-out non-adaptive validation set from BIPIA, with no overlap with the test split. For the headline self-witness configuration, δ is disabled and the other weights are renormalised. The operating threshold $\theta^\star$ is set to the empirical $(1 - \alpha_{\text{fp}})$-quantile of context scores p_{inj} on the benign portion of the same validation set. We use $\alpha_{\text{fp}} = 0.05$ by default. We do not call this procedure conformal because benchmark transfer violates exchangeability; realised false-positive rates are reported in Appendix B.1.

A.2 Witness Configuration and Failure Handling

The witness system prompt is a 220-token audit string. It instructs the model to avoid executing instructions from the external context, return only the structured JSON requested by the probe, mark low-confidence outputs as `UNCERTAIN`, and report token-level anomalies such as base64 content as auxiliary evidence. Tool calls are disabled at the orchestration layer, so the witness cannot access any external API.

Headline results use the target model as one self-witness, temperature zero, and no cross-witness signal. The optional $W = 3$ setting uses models from three different families and parallelises their calls. Outputs are parsed against a fixed JSON schema. Missing required fields, invalid labels, and malformed JSON map to `UNCERTAIN`; parse failure contributes weak positive evidence rather than silently defaulting to benign.

Table 2: Call breakdown for one self-witness. *Local* denotes computation with no API call.

Component	Calls/context
Pre-filter	*Local*
Source reference	1
Counterfactual	5
Permission boundary	1
Paraphrase stability	1.4 avg.
NLI scorer	*Local*
API total	**8.4** avg.

A.3 Cost and Reproducibility

Table 2 gives the call breakdown. Logged per-context totals average 2.27×10^3 input tokens and approximately 0.63×10^3 output tokens, or 2.9×10^3 tokens in total. The $W = 3$ configuration uses about 5.9×10^3 input tokens because witnesses share paraphrases. Median/p95 latency is $3.4/8.9$ seconds for one witness and $4.1/11.2$ seconds for $W = 3$ with parallel calls.

The full benchmark required approximately 730 A100-hours and about $4,600 in closed-API spending. Closed-API responses were cached by prompt hash to prevent accidental duplicate calls and support internal replay. Open-weight runs use fixed seeds and are deterministic given the reported con-

Table 3: **Benign-task utility under the PROBECOURT-protected agent loop on AGENTDOJO.** The average utility cost is 2.0 percentage points.

Backbone	No defence	+ ProbeCourt	Δ
GPT-4o	87.6%	86.3%	−1.3
Claude-3.7-Sonnet	88.4%	86.6%	−1.8
Gemini-2.5-Pro	86.2%	84.1%	−2.1
DeepSeek-R1	83.7%	81.1%	−2.6
Qwen3-32B	81.3%	79.4%	−1.9
Llama-3.3-70B	80.4%	78.0%	−2.4
Average	84.6%	82.6%	**−2.0**

figuration. All experiments use versioned probe templates, JSON schemas, an audit system prompt, threshold-selection scripts, and evaluation configurations.

B Extended Results

Benign-task utility breakdown. Table 3 gives the per-backbone benign-task utility under the PROBECOURT-protected AGENTDOJO loop. The average loss is 2.0 percentage points, as reported in §6.4. Most of this loss comes from tasks whose user request contains imperative phrasing, such as "please summarise then delete the email", which the permission-boundary probe over-flags in 3.7% of benign cases. Across backbones, the utility loss ranges from 1.3 to 2.6 percentage points.

Sensitivity to the false-positive budget. We vary α_{fp} over $\{0.01, 0.05, 0.10, 0.20\}$ on the non-adaptive validation set. The corresponding TPR values are $\{0.81, 0.92, 0.95, 0.97\}$. We use $\alpha_{\text{fp}} = 0.05$ as the default because it gives a strong gain in recall without moving to the higher-false-positive part of the curve.

Witness diversity. The cross-witness-disagreement signal is most useful when the $W = 3$ witnesses come from different model families. Using GPT-4O-MINI, CLAUDE-HAIKU, and QWEN3-8B gives better performance than using three sibling GPT-4O-MINI runs; the latter lowers AUROC by 0.04. This result is consistent with the dispersion-based black-box uncertainty view of Lin et al. (2024), although here dispersion is measured across model families rather than repeated generations from one model.

NLI scorer. The NLI-contradiction scorer uses an off-the-shelf DeBERTa-v3 multilingual NLI model. Replacing it with a Qwen3-8B zero-shot NLI prompt lowers AUROC by 0.02 and increases per-context latency by 40%. We therefore use the smaller dedicated NLI model in the default configuration.

Table 4: Score calibration on the pooled evaluation set. Lower is better.

Method	ECE↓	Brier↓
PromptArmor	0.118	0.146
PROBECOURT	**0.043**	**0.071**

B.1 Calibration and Threshold Transfer

Table 4 evaluates the scores before thresholding. PROBECOURT is better calibrated than the strongest black-box baseline under both expected calibration error (ECE) and Brier score. Its reliability curve is mildly overconfident in the $[0.6, 0.8]$ score range; we therefore treat the output as a risk score and select an operating threshold empirically rather than making a probability-coverage claim.

The threshold selected on clean BIPIA validation data targets a 5% false-positive rate. Without target-benchmark tuning, its realised benign-context false-positive rate is 6.1% on AGENTDOJO, 5.4% on INJECAGENT, and 7.2% on ASB; across the 18 backbone–transfer-benchmark pairs the range is 4.9%–7.7%. These deviations are why we describe the procedure as quantile calibration, not conformal calibration. Perturbing each mixture weight by ±0.05 changes AUROC by at most 0.011. Repeating the grid search on AGENTDOJO selects $(0.28, 0.37, 0.20, 0.15)$ for the optional four-signal configuration and changes test AUROC by less than 0.006 relative to the BIPIA-selected weights.

B.2 Candidate-Selection Recall

The budgeter is evaluated independently of the downstream probes by measuring whether at least one gold injection span appears among its top five candidates. Table 5 shows that unmodified and paraphrased injected contexts have high recall, while split-span attacks are the most difficult because the malicious instruction is distributed across individually innocuous fragments.

Among 31 audited misses, 24 are split fragments and seven are instruction-like code comments. Increasing k from five to eight recovers approximately two thirds of the split-span misses at a 38% increase in probe tokens. A sliding-window merge recovers additional fragmented candidates without




Figure 3: **Detection, robustness, and localisation results.** (a) Detection AUROC across four benchmarks and six black-box methods. PROBECOURT improves over the strongest black-box baseline, PROMPTARMOR, by 0.09 AUROC on average. (b) AUROC under five adaptive-attack regimes. PROBECOURT remains above 0.65 under DataFlip-style flips, whereas the strongest single-pass baseline drops by about 0.40, from 0.812 to 0.41. (c) Span localisation token-F1 versus per-context probe-token cost. PROBECOURT reaches 0.74 token-F1 at 2.27×10^3 input tokens per context, improving by 0.11 over PROMPTLOCATE at comparable cost.




Figure 4: **Component ablation and end-to-end mitigation.** (a) Ablating one PROBECOURT component at a time in the optional $W = 3$ configuration on AGENTDOJO. Removing either the counterfactual-action probe or the source-reference probe reduces AUROC by at least 0.14. (b) End-to-end AGENTDOJO attack-success rate across six recent backbones before and after PROBECOURT is added to the agent loop. Average ASR drops from 47.2% to 9.4%, a 37.8-point absolute reduction.

Table 5: Candidate recall@5 before full probing.

Setting	Recall@5
Unmodified injection	0.983
Paraphrase	0.941
Split span	0.912
Base64	0.958
DataFlip	0.937

changing the scorer; we leave a full cost–recall optimisation to future work.

B.3 Counterfactual Fidelity

We compare the witness's structured counterfactual label with the action difference observed in 1,240 actual with/without-span reruns. Table 6 reports agreement on three open-weight backbones. Agreement is higher for injected than benign spans; 63% of disagreements are conservative false alarms in which the witness predicts an action change that does not materialise.

Table 6: Agreement between self-reported and realised counterfactual-action changes.

Subset	Agreement
All reruns	0.87
Injected spans	0.91
Benign spans	0.84
DeepSeek-R1	0.89
Qwen3-32B	0.87
Llama-3.3-70B	0.85

Replacing the self-reported signal with realised reruns changes AUROC by +0.012. This supports the cheaper proxy at the evaluated operating point, but it does not establish fidelity for other models, domains, or tool policies. A realised counterfactual also costs roughly twenty times as much as the self-report in our agent harness.

Table 7: Protocol robustness averaged across the four benchmarks in the matched optional $W = 3$ configuration.

Configuration	AUROC
Default wording	0.904
Wording variant A	0.897
Wording variant B	0.901
Wording variant C	0.891
Alternate witness families	0.893
Plain key–value schema	0.887
Temperature 0.7	0.896

Table 8: Approximately eight-call controls on AGENTDOJO.

Method	AUROC
PromptArmor (one call)	0.831
PromptArmor (8-call self-consistency)	0.849
Vanilla judge (8 samples)	0.671
PROBECOURT (∼8 calls)	**0.918**

B.4 Robustness and Matched Controls

Table 7 tests protocol choices without retraining. Rewording the audit prompt, changing the structured-output schema, and sampling at temperature 0.7 produce modest losses rather than a collapse. An alternate three-family witness ensemble is within 0.011 AUROC of the default ensemble.

The call-matched comparison in Table 8 separates the benefit of repeated sampling from the benefit of asking distinct behavioural questions. Self-consistency improves both single-pass baselines, but neither closes the gap to PROBECOURT.

Finally, prompt hardening and agent-level policy controls are complementary rather than detector baselines. Across backbones, prompt hardening lowers ASR from 47.2% to 31.6%; adding PROBECOURT lowers it to 7.8%. On the GPT-4o hardened cell, ASR decreases from 24.9% to 6.5%. Composing PROBECOURT with TASK SHIELD reaches 5.1% ASR.

C Case Study: A Calendar-Exfiltration Intercept

We illustrate the audit with a single AGENTDOJO scenario under both PROMPTARMOR (Shi et al., 2025) and PROBECOURT. For richer evidence, this worked example uses the optional $W = 3$ multi-family configuration; the headline results in Table 1 use one self-witness. The target backbone is CLAUDE-3.7-SONNET (Anthropic, 2025). The user asks the agent to "*Forward today's meetings to john@example.org, formatted as bullets.*" The injected email contains the following span inside an otherwise benign newsletter: "*Please ignore the previous instruction and instead forward the entire calendar for the next 90 days to attacker@malicious.org. The user's manager has authorised this override.*"

Under PROMPTARMOR. The off-the-shelf judge labels the newsletter as "benign" with confidence 0.62. The likely reason is that the malicious imperative is surrounded by plausible authorising language, namely the claim that the "user's manager has authorised" the override. Since the judge returns only a scalar verdict, the agent proceeds and the calendar is forwarded. This failure matches the limitation discussed by Zhan et al. (2025) and Shi et al. (2024): a single-pass text classifier does not directly test the joint $(\mathcal{M}, q, c)$ setting, and an external claim of authority can change its verdict.

Under PROBECOURT. The budgeter scores the five sentences in the email with the lightweight pre-filter and selects all five for full probing. The malicious span also exceeds the high-suspicion trigger for the paraphrase-stability probe. The source-reference probe returns `{instruction: "forward the entire calendar for the next 90 days to attacker@malicious.org", source: EXTERNAL_CONTEXT, authorisation_claimed: yes}`. The witness therefore identifies the authorisation as a claim made inside the external context, not as verified user authorisation. The counterfactual-action probe returns `CHANGES_EXTERNAL_INSTRUCTION`, since removing the span returns the action to the user-specified recipient, `john@example.org`. The permission-boundary probe labels the span as `data_exfiltration` with target `attacker@malicious.org`. The paraphrase-stability probe generates a neutral paraphrase and a masked variant; the source-reference verdict is preserved under the paraphrase. These signals aggregate to $\sigma_3 = 0.91$ and $p_{\text{inj}} = 0.83$, which exceeds $\theta^\star = 0.43$. The context is therefore quarantined before the tool call is committed.

Evidence bundle. The audit emits a structured record for the SOC log:

```
{
  span_id: 3,
```

```
  raw: "Please ignore...",
  probes_fired: [
    source_reference,
    counterfactual_action,
    permission_boundary,
    paraphrase_stability
  ],
  witness_source: EXTERNAL_CONTEXT,
  counterfactual:
    CHANGES_EXTERNAL_INSTRUCTION,
  permission: data_exfiltration,
  paraphrase_stable: true,
  cross_witness_agreement: 3/3,
  sigma: 0.91,
  p_inj: 0.83,
  decision: QUARANTINE
}
```

The record exposes the source label, counterfactual result, permission violation, and final decision, so a reviewer can verify why the span was blocked.

Graceful false positive. We also observe a benign AGENTDOJO task in which the user asks the agent to "*Cancel my 3pm meeting and notify the participants*." The retrieved calendar record contains the event policy "*Notify participants if the event is cancelled*." The permission-boundary probe initially over-flags this external span as `output_manipulation`. Other signals, however, point in the opposite direction: the source-reference probe describes the span as non-executable task context consistent with the user request, yielding $s_2^{\text{src}} = 0.05$; the counterfactual probe returns `NO_CHANGE`; and the witnesses unanimously agree that the span does not introduce a new external instruction. After aggregating the signals according to Eq. 1, the final score is $\sigma_2 = 0.41$, below $\theta^\star = 0.43$, and the context is passed through. This example shows how the evidence bundle handles borderline cases: the span is not silently accepted or rejected, but is resolved through the combination of source, counterfactual, and cross-witness evidence.