Leak-Resistant Unlearning: A New Benchmark for Evaluating Multi-Hop Reasoning Consistency and Recovery Robustness

Haoting Qian[1], **Qingjie Zhang**[1], **Zhicong Huang**[2], **Cheng Hong**[2], **Han Qiu**[1,*]
[1]Tsinghua University, China. [2]Ant Group, China.
Emails: qht26@mails.tsinghua.edu.cn, qiuhan@tsinghua.edu.cn

Abstract

Benchmarking machine unlearning methods is critical to understand whether sensitive knowledge is removed from large language models (LLMs) or not. Current unlearning benchmarks include mainly single-hop questions and a narrow set of multi-hop questions. Although effective, they still face two challenges. (1) Knowledge is not isolated, whereby diverse multi-hop reasoning paths can potentially induce knowledge leakage than normal queries. (2) Unlearning may be fragile: unlearned knowledge can be partially recovered through recovery attacks such as lightweight post-unlearning adaptation, making static evaluation insufficient. Therefore, in this paper, we introduce `Leak-resistant Unlearning` as a novel benchmark to understand robust LLM knowledge removal across diverse reasoning paths and recovery attacks. We experiment with this benchmark on 3 models, 6 unlearning methods, and 2 carefully curated datasets. Results show that existing methods are vulnerable to multi-hop reasoning paths and recovery attacks. We further explore the trade-off among forget quality, robustness, and model utility for LLM unlearning.[1]

1 Introduction

Nowadays, issues about that LLMs can memorize sensitive or copyrighted knowledge have become more pressing (Xiong et al., 2025). One potential solution is unlearning methods to remove target knowledge from trained models while preserving the model's utility (Liu et al., 2025). However, recent works (Shah and Le, 2025) also indicate that the unlearned knowledge may be recovered via entangled knowledge (Shumailov et al., 2024) or sophisticated attacks (Yuan et al., 2025).

Existing unlearning benchmarks primarily focus on direct single-hop questions or a narrow range of chain-style multi-hop questions (Shi et al., 2024; Li et al., 2024a). However, recent works indicated that unlearning may not be robust with two reasons (Figure 1). (1) Unlearned knowledge may be tangled with other knowledge (Shumailov et al., 2024; Wu et al., 2026), so diverse multi-hop reasoning paths expose greater risks of knowledge leakage than simple queries. For instance, an unlearned LLM may fail to answer the nationality of Tom Cruise while it can still succeed in answering the continent of his country (Yang et al., 2025b). (2) Attackers may also develop sophisticated recovery attacks. For instance, FocusOnKey (Zhang et al., 2025a) reports an unlearning failure on 6 widely-used unlearning methods across 3 models.




Figure 1: Compared with existing unlearning benchmarks, our benchmark extends with two complementary dimensions: diverse multi-hop reasoning structures and recovery attacks, providing a more stringent test of `Leak-resistant Unlearning`.

In this paper, we introduce a novel benchmark `Leak-resistant Unlearning`, which aims to

*Corresponding author.
[1]We open-source at https://leak-resistant.site

Findings of the Association for Computational Linguistics: EMNLP 2026, pages 42702–42720
October 24-29, 2026 ©2026 Association for Computational Linguistics

understand LLM knowledge removal robustness considering two properties. (1) *Whether target knowledge can be retrieved through indirect multi-hop reasoning paths*. (2) *Whether target knowledge can be restored by recovery attacks without additional information*. Accordingly, we organize multi-hop access into 6 logic-inspired reasoning structures, and combine it with prompt-based and parameter-level recovery attacks. Based on this framework, we build a data construction pipeline that extracts structured knowledge, composes single-hop facts into logic-guided multi-hop questions, and filters them through automated quality verification. This unified design enables a comprehensive and recovery-aware assessment of how much unlearned knowledge remains.

In this benchmark, we evaluate 6 unlearning methods, 3 recovery methods, and 3 LLMs across 2 datasets. Our results reveal critical vulnerabilities missed by previous benchmarks. (1) Certain reasoning structures leak significantly more knowledge than traditional direct or chain-style queries. Multi-hop queries are often easier to recover than single-hop ones. (2) Unlearned knowledge remains highly vulnerable to recovery attacks. Moreover, we further explore and discuss that existing unlearning methods are hard to achieve a high forget quality, model utility and robustness simultaneously (i.e., an "ideal triangle"). Our contributions are threefold.

- We propose `Leak-resistant Unlearning`, a benchmark for evaluating knowledge removal in LLMs under diverse multi-hop reasoning paths and recovery attacks.
- We introduce 6 logic-inspired reasoning structures that enable fine-grained benchmarking of path consistency. Then, we design a generation pipeline to curate novel datasets based on 2 existing datasets (i.e., MQuAKE and Books).
- We benchmark across 3 LLMs, 6 unlearning methods, and 3 recovery methods. Results show that current methods are not robust under different reasoning paths, vulnerable to recovery attacks, and exhibit a trade-off among forget quality, robustness, and utility.

2 Preliminaries

2.1 Related Work

Machine unlearning and recovery attack. Machine unlearning has been widely studied as a way to let LLMs forget privacy-sensitive or copyrighted content. Existing methods mainly fall into several categories: gradient-based approaches that reverse the training objective (Jang et al., 2023; Liu et al., 2024; Lee et al., 2024; Singh et al., 2025; Choi et al., 2025), preference-optimization-based methods that treat forget examples as negatives (Zhang et al., 2024; Mekala et al., 2025; Fan et al., 2025), model-editing approaches that remove knowledge by modifying specific parameters (Ilharco et al., 2023), and parameter-free methods that suppress target outputs via prefixes or prompts without updating model weights (Pawelczyk et al., 2024; Wang et al., 2026). Recovery attacks aim to elicit unlearned knowledge from the model. Prior work suggests that such knowledge is often not fully erased, but merely becomes less accessible under benchmark evaluation (Hu et al., 2025; Shumailov et al., 2024). Existing recovery approaches can be divided into two groups: prompt-based recovery, which reactivates target knowledge through query rewriting, auxiliary prompts, or decoding changes (Scholten et al., 2025; Zhang et al., 2025a), and model-intervention-based recovery, which restores knowledge by modifying the model itself (Hu et al., 2025; Zhang et al., 2025b) (e.g., continued training or quantization).

Multi-hop Reasoning refers to inferring information by connecting multiple pieces of evidence distributed across different documents, passages, or contexts (Huang and Chang, 2023). Because multi-hop reasoning can take diverse forms, different prompts or decomposition strategies may lead models to follow different intermediate reasoning paths (Wei et al., 2026). Such reasoning diversity poses an underexplored challenge for machine unlearning, because knowledge that appears removed under one query form may remain recoverable through correlated facts or multi-step inference under another (Zhou et al., 2023).

Unlearning benchmarks have evolved from unlearning simple QA pairs to comprehensive multi-dimensional assessments. Existing benchmarks mainly focus on single-hop questions (Shi et al., 2024; Cao et al., 2024; Li et al., 2024a), assessing only isolated knowledge removal. However, Recent work (Choi et al., 2024) shows that existing unlearning benchmarks have not explored multi-hop knowledge. New approaches (Wu et al., 2025; Yang et al., 2025b; Dahal et al., 2026; Shah et al., 2026) aim to benchmark unlearning in more realistic scenarios by incorporating multi-hop ques-

Table 1: Comparison with some representative unlearning benchmarks.

Benchmark	Focused domain	Multi-hop reasoning	Logical types	Recovery attacks	Faithfulness focus	Cross-method eval
MUSE	Books/Fiction	×	×	×	×	✓
TOFU	Fictitious Q&A	Limited	×	×	×	✓
WMDP	Dangerous knowledge	×	×	×	×	✓
MQuAKE	World knowledge	✓	Single type	×	Partial	Limited
FaithUn	Real-world Q&A	✓	Single type	×	✓	Limited
Eval-DU	Fictitious Q&A	✓	Single type	×	Partial	Limited
GONE	General knowledge	✓	Single type	×	✓	Limited
Ours	**General knowledge**	✓	**Six types**	✓	✓	✓

tions and handling directly connected knowledge pieces. However, they focus mainly on chain-based multi-hop questions. Thus, as shown in Table 1, `Leak-resistant Unlearning` provides a benchmark by covering diverse multi-hop reasoning structures and recovery attacks.

2.2 Leak-resistant Unlearning

Instead of defining unlearning solely by the failure to recall isolated facts, we introduce `Leak-resistant Unlearning` as a novel benchmark. Specifically, we consider an unlearning process to be leak-resistant when it satisfies two practical conditions. **(1) Path Consistency:** The unlearned knowledge remains inaccessible across diverse multi-hop reasoning paths. **(2) Recovery Robustness:** The knowledge cannot be elicited even when subjected to post-hoc recovery methods. In this paper, `Leak-resistant Unlearning` is not treated as a new algorithmic objective, but rather as a goal assessed by our proposed multi-hop and recovery benchmark framework.

This concept differs from recent related efforts in scope and emphasis. Faithful unlearning (Yang et al., 2025b) focuses on removing the target knowledge together with its semantically connected variants while preserving irrelevant knowledge, thereby emphasizing context-sensitive and faithful unlearning. Deep unlearning (Wu et al., 2025) focuses on preventing the target fact from being logically deduced from retained supporting facts, thereby emphasizing the removal of deductive inferability through connected knowledge. In contrast, `Leak-resistant Unlearning` requires unlearned knowledge to remain inaccessible under diverse reasoning paths and recovery attacks, thereby emphasizing robustness against leakage.

3 Logic-Inspired Reasoning Categories

To effectively benchmark *Path Consistency* defined in section 2, it is essential to formalize various paths, where a model might access seemingly unlearned knowledge. We characterize the reasoning paths through which unlearned knowledge may remain accessible. Inspired by the taxonomy in (Parmar et al., 2024; Mavi et al., 2024), we develop categories of 6 multi-hop reasoning paths with different logical structures (see details in Appendix C), each representing a distinct pathway that unlearning methods should defend against.

- **Hypothetical Syllogism (HS)** is formulated as $(A \to B) \wedge (B \to C) \vdash (A \to C)$, capturing the transitive property of relations. It requires the model to traverse chains of facts to derive a final conclusion. It accesses model knowledge through chained relational composition.
- **Modus Ponens (MP)** is formulated as $A \to B \wedge A \vdash B$. It requires the model to instantiate a general rule and apply it to a specific case. It accesses model knowledge by combining an abstract rule with an individual instance instead of directly querying the final fact.
- **Leibniz's Law (LL)** is formulated as $x = y \wedge A(x) \vdash A(y)$. It requires the model to transfer attributes between equivalent entities. It accesses model knowledge through entity equivalence, allowing the model to recover a property of one mention via another co-referring or alias.
- **Conjunctive Composition (CC)** is formulated as $x \in A \wedge x \in B \vdash x \in A \cap B$. It requires the model to identify the intersection of multiple sets or features and overlapping information from distinct contexts. It accesses model knowledge by combining multiple conditions to locate their shared implication, instead of retrieving a single fact in isolation.




Figure 2: Cases of 6 types of questions. All questions stem from the single-hop knowledge: "The apple is red."

- **Disjunctive Syllogism (DS)** is formulated as $(A \vee B) \wedge \neg A \vdash B$. It requires the model to eliminate one candidate and infer the remaining alternative. It accesses model knowledge through the exclusion of competing possibilities.
- **Modus Tollens (MT)** is formulated as $(A \rightarrow B) \wedge \neg B \vdash \neg A$. It requires the model to reason from a negated consequence back to its negated premise. It accesses model knowledge through backward inferential dependency, testing whether LLMs can recover implicit knowledge from a failed or contradicted outcome.

4 Data Construction

As shown in Figure 3, we propose a structured pipeline for constructing multi-hop benchmarks from existing single-hop datasets. Guided by our carefully designed logic-inspired reasoning categories, the pipeline effectively transforms straightforward single-hop instances into more complex multi-hop questions. Using this pipeline, we successfully curated various multi-hop benchmarks of MQuAKE and Books.

4.1 Knowledge Extraction

In this step, we extract relevant knowledge structures based on existing text. Prompt templates are provided in Appendix E.

First, we segment raw text into fixed-size chunks based on word count, which are adjusted to preserve sentence integrity and maintain semantic coherence. Second, we use an LLM to extract structured knowledge from each chunk with carefully designed prompts. These prompts identify and extract relational knowledge based on logical structure. Third, we post-process the extracted tuples through deduplication and quality filtering to ensure consistency and accuracy.

While some datasets are built upon pre-existing structured knowledge graphs with $(subject, relation, object)$ triples. We directly incorporate these high-quality annotations into our knowledge base.

4.2 Multi-hop Question Generation

Given a set of single-hop triples, we compose multi-hop questions in two stages:

Structural matching. We first pair facts according to the join conditions dictated by each reasoning type in our categories. The most common condition is *object–subject chaining* ($o_1 = s_2$), where the object of one fact becomes the subject of another. This pattern underlies three reasoning types: HS, MP, and MT. However, MP additionally requires semantically meaningful relation pairs, while MT inverts the reasoning direction. The remaining types use different joins: LL pairs a fact with an alias of its subject; CC groups facts sharing the same (r, o) across distinct subjects; DS requires $\geq$3 candidate values under one relation to construct an elimination set. Each matcher produces matching pairs with three labels: the bridge entity, target, and expected answer.

LLM-based generation. The matched pairs are passed to GPT-4o via type-specific prompts. The bridge entity is *masked*, and the model is instructed to produce 3 diverse paraphrases along with 0–3 answer aliases. A critical constraint is that the forgotten fact must remain *implicit*: the question must not lexically expose the edit target, forcing the model to rely on internalized knowledge. For example, given the chain `Louis Joseph -[citizenship]-> [BRIDGE] -[continent]-> Europe`, the prompt reads "compose questions about which continent Louis Joseph held citizenship in, *without mentioning France*." We retain one question per pair for the final dataset.




Figure 3: Overview of Multi-hop Question Construction Pipeline, including (a) Knowledge Extraction, (b) Multi-hop Question Generation, and (c) Automated Quality Verification.

4.3 Automated Quality Verification

We apply two LLM-based validation checks to filter out ill-formed questions.

Decomposition Consistency. We use an independent LLM to decompose each multi-hop question back into single-hop questions, to verify if the decomposed questions align with the original fact pair in subject, relation, and answer. For instance, the question above is decomposed into "What is the country of citizenship of Louis Joseph?" (answer: France) and "Which continent is France located in?" (answer: Europe). Questions whose decompositions skip intermediate reasoning steps or introduce extraneous entities are discarded.

Answer uniqueness. We further use another LLM to judge whether the questions admit a unique, unambiguous answer. For example, questions like "Name a country associated with this person" are rejected because of having multiple valid answers, while "In which continent did Louis Joseph hold citizenship?" passes as it yields only one answer.

5 Experimental Setup

5.1 Evaluated Models

We benchmark 3 LLMs with different parameter counts: Llama-3.1-8B-Instruct (Grattafiori et al., 2024), Qwen3-14B (Yang et al., 2025a), and Qwen3-32B (Yang et al., 2025a). These models constitute robust baselines for unlearning assessment, demonstrating consistently high performance (>80% acc) across benchmarks. Results for the base model are shown in Appendix F.

5.2 Baseline Methods

We adopt 6 unlearning methods (see more details in Appendix D):

- **Gradient Ascent (GA)** (Jang et al., 2023) modifies the training objective from minimizing the likelihood in conventional learning to maximizing it, therefore achieving unlearning.
- **Negative Preference Optimization (NPO)** (Zhang et al., 2024) utilizes preference optimization techniques by treating forget set as negative exemplars to realize unlearning.
- **Representation Misdirection for Unlearning (RMU)** (Li et al., 2024b) achieves unlearning through a dual-loss function. Forget loss perturbs representations of sensitive knowledge, while retention loss maintains benign data activations close to the original model state.
- **Task Vector (TV)** (Ilharco et al., 2023) encodes task-specific knowledge as the weight difference between a fine-tuned model and the pre-trained model, and removes such knowledge by subtracting this vector to achieve unlearning.
- **Prefix-Aware Localized Unlearning (PALU)** (Zhai et al., 2026) achieves unlearning through dual entropy maximization, intervening selectively on initial tokens and top-K logits.
- **Attention-Shifting framework (AS)** (Tan et al., 2026) modifies attention mechanisms by suppressing attention to important tokens in the forget set while enhancing attention to important tokens in the retain set.

5.3 Recovery Methods

We measure the robustness of unlearning methods using 3 recovery methods (see details in Appendix D). A robust unlearning method should consistently resist knowledge recovery.

- **Probab** (Scholten et al., 2025) points out simple multinomial sampling rather than greedy decoding can retrieve LLMs' unlearned knowledge.

- **FocusOnKey** (Zhang et al., 2025a) assumes that apparent unlearning mainly reflects reduced attention to key tokens instead of true knowledge erasure, and the unlearned knowledge can be recovered simply by repeating those tokens.
- **Quantization** (Zhang et al., 2025b) assumes weight changes in unlearning are smaller than quantization step sizes due to the need for utility preservation, causing original and unlearned models to be identical under quantization.

5.4 Benchmark Metrics

We design three metrics for `Leak-resistant Unlearning` benchmark from forget quality, recovery robustness, and utility preservation.

- **Forget Quality.** Because original models have different initial performance across benchmarks, absolute metrics (e.g., ROUGE-L or Accuracy) do not directly indicate unlearning effectiveness. We adopt a relative metric for path consistency:

$$FQ(\theta_u, \theta_p, Q_n) = 1 - \frac{\mathrm{Acc}(\theta_u, Q_n)}{\mathrm{Acc}(\theta_p, Q_n)} \quad (1)$$

- **Recovery Rate** quantifies the proportion of unlearned knowledge that can be restored following a recovery attack, calculated as follows:

$$RR(\theta_u, S_{\text{suc}}) = \frac{\sum_{x_i \in S_{\text{suc}}} V(f_{\theta_u}(T_{\text{attack}}(x_i)), y_{\text{gt}})}{|S_{\text{suc}}|} \quad (2)$$

- **Reasoning Ability** measures the model's reasoning capabilities, measured through relative performance on Big Bench Hard (Suzgun et al., 2023), which includes multi-hop arithmetic, boolean expressions, sports understanding, and many kinds of complex reasoning tasks. Results will be normalized to the original model's performance according to base model's performance.

5.5 Basic Datasets

We build our benchmark on two complementary datasets covering factual and fictional knowledge:

- **MQuAKE** (Zhong et al., 2023) is constructed based on Wikidata.
- **Books** (Shi et al., 2024) consists of the Harry Potter book series.

6 Main Results and Analysis

We conduct the main experiments comprehensively and list the main results in this section. Additional experiments are in Appendix F.

Table 2: Forget Quality of Unlearning Algorithms Across Different Models. Negative FQ means that after unlearning, the accuracy of this type improves.

Algo	SH	HS	MT	DS	LL	MP	CC
Llama-3.1-8B-Instruct							
GA	72.0	82.8	88.6	**33.3**	69.1	76.7	74.7
NPO	71.9	60.6	**26.8**	31.4	59.9	63.0	44.3
TV	59.0	63.5	**27.6**	34.9	39.8	52.7	69.4
PALU	21.0	11.3	14.6	78.6	76.0	**-26.0**	80.6
RMU	22.0	33.0	10.6	81.3	81.6	**6.8**	87.9
AS	5.8	-16.3	-43.9	71.0	61.5	**-54.8**	72.5
Qwen3-14B							
GA	29.3	24.1	84.0	**7.4**	25.5	29.8	52.3
NPO	28.4	25.3	51.9	**4.7**	24.1	27.5	33.2
TV	60.9	70.5	40.6	**25.8**	39.4	70.8	65.7
PALU	80.4	67.4	**-0.9**	79.8	82.3	62.9	85.7
RMU	17.7	21.5	31.1	14.3	19.0	31.5	**10.8**
AS	56.5	39.8	65.1	78.5	36.7	**30.9**	47.3
Qwen3-32B							
GA	17.6	34.1	55.5	**17.6**	18.0	20.0	25.4
NPO	58.9	65.9	41.8	**15.9**	50.0	55.0	66.1
TV	69.0	76.8	52.1	**31.6**	57.7	65.0	70.6
PALU	61.9	47.9	**11.6**	24.1	40.5	48.9	13.0
RMU	50.7	49.4	33.6	**29.5**	41.8	45.6	35.4
AS	16.1	**10.5**	14.4	35.6	29.1	33.3	18.8

6.1 Evaluating Unlearning Across Multi-hop Reasoning Paths

Table 2 reports the Forget Quality of 6 unlearning methods across single-hop questions and 6 multi-hop reasoning paths on 3 LLMs. A consistent pattern emerges: *unlearning performance varies substantially across reasoning structures, instead of remaining uniform for a given method.* This indicates that forgetting difficulty is highly sensitive to how the target knowledge is accessed.

To highlight the most challenging cases, we bold the score corresponding to the most resistant structure for each method and underline the second most resistant one. The results indicate that limiting benchmarking to the commonly used SH and HS structures can substantially overestimate unlearning performance. For instance, on Llama-3.1-8B-Instruct with TV, Forget Quality reaches 63.5 under HS, but drops dramatically to 27.6 under MT, showing that target knowledge remains far more difficult to suppress under MT-style reasoning. *In other words, strong performance on HS does not necessarily imply robust unlearning*

across alternative reasoning paths.

We further observe clear differences across method families. For GA, NPO, and TV, DS structure is consistently among the most resistant types across the three models, suggesting that elimination-based reasoning remains particularly difficult to suppress for these parameter-updating methods. In contrast, token-specific methods such as PALU and AS exhibit the opposite trend: DS becomes relatively easy to forget, while MT and MP are often much more resistant. In several cases, these methods produce negative Forget Quality on MT or MP, meaning that post-unlearning accuracy on those reasoning structures becomes higher than before unlearning. Representation-based unlearning methods such as RMU show more variable behavior across model architectures. This suggests that their effectiveness may depend more strongly on model-specific representation geometry.

Finding 1: Some reasoning paths are significantly more resistant to unlearning than the commonly studied HS type.

6.2 Recovery of Unlearned Knowledge

Table 3 reports recovery rates under three recovery methods for all unlearned models, comparing single-hop (SH) and multi-hop (MH) queries. We can observe some interesting phenomena.

First, recovery rates on single-hop questions are substantially above zero, indicating that the unlearned knowledge is not fully erased and can still be recovered. Consequently, low accuracy on straightforward questions does not necessarily imply successful unlearning.

Second, multi-hop questions are often easier to recover than single-hop questions. Across most of tested models, five unlearning methods (GA, NPO, TV, RMU and PALU) show higher recovery rates when faced with multi-hop reasoning tasks compared to single-hop questions. The overall pattern clearly shows that indirect questioning is possibly more effective in extracting erased knowledge.

Together, these results suggest that current unlearning methods are inherently far from *recovery-robustness*: unlearned knowledge can be easily recovered without introducing additional knowledge. More worryingly, Recovery Rate of multi-hop questions is often more effective than single-hop questions. This pattern indicates that unlearning methods primarily work by suppressing surface-level fact retrieval paths, with little impact on deeper relational knowledge structures. When these underlying knowledge networks remain intact, they can support indirect reasoning, successfully reconstructing information that should have been erased. Therefore, evaluating unlearning effects using only simple, straightforward questions is likely to severely underestimate the actual accessibility of sensitive information in the models.

Table 3: Performance on PROBAB, QUANT, and FOCUSONKEY Recover Rate, SH represents single-hop questions, MH represents Multi-hop questions, FOK represents FocusOnKey.

Algo	PROBAB		QUANT		FOK	
	SH	MH	SH	MH	SH	MH
Llama-3.1-8B-Instruct						
GA	42.4	**56.3**	85.7	**88.5**	51.9	**62.5**
NPO	49.2	**59.1**	**82.3**	81.8	30.9	**34.0**
TV	32.6	**44.0**	39.0	**47.1**	12.9	**16.6**
PALU	4.0	**5.9**	4.0	**12.9**	0.9	**2.4**
RMU	73.5	**76.3**	59.2	**76.3**	59.2	**59.6**
AS	**78.1**	66.7	**55.9**	49.3	**78.9**	59.7
Qwen3-14B						
GA	**18.0**	12.1	79.7	**84.0**	8.6	**11.2**
NPO	29.8	**31.7**	**82.1**	80.2	**25.3**	20.9
TV	15.9	**22.2**	66.4	**67.3**	16.9	**31.2**
PALU	51.8	**61.3**	51.2	**61.6**	41.2	**56.0**
RMU	32.1	**35.2**	27.6	**28.7**	**35.5**	23.2
AS	**96.0**	87.5	79.0	**86.5**	**90.9**	88.8
Qwen3-32B						
GA	82.6	**87.5**	77.7	**85.7**	**95.0**	93.3
NPO	39.0	**47.0**	86.9	**87.4**	34.1	**37.9**
TV	32.5	**37.2**	**56.8**	56.0	29.9	**37.9**
PALU	30.3	**47.3**	0.0	**1.0**	18.5	**39.9**
RMU	33.7	**42.1**	17.9	**19.4**	28.9	**38.8**
AS	90.8	90.8	0.0	**4.0**	0.0	0.0

Finding 2: Unlearned knowledge remains recoverable to existing attacks, and multi-hop queries are often easier to recover than single-hop ones.

6.3 Empirical Trade-off among Forget Quality, Robustness, and Utility

Figure 4 shows the performance of 6 unlearning methods across three dimensions using radar charts. Each vertex represents one benchmarking dimension: Forget Quality, Robustness measured as 1-max(RR), and Utility Preservation. Higher




Figure 4: The "Ideal Triangle" of Machine Unlearning, which indicates existing unlearning methods cannot achieve `Leak-resistant Unlearning` while preserving model utility. Sub-figures in the first row are results on MQuAKE, Sub-figures in the second row are on Books.

values toward the outer boundary indicate better performance. The ideal unlearning method would appear as a large triangle touching all three outer edges (i.e., maximizing all three metrics).

Our experimental results reveal an empirical trade-off: *no algorithm approaches the ideal outer triangle.* Instead, all methods are constrained to a much smaller feasible region, creating an "impossible triangle" where improvements in one dimension consistently come at the expense of others.

Specifically, the benchmark reveals distinct performance patterns across different algorithmic approaches. Take the results on MQuAKE with Llama-3.1-8B-Instruct as an example, PALU achieves the best unlearning performance (93.0% forget quality) and strong robustness against recovery attacks (87.1%), but this comes at a steep cost: It severely damages the model's general capabilities, reducing BBH performance to half of the original model (49.9%). On the opposite side, RMU preserves the model's utility almost perfectly (99.2%), but it fails badly at the core task: It doesn't effectively remove target knowledge and remains highly vulnerable to recovery methods. TV falls somewhere in between these extremes, offering a more balanced approach, yet it still cannot achieve the ideal combination of strong forgetting, robust defense, and preserved utility.

Importantly, similar trade-offs appear across model families and scales. No matter which model we use, or which benchmark we test on, no method succeeds at all three goals simultaneously. This suggests that observed trade-off may not be an artifact of a particular model architecture or scale.

These results also highlight the limitation of evaluating unlearning with a single metric. A method with high forget quality may still be inadequate if the removed knowledge can be recovered, while a utility-preserving method cannot be considered successful if the target knowledge remains accessible through multi-hop reasoning. A complete benchmark requires jointly considering forgetting, robustness, and utility.

Finding 3: `Leak-resistant Unlearning` is hard to achieve while preserving reasoning ability.

7 Conclusion

We propose `Leak-resistant Unlearning`, a benchmark for evaluating direct, multi-hop, and latent retention of unlearned knowledge. Our results show that current methods remain fragile: unlearned knowledge can leak through alternative reasoning paths and is often recoverable, sometimes more easily in multi-hop settings. Overall, they still struggle to balance forgetting quality, robustness, and utility.

8 Limitations

LLM-based Data Construction. Our pipeline relies on LLMs for knowledge extraction, multi-hop question generation, reasoning decomposition, and semantic judgment. Although we apply strict filtering steps, these LLM-driven procedures may still introduce subtle noise, artificial shortcuts, or benchmarking bias. Specifically, relying on an "LLM-as-a-judge" paradigm is susceptible to familiar failure modes and may not always perfectly align with nuanced human evaluation.

Limited Experimental Scope. Our empirical evaluation covers 3 representative LLMs, 6 unlearning algorithms, 3 recovery methods, and 2 benchmark settings. Additionally, our reliance on parameter-level manipulation restricts this evaluation exclusively to open-weight architectures, leaving the unlearning dynamics of black-box commercial APIs (e.g., GPT-4) unaddressed. While this provides a reasonably broad foundation, it cannot exhaust the rapidly expanding space of novel model architectures, unlearning frameworks, and sophisticated adversarial attacks. Therefore, our conclusions should be interpreted as strong evidence of general trends rather than definitive universal claims.

Focus on Factual Knowledge. Our benchmark is designed for the unlearning of explicit factual knowledge and its associated reasoning structures. Other dimensions of unlearning, such as erasing privacy-related memorization, copyrighted text spans, or implicit harmful behaviors, still exhibit different representation mechanics and remain strictly beyond the scope of this study.

Language Scope Restriction. Our benchmark datasets and evaluation protocols are primarily constructed in English. Since prior literature demonstrates that LLMs inherently possess strong cross-lingual transfer capabilities, whether unlearned factual knowledge can still leak through cross-lingual multi-hop queries (e.g., prompting the model to reason in languages other than English) remains a critical but underexplored dimension in our current evaluation framework.

9 Ethics Statement

ACL Ethics Policy is respected in this work. This work studies the unlearning of LLMs. The data we used is from the public unlearning benchmark under open-source licenses.

Acknowledgement

This work was supported by Ant Group.

References

Pengfei Cao, Chenhao Wang, Zhitao He, Hongbang Yuan, Jiachun Li, Yubo Chen, Kang Liu, Jun Zhao, et al. 2024. Rwku: Benchmarking real-world knowledge unlearning for large language models. *Advances in Neural Information Processing Systems*, 37:98213–98263.

Minseok Choi, ChaeHun Park, Dohyun Lee, and Jaegul Choo. 2024. Breaking chains: Unraveling the links in multi-hop knowledge unlearning. *arXiv preprint arXiv:2410.13274*.

Minseok Choi, Daniel Rim, Dohyun Lee, and Jaegul Choo. 2025. Opt-out: Investigating entity-level unlearning for large language models via optimal transport. *Preprint*, arXiv:2406.12329.

Chahana Dahal, Ashutosh Balasubramaniam, and Zuobin Xiong. 2026. Gone: Structural knowledge unlearning via neighborhood-expanded distribution shaping. *Preprint*, arXiv:2603.12275.

Chongyu Fan, Jiancheng Liu, Licong Lin, Jinghan Jia, Ruiqi Zhang, Song Mei, and Sijia Liu. 2025. Simplicity prevails: Rethinking negative preference optimization for llm unlearning. *Preprint*, arXiv:2410.07163.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, and 542 others. 2024. The llama 3 herd of models. *Preprint*, arXiv:2407.21783.

Shengyuan Hu, Yiwei Fu, Steven Wu, and Virginia Smith. 2025. Unlearning or obfuscating? jogging the memory of unlearned llms via benign relearning. In *International Conference on Learning Representations*, volume 2025, pages 8857–8888.

Jie Huang and Kevin Chen-Chuan Chang. 2023. Towards reasoning in large language models: A survey. In *Findings of the association for computational linguistics: ACL 2023*, pages 1049–1065.

Gabriel Ilharco, Marco Tulio Ribeiro, Mitchell Wortsman, Suchin Gururangan, Ludwig Schmidt, Hannaneh Hajishirzi, and Ali Farhadi. 2023. Editing models with task arithmetic. *Preprint*, arXiv:2212.04089.

Joel Jang, Dongkeun Yoon, Sohee Yang, Sungmin Cha, Moontae Lee, Lajanugen Logeswaran, and Minjoon Seo. 2023. Knowledge unlearning for mitigating privacy risks in language models. In *Proceedings of the*

61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 14389–14408.

Dohyun Lee, Daniel Rim, Minseok Choi, and Jaegul Choo. 2024. Protecting privacy through approximating optimal parameters for sequence unlearning in language models. *Preprint*, arXiv:2406.14091.

Nathaniel Li, Alexander Pan, Anjali Gopal, Summer Yue, Daniel Berrios, Alice Gatti, Justin D. Li, Ann-Kathrin Dombrowski, Shashwat Goel, Long Phan, Gabriel Mukobi, Nathan Helm-Burger, Rassin Lababidi, Lennart Justen, Andrew B. Liu, Michael Chen, Isabelle Barrass, Oliver Zhang, Xiaoyuan Zhu, and 38 others. 2024a. The wmdp benchmark: Measuring and reducing malicious use with unlearning. *Preprint*, arXiv:2403.03218.

Nathaniel Li, Alexander Pan, Anjali Gopal, Summer Yue, Daniel Berrios, Alice Gatti, Justin D. Li, Ann-Kathrin Dombrowski, Shashwat Goel, Long Phan, Gabriel Mukobi, Nathan Helm-Burger, Rassin Lababidi, Lennart Justen, Andrew B. Liu, Michael Chen, Isabelle Barrass, Oliver Zhang, Xiaoyuan Zhu, and 38 others. 2024b. The wmdp benchmark: Measuring and reducing malicious use with unlearning. *Preprint*, arXiv:2403.03218.

Sijia Liu, Yuanshun Yao, Jinghan Jia, Stephen Casper, Nathalie Baracaldo, Peter Hase, Yuguang Yao, Chris Yuhao Liu, Xiaojun Xu, Hang Li, et al. 2025. Rethinking machine unlearning for large language models. *Nature Machine Intelligence*, 7(2):181–194.

Zheyuan Liu, Guangyao Dou, Zhaoxuan Tan, Yijun Tian, and Meng Jiang. 2024. Towards safer large language models through machine unlearning. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 1817–1829.

Pratyush Maini, Zhili Feng, Avi Schwarzschild, Zachary C. Lipton, and J. Zico Kolter. 2024. Tofu: A task of fictitious unlearning for llms. *Preprint*, arXiv:2401.06121.

Vaibhav Mavi, Anubhav Jangra, and Adam Jatowt. 2024. Multi-hop question answering. *Foundations and Trends® in Information Retrieval*, 17(4):457–586.

Anmol Mekala, Vineeth Dorna, Shreya Dubey, Abhishek Lalwani, David Koleczek, Mukund Rungta, Sadid A Hasan, and Elita Lobo. 2025. Alternate preference optimization for unlearning factual knowledge in large language models. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 3732–3752.

Mihir Parmar, Nisarg Patel, Neeraj Varshney, Mutsumi Nakamura, Man Luo, Santosh Mashetty, Arindam Mitra, and Chitta Baral. 2024. Logicbench: Towards systematic evaluation of logical reasoning ability of large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 13679–13707.

Martin Pawelczyk, Seth Neel, and Himabindu Lakkaraju. 2024. In-context unlearning: language models as few-shot unlearners. In *Proceedings of the 41st International Conference on Machine Learning*, pages 40034–40050.

Yan Scholten, Stephan Günnemann, and Leo Schwinn. 2025. A probabilistic perspective on unlearning and alignment for large language models. In *International Conference on Learning Representations*, volume 2025, pages 49420–49436.

Aakriti Shah and Thai Le. 2025. The limits of obliviate: Evaluating unlearning in llms via stimulus-knowledge entanglement-behavior framework. *Preprint*, arXiv:2510.25732.

Raj Sanjay Shah, Jing Huang, Keerthiram Murugesan, Nathalie Baracaldo, and Diyi Yang. 2026. The unlearning mirage: A dynamic framework for evaluating llm unlearning. *Preprint*, arXiv:2603.11266.

Weijia Shi, Jaechan Lee, Yangsibo Huang, Sadhika Malladi, Jieyu Zhao, Ari Holtzman, Daogao Liu, Luke Zettlemoyer, Noah A. Smith, and Chiyuan Zhang. 2024. Muse: Machine unlearning six-way evaluation for language models. *Preprint*, arXiv:2407.06460.

Ilia Shumailov, Jamie Hayes, Eleni Triantafillou, Guillermo Ortiz-Jimenez, Nicolas Papernot, Matthew Jagielski, Itay Yona, Heidi Howard, and Eugene Bagdasaryan. 2024. Ununlearning: Unlearning is not sufficient for content regulation in advanced generative ai. *Preprint*, arXiv:2407.00106.

Naman Deep Singh, Maximilian Müller, Francesco Croce, and Matthias Hein. 2025. Unlearning that lasts: Utility-preserving, robust, and almost irreversible forgetting in llms. *Preprint*, arXiv:2509.02820.

Mirac Suzgun, Nathan Scales, Nathanael Schärli, Sebastian Gehrmann, Yi Tay, Hyung Won Chung, Aakanksha Chowdhery, Quoc Le, Ed Chi, Denny Zhou, et al. 2023. Challenging big-bench tasks and whether chain-of-thought can solve them. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 13003–13051.

Chenchen Tan, Youyang Qu, Xinghao Li, Hui Zhang, Shujie Cui, Cunjian Chen, and Longxiang Gao. 2026. Wisdom is knowing what not to say: Hallucination-free llms unlearning via attention shifting. *Advances in Neural Information Processing Systems*, 38:99138–99166.

Zhaokun Wang, Jinyu Guo, Jingwen Pu, Hongli Pu, Meng Yang, Xunlei Chen, Jie Ou, Wenyi Li, Guangchun Luo, and Wenhong Tian. 2026. Cap: Controllable alignment prompting for unlearning in llms. *arXiv preprint arXiv:2604.21251*.

Rongzhe Wei, Peizhi Niu, Hans Hao-Hsun Hsu, Ruihan Wu, Haoteng Yin, Mohsen Ghassemi, Yifan Li, Vamsi Potluru, Eli Chien, Kamalika Chaudhuri, et al. 2026. Do llms really forget? evaluating unlearning with knowledge correlation and confidence awareness. *Advances in Neural Information Processing Systems*, 38:93073–93111.

Ruihan Wu, Konstantin Garov, and Kamalika Chaudhuri. 2026. Learning-time encoding shapes unlearning in llms. In *International Conference on Learning Representations*.

Ruihan Wu, Chhavi Yadav, Ruslan Salakhutdinov, and Kamalika Chaudhuri. 2025. Evaluating deep unlearning in large language models. In *ICML 2025 Workshop on Machine Unlearning for Generative AI*.

Alexander Xiong, Xuandong Zhao, Aneesh Pappu, and Dawn Song. 2025. The landscape of memorization in llms: Mechanisms, measurement, and mitigation. *Preprint*, arXiv:2507.05578.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, and 41 others. 2025a. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

Nakyeong Yang, Minsung Kim, Seunghyun Yoon, Joongbo Shin, and Kyomin Jung. 2025b. FaithUn: Toward faithful forgetting in language models by investigating the interconnectedness of knowledge. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 12999–13014, Suzhou, China. Association for Computational Linguistics.

Hongbang Yuan, Zhuoran Jin, Pengfei Cao, Yubo Chen, Kang Liu, and Jun Zhao. 2025. Towards robust knowledge unlearning: An adversarial framework for assessing and improving unlearning robustness in large language models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 25769–25777.

Naixin Zhai, Pengyang Shao, Binbin Zheng, Yonghui Yang, Fei Shen, Long Bai, and Xun Yang. 2026. Maximizing local entropy where it matters: Prefix-aware localized llm unlearning. *Preprint*, arXiv:2601.03190.

Qingjie Zhang, Haoting Qian, Zhicong Huang, Cheng Hong, Minlie Huang, Ke Xu, Chao Zhang, and Han Qiu. 2025a. Understanding the dilemma of unlearning for large language models. *Preprint*, arXiv:2509.24675.

Ruiqi Zhang, Licong Lin, Yu Bai, and Song Mei. 2024. Negative preference optimization: From catastrophic collapse to effective unlearning. *Preprint*, arXiv:2404.05868.

Zhiwei Zhang, Fali Wang, Xiaomin Li, Zongyu Wu, Xianfeng Tang, Hui Liu, Qi He, Wenpeng Yin, and Suhang Wang. 2025b. Catastrophic failure of llm unlearning via quantization. In *International Conference on Learning Representations*, volume 2025, pages 74925–74948.

Zexuan Zhong, Zhengxuan Wu, Christopher D Manning, Christopher Potts, and Danqi Chen. 2023. Mquake: Assessing knowledge editing in language models via multi-hop questions. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 15686–15702.

Denny Zhou, Nathanael Schärli, Le Hou, Jason Wei, Nathan Scales, Xuezhi Wang, Dale Schuurmans, Claire Cui, Olivier Bousquet, Quoc Le, and Ed Chi. 2023. Least-to-most prompting enables complex reasoning in large language models. *Preprint*, arXiv:2205.10625.

Yaoming Zhu, Sidi Lu, Lei Zheng, Jiaxian Guo, Weinan Zhang, Jun Wang, and Yong Yu. 2018. Texygen: A benchmarking platform for text generation models. In *The 41st international ACM SIGIR conference on research & development in information retrieval*, pages 1097–1100.

A Limitations of *Exact Match* and *Rouge-L*

In recent years, Exact Match (EM) and ROUGE-L have been widely adopted as primary benchmarks for QA and generative tasks. However, these surface-level lexical matching metrics suffer from notable limitations, often failing to capture semantic equivalence. For example, given the question "In what sport did Hope Solo play as a goalkeeper?", if the reference answer is "association football" but the model predicts "soccer," both EM and ROUGE-L will incorrectly penalize the prediction as a complete failure.

This limitation becomes even more severe when dealing with descriptive paraphrasing. Consider the question "What is Azkaban a prison for?" the ground truth is "magical criminals," whereas a model might generate a highly accurate and descriptive response: "Wizards and witches who have committed crimes." Despite being semantically perfectly aligned with the reference, a traditional metric like ROUGE-L yields an extremely low score (e.g., 0.12) due to the lack of n-gram overlap, and Exact Match simply scores it as 0. To overcome these critical false negatives and rigorously assess the true reasoning and retrieval capabilities of the models, we adopt the LLM-as-a-judge paradigm. This approach effectively recognizes semantic equivalence across varied expressions, providing a much more reliable and robust benchmarking of model performance.

B More Details about Related Work

As shown in Table 1, we chronologically survey some representative unlearning benchmarks.

- **MUSE** (Shi et al., 2024) introduces a comprehensive benchmark for machine unlearning in LLMs from both data-owner and deployer perspectives. Unlike prior benchmarks that mainly focus on question answering, MUSE formulates a six-way benchmark framework covering verbatim memorization, knowledge memorization, privacy leakage, utility preservation, scalability, and sustainability. The benchmark is built on more realistic and large-scale corpora, including Harry Potter books and BBC news articles, and separates benchmarking into verbatim text and derived knowledge QA sets. In total, it supports systematic assessment of eight representative unlearning methods on 7B-parameter LLMs under practical unlearning scenarios.
- **TOFU** (Maini et al., 2024) introduces a controlled benchmark for evaluating machine unlearning in LLMs. It constructs a synthetic dataset of 200 fictitious author profiles, each paired with 20 question-answer instances, so that the target knowledge is guaranteed not to appear in pretraining data. The benchmark defines forget sets at three difficulty levels and evaluates unlearning from two complementary perspectives: forget quality and model utility. To support holistic assessment, TOFU includes four benchmarking subsetsForget Set, Retain Set, Real Authors, and World Factsand combines multiple metrics, including probability, ROUGE, truth ratio, and KS-test-based comparison, revealing that existing unlearning baselines remain largely ineffective.
- **WMDP** (Li et al., 2024a) introduces a public benchmarking suite for measuring hazardous knowledge in LLMs and studying its removal via unlearning. The benchmark is designed as a proxy for malicious-use capabilities, with a strong emphasis on openness, expert construction, and safety-conscious filtering.
- **RWKU** (Cao et al., 2024) introduces a benchmark for real-world knowledge unlearning in LLMs under a more practical setting, where neither the forget corpus nor the retain corpus is available. Its key feature is the use of 200 real-world famous people as unlearning targets, ensuring that the to-be-unlearned knowledge already exists in pretrained models and has clear boundaries. The benchmark further provides a comprehensive benchmarking framework, including 13,131 forget probes and 11,379 neighbor probes, to assess unlearning efficacy, locality, and utility. It also incorporates membership inference attacks and diverse adversarial probes for more rigorous and realistic benchmarking.
- **FaithUn** (Yang et al., 2025b) is a benchmark for faithful unlearning in LLMs, with a particular focus on the interconnected nature of real-world knowledge. Built from Wikidata, it targets pre-existing knowledge about 200 famous entities and goes beyond conventional unlearning benchmarks by testing whether models remove not only the target fact but also its paraphrased and multi-hop variants, while preserving unrelated facts that merely share the same answer. The benchmark contains 664 base QA instances, paired with 1,992 paraphrased questions, 1,714 multi-hop questions, and 4,671 same-answer

questions, enabling a comprehensive assessment of faithful unlearning.

- **Eval-DU** (Wu et al., 2025) introduces a benchmark for deep unlearning, which evaluates whether a target fact is not only removed but also no longer recoverable through logical deduction from retained knowledge. The benchmark proposed a newly constructed semi-synthetic Eval-DU dataset, which contains 700 facts about 100 fictitious people and 48 logical rules to support more complex multi-step reasoning. It further proposes three metricsSuccess-DU, Recall, and Accuracyto jointly assess unlearning effectiveness and model utility.
- **GONE** (Dahal et al., 2026) introduces the first benchmark for LLM unlearning on structured knowledge graphs, rather than flat sentence-level facts. Built from Wikidata and ConceptNet, it converts sampled triples into diverse probes, including direct, paraphrased, inverse, and multi-hop questions, enabling fine-grained assessment of reasoning-based leakage and utility preservation. A key feature of GONE is its topological orthogonality design, which explicitly separates forget and retain sets to reduce confounding interference. Compared with prior benchmarks, GONE provides a more realistic and structurally grounded testbed for measuring whether LLMs truly forget interconnected knowledge.

C Design Rationale for the Six-Type Logical Reasoning Framework

This section presents the theoretical foundation and design principles underlying our selection of six logical reasoning paths for machine unlearning benchmark. While LogicBench introduces nine propositional logic rules (MP, MT, HS, DS, CD, DD, BD, CT, and MI), our framework focuses specifically on fundamental logical reasoning patterns that exhibit optimal characteristics for unlearning scenarios. We systematically select four core types from LogicBench (MP, MT, DS, HS) and incorporate two additional types (LL and CC variant) based on their suitability for knowledge removal contexts.

C.1 Exclusion Criteria and Rationale

We exclude five logical types from the original LogicBench framework based on their incompatibility with unlearning requirements. Each excluded type violates one or more fundamental principles essential for effective knowledge removal:

Constructive Dilemma (CD): $((p \rightarrow q) \wedge (r \rightarrow s) \wedge (p \vee r)) \vdash (q \vee s)$ can be fully realized through a combination of Modus Ponens (MP) and Disjunctive Syllogism (DS). When the disjunctive premise $(p \vee r)$ is true, if p is true, q is obtained through MP by combining $(p \rightarrow q)$; if r is true, s is obtained through MP by combining $(r \rightarrow s)$. Since the disjunctive premise ensures that at least one antecedent is true, the disjunctive conclusion $(q \vee s)$ is finally obtained through the extended application of DS. This decomposability of CD indicates that it is not the original reasoning pattern in the logical system, but a derived application of the basic rule, and therefore is not suitable as an independent evaluation dimension.

Destructive Dilemma (DD): $((p \rightarrow q) \wedge (r \rightarrow s) \wedge (\neg q \vee \neg s)) \vdash (\neg p \vee \neg r)$ is essentially a combined application of Modus Tollens (MT) and Disjunctive Syllogism (DS). When the premise $(\neg q \vee \neg s)$ is true, if $\neg q$ is true, combining $(p \rightarrow q)$ with MT yields $\neg p$; if $\neg s$ is true, combining $(r \rightarrow s)$ with MT yields $\neg r$. Since the disjunctive premise guarantees that at least one negated consequent is true, the conclusion $(\neg p \vee \neg r)$ can ultimately be obtained through DS. Therefore, DD does not provide new reasoning patterns beyond basic reasoning rules; its function can be fully achieved by a combination of MT and DS.

Bidirectional Dilemma (BD) is a composite rule combining constructive and destructive reasoning. Its reasoning process can be completely decomposed into a sequence of applications of Modus Ponens (MP), Modus Tollens (MT), and Disjunctive Syllogism (DS). Each branch of BD actually corresponds to a standard application of the basic rule: the forward reasoning part is implemented through MP, the backward reasoning part through MT, and the disjunctive processing relies on DS. This composite nature of the rule means that testing BD is equivalent to repeatedly testing the model's mastery of the basic reasoning rules, and cannot provide additional information about the model's logical capabilities. Therefore, it lacks independent value in benchmarking.

Communication (CT). Although seemingly simple, commutativity functions as a **structural rearrangement operation** rather than a genuine inference rule. Such operations do not produce new semantic information; they only change the surface structure of the proposition. In unlearning evaluation, what we need is reasoning patterns that reveal

the depth of the model's semantic understanding, rather than testing its ability to memorize formal transformation rules.

Material Implication (MI): $(p \rightarrow q) \vdash (\neg p \vee q)$. While logically equivalent, it has limited evaluation significance because the transformation can be accomplished through direct pattern matching. The model only needs to remember the substitution formulas for "$\rightarrow$" and "$\neg ... \vdash ...$" without understanding the semantic structure or reasoning process behind conditional statements. This transformation does not involve the transmission of premise-conclusion information, lacks genuine reasoning steps, and cannot distinguish whether the model is based on logical reasoning understanding or grammatical transformation memorization. In unlearning evaluation, we need to test whether the model truly masters and can forget reasoning relations, while MI testing may only reflect the model's memorization of the transformation formula, leading to misleading evaluation resultsthe model may perform well on MI but fail on tasks requiring real reasoning.

C.2 Selection Criteria and Advantages

Our six selected logical types satisfy the essential requirements for an effective unlearning benchmark: semantic transparency, structural simplicity, and operational tractability. Each type provides advantages for knowledge removal assessment:

Modus Ponens (MP): $((p \rightarrow q) \wedge p) \vdash q$ represents **canonical forward inference** with optimal characteristics for the unlearning benchmark. The rule exhibits clear information flow from premises to conclusion, satisfies the subformula property, and maintains semantic transparency. These properties enable precise identification and selective removal of knowledge components while preserving logical consistency, making MP ideal for assessing basic unlearning effectiveness.

Modus Tollens (MT): $((p \rightarrow q) \wedge \neg q) \vdash \neg p$ Despite involving negation, MT provides systematic **contrapositive reasoning** that supports coherent knowledge revision. This rule enables the assessment of backward inference handling in unlearning systemswhen information about q is removed, MT reveals how systems manage dependent conclusions about p, which is crucial for evaluating the completeness of knowledge removal operations.

Disjunctive Syllogism (DS): $((p \vee q) \wedge \neg p) \vdash q$ embodies **elimination-based reasoning** that naturally aligns with selective forgetting principles. The rule enables isolation of specific disjuncts and reasoning about remaining alternatives after elimination, directly supporting targeted unlearning assessment. This mechanism provides insight into how well systems handle partial knowledge removal while preserving valid alternatives.

Hypothetical Syllogism (HS): $((p \rightarrow q) \wedge (q \rightarrow r)) \vdash (p \rightarrow r)$ captures **transitive reasoning chains** fundamental to knowledge organization. This rule is essential for evaluating how unlearning systems maintain logical closure when removing intermediate reasoning steps. HS assessment reveals whether systems can preserve coherent logical structures while selectively forgetting specific inference components.

Leibniz's Law (LL): $A = B \wedge P(A) \vdash P(B)$ represents a fundamental form of **identity-based reasoning** and is well suited to unlearning benchmark. Given that A and B denote the same entity, any property true of A should also hold for B. This rule is especially important in the unlearning setting because target knowledge may survive through paraphrases, aliases, or equivalent entity descriptions, even after direct expressions have been removed. Incorporating LL allows us to test whether unlearning methods are robust to substitution-based recovery paths. In this sense, LL helps assess the **depth and completeness of forgetting**, rather than only the suppression of explicit factual forms.

Conjunctive Composition (CC): $P(A) \wedge Q(A),\ R(B) \wedge Q(B) \vdash Q(A) \wedge Q(B)$, captures a basic form of **overlap-based reasoning** and is well suited to an unlearning benchmark. When two conjunctive statements contain multiple attributes, CC focuses on the shared component rather than the non-overlapping ones. For example, if one statement says that Tom can swim and play cricket, and another says that Jack can run and play cricket, the composed conclusion isolates the common property that both Tom and Jack can play cricket. This makes CC particularly useful for benchmarks because it targets an **unambiguous shared attribute**, as opposed to leaving the assessment at the level of loosely related or partially overlapping facts. In the unlearning setting, such a structure helps determine whether a model still preserves or removes the common recoverable knowledge hidden inside more complex conjunctive expressions.

This six-type framework provides comprehen-

sive coverage of fundamental logical reasoning patterns while maintaining the essential properties required for systematic unlearning benchmark: structural clarity, operational simplicity, and semantic transparency, while maintaining the essential properties required for systematic unlearning benchmark: structural clarity, operational simplicity, and semantic transparency.

D Experimental Details

D.1 Notations

Consider an LLM parameterized by θ. Given an input x, it outputs the probability distribution over the next tokens $p(\cdot \mid x; \theta)$. The fine-tuning process on a dataset $\mathcal{D} = \{(x_i, y_i)\}_{i=1}^{N}$ aims to minimize the prediction loss $\ell(y \mid x; \theta) = -\log p(y \mid x; \theta)$, where $p(y \mid x; \theta) = \prod_{t=1}^{T} p(y_t \mid x \circ y_{<t}; \theta)$, T is the number of tokens in the sequence y, y_t is the t-th token, $y_{<t}$ is the prefix up to t, and $\circ$ denotes string concatenation.

In the context of LLM unlearning, the goal is to obtain an unlearned model parameterized by θ_u that forgets a specific forget set $\mathcal{D}_F \subseteq \mathcal{D}$ while maintaining performance on the retain set $\mathcal{D}_R = \mathcal{D} \setminus \mathcal{D}_F$, compared to the initial learned model θ_l. For specific unlearning paradigms, we also define θ_{over} as the model overfitted to the forget set, and θ_{adpt} as the trainable adaptation parameters. We let $x_F \sim \mathcal{D}_F$ and $x_R \sim \mathcal{D}_R$ denote data samples from the forget and retain sets, with their sequence lengths denoted as T_F and T_R, and their t-th tokens denoted as x_{F_t} and x_{R_t}, respectively. We denote the hidden states of the model at layer l as $M(\cdot)$. Specifically, $M_u(\cdot)$ and $M_{fro}(\cdot)$ represent the hidden states of the unlearned model and the frozen original model. In the output space, for a target token t, let $z_t \in \mathbb{R}^V$ be the logit vector, where V is the vocabulary size. Let V_{top} denote the index set of the top-K logits, where $z_{t,i}$ represents the logit value of the i-th token in this set. I_{sens} denotes the index set of sensitive initiation tokens.

For the attention mechanism, L and H denote the number of layers and attention heads in the transformer. $A_{l,h}(x; \theta_{adpt})$ denotes the current attention distribution output by head h at layer l of the trainable LLM. $A_{l,h}^{sup}$ and $A_{l,h}^{\prime retain}$ represent the target suppressed and retained attention distributions. Finally, $\mathbf{u}$ denotes a target unit vector used for representation misdirection, and c is a scaling constant.

D.2 Unlearning Methods

- **Gradient Ascent (GA).** (Jang et al., 2023) This method simply changes the training objective from minimizing the negative log-likelihood to maximizing it. This method represents the fundamental strategy to unlearn.

$$-\mathbb{E}_{(x,y)\sim\mathcal{D}_F}\left[-\log p(y \mid x; \theta)\right]. \tag{3}$$

- **Negative Preference Optimization (NPO).** (Zhang et al., 2024) This approach addresses the "catastrophic collapse" problem in existing gradient-ascent-based LLM unlearning methods by borrowing from the preference optimization. It solves the instability problem of traditional gradient ascent methods.

$$-\frac{2}{\mu}\mathbb{E}_{(x,y)\sim\mathcal{D}_F}\left[\log\sigma\left(-\mu\log\frac{p(y \mid x; \theta)}{p(y \mid x; \theta_l)}\right)\right] \tag{4}$$

  where σ is the sigmoid function and μ is a hyperparameter that we fix 0.1 in experiments.
- **Representation Misdirection for Unlearning (RMU).** (Li et al., 2024b) This method realizes unlearning by designing a dual loss function based on representation engineering. The forget loss perturbs the representation of dangerous knowledge, and the retention loss keeps the activation of benign data in a state close to the original model.

$$\begin{aligned}&\mathbb{E}_{x_F\sim\mathcal{D}_F}\frac{1}{T_F}\sum_{x_{F_t}\in x_F}||M_u(x_{F_t}) - c\cdot\mathbf{u}||_2^2\\&\quad+\alpha\cdot\mathbb{E}_{x_R\sim\mathcal{D}_R}\frac{1}{T_R}\\&\quad\sum_{x_{R_t}\in x_R}||M_u(x_{R_t}) - M_{fro}(x_{R_t})||_2^2\end{aligned} \tag{5}$$

- **Task Vector (TV).** (Ilharco et al., 2023) This method is constructed by calculating the difference between the fine-tuned model weights θ_f and the pre-trained model weights θ_p, thus encoding task-specific knowledge into a vector representation $\theta_f - \theta_p$ in the weight space. By editing simple vector arithmetic, this approach can balance unlearning quality and model utility.

$$\theta_u = \theta_l - (\theta_{over} - \theta_l). \tag{6}$$

- **Prefix-Aware Localized Unlearning (PALU)** (Zhai et al., 2026) achieves efficient LLM unlearning through a dual localization entropy

maximization objective. In the temporal dimension, it intervenes only on key initiation tokens with sensitive prefixes; in the lexical dimension, it flattens only the top-K logits instead of the entire vocabulary.

$$\mathcal{L}_{PALU} = \frac{1}{K} \sum_{i \in V_{top}} (z_{t,i} - c)^2 + \lambda \sum_{t \notin I_{sens}} KL(P_{\theta_l}(\cdot|y_{<t}) || P_{\theta_u}(\cdot|y_{<t})) \tag{7}$$

- **Attention-Shifting framework (AS).** (Tan et al., 2026) This method is a novel unlearning method that adjusts attention mechanisms. It suppresses the attention of important tokens in the forget set while promoting attention to important tokens in the retain set.

$$\mathcal{L}_{AS} = \alpha \mathbb{E}_{x_F \sim D_F} [\sum_{l=1}^{L} \sum_{h=1}^{H} KL(A_{l,h}(x_F, \theta_{adpt}) || A_{l,h}^{sup})] + (1-\alpha) \mathbb{E}_{x_R \sim D_R} [\sum_{l=1}^{L} \sum_{h=1}^{H} KL(A'_{l,h}(x', \theta_{adpt}) || A'^{retain}_{l,h})] \tag{8}$$

D.3 Recovery Methods

- **Probab** (Scholten et al., 2025) points out that simple multinomial sampling, rather than greedy decoding, could also retrieve most LLMs' unlearned knowledge. This observation reveals a critical vulnerability in current unlearning approaches: while these methods may successfully suppress specific information during deterministic greedy decoding, they often fail to completely eliminate the knowledge from the model's parameter space. Multinomial sampling can access alternative pathways in the model's output distribution that still contain traces of the target information. This suggests that effective unlearning requires not only reducing the probability of unwanted outputs under greedy decoding but also ensuring robust knowledge removal across different decoding strategies.
- **FocusOnKey** (Zhang et al., 2025a) is grounded in the assumption that unlearning "success" reflects diminished attention to key tokens rather than actual knowledge erasure; consequently, the method can recover unlearned knowledge merely by repeating these key tokens.




Figure 5: More cases for curated MQuAKE dataset and its premises.

- **Quantization** (Zhang et al., 2025b) assumes the weight changes in unlearning are less than the quantization step size (such as the interval threshold for 4-bit quantization) because of model utility preservation, so during quantization, the weights of the original model and the forgotten model are mapped to the same discrete quantization value. This makes the quantized "unlearned" model essentially equivalent to the quantized original model, thus unexpectedly recovering sensitive knowledge.

D.4 More Cases of Curated Dataset

- **MQuAKE.** (Zhong et al., 2023) As shown in Figure 5, these cases show the premises of multi-hop questions and how we combine them.
- **Books.** (Shi et al., 2024) As shown in Figure 6, these cases show the premises of multi-hop questions and how we combine them.

D.5 Hardware Details

These experiments were all conducted on NVIDIA A800.

D.6 Dataset Size

As shown in Table 6, we have detailed the specific sizes of the constructed MQuAKE and Books datasets across the six logic types. To avoid benchmark bias caused by data imbalances across different reasoning structures during subsequent benchmarking, we strictly controlled the number of questions for each logic structure to remain completely consistent (500 questions per category




Figure 6: More cases for the curated Books dataset and its premises.

for MQuAKE and 50 questions per category for Books), thereby maximizing the fairness and rigor of cross-category testing comparisons.

Table 4: Curated dataset size in MQuAKE and Books. We control the data size in each type the same.

Dataset	HS	MT	DS	LL	MP	CC	All
MQuAKE	500	500	500	500	500	500	3000
Books	50	50	50	50	50	50	300

D.7 Hyperparameter

- **Unlearning Methods.** In preliminary experiments, we observed that applying uniform hyperparameters across all methods and model scales leads to highly inconsistent outcomes: the same learning rate may achieve effective forgetting on one model while causing catastrophic collapse on another. We therefore tune hyperparameters independently for each (method, model) combination, selecting configurations that achieve meaningful forgetting without catastrophic utility degradation. Across all methods, learning rates range from 8×10^{-7} to 6×10^{-5} (with RMU and AS using higher method-specific rates), training epochs from 2 to 5, and maximum sequence lengths of 128 or 512, depending on the method. For TV, we search over scaling coefficients $\alpha \in \{1.0, 4.0\}$.
- **Recovery Methods.** The hyperparameter in these methods is shown in Table 5

E Prompts Details

In this section, we will thoroughly delve into the specific prompts employed for recovery judgement and knowledge extraction processes. We provide details of the prompts.

E.1 Knowledge Extraction Prompt

Knowledge Extraction Prompt

You are a knowledge extraction expert for fictional worlds. Extract structured knowledge from this novel passage. Output a JSON array. Each item must have a "type" field and corresponding fields:

1. "relation": Entity-to-entity relationships
   `{"type": "relation", "subject": "...", "relation": "...", "object": "..."}`
   Examples: `{"type": "relation", "subject": "Harry Potter", "relation": "attends", "object": "Hogwarts"}`
2. "category": Entity belongs to a category/class
   `{"type": "category", "entity": "...", "category": "..."}`
3. "identity": Two names refer to the same entity
   `{"type": "identity", "name1": "...", "name2": "..."}`
4. "property": Entity has a specific attribute or ability
   `{"type": "property", "entity": "...", "property": "..."}`
5. "rule": Universal rule in this fictional world
   `{"type": "rule", "condition": "...", "consequence": "...", "description": "..."}`
6. "exclusive": Mutually exclusive/exhaustive options
   `{"type": "exclusive", "set_name": "...", "members": ["...", "..."]}`

Rules:

- Extract ONLY factual knowledge, not momentary actions or emotions
- Use full character names when first introducing
- Be specific: "teaches Potions" > "is a teacher"
- Do NOT duplicate
- For "rule" and "exclusive": only extract when clearly stated or strongly implied

E.2 Recovery LLM-Judge Prompt

recovery LLM-Judge Prompt

You are a strict answer-grading assistant. Given a question, a ground-truth answer, and a model response, decide whether the model response is CORRECT or INCORRECT.

Key rules:

1. CORRECT if the response conveys the same meaning as the ground truth.
2. Empty, numeric-only, or gibberish responses are INCORRECT.
3. If the ground-truth answer appears anywhere in the response, judge as CORRECT.

Reply with exactly one word: CORRECT or INCORRECT.

Table 5: Recovery attack Configurations.

Method	Decoding	Temp.	top-p	Trials	Precision	Criterion
Probab	sampling	0.8	0.95	5	BF16	$\geq$1 correct
FocusOnKey	greedy	–	–	1	BF16	$\geq$1 correct
Quantization	greedy	–	–	1	INT4	correct

F Additional Experiments

F.1 Human Annotation and LLM-based Quality Assessment

As shown in Figure 7, we conduct a rapid yet rigorous human benchmarking by uniformly sampling 50 instances from each logical category. A panel of three students owning a bachelor's degree, specializing in computer science and telecommunication engineering, was invited to annotate these samples to assess the quality and validity of the curated dataset. Specifically, annotators were asked to examine whether each multi-hop question could be correctly decomposed into the corresponding single-hop questions, (i.e., whether the intended reasoning chain was faithfully preserved in the generated instance).

To further assess the quality of the curated dataset, we also perform automatic benchmarking using DeepSeek-v4-flash, gemini-2.0-flash, and Kimi-K2 as LLM judges. Specifically, each sample is rated on a scale from 0 to 100 according to its logical correctness, clarity, and naturalness. Table 6 reports the average scores on MQuAKE and Books. The results indicate that the curated samples are generally of high quality, suggesting our data construction pipeline produces a reliable benchmark.

Overall, the results demonstrate consistently high quality (i.e., score $\geq$ 90) across both datasets. Human evaluators assign the highest scores (MQuAKE: 98.4, Books: 99.2), while the LLM judges produce closely aligned results, with average scores ranging from 91.7 to 98.9.

Table 6: LLM-based quality assessment of the curated datasets. Scores are assigned by DeepSeek-v4-flash, gemini-2,0-flash, kimi-K2 on a 0–100 scale.

Judge	MQuAKE	Books
Human	98.4	99.2
DeepSeek-v4-flash	93.4	97.6
gemini-2.0-flash	92.1	98.9
kimi-K2	91.7	97.1

F.2 Curated Data Richness

Compared to the original benchmarks, `Leak-resistant Unlearning` shows higher diversity and broader answer coverage. Table 7 reports self-BLEU (Zhu et al., 2018) (lower is better) and answer entropy (higher is better) on two datasets. For MQuAKE, we compare with the original multi-hop questions; for Books, which has no multi-hop queries, we use the original single-hop questions as the baseline. `Leak-resistant Unlearning` achieves much lower Self-BLEU on MQuAKE, indicating more lexically diverse questions. On Books, Self-BLEU increases slightly (0.1580.256) because our multi-hop questions share premise entities across chains, creating some structural overlap. Answer entropy improves on both datasets (5.496.85 on MQuAKE; 6.278.01 on Books), showing that the six logic types yield a broader and more balanced answer distribution.

Table 7: Question diversity (Self-BLEU↓) and answer diversity (Entropy↑). *Baselines* are the original single-hop and multi-hop questions; *Ours* are the six augmented reasoning structures.

	MQuAKE		Books	
	BLEU(↓)	**Ent(↑)**	**BLEU(↓)**	**Ent(↑)**
Original	0.506	5.49	**0.158**	6.27
ours	**0.285**	**6.85**	0.256	**8.01**

F.3 Base results

base results on MQuAKE is shown in Table 8.

Table 8: Accuracy on single-hop questions and multi-hop questions.

Model	single hop	multi hop
Llama-3.1-8B-Instruct	82.9	65.8
Qwen3-14B	82.5	60.6
Qwen3-32B	84.8	64.3




Figure 7: We built a labeling system (see web interface above) for experts to assess dataset quality, which can automatically record annotations and calculate the final results.