Trinity: Human–Agent–Environment Alignment for Embodied Task Planning

Hyungmin Kim[1], Hobeom Jeon[1], Dohyung Kim[1,2,*], Jinhyeok Jang[1,2], Minsu Jang[1,2]

[1]University of Science and Technology [2]Electronics and Telecommunication Research Institute
{khm159}@ust.ac.kr {tiger, dhkim008, jjh6297, minsu}@etri.re.kr

Abstract

LLM-based embodied agents are increasingly evaluated on environment-grounded, long-horizon planning, yet existing benchmarks rarely test whether an agent can condition its plans on the specific user it serves. This gap points to a broader limitation in embodied task-planning systems, which often ground their reasoning only in the physical environment while overlooking the diversity of the people they serve. We frame this problem as Planning with Human Attributes (PHA), in which an agent must integrate explicit user information into long-horizon embodied task planning. We introduce Trinity[1], a benchmark designed to evaluate PHA capabilities. Within Trinity, a single instruction can yield different, equally valid, or even opposing outcomes depending on a user's personal attributes. Our experiments reveal that standard off-the-shelf in-context learning-based agents commonly fail at the human-grounding component, whether or not they are provided with relevant examples, highlighting a key obstacle for PHA tasks. Beyond benchmarking, we contribute a bottom-up failure-mode analysis that isolates where and why agents break, and we distill it into concrete, model-agnostic design principles for human-agent-environment (HAE) aligned agents. We hope Trinity brings domestic robots a step closer to becoming trusted, socially acceptable partners.

1 Introduction

Large language models are increasingly used as high-level controllers for embodied agents that plan long-horizon household tasks from natural-language instructions. However, these agents are typically evaluated only on environment grounding, rather than on whether they tailor their plans to the individual user they serve. Such user-aware behavior is also important for trust and social acceptance in human–robot interaction (Macalupu et al., 2025; Barfield, 2023), but it remains largely overlooked in task-centric embodied planning.

Although current embodied task-planning methods (Ichter et al., 2023) effectively translate natural language commands into executable actions, they largely cast humans as mere instruction givers rather than active entities with diverse characteristics (Yang et al., 2024). To address this, planners should model human diversity and adapt their behavior to individual expectations.

While previous research such as Situated Instruction Following (SIF) (Min et al., 2025) and Preference-Based Planning (PBP) (Xu et al., 2025) considered human behaviors or preferences, they overlook broader attributes, such as religious practices, that are difficult to infer from a few human demonstrations (Xu et al., 2025).

In this paper, we introduce **Planning with Human Attributes (PHA)**, as an embodied task in which the agent at each step receives an instruction, a set of human attributes and the trajectory context and then selects an appropriate action. Unlike prior work, PHA explicitly conditions task goals on human attributes. As a result, the same instruction can imply different goals for different individuals (see Figure 1 for an illustrative example).

We present the Trinity benchmark to evaluate embodied agents on their ability to plan actions while accounting for human diversity. Trinity provides two datasets. Agent-Environment alignment (AE) supports evaluation of environmental grounding. Human-Agent-Environment alignment (HAE) assesses human-centered reasoning across 151 unique attribute combinations. This dual-dataset design prevents bias toward either Human-Agent or Agent-Environment alignment. Unlike LLM-based benchmarks (Wu et al., 2023; Yin et al., 2024) that lack reproducibility, Trinity specifies explicit goal conditions and uses reproducible simulation environments.

*Corresponding author

[1]Code and dataset are publicly available at https://github.com/khm159/trinity_etp.

Findings of the Association for Computational Linguistics: EMNLP 2026, pages 4974–5013
October 24-29, 2026 ©2026 Association for Computational Linguistics



Figure 1: Overview of the Trinity benchmark and an example trajectory. (Left) In the Trinity benchmark, the agent must consider various human attributes while addressing user requests in a household environment. (Right) A failure trajectory of the ReAct-IM (Inner Monologue) agent (one of the baseline agents, see Section 4.1 for more details) *with relevant examples*. Although the nut pie contains butter and is therefore unsuitable for a vegan, the agent correctly grounds the task (preparing food on the dresser) but fails to reason about the appropriateness of the item selection.

In summary, our contributions are as follows:

Integrating user diversity with task grounding. We propose PHA, a novel task that integrates individual human characteristics into embodied task planning. In PHA, agents may receive identical instructions, yet the goal conditions adapt dynamically to each user's unique attribute combination. To solve household tasks, the agent must first infer and reason about the user's characteristics before interacting with objects.

Runnable and reproducible benchmark—Trinity. We introduce Trinity, a unified benchmark that measures an agent's ability to adapt to diverse human attributes while executing household tasks, moving beyond environmental grounding. Built on realistic household scenes and everyday objects conditioned on human attributes, Trinity evaluates both planning efficiency and the agent's alignment with complex human characteristics.

Systematic evaluation of embodied LLM agents. We benchmark several current embodied agent architectures on Trinity. Our results show that failures to ground human attributes when interacting with the environment are pervasive, whether or not agents are given relevant examples. This shortcoming highlights the need for the PHA formulation and the Trinity benchmark to support robust human-agent-environment alignment.

Failure-mode diagnosis and design principles. Beyond aggregate success rates, we derive a bottom-up failure taxonomy, analyze how it changes with profile complexity and few-shot adaptation, and translate the dominant patterns into model-agnostic design principles for HAE-aligned agents. These findings show that Trinity can serve not only as a benchmark but also as a diagnostic tool for embodied agents.

2 Related Work

Numerous agent architectures and benchmarks for embodied task planning exist. This section offers a brief overview of the related research, while a detailed literature review is available in Appendix A.

2.1 Embodied Task Planning Benchmarks for Household Environments

Table 1 compares recent embodied task-planning benchmarks. Most existing benchmarks focus mainly on environmental grounding (Shridhar et al., 2020; Shridhar et al.; Li et al., 2023; Choi et al., 2024; Yang et al., 2025), while benchmarks involving human interaction, safety, or collaboration only partially address human grounding (Padmakumar et al., 2022; Gao et al., 2022; Min et al., 2025; Yin et al., 2024; Chang et al., 2025; Xu et al., 2025). DialFRED (Gao et al., 2022) introduce dialogue-based task assistance, and PARTNR (Chang et al., 2025) studies human–robot collaboration, but these benchmarks do not evaluate whether

Benchmark	Human Diversity		Evaluation Features			Environment	
	HA	C. of HA	Env. Grounding	Human Grounding	GC-based Evaluation	Multi Room	HA-aware Objects
ALFRED (Shridhar et al., 2020)	×	×	✓	×	✓	×	×
Alfworld (Shridhar et al.)	×	×	✓	×	✓	×	×
BEHAVIOR-1K (Li et al., 2023)	×	×	✓	×	✓	✓	×
WAH-NL (Choi et al., 2024)	×	×	✓	×	✓	✓	×
EmbodiedBench (Yang et al., 2025)	×	×	✓	×	✓	Δ	×
DialFRED (Gao et al., 2022)	×	×	✓	Δ	✓	×	×
SIF (Min et al., 2025)	×	×	✓	Δ	✓	✓	×
SafeAgentBench (Yin et al., 2024)	×	×	Δ	Δ	Δ	×	×
PARTNR (Chang et al., 2025)	×	×	✓	Δ	✓	✓	×
PBP (Xu et al., 2025)	✓	×	✓	Δ	Δ	✓	×
Trinity (Ours)	✓	✓	✓	✓	✓	✓	✓

Table 1: Comparison of evaluation capabilities and characteristics across existing benchmarks. Abbreviations: Human Attributes (HA), Combinations of Human Attributes (C. of HA), and Goal Condition (GC). Δ indicates partial (insufficient) adoption.

the same instruction should lead to different goal conditions depending on user-specific human attributes. SafeAgentBench (Yin et al., 2024) focuses on commonsense constraints such as safety, but cannot evaluate individualized, user-aware goal conditions. PBP (Xu et al., 2025) supports both environment and human-preference grounding, yet it only focuses on human preference. Also, PBP relies solely on demonstration-based preferences, making it unsuited to capture diverse human attributes (e.g., religion) that are hard to encode through limited demonstrations.

2.2 In-Context-Learning–Based Embodied Task Planning Agent

The embodied task planning is a widely focused topic that makes an agent system that can follow the user instructions to solve the given task while interacting with the environment using a physically embodied agent (Huang et al., 2022; Ichter et al., 2023; Huang et al., 2023; Yao et al., 2023; Song et al., 2023; Rozanov and Rei, 2025; Fu et al., 2025). Among them, our focus is few-shot or zero-shot task planning agent solving the household tasks without extra tool usage (Liu et al., 2025), heavy data collection and retrieval (Zhao et al., 2024a), and a multiple-trial-based agent at the same initial condition (Shinn et al., 2023). Because in real-world scenarios, the data collection and retrieval with physical interaction is a huge burden, and importantly, the multi-trial at identical initial states is not possible for real-world embodied agents such as robots due to irreversible actions such as slicing an object.

Prior embodied task-planning methods focus on aligning agents with their environments by grounding LLMs in physical or textual contexts (Huang et al., 2022; Ichter et al., 2023; Huang et al., 2023; Yao et al., 2023; Shinn et al., 2023; Song et al., 2023; Rozanov and Rei, 2025; Fu et al., 2025). However, to deploy agents that are both technically reliable and socially trustworthy, we need a new layer of alignment that adapts to the unique human attributes of each user. In other words, a comprehensive alignment of Humans, Agents, and Environments—referred to here as "Trinity" alignment—is imperative for delivering embodied agents that can robustly and meaningfully operate in everyday life.

3 Trinity Benchmark: Align Human, Agent, and Environment

3.1 Planning with Human Attributes

In this section, we introduce a novel task formulation called Planning with Human Attributes (PHA), which modifies the Partially Observable Markov Decision Process (POMDP). Specifically, PHA modifies POMDP by introducing a human attribute profile h, provided in natural language, as a distinct additional input. This profile explicitly influences how a given natural language instruction i is interpreted, defining a goal condition $g(h, i)$ expressed as a condition over states. The human attribute profile is distinct from the observation space.

In PHA, an agent operates in a state space $\mathcal{S}$, action space $\mathcal{A}$, and observation space $\mathcal{O}$. Although the agent observes only observations and actions, underlying states s are implicitly inferred from context. At each time step t, the agent receives instruction i, human attributes h, and con-

Splits	Level	PF	PD	PF&D	PH	Total
Train	1	68	34	72	53	227
	2	190	129	154	0	473
	3	142	124	110	0	376
Train Total		400	287	336	53	1,076
Test	1	33	12	42	24	111
	2	54	33	54	0	141
	3	66	47	62	0	175
Test Total		153	92	158	24	427
Overall Total		553	379	494	77	1,503

Table 2: **HAE dataset statistics.** Abbreviations: Prepare Food (PF), Prepare Drink (PD), Prepare Food and Drink (PF&D), and Prepare Hobby (PH).

text $c_t = \{o_1, a_1, \ldots, o_{t-1}, a_{t-1}, o_t\}$, where a_t and o_t denote action and observation. The policy $\pi(a_t|c_t, i, h)$ selects the next action a_t based on c_t, i, and h. The objective is to achieve the goal condition $g(h, i)$ by selecting actions. The distinctiveness of the PHA task lies in conditioning this goal on h, requiring the agent to reason and plan in alignment with complex human profiles and environmental observations simultaneously.

3.2 HAE Dataset

The Human–Agent–Environment (HAE) alignment dataset is designed to evaluate whether agents can reason about diverse and complex human attributes of the service target while generating task plans for household activities. In HAE scenarios, the agent must integrate the user's attributes throughout the planning process—from deciding which objects to use to how the task should be carried out—ensuring that both the selected items and the execution steps align with user-specific constraints. Since meal preparation is a widely adopted task in embodied planning benchmarks (e.g., (Shridhar et al., 2020; Shridhar et al.; Choi et al., 2024)), the HAE dataset includes three core tasks—preparing food, preparing a drink, and preparing both—alongside an additional task involving a hobby-related item.

The HAE dataset comprises 1,076 training samples and 427 test samples, with detailed statistics presented in Table 2. Each sample is categorized into one to three complexity levels, which are defined by the number of human attributes combined in a task, ranging from one to three. Additional information is available in Appendix G.

3.2.1 Human Attributes

Human attributes are fundamental to our proposed Trinity benchmark, yet their broad, complex, and abstract characteristics make them challenging to clearly represent within simulation environments. Developing embodied task-planning agents extends beyond question-and-answer interactions, requiring realistic engagement and strict adherence to real-world constraints. Therefore, reproducible and environmental state-based evaluations become essential. However, fully capturing the extensive diversity of human attributes in simulation is practically infeasible. As an unavoidable choice, we thus focus on fundamental household tasks—"prepare food", "prepare drink", and "prepare food & drink"—and establish representative proxy attributes directly tied to these tasks, measurable through state-based goal conditions. Specifically, we select "allergy" to indicate personal health conditions, "religion" to reflect individual beliefs and mental states, "diet" to represent faith-based or ethical lifestyle choices, and "hobby" to embody personal preferences, introducing the additional task "prepare hobby" for its explicit evaluation.

Allergies play a crucial role in shaping dietary choices, as they affect individuals across all demographics and can pose serious health risks if overlooked (Asher et al., 2006). To ensure clarity and minimize labeling noise, we focus on seven common allergens—fish, meat, nuts, nitrite, sulfite, caffeine, and alcohol—each of which can impose meaningful restrictions on food and drink selection.

Religion is selected as a human attribute because it reflects personal beliefs and mental states. Religious practices often influence dietary behavior by imposing specific restrictions or guidelines on food and drink consumption (Arslan and Aydın, 2024). To capture this aspect, we focus on religions that are both widely practiced and have well-defined dietary rules. Specifically, we include Islam, Hinduism, and Judaism in our benchmark.

Dietary preference reflects both health motivations and ethical values, such as animal welfare or environmental sustainability (D'Souza et al., 2022). We focus on three diets—Vegan, Lacto-Ovo Vegetarian, and Pesco-Vegetarian—within the broader vegetarian, plant-based spectrum. This choice creates subtle but challenging decision points for agents, preventing item-selection shortcuts.

Finally, we include hobbies as a proxy for lifestyle and behavioral patterns. Although hobbies do not directly influence food or drink selection, they offer valuable context about an individual's interests and routines. By including hobbies as a human attribute, we extend the scope of our bench-




Figure 2: Overview of the Trinity Environment and Dataset. (Left) Within the Trinity benchmark, agents are equipped with 7 high-level actions to support task planning. (Middle) The Trinity benchmark is composed of realistic, multi-room houses, with environments containing up to 10 rooms. A total of 95 new objects have been adopted specifically as human attribute-aware items, forcing human-aware reasoning in the agent's decision-making process. (Right) There are three complexity levels in the Trinity benchmark, defined as the number of human attributes, resulting in 151 unique combinations of human attributes.

mark to encompass personal interests and preferences.

Each human attribute imposes constraints on the task goal, often requiring the agent to adjust both its object choices and execution plan. For example, if a Muslim user asks the robot to prepare the drink on the dining table, the agent must identify and serve an appropriate halal beverage while avoiding non-compliant options. A complete specification of restricted object sets is provided in Table 15.

3.2.2 Joint Combination of Human Attributes

Humans cannot be characterized by a single attribute. Rather, each individual embodies multiple attributes. To capture this complexity, the HAE dataset is organized into three levels, each corresponding to the number of human attributes combined within a given task scenario. Although the total number of individual attributes used in this study is relatively small, their combinatorial interactions yield a rich and diverse set of scenarios. By structuring the dataset this way, we aim to evaluate an agent's ability to reason about and align with multiple human attributes while solving the household tasks. In total, the dataset spans 151 unique attribute combinations, and our experiments reveal that existing agents' performance declines as the complexity level increases.

The HAE dataset groups tasks into three complexity levels. Level 1 uses a single attribute—diet, religion, allergies, or hobby. Level 2 combines any two attributes selected from diet, religion, and allergies. Level 3 increases complexity by incorporating all three of these attributes. The hobby attribute is limited to Level 1 because it is orthogonal to the others and does not interact with goal conditions in ways that compound task complexity. We include hobby as an optional axis that demonstrates extensibility beyond food- and drink-related restrictions; our central conclusions about human-grounding difficulty are drawn from the diet, religion, and allergy attributes and do not depend on the hobby subset.

3.3 AE Dataset

The Agent–Environment (AE) alignment dataset serves as a cross-checking dataset, following prior embodied task planning datasets. Unlike HAE, AE omits human attributes and evaluates whether agents can ground natural language instructions into executable action sequences without user-specific considerations. To isolate the effect of human attributes, AE shares the same scene layouts and action interfaces as HAE, so performance differences can be attributed to the presence or absence of human-related information.

It draws inspiration from ALFRED and WAH-NL, which incorporate goal conditions directly into the task instructions. We collected AE data in the Trinity environment using object and task templates derived from ALFRED. Following the setup in Lota-bench (Choi et al., 2024), we selected six tasks—Examine Object in Light, Pick and Place Simple, Pick and Place with Cooling, Pick and Place with Heating, Pick and Place with Cleaning, and Pick and Place with Movable Recep-

Task	Train	Test	Total
Examine Object	1,463	20	1,483
PNP–Simple	1,277	20	1,297
PNP–Movable Receptacle	813	20	833
PNP–Cooling	443	20	463
PNP–Cleaning	231	20	251
PNP–Heating	155	20	175
Total	4,382	120	4,502

Table 3: **AE dataset statistics.** "PNP" denotes pick-and-place.

tacle. The dataset contains 4,382 training samples and 120 validation samples. All AE and HAE instances are solvable, a claim verified by a heuristic task solver. Details appear Appendix F.

3.4 Trinity Environment

To create a realistic environment, we collect scenes from the PROCTHOR-10k dataset (Deitke et al., 2022). This choice offers a more authentic setting compared to the single-room environments used in benchmarks (Shridhar et al., 2020; Shridhar et al.; Yin et al., 2024). For the HAE dataset, we add 95 unique human-attributes conditioned objects sampled from Objaverse (Deitke et al., 2023). Also, we have implemented a high-level controller for the latest version of the AI2THOR simulator (Kolve et al., 2017). Further details are in Appendix E.

4 Experiments and Analysis

We designed three experiments to evaluate how well current agents handle PHA tasks. The first experiment measures an agent's environmental grounding capabilities using the AE dataset. The second, Naive Adaptation (NA), tests whether strong environmental grounding alone transfers to PHA tasks, by providing only AE examples without any PHA-specific demonstrations. The third, Few-shot Adaptation (FA), evaluates in-context learning by providing relevant HAE examples and comparing performance. Similar to previous work (Choi et al., 2024; Fu et al., 2025; Yao et al., 2023), the main metric of the experiments is Task Success Rate (TSR), which checks the final state is appropriate for the given goal condition.

4.1 Agents

We selected agents from popular benchmarks including ALFRED (Shridhar et al., 2020), AlfWorld (Shridhar et al.), and Lota-bench (Choi et al., 2024). See Appendix D for implementation details.

- **Act Agent (Yao et al., 2023):** Serves as a lower-bound baseline by directly selecting the next-step action to achieve the goal condition, without any explicit reasoning process.
- **ReAct Agent (Yao et al., 2023):** A widely adopted agent in which the agent can choose to "Think" or "Act" at each time step, allowing it to engage in a reasoning process before producing the output or selecting its next action.
- **ReAct-IM Agent (Yao et al., 2023; Huang et al., 2023):** This is a step-by-step "Think and Act" version of the ReAct agent. While it can be interpreted as a standard ReAct agent in the context of several text-based tasks, it is originally based on the ReAct-IM agent (Yao et al., 2023), which performs chain-of-thought reasoning guided by feedback signals at every time step.
- **StateAct Agent (Rozanov and Rei, 2025):** A recently introduced architecture that continuously tracks the current state of the agent and the task goal.
- **PreAct Agent (Fu et al., 2025):** An architecture that predicts the next step future trajectory or observation after selecting the next action.

Agents	TSR (%)	Avg. Steps
ReAct	**37.22** $\pm$ 4.83	23.64
ReAct-IM	31.11 $\pm$ 1.42	21.95
StateAct	28.34 $\pm$ 3.12	23.97
PreAct–P	18.89 $\pm$ 1.71	38.82
Act	17.75 $\pm$ 1.06	22.55

Table 4: **AE dataset results.** Values are reported as mean $\pm$ standard deviation over three runs.

4.2 Environment Grounding Only Evaluation

Table 4 reports results on the AE dataset. Among the five agents, ReAct achieves the highest scores and, consistent with (Yao et al., 2023), outperforms ReAct-IM, suggesting that explicit step-by-step reasoning is not always beneficial. Intermediate operations such as future-state prediction (PreAct) or online state tracking (StateAct) are less effective than simpler reasoning. PreAct is especially weak on AE, requiring more steps, as hallucinated future states often contaminate context, derail reasoning, and produce inefficient plans (see Appendix B.1.1). Overall, ReAct and ReAct-IM offer the best performance–efficiency trade-off for environment-grounding-only tasks on AE.

Agent	Setting	L1	L2	L3	AVG
ReAct	NA	18.02 ±2.20	**12.77** ±2.10	**10.48** ±0.71	**13.76**
	FA	22.82 ±2.37	16.31 ±1.53	**16.38** ±1.50	17.48
ReAct-IM	NA	16.22 ±2.21	11.82 ±1.21	9.71 ±1.23	12.58
	FA	**23.42** ±1.95	**17.73** ±0.58	16.00 ±1.23	**18.26**
StateAct	NA	**19.22** ±2.12	9.93 ±1.53	9.14 ±0.00	12.76
	FA	22.22 ±1.12	15.36 ±0.33	15.05 ±1.43	17.07
PreAct	NA	17.72 ±3.48	9.46 ±0.89	8.95 ±1.43	12.04
	FA	22.22 ±2.36	10.40 ±0.67	12.57 ±1.40	15.06
Act	NA	6.01 ±0.85	4.02 ±0.66	3.24 ±0.97	4.42
	FA	16.22 ±2.04	7.56 ±2.04	5.90 ±0.72	9.89

Table 5: **Main results under the NA and FA settings**. TSR is reported as mean ± standard deviation over three runs; AVG values are the average of these means.

4.3 Failure Modes in PHAs

Using a bottom-up approach, we formalize failure types from agent trajectories, classified into six categories within two overarching classes: Human Grounding Failures (HGF) and Environment-Grounding Failures (EGF). Relevant details are provided in Appendix B.2 and Appendix B.3.

We group six failure types into two classes. **Human-Grounding Failures (HGF)**: *Object Selection* (HGF-OS), selecting an item that violates the user profile despite feasible execution; and *Goal Condition* (HGF-GC), misreading the goal, typically by confusing the target object category. **Environment-Grounding Failures (EGF)**: *Physical Constraints* (EGF-PC), ignoring embodiment limits such as the single-arm assumption; *Non-Existent Skills* (EGF-NES), invoking actions outside the API; *Skill Constraints* (EGF-SC), violating skill preconditions, often during navigation; and *Search Failure* (EGF-SF), stopping before exploring all plausible locations. Detailed definitions and examples are provided in Appendix B.2.

4.4 Naive Adaptation Experiments

Before Trinity, no benchmark jointly evaluated environment grounding and planning conditioned on complex user profiles. We therefore test Naive Adaptation (NA), where agents see only AE examples and are evaluated on HAE. As expected, failures are dominated by human-grounding errors in object selection (HGF–OS)—agents frequently choose items that conflict with the user's attributes (e.g., selecting a butter-containing nut pie for a vegan user; Figure 1, right). Our failure analysis confirms that human-grounding failures occur more frequently than environment-grounding failures in most settings (8 out of 12 agent–level settings, see Appendix B.2.2), and HGF–OS is the most common failure mode (ranked first in 8 out of 12 settings, see Appendix B.2.3). These results show that without human-conditioned experience, agents fall back on shortcut reasoning and miss user-specific constraints even in simple household tasks.

ReAct, the best AE performer (Table 4), also achieves the highest NA success on HAE (Table 5), indicating that strong environment grounding is necessary but still insufficient for PHA, as all agents exhibit large human-alignment gaps. EGFs such as incomplete search or invalid "inspect" actions (Appendix B.2.6) remain secondary and are sometimes triggered by human-grounding uncertainty.

To test whether these NA results are specific to *gpt-4o-mini*, we additionally evaluate HAE-NA with two open-source backbones (*Llama 3.3 70B Instruct* and *gpt-oss-120b*) under fixed scaffolds. Larger backbones improve absolute TSR—*gpt-oss-120b* reaches 25.80% average with PreAct—yet remain far from reliable PHA, and the strongest scaffold varies by backbone and setting (Appendix C). Trinity thus diagnoses both human-grounding difficulty and backbone–scaffold interactions.

4.5 Few-Shot Adaptation Experiments

FA evaluates whether agents can adapt to goals conditioned on diverse human attributes, given few-shot examples. While all agents receive the same action demonstrations, only reasoning-based agents are shown examples with explicit reasoning. Without it, Act performs worse—often selecting plausible but misaligned items (e.g., a Coke can for a caffeine-sensitive user. See Appendix B.3.1). This underscores the importance of reasoning for aligning behavior to user-specific needs.

Agents with strong NA performance (ReAct and ReAct-IM) achieve substantial gains in the FA setting. ReAct improves from 13.76% to 17.48%, while ReAct-IM rises from 12.58% to 18.26%, based on average success rates. These gains of




Figure 3: Average failure subtype distributions by level for NA (left) and FA (right). Stacked bars show the mean failure type composition across agents at each level, computed by normalizing each agent's failure subtype proportions to 100% and then averaging without weighting. Agent-wise distributions are provided in Figure 4 and Figure 5.

roughly 5–6 percentage points suggest that combining human-grounded examples with flexible reasoning facilitates effective adaptation. In contrast, agents with rigid reasoning structures, including PreAct and StateAct, show lower average performance than ReAct. Overall, simpler yet expressive reasoning strategies, as demonstrated by ReAct-based agents, support stronger generalization across both AE and PHA tasks.

Few-shot examples improve success but reduce efficiency, prompting agents to reason more thoroughly and explore longer action paths (see Appendix B.5).

Despite these gains, HGFs remain the most prevalent error. In the FA setting, they are the most frequent failure mode in 9 of 12 agent–level combinations (Appendix B.3.2). EGFs also persist, particularly incomplete search (EGF-SF) and physical-constraint misinterpretation (EGF-PC) (Appendix B.3.3). Few-shot examples are therefore helpful but insufficient for generalizing to unseen attribute combinations or fully resolving the alignment problem among agent reasoning, human profiles, and environmental dynamics.

FA trends are not unique to *gpt-4o-mini*. In supplementary comparisons with *gpt-oss-120b* (OpenAI, 2025) and *Llama 3.3 70B Instruct* (AI@Meta, 2024), reasoning-based scaffolds again outperform the direct-action baseline on average, with ReAct-IM remaining the strongest across both backbones in this few-shot (FA) setting; under NA, PreAct becomes the strongest open-source scaffold, with StateAct close behind. Detailed level-wise results are reported in Appendix C.

5 Design Implications for HAE-Aligned Agents

Our failure-mode analysis (Section 4.3) shows that the dominant errors are often loop-like and cumulative. A single human- or environment-grounding mistake can propagate through the rest of the reasoning–action chain, making long-horizon recovery difficult. This motivates two model-agnostic design principles. **First**, agents should verify both the reasoning chain and the selected action before and after execution. Rather than relying on hand-written rules, this verification should score the reasoning text itself against criteria derived from the system specification, for example through a learned reward model. This can help catch human-grounding (HGF-OS/GC) and environment-grounding (EGF-SC/NES/PC) failures. **Second**, agents should track the task-oriented search space with a memory of explored branches, while guarding this memory against hallucinated entities. This can help prevent the reasoning shortcuts that lead to search failures (EGF-SF). Appendix B.4 details these directions, including external-knowledge grounding and fast-recovery mechanisms.

6 Conclusion

This work introduces Trinity, a benchmark for human-agent-environment alignment in embodied planning that emphasizes reasoning over complex user profiles, instruction-conditioned goals, and environment-grounded execution. Current agents struggle to integrate human constraints, often taking shortcuts or misreading goal semantics. Across five in-context-learning agents, experiments show that strong environment grounding is necessary but not sufficient for PHA, as human-grounding errors

remain dominant. These errors most often involve actions that violate the user profile, and they persist even after few-shot adaptation. Building on this analysis, Trinity provides model-agnostic design principles for HAE-aligned agents. We hope it helps measure progress toward embodied agents that plan reliably for individual users.

Limitations

While Trinity marks an important step forward, it has limitations. For reproducibility, it models proxy human attributes (diet, religion, allergy, hobby) as state-verifiable goal conditions and provides them explicitly, which isolates whether an agent can *use* given human information rather than infer it; and it adopts household serving as a representative domain that the same goal-condition design extends to others, such as cleaning or safety-constrained tasks. Importantly, even under these controlled conditions agents still fail substantially at human grounding, indicating that the exposed difficulty is not an artifact of these simplifications. Extending Trinity toward inferred or evolving user attributes and broader domains is a natural direction for future work.

Limitations

While Trinity marks an important step forward, it has limitations. For reproducibility, it models proxy human attributes (diet, religion, allergy, hobby) as state-verifiable goal conditions and provides them explicitly, which isolates whether an agent can *use* given human information rather than infer it; and it adopts household serving as a representative domain that the same goal-condition design extends to others, such as cleaning or safety-constrained tasks. Importantly, even under these controlled conditions agents still fail substantially at human grounding, indicating that the exposed difficulty is not an artifact of these simplifications. Extending Trinity toward inferred or evolving user attributes and broader domains is a natural direction for future work. We discuss the ethical implications of these simplifications in the Ethics Statement below.

Ethics Statement

Human attributes as evaluation proxies. Trinity encodes diet, religion, allergy, and hobby as state-verifiable goal conditions so that human-grounded planning can be measured reproducibly. These are deliberate simplifications for evaluation and are not intended to characterize any real individual or community. The religious rules we encode (Islam, Hinduism, and Judaism) are reduced to a small set of prohibited items, items that would normally require certification are assumed to be certified, and the diet and allergy categories are narrowed to a fixed list. Real practice is far more varied and context-dependent than these proxies.

Trinity is not a safety certification. Some attributes, most notably allergy, are safety-critical in the physical world, yet our goal conditions ignore cross-contamination and other preparation-time hazards that cannot be verified from simulator state. A high score therefore shows only that an agent used the supplied profile consistently in simulation. It is not evidence of safe deployment and should not justify reducing human oversight where an error could harm a user. Since even our strongest agents fail substantially at human grounding, we regard such deployment as premature.

Data and use of AI assistants. All scenes come from existing simulated-environment resources and all user profiles were constructed by the authors. Trinity contains no human-subject data or personally identifying information, and no annotators were recruited. AI assistants were used only for language polishing of author-written text, and all scientific content, experimental design, analyses, and conclusions were produced and verified by the authors. The LLM used to generate AE task instructions is part of our dataset construction method (Appendix F).

Acknowledgments

This work was supported by the Institute of Information & Communications Technology Planning & Evaluation (IITP) grant funded by the Korea government (MSIT) (RS-2024-00336738, Development of Complex Task Planning Technologies for Autonomous Agents, 40%), Development of Uncertainty-Aware Agents Learning by Asking Questions, 30%), and supported by the National Research Council of Science & Technology(NST) grant by the Korea government(MSIT) (No. GTL25042-000, 30%).

References

AI@Meta. 2024. Llama 3 model card.

Sedat Arslan and Ayça Aydın. 2024. Religious dietary practices: Health outcomes and psychological insights from various countries. *Journal of religion and health*, 63(5):3256–3273.

M Innes Asher, Stephen Montefort, Bengt Björkstén, Christopher KW Lai, David P Strachan, Stephan K Weiland, and Hywel Williams. 2006. Worldwide time trends in the prevalence of symptoms of asthma, allergic rhinoconjunctivitis, and eczema in childhood: Isaac phases one and three repeat multicountry cross-sectional surveys. *The lancet*, 368(9537):733–743.

Jessica K Barfield. 2023. Towards diversity, equity, and inclusion in human-robot interaction. In *International Conference on Human-Computer Interaction*, pages 3–17. Springer.

Matthew Chang, Gunjan Chhablani, Alexander Clegg, Mikael Dallaire Cote, Ruta Desai, Michal Hlavac, Vladimir Karashchuk, Jacob Krantz, Roozbeh Mottaghi, Priyam Parashar, Siddharth Patki, Ishita Prasad, Xavier Puig, Akshara Rai, Ram Ramrakhya, Daniel Tran, Joanne Truong, John Turner, Eric Undersander, and Tsung-Yen Yang. 2025. Partnr: A benchmark for planning and reasoning in embodied multi-agent tasks. In *International Conference on Learning Representations*, volume 2025, pages 65205–65268.

Jae-Woo Choi, Youngwoo Yoon, Hyobin Ong, Jaehong Kim, and Minsu Jang. 2024. Lota-bench: Benchmarking language-oriented task planners for embodied agents. In *The Twelfth International Conference on Learning Representations*.

Matt Deitke, Dustin Schwenk, Jordi Salvador, Luca Weihs, Oscar Michel, Eli VanderBilt, Ludwig Schmidt, Kiana Ehsani, Aniruddha Kembhavi, and Ali Farhadi. 2023. Objaverse: A universe of annotated 3d objects. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 13142–13153.

Matt Deitke, Eli VanderBilt, Alvaro Herrasti, Luca Weihs, Kiana Ehsani, Jordi Salvador, Winson Han, Eric Kolve, Aniruddha Kembhavi, and Roozbeh Mottaghi. 2022. Procthor: Large-scale embodied ai using procedural generation. *Advances in Neural Information Processing Systems*, 35:5982–5994.

Clare D'Souza, Anne Renée Brouwer, and Stephen Singaraju. 2022. Veganism: Theory of planned behaviour, ethical concerns and the moderating role of catalytic experiences. *Journal of retailing and consumer services*, 66:102952.

Dayuan Fu, Jianzhao Huang, Siyuan Lu, Guanting Dong, Yejie Wang, Keqing He, and Weiran Xu. 2025. PreAct: Prediction enhances agent's planning ability. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 1–16, Abu Dhabi, UAE. Association for Computational Linguistics.

Xiaofeng Gao, Qiaozi Gao, Ran Gong, Kaixiang Lin, Govind Thattai, and Gaurav S. Sukhatme. 2022. Dialfred: Dialogue-enabled agents for embodied instruction following. *IEEE Robotics and Automation Letters*, 7(4):10049–10056.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, and 1 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Kelly Hong, Anton Troynikov, and Jeff Huber. 2025. Context rot: How increasing input tokens impacts llm performance. Chroma technical report, Chroma Research. Accessed: 2025-07-29.

Wenlong Huang, Pieter Abbeel, Deepak Pathak, and Igor Mordatch. 2022. Language models as zero-shot planners: Extracting actionable knowledge for embodied agents. In *International conference on machine learning*, pages 9118–9147. PMLR.

Wenlong Huang, Fei Xia, Ted Xiao, Harris Chan, Jacky Liang, Pete Florence, Andy Zeng, Jonathan Tompson, Igor Mordatch, Yevgen Chebotar, Pierre Sermanet, Tomas Jackson, Noah Brown, Linda Luu, Sergey Levine, Karol Hausman, and brian ichter. 2023. Inner monologue: Embodied reasoning through planning with language models. In *Proceedings of The 6th Conference on Robot Learning*, volume 205 of *Proceedings of Machine Learning Research*, pages 1769–1782. PMLR.

Brian Ichter, Anthony Brohan, Yevgen Chebotar, Chelsea Finn, Karol Hausman, Alexander Herzog, Daniel Ho, Julian Ibarz, Alex Irpan, Eric Jang, Ryan Julian, Dmitry Kalashnikov, Sergey Levine, Yao Lu, Carolina Parada, Kanishka Rao, Pierre Sermanet, Alexander T Toshev, Vincent Vanhoucke, and 26 others. 2023. Do as i can, not as i say: Grounding language in robotic affordances. In *Proceedings of The 6th Conference on Robot Learning*, volume 205 of *Proceedings of Machine Learning Research*, pages 287–318. PMLR.

Tomoyuki Kagaya, Thong Jing Yuan, Yuxuan Lou, Jayashree Karlekar, Sugiri Pranata, Akira Kinose, Koki Oguri, Felix Wick, and Yang You. 2024. Rap: Retrieval-augmented planning with contextual memory for multimodal llm agents. In *NeurIPS 2024 Workshop on Open-World Agents*.

Eric Kolve, Roozbeh Mottaghi, Winson Han, Eli VanderBilt, Luca Weihs, Alvaro Herrasti, Matt Deitke, Kiana Ehsani, Daniel Gordon, Yuke Zhu, and 1 others. 2017. Ai2-thor: An interactive 3d environment for visual ai. *arXiv preprint arXiv:1712.05474*.

Chengshu Li, Ruohan Zhang, Josiah Wong, Cem Gokmen, Sanjana Srivastava, Roberto Martín-Martín, Chen Wang, Gabrael Levine, Michael Lingelbach, Jiankai Sun, and 1 others. 2023. Behavior-1k: A

benchmark for embodied ai with 1,000 everyday activities and realistic simulation. In *Conference on Robot Learning*, pages 80–93. PMLR.

Yanming Liu, Xinyue Peng, Jiannan Cao, Bo Shi, Yuwei Zhang, Xuhong Zhang, Sheng Cheng, Xun Wang, Jianwei Yin, and Tianyu Du. 2025. Tool-planner: Task planning with clusters across multiple tools. In *International Conference on Learning Representations*, volume 2025, pages 50983–51031.

Valeria Macalupu, Evonne Miller, Lee Martin, and Glenda Caldwell. 2025. Human–robot interactions and experiences of staff and service robots in aged care. *Scientific Reports*, 15(1):2495.

So Yeon Min, Xavi Puig, Devendra Singh Chaplot, Tsung-Yen Yang, Akshara Rai, Priyam Parashar, Ruslan Salakhutdinov, Yonatan Bisk, and Roozbeh Mottaghi. 2025. Situated instruction following. In *Computer Vision – ECCV 2024*, pages 202–228, Cham. Springer Nature Switzerland.

OpenAI. 2025. gpt-oss-120b gpt-oss-20b model card. *Preprint*, arXiv:2508.10925.

Aishwarya Padmakumar, Jesse Thomason, Ayush Shrivastava, Patrick Lange, Anjali Narayan-Chen, Spandana Gella, Robinson Piramuthu, Gokhan Tur, and Dilek Hakkani-Tur. 2022. Teach: Task-driven embodied agents that chat. *Proceedings of the AAAI Conference on Artificial Intelligence*, 36(2):2017–2025.

Devjeet Roy, Xuchao Zhang, Rashi Bhave, Chetan Bansal, Pedro Las-Casas, Rodrigo Fonseca, and Saravan Rajmohan. 2024. Exploring llm-based agents for root cause analysis. In *Companion Proceedings of the 32nd ACM International Conference on the Foundations of Software Engineering*, pages 208–219.

Nikolai Rozanov and Marek Rei. 2025. StateAct: Enhancing LLM base agents via self-prompting and state-tracking. In *Proceedings of the 1st Workshop for Research on Agent Language Models (REALM 2025)*, pages 367–385, Vienna, Austria. Association for Computational Linguistics.

Suyeon Shin, Sujin Jeon, Junghyun Kim, Gi-Cheon Kang, and Byoung-Tak Zhang. 2025. Socratic planner: Self-qa-based zero-shot planning for embodied instruction following. In *2025 IEEE International Conference on Robotics and Automation (ICRA)*, pages 16217–16224.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: language agents with verbal reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 36, pages 8634–8652. Curran Associates, Inc.

Mohit Shridhar, Jesse Thomason, Daniel Gordon, Yonatan Bisk, Winson Han, Roozbeh Mottaghi, Luke Zettlemoyer, and Dieter Fox. 2020. Alfred: A benchmark for interpreting grounded instructions for everyday tasks. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 10740–10749.

Mohit Shridhar, Xingdi Yuan, Marc-Alexandre Cote, Yonatan Bisk, Adam Trischler, and Matthew Hausknecht. Alfworld: Aligning text and embodied environments for interactive learning. In *International Conference on Learning Representations*.

Chan Hee Song, Jiaman Wu, Clayton Washington, Brian M Sadler, Wei-Lun Chao, and Yu Su. 2023. Llm-planner: Few-shot grounded planning for embodied agents with large language models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 2998–3009.

Nikhil Verma and Manasa Bharadwaj. 2025. LEAP & LEAN: Look-ahead planning and agile navigation for LLM agents. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 6: Industry Track)*, pages 896–933, Vienna, Austria. Association for Computational Linguistics.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc V Le, and Denny Zhou. 2022. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems*, volume 35, pages 24824–24837. Curran Associates, Inc.

Zhenyu Wu, Ziwei Wang, Xiuwei Xu, Jiwen Lu, and Haibin Yan. 2023. Embodied task planning with large language models. *arXiv preprint arXiv:2307.01848*.

Manjie Xu, Xinyi Yang, Wei Liang, Chi Zhang, and Yixin Zhu. 2025. Learning to plan with personalized preferences. *arXiv preprint arXiv:2502.00858*.

Rui Yang, Hanyang Chen, Junyu Zhang, Mark Zhao, Cheng Qian, Kangrui Wang, Qineng Wang, Teja Venkat Koripella, Marziyeh Movahedi, Manling Li, Heng Ji, Huan Zhang, and Tong Zhang. 2025. EmbodiedBench: Comprehensive benchmarking multi-modal large language models for vision-driven embodied agents. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 70576–70631. PMLR.

Zonghan Yang, An Liu, Zijun Liu, Kaiming Liu, Fangzhou Xiong, Yile Wang, Zeyuan Yang, Qingyuan Hu, XinRui Chen, Zhenhe Zhang, Fuwen Luo, Zhicheng Guo, Peng Li, and Yang Liu. 2024. Towards unified alignment between agents, humans, and environment. In *ICLR 2024 Workshop on Large Language Model (LLM) Agents*.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023. React: Synergizing reasoning and acting in language

models. In *International Conference on Learning Representations (ICLR)*.

Sheng Yin, Xianghe Pang, Yuanzhuo Ding, Menglan Chen, Yutong Bi, Yichen Xiong, Wenhao Huang, Zhen Xiang, Jing Shao, and Siheng Chen. 2024. Safeagentbench: A benchmark for safe task planning of embodied llm agents. *arXiv preprint arXiv:2412.13178*.

Kechi Zhang, Jia Li, Ge Li, Xianjie Shi, and Zhi Jin. 2024. CodeAgent: Enhancing code generation with tool-integrated agent systems for real-world repo-level coding challenges. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 13643–13658, Bangkok, Thailand. Association for Computational Linguistics.

Andrew Zhao, Daniel Huang, Quentin Xu, Matthieu Lin, Yong-Jin Liu, and Gao Huang. 2024a. Expel: Llm agents are experiential learners. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 19632–19642.

Qi Zhao, Haotian Fu, Chen Sun, and George Konidaris. 2024b. EPO: Hierarchical LLM agents with environment preference optimization. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 6401–6415, Miami, Florida, USA. Association for Computational Linguistics.

A Detailed Review of the Related Work

A.1 Embodied Task Planning Benchmarks for Household Environments

ALFRED (Shridhar et al., 2020) is among the most widely utilized benchmarks in embodied AI research, offering a comprehensive dataset in which agents execute tasks within simulated single-room environments. Despite its broad adoption, the primary limitation of the ALFRED lies in its restriction to single-room scenarios, thus reducing its representativeness of real-world household settings.

Alfworld (Shridhar et al.) extends ALFRED by introducing parallel text-based and embodied environments. It provides textual world-state feedback to the agent, enabling LLMs to better understand environmental conditions and formulate feasible plans. Nonetheless, as Alfworld is a subset of ALFRED, it inherits similar constraints, notably the lack of complexity due to its single-room settings.

WAH-NL dataset (Choi et al., 2024) addresses limitations of ALFRED by introducing multi-room household scenarios, enabling more realistic and complex task planning evaluations. Despite its improvements in realism, WAH-NL still lacks consideration of human-centric factors such as individual variability or social norms in task execution.

TEACh (Padmakumar et al., 2022) studies embodied task completion through human–human interactive dialogues, where a commander provides information and a follower executes household tasks in simulation. DialFRED (Gao et al., 2022) similarly extends ALFRED with dialogue by allowing agents to ask task-relevant clarification questions. These benchmarks are valuable for evaluating communication, ambiguity resolution, and language grounding, but they do not model user-specific human attributes as inputs that change the valid goal condition. In contrast, Trinity evaluates whether agents adapt the task goal itself to the served user's attributes.

BEHAVIOR-1K (Li et al., 2023) provides a large-scale embodied AI benchmark with 1,000 everyday activities in realistic simulated environments. It is valuable for evaluating activity execution, physical interaction, and long-horizon manipulation, but it does not condition task goals on user-specific profiles or human attributes. Therefore, it cannot evaluate whether the same request should lead to different goal conditions for different users, which is the central focus of Trinity.

EmbodiedBench (Yang et al., 2025) provides a comprehensive vision-driven MLLM benchmark across high- and low-level embodied tasks, offering fine-grained evaluations of capabilities such as visual perception, spatial awareness, and long-horizon planning. It is useful for measuring multimodal perception and environmental grounding, but its tasks are not conditioned on personal attributes such as diet, allergy, religion, or hobby. Trinity is complementary because it tests whether agents jointly ground the environment and a user-dependent goal.

PARTNR (Chang et al., 2025) evaluates planning and reasoning in human–robot collaborative household tasks, emphasizing coordination under spatial, temporal, and heterogeneous capability constraints. Although PARTNR explicitly involves a human collaborator, the human is modeled mainly as a partner in task execution rather than as an individual whose attributes redefine the task goal. Thus, it does not address PHA-style alignment, where user-specific attributes determine what outcome is valid.

SIF (Situational Instruction Following) (Min et al., 2025) is an embodied task-planning benchmark that emphasizes verbal uncertainty and dynamic environmental changes caused by human intervention. As pioneering research, SIF explicitly incorporates the "human" element into the environment, creating more realistic human-robot interaction scenarios. However, it still adopts a generalized approach—assuming it doesn't matter who the individual is—and therefore does not account for the unique characteristics of different users.

SafeAgentBench (Yin et al., 2024) is a recent benchmark centered on safety constraints, featuring three task categories: abstract, detailed, and long-horizon. In abstract and detailed tasks, agents must detect and refuse hazardous or inappropriate plans, while long-horizon tasks test continual compliance with safety constraints over extended executions. However, like ALFRED, SafeAgentBench is confined to single-room AI2-THOR environments and does not provide explicit instruction–goal pairs. Instead, it relies on LLMs to evaluate the resulting action trajectories, which can yield inconsistent and non-reproducible assessments.

PBP(Preference-based Planning) (Xu et al., 2025) is a recent benchmark that centers on personal preference constraints by requiring agents to infer user preferences during a "watching stage" of human demonstrations. Although PBP effectively models preference-based attributes, it depends on this demonstration phase. In contrast,

many real-world human attributes—such as religious practices or dietary restrictions—cannot be conveyed through a few demonstrations. Our benchmark is orthogonal to PBP: it evaluates a broader range of human attributes and their combinations without relying on any demonstration stage.

A.2 In-Context-Learning–Based Embodied Task Planning Agent

As a pioneering high-level planning approach for household tasks, the zero-shot planner (Huang et al., 2022) treats an LLM as a likelihood-based policy model, leveraging the model's own next-token probabilities to select actions in an interactive loop. Earlier efforts, such as SayCan (Ichter et al., 2023), couple an LLM with robotic manipulation skill models, where the LLM proposes possible next actions, and a value function filters them. Huang et al. introduced Inner Monologue (Huang et al., 2023), which keeps the LLM continuously "in the loop" by incorporating real-time feedback—like scene descriptions, vision signals, and success or failure detection-into the prompt. Yao et al. proposed the ReAct framework (Yao et al., 2023), which interweaves reasoning and acting by prompting the LLM to generate a chain-of-thought explanation along with each next action, thus allowing the model to reason on the current state and predict outcomes before executing an action. More recently, Song et al. developed LLM-Planner (Song et al., 2023), a few-shot hierarchical planner that produces multi-step task plans and refines these plans dynamically based on the agent's progress and visual feedback. Socratic Planner(Shin et al., 2025) combines self-questioning and answering to decompose the initial instruction into sub-goals, then uses dense visual feedback to repair or refine the plan on the fly, enabling the robot to generate—and iteratively improve—a complete solution.

ReAct's robust reasoning, together with a simple architecture that adapts easily to new tasks, has made it the de facto standard for agent design in domains such as question answering (Yao et al., 2023), code generation (Zhang et al., 2024), software engineering (Roy et al., 2024), embodied task planning (Rozanov and Rei, 2025; Fu et al., 2025), and cooperative agents (Chang et al., 2025). Building on this foundation, recent work has enriched ReAct's reasoning loop to produce more contextually grounded action sequences. For example, Fu et al. introduced PreAct(Fu et al., 2025), which augments ReAct with a "prediction" phase that simulates the potential outcomes of candidate actions—enabling more strategic and confident decision-making. Similarly, LEAP and LEAN (Verma and Bharadwaj, 2025) propose simulating multiple possible actions to collect intermediate observations at each step, allowing the evaluation of top-N high-value actions. However, such approaches are largely impractical in real-world environments, as they require actually executing and reverting actions—an infeasible process for irreversible operations (e.g., object slicing). Moreover, real-world state transitions are inherently non-deterministic, further complicating accurate simulation. Rozanov et al. proposed StateAct (Rozanov and Rei, 2025), a framework that continuously monitors the agent's current state and goal conditions to support embodied planning without dependence on external tools.

B Additional Discussions

B.1 Environment Grounding Only Evaluation

This section presents a detailed analysis of the environment-grounding-only setting on the AE dataset. We identify key weaknesses introduced by baseline design choices for agent–environment grounding. We also find that several explicit reasoning strategies common in recent agent designs can degrade agent–environment alignment, and we analyze the associated failure modes, including those of ReAct. In each experiment, we analyze a random 10% of failure trajectories from the first execution trial.

B.1.1 Context contamination from hallucinated future-state predictions.

Among the failure cases, we observe abnormal "think" steps driven by hallucinated future-state predictions. The PreAct-p agent (Fu et al., 2025) is the second-worst performer on the AE dataset in our experiments—outperforming the Act agent, our lower-bound baseline, by only 1.14%—despite its additional explicit "prediction" step. Although future-state prediction with reflective insights is a promising idea, in many traces the predicted state improperly incorporates the *effects* of the current action and is tightly coupled to the goal condition (see Listing 1 for a detailed example).

The predictions also often posit unobserved yet possible object *states* (e.g., asserting that a movable receptacle already contains other objects). When such hallucinated states are injected into the con-

text, subsequent reasoning diverges from the actual environment and yields inefficient plans (see Listing 2). More broadly, contaminated context can cause the agent to believe that objects or receptacles not yet searched have already been searched by mistakenly treating the predicted context as ground truth.

Overall for PreAct-p, the dominant failure mode is context contamination by hallucinated predictions (54.55%). Additional errors include incorrect reasoning about physical constraints (e.g., planning as if the robot had *dual* arms when it does not; 18.18%) and object-search failures (9.09%). The remaining cases are due to unmet goal conditions (e.g., attempting to "examine in light" without holding the object) and flawed initial plans (e.g., deciding to cool an apple using a microwave, leading to error accumulation).

These contamination effects align with recent work showing that longer inputs make LLMs less reliable and more sensitive to distractors and haystack structure (Hong et al., 2025). In principle, a prediction step could constrain or prune context, but in our experiments speculative predictions often inject additional assumptions, which lengthens the working context and exacerbates spurious content accumulation.

Listing 1: Action-effect reasoning contamination from hallucinated future-state predictions. Despite successful execution of "put down Apple (1)", the PreAct-P agent misinterprets the outcome due to an injected failed prediction from a previous step.

```
Your task is to: Put a heated
apple in the garbage can.

...

You see : CellPhone (1),
GarbageCan (1), Microwave (1),
Apple (1), Book (2-4), Plate (1),
 CounterTop (1), Pen (1),
DiningTable (1), Chair (1), Chair
 (2), Chair (4), Chair (5),
SaltShaker (1), Fridge (1), Pot (
1), Mug (1), CreditCard (1).
Microwave (1) is opened. I am
holding Apple (1) now.

Think: Now that the Microwave (1)
 is open, I can place Apple (1)
inside to heat it. After heating,
 I will head to the Garbage Can (
1) to dispose of the apple as per
 the task requirements.

Act: put down Apple (1)

Predict: 1. I put down Apple (1)
inside Microwave (1). The next
step is to close the microwave
and turn it on to heat the apple.

2. I fail to put down Apple (1) inside
Microwave (1). I will check if there are
any space constraints or obstacles
preventing me from placing the apple.

You put down Apple (1). You see :
CellPhone (1), GarbageCan (1),
Microwave (1), Apple (1), Book (2
-4), Plate (1), CounterTop (1),
Pen (1), DiningTable (1), Chair (
1), Chair (2), Chair (4), Chair (
5), SaltShaker (1), Fridge (1),
Pot (1), Mug (1), CreditCard (1).
 Microwave (1) is opened.
I am not holding anything now.

Think: I attempted to put down
Apple (1) inside Microwave (1),
but I am still holding it. It might be
that there isn't enough space or some
other issue preventing me from placing
it inside. However, the microwave
is open, so I need to check if I
can place Apple (1) again. I will
 try to put it down carefully and
 see if that allows me to place
it inside the microwave
successfully.

Act: put down Apple (1)

...
```

Listing 2: Example of object-state contamination caused by hallucinated future-state predictions. An injected prediction from an earlier step leads the LLM to believe that the remote control is inside Box (1); as a result, the PreAct-P agent does not check the box and skip required intermediate action steps.

```
Your task is to: Put a box with
the remote control in it on the
armchair.
```

```
...

You arrive at Bedroom (1). You
see : DogBed (1), DiningTable (1)
, Bed (1), GarbageCan (1),
Dresser (1). I am not holding
anything now.

Think: Now that I've returned to
Bedroom (1), I need to check the
previously found furniture again
to ensure I don't overlook the
box with the remote control. I
should start with the DiningTable
 (1) since it was the first piece
 of furniture I encountered in
this room.

Act: go to DiningTable (1)

Predict:
1. I check the DiningTable (1) and find
the box with the remote control,
allowing me to pick it up and
then go to the armchair in
LivingRoom (1) to place it down.
2. I do not find the box in
DiningTable (1), which implies
that I need to explore other
areas again, likely starting with
 Bedroom (1) where I can cross-
check my findings.

You arrive at DiningTable (1).
You see : Mug (1), DiningTable (1
), Chair (1-2), Bed (1), Box (1),
HousePlant (1), GarbageCan (1),
Dresser (1). I am not holding
anything now.

Think:
I have finally found the Box (1) while
 checking DiningTable (1) in
Bedroom (1). I need to pick up
the box and then go to the
armchair in LivingRoom (1) to
place it down.

Act: pick up Box (1)

Predict: 1. I successfully pick up
Box (1), and the next step will
be to go to the armchair in
LivingRoom (1) to put it down. 2.
 I fail to pick up Box (1). I
will need to try again to pick up
 Box (1) or check if it can be
accessed differently.

You pick up Box (1). You see :
Mug (1), DiningTable (1), Chair (
1-2), Bed (1), Box (1),
HousePlant (1), GarbageCan (1),
Dresser (1). I am holding Box (1)
 now.

Think:
I have successfully picked up Box (1)
which contains the remote control. Next
, I need to go to the LivingRoom
(1) and specifically to the
ArmChair (1) where I will put
down the box.

Act: go to LivingRoom (1)

...
```

B.1.2 Key observations on agent–environment alignment (ReAct).

On the AE dataset, the ReAct agent's dominant failure mode is failure to locate the object or its target receptacle (57.14%). The next most common error is selecting a nonexistent skill, which yields mismatched actions from skill set driven from observation (14.28%; e.g., issuing `inspect/examine` when that skill is unavailable). We also observe initial reasoning failures (14.28%) and violations of skill preconditions/constraints (14.28%; e.g., attempting to `put down` an object onto a visible receptacle without first navigating to and specifying the target receptacle). These patterns suggest concrete opportunities to improve search procedures, action-set validation, and precondition checking in ReAct-style agents.

Although the agent is provided with the full set of available actions, the feedback after each action, and a room layout that lists all room names and the static receptacles in each room, it often *forgets* this context over the course of multiple interactions. A promising direction is to *explicitly validate* each generated next-step action token so that

it satisfies the environment interface constraints, including whether the action actually exists and whether required arguments and preconditions are met. In parallel, the agent should maintain generic subgoal-level state that tracks key information such as progress in object search and locations already visited, and this tracking should remain domain agnostic rather than relying on task-specific heuristics. Because early mistakes tend to compound, strong initial reasoning is crucial, and the agent ought to re-evaluate its initial plan before execution to catch inconsistencies and reduce downstream error accumulation.

B.2 Failure Modes in the Naive Adaptation Scenario

As discussed in the main manuscript, contemporary embodied task-planning agents are primarily optimized for Agent–Environment (AE) alignment. Because in-context learning-based agents are strongly shaped by the examples provided, an agent exposed only to AE-alignment demonstrations can be deployed on the PHA tasks introduced in this paper without any PHA-specific guidance. The Naive Adaptation (NA) experiment instantiates this setting. We give AE-only in-context examples to agents but evaluate on PHA tasks to assess how current agents respond and whether they can handle PHA without additional adaptation.

B.2.1 Taxonomy of failure modes.

We collect failure types from execution trajectories and organize them in a bottom-up manner. After classification we group them into six categories. The Act agent is excluded from this analysis because it has no explicit reasoning step which makes its intent hard to infer and its overall performance is too low.

- **Human Grounding Failure (reasoning about Object Selection) (HGF-OS)**. This is the dominant type in the NA experiment. In most runs HGF-OS is the primary failure. It reflects errors in reasoning for selecting items that depend on human attributes. For example the agent picks an alcoholic beverage for a Muslim user.

- **Human Grounding Failure (goal condition reasoning) (HGF-GC)**. The agent fails to correctly interpret the goal condition specified by the instruction, often misunderstanding what constitutes a valid outcome under the user-conditioned constraints. This includes confusing the intended target category or selecting objects that are inconsistent with the semantic requirements of the task. For example, the agent may treat a prepare drink" request as a generic prepare something" goal, retrieving food items instead of beverages (or vice versa), thereby violating the instruction-level goal condition even when the physical pick-and-place actions are executed correctly.

- **Environment Grounding Failure (ignoring Physical Constraints) (EGF-PC)**. The agent misunderstands its physical limitations. In our environment the agent is a mobile manipulator with a single arm. Many cases plan as if the robot had dual arms.

- **Environment Grounding Failure (selecting Non-Existent Skill) (EGF-NES)**. The agent selects an action that is not in the skill set (see Appendix D.1.3 for skill set generation and matching details) such as "inspect object". We classify this as an environment-grounding failure yet it is often triggered by uncertainty in human grounding. When the agent is unsure whether an object is acceptable for the user it attempts extra behaviors such as inspection which violates rules that encode environment constraints (check Appendix D.1.1 for list of available skills).

- **Environment Grounding Failure (violating Skill Constraints) (EGF-SC))**. The agent ignores preconditions in the skill definitions. Most cases involve navigation. The robot cannot go directly to a target object and must move to the appropriate room first. Under our skill-matching strategy where skills are derived from partial observations and affordances an invalid choice is mapped to a random action which leads to error accumulation.

- **Environment Grounding Failure (Searching Failure) (EGF-SF)**. The agent does not visit all plausible locations. It fails to find the target object and terminates early.

B.2.2 Limitations of Agents in Human Grounding with Only AE Examples

Agents suffer from human grounding with only AE examples. In Table 6 we report detailed failure

Table 6: Failure-mode breakdown on NA experiments by agent and complexity level (%). The Act agent is omitted (see Appendix B.2.)

	ReAct			ReAct-IM			PreAct			StateAct		
Level	1	2	3	1	2	3	1	2	3	1	2	3
HGF-OS	44.44	58.38	66.67	33.33	66.67	60.00	55.56	54.55	26.67	22.22	50.00	26.67
HGF-GC	22.22	8.33	13.33	0.00	0.00	13.33	0.00	18.18	26.67	11.11	0.00	6.67
HGF total	66.66	66.71	80.00	33.33	66.67	73.33	55.56	72.73	53.34	33.33	50.00	33.34
EGF-PC	11.11	0.00	0.00	11.11	0.00	0.00	11.11	0.00	6.67	22.22	25.00	6.67
EGF-NES	11.11	25.00	0.00	0.00	16.67	0.00	22.22	9.09	26.67	0.00	25.00	40.00
EGF-SC	0.00	0.00	6.67	11.11	8.33	0.00	11.11	9.09	6.67	22.22	0.00	0.00
EGF-SF	11.11	8.33	13.33	44.44	8.33	26.67	0.00	9.09	6.67	22.22	0.00	20.00
EGF total	33.33	33.33	20.00	66.66	25.00	26.67	44.44	27.27	46.68	66.66	50.00	66.67

Values are percentages. Decimal points are aligned for readability.




Figure 4: NA failure type distributions for each agent

statistics. In eight of twelve agent-level combinations human-grounding failures HGF are more frequent than environment-grounding failures EGF. Under NA agents struggle with human-grounded reasoning, including human-centric item selection and goal interpretation. The pattern appears even in basic household tasks when no human-grounding exemplars are provided. These findings highlight the value of evaluating PHA tasks to spur development of agents aligned with both human and environment constraints.

B.2.3 Failure to Integrate Human Profiles, Goals, and Environment Grounding (HGF-OS)

HGF–OS reflects a breakdown in Trinity alignment, as agents fail to simultaneously account for the user's complex human profile, the goal conditions implied by the instruction, and the environment-grounded execution required for pick-and-place interactions. Under the NA setting, such failures are pervasive across agents and complexity levels, making HGF–OS the dominant error type in the majority of agent–level combinations. This pattern suggests that exposure only to AE demonstrations biases agents toward environment-only objectives and encourages shortcut heuristics, rather than verifying whether the selected object satisfies the user-conditioned goal. For example, in Listing 3, the agent selects `BeefMeatloafCan` for a user who practices Hinduism; although it executes the physical pick-and-place sequence correctly, it fails to detect the conflict between the item and the user's profile, ultimately violating human–agent–environment alignment.

B.2.4 Difficulties in Reasoning About Verbally Specified Goal Conditions (HGF-GC)

Agents struggle to reason about verbal uncertainty without relevant examples (HGF-GC). Goal-condition understanding often hinges on implicit human intent that may be unstated or compressed into terse wording, which obscures the intended constraint. In our experiments agents frequently misclassified the tasks prepare food and prepare drink. When users issue brief requests that omit the food versus drink distinction agents often choose the wrong category. Despite this HGF-GC

is generally less prevalent than HGF-OS, underscoring that the most critical failures arise from human alignment across diverse user attributes. Listing 4 shows an example of HGF-GC.

Listing 3: Example of HGF-OS in PreAct

```
Your task is to: Please place the
 food on the dresser.
The characteristics of the person
 you are to serve are as follows:
 The person has nuts allergies
and believes in Hinduism.

...

You arrive at Fridge (1). You see
 : Microwave (1), Fridge (1),
DiningTable (2), CounterTop (1).
I am not holding anything now.

Think: I have arrived at the
Fridge (1) but I cannot see any
food items directly. I need to
open the fridge to check if there
 are any safe food items for the
person with nut allergies. Since
I have not yet found food, my
next step will be to open Fridge
(1) and examine its contents.

Act: open Fridge (1)

Predict: 1. I open Fridge (1) and
find safe food items that I can
place on the Dresser (1). The
next step will be to pick up that
 food. 2. I fail to open Fridge (
1) or find no food inside. I will
 then check DiningTable (2) for
any food items.

You see : BeefMeatloafCan (1),
FlatWhiteLattee (1),
MountainDewSodaCan (1), Microwave
 (1), DiningTable (2),
AmericanoCup (1), Fridge (1),
ASAHISuperDryBeerCan (1),
CounterTop (1). Fridge (1) is
opened. I am not holding anything
 now.

Think: Now that I've opened the
fridge, I can see the food items
inside. The person has nut
allergies, so I need to ensure
that I select food items that do
not contain nuts.
The Beef Meatloaf is likely safe,
while the Flat White Latte may
potentially contain nuts.
It's best to pick the Beef Meatloaf for
placement on the dresser. My next step
will be to pick up the Beef Meatloaf.

Act: pick up BeefMeatloafCan (1)

Predict: 1. I pick up the
BeefMeatloafCan. The next step
will be to go to the Dresser (1)
to place it down. 2. I fail to
pick up the BeefMeatloafCan. I
will check if I can pick up
FlatWhiteLattee instead.

...
```

Listing 4: Example of HGF-GC in ReAct

```
Your task is to: Please place the
 food on the counter top.
The characteristics of the person
 you are to serve are as follows:
 The person has fish allergies,
follows a lactoovovegetarian diet
 and believes in Judaism.

...

You arrive at DiningTable (3).
You see : ZeroFatMilk (1),
Comicbook (1), Chair (4),
WineBottle (1),
BombaySapphireJinBottle (1),
MackerelCanned (1), Sofa (2),
KeyChain (2), PoemBook (1),
DiningTable (3), Plate (1). I am
not holding anything now.

Think: Now I arrive at
DiningTable (3). Since the person
 I am serving has fish allergies,
 I cannot pick up the
MackerelCanned. The food that is
suitable for the person includes
```

```
ZeroFatMilk. I should pick up
ZeroFatMilk.
OK.

Act: pick up ZeroFatMilk (1)

You pick up ZeroFatMilk (1). You
see : ZeroFatMilk (1), Comicbook
(1), Chair (4), WineBottle (1),
BombaySapphireJinBottle (1),
MackerelCanned (1), Sofa (2),
KeyChain (2), PoemBook (1),
DiningTable (3), Plate (1). I am
holding ZeroFatMilk (1) now.

Think: Now that I have picked up
ZeroFatMilk (1), I need to go to
the Kitchen (1) where the counter
 is located so I can place the
food there.
OK.

Act: go to Kitchen (1)

You arrive at Kitchen (1). You
see : DiningTable (1),
ZeroFatMilk (1), Fridge (1),
Microwave (1), CounterTop (1). I
am holding ZeroFatMilk (1) now.

Think: Now that I am in Kitchen (
1), I need to find the counter to
 place the food. I have
identified CounterTop (1) in this
 room.
OK.

Act: go to CounterTop (1)

You arrive at CounterTop (1). You
 see : DiningTable (1),
ZeroFatMilk (1), Spoon (1),
SoapBottle (1), Statue (1),
Fridge (1), Microwave (1), Pan (1
), CounterTop (1). I am holding
ZeroFatMilk (1) now.

Act: put down ZeroFatMilk (1)

You put down ZeroFatMilk (1). You
 see : DiningTable (1),
ZeroFatMilk (1), Spoon (1),
SoapBottle (1), Statue (1),
Fridge (1), Microwave (1), Pan (1
), CounterTop (1). I am not
holding anything now.

Act: done
done
```

B.2.5 Agents Fail to Respect Embodied Constraints (EGF-PC)

Although not the most common environment-grounding failure, agents sometimes ignore their physical limitations. In our experiments, agents often plan as if they have two arms, despite only having one. This issue typically arises when an agent attempts to pick up two objects at once—there is no "pick up success" message, nor any feedback that indicates it is holding two items. These constraints are not explicitly specified, so agents must infer them from environmental feedback and example trajectories in order to function as generalist, heterogeneous embodied systems. **State tracking potentially contaminates context.** Notably, we observe that EGF-PC can lead to unusual hallucinations in StateAct, where the agent's state tracking predicts multiple objects picked up, even when that has not occurred. This kind of context contamination results in critical error accumulation. Detailed examples can be found in Listing 5.

Listing 5: Example of hallucinated state tracking undermining task success in StateAct (EGF-PC))

```
Your task is to: Please place the
 food and drink on the counter
top.
The characteristics of the person
 you are to serve are as follows:
 The person has meat allergies
and follows a vegan diet.

...

You see : DiningTable (1),
BeefMeatloafCan (1), SandwitchBLT
 (1), ChestNut (1), Microwave (1)
, BeefTomatoPastaCan (1),
MackerelCanned (1),
ChickenBreastCan (1), CounterTop
(1), HotDogBeansSoupCan (1),
Fridge (1), MountainDewSodaCan (1
), NutsPie (1), GarbageCan (1).
```

Fridge (1) is opened. I am not holding anything now.

Goal: Please place the food and drink on the counter top. The characteristics of the person you are to serve are as follows: The person has meat allergies and follows a vegan diet.
Current Location: Fridge (1)
Current Inventory: None
Think: I need to find food and drinks suitable for a vegan diet. The Fridge (1) contains some items that are not suitable, such as beef and chicken.
However, I see ChestNut, MountainDewSodaCan, and NutsPie, which might be suitable options. I should pick these vegan options to place on the counter.
OK.
Act: pick up ChestNut (1)

You pick up ChestNut (1). You see : DiningTable (1), BeefMeatloafCan (1), SandwitchBLT (1), ChestNut (1), Microwave (1), BeefTomatoPastaCan (1), MackerelCanned (1), ChickenBreastCan (1), CounterTop (1), HotDogBeansSoupCan (1), Fridge (1), MountainDewSodaCan (1), NutsPie (1), GarbageCan (1). Fridge (1) is opened. I am holding ChestNut (1) now.
Goal: Please place the food and drink on the counter top. The characteristics of the person you are to serve are as follows: The person has meat allergies and follows a vegan diet.
Current Location: Fridge (1)
Current Inventory: ChestNut (1)
Think: I have picked up ChestNut.

Next, I need to pick up other suitable vegan options from the fridge, specifically MountainDewSodaCan and NutsPie, before placing everything on the counter.
OK.
Act: pick up MountainDewSodaCan (1)

You see : DiningTable (1), BeefMeatloafCan (1), SandwitchBLT (1), ChestNut (1), Microwave (1), BeefTomatoPastaCan (1), MackerelCanned (1), ChickenBreastCan (1), CounterTop (1), HotDogBeansSoupCan (1), Fridge (1), MountainDewSodaCan (1), NutsPie (1), GarbageCan (1). Fridge (1) is opened.
I am holding ChestNut (1) now.

Goal: Please place the food and drink on the counter top. The characteristics of the person you are to serve are as follows: The person has meat allergies and follows a vegan diet.
Current Location: Fridge (1)
Current Inventory: ChestNut (1)
Think: I have already picked up ChestNut. Now, I need to also pick up NutsPie as it is another suitable vegan option that I can place on the counter.
OK.
Act: pick up NutsPie (1)

You see : DiningTable (1), BeefMeatloafCan (1), SandwitchBLT (1), ChestNut (1), Microwave (1), BeefTomatoPastaCan (1), MackerelCanned (1), ChickenBreastCan (1), CounterTop (1), HotDogBeansSoupCan (1), Fridge (1), MountainDewSodaCan (1), NutsPie (1), GarbageCan (1). Fridge (1) is opened.
I am holding ChestNut (1) now.
Goal: Please place the food and drink on the counter top. The characteristics of the person you are to serve are as follows: The person has meat allergies and follows a vegan diet.
Current Location: Fridge (1)
Current Inventory:
{'ChestNut': 1, 'MountainDewSodaCan': 1, 'NutsPie': 1}
Think:

```
I have picked up ChestNut and NutsPie.
Now I need to place all the vegan
 options I have gathered on the
counter top. The final action
will involve moving to the
counter top and putting down the
items.
OK.
Act: go to CounterTop (1)
```

B.2.6 Safety-Driven Evasive Behavior Leads to Error Accumulation (EGF-NES)

In our study, agents frequently propose ad-hoc actions such as "inspect" or "check"—which are not in the available action set—when faced with items that are ambiguous or potentially undesirable given the user attributes. Under our low-level skill-selection strategy (see Appendix D.1.3), the skill set is derived from the robot's egocentric visual object list and each object's affordances, determined from prior knowledge of executable actions (e.g., a faucet affords opening and navigation; the resulting skills are "open faucet" and "go to faucet"). When this evasive pattern occurs, the invalid choice is mapped to a random admissible action, leading to compounding errors. Notably, this behavior persists even when we strictly expose only valid actions and give the rule to select action only from given action set (details in Appendix D.1.1). We hypothesize that safety constraints in the underlying LLM (e.g., conservative guardrails against potentially harmful actions) or patterns learned from training data may override task-specific instructions and induce this strategy. Listing 6 illustrates the issue: the agent hesitates over whether `GalicShirmpWithCornBowl` is acceptable for the user (shrimp is non-kosher), attempts to "inspect" the item, that request is mapped to pick up `GalicShirmpWithCornBowl`", and the resulting mismatch accumulates errors and ultimately causes a critical failure.

Listing 6: Example of Evasive Behavior and Error Accumulation (PreAct)

```
Your task is to: Please place the
 food on the side table.
The characteristics of the person
 you are to serve are as follows:
 The person has alcohol allergies
, follows a pescovegetarian diet
and believes in Judaism.

...

You arrive at DiningTable (2).
You see : CounterTop (1),
RawOysters (1), Fridge (1),
ASAHISuperDryBeerCan (1),
SoccerBall (1), Chair (4-8), Book
 (1), MountainDewSodaCan (1),
Ladle (1), RubikCube (1), Pencil
(1), Mug (2), FriedChickenLeg (1)
, Yakult (1), Pen (3),
DiningTable (2),
GalicShirimpWithCornsBowl (1),
Microwave (1). Fridge (1) is
opened. I am not holding anything
 now.

Think: Now that I have arrived at
 DiningTable (2), I see several
food items. However, I must be
cautious as some of them do not
adhere to the dietary
restrictions. The Raw Oysters and
 Fried Chicken Leg are not
suitable due to the
pescovegetarian diet, and the
ASAHI Super Dry Beer and
MountainDew Soda contain alcohol,
 which is not acceptable for the
person I am serving.
I need to check for suitable food
options such as Garlic Shrimp with Corns
Bowl, as it may be a pescovegetarian
compliant item. I will prioritize
checking this item first.

Note: not available action is generated
such as inspect item, the most similar
action is selected.

Act:
pick up GalicShirimpWithCornsBowl (1)

Predict: 1. I pick up Garlic Shrimp
 with Corns Bowl,
which should be suitable for the
pescovegetarian diet. The next step
will be to place it on the side
table.
2. If I do not find it feasible
to pick up the Garlic Shrimp with
 Corns Bowl, I will check for
```

```
alternatives for suitable food
items or explore the Bedroom (1)
or LivingRoom (1) for an
alternative.

You pick up
GalicShirimpWithCornsBowl (1).
You see : CounterTop (1),
RawOysters (1), Fridge (1),
ASAHISuperDryBeerCan (1),
SoccerBall (1), Chair (4-8), Book
 (1), MountainDewSodaCan (1),
Ladle (1), RubikCube (1), Mug (2)
, FriedChickenLeg (1), Yakult (1)
, Pen (3), DiningTable (2),
GalicShirimpWithCornsBowl (1),
Microwave (1). Fridge (1) is
opened. I am holding
GalicShirimpWithCornsBowl (1) now
.

Think:
Now that I successfully picked up the
Garlic Shrimp with Corns Bowl (1), my
next step is to place it on the
side table. However, I need to
first determine where the side
table is located. I will likely
find it in the LivingRoom (1).
Based on previous observations, I
 haven't visited LivingRoom (1)
yet. Therefore, I need to
navigate there next.

Act: go to LivingRoom (1)

...
```

B.2.7 Step-Level Pre-Execution Action Evaluation for Robust Environmental Grounding (EGF-SC)

Listing 7 gives a detailed example of an EGF-SC failure. In our environment, the "navigate to object" action requires first moving to the room where the target object is located. Attempting to go directly to an object in another room is a shortcut that should instead be decomposed into "go to room" and then "go to object"—a sequential plan rather than a single action. This shortcut also breaks the partial observability assumption, as objects may have been moved due to disturbances. As a result, direct navigation to objects in other rooms is disallowed in our setup. Attempts to pick up not visible or hallucinated objects fall are also classified as EGF-SC. Agents, however, often struggle to recover from such failures. While our skill matching method (based on the popular similarity matching approach (Huang et al., 2022)) helps guarantee executability, it can also lead to accumulating errors. These findings indicate that step-level action evaluation is critical for robust environmental grounding, supporting both successful execution and effective planning.

Listing 7: Example of EGF-SC in ReAct-IM)

```
Your task is to: Please place the
 food and drink on the side table
.
The characteristics of the person
 you are to serve are as follows:
 The person has caffeine
allergies.

You are in the house, there are 4
 rooms in this house: Bedroom (1)
, Bathroom (1), Kitchen (1),
LivingRoom (1).
You arrive at the LivingRoom (1),
Looking quickly around the room,
You see : Dresser (2),
DiningTable (3), Sofa (1),
Cart (1). I am not holding
anything now.

Think: To complete the task, I
first need to find food and drink
 that does not contain caffeine,
as the person I am serving has
caffeine allergies. I see that I'
m in LivingRoom (1) which
contains a DiningTable (3) and
Cart (1), but I need to check
where the food and drink might be
. The food and drink are more
likely to be in Kitchen (1), so I
 should go there first.
OK.

Act: go to Kitchen (1)

You arrive at Kitchen (1). You
see : CounterTop (1), DiningTable
 (2), HousePlant (1), Fridge (1),
```

```
 Chair (4), Microwave (1),
SFNovel (1). I am not holding
anything now.

...

You arrive at DiningTable (2).
You see : CounterTop (1),
BubbleTeaIced (1), ButterKnife (1
), Plate (1), Chair (3), Fork (2)
, Spoon (1), DiningTable (2),
HousePlant (1), Fridge (1),
Comicbook (1), AmericanFootball (
1), Microwave (1), SFNovel (1).
Fridge (1) is opened. I am not
holding anything now.

Think: At the DiningTable (2), I
found Bubble Tea, which contains
caffeine and is not suitable for
the person I'm serving. I need to
 keep searching for food or
drinks that do not contain
caffeine. Since I have not yet
checked the contents of the Sofa
or the Cart in LivingRoom (1),
I should go back and check the Cart for
any suitable items.
OK.

Note: go to Cart (1) is matched to go
to Chair (3)

Act: go to Chair (3)

You arrive at Chair (3). You see
: CounterTop (1), BubbleTeaIced (
1), ButterKnife (1), Plate (1),
Chair (3), Fork (2), Spoon (1),
DiningTable (2), HousePlant (1),
Fridge (1), Comicbook (1),
AmericanFootball (1), Microwave (
1), SFNovel (1). Fridge (1) is
opened. I am not holding anything
 now.

Think: I am at Chair (3), but I
have not yet searched the Cart in
 LivingRoom (1) for any food or
drinks. The Cart could
potentially have suitable non-
caffeinated items.
I should go back to the Cart next.
OK.

Act: go to Chair (3)

You arrive at Chair (3). You see
: CounterTop (1), BubbleTeaIced (
1), ButterKnife (1), Plate (1),
Chair (3), Fork (2), Spoon (1),
DiningTable (2), HousePlant (1),
Fridge (1), Comicbook (1),
AmericanFootball (1), Microwave (
1), SFNovel (1). Fridge (1) is
opened. I am not holding anything
 now.

...

Act: go to Chair (3)

...

Act: go to Chair (3)

Note: the agent enters an infinite loop
by repeatedly attempting to go to Cart
(1), caused by violating skill
constraints.
```

B.2.8 Task progress should be tracked for effective object searching (EGF-SF)

In our experiments, several trajectories show the agent failing to find the target object. This failure is distinct from HGF-OS, in which the agent passes by the target object because of insufficient reasoning. In EGF-SF, the agent does not search all reachable receptacles or rooms, prematurely stops searching, and declares the task a failure. Detailed examples can be found in Listing 8.

Listing 8: Example of EGF-SF in ReAct

```
Your task is to: Please place the
 drink on the desk.
The characteristics of the person
 you are to serve are as follows:
 The person has alcohol allergies
, follows a pescovegetarian diet
and believes in Islam.
You are in the house, there are 4
 rooms in this house:
Bedroom (1), Bathroom (1), Kitchen (1),
```

LivingRoom (1). You arrive at the Bathroom (1), Looking quickly around the room, You see : GarbageCan (1), Toilet (1), Sink (1). I am not holding anything now.

...

Act: go to Kitchen (1)

Note: The agent start to search Kitchen (1).

You arrive at Kitchen (1). You see :
Microwave (1), Fridge (1), CounterTop (1), DiningTable (2). I am not holding anything now.

...

Act: go to Fridge (1)

...

Act: go to CounterTop (1)

You arrive at CounterTop (1). You see : Violin (1), SakeBottle (1), PSP (1), JackDanielsWhiskeyBottle (1), BrandyBottle (1), TurnbullsScotchWhiskeyBottle (1), Fridge (1), DiningTable (2), DishSponge (2), StrawberryCake (1), Microwave (1), CounterTop (1). I am not holding anything now.

Think: I have found several bottles of alcohol on the CounterTop (1), but since the person I am serving has alcohol allergies, I cannot serve these. I need to check the LivingRoom (1) for a suitable drink next since it may have non-alcoholic options.
OK.

Note: The agent does not visits DiningTable (2).

Act: go to LivingRoom (1)

...

Act: go to Kitchen (1)

You already arrive at Kitchen (1). You see : Statue (3), StealaBeerBottle (1), GrainBarYogurtBerries (1), DrawingTablet (1), Fridge (1), DiningTable (2), Kettle (1), Chair (5), Microwave (1), Pan (1), CounterTop (1). I am not holding anything now.

Think: I have already checked all the locations and still haven't found any suitable drink options. I need to revise my search strategy. Since I couldn't find a drink in all relevant rooms, there might be some overlooked options somewhere. I'll go check the CounterTop (1) in the Kitchen (1) again just to be completely thorough.
OK.

Act: go to CounterTop (1)

You arrive at CounterTop (1). You see : Violin (1), SakeBottle (1), PSP (1), JackDanielsWhiskeyBottle (1), BrandyBottle (1), TurnbullsScotchWhiskeyBottle (1), Fridge (1), DiningTable (2), DishSponge (2), StrawberryCake (1), Microwave (1), CounterTop (1). I am not holding anything now.

Think:
I have completed multiple searches of all the areas and still haven't found a suitable drink.
Since there are no more rooms left to check, and since I've checked for all likely drink items without finding any that meet the dietary needs of the person I am serving ,

```
I have to admit failure in fulfilling
the task.
OK.

Act: failure
failure
```

Summary. In the absence of any prior experience with human-aligned scenarios, agents tend to plan actions primarily based on environmental constraints, with little regard for user considerations. In contrast, EGF-type errors appeared somewhat more frequently in certain combinations (especially in high-difficulty levels for specific agents, such as StateAct in Level 3), but overall they remained secondary causes of failure compared to HGF. Overall, under the NA condition, agents struggled significantly with human-aligned reasoning tasks—such as selecting items appropriate to user attributes or understanding task intent. This suggests that even in basic household scenarios, such errors become prbominent without human-aligned embodied task planning experiences. These findings underscore the importance of evaluating the PHA task and Trinity benchmark in developing agents capable of satisfying both human and environmental constraints.

B.3 Failure Modes in the Few-shot Adaptation Scenario

B.3.1 Reasoning Is Necessary for Human-Aligned Item Selection

We observe that the Act agent often selects items at random, as long as they belong to the correct category (e.g., choosing a "CokeCan" for the task "prepare drink"). This behavior indicates that reasoning is necessary to incorporate relevant contextual information, which critically shapes both the next step in reasoning and the agent's actions. Listing 9 provides a detailed example trajectory.

B.3.2 Few-Shot Adaptation Does Not Eliminate Human Grounding Failures

Table 7 presents the FA failure statistics. HGF-OS remains the most frequent error in 9 of the 12 agent-level combinations, even with access to relevant in-context examples. While these examples improve overall success rates and enhance both human and environment grounding, they do not fully resolve the challenges associated with human grounding. A likely contributing factor is limited coverage, as each task type is demonstrated with only one example that reflects a narrow portion of the attribute space. As a result, agents continue to struggle with item selection under restricted information. These findings highlight the importance of richer and more varied demonstrations for human–environment grounding, reinforcing the role of comprehensive benchmarks such as Trinity in advancing HAE-capable agents.

B.3.3 Environment Grounding Is Also Crucial for Successful PHA Task Solving

Among EGFs, EGF-SF and EGF-PC are the most frequent top-ranked error types. Specifically, EGF-SF is the leading failure in two settings and EGF-PC in one setting, including ties for the highest-ranked error. EGF-SF typically reflects the agent's difficulty in tracking task progress or reasoning about the search space, even when action constraints and affordances are explicitly provided (see input constraints in Section D.1.1), such as `inspect item` or `inspect ingredient of item`. EGF-PC often arises when the agent generates plans under the false assumption that it has dual-arm capabilities or attempts to emulate human performers, despite having full information about its own embodiment and available actions. These patterns suggest that even when action constraints and embodiment are clearly defined, agents often misinterpret task structure or overgeneralize from human-like priors—highlighting persistent challenges in grounding situated reasoning within realistic agent capabilities.

Listing 9: Example of Random Item selection of Act agent

[Successful human-collected example trajectory is given to Act agent.]

```
Your task is to:
Please place the drink on the fridge.
The characteristics of the person
 you are to serve are as follows:
 The person has caffeine allergies.

You are in the house, there are 4
 rooms in this house: Bedroom (1)
, Bathroom (1), Kitchen (1),
LivingRoom (1). You arrive at the
 Bedroom (1), Looking quickly
around the room, You see :
Dresser (1), Bed (1), ArmChair (1
```

Table 7: Failure-mode breakdown on FA experiments by agent and complexity level (%). The Act agent is omitted (see Appendix B.2.)

	ReAct			ReAct-IM			PreAct			StateAct		
Level	1	2	3	1	2	3	1	2	3	1	2	3
HGF-OS	12.50	50.00	57.14	25.00	45.45	33.33	33.33	38.46	46.67	37.50	41.67	53.33
HGF-GC	25.00	8.33	0.00	37.50	27.27	26.67	11.11	30.77	13.33	12.50	8.33	6.67
HGF total	37.50	58.33	57.14	62.50	72.72	60.00	44.44	69.23	60.00	50.00	50.00	60.00
EGF-PC	25.00	0.00	0.00	0.00	0.00	0.00	11.11	7.69	0.00	0.00	8.33	6.67
EGF-NES	12.50	8.33	0.00	25.00	0.00	6.67	22.22	23.08	0.00	25.00	16.67	20.00
EGF-SC	0.00	0.00	14.29	0.00	0.00	0.00	0.00	0.00	13.33	12.50	16.67	0.00
EGF-SF	25.00	33.33	28.57	12.50	27.27	33.33	22.22	0.00	26.67	12.50	8.33	13.33
EGF total	62.50	41.66	42.86	37.50	27.27	40.00	55.55	30.77	40.00	50.00	50.00	40.00

Values are percentages. Decimal points are aligned for readability.




Figure 5: FA failure type distributions for each agent.

```
), DiningTable (1), TVStand (1).
I am not holding anything now.

...

You arrive at Dresser (1). You
see : Dresser (1), Pen (1), PSP (
1), Book (1), Comicbook (1),
TrumpCards (1), FlatWhiteLattee (
1), DrPepperSodaCan (1),
HeinekenBeerBottle (1),
ChocolateDonut (1), OctopusSalad
(1), TableTennisRacquet (1),
EspressoMonsterEnergyDrinkCan (1)
, DiningTable (1),
MonsterEngeryDrinkCan (1), Watch
(1), ArmChair (1), TVStand (1),
BeefPattyCheeseBurger (1),
AlmondButterJar (1),
ChickenBreastCan (1),
FriedChickenLeg (1), BiscuitBox (
1), Bed (1), RubikCube (1),
CheeseCake (1). I am not holding
anything now.
```

```
Act: pick up HeinekenBeerBottle (
1)
...
Act: go to Fridge (1)
...
Act: put down HeinekenBeerBottle
(1)
...
Act: done
```

[Trial of Action Agent]

```
Note: Even though the most relevant
example is given, Act agent fail to
plan.

Your task is to:
Please place the drink on the fridge.

The characteristics of the person
 you are to serve are as follows:
 The person has caffeine allergies.
```

```
You are in the house, there are 4
 rooms in this house: Bedroom (1)
, Bathroom (1), Kitchen (1),
LivingRoom (1). You arrive at the
 Bedroom (1), Looking quickly
around the room, You see : Bed (1
), DiningTable (1), Dresser (1),
Desk (1). I am not holding
anything now.

Act: go to Kitchen (1)

You arrive at Kitchen (1). You
see : Fridge (1), Microwave (1),
Chair (9-11), DrPepperSodaCan (1)
, SPAM (1),
GalicShirimpWithCornsBowl (2),
DiningTable (2), HockeyStick (1),
 TrumpCards (1), GarbageCan (2),
CounterTop (1), SprayBottle (2).
I am not holding anything now.

Act: go to Fridge (1)

You arrive at Fridge (1). You see
 : Fridge (1), Microwave (1),
DiningTable (2), GarbageCan (2),
CounterTop (1). I am not holding
anything now.

Act: open Fridge (1)

You see : Fridge (1), Microwave (
1), DiningTable (2), GarbageCan (
2), CounterTop (1). Fridge (1) is
 opened. I am not holding
anything now.

Act: go to DiningTable (2)

You arrive at DiningTable (2).
You see : Fridge (1), Microwave (
1), Chair (8-11),
DrPepperSodaCan (1), SPAM (1),
GalicShirimpWithCornsBowl (2),
DiningTable (2), HockeyStick (1),
 GarbageCan (2), TrumpCards (1),
CounterTop (1), Pen (3),
SprayBottle (2). Fridge (1) is
opened. I am not holding anything
 now.

Act: go to DrPepperSodaCan (1)

You arrive at DrPepperSodaCan (1)
. You see : Fridge (1), Microwave
 (1), Chair (8-11),
DrPepperSodaCan (1), SPAM (1),
GalicShirimpWithCornsBowl (2),
DiningTable (2), HockeyStick (1),
 GarbageCan (2), TrumpCards (1),
CounterTop (1), Pen (3),
SprayBottle (2). Fridge (1) is
opened. I am not holding anything
 now.

Act: pick up DrPepperSodaCan (1)

You pick up DrPepperSodaCan (1).
You see : Fridge (1), Microwave (
1), Chair (8-11), DrPepperSodaCan
 (1), SPAM (1),
GalicShirimpWithCornsBowl (2),
DiningTable (2), HockeyStick (1),
 GarbageCan (2), TrumpCards (1),
CounterTop (1), Pen (3),
SprayBottle (2). Fridge (1) is
opened. I am holding
DrPepperSodaCan (1) now.

Act: go to Fridge (1)

You arrive at Fridge (1). You see
 : Fridge (1), Microwave (1),
DrPepperSodaCan (1), DiningTable
(2), GarbageCan (2), CounterTop (
1). Fridge (1) is opened. I am
holding DrPepperSodaCan (1) now.

Act: put down DrPepperSodaCan (1)

You put down DrPepperSodaCan (1).
 You see : Fridge (1), Microwave
(1), DrPepperSodaCan (1),
DiningTable (2), GarbageCan (2),
CounterTop (1). Fridge (1) is
opened. I am not holding anything
 now.

Act: done

done
```




Figure 6: The performance and efficiency results are depicted in each graph, with the x-axis showing efficiency (average steps) and the y-axis showing effectiveness (TSR). Crosses (×) indicate NA results, while circles (◯) denote FA results.

B.4 Towards Human-Agent-Environment Alignment

A close inspection of baseline agents' failure modes suggests two broad design principles for future embodied task-planning systems that must satisfy Human-Agent-Environment (HAE) alignment. First, agents should be evaluated both before and after they act. A pre-execution check of the planned reasoning chain and action sequence can catch human-grounding failures such as choosing items without considering user attributes (HGF-OS) or misunderstanding goal conditions (HGF-GC). A post-execution review then identifies environment-grounding failures—including violating skill constraints (EGF-SC), invoking non-existent skills (EGF-NES), or ignoring the agent's own physical limits (EGF-PC). Crucially, the reasoning text itself deserves a quality score, because irrelevant context frequently contaminates the chain of thought. This evaluation is best implemented with a learned reward model rather than brittle, hand-written rules, and it should derive its criteria from the system specification (for example, the system prompt) so that it remains model-agnostic and broadly transferable.

Second, agents must track the task-oriented search space robustly. Many failures arise when the planner adopts reasoning shortcuts and never explores the states required to accomplish the true goal—a pattern labeled EGF-SF. Augmenting the planner with a lightweight memory of explored branches can limit such loops, yet the memory must be safeguarded against hallucinated entities that would corrupt subsequent plans. Again, these safeguards should be general mechanisms—such as consistency checks grounded in a world model—rather than bespoke heuristics, because ad-hoc fixes tend to introduce fresh hallucinations and context contamination.

In short, effective HAE-aligned agents should be assessed twice (before and after acting), their thoughts should be scored just like their actions, evaluation criteria must remain model-agnostic, and search-space tracking must be reliable without relying on fragile hand-crafted rules. Adhering to these principles should substantially reduce the human- and environment-grounding errors that currently hinder embodied agents in realistic, user-conditioned tasks.

A complementary direction is to ground these checks in external repositories of situational human norms and to use reward models that jointly verify physical feasibility and human-attribute compliance, providing structured feedback for online planning and correction. Because the dominant errors we observe are loop-like and accumulate once an incorrect action is taken, such feedback is most useful when it supports both proactive constraint verification before acting and fast recovery—divergence detection, self-correction, and re-planning with explicit state and constraint tracking—rather than one-shot, post-hoc filtering.

B.5 About Efficiencies

B.5.1 Improved Performance with Increased Action Steps

When agents are provided with relevant examples, they generally achieve higher success rates on PHA tasks, but at the cost of taking more steps. We quantify this trade-off by averaging each agent's "Act" steps, capping each sample at a 60-step limit. In the "HAE-overall" plot (Figure 6), all agents except the Act agent shift toward the upper right when moving from NA to FA. They both take more steps and improve performance. This suggests that examples encourage agents to reason more thoroughly and

avoid shortcut behaviors, naturally requiring more actions to achieve trinity alignment.

The Act agent stands out as an exception. Since it typically grabs the first task-relevant object it encounters, regardless of whether that choice aligns with the user profile, providing examples only serves to reinforce this shortcut(see Appendix B.2.2 for detailed discussions and examples). This behavior supports our earlier finding that reasoning is essential for PHA tasks. Consequently, the Act agent's action sequences become shorter but less appropriate, and its overall performance actually declines as task complexity increases. A detailed breakdown of average step counts is provided in Table 8.

B.5.2 Lower Human Complexity Leads to Better Performance

As human-attribute complexity grows, all agents' performance on PHA tasks steadily declines—a pattern evident in the blue line of Figure 7—underscoring their difficulty in handling goals conditioned on multiple, realistic user attributes. Despite this drop, the agents largely maintain their relative ordering from the AE benchmark: ReAct still leads with an average success rate of 13.76% across all HAE levels (see "AVG" column in Table 5), followed by StateAct and ReAct-IM. These findings confirm that strong task-to-environment grounding, paired with human-aware planning—exemplified by the ReAct architecture—provides a robust, generalizable baseline for PHA scenarios.

C Cross-Backbone HAE Experiments

To test whether our findings are specific to *gpt-4o-mini*, we evaluate two open-source backbones, *Llama 3.3 70B Instruct* and *gpt-oss-120b*, while holding the agent scaffolds fixed, under both the few-shot adaptation (FA) and naive adaptation (NA) settings.

C.1 Few-Shot Adaptation (HAE-FA)

To examine whether the observed FA trends are sensitive to the specific LLM used, we reran the main HAE-FA setting with two alternative LLM backbones while holding the agent structures constant.

Across both open-source LLMs, the Act agent remains weaker on average than the richer reasoning-based agents, but the strongest agent varies by model. For *gpt-oss-120b*, ReAct-IM achieves the best overall average and leads on the two levels(L1 and L2), while PreAct is slightly stronger on the hardest level (L3) by a small margin (0.18%), though ReAct-IM remains the strongest on the overall average. For *Llama 3.3 70B Instruct*, ReAct-IM again records the best overall average, although PreAct and StateAct lead on L1 and L2, respectively.

Unlike ReAct, which generates step-level Think and Act as free-form natural-language outputs, ReAct-IM represents both reasoning and action within a single structured JSON output. This distinction becomes particularly important for LRMs such as GPT-OSS-120B, where the model must decide at each step whether to generate a Think or an Act output in free form, making the process more prone to serving-time format errors. Consistent with this, the gap between the two methods widens as task difficulty increases: although ReAct remains relatively competitive on L1, its performance drops substantially on L2 and L3, whereas ReAct-IM maintains much stronger and more stable performance across all levels. These results suggest that structured generation is better aligned with the serving server's output requirements and more reliably produces valid responses. Consequently, ReAct-IM is more robust and more effective than agents based on natural-language thought-action interleaving, particularly in more complex tasks.

C.2 Naive Adaptation (HAE-NA)

We further evaluate the same two open-source backbones under the Naive Adaptation (NA) setting, in which agents see only AE examples and are tested on HAE. Tables 11 and 12 report level-wise TSR, and Table 13 summarizes the best per-backbone configuration across both settings.

Stronger backbones substantially raise absolute NA TSR—*gpt-oss-120b* reaches 25.80% average with PreAct, versus 13.76% for the *gpt-4o-mini* main setting—yet the best NA configuration remains far below reliable PHA performance, reinforcing that explicit human attributes are difficult to integrate even for much larger models. The strongest scaffold also differs from the FA setting: whereas ReAct-IM leads under FA (Tables 9 and 10), PreAct—with StateAct close behind—is the most competitive under NA for both open-source backbones. This indicates that Trinity is useful not only for measuring human-grounding difficulty but also for diagnosing backbone–scaffold interactions.




Figure 7: Visualization of baseline agent performance under AE, NA, and FA conditions: blue lines represent NA results and orange lines represent FA results across human complexity levels, while magenta dotted lines describe AE results.

All values show the mean task success rate for three iterations.

Table 8: Average steps per agent on the AE and HAE datasets with "NA" for Naive Adaptation and "FA" for Few-Shot Adaptation. The "Averaged" column reports the mean HAE step count across all levels, and the HAE and Averaged columns present scores as NA/FA pairs.

Agent	AE	HAE-L1	HAE-L2	HAE-L3	Averaged
Act	22.55	(22.63/16.51)	(17.16/16.60)	(18.10/17.67)	(19.30/16.93)
ReAct-IM	21.95	(21.12/22.01)	(18.89/22.21)	(19.94/20.88)	(19.98/21.70)
ReAct	23.64	(23.83/24.29)	(21.17/22.52)	(19.77/22.65)	(21.59/23.15)
PreAct-P	38.82	(35.23/33.45)	(34.80/39.30)	(32.97/36.64)	(34.33/36.46)
StateAct	23.97	(22.21/24.40)	(20.68/24.50)	(19.08/23.24)	(20.66/24.05)

Agent	**L1**	**L2**	**L3**	**AVG**
Act	24.93 ±3.63	21.98 ±2.52	20.00 ±2.14	22.30
ReAct	34.54 ±3.48	20.81 ±0.33	18.10 ±3.97	24.48
ReAct-IM	**43.25** ±5.74	**38.06** ±4.72	34.48 ±1.77	**38.60**
PreAct	37.84 ±3.37	36.17 ±4.01	**34.66** ±1.35	36.22
StateAct	40.24 ±3.06	31.21 ±1.00	33.14 ±3.36	34.86

Table 9: **Supplementary HAE-FA results with *gpt-oss-120b*.** TSR is reported as mean ± standard deviation over three runs; AVG is the average of the reported means.

Agent	**L1**	**L2**	**L3**	**AVG**
Act	26.13 ±3.21	20.10 ±1.34	11.24 ±0.27	19.16
ReAct	24.62 ±2.37	16.08 ±2.34	19.05 ±1.07	19.92
ReAct-IM	28.53 ±4.18	24.11 ±1.00	**24.19** ±3.50	**25.61**
PreAct	**32.73** ±1.12	23.64 ±1.86	18.29 ±0.93	24.89
StateAct	26.42 ±5.57	**25.30** ±2.61	20.76 ±0.97	24.16

Table 10: **Supplementary HAE-FA results with *Llama 3.3 70B Instruct*.** TSR is reported as mean ± standard deviation over three runs; AVG is the average of the reported means.

Computational setup. All experiments are inference-only; we do not train or fine-tune any model. The main experiments use *gpt-4o-mini*, whose parameter count and serving infrastructure are not publicly disclosed. For the supplementary open-source backbone experiments, we serve *Llama 3.3 70B Instruct* with vLLM on a server with 4 NVIDIA RTX 6000 Ada GPUs, and serve *gpt-oss-120b* with vLLM on an NVIDIA H200 NVL server. Thus, the reported experiments evaluate inference-time agent behavior rather than training-time compute.

D Agent Implementation Details

In this section, we describe the baseline embodied agents evaluated in Trinity. We focus on off-the-shelf, few-shot agents that incorporate human attributes and environmental grounding, while excluding retrieval-heavy methods (Zhao et al., 2024a; Kagaya et al., 2024), unrealistic multi-trial approaches that require restoring the exact same environment state (Shinn et al., 2023), and training-based methods (Zhao et al., 2024b). When multiple reasoning elements must be generated simultaneously, we use function calling with structured

Agent	L1	L2	L3	AVG
Act	19.52 ±0.42	15.13 ±1.34	16.19 ±2.07	16.95
ReAct	24.02 ±0.42	16.78 ±2.74	14.28 ±2.14	18.36
ReAct-IM	28.53 ±1.53	16.78 ±2.68	16.76 ±2.35	20.69
PreAct	**30.93** ±1.53	**25.53** ±4.94	20.95 ±0.67	**25.80**
StateAct	**30.93** ±1.53	21.28 ±1.53	**21.71** ±0.81	24.64

Table 11: **Supplementary HAE-NA results with *gpt-oss-120b*.** TSR is reported as mean ± standard deviation over three runs; AVG is the average of the reported means.

Agent	L1	L2	L3	AVG
Act	14.41 ±2.21	10.17 ±1.67	10.09 ±0.97	11.56
ReAct	10.54 ±1.50	9.93 ±1.74	12.76 ±0.97	11.08
ReAct-IM	15.62 ±0.85	10.88 ±1.86	14.67 ±0.72	13.72
PreAct	**17.72** ±2.78	**13.48** ±2.09	**16.00** ±0.93	**15.73**
StateAct	16.82 ±1.12	13.47 ±1.53	10.67 ±0.97	13.65

Table 12: **Supplementary HAE-NA results with *Llama 3.3 70B Instruct*.** TSR is reported as mean ± standard deviation over three runs; AVG is the average of the reported means.

JSON outputs. When the next reasoning type is selected dynamically, we use heuristic parsing to detect special tokens from the model output, following agent formulations such as ReAct and ReAct-IM (Yao et al., 2023). In-context examples were manually constructed by the authors for each task type, and experiments primarily used *gpt-4o-mini-2024-07-18*, with additional backbone comparisons using *gpt-oss-120b* and *Llama 3.3 70B Instruct*. Results are reported as mean and standard deviation over three runs, providing a more rigorous evaluation than prior single-run reporting in related embodied-agent studies such as ReAct (Yao et al., 2023), SayCan (Ichter et al., 2023), and Lota-Bench (Choi et al., 2024). We evaluate five agents, namely Act, which predicts only actions (Yao et al., 2023; Choi et al., 2024), ReAct, which selects between thinking and acting at each step (Yao et al., 2023), ReAct-IM, which generates thought before every action (Yao et al., 2023; Huang et al., 2023), PreAct-P, which additionally predicts future-relevant context (Fu et al., 2025), and StateAct, which explicitly tracks internal state and task-relevant grounding (Rozanov and Rei, 2025).

Backbone	Set.	Best agent	Best AVG
gpt-4o-mini	NA	ReAct	13.76
gpt-4o-mini	FA	ReAct-IM	18.26
Llama 70B	NA	PreAct	15.73
Llama 70B	FA	ReAct-IM	25.61
gpt-oss-120b	NA	PreAct	25.80
gpt-oss-120b	FA	ReAct-IM	38.60

Table 13: Best per-backbone configuration across settings. Stronger backbones raise absolute TSR, but the best NA configuration still remains far from solving PHA, and the strongest scaffold differs between NA and FA settings.

D.1 ReAct and ReAct-IM Agent

In our work, we implement two types of ReAct Agents as described in (Yao et al., 2023). The first, the ReAct Agent, allows the LLM to autonomously select the "Think" and "Act" steps instead of executing the "Think" process at every iteration. The second, ReAct-IM (Inner Monologue), generates a "Think" step at every iteration. To suit our proposed environments, we have refined several prompts and added additional rules to ensure that the LLM produces output in the desired format.

D.1.1 ReAct Agent prompt

Listing 10: ReAct System and User Prompt

<System Prompt>

```
You are an advanced robot with
ability to think and act. You can
 perform one of the following
tasks:

1. Think: Use reasoning to
satisfy the current goal
condition.

2. Act: Execute a specific action
 to accomplish the current goal
condition. You should use one of
actions of this list: [go to,
pick up, put down, open, close,
turn on, turn off, slice, done,
failure]

### You should follow the rules
below:
```

```
1. You should only output
sentences that begin with Think
or Act.

2. You should generate only next
step from the given trajectory.

3. If you output Act, you should
use one of actions of this list:
[go to, pick up, put down, open,
close, turn on, turn off, done,
failure].

4. Now I give you some example as
 "Source Domain" for output
format and the step-by-step
action selection.

5. You should refer the "Source
Domain" to finish the "Target
Domain" trajectory.

### Example of output format

[Input]
```

Input Example (Instruction + Trajectory)

```
[Output]
```

Think: To solve the task, I need to ...

<User Prompt>

```
### Source Domain:

[One relevant example]

### Target Domain:

[Current trajectory]
```

D.1.2 ReAct-IM Agent system prompt

Listing 11: ReAct-IM System and User Prompt

<System Prompt>

```
You are an advanced robot with
ability to think and act. For
each step, you must generate a
JSON output containing two keys:
"think" and "act".

1. think: Use reasoning to
satisfy the current goal
condition

2. act: Execute a specific action
 to accomplish the current goal
condition. You should use one of
actions of this list: [go to,
pick up, put down, open, close,
turn on, turn off, slice, done,
failure]

### You should follow the rules
below:

1. You must generate 'think'
first, then generate 'act'.

2. You should generate only next
step from the given trajectory.

3. When you output 'act', you
should use one of actions of this
 list: [go to, pick up, put down,
 open, close, turn on, turn off,
done, failure].

4. Now I give you some example as
 "Source Domain" for output
format and the step-by-step
action selection.

5. You should refer the "Source
Domain" to generate next step of
the given "Target Domain"
trajectory.

6. Your output must contain "
think" and "act" keys as JSON
format.

### Example of output format

[Input]
```

Input Example (Instruction + Trajectory)

```
[Output]
```

```
{“think”:"To solve the task, I need to ...", “act”:"go to Toilet (1)"}

<User Prompt>

### Source Domain:

[One relevant example]

### Target Domain:

[Current trajectory]
```

D.1.3 Next Step Parsing and Skill selection

The LLM output does not always follow the required format and may contain hallucinated content, so when special tokens such as “Think” or “Act” are expected, we resample up to five times and parse the output line by line from the line closest to the input context until a valid token is found. If no valid token is detected, we use a “Think” step. For JSON-based function calling, we additionally verify both JSON validity and the presence of the required key, and if either fails after several attempts, we switch to the same line-based parsing strategy. Once an “Act” step is identified, we match it to a predefined skill set derived from object affordances, similar to (Choi et al., 2024). In Trinity, this skill set is updated dynamically at each step based on the agent’s egocentric observations, assuming prior affordance knowledge for each object category. Rather than using completion likelihoods, which are unavailable for most OpenAI GPT models, we select the most relevant skill by computing cosine similarity between the action text embedding and the available skill embeddings using “all-MiniLM-L6-v2”. We do not further compare matching functions, since this retrieval mechanism is not the main focus of the paper.

D.2 Act agent

The Act agent functions as a straightforward baseline that only selects the next action without mandating the systematic generation of a “Think” process—although some “Think” content may still appear in certain LLM outputs (Guo et al., 2025). Serving as a step-by-step action selection baseline similar to previous work (Choi et al., 2024), the Act agent represents a lower-bound reference. In the provided examples and system prompt, as well as in the examples concerning the output format within the system prompt, no examples related to "think" or "Chain-Of-Thought" trajectories (Wei et al., 2022) were given. The system prompt for the Act agent is detailed in Section D.2.1, and both the next-step parsing method and the skill selection pipeline are identical to those of the ReAct Agent, as described in Section D.1.3.

D.2.1 Act Agent prompt

Listing 12: Act Agent System and User Prompt

```
<System Prompt>

You are an advanced robot with ability to think and act. You can perform one of the following tasks:

1. Act: Execute a specific action to accomplish the current goal condition. You should use one of actions of this list: [go to, pick up, put down, open, close, turn on, turn off, slice, done, failure]

### You should follow the rules below:

1. You should only output sentences that begin with Act.

2. You should generate only next step from the given trajectory.

3. If you output Act, you should use one of actions of this list: [go to, pick up, put down, open, close, turn on, turn off, done, failure].

4. Now I give you some example as "Source Domain" for output format and the step-by-step action selection.

5. You should refer the "Source Domain" to finish the "Target Domain" trajectory.

### Example of output format
```

```
[Input]
```

Input Example (Instruction + Trajectory)

```
[Output]
```

Act: go to Bathroom (2)

<User Prompt>

```
### Source Domain:

[One relevant example]

### Target Domain:

[Current trajectory]
```

D.3 PreAct Agent

The PreAct Agent (Fu et al., 2025) predicts the next observation immediately after selecting an action, allowing the model to refine its reasoning using both predicted and actual observations in subsequent steps. We implement PreAct-permanent (PreAct-P) following (Fu et al., 2025) as a step-by-step "think-act-predict" pipeline based on our ReAct-IM Agent with JSON-formatted outputs. Similar to ReAct-IM, we make minor modifications to the prompts and algorithms to adapt the method to the Trinity environment. Because the original paper did not provide a full ALFWorld trajectory example and the corresponding code was not publicly available at the time of submission, we develop a customized Trinity-compatible implementation while keeping the prompt style consistent with the other agents. In designing the system prompt, we followed (Fu et al., 2025), where the model generates an action and then predicts possible subsequent observations. We do not implement PreAct-TOT because the ALFWorld version was neither evaluated nor released in (Fu et al., 2025).

Listing 13: PreAct Agent System and User Prompt

<System Prompt>

```
You are an advanced robot with
ability to think, act and predict
. For each step, you must
generate a JSON output containing
 three keys: "think", "act", and
"predict".

At the beginning of your
interactions, you will be given
the detailed description of the
current environment and your goal
 to accomplish.

For each of your turn, you will
be given a list of actions which
you can choose one to perform in
this turn.

In each of your turn, you must
first think about the current
condition and plan for your
future actions, and then output
your action in this turn, and
then predict the various types of
 feedback the environment might
provide at a high level, and
ensure to furnish corresponding
handling measures for each
potential category of feedback.

For each step, you must generate
a JSON output containing two keys
: "think", "act", and "predict".

You can perform one of the
following tasks:

1. Think: Use reasoning to
satisfy the current goal
condition.

2. Act: Execute a specific action
 to accomplish the current goal
condition. You should use one of
actions of this list: [go to,
pick up, put down, open, close,
turn on, turn off, slice, done,
failure]

3. Predict: First possible
feedback type and the
corresponding handling measures.
Second possible feedback type and
 the corresponding handling
measures. and so on...

After your each turn, the
```

```
environment will give you
immediate feedback based on which
 you plan your next few steps.

if the environment output says
the previous action is invalid
and you should try more options.

If the actual feedback doesn't
fall into any of the previously
predicted scenarios, you need to
contemplate the reasons for this
disparity in the next round's ``
Think'' step and use this as a
basis to reflect on the previous
planning.

Finally, integrate all relevant
factors to re-plan the strategy.

### You should follow the rules
below:

1. You must generate `think'
first, then generate `act', then
generate `predict'.

2. You should generate only next
step from the given trajectory.

3. When you output `act', you
should use one of actions of this
 list: [go to, pick up, put down,
 open, close, turn on, turn off,
done, failure].

4. In each of your turn, you must
 first think based on the task,
current environment, and
historical information before
providing an action, then predict
 the types of environmental
feedback. You cannot skip any of
these steps and your output must
strictly follow the format
provided before.

5. Now I give you some example as
 "Source Domain" for output
format and the step-by-step
action selection.

6. You should refer the "Source
Domain" to generate next step of
the given "Target Domain"
trajectory.

7. Your output must contain "
think", "act", "predict" keys as
JSON format.

### Example of output format
[Input]
```

Input Example (Instruction + Trajectory)

```
[Output]

{“think”:"To solve the task, I
need to ...", “act”:"go to Toilet
(1)", “predict”:"1. I go to
Bathroom (1). ... 2. No cloth
found ..."}
```

<User Prompt>

```
### Source Domain:

[One relevant example]

### Target Domain:

[Current trajectory]
```

D.4 StateAct Agent

The StateAct Agent (Rozanov and Rei, 2025) continuously tracks the agent state and task goal during step-by-step reasoning and acting. Following the original formulation, the context vector at time step t is defined as $c_t = (g_0, s_t, r_t, a_t)$, where g_0 is the goal, s_t is the current state, r_t is the step-wise reasoning result, and a_t is the selected action. We implement StateAct with minor prompt modifications for the Trinity environment and use JSON-formatted outputs with the keys “current_location”, “current_inventory”, “think”, and “act”. For HAE tasks, human attributes are incorporated into the user instruction and included in the goal input g_0. Following the original implementation, the agent outputs None” for the think” field when intermediate reasoning is unnecessary.

D.5 StateAct Agent System Prompt

Listing 14: StateAct Agent System and User Prompt

<System Prompt>

```
You are an advanced robot with
ability to track state like '
current_location', and '
current_invengory', think, and
act. For each step, you must
generate a JSON output containing
 four keys: "current_location", "
current_inventory", "think", "act
".

1. current_location: Current
location of the agent.

2. current_inventory: Current
inventory object of the agent.

3. think: Use reasoning to
satisfy the current goal
condition

4. act: Execute a specific action
 to accomplish the current goal
condition. You should use one of
actions of this list: [go to,
pick up, put down, open, close,
turn on, turn off, slice, done,
failure]

### You should follow the rules
below:

1. You must generate 'think'
first, then generate 'act'.

2. You should generate only next
step from the given trajectory.

3. When you output 'act', you
should use one of actions of this
 list: [go to, pick up, put down,
 open, close, turn on, turn off,
done, failure].

4. Now I give you some example as
 "Source Domain" for output
format and the step-by-step
action selection.

5. You should refer the "Source
Domain" to generate next step of
the given "Target Domain"
trajectory.

6. Your output must contain "
think" and "act" keys as JSON
format.

### Example of output format

[Input]
```

Input Example (Instruction + Trajectory)

```
[Output]
```

{**“current_location”** : "starting location", **“current_inventory”** : None , **“think”** :"To solve the task, I need to ...", **“act”** :"go to Toilet (1)"}

<User Prompt>

```
s
### Source Domain:

[One relevant example]

### Target Domain:

[Current trajectory]
```

E Trinity Environment

E.1 Trinity Environment

The Trinity environment is a partially observable multi-room setting. Agents are provided only with the room layout, including receptacle locations and the list of rooms, together with an egocentric list of currently visible objects and their states. They cannot interact with objects or receptacles outside the current room or beyond their visible range. We implement low-level actions that follow commonsense constraints under partial observability. Examples of these actions are shown in Table 14. Each environment is built on a PROCTHOR-10K house layout with up to 10 rooms and extended with additional collected objects. An example house layout is shown in Fig. 8.




Figure 8: An example of a multi-room scene sampled from the PROCTHOR-10K dataset is shown.



Figure 9: Examples of newly added object renderings in the HAE dataset. We introduce a variety of items related to food, beverages, and hobbies that can influence multiple human attributes.

F AE Dataset Collection

AE is a multi-room dataset built from ALFRED task types and object templates, where goal conditions are defined by the target object, its required state, and the target receptacle. Using these templates, we automatically filtered PROCTHOR-10K scenes by checking the presence of required objects, task-specific interactive items, and whether target objects were already placed in goal receptacles, then sampled compatible scenes and reconstructed them in AI2-THOR, excluding scenes that failed to load. To ensure reproducibility, we store each scene's initial agent state in JSON, and to enrich task diversity, we additionally generate natural language instructions for each task using an LLM with ALFRED-based instruction examples and previously generated outputs as context. Finally, we verified that all tasks in the dataset are solvable using a heuristic oracle task solver.

G HAE Dataset Collection

HAE dataset contains four tasks—prepare drink, prepare food, prepare both food and drink, and prepare hobby—and is designed to test whether agents can act in accordance with user attributes. We first sample PROCTHOR-10K scenes containing essential assets such as a fridge, microwave, and target receptacle, then collect task-relevant objects from Objaverse and AI2-THOR and categorize them into allowed and prohibited sets based on dietary restrictions, religious beliefs, allergies, and hobbies. To enforce attribute-aware reasoning, each scene includes exactly one prohibited object for each attribute setting and only one valid object for each required sub-goal. Each task uses a fixed, attribute-agnostic instruction paired with a natural-language user profile, and success requires placing all required valid objects on the target receptacle while avoiding prohibited ones.

For prohibited-object construction, we define attribute-specific negative object lists, including hobby-associated items, while avoiding ambiguous cases. An object is labeled prohibited if its primary ingredient conflicts with a user's allergy, religion, or diet; cross-contamination is ignored due to ambiguity; and otherwise permissible items are assumed to have relevant Halal or Kosher certification when certification would normally be required. This design prevents shortcut reasoning and encourages agents to infer the most appropriate object from the scene context.

Table 14: The list of implemented available set of skills.



Command	Description	Images
“go to GarbageCan (1)”	Object Navigation: The agent cannot move toward an object located in a different room from where it currently is.	
“go to LivingRoom (1)”	Room to room navigation: The agent can move room to room in the house.	
“pick up Book (1)”	Picking up the object	
“put down Book (3)”	placing the object	
“slice Potato (2)”	Slicing the object. The agent should be holding the slicing tools such as ButterKnife, and Knife.	
“turn on TV (1)”	Toggling on the object.	
“turn off DeskLamp (1)”	Toggling off the object.	

Table 15: Definitions of Allowed and Prohibited Items in the HAE Dataset

Attributes	Sub Attribute	Definition
Allergy	Fish	All fish—such as baked saury and canned tuna—as well as any foods or beverages containing these ingredients.
	Alcohol	All items containing alcohol, such as whiskey or beer.
	Caffeine	All items containing caffeine, such as coffee or energy drinks.
	Meat	This includes all meats and processed meats—such as beef pork, ham, and SPAM—as well as foods or beverages any containing these ingredients.
	Nitrite	All processed meats containing nitrites—such as ham and SPAM—as well as any foods or beverages containing these ingredients, for example hot dogs and baked beans.
	Nuts	All nuts—such as peanuts and chestnuts—as well as any foods or beverages primarily containing these ingredients, for example almond croissants and peanut butter.
	Shellfish	All shellfish—such as shrimp and raw oysters—as well as any foods or beverages containing these ingredients, for example, octopus salad.
	Sulfite	All items containing sulfites—such as wine or beer.
Religion	Hinduism	All beef—and any foods or beverages containing beef.
	Islam	All non-Halal foods and any items containing non-Halal ingredients are excluded. If a product's primary ingredient is Halal, we treat it as Halal-certified even without an explicit "Halal certification" label.
	Judaism	All non-kosher foods and any products containing non-kosher ingredients are excluded. If a product's primary ingredient is inherently kosher, we assume it is kosher-certified—for example, a can of chicken breast is considered kosher even without an explicit "kosher certified" label.
Diet	Vegan	All meats, fishes and animal-derived ingredients—such as milk and eggs—or products in which these are the primary ingredients.
	Lacto-Ovo Vegetarian	All meats, fishes and any products, foods, or beverages in which meat and fish are the primary ingredient.
	Pesco Vegetarian	All meats, as well as any foods, products, or beverages where meat is the main ingredient.