Planning Before Reasoning: A Vision-Language Dataset for Structured Stepwise Reasoning in Document Understanding

DongJae Shin[1]*, Hangyeol Yoo[2]*, Yerin Nam[2], Hoyeon Shin[3]
SeungWoo Song[2], Seohyun Song[3], Donghun Yang[4], KyungTae Lim[2]

[1]TutorusLabs [2]KAIST [3]Seoultech [4]KISTI

djshin1998@tutoruslabs.com, {hg.yoo,yerinnam,sswoo,ktlim}@kaist.ac.kr,
{hy_shin, alexalex225225}@seoultech.ac.kr, yangdonghun3@kisti.re.kr

Abstract

This paper introduces DocPlan, a vision-language training dataset designed to emulate the stepwise reasoning strategies employed by human during visual document understanding. DocPlan was constructed to enable vision-language models (VLMs) to effectively learn the structured reasoning process that humans typically follow when interpreting documents. We reorganized existing document understanding datasets into 133K examples annotated with the following four sequential stages: Recognition → Planning → Extraction and Reasoning → Conclusion. To evaluate the effectiveness of DocPlan, we fine-tuned the direct prediction-based VLMs to perform stepwise reasoning generation across these stages. The experimental results demonstrated that our approach achieved up to a 13.8%p improvement in accuracy on document-based benchmarks. [1] [2]

1 Introduction

Humans intuitively and effectively understand patterns and trends in data by utilizing not only text but also visual information when reading documents (Islam et al., 2024). Recently, various datasets have been proposed to enhance the document comprehension abilities of vision-language models (VLMs) to human-level performance (Mathew et al., 2022; Masry et al., 2022; Mathew et al., 2021). However, existing studies have predominantly focused on quantifying the understanding of documents and visual materials by relying solely on direct prediction methods. This approach presents challenges for VLMs to learn the reasoning processes underlying their answers (Zhang, 2024; Islam et al., 2024). Consequently, persistent concerns have been raised regarding the interpretability and reliability of these models (Jin et al., 2024). For instance, Figure 1 illustrates a representative case of a think-answer mismatch, identified through the restructuring of `Llama3.2-Vision` based on the "Think-Then-Respond" framework (Jin et al., 2024). According to the experimental results, it was frequently observed that even when the model eventually produced the correct answer, it often engaged in illogical reasoning or relied on incorrect information. This phenomenon has also been reported in commercial models. For instance, GPT-4V demonstrated a correct answer accuracy but exhibited an error rate of more than 27.2% in image interpretation processes (Jin et al., 2024).




Figure 1: An example where the answer is correct despite errors in intermediate reasoning on ChartQA

In this context, we raise the following question: "How can a VLM be endowed with the ability to plan and reason on the basis of verified facts in a manner comparable to that of humans?" This study emphasizes the necessity of stepwise reasoning-based vision-language datasets that mimic human visual cognitive problem-solving strategies. According to prior research, when interpreting documents and visual materials, humans typically follow a sequential process such as "problem identification and planning → visual cue selection → text alignment → value comparison → conclusion (Goldberg and Helfman, 2011; Peebles and Cheng, 2003; Acartürk and Habel, 2012)". Reflecting these human cognitive strategies, this paper introduces DocPlan-pipe, comprising the following four stages: "Recognition → Planning → Extraction and Reasoning → Conclusion (referred

[1]DocPlan Dataset (HuggingFace)
[2]DocPlan-HF Dataset (HuggingFace)

Findings of the Association for Computational Linguistics: EMNLP 2026, pages 21022–21061
October 24-29, 2026 ©2026 Association for Computational Linguistics

Dataset	Images	Text type	Captioned by	# Images	# Questions	Open	Descriptive	Reason	Extraction	Plan
DocVQA	Documents	Pr,Tw,Hw,BD	Human-annotated	10K	39 K	✓	✗	✗	✗	✗
InfoVQA	Infographics	BD	Human-annotated	2K	14K	✓	✗	✗	✗	✗
ChartQA	Charts	BD	Human-annotated, Machine-generated	18K	28K	✓	✗	✗	✗	✗
TableVQA	Tables	BD	Human-annotated, GPT-based	1K	1.5K	✓	✗	✗	✗	✗
OCR-VQA	Book Covers	BD	Human-annotated, Template-based	207K	1M	✓	✗	✗	✗	✗
PlotQA	Plots, Graphs	BD	Human-annotated, Template-based	225K	28M	✓	✗	✗	✗	✗
FigureQA	Graphs	BD	Machine-generated	120K	1.5M	✓	✗	✗	✗	✗
Llava-CoT	Doc,Chart,General	Pr,Tw,Hw,BD	GPT-based	100K	410K	✓	✓	✓	✗	✗
LlamaV-o1	Doc,Chart,General	Pr,Tw,Hw,BD	GPT-based	174K	unknown	✗	✓	✓	✗	✗
Ours	Doc,Chart,Info	Pr,Tw,Hw,BD	GPT-based	28,954	133,623	✓	✓	✓	✓	✓

Table 1: **Summary of VQA train datasets where text on the images must be read to answer questions.** Text type abbreviations are as follows: Born Digital: BD, Printed: Pr, Handwritten: Hw, Scene Text: ST, and Typewritten: Tw

to as DocPlan-pipe)". Based on this framework, we propose the DocPlan dataset, a comprehensive dataset consisting of approximately 133K samples derived from publicly available document-based visual question answering (VQA) datasets (DocVQA, InfoVQA and ChartQA). DocPlan includes newly generated questions that are based on visual documents and present a step-by-step reasoning process for solving them. In particular, it employs various specialized tags grounded in the structured thinking approach (Wen et al., 2025), designed to encourage models to independently plan and execute their thought processes.

Against this backdrop, the central question addressed by the proposed DocPlan dataset is whether VLMs can inherently acquire human-like planning and reasoning abilities directly from training data. To investigate this, we fine-tuned VLMs, originally utilizing a direct prediction approach, with the DocPlan dataset and subsequently evaluated their performance on document-based benchmarks. The results demonstrated that the proposed model achieved performance improvements of up to 13.8%p compared with traditional methods, particularly excelling in resolving complex reasoning tasks with greater accuracy and consistency.

Furthermore, the model trained on the DocPlan dataset demonstrated an improvement in terms of interpretability of the reasoning process compared to existing reasoning models. The primary contributions of this study can be summarized as follows:

- We release **DocPlan**, a four-stage (perceive, plan, reason, conclude) reasoning dataset reflecting human problem-solving behavior.
- We propose a diversity-aware pipeline for generating and filtering high-quality synthetic data tailored to VLMs.
- We conduct an in-depth study showing that explicit plan-and-reason training boosts both benchmark accuracy and interpretability.

2 Related Work

2.1 Visual Document Understanding Dataset

Recently, the rapid progress of VLMs for visually grounded document understanding has led to the emergence of various datasets designed to improve and evaluate model performance. Early datasets such as TextVQA (Singh et al., 2019) and OCR-VQA (Mishra et al., 2019) primarily focused on extracting and recognizing text within images, subsequent datasets such as DocVQA (Mathew et al., 2021) and DocMatix (Laurençon et al., 2024) expanded their scope to include the comprehension of complex structures and layouts in real-world documents. Furthermore, datasets that independently address detailed document elements such as plots (PlotQA (Methani et al., 2020), FigureQA (Kahou et al., 2017)), charts (ChartQA (Masry et al., 2022)), tables (TableVQA (Kim et al., 2024)), and infographics (InfoVQA (Mathew et al., 2022)) have been proposed.

Comparing the "images" and "text type" attributes, as presented in Table 1, we can observe that existing datasets possess mutually complementary characteristics. For example, DocVQA and InfoVQA are similar in that both require text recognition within images. However, InfoVQA additionally demands the ability to interpret complex layouts and multiple charts that characteristic of infographics. ChartQA and PlotQA primarily focus on numerical logical reasoning tasks (such as classification and comparison), whereas DocVQA emphasizes text-centric question answering.

Recently, training data generated by augmenting existing datasets with reasoning processes have also been proposed. For example, Llava-CoT (Xu et al., 2025) utilized GPT-4o (OpenAI et al., 2024) to construct approximately 100K reasoning-augmented data based on existing VQA datasets, and similarly, LlamaV-o1 (Thawakar et al.,




Figure 2: Example of DocPlan training data. DocPlan is an reasoning-oriented training dataset designed for document understanding. Unlike conventional datasets that consist solely of question–answer pairs, DocPlan extends each instance into five distinct query types and decomposes the reasoning process into four structured stages, namely, (1) query analysis, (2) definition plan, (3) execution plan (extraction and inference), and (4) final answer.

2025) proposed sequential reasoning data derived from step-by-step dialogues with GPT-4o. However, these differ in purpose and approach from the explicit and systematic "Recognition → Planning → Extraction and Reasoning" process emphasized in this study. The detailed characteristics and more specific comparisons of each dataset are provided in the Appendix A.

2.2 VLMs with Reasoning and Planning

Early VLMs, such as BLIP (Li et al., 2023), Llava (Liu et al., 2023), and Kosmos-2 (Peng et al., 2023), primarily focused on the alignment between general language models and visual encoders. Following the success of reasoning-centered language models, these reasoning methodologies began to be actively incorporated within the vision-language field as well. Notably, Llava-CoT introduced a four-stage reasoning mechanism to improve accuracy in complex visual queries, and the LlamaV-o1 model strengthened reasoning capabilities through multi-stage curriculum learning, achieving competitive performance compared to with closed models such as GPT-4o or Gemini-1.5-Flash (Team et al., 2024).

However, these models still exhibit a gap with respect to the systematic visual-cognitive strategies employed by humans during document interpretation stages including "problem identification and planning → visual cue selection → text alignment → value comparison → conclusion". To address this gap, the read-think model (Zhang, 2024) emerged, explicitly reflecting human planning and information extraction steps, resulting in significant performance improvements on the DocVQA task. This research emphasizes that the verification capability of the model's reasoning process of a model diminishes if the information extraction steps are not explicitly clarified.

3 Proposed Dataset

In this section, we describe the construction method of the DocPlan dataset following the DocPlan-pipe structure. This dataset is designed to enable the model to acquire stepwise reasoning capabilities based on human cognitive strategies.

3.1 Overall Structure of the DocPlan Dataset

The DocPlan dataset comprises four stages to reflect the DocPlan-pipe structure: (1) query analysis, (2) definition of plan, (3) plan execution (extraction and reasoning), and (4) final answer generation. Figure 2 shows a data sample that includes the four proposed stages of DocPlan. In contrast to the conventional method that provides only the query




Figure 3: Construction process of the DocPlan dataset consists of three stages: (1) query generation, (2) plan and reasoning generation, and (3) data filtering

and final answer (as shown in the example in Figure 1), this approach is distinguished by explicitly presenting four additional pieces of information. The specific contents of each stage are as follows:

Query Analysis (<QUERY_ANALYSIS>). This stage is the starting point that analyzes the core requirements from the given query, determining the direction for subsequent planning and response generation. The results of the query analysis enhance the consistency and accuracy of the reasoning process and improve the interpretability of the final answer. This stage is denoted by the special tag, <QUERY_ANALYSIS>.

Definition of the Plan (<DEF_PLAN>). In this stage, an overall strategy for query resolution is established based on the preceding query analysis. After the VLMs clearly understand the query objective, the query is divided and structured into detailed, achievable sub-goals, systematically defining the sequence of tasks to be performed in subsequent stages. This process is denoted by the <DEF_PLAN> tag, signaling the initiation of planning, and the <SUB_PLAN> tag, indicating detailed sub-goals.

Execution of the Plan (<EXEC_PLAN>). In this stage, the previously defined sub-goals are sequentially executed. Here, the process is designed to integratively conduct information extraction and reasoning because performing extraction and reasoning separately frequently results in a phenomenon in which the original goal is forgotten during reasoning (Trivedi et al., 2023). To address this issue, at each execution of the sub-goals, the task objectives and execution processes are explicitly reconfirmed, necessary information is extracted from the document (<EXTRACTED_INFO>), reasoning is performed based on this information (<THINK>), and an intermediate answer regarding the specific plan (<PLAN_ANS>) is derived.

Generation of the Final Answer (<FINAL_ANS>) In the final stage, the intermediate results from the previous stages are synthesized to generate a final response to the user query. Through this, a logical and clear final conclusion can be provided.

3.2 Data Construction Method

We utilized the existing datasets, DocVQA, ChartQA, and InfoVQA datasets. Figure 3 illustrates the overall process for constructing the DocPlan dataset, that is largely divided into (1) question generation, (2) planning and reasoning data generation, and (3) filter and validation stages. Each stage was conducted independently using the Qwen2.5-VL model (Bai et al., 2025b) to enhance the generation quality. The detailed procedures for each stage are as follows, and specific prompts can be provided in the Appendix B.

Image Collection. We utilized all images provided in the existing training datasets of DocVQA, InfoVQA, and ChartQA without modification. We secured a total of 28K images while maintaining the original image quality and document structure.

Generation of the Query. Most queries and answers in existing datasets primarily consisted of simple information extraction queries that limited the learning of higher-order complex reasoning. Although prior studies, such as Llava-CoT addressed this issue by filtering for only complex queries, this

ultimately reduced both the number and diversity of queries (Appendix B.4). Therefore, in this study, we additionally generated high-level complex reasoning queries suited to the document domain. We referred to the query classification framework of MMStar (Chen et al., 2024) and defined five types of document-specific queries. Step 1 in Figure 3 illustrates the query generation process, and examples of the generated queries are shown at the bottom of Figure 2. The five query types were as follows:

- Fine-Grained Perception (FP): Extraction of details such as names, dates, and figures.
- Coarse Perception (CP): Understanding the overall structure and layout.
- Instance Reasoning (IR) : Analysis of the relationships among elements within the document.
- Logical Reasoning (LR): Logical flow of the document and reasoning of implicit conclusions.
- Mathematics (MA): Numerical calculation and comparison within the document

The query difficulty was defined by reconstructing the criteria from previous studies (Choi et al., 2021; Hendrycks et al., 2021; Hosseini et al., 2024) into three levels: Basic, Intermediate, and Advanced. Query generation was performed using the Qwen2.5-VL model with prompts reflecting these query types and difficulty levels (see Appendix B.2), resulting in 80K newly created queries. Combined with 82K queries from existing datasets, this yielded a total of 162K queries.

Generation of the Query Analysis. Query analysis (<QUERY_ANALYSIS>) was performed for each of the 162K constructed queries to clarify the user intent and the type of response desired.

Generation of Plan. Using the generated query and the result of the query analysis as inputs, a specific detailed plan (<DEF_PLAN>) for the final answer was derived. At this stage, the system was designed to automatically determine the number (N) of detailed sub-plans (<SUB_PLAN>) according to the type and difficulty of the query.

Generation of the Extraction and Reasoning Process. Each detailed plan was used as an input to extract relevant information from the document and subsequently generate a corresponding reasoning process. This procedure was iteratively repeated N times, according to the number of sub-plans defined. In each iteration, the intermediate reasoning outcomes from previous steps were referenced to ensure logical coherence and continuity throughout the entire problem-solving process.

Generation of the Final Answer. The final answer was generated by integrating all the intermediate results produced in the preceding steps.

3.3 Data Filtering

The initial DocPlan dataset (162K samples) was synthesized using a Vision-Language model (Qwen2.5-VL), and therefore may contain various types of noise such as mismatches between images and text or hallucinations. To address these issues, this study applies a filtering process, as illustrated in Step-3 of Figure 3, to refine the data. The filtering process distinguishes between origin queries (82K), which have ground-truth answers, and generated queries (80K), which are without ground-truth answers. Filtering strategies tailored to the characteristics of each query type are applied.

Origin Queries For origin queries with ground-truth answers, a rule-based tag validation is first performed to filter out samples with formatting issues such as missing tags, undefined token usage, or structural errors. Then, for the samples that pass this validation, the tuple (Image, Question, Reasoning Trace, Final Answer, Ground Truth) is input into Qwen2.5-VL, GPT-4o, and Gemini 2.0. Each model generates results of evaluation metrics with confidence metric(Question Interpretation Accuracy, Image-Reasoning-Answer Consistency, Overall Appropriateness, and Answerable Without Image, Answer–Ground-truth Agreement, Suitable for Training Data). Based on the results of these metrics, an additional filtering process is conducted using a Model Agreement strategy, which ultimately refines the DocPlan data derived from origin queries.

Generated Queries For generated queries, a modified approach is applied since ground-truth answers are not available. First, the (Image, Query) pair is input into the GPT-4o model to assess the validity of the query in relation to the image, filtering out inappropriate generated queries. For the filtered samples, the same rule-based tag validation used for origin queries is then applied. Since ground-truth answers are not available for these refined generated query samples, only the (Image, Query,

Reasoning Trace, Final Answer) tuple is used for model agreement-based filtering.

Consequently, the DocPlan dataset comprises 133,623 curated samples 68,513 from original queries and 65,110 from generated queries. Prompts and sample counts for each filtering stage are detailed in Appendix B.5.

4 Experiment

This section describes the experimental method used to verify the effectiveness of the DocPlan dataset and presents the results.

4.1 Experimental Settings

We quantitatively evaluated the effectiveness of the DocPlan data on widely used open-source VLMs. The experiments were conducted separately for document-domain benchmarks (DocVQA_val, InfoVQA_val, ChartQA_test, and ChartQAPro_test (Masry et al., 2025)). DocVQA and InfoVQA are evaluated using the ANLS metric, while ChartQA and ChartQAPro use accuracy scores based on the LLM-as-a-judge (Zheng et al., 2023) approach with GPT-4o. Following Xu et al. (2025), training was conducted using visual instruction following, a commonly adopted post-training approach for VLMs, for a total of three epochs. All evaluations were performed fairly under consistent conditions using VLMEvalKit (Duan et al., 2024). The detailed hyperparameters for model training and evaluation are described in the Appendix C.

4.2 Intrinsic Evaluation of the Model

Table 2 presents the results of the performance comparison among the models trained under various data conditions. The models presented in this table are distinguished based on the following data.

- **`+origin dataset`**: A model trained on 82K instances from the existing DocVQA, InfoVQA, and ChartQA datasets without any reasoning process
- **`+DocPlan(origin)`**: A model trained on 68K reasoning data filtered after converting the original 82K data into the DocPlan format
- **`+DocPlan`**: A model trained on the aforementioned 68K data (DocPlan(origin)) along with an additional 65K generated queries

Impact of DocPlan Data. Table 2 presents for a comparison between the performance of the baseline model and the model trained with the DocPlan data. Overall, a clear performance improvement was observed when using the DocPlan data for Llama3.2 (Grattafiori et al., 2024), SmolVLM2 (Marafioti et al., 2025), paligemma2 (Steiner et al., 2024) and gemma3 (Team et al., 2025). In particular, paligemma2 showed a 13.8%p improvement in performance (from 40.1 to 53.9) when trained with DocPlan, demonstrating that the DocPlan data effectively enhances the document and chart understanding capabilities of the model.

Model	DocVQA	InfoVQA	ChartQA	ChartQAPro	Avg
SmolVLM2-2.2B	**80.9**	**47.6**	66.1	17.8	53.1
+origin dataset	77.0	45.1	63.3	18.3	50.9
+DocPlan(origin)	75.8	43.8	70.8	17.1	51.9
+DocPlan	80.1	44.4	**72.7**	**18.9**	**54.0**
gemma-3-4b-it	62.0	30.1	57.4	21.6	42.8
+origin dataset	**83.7**	50.3	76.1	24.1	58.6
+DocPlan(origin)	82.7	**52.9**	81.0	27.3	**61.0**
+DocPlan	82.8	50.4	**81.3**	**28.9**	60.9
Qwen2-VL-7B	**93.1**	72.7	83.1	26.6	68.9
+origin dataset	89.2	66.0	78.6	23.1	64.2
+DocPlan(origin)	91.8	**73.4**	79.9	29.9	68.8
+DocPlan	91.8	71.2	**83.2**	**30.0**	**69.0**
paligemma2-10B	69.0	34.9	34.2	**22.4**	40.1
+origin dataset	71.9	39.5	67.6	16.6	48.9
+DocPlan(origin)	74.9	**42.3**	71.5	20.7	52.3
+DocPlan	**76.4**	**42.3**	**74.5**	**22.4**	**53.9**
Llama3.2-11B-V	83.0	41.0	74.2	11.0	52.3
+origin dataset	87.8	59.5	73.4	16.5	59.3
+DocPlan(origin)	90.4	**68.3**	79.8	27.1	66.4
+DocPlan	**91.5**	68.2	**86.6**	**30.6**	**69.2**

Table 2: Comparison of model performance across various benchmarks under different training configurations.

Direct Prediction vs Plan-Reason Prediction. Table 2 compares the performance of models trained with the `+origin dataset` and `+DocPlan(origin)`, highlighting the impact of restructuring the original data into a planning and reasoning-oriented format. Through this, we evaluate the benefits of integrating structured intermediate reasoning steps into the training process. The results showed that the Llama3.2 model explicitly trained on planning and reasoning processes exhibited a 7.1%p improvement in performance (from 59.3 to 66.4) compared with the conventional approach. Similarly, gemma3 also showed a 2.4%p gain (from 58.6 to 61.0), with particularly notable improvements in tasks that required complex reasoning.

Effectiveness of The Generated Data. One contribution of this study is the use of the generated queries as training data; which differs from previous studies. In this case, incorrect answers may be naturally included. According to prior research, even data that include incorrect answers can positively affect model performance if the over-

Model	#Param	DocVQA	InfoVQA	ChartQA
Commercial (Zero-shot)				
GPT-4o	-	85.6	65.1	85.7
GPT-4.1	-	88.3	70.1	81.0
Claude-3.5 Sonnet	-	86.1	47.8	90.8
Open (Fine-tuned)				
Llava-CoT	11B	89.8	69.6	82.6
Llama-3.2+DocPlan	11B	91.5	68.2	86.6

Table 3: Performance comparison of various models on document VQA benchmarks. Zero-shot commercial systems are shown separately from our fine-tuned open models.

all inference quality is high (Muennighoff et al., 2025). Accordingly, we hypothesized that a similar positive effect would be observed in VLMs, and we validated this hypothesis through experiments. A comparison between +DocPlan(origin) and +DocPlan, as presented in Table 2 showed that DocPlan using the generated queries demonstrated an approximately 2.8%p higher performance in the case of Llama3.2 In particular, the improvement was more pronounced in the ChartQA task, where the proportion of generated queries was higher (presumably because of the large proportion of ChartQA queries among the generated data). This supports the hypothesis that the generated data have a positive effect on the performance of VLMs.

Reasoning Capability in Small-Scale Models. As reported in the field of language models, small models tend to exhibit limited performance improvements when trained on data involving long reasoning processes. In this experiment, the small model, SmolVLM2-2.2B, exhibited only a 0.9%p performance improvement in DocPlan training compared with direct prediction (baseline). This contrasted with the 16.9%p improvement achieved by the 11B-sized model under the same conditions indicating that the performance of the small model was limited because of frequent repetition issues during long reasoning processes (approximately 4% of incorrect cases). This result exhibits a trend similar to the limitations of small models observed in the language model.

4.3 Comparative Analysis of Performance with External Models

Table 3 presents the results of performance comparisons on the Document Task between the DocPlan model and external models. The DocPlan model (Llama-Vision) demonstrates superior performance compared to both the open-source reasoning model (Llava-CoT) and commercial models (GPT-4o, Claude-3.5). This indicates that DocPlan can achieve competitive performance in the Document Task with a comparatively small dataset and resources, outperforming large-scale general-purpose models.

Model	DocVQA	InfoVQA *In-domain*	ChartQA	TextVQA *Held-out*
Qwen3-VL-8B-Instruct	93.94	77.37	75.92	**86.72**
+DocPlan	**94.28 (+0.34)**	**83.11 (+5.74)**	**83.32 (+7.40)**	86.06 (-0.66)
Gemma3-4B-it	62.0	30.1	57.4	58.14
+DocPlan	**82.8 (+20.8)**	**50.4 (+20.3)**	**81.3 (+23.9)**	**62.91 (+4.77)**

Table 4: Performance on document VQA benchmarks. DocVQA, InfoVQA, and ChartQA are in-domain; TextVQA is a held-out benchmark not seen during fine-tuning.

Model	MMMU	Model	MMMU
SmolVLM2-2.2B	39.8	Qwen2-VL-7B	51.2
+origin dataset	29.9	+ origin dataset	40.3
+DocPlan(origin)	0.2	+ DocPlan(origin)	43.4
+DocPlan	0.2	+ DocPlan	46.0
paligemma2-10B	36.0	Llama3.2-11B-Vision	44.9
+ origin dataset	38.8	+ origin datasets	13.7
+ DocPlan(origin)	33.1	+ DocPlan(origin)	25.9
+ DocPlan	33.4	+ DocPlan	29.9

Table 5: Comparison of various models on MMMU benchmark.

4.4 Generalization and Robustness

In-domain vs. Held-out Generalization. We further examine whether the improvements from DocPlan generalize beyond the benchmarks used for fine-tuning. DocVQA, InfoVQA, and ChartQA constitute the in-domain benchmarks, while TextVQA is held out and not seen during fine-tuning. As shown in Table 4, Gemma3-4B-it+DocPlan achieves a gain of +4.77%p on TextVQA, suggesting that DocPlan does not simply induce overfitting to the three source datasets but instead teaches a structured reasoning ability that transfers to unseen domains. For Qwen3-VL-8B-Instruct (Bai et al., 2025a), which already performs strongly on TextVQA (86.72), performance remains essentially unchanged after DocPlan training (86.06, -0.66%p), we take this small a change to be within the range of run-to-run variation rather than evidence of catastrophic forgetting. At the same time, in-domain gains hold even for this already strong model, with clear improvements on the benchmarks that require multi-step reasoning, InfoVQA (+5.74%p) and ChartQA (+7.40%p). Together, these results indicate that DocPlan improves reasoning in the target domain without sacrificing held-out performance, even for recent and stronger base models.

Model	DocVQA	InfoVQA	ChartQA	Avg
Llama-3.2-11B-V	83.1	41.0	74.2	66.1
+origin dataset	87.8	59.5	73.4	73.6
(+Query Analysis)	87.1	61.7	74.1	74.3
(+Definition of Plan)	87.3	61.2	74.2	74.2
(+Execution of Plan)	**90.4**	**68.3**	**79.8**	**79.5**

Table 6: Ablation study of the DocPlan-pipe stages on Llama3.2-11B-Vision using +DocPlan(origin) data.

Model	Setting	DocVQA	InfoVQA	ChartQA
Gemma3-4b	free-form CoT	53.46	36.1	54.0
	+DocPlan	**82.8**	**50.4**	**81.3**
Llama-Vision	free-form CoT	84.71	54.83	58.3
	+DocPlan	**91.8**	**71.2**	**83.2**

Table 7: Controlled comparison between free-form Chain-of-Thought (CoT) prompting and DocPlan's structured reasoning supervision, using the same base models.

Effectiveness of General Tasks. We analyze the impact of the DocPlan data on the general-purpose benchmark MMMU_dev_val (Yue et al., 2024), which evaluates generic images and object recognition outside the document/chart domain. As shown in Table 5, fine-tuning with DocPlan led to a performance drop compared with the baseline, though this degradation was considerably smaller for models with stronger underlying capacity than for those trained with direct prediction (+origin dataset). For instance, Llama3.2-11B-Vision dropped less under DocPlan (-15.0%p) than under direct prediction (-31.2%p), and Qwen2-VL-7B similarly showed a smaller drop under DocPlan (-5.2%p) than direct prediction (-10.9%p). This suggests DocPlan-based training better preserves general reasoning ability in sufficiently capable base models.

5 Ablation Study and Analysis

Comparison with Free-form Chain-of-Thought. We compare DocPlan against free-form Chain-of-Thought (CoT) prompting, in which the model is asked to reason step by step without any structured stage supervision. Table 7 reports results for Gemma3-4b and Llama-Vision under both settings. Across all three benchmarks, models trained with DocPlan substantially outperform their free-form CoT counterparts, with Gemma3-4b+DocPlan improving over free-form CoT by up to +29.34 points on DocVQA and +27.3 points on ChartQA. Llama-Vision+DocPlan shows a similar pattern, with the largest gain of +16.37 points on InfoVQA. These results indicate that the benefit of DocPlan does not simply come from encouraging step-by-step reasoning in general, but from DocPlan-pipe, the explicit four-stage structure (Recognition, Planning, Extraction and Reasoning, Conclusion) that guides the model toward more reliable intermediate reasoning.

Model	DocVQA	InfoVQA	ChartQA	AVG.
Llava-CoT	62.8	38.3	53.4	51.5
Llama3.2+DocPlan	**87.2**	38.3	**60.6**	**62.0**

Table 8: Comparison of Llama3.2+DocPlan and Llava-CoT based on their reasoning traces

Analysis of the Importance of Each Stage. The DocPlan dataset is designed to guide models through a sequential reasoning process. A critical question here is identifying which stages primarily contribute to performance improvements. Table 6 shows results from training the Llama-3.2 model under various conditions with the +DocPlan(origin) dataset. Specifically, (+Query Analysis) uses only <QUERY_ANALYSIS> and <FINAL_ANSWER>. (+Definition of Plan) adds <DEF_PLAN> to this configuration; (+Execution of Plan) includes all stages. Our analysis reveals that including <EXEC_PLAN> yields the largest improvement (5.3%p). In contrast, <QUERY_ANALYSIS> and <DEF_PLAN> show minimal gains, likely due to their similarity to the +origin dataset baseline.

Evaluation of Interpretability. A key advantage of the proposed planning methodology is enhanced interpretability. To validate this claim, we employed the Simulatability Test, which measures answer accuracy using only the reasoning process, without incorporating image input. Both quantitative and qualitative evaluations were performed, with the corresponding results reported in Table 8 and Figure 4. Further details are provided in Appendix E. Experimental results demonstrate that the DocPlan model outperforms Llava-CoT by 10.5%p in quantitative evaluation. In qualitative evaluation, DocPlan achieves an average win rate of 71.3%, surpassing Llava-CoT (26.1%) by 45.2%p. These findings suggest that the planning methodology employed in DocPlan can effectively improve interpretability over conventional reasoning structures.

Effectiveness of Human Filtering and Error Analysis To refine the dataset beyond the automatic filtering described in Section 3.3, we applied an additional human filtering step targeting data points with a high likelihood of errors. We hypothesized that a high-quality reasoning trace should allow GPT-4 to correctly infer the final answer; thus,




Figure 4: Preference evaluation results on interpretability by GPT: `Llama3.2+DocPlan` vs. `Llava-CoT`

Model	DocVQA	InfoVQA	ChartQA	Avg
`Llama-3.2-11B-V`	83.1	41.0	74.2	66.1
`+original dataset`	87.8	59.5	73.4	73.6
`+DocPlan(origin)`	90.4	68.3	79.8	79.5
`+Hard Filtering`	89.8	68.9	83.4	80.7
`+DocPlan`	**91.5**	68.2	**86.6**	**82.1**
`+Hard Filtering`	90.9	**69.2**	86.2	**82.1**

Table 9: Ablation study on the impact of Hard Filtering on `Llama3.2-11B-Vision`

discrepancies between trace-based predictions and ground-truth answers were used as indicators of potential errors. Through this "hard filtering" process, we identified 10,207 potentially erroneous instances from the original pool of 133,623 data points.

Three human annotators manually reviewed error instances, classifying them into six error types. The analysis revealed that most issues stemmed from formatting (e.g., Answer format, Measure) rather than core components like Reasoning or OCR. Of these, 7,041 cases involving minor issues, such as incorrect unit annotations, were rectified and reincorporated, while the remaining erroneous points were discarded.

The resulting refined dataset (`+Hard Filtering`) consists of 124,053 data points. As shown in Table 9, this process yielded an average performance improvement of 1.2%p for DocPlan(origin). While these results demonstrate that reasoning trace–based verification effectively maintains a low error rate, the marginal gains suggest that our original automated method also remains a practical, cost-effective alternative. Detailed definitions and verification procedures are provided in Appendix B.5.

Latency and Throughput Analysis DocPlan is designed to explicitly generate stepwise reasoning traces, ranging from `<QUERY_ANALYSIS>` to `<FINAL_ANS>`. Consequently, response lengths are inevitably longer compared to direct prediction methods, leading to increased inference latency. As

Model (token)	DocVQA	InfoVQA	ChartQA
`SmolVLM2-2.2B`	7.7	6.1	6.2
`+DocPlan`	418.1	494.7	489.3
`gemma-3-4b-it`	5.3	3.9	4.7
`+DocPlan`	466.0	624.9	598.2
`Qwen2-VL-7B`	6.1	4.4	4.5
`+DocPlan`	330.5	421.9	325.6
`paligemma2-10B`	4.8	3.7	3.8
`+DocPlan`	474.2	588.4	629.8
`Llama3.2-11B-V`	5.7	8.4	26.1
`+DocPlan`	177.5	285.3	284.3

Table 10: Average number of tokens generated in the response.

shown in Table 10, the average generated tokens increased significantly across all models, creating a clear throughput trade-off (see Appendix F).

However, this increase in inference cost should be interpreted as a Reliability Cost incurred to transparently disclose the model's decision-making logic, rather than mere verbosity. The results of the Simulatability Test in Section 5 quantitatively support this interpretation. When inferring the final answer using only the reasoning traces generated by the model excluding image input the DocPlan-trained model achieved 10.5%p higher accuracy compared to `Llava-CoT`. This indicates that the hundreds of generated tokens possess logical completeness and substantial evidentiary value required to reach the correct answer.

In conclusion, DocPlan provides a significant gain in interpretability that outweighs the necessary costs of transitioning from "black-box prediction" to "verifiable reasoning" in document understanding tasks where high reliability is paramount.

6 Conclusion

In this study, we introduce DocPlan, a novel dataset designed to comprehensively enhance planning and reasoning capabilities akin to human cognition within the visual document understanding domain. DocPlan systematically structures the entire process of planning and reasoning generation in a human-like manner, thereby addressing the limitations of conventional training paradigms that focus primarily on final answer prediction. Evaluation results on several state-of-the-art VLMs demonstrate that leveraging DocPlan achieves significant improvements over existing methods, both in terms of accuracy and interpretability of reasoning.

7 Limitations

While DocPlan yields consistent gains in accuracy and interpretability, we note several minor limita-

tions that primarily suggest directions for future work. First, the explicit generation of planning and reasoning traces increases output length compared to direct prediction. Although this overhead is intentionally introduced to improve transparency and is supported by the Simulatability Test, it may be unnecessary for applications requiring minimal explanation. Second, DocPlan is specialized for document-centric visual understanding tasks. Extending the proposed planning framework to broader vision–language domains remains an interesting future direction. Finally, our experiments focus on a representative set of open-source VLMs. Evaluating the approach across a wider range of architectures and scales may provide additional insights but is beyond the scope of this work.

Acknowledgements

This work was partly supported by Institute of Information & Communications Technology Planning & Evaluation(IITP) grant funded by the Korea government(MSIT) (RS-2026-25518137, Development of expandable Vision-Language-Action Models, 40%), Korea Institute of Science and Technology Information(KISTI) in 2026 (No. (KISTI)K26L3M1C1, 30%), and 'Open Source AI/SW Development and Utilization Support Project' through the Ministry of Science and ICT(MSIT) and the National IT Industry Promotion Agency(NIPA), Republic of Korea (Grant No. PJT-26-040055, 30%). This work also utilized GPU resources from the "Advanced GPU Utilization Support Program" funded by MSIT, Republic of Korea (awarded to KyungTae Lim).

References

Cengiz Acartürk and Christopher Habel. 2012. Eye tracking in multimodal comprehension of graphs. In *Proceedings of the workshop on technology-enhanced diagrams research*, volume 887, pages 11–25.

Shuai Bai, Yuxuan Cai, Ruizhe Chen, Keqin Chen, Xionghui Chen, Zesen Cheng, Lianghao Deng, Wei Ding, Chang Gao, Chunjiang Ge, et al. 2025a. Qwen3-vl technical report. *arXiv preprint arXiv:2511.21631*.

Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, Jiabo Ye, Xi Zhang, Tianbao Xie, Zesen Cheng, Hang Zhang, Zhibo Yang, Haiyang Xu, and Junyang Lin. 2025b. Qwen2.5-vl technical report. *Preprint*, arXiv:2502.13923.

Lin Chen, Jinsong Li, Xiaoyi Dong, Pan Zhang, Yuhang Zang, Zehui Chen, Haodong Duan, Jiaqi Wang, Yu Qiao, Dahua Lin, et al. 2024. Are we on the right way for evaluating large vision-language models? *Advances in Neural Information Processing Systems*, 37:27056–27087.

Seongho Choi, Kyoung-Woon On, Yu-Jung Heo, Ahjeong Seo, Youwon Jang, Minsu Lee, and Byoung-Tak Zhang. 2021. Dramaqa: Character-centered video story understanding with hierarchical qa. In *Proceedings of the aaai conference on artificial intelligence*, volume 35, pages 1166–1174.

Haodong Duan, Junming Yang, Yuxuan Qiao, Xinyu Fang, Lin Chen, Yuan Liu, Xiaoyi Dong, Yuhang Zang, Pan Zhang, Jiaqi Wang, et al. 2024. Vlmevalkit: An open-source toolkit for evaluating large multi-modality models. In *Proceedings of the 32nd ACM international conference on multimedia*, pages 11198–11201.

Joseph Goldberg and Jonathan Helfman. 2011. Eye tracking for visualization evaluation: Reading values on linear versus radial graphs. *Information Visualization*, 10:182–195.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, et al. 2024. The llama 3 herd of models. *arXiv e-prints*, pages arXiv–2407.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021. Measuring mathematical problem solving with the math dataset. *arXiv preprint arXiv:2103.03874*.

Pedram Hosseini, Jessica M Sin, Bing Ren, Bryceton G Thomas, Elnaz Nouri, Ali Farahanchi, and Saeed Hassanpour. 2024. A benchmark for long-form medical question answering. *arXiv preprint arXiv:2411.09834*.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, Weizhu Chen, et al. 2022. Lora: Low-rank adaptation of large language models. *ICLR*, 1(2):3.

Mohammed Saidul Islam, Raian Rahman, Ahmed Masry, Md Tahmid Rahman Laskar, Mir Tafseer Nayeem, and Enamul Hoque. 2024. Are large vision language models up to the challenge of chart comprehension and reasoning. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 3334–3368, Miami, Florida, USA. Association for Computational Linguistics.

Qiao Jin, Fangyuan Chen, Yiliang Zhou, Ziyang Xu, Justin M Cheung, Robert Chen, Ronald M Summers, Justin F Rousseau, Peiyun Ni, Marc J Landsman, et al.

2024. Hidden flaws behind expert-level accuracy of multimodal gpt-4 vision in medicine. *npj Digital Medicine*, 7(1):190.

Samira Ebrahimi Kahou, Vincent Michalski, Adam Atkinson, Ákos Kádár, Adam Trischler, and Yoshua Bengio. 2017. Figureqa: An annotated figure dataset for visual reasoning. *arXiv preprint arXiv:1710.07300*.

Yoonsik Kim, Moonbin Yim, and Ka Yeon Song. 2024. Tablevqa-bench: A visual question answering benchmark on multiple table domains. *arXiv preprint arXiv:2404.19205*.

Hugo Laurençon, Andrés Marafioti, Victor Sanh, and Léo Tronchon. 2024. Building and better understanding vision-language models: insights and future directions. In *Workshop on Responsibly Building the Next Generation of Multimodal Foundational Models*.

Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. 2023. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. In *International conference on machine learning*, pages 19730–19742. PMLR.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. 2023. Visual instruction tuning. *Advances in neural information processing systems*, 36:34892–34916.

Andrés Marafioti, Orr Zohar, Miquel Farré, Merve Noyan, Elie Bakouch, Pedro Cuenca, Cyril Zakka, Loubna Ben Allal, Anton Lozhkov, Nouamane Tazi, Vaibhav Srivastav, Joshua Lochner, Hugo Larcher, Mathieu Morlon, Lewis Tunstall, Leandro von Werra, and Thomas Wolf. 2025. Smolvlm: Redefining small and efficient multimodal models. *arXiv preprint arXiv:2504.05299*.

Ahmed Masry, Mohammed Saidul Islam, Mahir Ahmed, Aayush Bajaj, Firoz Kabir, Aaryaman Kartha, Md Tahmid Rahman Laskar, Mizanur Rahman, Shadikur Rahman, Mehrad Shahmohammadi, et al. 2025. Chartqapro: A more diverse and challenging benchmark for chart question answering. *arXiv preprint arXiv:2504.05506*.

Ahmed Masry, Do Xuan Long, Jia Qing Tan, Shafiq Joty, and Enamul Hoque. 2022. Chartqa: A benchmark for question answering about charts with visual and logical reasoning. *arXiv preprint arXiv:2203.10244*.

Minesh Mathew, Viraj Bagal, Rubèn Tito, Dimosthenis Karatzas, Ernest Valveny, and CV Jawahar. 2022. Infographicvqa. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 1697–1706.

Minesh Mathew, Dimosthenis Karatzas, and CV Jawahar. 2021. Docvqa: A dataset for vqa on document images. In *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, pages 2200–2209.

Nitesh Methani, Pritha Ganguly, Mitesh M Khapra, and Pratyush Kumar. 2020. Plotqa: Reasoning over scientific plots. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 1527–1536.

Anand Mishra, Shashank Shekhar, Ajeet Kumar Singh, and Anirban Chakraborty. 2019. Ocr-vqa: Visual question answering by reading text in images. In *2019 international conference on document analysis and recognition (ICDAR)*, pages 947–952. IEEE.

Niklas Muennighoff, Zitong Yang, Weijia Shi, Xiang Lisa Li, Li Fei-Fei, Hannaneh Hajishirzi, Luke Zettlemoyer, Percy Liang, Emmanuel Candès, and Tatsunori Hashimoto. 2025. s1: Simple test-time scaling. *arXiv preprint arXiv:2501.19393*.

OpenAI, :, Aaron Hurst, Adam Lerer, Adam P. Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, Aleksander Mądry, Alex Baker-Whitcomb, Alex Beutel, Alex Borzunov, Alex Carney, Alex Chow, Alex Kirillov, Alex Nichol, Alex Paino, Alex Renzin, Alex Tachard Passos, Alexander Kirillov, Alexi Christakis, Alexis Conneau, Ali Kamali, Allan Jabri, Allison Moyer, Allison Tam, Amadou Crookes, Amin Tootoochian, Amin Tootoonchian, Ananya Kumar, Andrea Vallone, Andrej Karpathy, Andrew Braunstein, Andrew Cann, Andrew Codispoti, Andrew Galu, Andrew Kondrich, Andrew Tulloch, Andrey Mishchenko, Angela Baek, Angela Jiang, Antoine Pelisse, Antonia Woodford, Anuj Gosalia, Arka Dhar, Ashley Pantuliano, Avi Nayak, Avital Oliver, Barret Zoph, Behrooz Ghorbani, Ben Leimberger, Ben Rossen, Ben Sokolowsky, Ben Wang, Benjamin Zweig, Beth Hoover, Blake Samic, Bob McGrew, Bobby Spero, Bogo Giertler, Bowen Cheng, Brad Lightcap, Brandon Walkin, Brendan Quinn, Brian Guarraci, Brian Hsu, Bright Kellogg, Brydon Eastman, Camillo Lugaresi, Carroll Wainwright, Cary Bassin, Cary Hudson, Casey Chu, Chad Nelson, Chak Li, Chan Jun Shern, Channing Conger, Charlotte Barette, Chelsea Voss, Chen Ding, Cheng Lu, Chong Zhang, Chris Beaumont, Chris Hallacy, Chris Koch, Christian Gibson, Christina Kim, Christine Choi, Christine McLeavey, Christopher Hesse, Claudia Fischer, Clemens Winter, Coley Czarnecki, Colin Jarvis, Colin Wei, Constantin Koumouzelis, Dane Sherburn, Daniel Kappler, Daniel Levin, Daniel Levy, David Carr, David Farhi, David Mely, David Robinson, David Sasaki, Denny Jin, Dev Valladares, Dimitris Tsipras, Doug Li, Duc Phong Nguyen, Duncan Findlay, Edede Oiwoh, Edmund Wong, Ehsan Asdar, Elizabeth Proehl, Elizabeth Yang, Eric Antonow, Eric Kramer, Eric Peterson, Eric Sigler, Eric Wallace, Eugene Brevdo, Evan Mays, Farzad Khorasani, Felipe Petroski Such, Filippo Raso, Francis Zhang, Fred von Lohmann, Freddie Sulit, Gabriel Goh, Gene Oden, Geoff Salmon, Giulio Starace, Greg Brockman, Hadi Salman, Haiming Bao, Haitang Hu, Hannah Wong, Haoyu Wang, Heather Schmidt, Heather Whitney, Heewoo Jun, Hendrik Kirchner, Henrique Ponde de Oliveira Pinto, Hongyu Ren, Huiwen Chang,

Hyung Won Chung, Ian Kivlichan, Ian O'Connell, Ian O'Connell, Ian Osband, Ian Silber, Ian Sohl, Ibrahim Okuyucu, Ikai Lan, Ilya Kostrikov, Ilya Sutskever, Ingmar Kanitscheider, Ishaan Gulrajani, Jacob Coxon, Jacob Menick, Jakub Pachocki, James Aung, James Betker, James Crooks, James Lennon, Jamie Kiros, Jan Leike, Jane Park, Jason Kwon, Jason Phang, Jason Teplitz, Jason Wei, Jason Wolfe, Jay Chen, Jeff Harris, Jenia Varavva, Jessica Gan Lee, Jessica Shieh, Ji Lin, Jiahui Yu, Jiayi Weng, Jie Tang, Jieqi Yu, Joanne Jang, Joaquin Quinonero Candela, Joe Beutler, Joe Landers, Joel Parish, Johannes Heidecke, John Schulman, Jonathan Lachman, Jonathan McKay, Jonathan Uesato, Jonathan Ward, Jong Wook Kim, Joost Huizinga, Jordan Sitkin, Jos Kraaijeveld, Josh Gross, Josh Kaplan, Josh Snyder, Joshua Achiam, Joy Jiao, Joyce Lee, Juntang Zhuang, Justyn Harriman, Kai Fricke, Kai Hayashi, Karan Singhal, Katy Shi, Kavin Karthik, Kayla Wood, Kendra Rimbach, Kenny Hsu, Kenny Nguyen, Keren Gu-Lemberg, Kevin Button, Kevin Liu, Kiel Howe, Krithika Muthukumar, Kyle Luther, Lama Ahmad, Larry Kai, Lauren Itow, Lauren Workman, Leher Pathak, Leo Chen, Li Jing, Lia Guy, Liam Fedus, Liang Zhou, Lien Mamitsuka, Lilian Weng, Lindsay McCallum, Lindsey Held, Long Ouyang, Louis Feuvrier, Lu Zhang, Lukas Kondraciuk, Lukasz Kaiser, Luke Hewitt, Luke Metz, Lyric Doshi, Mada Aflak, Maddie Simens, Madelaine Boyd, Madeleine Thompson, Marat Dukhan, Mark Chen, Mark Gray, Mark Hudnall, Marvin Zhang, Marwan Aljubeh, Mateusz Litwin, Matthew Zeng, Max Johnson, Maya Shetty, Mayank Gupta, Meghan Shah, Mehmet Yatbaz, Meng Jia Yang, Mengchao Zhong, Mia Glaese, Mianna Chen, Michael Janner, Michael Lampe, Michael Petrov, Michael Wu, Michele Wang, Michelle Fradin, Michelle Pokrass, Miguel Castro, Miguel Oom Temudo de Castro, Mikhail Pavlov, Miles Brundage, Miles Wang, Minal Khan, Mira Murati, Mo Bavarian, Molly Lin, Murat Yesildal, Nacho Soto, Natalia Gimelshein, Natalie Cone, Natalie Staudacher, Natalie Summers, Natan LaFontaine, Neil Chowdhury, Nick Ryder, Nick Stathas, Nick Turley, Nik Tezak, Niko Felix, Nithanth Kudige, Nitish Keskar, Noah Deutsch, Noel Bundick, Nora Puckett, Ofir Nachum, Ola Okelola, Oleg Boiko, Oleg Murk, Oliver Jaffe, Olivia Watkins, Olivier Godement, Owen Campbell-Moore, Patrick Chao, Paul McMillan, Pavel Belov, Peng Su, Peter Bak, Peter Bakkum, Peter Deng, Peter Dolan, Peter Hoeschele, Peter Welinder, Phil Tillet, Philip Pronin, Philippe Tillet, Prafulla Dhariwal, Qiming Yuan, Rachel Dias, Rachel Lim, Rahul Arora, Rajan Troll, Randall Lin, Rapha Gontijo Lopes, Raul Puri, Reah Miyara, Reimar Leike, Renaud Gaubert, Reza Zamani, Ricky Wang, Rob Donnelly, Rob Honsby, Rocky Smith, Rohan Sahai, Rohit Ramchandani, Romain Huet, Rory Carmichael, Rowan Zellers, Roy Chen, Ruby Chen, Ruslan Nigmatullin, Ryan Cheu, Saachi Jain, Sam Altman, Sam Schoenholz, Sam Toizer, Samuel Miserendino, Sandhini Agarwal, Sara Culver, Scott Ethersmith, Scott Gray, Sean Grove, Sean Metzger, Shamez Hermani, Shantanu Jain, Shengjia Zhao, Sherwin Wu, Shino Jomoto, Shirong Wu, Shuaiqi, Xia, Sonia Phene, Spencer Papay, Srinivas Narayanan, Steve Coffey, Steve Lee, Stewart Hall, Suchir Balaji, Tal Broda, Tal Stramer, Tao Xu, Tarun Gogineni, Taya Christianson, Ted Sanders, Tejal Patwardhan, Thomas Cunninghman, Thomas Degry, Thomas Dimson, Thomas Raoux, Thomas Shadwell, Tianhao Zheng, Todd Underwood, Todor Markov, Toki Sherbakov, Tom Rubin, Tom Stasi, Tomer Kaftan, Tristan Heywood, Troy Peterson, Tyce Walters, Tyna Eloundou, Valerie Qi, Veit Moeller, Vinnie Monaco, Vishal Kuo, Vlad Fomenko, Wayne Chang, Weiyi Zheng, Wenda Zhou, Wesam Manassra, Will Sheu, Wojciech Zaremba, Yash Patil, Yilei Qian, Yongjik Kim, Youlong Cheng, Yu Zhang, Yuchen He, Yuchen Zhang, Yujia Jin, Yunxing Dai, and Yury Malkov. 2024. Gpt-4o system card. *Preprint*, arXiv:2410.21276.

David Peebles and Peter C.-H. Cheng. 2003. Modeling the effect of task and graphical representation on response latency in a graph reading task. *Human Factors*, 45(1):28–46. PMID: 12916580.

Zhiliang Peng, Wenhui Wang, Li Dong, Yaru Hao, Shaohan Huang, Shuming Ma, and Furu Wei. 2023. Kosmos-2: Grounding multimodal large language models to the world. *arXiv preprint arXiv:2306.14824*.

Amanpreet Singh, Vivek Natarajan, Meet Shah, Yu Jiang, Xinlei Chen, Dhruv Batra, Devi Parikh, and Marcus Rohrbach. 2019. Towards vqa models that can read. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 8317–8326.

Andreas Steiner, André Susano Pinto, Michael Tschannen, Daniel Keysers, Xiao Wang, Yonatan Bitton, Alexey Gritsenko, Matthias Minderer, Anthony Sherbondy, Shangbang Long, et al. 2024. Paligemma 2: A family of versatile vlms for transfer. *arXiv preprint arXiv:2412.03555*.

Gemini Team, Petko Georgiev, Ving Ian Lei, Ryan Burnell, Libin Bai, Anmol Gulati, Garrett Tanzer, Damien Vincent, Zhufeng Pan, Shibo Wang, et al. 2024. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. *arXiv preprint arXiv:2403.05530*.

Gemma Team, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivière, Louis Rouillard, Thomas Mesnard, Geoffrey Cideron, Jean bastien Grill, Sabela Ramos, Edouard Yvinec, Michelle Casbon, Etienne Pot, Ivo Penchev, Gaël Liu, Francesco Visin, Kathleen Kenealy, Lucas Beyer, Xiaohai Zhai, Anton Tsitsulin, Robert Busa-Fekete, Alex Feng, Noveen Sachdeva, Benjamin Coleman, Yi Gao, Basil Mustafa, Iain Barr, Emilio Parisotto, David Tian, Matan Eyal, Colin Cherry, Jan-Thorsten Peter, Danila Sinopalnikov, Surya Bhupatiraju, Rishabh Agarwal, Mehran Kazemi, Dan Malkin, Ravin Kumar, David Vilar, Idan Brusilovsky, Jiaming Luo, Andreas Steiner,

Abe Friesen, Abhanshu Sharma, Abheesht Sharma, Adi Mayrav Gilady, Adrian Goedeckemeyer, Alaa Saade, Alex Feng, Alexander Kolesnikov, Alexei Bendebury, Alvin Abdagic, Amit Vadi, András György, André Susano Pinto, Anil Das, Ankur Bapna, Antoine Miech, Antoine Yang, Antonia Paterson, Ashish Shenoy, Ayan Chakrabarti, Bilal Piot, Bo Wu, Bobak Shahriari, Bryce Petrini, Charlie Chen, Charline Le Lan, Christopher A. Choquette-Choo, CJ Carey, Cormac Brick, Daniel Deutsch, Danielle Eisenbud, Dee Cattle, Derek Cheng, Dimitris Paparas, Divyashree Shivakumar Sreepathihalli, Doug Reid, Dustin Tran, Dustin Zelle, Eric Noland, Erwin Huizenga, Eugene Kharitonov, Frederick Liu, Gagik Amirkhanyan, Glenn Cameron, Hadi Hashemi, Hanna Klimczak-Plucińska, Harman Singh, Harsh Mehta, Harshal Tushar Lehri, Hussein Hazimeh, Ian Ballantyne, Idan Szpektor, Ivan Nardini, Jean Pouget-Abadie, Jetha Chan, Joe Stanton, John Wieting, Jonathan Lai, Jordi Orbay, Joseph Fernandez, Josh Newlan, Ju yeong Ji, Jyotinder Singh, Kat Black, Kathy Yu, Kevin Hui, Kiran Vodrahalli, Klaus Greff, Linhai Qiu, Marcella Valentine, Marina Coelho, Marvin Ritter, Matt Hoffman, Matthew Watson, Mayank Chaturvedi, Michael Moynihan, Min Ma, Nabila Babar, Natasha Noy, Nathan Byrd, Nick Roy, Nikola Momchev, Nilay Chauhan, Noveen Sachdeva, Oskar Bunyan, Pankil Botarda, Paul Caron, Paul Kishan Rubenstein, Phil Culliton, Philipp Schmid, Pier Giuseppe Sessa, Pingmei Xu, Piotr Stanczyk, Pouya Tafti, Rakesh Shivanna, Renjie Wu, Renke Pan, Reza Rokni, Rob Willoughby, Rohith Vallu, Ryan Mullins, Sammy Jerome, Sara Smoot, Sertan Girgin, Shariq Iqbal, Shashir Reddy, Shruti Sheth, Siim Põder, Sijal Bhatnagar, Sindhu Raghuram Panyam, Sivan Eiger, Susan Zhang, Tianqi Liu, Trevor Yacovone, Tyler Liechty, Uday Kalra, Utku Evci, Vedant Misra, Vincent Roseberry, Vlad Feinberg, Vlad Kolesnikov, Woohyun Han, Woosuk Kwon, Xi Chen, Yinlam Chow, Yuvein Zhu, Zichuan Wei, Zoltan Egyed, Victor Cotruta, Minh Giang, Phoebe Kirk, Anand Rao, Kat Black, Nabila Babar, Jessica Lo, Erica Moreira, Luiz Gustavo Martins, Omar Sanseviero, Lucas Gonzalez, Zach Gleicher, Tris Warkentin, Vahab Mirrokni, Evan Senter, Eli Collins, Joelle Barral, Zoubin Ghahramani, Raia Hadsell, Yossi Matias, D. Sculley, Slav Petrov, Noah Fiedel, Noam Shazeer, Oriol Vinyals, Jeff Dean, Demis Hassabis, Koray Kavukcuoglu, Clement Farabet, Elena Buchatskaya, Jean-Baptiste Alayrac, Rohan Anil, Dmitry, Lepikhin, Sebastian Borgeaud, Olivier Bachem, Armand Joulin, Alek Andreev, Cassidy Hardin, Robert Dadashi, and Léonard Hussenot. 2025. Gemma 3 technical report. *Preprint*, arXiv:2503.19786.

Omkar Thawakar, Dinura Dissanayake, Ketan More, Ritesh Thawkar, Ahmed Heakl, Noor Ahsan, Yuhao Li, Mohammed Zumri, Jean Lahoud, Rao Muhammad Anwer, et al. 2025. Llamav-o1: Rethinking step-by-step visual reasoning in llms. *arXiv preprint arXiv:2501.06186*.

Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. 2023. Interleaving retrieval with chain-of-thought reasoning for knowledge-intensive multi-step questions. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 10014–10037.

Pengcheng Wen, Jiaming Ji, Chi-Min Chan, Juntao Dai, Donghai Hong, Yaodong Yang, Sirui Han, and Yike Guo. 2025. Thinkpatterns-21k: A systematic study on the impact of thinking patterns in llms. *arXiv preprint arXiv:2503.12918*.

Guowei Xu, Peng Jin, Hao Li, Yibing Song, Lichao Sun, and Li Yuan. 2025. Llava-cot: Let vision language models reason step-by-step. *Preprint*, arXiv:2411.10440.

Xiang Yue, Yuansheng Ni, Kai Zhang, Tianyu Zheng, Ruoqi Liu, Ge Zhang, Samuel Stevens, Dongfu Jiang, Weiming Ren, Yuxuan Sun, et al. 2024. Mmmu: A massive multi-discipline multimodal understanding and reasoning benchmark for expert agi. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9556–9567.

Jinxu Zhang. 2024. Read and think: An efficient step-wise multimodal language model for document understanding and reasoning. *Preprint*, arXiv:2403.00816.

Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q Weinberger, and Yoav Artzi. 2019. Bertscore: Evaluating text generation with bert. *arXiv preprint arXiv:1904.09675*.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, et al. 2023. Judging llm-as-a-judge with mt-bench and chatbot arena. *Advances in Neural Information Processing Systems*, 36:46595–46623.

A VQA Datasets for Document Understanding

DocVQA is a dataset comprising 12,767 industrial document images (receipts, letters, tables, etc.) annotated with 50,000 questions. Its distinguishing feature is that answers always appear as continuous spans of text within the images. Understanding the document layout (headers, tables, columns) and diverse fonts (printed, typed, handwritten) is necessary, with questions categorized into types such as layout, table/list, running text, and handwritten. Therefore, DocVQA emphasizes not only pure text comprehension but also the utilization of page structure and non-textual information.

InfographicVQA. InfographicVQA consists of 5,485 infographic images collected from the web and 30,035 questions, characterized by born-digital images featuring extensive text and diagrams. Many questions demand numerical calculations, such as "How many...?" or ratio computations, with most answers being numeric. Answers can either be spans extracted from image texts or numeric calculation results. Compared to DocVQA, InfographicVQA requires comprehension of significantly longer sentences and complex visual element interactions (charts, icons, etc.), and it also has a higher proportion of unique questions.

ChartQA ChartQA is composed of approximately 20,000 real-world chart images collected from sources like Statista, Pew, OWID, and OECD. It provides 9,608 human-authored questions (ChartQA-H) and 23,111 auto-generated questions (ChartQA-M) about 4,804 charts. The dataset covers various chart types including bar charts, line graphs, and pie charts. Questions involve complex compositional queries requiring arithmetic and logical operations such as sum, difference, and average, as well as queries about visual attributes like colors and sizes. Models must first process chart images to extract underlying data tables (ChartOCR), then utilize Transformer-based QA models combining visual features with extracted table data (e.g., Vision-TaPas, VL-T5). Unlike earlier datasets like DVQA/FigureQA, ChartQA features numerous human-authored questions while retaining open-ended answers not restricted to fixed vocabularies.

TableQA TableVQA-Bench is a benchmark dataset designed to evaluate visual question answering (VQA) performance using table images from various domains, comprising a total of 894 table images and 1,500 questions. It extends the existing TableQA dataset by including four subsets (VWTQ, VWTQ-Syn, VTabFact, FinTabNetQA). The questions require complex operations such as summation, comparison, and conditional filtering, beyond simple cell-value extraction. Notably, the dataset includes artificially generated table images that diversify visual attributes such as fonts, colors, and borders, in addition to real-world table captures, to comprehensively assess the model's visual generalization capabilities.

PlotQA PlotQA is a large-scale visual question answering dataset consisting of 224,000 scientific plot images and approximately 280,000 questions. It was proposed to overcome the limitations of previous datasets such as FigureQA and DVQA, including limited diversity in data labels, lack of support for numerical answers, and a focus on overly simple questions. Specifically, PlotQA introduces a hybrid approach in which some questions are answered by first extracting a structured table from the plot image and then applying a table-based question answering engine. This method significantly improves performance, achieving an accuracy of 22.52 on PlotQA, outperforming existing models.

FigureQA It is a synthetic dataset designed to comprehensively evaluate a model's understanding of charts and its visual question answering (VQA) capabilities. The dataset consists of 140,000 chart images of various types—including bar graphs, line graphs, and pie charts—and approximately 1,800,000 yes/no question–answer pairs. Each image is generated with arbitrary values and includes at least two color legends, while the questions are crafted to assess the model's ability to interpret visual elements such as legend colors, order, and numerical relationships within the graph. A key characteristic of this dataset is that all questions are solvable using visual information alone, without relying on text OCR. Due to these properties, the dataset emphasizes the need for accurate visual structure parsing, understanding of color-value relationships within charts, and the ability to perform figure-based reasoning through visual pattern recognition rather than language-based knowledge.

DVQA This dataset is constructed to evaluate bar chart interpretation and visual question answering (VQA) performance. It consists of 300,000 bar

chart images and approximately 3,487,194 question–answer pairs generated based on those images. Each image is associated with various types of questions, including chart structure understanding, specific value retrieval, and numerical comparison. The answers are designed to require precise interpretation of the visual elements within the graph. Since the charts are dynamically generated with varying text and numerical information (e.g., item names, values, abbreviations), it is difficult to rely on a predefined fixed vocabulary. As a result, the dataset demands an integrated capability in OCR-based text recognition, chart structure parsing, and numerical reasoning.

Docmatix Docmatix is a large-scale document VQA dataset composed of 2.4 million images extracted from over 1.3 million PDF documents, containing 9.5 million questions, thus expanding approximately 240 times compared to the existing DocVQA dataset. The primary feature of Docmatix is its comprehensive coverage of various query types that can arise in realistic document understanding scenarios. For example, it encompasses complex tasks like extracting information from tables or lists, multi-step reasoning, and document layout comprehension. Unlike previous datasets, which primarily focus on simple fact-checking questions, Docmatix distinguishes itself by reflecting diverse cognitive tasks required in actual document analysis, thus maximizing model practicality.

Llava-CoT This dataset is designed to train systematic step-by-step reasoning capabilities for complex visual-language question answering (VQA) tasks. It consists of approximately 99,000 image–question pairs, each accompanied by a Chain-of-Thought (reasoning process) and a final answer. Each sample is structured using four explicit tags: `<SUMMARY>`, `<CAPTION>`, `<REASONING>`, and `<CONCLUSION>`, which delineate the stages of reasoning. The questions cover a wide range of inference types, including numerical calculation, logical judgment, situational reasoning, and scientific interpretation. The dataset is designed not only to assess the correctness of the final answer but also to evaluate the validity and logical coherence of the entire reasoning process. In particular, the ability to integratively interpret both visual and linguistic information and to explicitly articulate the reasoning steps is crucial.

LlamaV-o1 It is a dataset designed to perform complex multi-step visual reasoning. Unlike previous approaches that focused solely on answer accuracy, this work proposes a novel evaluation strategy that rigorously assesses the validity and logical coherence of the reasoning process itself. From a training perspective, the model adopts a curriculum learning strategy, gradually increasing the level of difficulty to facilitate structured learning.

B Detailed Information for Data Construction

B.1 Why was the Qwen2.5-VL-72B model chosen to generate the DocPlan dataset?

GPT-4o, Gemini2.0, and the Qwen2.5-VL family have all achieved state-of-the-art (SOTA) performance on recent vision–language tasks. Therefore, to select a model for generating the DocPlan dataset proposed in this study, we built a validation set using images from existing document VQA datasets and input prompts to generate DocPlan sample data. According to the evaluation results of the generated data, Qwen2.5-VL-72B showed the lowest error rate among the three models. Furthermore, since we conduct GPT-based qualitative evaluations, we judged that using a model from the same family to generate data could introduce bias. Given that Qwen2.5-VL-72B is an open-source model, we also determined that it could enhance the reproducibility of the data generation method proposed in this study, and thus selected it as the final data generation model. (The data generation process was carried out using an NVIDIA DGX system equipped with 8 H100 GPUs.)

B.2 Prompt for Query Generation

Figure 6 shows the prompts used to generate queries for the five query types (FP, CP, IR, LR, MA) and three difficulty levels (Basic, Intermediate, Advanced), based on images from existing datasets, as defined in Section 3.2.

B.3 Prompt for Data Generation

The DocPlan dataset was constructed following the DocPlan-pipe. To enhance data quality, a step-by-step generation method was adopted, and the prompts used for data generation at each stage are shown in Figure 7 to Figure 10.

B.4 Analysis of Query Diversity in DocPlan and Llava-CoT

Llava-CoT was constructed using only queries from existing datasets within the document domain. This approach has the advantage of enabling reliable evaluation in comprehensively understanding both the visual and textual elements of documents, as it is based on queries from credible, pre-existing datasets. However, it lacks diversity in query types, which limits its ability to encompass complex or high-level reasoning required for document understanding. To address this limitation, our study generated additional queries from various document formats and information extraction perspectives. Figures 11 and 12 illustrate the distribution of query diversity in the DocPlan dataset and the Llava-CoT dataset within the document domain, respectively. These comparisons confirm that the DocPlan dataset demonstrates significantly greater query diversity compared to Llava-CoT.

B.5 Detailed Filtering process

Since the newly generated queries do not have ground truth answers unlike those in existing datasets, we used a combination of closed vision-language models such as GPT-4o and Gemini 2.0, along with open models like Qwen2.5-VL-72B, to perform a Pass/Fail evaluation for improving data quality. Only the samples that received a "Pass" from all models were selected for inclusion in the final dataset. The data filtering process consisted of two stages, and the detailed procedures for each stage are described below.

Query Filtering The generated queries were evaluated using a Pass/Fail approach based on three criteria: *Query Appropriateness*, *Answer Possibility*, and *Final Response Feasibility*. *Query Appropriateness* assesses whether the query is appropriate given the document's content and context. *Answer Possibility* determines whether a valid answer can be derived from the document, and *Final Response Feasibility* evaluates whether a model can generate a coherent and complete response to the query. Additionally, a *Confidence* metric was introduced, and only samples with a confidence score between 95 and 100 were retained. The filtering prompt used in this process is shown in Figure 13.

Model Agreement For the responses based on the filtered queries following the DocPlan-pipe format, a Pass/Fail (O/X) evaluation was conducted based on the following five criteria:

1. **Question Interpretation Accuracy**: Assesses whether the query is interpreted accurately within context, ensuring that its meaning is clear and appropriate.

2. **Image-Reasoning-Answer Consistency**: Evaluate whether the reasoning derived from the image aligns with the actual content of the image, and whether the answer logically follows from this reasoning.

3. **Overall Appropriateness**: Examines the overall naturalness and validity of the query-response pair.

4. **Answerable Without Image**: Determines whether the question can be sufficiently answered using only document information, without relying on the image.

5. **(Optional) Answer–Ground-truth Agreement**: Evaluates whether the generated answer matches the provided ground-truth response in content and intent. This includes checking for semantic alignment, factual consistency, and relevance. This criterion is applied only when ground-truth data is available.

6. **Suitable for Training Data**: Assesses whether the sample is appropriate for use as training data.

A *Confidence* metric was also applied to each criterion, and only samples with a confidence score between 95 and 100 were selected. The filtering prompt used in this stage is shown in Figure 14.

Hard Filtering As detailed in the additional filtering procedure of Section 5, we constructed a fine-grained DocPlan dataset by applying an extra hard-filtering stage to the samples that had already been refined by the pipeline in Section 3.3. The statistics for the samples retained after each step appear in Table 12,13. In total, the curated dataset contains 124,053 examples 65,347 origin queries and 58,706 generated queries. For the origin queries, we supplied GPT-4o with only the reasoning trace omitting the question, the original final answer, and all images to obtain a new final answer. Comparing these answers with the ground-truth responses revealed 10,207 erroneous cases. Subsequent review by three annotators identified 7,041 instances as minor issues(e.g., inconsistent unit notation). these were corrected and reinstated. The remaining 3,166 items, judged to be clear errors, were removed. Human evaluation was carried out by three students (two in computational linguistics and one in linguistics) see Table 11 for details. Because each example contains the query, the full reasoning trace, and the answer, annotation was time-consuming, so the 10k examples were single-annotated rather than cross-validated. For the generated queries, we likewise produced new final answers. In the absence of ground-truth labels, we measured the similarity between the original and newly generated answers using BERTScore (Zhang et al., 2019). Only those instances with a BERTScore of 0.8 or higher were retained in the final dataset. The Final Answer was generated using the prompt shown in Figure 10.

Analysis of Error Sample Through the hard filtering process, samples that were ultimately classified as errors were reviewed by seven human annotators. The error types were broadly categorized into seven groups, with each category defined as follows:

1. **Unit**: Errors caused by the presence or absence of unit expressions, such as "30" → "30 km".

2. **Measure**: Errors due to differences in numerical expression, for example, "30,423" → "Approximately 30,000".

3. **Answer format**: Errors stemming from variations in answer format or phrasing, such as "I'm a boy" → "boy".

4. **Reasoning**: Reasoning-related errors where OCR was performed correctly, but the model misinterpreted the problem conditions during the reasoning process, leading to an incorrect final answer.

5. **Final Answer**: Cases where both OCR and reasoning were performed correctly, but the final answer failed to reflect the conclusion derived from the reasoning process.




Figure 5: Distribution of error types as categorized by human annotators during error analysis.

Examples of each error type are shown in Figure 15. to Figure 21, and their statistical distribution is presented in Figure 5.

Category	Human Annotator 1	Human Annotator 2	Human Annotator 3
Birth Year	Born in 1996	Born in 1998	Born in 1997
Major	Computational Linguistics	Computational Linguistics	Linghistics
Education Level	Master's graduate	Enrolled in Master's program	Master's graduate
Primary Language	Korean	Korean	Korean

Table 11: Demographic and academic background of the three human annotators who participated in the filtering. All annotators are at least a bachelor's degree. Annotators 1 and 2 majored in computational linguistics, while Annotator 3 majored in linguistics. Two annotators have completed a master's program, and one is currently enrolled.

Prompt for Question Generation

Role & Task
Analyze the given document to generate questions across five categories (CP, FP, IR, LR, MA) with three difficulty levels (A/B/C). All questions must require explicit document reference.

Core Principles
1. Document Dependency : Every question must require analyzing the document image.
2. Progressive Difficulty : Clear distinction between A/B/C levels.
3. Category Integrity : Strict adherence to category definitions.
4. MA Validation : Include MA only when numerical/mathematical elements exist.

Category Definitions
1. Coarse Perception (CP): Document structure, layout, overall purpose
2. Fine-grained Perception (FP): Specific details (names, dates, values)
3. Instance Reasoning (IR): Element relationships within document
4. Logical Reasoning (LR): Implications, conclusions, logical flow
5. Mathematical Analysis (MA): Numerical calculations/relationships (conditional)

Difficulty Criteria
- Level A (Basic):
  • Single-element extraction
  • Direct text/location reference
  • Example: "What is labeled in the top-right corner?"
- Level B (Intermediate):
  • Two-element connection
  • Simple inference required
  • Example: "How does [Concept A] relate to [Diagram B]?"
- Level C (Advanced):
  • Three + element synthesis
  • Multi-step reasoning
  • Example: "What conclusion can be drawn from [X] and [Y] combined with [Table Z]?"

MA Handling Rules
1. Automatic exclusion if document contains:
  - Only ordinal numbers (1st, 2nd)
  - Simple dates/measurements without calculations
2. Mandatory inclusion when:
  - Numerical comparisons exist
  - Formulas/statistical data present - Requires arithmetic operations

Workflow
1. Document Analysis:
  - Identify key sections and data types
  - Flag potential mathematical content

⋮

2. Category Mapping:
  - Tag content segments with applicable categories
  - Validate MA eligibility
3. Question Generation:
  - Generate 3 questions per category (A/B/C)
  - Apply difficulty escalation filters:
    A → B: Add element connection
    B → C: Require cross-reference + synthesis
  - Omit entire MA section if inapplicable
4. Quality Control:
  - Validate document dependency: Add locators like "[Figure 3]" in questions
  - Ensure no overlap between categories
  - Confirm progressive complexity within each category

Output Format
Strictly follow this structure:

Coarse Perception (CP)
- Level A: [Direct layout question]
- Level B: [Structural relationship question]
- Level C: [Purpose inference question]

Fine-grained Perception (FP)
- Level A: [Specific detail extraction]
- Level B: [Detail comparison]
- Level C: [Contextual interpretation]

Instance Reasoning (IR)
- Level A: [Element identification]
- Level B: [Bilateral relationship]
- Level C: [System network analysis]

Logical Reasoning (LR)
- Level A: [Explicit logic identification]
- Level B: [Implicit assumption detection]
- Level C: [Holistic conclusion synthesis]

Mathematical Analysis (MA) (Conditional)
- Level A: [Single-value calculation] or None
- Level B: [Comparative analysis] or None
- Level C: [Predictive modeling] or None

Figure 6: Prompt for question generation

Prompt for data generation: Query Analysis

You are an expert in analyzing user queries. Your primary goal is to:
- Identify the **core intent** behind the user's question.
- Determine if the user has specified a preferred response format (e.g., brevity, detail, list, table, code, tone).

Instructions:
- Focus on the **main purpose** of the query rather than surface details.
- If the user's query is vague, infer the most **logical intent** based on context.
- Do not answer the question or extract evidence from documents in this step.

Output Format:
<QUERY_ANALYSIS>
Clearly state the intent of the query.
</QUERY_ANALYSIS>

Key Guidelines:
Be **concise and precise**—focus on intent.
Do **not** answer the question—only analyze it.
Do **not** extract or refer to documents in this step.
Follow the **exact format** for consistency in multi-turn reasoning.

Figure 7: Prompt for data generation - query analysis

Prompt for data generation: Definition of Plan

You are an expert in creating concise and actionable plans to solve complex problems. Your role is to develop clear steps (PLANS) necessary to derive the final answer based on the user query and the provided query analysis results.

2. Plan Creation (STEP 2)
Objective
- To create clear and concise PLANS necessary to compose the final answer.

Key Guidelines
1. Number of PLANS
- The number of sub-plans should be determined by comprehensively considering the complexity of the question, the amount of information, and the scope of analysis.
- Use specific indicators such as the type of question, the volume of data to process, and the number of steps required to derive the final answer in order to decide on an appropriate number of sub-plans.
- It is important not to be constrained by specific numbers and to adjust freely according to the nature of the task.
- Ensure that the logical connections between each step are maintained.

2. Plan Format
- Use imperative sentences (e.g., "Identify...", "Extract...", "Summarize...").
- Focus only on the action required for each step.
- Avoid unnecessary explanations or references to specific documents, images, or evidence.

3. Logical Connection
- Ensure each PLAN logically follows from the previous one and leads to the next.

4. Complexity Assessment
- Consider the following factors to gauge the complexity of the query:
  1. Step-by-step reasoning: Whether multiple intermediate conclusions are needed.
  2. Amount of information: Whether the query involves a large volume of data or multiple elements.
  3. Scope of analysis: Whether the query requires comparing scenarios or synthesizing information.

Output Format
<DEF_PLAN>
<SUB_PLAN>[1st PLAN]</SUB_PLAN>
<SUB_PLAN>[2nd PLAN]</SUB_PLAN>
...
<SUB_PLAN>[Nth PLAN]</SUB_PLAN>
</DEF_PLAN>

Figure 8: Prompt for data generation - definition of plan

Prompt for data generation: Execution of Plan

Method

- Execute each Sub Plan by creating an <EXEC_PLAN> block for each step.
- Strictly adhere to the details outlined in each SUB_PLAN without deviation. Ensure that all actions and analyses are directly aligned with the stated sub-plan objectives.
- Extracted evidence (text, paragraphs, table, etc.) from the document should be placed within the <EXTRACTED_INFO> tag in Markdown code block(using triple backticks) format.
- Formatting Guidelines for Extracted Information.
  - If a summary is needed, provide it in the <THINK> tag instead of modifying the original content.
- When table format is required, maintain the original table structure as closely as possible for clarity and accuracy.
- When table format is necessary, ensure that:
  - The table structure is faithfully preserved.
  - Data is accurately copied without modification.
  - The format follows standard Markdown table syntax:
[column]	[column]
[data]	[data]
[data]	[data]
[data]	[data]
- The <EXTRACTED_INFO> tag is not mandatory and may be omitted when information extraction is not required.
- Logical analysis of the extracted information should be presented in the <THINK> tag, adjusting dynamically based on the number of extracted information points.
- The execution result (Plan Execution Result) should be written inside the <PLAN_ANS> tag.

Output Format

<EXEC_PLAN>
<SUB_PLAN>[Plan Title]</SUB_PLAN>
<EXTRACTED_INFO>
```markdown
[Extract relevant evidence (e.g., specific sentences, data, tables, etc.) from the document, preserving the original format (text, paragraphs, tables, etc.) without modification. If no information extraction is needed, this section can be omitted.]
```
</EXTRACTED_INFO>
<THINK>
[Analyze the provided information and derive a logical response based on extracted information]
- If one piece of information is extracted: Provide one logical deduction.
- If two pieces of information are extracted: Provide two logical deductions that build on each other.
- If three or more pieces of information are extracted: Present step-by-step reasoning in multiple deductions, ensuring each point logically follows from the extracted data.
</THINK>
<PLAN_ANS> [Provide a concise and well-reasoned execution result based on extracted evidence.]
</PLAN_ANS>
</EXEC_PLAN>

Figure 9: Prompt for data generation - execution of plan

Prompt for data generation: Final Answer

4. Final Answer Composition (STEP 4)
Objective

- You will be provided with the user query, query analysis results, the generated plan, and the sequentially executed plan. Your role is to generate the final answer based on the provided information.

Method

- Compose the final answer using the <FINAL_ANSWER> tag. If the user specifies a desired format, follow it; otherwise, provide a clear and appropriately detailed response for easy understanding.

Output Format

<FINAL_ANSWER>
[Final answer content]
</FINAL_ANSWER>

Figure 10: Prompt for data generation - final answer




Figure 11: Query diversity distribution of the DocPlan dataset




Figure 12: Query diversity distribution in the document domain of the Llava-CoT dataset

Prompt for query filtering

You are an evaluator. Your task is to first extract all readable text from a given document image. Then, based on the extracted text and a related query, assess the following three criteria:

Whether the query is appropriate.

Whether it is possible to provide an answer.

Whether a final response can be given based on the extracted content and the query.

You must respond strictly in the following format without any deviation, explanation, or additional commentary. Do not add any extra text.

[Response Format — Use exactly this template]
Query Appropriateness: O / X
Answer Possibility: O / X
Final Response Feasibility: O / X
Reason for Inability to Respond: (Only include this line if any of the above is 'X')
Confidence Level: (0~100%)

Figure 13: Instruction template for evaluating the appropriateness, answerability, and response feasibility of queries based on extracted text from document images

Prompt for Model Agreement

You are an evaluator for a visual question answering system. Your task is to assess the quality of a given answer based on an image and a question.

You will be provided with:
1. An image
2. A question about the image
3. A Reasoning Trace about the question
4. An answer to that question
5. (Optional) Ground-truth answer

Evaluate the following criteria:
1. **Question Interpretation Accuracy** — Was the question correctly understood in the context of the image?
2. **Image-Reasoning-Answer Consistency** — Does the reasoning align with the content of the image, and does the answer logically follow from the reasoning?
3. **Overall Appropriateness** — Is the answer appropriate overall?
4. **Answerability Without Image** — Can this question be answered reasonably without seeing the image?
5. **Answer–Ground-truth Agreement** — Does the answer match the provided ground-truth? (only if ground-truth is supplied)
6. **Suitability for Training Data** — Should this example (image, question, answer) be used as training data?
   → When evaluating criterion 5 (Training Data Suitability), take into account all previous criteria. Especially, if the question is answerable without the image (criterion 4 = O), consider whether that reduces its value as a visual training sample.

For each criterion, respond with:
* "O" for Yes/Correct, or "X" for No/Incorrect
* A numeric confidence score from 0 to 100 (integers only)
❗ Output must strictly follow this format. Do not provide any explanations.

Output:
Question Interpretation Accuracy: O/X (Confidence: NN)
Image–Reasoning-Answer Consistency: O/X (Confidence: NN)
Overall Appropriateness: O/X (Confidence: NN)
Answerable Without Image: O/X (Confidence: NN)
(Optional) Answer–Ground-truth Agreement: O/X (Confidence: NN)
Suitable for Training Data: O/X (Confidence: NN)

Input:
Question: {question}
Reasoning: {Reasoning Trace}
Answer: {answer}
Ground-truth: {Ground-truth}

Figure 14: Instructions for evaluating answer quality based on image-question-Reasoning-answer sets, covering criteria such as interpretation accuracy, consistency, and training data suitability

Stage	Before	After	Change
Format error	82,275	74,893	$-7{,}382$
Model Agreement	74,893	68,513	$-6{,}380$
Reasoning Consistency	68,513	58,306	$-10{,}207$
Human Filtering	58,306	65,347	$+7,041$

Table 12: Remaining dataset size after each filtering stage for origin queries

Stage	Overall	Basic	Intermediate	Advanced
Format error	80,397 → 78,293	32,303 → 31,597	31,389 → 30,395	16,705 → 16,301
Query Filtering & Model Agreement	78,293 → 65,110	31,597 → 28,167	30,395 → 27,358	16,301 → 9,585
Reasoning Consistency & Metric	65,110 → 58,706	28,167 → 26,976	27,358 → 24,027	9,585 → 7,703

Table 13: Remaining dataset size after each filtering stage for generated queries





Figure 15: An example of an Answer Format error, where the system's response does not exactly match the expected label due to formatting differences. In this case, the correct answer is "A pound of beef", but the model outputs "beef", omitting necessary details. Such errors typically occur when the answer is overly abbreviated or lacks required context compared to the expected format.

Error type:Unit Example

Q : How many daily active users did Pokmon GO have on August 16, 2016? Answer briefly.



<QUERY_ANALYSIS>
The core intent of the query is to find out the number of daily active users for Pokémon GO on August 16, 2016. The user prefers a brief response format.
</QUERY_ANALYSIS>

<DEF_PLAN>
<SUB_PLAN>Identify the bar corresponding to August 16 on the chart.</SUB_PLAN>
<SUB_PLAN>Read the number of daily active users from the top of the identified bar.</SUB_PLAN>
</DEF_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Identify the bar corresponding to August 16 on the chart.</SUB_PLAN>
<EXTRACTED_INFO>
```markdown
| Date | Number of Users (in millions) |
|---|---|
| August 16 | 30 |
```
</EXTRACTED_INFO>
<THINK>
The bar corresponding to August 16 is clearly labeled with the number 30, indicating the number of daily active users in millions.
</THINK>
<PLAN_ANS> The bar for August 16 shows that Pokémon GO had 30 million daily active users.
</PLAN_ANS>
</EXEC_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Read the number of daily active users from the top of the identified bar.</SUB_PLAN>
<EXTRACTED_INFO>
```markdown
| Date | Number of Users (in millions) |
|---|---|
| August 16 | 30 |
```
</EXTRACTED_INFO>
<THINK>
The number at the top of the bar for August 16 is 30, which represents the number of daily active users in millions.
</THINK>
<PLAN_ANS> On August 16, 2016, Pokémon GO had 30 million daily active users. </PLAN_ANS>
</EXEC_PLAN>


<FINAL_ANSWER>
30 million
</FINAL_ANSWER>

Label : 30

Figure 16: An example of a Unit error, where the predicted answer includes an unnecessary unit or uses an incorrect unit compared to the expected label. In this case, the correct answer is "30", but the model outputs "30 million", adding a unit suffix that does not match the label format.

Error type:OCR Example

Q : What was Suriname's gross domestic product in 2019? Keep it brief.



<QUERY_ANALYSIS>
The user wants to know the gross domestic product (GDP) of Suriname in 2019 and prefers a brief response.
</QUERY_ANALYSIS>

<DEF_PLAN>
<SUB_PLAN>Locate the year 2019 on the x-axis of the chart.</SUB_PLAN>
<SUB_PLAN>Find the corresponding GDP value on the y-axis for the year 2019.</SUB_PLAN>
<SUB_PLAN>Report the GDP value in billion U.S. dollars for Suriname in 2019.</SUB_PLAN>
</DEF_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Locate the year 2019 on the x-axis of the chart.</SUB_PLAN>
<EXTRACTED_INFO>
```markdown
The year 2019 is located on the x-axis of the chart.
```
</EXTRACTED_INFO>
<THINK>
The year 2019 has been successfully located on the x-axis, which is the first step in determining Suriname's GDP for that year.
</THINK>
<PLAN_ANS> The year 2019 is identified on the x-axis. </PLAN_ANS>
</EXEC_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Find the corresponding GDP value on the y-axis for the year 2019.</SUB_PLAN>
<EXTRACTED_INFO>
```markdown
The corresponding GDP value for the year 2019 is approximately 3.47 billion U.S. dollars.
```
</EXTRACTED_INFO>
<THINK>
The GDP value for Suriname in 2019 is approximately 3.47 billion U.S. dollars as indicated on the y-axis.
</THINK>
<PLAN_ANS> The GDP value for Suriname in 2019 is approximately 3.47 billion U.S. dollars.
</PLAN_ANS>
</EXEC_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Report the GDP value in billion U.S. dollars for Suriname in 2019.</SUB_PLAN>
...
<PLAN_ANS> The gross domestic product (GDP) of Suriname in 2019 was approximately 3.47 billion U.S. dollars. </PLAN_ANS>
</EXEC_PLAN>


<FINAL_ANSWER>
3.47 billion U.S. dollars
</FINAL_ANSWER>

Label : 3.7

Figure 17: An example of an OCR error, where incorrect text extraction from the chart leads to an inaccurate answer. In this case, the system misinterprets the value for 2019, producing "3.47 billion U.S. dollars" instead of the correct value "3.7." Such errors typically occur when optical character recognition fails to accurately read numbers or labels from the image.

Error type:Measure Example

Q : How many liters of metered water were consumed in Malaysia in 2019? Answer briefly.



<QUERY_ANALYSIS>
The core intent of the query is to find out the total volume of metered water consumed in Malaysia in 2019, with a preference for a brief response.
</QUERY_ANALYSIS>

<DEF_PLAN>
<SUB_PLAN>Identify the value for 2019 from the bar chart</SUB_PLAN>
<SUB_PLAN>Multiply the identified value by one billion to convert it into liters</SUB_PLAN>
</DEF_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Identify the value for 2019 from the bar chart</SUB_PLAN>
<EXTRACTED_INFO>
```markdown
| Year | Consumption in billion liters per day |
|------|---------------------------------------|
| 2019*| 6.82                                  |
```
</EXTRACTED_INFO>
<THINK>
The bar chart shows that in 2019, Malaysia consumed 6.82 billion liters of metered water per day.
</THINK>
<PLAN_ANS> In 2019, Malaysia consumed 6.82 billion liters of metered water per day.
</PLAN_ANS>
</EXEC_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Multiply the identified value by one billion to convert it into liters</SUB_PLAN>
<EXTRACTED_INFO>
```markdown
| Year | Consumption in billion liters per day |
|------|---------------------------------------|
| 2019*| 6.82                                  |
```
</EXTRACTED_INFO>
<THINK>
To convert the consumption value from billions of liters per day to just liters, we need to multiply 6.82 by one billion (1,000,000,000). This calculation will give us the total number of liters consumed in a day.

Calculation: \(6.82 \times 1,000,000,000 = 6,820,000,000 \) liters per day.
</THINK>
<PLAN_ANS> In 2019, Malaysia consumed 6,820,000,000 liters of metered water per day.
</PLAN_ANS>
</EXEC_PLAN>


<FINAL_ANSWER>
6,820,000,000
</FINAL_ANSWER>

Label : 6.82

Figure 18: An example of a Measure error, where the predicted answer differs from the expected label due to unit conversion or rounding issues. In this case, the system outputs “6,820,000,000 liters” instead of the expected “6.82”, as it converts the value from billions to raw liters rather than keeping the original unit.

Error type:Reasoning Example

Q : Who is regarded as one of the most successful players in the history of English football? Keep it brief.



<QUERY_ANALYSIS>
The core intent of the query is to identify a highly successful player in English football history, with a preference for a brief response.
</QUERY_ANALYSIS>

<DEF_PLAN>
<SUB_PLAN>Identify the top players based on goals scored from the chart.</SUB_PLAN>
<SUB_PLAN>Analyze the historical significance and achievements of the top players identified.</SUB_PLAN>
<SUB_PLAN>Determine which player is most commonly regarded as one of the most successful in English football history based on the analysis.</SUB_PLAN>
</DEF_PLAN>

<EXEC_PLAN> ... </EXEC_PLAN>

<EXEC_PLAN> ... </EXEC_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Determine which player is most commonly regarded as one of the most successful in English football history based on the analysis.</SUB_PLAN>
<THINK>
Considering the combined factors of goal-scoring prowess, historical significance, and overall impact on the sport:
1. Wayne Rooney stands out due to his extensive career achievements and numerous records.
2. Bobby Charlton is highly esteemed for his pivotal role in England's World Cup victory and his legendary status at Manchester United.
3. Gary Lineker's consistent performance in international tournaments adds to his legacy.
4. Jimmy Greaves' prolific scoring record solidifies his place among the greats.
5. Michael Owen's individual accolades highlight his peak performance.
Among these, Wayne Rooney and Bobby Charlton are often cited as two of the most successful players in English football history due to their comprehensive achievements and lasting legacies.
</THINK>
<PLAN_ANS> Wayne Rooney and Bobby Charlton are most commonly regarded as two of the most successful players in the history of English football. </PLAN_ANS>
</EXEC_PLAN>


<FINAL_ANSWER>
Wayne Rooney and Bobby Charlton
</FINAL_ANSWER>

Label : Wayne Rooney

Figure 19: An example of a Reasoning error, where the system fails to correctly follow the logical steps required to answer the question. In this case, instead of providing the expected single answer “Wayne Rooney”, the system outputs “Wayne Rooney and Bobby Charlton”, indicating incorrect reasoning in selecting the most relevant entity.

Error type:Final Answer Example

Q: `What is purchase order number? Answer the question with short words or phrases.`



DATE ASSIGNED: November 1, 2000
PURCHASE ORDER NUMBER: 4012
DUE DATE (draft): January 3, 2000

WRITER'S FEE: $3,500. One-third ($1,167) may be invoiced upon commencement of work; one-third may be invoiced upon acceptance of the manuscript by DesignWrite ($1,167); and one-third may be invoiced upon submission of the paper to the target journal ($1,166). Out-of-pocket expenses for telephone calls, faxes, and mailings will be reimbursed following submission of proper receipts.

DesignWrite reserves the right to terminate the project if the first draft is deemed unacceptable, i.e., the manuscript needs to be entirely rewritten. The total payment for a project terminated after the first draft will be $1,167. Payment will be made once all materials have been returned to DesignWrite.

COMMENTS: The document should be double-spaced and written using Word 97 (with MS Office 98) or a lower version. You may either submit a hard copy of the document along with a disk containing the file, or an e-mail version.

The manuscript should conform to the "Uniform Requirements for Manuscripts Submitted to Biomedical Journals." DesignWrite utilizes Reference Manager for formatting reference citations. If an article you use has the Reference Manager number at the top right that we have assigned it (in, "RM#0122"), please insert this number within braces (eg, {2122} or if more than one citation, {2122,3405,6402}) in the article at the appropriate citation point. If you are using an article that does not have a RM#, please insert the last name of the first author and the date within braces (eg, {Lobo 1997}). When a first author has more than one reference cited in a given year, add a letter after the date and identify this clearly on the article.

ASSIGNED BY: _____
Karen D. Mittleman, Ph.D. Date: November 1, 2000

ASSIGNMENT ACCEPTED BY:
_____
Fiona M. Hesr, Ph.D. Date:

3

DWRITE 003271

Source: https://www.industrydocuments.ucsf.edu/docs/yhcw0217

<QUERY_ANALYSIS>
The user wants to know the definition or meaning of a "purchase order number" and prefers a concise response using short words or phrases.
</QUERY_ANALYSIS>

<DEF_PLAN>
<SUB_PLAN>Identify the section of the document that contains purchase order information.**</SUB_PLAN>**
<SUB_PLAN>Extract the purchase order number from the identified section.**</SUB_PLAN>**
</DEF_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Identify the section of the document that contains purchase order information.**</SUB_PLAN>**
<EXTRACTED_INFO>
```markdown
PURCHASE ORDER NUMBER: 4012
```
</EXTRACTED_INFO>
<THINK>
The document clearly states the purchase order number in a dedicated line, making it straightforward to identify.
</THINK>
<PLAN_ANS> The section containing the purchase order information is identified as "PURCHASE ORDER NUMBER: 4012". **</PLAN_ANS>**
</EXEC_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Extract the purchase order number from the identified section.**</SUB_PLAN>**
<EXTRACTED_INFO>
```markdown
4012
```
</EXTRACTED_INFO>
<THINK>
The extracted purchase order number is 4012, which directly answers the user's query.
</THINK>
<PLAN_ANS> The purchase order number is 4012. **</PLAN_ANS>**
</EXEC_PLAN>

<FINAL_ANSWER>
A unique number identifying a purchase order.
</FINAL_ANSWER>

Label : 4012

Figure 20: An example of a Final Answer error, where the reasoning steps and extracted information are correct, but the final answer is incorrect. In this case, although the model correctly identifies the purchase order number as "4012", it outputs a definition instead of the expected numeric value.

Error type:Others (Label Error) Example

Q: `Which state has the life expectancy average lower than 75? Keep it brief.`



<QUERY_ANALYSIS>
The core intent of the query is to identify which U.S. state has an average life expectancy lower than 75 years, with a preference for a brief response format.
</QUERY_ANALYSIS>

<DEF_PLAN>
<SUB_PLAN>Identify states with life expectancy values**</SUB_PLAN>**
<SUB_PLAN>Compare each state's value to 75**</SUB_PLAN>**
<SUB_PLAN>List states with values below 75**</SUB_PLAN>**
</DEF_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Identify states with life expectancy values**</SUB_PLAN>**
<EXTRACTED_INFO>
```markdown
| State | Life Expectancy |
|---|---|
| Mississippi | 74.91 |
```
</EXTRACTED_INFO>
<THINK>
The map shows the life expectancy for each state. The only state with a value below 75 is Mississippi, with a life expectancy of 74.91.
</THINK>
<PLAN_ANS> Mississippi has a life expectancy average lower than 75. **</PLAN_ANS>**
</EXEC_PLAN>

<EXEC_PLAN> ... </EXEC_PLAN>

<EXEC_PLAN>
<SUB_PLAN>List states with values below 75**</SUB_PLAN>**
<EXTRACTED_INFO>
```markdown
| State | Life Expectancy |
|---|---|
| Mississippi | 74.91 |
```
</EXTRACTED_INFO>
<THINK>
Based on the comparison, Mississippi is the only state with a life expectancy value below 75.
</THINK>
<PLAN_ANS> The state with a life expectancy average lower than 75 is Mississippi. **</PLAN_ANS>**
</EXEC_PLAN>

<FINAL_ANSWER>
Mississippi
</FINAL_ANSWER>

Label : Missipi

Figure 21: An example of an Others (Label Error) case, where the error does not fall into standard categories and is caused by issues such as incorrect ground-truth labels or problematic questions. In this example, the label contains a typo ("Missipi" instead of "Mississippi"), even though the model's reasoning and answer are correct.

C Training Details and Hyperparameters

C.1 Training Details

The Vision-Language Models (VLMs) used in this study were trained on the DocPlan dataset using the Visual Instruction Tuning (VIT) approach. The VIT, proposed by Liu et al., efficiently trains VLMs composed of a visual encoder, a projection layer, and a large language model (LLM), integrating visual and linguistic information to generate high-quality multimodal responses. Although the SmolVLM2-2.2B, Qwen2-VL-7B, paligemma2-10B, and Llama3.2-11B-Vision models adopted in this research differ in detailed structures, they share a common core architecture and were trained following the same VIT-based protocol. The training procedure for VIT can be summarized into three steps: (1) Tokenization of visual information, (2) Combination of multimodal sequences, and (3) Supervised Fine-Tuning through next-token prediction. When an image and user instruction text are input, the input image v is first passed through the visual encoder $H(\cdot)$ to obtain an image representation Z_v. This representation is then projected into an embedding space understandable by the language model via the projection layer Proj$(\cdot)$, resulting in R_v.

$$H(v) = Z_v,\ Proj(Z_v) = R_v \tag{1}$$

In the case of user instruction text (q), it is embedded through the language model's embedding layer $G(\cdot)$ to produce R_q. Finally, the text embeddings R_q and image embeddings R_v are combined into a single multimodal sequence X, separated by a special image token `[IMG]`.

$$G(q) = R_q, \text{Concat}(R_q, \texttt{[IMG]}, R_v) = X \tag{2}$$

This sequence X is fed into the language model and trained toward the Supervised Fine-Tuning objective via next-token prediction. The loss function employed in this process is the Causal Language Modeling Loss, defined as follows:

$$\mathcal{L}(\theta) = -\sum_{i=1}^{T} \log P(y_i \mid \hat{y}_{<i}, X) \tag{3}$$

Recent studies have adopted methods of jointly training the projection layer, LLM, and even the visual encoder. However, this study adopted the original VIT training method to ensure experimental stability.

Parameter	Value
optimizer	AdamW (8-bit)
learning rate	5e-4
lr scheduler	cosine
lr scheduler type	cosine_with_min_lr
min lr	1e-6
epoch	3
batch Size	2
gradient accumulation	2
warmup ratio	0.01
precision	bfloat16
llm	lora
projection layer	lora
vision encoder	frozen
lora_trainable	q, k, v, o, up, down, gate, embed, lm_head

Table 14: Applied hyperparameter settings

C.2 Hyperparameter Settings

In this study, LoRA (Hu et al., 2022) was used for training the VLM on DocPlan. Detailed hyperparameter settings related to training are provided in Table 14.

C.3 Evaluation Prompt for ChartQA and ChartQAPro

In this study, we found that the commonly used evaluation metric, relaxed accuracy, adopted by existing benchmarks such as ChartQA and ChartQAPro, falls short in capturing the semantic validity of answers. Therefore, we adopted the LLM-as-judge approach for a more accurate evaluation. The prompt used for evaluation is shown in Figure 22.

D Example of DocPlan dataset

The DocPlan dataset contains a varying number of subplans depending on the complexity of the image and the query. Figures 23, 24, and 25 illustrate examples with 1, 2, and 3 subplans, respectively, demonstrating how the structure of step-by-step reasoning changes with task difficulty.

E Detailed GPT Prompts & Comparative Reasoning Examples

To evaluate whether the DocPlan dataset-trained model proposed in this study demonstrates improvements in interpretability compared to other reasoning-based VLMs, a comparative evaluation was conducted against the Llava-CoT model. The evaluation utilized an LLM-as-judge method to assess: (1) the Final Answer derived from inputs containing only questions and reasoning processes

Evaluation Prompt for ChartQA and ChartQAPro

You are given a question, a correct label (answer), and a model-generated answer. Your task is to evaluate whether the model's answer is correct.

- Treat the model answer as correct (respond with **"O"**) if **any** of the following is true:
  1. It contains exactly the correct option letter (e.g. “A”).
  2. It contains the letter plus punctuation (e.g. “A)”, “A.”).
  3. It contains the full text of the correct option (e.g. “banana”).
  4. It combines letter and text (e.g. “A) banana”, “A. banana”).
- Otherwise respond with **"X"**

Input Format:
Question: {question}
Option: {Option}
Label: {answer}
Model Answer: {prediction}

Output Format:
Result: O / X

Figure 22: Instructions for evaluating the correctness of model-generated answers in ChartQA and ChartQAPro using structured matching rules





Figure 23: An example of DocPlan data with one subplan.

without images, (2) the accuracy of the derived Final Answer, and (3) interpretability preference. The prompts used for each evaluation are shown from Figure 26 to Figure 28, and comparative examples are provided in Figure 29.

F Detailed Token Distribution Analysis

To provide a more granular understanding of the inference cost associated with DocPlan, we analyzed the average number of generated tokens per DocPlan-pipe stage across all models and benchmarks. The detailed statistics are presented in Table 15, and the key observations for each stage are

2 Sub Plans Data Example



INTERNATIONAL ACTIVITIES INDEX

For each of the 9 categories below:

a) indicate the approximate number of persons involved during the past year (July 1963 thru June 1964), and,

b) indicate whether any personnel were thus involved during the preceding 3-year period (July 1960 thru June 1963).

In calculating your figures, please exclude persons working in or coming from the following countries:

Puerto Rico — Europe (all countries)
Canada — Japan
Australia — Israel
New Zealand — Republic of South Africa

(a) Current Programs Number Involved (If none, so state)	CATEGORIES	(b) Past Programs (Circle appropriate response)
	Your Personnel Working Abroad	
None	Medical students in clerkships or research programs	(Yes) No
___	House staff members in clinical or research programs	Yes No
___	Visiting faculty at foreign medical schools	Yes No
___	Faculty members in research programs	(Yes) No
	Foreign Personnel in Your School	
___	In internship programs of affiliated hospitals	Yes No
___	In residency programs of affiliated hospitals	Yes No
___	In fellowship programs of affiliated hospitals	Yes No
___	Post-graduate fellows in the basic sciences - See attached	Yes No
___	As visiting faculty	Yes No

(c)

Does your school have any grants or contracts which provide funds for programs in international medical education? If so, please describe briefly on reverse side.

Also, please describe any activities in international medical education engaged in by your school, other than those in the above categories.

PLEASE PROVIDE ANY REPORTS, ARTICLES, OR OTHER MATERIALS, PUBLISHED OR UNPUBLISHED, WHICH DESCRIBE YOUR SCHOOL'S INTERNATIONAL ACTIVITIES.

SUBMITTED BY: _____ (Name) _____ (Title) _____ (School)

Q : How many categories are there?

<QUERY_ANALYSIS>
The user wants to find the AUTH. NO. associated with TYRONE W AUSTIN in the provided document. The preferred response format is a direct and concise answer.
</QUERY_ANALYSIS>

<DEF_PLAN>
<SUB_PLAN>Identify and list all the categories mentioned in the document.**</SUB_PLAN>**
<SUB_PLAN>Count the total number of categories identified.**</SUB_PLAN>**
</DEF_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Identify and list all the categories mentioned in the document.**</SUB_PLAN>**
<EXTRACTED_INFO>
```markdown
CATEGORIES

Your Personnel Working Abroad
- Medical students in clerkships or research programs
- House staff members in clinical or research programs
- Visiting faculty at foreign medical schools
- Faculty members in research programs

Foreign Personnel in Your School
- In internship programs of affiliated hospitals
- In residency programs of affiliated hospitals
- In fellowship programs of affiliated hospitals
- Post-graduate fellows in the basic sciences
- As visiting faculty
```
</EXTRACTED_INFO>
<THINK>
The extracted information shows two main sections: "Your Personnel Working Abroad" and "Foreign Personnel in Your School." Each section lists specific categories under it. By counting these, we can determine the total number of categories.
</THINK>
<PLAN_ANS> There are 9 categories listed in the document. **</PLAN_ANS>**
</EXEC_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Count the total number of categories identified.**</SUB_PLAN>**
<THINK>
From the previous step, we have identified 9 distinct categories under the two main sections. Counting these confirms the total number.
</THINK>
<PLAN_ANS> The total number of categories is 9. **</PLAN_ANS>**
</EXEC_PLAN>

<FINAL_ANSWER>
The document contains a total of 9 categories.
</FINAL_ANSWER>

Figure 24: An example of DocPlan data with two subplan.

summarized as follows.


Query Analysis. This stage consumes the fewest tokens across all configurations but serves as a critical prerequisite that determines the direction of subsequent reasoning. Notably, Gemma3, which allocated a relatively higher number of tokens to this stage, recorded the highest average performance improvement (18.1%p) under the `+DocPlan` configuration.

Definition of Plan. In most models, `+DocPlan` recorded higher performance compared to `+DocPlan(origin)`, supporting the premise that DocPlan's structured planning, rather than simple data augmentation, substantially contributes to reasoning quality.

Execution of Plan. As the stage accounting for the majority of total inference cost, significant performance improvements were observed in ChartQA for models such as Llama-Vision (74.2 $\rightarrow$ 86.6) and Gemma3 (57.4 $\rightarrow$ 81.3). Notably, Llama-Vision achieved top-tier performance while maintaining the lowest total token consumption (284.3 tokens), whereas paligemma2 showed relatively limited improvement despite a higher token count (629.8 tokens). This suggests that the quality of the structured execution path, rather than the absolute quantity of tokens, governs overall performance.

Final Answer. This stage consumed the fewest tokens with minimal variance across models, implying that the difference in final performance is determined by the quality of the reasoning chain established in the preceding stages rather than the answer generation itself. These findings reaffirm that DocPlan's stepwise reasoning design achieves both token efficiency and performance enhancement.

3 Sub Plans Data Example



Q: `Compare the share of businesses with 50-249 employees between 2013 and 2016.`

<QUERY_ANALYSIS>
The user's query is asking to compare the share of businesses with 50-249 employees between the years 2013 and 2016. The intent (INTENT) is to analyze the data for the specified employment size range and determine if there was an increase, decrease, or no change in the share of businesses over the given time period. There is no specified preferred response format, so a clear comparison will suffice.
</QUERY_ANALYSIS>

<DEF_PLAN>
<SUB_PLAN>Extract the share of businesses with 50-249 employees for the year 2013.</SUB_PLAN>
<SUB_PLAN>Extract the share of businesses with 50-249 employees for the year 2016.</SUB_PLAN>
<SUB_PLAN>Compare the shares from 2013 and 2016 to determine any changes.</SUB_PLAN>
</DEF_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Extract the share of businesses with 50-249 employees for the year 2013.</SUB_PLAN>
<EXTRACTED_INFO>
```markdown
| Employment size | Share of businesses |
|-----------------|---------------------|
| 50-249          | 59.2%               |
```
</EXTRACTED_INFO>
<THINK>
The share of businesses with 50-249 employees in 2013 is 59.2%.
</THINK>
<PLAN_ANS> The share of businesses with 50-249 employees in 2013 is 59.2%. </PLAN_ANS>
</EXEC_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Extract the share of businesses with 50-249 employees for the year 2016.</SUB_PLAN>
<EXTRACTED_INFO>
```markdown
| Employment size | Share of businesses |
|-----------------|---------------------|
| 50-249          | 73.1%               |
```
</EXTRACTED_INFO>
<THINK>
The share of businesses with 50-249 employees in 2016 is 73.1%.
</THINK>
<PLAN_ANS> The share of businesses with 50-249 employees in 2016 is 73.1%. </PLAN_ANS>
</EXEC_PLAN>

<EXEC_PLAN>
<SUB_PLAN> Compare the shares from 2013 and 2016 to determine any changes.</SUB_PLAN>
<THINK>
Comparing the shares, we see that the share of businesses with 50-249 employees increased from 59.2% in 2013 to 73.1% in 2016. This indicates a significant rise in the share of businesses within this employment size range over the three-year period.
</THINK>
<PLAN_ANS> The share of businesses with 50-249 employees increased from 59.2% in 2013 to 73.1% in 2016, indicating a significant rise.
</PLAN_ANS>
</EXEC_PLAN>

<FINAL_ANSWER>
The share of businesses with 50-249 employees increased from 59.2% in 2013 to 73.1% in 2016, indicating a significant rise over the three-year period.
</FINAL_ANSWER>

Figure 25: An example of DocPlan data with three subplan.

Model	Query Analysis	Definition of Plan	Execution of Plan	Final Answer
DocVQA				
SmolVLM2	27.7 / 5.9	61.1 / 25.5	352.6 / 226.2	4.9 / 3.8
Gemma3	28.7 / 6.4	49.7 / 20.7	323.6 / 282.2	3.9 / 3.5
Qwen2-VL	27.7 / 7.0	46.4 / 18.4	343.8 / 222.2	5.0 / 3.4
paligemma2	22.6 / 6.0	37.0 / 20.1	248.6 / 260.5	4.6 / 3.2
Llama-Vision	22.8 / 5.1	38.8 / 17.4	267.2 / 184.2	4.1 / 3.2
InfoVQA				
SmolVLM2	33.4 / 6.2	75.3 / 18.2	455.2 / 265.5	3.3 / 3.2
Gemma3	35.0 / 7.2	59.7 / 16.2	446.7 / 232.4	3.0 / 2.9
Qwen2-VL	31.6 / 7.2	55.7 / 14.5	432.1 / 202.3	3.3 / 2.6
paligemma2	29.8 / 7.3	60.5 / 16.3	419.0 / 171.7	3.4 / 3.5
Llama-Vision	27.6 / 6.5	52.6 / 15.5	368.1 / 153.5	2.9 / 3.2
ChartQA				
SmolVLM2	33.8 / 6.6	73.9 / 21.9	514.1 / 264.9	3.6 / 2.0
Gemma3	36.2 / 7.2	61.3 / 17.8	519.2 / 277.9	3.3 / 1.7
Qwen2-VL	31.6 / 6.3	55.2 / 15.6	437.4 / 213.0	3.6 / 2.2
paligemma2	29.7 / 6.1	59.2 / 18.9	436.6 / 206.7	3.4 / 1.7
Llama-Vision	27.6 / 5.1	51.0 / 15.2	357.2 / 162.3	2.2 / 1.3

Table 15: Average number of generated tokens per DocPlan-pipe stage (mean/std). Each value represents the token count for the corresponding stage across different benchmarks.

Test Prompt for Simulatability

You are given a question and a structured reasoning trace that includes analysis, step-by-step planning, and conclusions.

Your task:
- Carefully read the reasoning and extract the most accurate final answer to the question.
- The answer must be short and specific (e.g., a word or phrase).
- Always output exactly one line starting with: final_answer:
- Do not leave the answer blank.
- Even if the reasoning is indirect, you must infer the best possible answer from the provided content.

Question:
{**question**}

Reasoning:
{**reasoning**}

[Output format]
final_answer:
<Your final answer here — must not be empty>

Figure 26: Instructions for identifying and outputting a concise, specific final answer based on structured reasoning in response to a question

Evaluation Prompt for Final Answer

You are given:
- A list of semantically equivalent correct answer variants.
- A model's prediction.

Your task:
- Determine whether the prediction has the same meaning as any of the correct answer variants.
- Focus only on meaning, not formatting or wording.
- If the prediction matches any of the variants in meaning, output: Correct
- Otherwise, output: Incorrect
- Output exactly one word: Correct or Incorrect
- Do not include any explanation or additional text.

Correct Answer Variants:
{**Label**}

Model Prediction:
{**Model prediction**}

[Output format]
Correct
or
Incorrect

Figure 27: Instructions for determining whether a model's answer is semantically equivalent to a list of correct answer variants, with strict output rules

Evaluation Prompt for Preference

You are a human evaluator comparing the interpretability of reasoning between two AI models.

You are provided with:
- An image (assume it is visible to you)
- A question about the image
- Two model responses that include reasoning and a final answer

Task:
Evaluate which model demonstrates more interpretable reasoning based on both the image and the text. By "interpretable", we mean:
- Is the reasoning logically consistent and easy to follow?
- Does it clearly connect visual evidence from the image to the answer?
- Are intermediate steps transparent and well-explained?

If one model is clearly more interpretable, choose that model.
If both models are similarly interpretable, select "**tie**".

Inputs:
Question: {**question**}

Model A Answer:
{**model_a_answer**}

Model B Answer:
{**model_b_answer**}

Respond with only one of the following exact outputs:
- **A model is better**
- **B model is better**
- **tie**


Do not provide any explanation or additional text.

Figure 28: Instructions for evaluating and selecting the more interpretable reasoning between two AI model responses based on image-grounded questions

Example of comparison between Llava CoT and DocPlan

Question:
How many merchant wholesalers were there in Ontario as of December 2020?

Answer:
399



Answer from Llava CoT

<SUMMARY> To solve the problem, I will identify the number of merchant wholesalers in Ontario from the bar graph in the image. I will look specifically at the bar labeled "Ontario" and note the number associated with it. </SUMMARY>

<CAPTION> The image is a bar graph showing the number of merchant wholesalers across various provinces and territories in Canada as of December 2020. Each bar represents a different location, with numbers on the x-axis representing the count of establishments. Ontario is the first bar and has the highest value in the graph. </CAPTION>

<REASONING> To determine the number of merchant wholesalers in Ontario, I will locate the bar labeled "Ontario" on the graph. The length of the bar and the number next to it indicate the total count of wholesalers. According to the graph, Ontario has a bar that extends to the value 399 on the x-axis. This signifies there are 399 merchant wholesalers in Ontario. </REASONING>

<CONCLUSION> 399 </CONCLUSION>

Answer from Self-Planning DocPlan-pipe

<QUERY_ANALYSIS>
The core intent of the query is to find out the specific number of merchant wholesalers in Ontario as of December 2020. The user has not specified a preferred response format.
</QUERY_ANALYSIS>

<DEF_PLAN>
<SUB_PLAN>Identify the bar corresponding to Ontario in the chart.</SUB_PLAN>
<SUB_PLAN>Read the number of establishments indicated for Ontario.</SUB_PLAN>
</DEF_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Identify the bar corresponding to Ontario in the chart.</SUB_PLAN>
<EXTRACTED_INFO>
```markdown
| Province | Number of establishments |
|----------|--------------------------|
| Ontario | 399 |
```
</EXTRACTED_INFO>
<THINK> The bar corresponding to Ontario is clearly identified and shows a value of 399. </THINK>
<PLAN_ANS> The number of merchant wholesalers in Ontario as of December 2020 was 399. </PLAN_ANS>
</EXEC_PLAN>

<EXEC_PLAN>
<SUB_PLAN>Read the number of establishments indicated for Ontario.</SUB_PLAN>
<EXTRACTED_INFO>
```markdown
| Province | Number of establishments |
|----------|--------------------------|
| Ontario | 399 |
```
</EXTRACTED_INFO>
<THINK> The number of establishments indicated for Ontario is 399, which directly answers the user's query.</THINK>
<PLAN_ANS> There were 399 merchant wholesalers in Ontario as of December 2020. </PLAN_ANS>
</EXEC_PLAN>

<FINAL_ANSWER>
There were 399 merchant wholesalers in Ontario as of December 2020.
</FINAL_ANSWER>

Figure 29: Example of comparison between Llava CoT and DocPlan

G Statistical Analysis of DocPlan Dataset




Figure 30: Across all three difficulties, questions categorized as LR tend to have longer token lengths. In most query types, token lengths decrease from 'Advanced' to 'Intermediate' to 'Basic', indicating that lower difficulties are generally associated with shorter token lengths.




Figure 31: **Sub-Plan distribution by image type.** The number of Sub-Plans tends to be clustered clustered around 2 and 3. InfoVQA has the largest proportion at 3 Sub-Plans. DocVQA and ChartQA are spread relatively evenly from 1 to 4, while Generation shows a more balanced distribution across all values from 1 to 6, suggesting a wider variety of Sub-Plan counts.




Figure 32: **Question distribution of DocVQA.** Most questions start with *what*, followed by *who*, *which*, and *how*. *What* questions are dominant and show diverse structures.




Figure 33: **Question distribution of ChartQA.** The majority of questions begin with *what* or *how*, with *what* focusing on factual or numerical values, and *how* often paired with *many* or *much* to indicate quantitative reasoning. This suggests a high proportion of questions requiring numerical inference.




Figure 34: **Question distribution of InfoVQA.** *What* questions dominate, often paired with terms like *percentage*, *number*, and *difference*, indicating a focus on statistical or comparative reasoning. *How many* and *which* questions are also frequent, highlighting the dataset's emphasis on data interpretation and entity selection.




Figure 35: **Question distribution of Generation.** Question prefixes such as *what*, *how*, *explain* and *identify* indicate a strong focus on higher-order reasoning tasks. Terms like *implicit*, *explicit*, *compare*, and *relationship* suggest that many questions require interpretation, abstraction, and explanation beyond surface-level information.




Figure 36: **Heatmap of query type and query difficulty.** The number of generated Sub-Plans ranges from 0 to 11, with the average clustered around 3 to 4. This reflects a strong bias toward FP_A type questions. For questions with more than 6 Sub-Plans, the dominant types are IR and LR, and the majority of these questions are labeled as difficulty level C. This suggests that as questions require more reasoning or have higher difficulty, they tend to generate more Sub-Plans.




Figure 37: **Detailed distribution of Sub-Plan counts across four image types:** InfoVQA, DocVQA, ChartQA, and Generation. It can be observed that both the questions with no Sub-Plans(0) and those with more than 6 Sub-Plans are primarily from the Generation image type.




Figure 38: DocPlan includes not only simple lookup questions but also a substantial number of high-level reasoning types such as how and command. While why-type questions are rare due to the lack of explicit reasoning in documents, implicit reasoning is effectively covered through how and command types, enhancing the dataset's reasoning depth.




Figure 39: Each query type exhibits a distinct token length distribution, indicating varying levels of reasoning complexity depending on the type.




Figure 40: As query difficulty increases, the lengths of questions, answers, and contexts grow accordingly. This trend highlights the clear separation of difficulty levels in the DocPlan dataset.




Figure 41: Each stage—DEF PLAN, EXEC PLAN, THINK, FINAL ANSWER—exhibits distinct lexical patterns aligned with its functional role: problem setup, information retrieval, reasoning, and summarization. This reflects a clear division of reasoning steps through language use.




Figure 42: User questions often include terms like answer, please, response, indicating the expected answer format. In contrast, the full context contains directive words such as identify, section, value, document, guiding the model on where and how to locate relevant information within the document.




Figure 43: User interface employed for the human filtering process