

- Voters for Tweet Polarity Classification,” arXiv preprint arXiv:1705.02023, 2017.
- [5] C. Baziotis, N. Pelekis, and C. Doulkeridis. “Datastories at semeval-2017 task 4: Deep lstm with attention for message-level and topic-based sentiment analysis,” In: Proceedings of the 11th International Workshop on Semantic Evaluation (SemEval-2017), pp. 747-754, 2017.
- [6] F.A. Gers, J. Schmidhuber, and F. Cummins,” Learning to forget: Continual prediction with LSTM”, 1999.
- [7] M. Cliché, “BB_twtr at SemEval-2017 Task 4: Twitter Sentiment Analysis with CNNs and LSTMs,” arXiv preprint arXiv:1704.06125, 2017.
- [8] S. Mohammad, F. Bravo-Marquez, and M. Salameh, “Semeval-2018 task 1: Affect in tweets,” In: Proceedings of The 12th International Workshop on Semantic Evaluation, pp. 1-17, 2018.
- [9] S. Rosenthal, N. Farra, and P. Nakov. ”SemEval-2017 task 4: Sentiment analysis in Twitter,” In: Proceedings of the 11th International Workshop on Semantic Evaluation (SemEval-2017), pp. 502-518, 2017.
- [10] Z.Y. Gao, and C.P. Chen, “deepSA2018 at SemEval-2018 Task 1: Multi-task Learning of Different Label for Affect in Tweets,” In: Proceedings of The 12th International Workshop on Semantic Evaluation, pp. 226-230, 2018.
- [11] T. Mikolov, I. Sutskever, K. Chen, and G.S. Corrado, “Distributed representations of words and phrases and their compositionality,” In: Advances in neural information processing systems, pp. 3111-3119, 2013.
- [12] Y. Wang, M. Huang, and L. Zhao,” Attention-based lstm for aspect-level sentiment classification,” In: Proceedings of the 2016 conference on empirical methods in natural language processing, pp. 606-615, 2016.